OMB Control Number: 2040-XXXX Approval Expires: 05/dd/2013 Plant ID: Insert Plant ID
Plant Name: Insert Plant Name



Steam Electric Questionnaire

PART C - ASH HANDLING

Table of Contents

Section Title	Tab Name
Part C Instructions	Part C Instructions
Ash Generation	Part C Section 1
Fly Ash Handling - Generating Unit Level Information	Part C Section 2.1
Fly Ash Handling - Storage and Use Data	Part C Section 2.2
Fly Ash Cost Information - Conveyance	Part C Section 2.3
Fly Ash Cost Information - Intermediate Storage	Part C Section 2.4
Fly Ash Cost Information - Transport/Disposal	Part C Section 2.5
Bottom Ash Handling - Generating Unit Level Information	Part C Section 3.1
Bottom Ash Handling - Storage and Use Data	Part C Section 3.2
Bottom Ash Cost Information - Conveyance	Part C Section 3.3
Bottom Ash Cost Information - Intermediate Storage	Part C Section 3.4
Bottom Ash Cost Information - Transport/Disposal	Part C Section 3.5
Economizer Ash Handling Information	Part C Section 4
Air Heater Ash Handling Information	Part C Section 5
Part C Comments	Part C Comments
Steam Electric Questionnaire Code Tables	Code Tables

Plant ID: <u>Insert Plant ID</u> Plant Name: <u>Insert Plant Name</u>

PART C. ASH HANDLING

INSTRUCTIONS

Part C requests information about ash handling operations at your plant. Complete Part C if ash is generated in any fossil-fueled steam electric generating units at your plant. See Part A Section 8 for steam electric generating unit fuel classifications.

As you are completing the electronic form, note the following: When you enter your plant name and plant ID on the Part C TOC tab, all name and ID fields throughout Part C will automatically populate. Refer to the overall questionnaire instructions, the glossary, and the acronym list for assistance with completing Part C.

Please provide all free response answers in the highlighted yellow areas. Throughout Part C, you may need to make copies of certain sections/questions. Instructions are provided throughout Part C regarding making copies. Note that Steam Electric Unit IDs or Storage IDs must be populated on the copied tab or section, located in the upper right corner under "Plant ID" and "Plant Name", in order to correlate the requested information with the steam electric unit or ash handling system.

Where the questionnaire indicates to provide an attachment, an electronic format (e.g., PDF) is preferred; however, hardcopies are also acceptable.

Use the Part C Comments tab to do the following: provide additional information as requested in certain questions within Part C; indicate atypical data (e.g., if 2009 information is not representative of normal operations); and note methods used to make best engineering estimates in the event that exact data are not available.

Refer to the following definitions throughout Part C:

"Fly ash collection" is the separation of fly ash from the flue gas. Examples of fly ash collection equipment include ESPs and baghouses. Fly ash may also be collected by wet scrubbers.

"Fly ash conveyance" is the conveyance of fly ash from the fly ash collection equipment (ESP or baghouse) of one or more generating units to intermediate or final storage (e.g., storage silos or ponds/impoundments). Common dry fly ash conveyance components include filter/separators, vacuum/pressure transfer stations, high pressure blowers, and associated high pressure piping (note that conveyance does NOT include the storage/loading silos). Wet fly ash conveyance equipment is used to sluice fly ash and pump it to wet ash storage (e.g., ash ponds/impoundments).

"Bottom ash conveyance" is the conveyance of bottom ash from the boiler(s) of one or more generating units to the intermediate or final storage of the bottom ash. Dry bottom ash conveyance does not use water to convey bottom ash to intermediate/final storage. Dry bottom ash conveyance includes systems that collect and convey the bottom ash without any use of water, as well as systems in which bottom ash is conveyed mechanically or pneumatically away from a quench water bath (e.g., submerged chain conveyor systems). Wet bottom ash conveyance uses water (i.e., a sluice) to convey bottom ash away from the boiler to intermediate/final storage (e.g., ponds/impoundments). Note that dewatering bins are considered part of bottom ash conveyance.

"Intermediate storage" refers to a facility or site where collected fly ash or bottom ash is stored after conveyance and prior to being transported to final disposal. Dry fly ash intermediate storage typically consists of storage silos. Dry bottom ash intermediate storage typically consists of stackout piles for the bottom ash collected from mechanical drag systems. Wet fly ash or bottom ash intermediate storage typically consists of ponds/impoundments.

"Ash transport/disposal" refers to the transportation of ash from intermediate storage to final disposal. Examples of ash transport/disposal include transportation used to haul ash off site (e.g., ash that is marketed and shipped off site to a reuse application). Ash transport typically consists of roads and vehicles that are used to transport the ash.

Plant ID: Insert Plant ID
Plant Name: Insert Plant Name

	Part: C Section Title: 1. Ash	Generation			
CBI? □ Yes		generated in any foss ating unit fuel classific		ng units at the plant? See Pa	art A Section 8 for steam electric
	○ Yes		(Continue)		
	○ No		(Skip to next Questionnaire Par	t)	
CBI? □ Yes	proper				including all contiguous and non-adjoining ne ultimate parent, and receiving the
			Table C-1. Plant Acreage Brea		
		Total Plant Area	Category	Acreage	
		Parking lots			
		Buildings and Other	Developed Areas		
		Active/Inactive/Oper	ash ponds		
		Active/Inactive/Open	landfills		
		Closed ponds/impou	indments and landfills		
		Unusable land (e.g., Specify type(s):	wetlands, cooling reservoir)		
		Other:			
		Other:			
CBI? □ Yes		sh generated in any fating unit fuel classific		ating units at the plant? See	Part A Section 8 for steam electric
	○ Yes	(Continue)			
	○ No	(Skip to Section 3.1)			

Plant ID: Insert Plant ID
Plant Name: Insert Plant ID
SE Unit ID: Insert Unit ID

Part: C

Section Title: 2.1. Fly Ash Handling - Generating Unit Level Information

Instructions: Throughout Section 2.1 (Questions C2-1 through C2-24), provide ash handling information for each steam electric generating unit operated at any time in 2009, including units that may have been idle for an extended period of time. Make copies of Section 2.1 for each steam electric generating unit using the "Copy Section 2.1" button below. Enter the steam electric generating Unit ID (use Unit IDs assigned in Table A-8) in the space above titled "SE Unit ID".

Copy Section 2.1

CBI? ☐ Yes C2-1. Provide fly ash handling information in Table C-2, for each steam electric generating unit reported in Table A-8, following these instructions:

- Provide fly ash handling information at the steam electric generating unit level. For the purpose of this questionnaire, more than one type of fly ash handling (e.g., wet sluicing, mechanical system) may be selected for one generating unit. Check all types of fly ash handling that apply to this steam electric generating unit.
- For the "Type of Fly Ash Collection", only mark "Wet scrubber" if it is the ONLY means of collection. Note: For any fly ash handling systems marked as "Wet scrubber", do NOT complete the remainder of Part C, Section 2 AND proceed to Part C, Section 3.1.
- Provide the wet conveyed "Typical Amount of Fly Ash Produced in 2009 (Dry weight basis)" as tons of ash produced per day prior to sluicing from this steam electric generating unit.

Table C-2. Fly Ash Handling Systems Operated in 2009 by Generating Unit

Type of Fly Ash Collection	Type of Fly Ash Handling	Typical Amount of Fly Ash Produced in 2009 (Dry weight basis)		Design Ash Handling Rate (Dry weight basis)		Number of Days Ash was Conveyed in 2009		Loss on Ignition of Fly Ash Produced (Provide typical range for 2009)		
		Wet Conveyed	Dry Conveyed	Wet Conveyed	Dry Conveyed	Wet Conveyed	Dry Conveyed	Wet Conveyed	Dry Conveyed	
O ESP(s), dry, hot side	✓ Wet sluicing (hydraulic)									
O ESP(s), dry, cold side	Wet vacuum system (pneumatic)									
ESP(s), wet Baghouse(s) (fabric filter) Wet scrubber(s) (only) Other:	☑ Dry vacuum system ☐ Pressure system ☐ Combined vacuum/pressure system ☐ Mechanical system ☐ Other:	<u>1,500</u> tpd <u>165</u> dpy	1,500 tpd 200 dpy	2,000 tpd 365 dpy	2,000 tpd 365 dpy	<u>165</u> days	<i>200</i> days	1 to <u>2</u> %	<u>1</u> to <u>2</u> %	
O ESP(s), dry, hot side	Wet sluicing (hydraulic)									
O ESP(s), dry, cold side	Wet vacuum system (pneumatic) □ Dry vacuum system									
O ESP(s), wet	Pressure system	tpd	tpd	tpd	tpd	days	days	to %	to %	
O Baghouse(s) (fabric filter)	Combined vacuum/pressure system	dny	day	day	dov		aayo			
O Wet scrubber(s) (only)	Mechanical system	dpy	dpy	dpy	dpy					
O Other:	Other:									

C-2 Approved: May XX, 2010

CBI?

☐ Yes

C2-2. Is wet sluicing a type of fly ash handling for this steam electric generating unit?

O Yes (Continue)

O_{No} (Skip to Question C2-6)

Provide information for wet fly ash handling in Table C-3. For the source of sluice water, you may enter more than one source from the following options:

- "IN" if raw intake water is used:
- "IN-Makeup" if raw intake water is only used as makeup;
- "TR" for use of intake water that has been treated on site prior to use;
- "TR-Makeup" if treated intake water is used only as makeup; and/or
- Process wastewater and/or treated wastewater described in the code tables on the "Code Tables" tab provided at the end of this workbook.

An example is provided in Table C-3 for a plant that uses the effluent from its ash pond (WWT-1, as would be defined in Part A) for fly ash sluicing and also makes up for losses with untreated river water (which is code IN-Makeup as shown above).

Table C-3. Process Wastewater Generated from Wet Fly Ash Handling in 2009 Average Sluice Water Flow Rate (gpd) Typical Duration AND Source(s) of Sluice Water **Percent Contribution** Frequency of Sluicing (hpd of Source to Sluice AND dpy) **Water Flow** EXAMPLE: • WWT-1 Effluent • IN-Makeup 14,400,000 24 10 _gpd hpd ▼ Sluice Water Source 365 dpy Other: -Sluice Water Source -Sluice Water Source gpd hpd Sluice Water Source Other:

CBI? □Yes		or water sources that may be used as a source of fly ash sluice water (e.g., fresh intake, recycled process water), indicate the maximum chlorides concentration and the naximum solids percentage that is acceptable for the water to be used for those purposes. [Check all boxes that apply.]						
		Chlorides concentration, less than: ppm						
		Solids percentage, less than: %						
		Other:ppm						
CBI?	C2-4. Is any of the wet fly ash sluice water immediately recycled (e.g., without treatment such as a pond) back to the plant process?							
Yes	○ Yes	(Continue)						
	○ No	(Skip to Question C2-5)						
	Describe ho	w the wet fly ash sluice is reused:						

C-3 Approved: May XX, 2010

CBI? ☐ Yes	C2-5	. Is any of the we	et fly ash sluice indirec	tly discharged to a publicly or p	orivately owned treatment wo	rks, either with or witho	out pretreatment?		
		○ No							
CBI?	C2-6	. Is a wet vacuur	m system (pneumatic) a	a type of fly ash handling for th	is steam electric generating	unit?			
Yes		O Yes	(Continue)						
		○ No	(Skip to Question Ca	2-9)					
CBI? □Yes	C2-7	. Provide the typ	ical volume of the vacu	um water of the wet vacuum s	system generated annually (g	py) and the number o	of days during which this proces	s wastewater is generated	i.
			gpy	dpy					
CBI? ☐ Yes	C2-8. What is the destination(s) of the vacuum water for the dry fly ash handling system? If the plant recycles the process wastewater, indicate the plant process to which this process wastewater is recycled. [Check all boxes that apply.]								\$
		☐ Immediately recyc	ed back to plant process. Please of	lescribe how the process wastewater is reuse	t:				
		Transferred to on-	site treatment system. Identify the	type of treatment system below. [Check all b	oxes that apply.				
			Settling pond	Constructed wetlands					
			pH adjustment	Other, specify:					
			Chemical precipitation						
				d outfall number (from Part A Section 2.2):					
			to a publicly or privately owned tre	atment works					
		Other, explain:							
CBI? □Yes	C2-9	In Table C-4, id destination.	dentify the destination(s	s) for fly ash from this steam el	ectric generating unit. Provid	e the distribution of the	e wet and dry fly ash by destina	tion and whether the stora	age identified is an intermediate or final

Note: The sum of the percentage of ash distribution should equal 100% for the dry and wet fly ash, separately.

Table C-4. Storage Destinations that Receive Fly Ash Dry Conveyed Fly Ash Wet Conveyed Fly Ash Percent of Wet Conveyed Storage Destination(s) Percent of Dry Conveyed Fly | Destination Type Storage Destination(s) **Destination Type** Ash to this Destination Fly Ash to this Destination • • O Intermediate Storage Destination Table O Intermediate Storage Destination Table O Final O Final If other, explain: If other, explain: Storage Destination Table • O Intermediate • O Intermediate Storage Destination Table O Final O Final If other, explain: If other, explain: Storage Destination Table • O Intermediate • O Intermediate Storage Destination Table O Final O Final If other, explain: If other, explain: Storage Destination Table O Intermediate \blacksquare O Intermediate Storage Destination Table O Final O Final If other, explain: If other, explain: Storage Destination Table • $\begin{center} O & Intermediate \end{center}$ • O Intermediate Storage Destination Table O Final O Final If other, explain: If other, explain: Total Dry 100 % **Total Wet** 100 %

CBI? □Yes	C2-10. Was the fly ash from this steam electric generating unit conveyed both wet and dry in 2009?
	O Yes (Continue)
	○ No (Skip to Question C2-13)
CBI? □Yes	C2-11. Indicate why fly ash from the steam electric generating unit was conveyed both wet and dry in 2009. [Check all boxes that apply.] For each selection, identify the number of days in 2009 the wet system was operated for this reason.
	Wet fly ash handling system operated during times in which the dry fly ash was not marketable.
	Wet fly ash handling system operated when the dry fly ash collection system was not operational due to maintenance issues.
	Wet fly ash handling system operated in order to maintain its function as a backup to the dry system (i.e., wet system operated to ensure that it is still functional.)
	Wet fly ash handling system operated because the dry fly ash handling system does not have the capacity to handle all of the fly ash.
	Other, explain:
CBI? □Yes	C2-12. What modifications would be required to handle all the fly ash with the dry fly ash handling system? [Check all boxes that apply.]
	No system modifications necessary. Procedural changes would be sufficient.
	☐ Increase the capacity of the silo(s).
	☐ Increase the number of silos.
	Modify the loading silos to have the ability to moisture condition the ash.
	☐ Install/increase the capacity of landfills.
	☐ Increase the capacity of the dry fly ash conveying equipment.
	Design/develop new infrastructure to dispose of dry ash. Specify new infrastructure needed:
	Other, explain:
CBI? ☐ Yes	C2-13. If the current fly ash handling operations for the steam electric generating unit are expected to significantly change by December 31, 2020, indicate how (i.e., convert to or add dry handling capability). [Check all boxes that apply.]
	Expand capacity (handling and/or storage).
	Decreased use of wet fly ash handling system. (expected operating days per year for wet system)
	End use of wet fly ash handling system. (expected end date)
	□ No change expected in fly ash handling operations.
	Other, explain:
CBI? ☐ Yes	C2-14. Was dry fly ash handling installed as a retrofit to the steam electric generating unit?
	O NA, this unit does not use dry fly ash handling (Skip to Question C2-17)
	O No (Skip to Question C2-17)
	O Yes (Continue)
	Year Built:
	Shutdown time (days) required to bring dry fly ash handling system on line:
	Was a generating unit outage(s), outside of regularly scheduled outages, required to bring the dry fly ash handling system on line?
	○ Yes
	O No.

C-5 Approved: May XX, 2010

CBI? □Yes	C2-15. What type of retrofit was the dry fly ash handling system?							
∐ Yes	O The retro	fit was made to an existing dry s	system.	(Skip to Question C2-23)				
	O A dry fly	ash handling system was installe	d (for operation in addition to the wet fly ash handling system).	(Continue)				
	O The retro	fit was a complete conversion fr	om a wet to dry fly ash handling system.	(Continue)				
CBI? ☐ Yes	C2-16. Describe the		required to retrofit (for a retrofit to an existing dr	y system, an installation of a dry system, or a complete conversion from wet to dry). [Check all				
		Physical changes	Installation of pressure/vacuum system and pi Expansion of pressure/vacuum system and pi Installation of storage silos Modification of the silos to moisture-condition Modification of the silos for ash transfer to rail Modification of the silos for marketable ash Construction of haul roads Construction of rail track Construction of landfill. Provide the landfill ID(Increasing landfill capacity. Provide the landfill Changes to air permit Other, explain:	the ash cars s) from Table A-6:				
CBI?	C2-17. Is the plant	in the process of insta	alling a dry fly ash handling system to handle so	me or all of the ash currently handled by the wet fly ash handling system?				
Yes	O Yes	Estimated shutdown	time (days) required to bring dry fly ash handling sys	tem online: (Skip to Question C2-19)				
	○ No	(Continue to Question	on C2-18)					
CBI? □ Yes	C2-18. Is the plant	planning to install a d	ry fly ash handling system by December 31, 202	0 to handle some or all of the ash currently handled by the wet fly ash handling system?				
	○ Yes	Estimated shutdown	time (days) required to bring dry fly ash handling sys	tem online: (Continue to Question C2-19)				
	○ No	(Skip to Question Ca	2-22)					

C-6 Approved: May XX, 2010

?		is in the process oversion/installation	of installing, or planning to install, a dry fly ash handing system by December 31, 2020, provide the cost estimates that have been developed for 1.
	O Yes	(Provide docum	entation/costs, for example, bid proposals or internal plant engineering estimates.)
	O No	(Skip to Questio	on C2-22)
	Note: All b	id proposals and	l/or other documentation/costs originally submitted to the plant as CBI, should be marked CBI for the purpose of this collection request
		O I have attached doo	cumentation/costs.
		O I did not attach doc	cumentation/costs. Below, explain why:
?	C2-20. Describe th	ne modifications th	nat will be required to install the dry fly ash handling system. [Check all boxes that apply.]
		Physical chang	ges to facility
			Installation of pressure/vacuum system and piping
			Expansion of pressure/vacuum system and piping
			Installation of storage silos
			Modification of the silos to moisture-condition the ash
			Modification of the silos for ash transfer to railcars
			Modification of the silos for marketable ash
			Construction of haul roads
			Construction of rail track
			Construction of landfill. Provide the landfill ID(s) from Table A-6:
			Increasing landfill capacity. Provide the landfill ID(s) from Table A-6:
			Changes to air permit
			Other, explain:
		Changes in pe	ersonnel/training, explain:
		• .	th disposal practices
	_		Storage of ash in landfills. Provide the landfill ID(s) from Table A-6:
			Marketing of ash
			Hauling ash to off-site storage
			Dust suppression activities
		П	Other, explain:

C-7 Approved: May XX, 2010

CBI? ☐ Yes	C2-21.		e the types of destinations expected for the dry fly ash from the planned system and the percentage of the dry fly ash that is expected to go to each destination. [Check all hat apply.]				
			Marketed, sold, and/or given av	vay			
			Market Destinations	▼	% of the dry fly ash		
			If other, specify:				
			Market Destinations	▼	% of the dry fly ash		
			If other, specify:				
			Market Destinations	▼	% of the dry fly ash		
			If other, specify:				
			Stored in landfills reported in Ta	able A-6	% of the dry fly ash		
			Stored in landfills NOT reported	I in Table A-6	% of the dry fly ash		
			Other, specify:		% of the dry fly ash		
CBI?	C2-22.		t is not in the process of installing or	planning to install a	dry fly ash handling system, have cost estimates been obtained/developed since January 1, 1995, for such a		
			O Yes	(Dues side de es une ent	tation/costs, for example, bid proposals or internal plant engineering estimates.)		
				•			
			O No	(Skip to Question C	S2-23)		
		Note: All	bid proposals and/or other docun	nentation/costs orig	ginally submitted to the plant as CBI, should be marked CBI for the purpose of this collection request.		
			O I have attached documentation/costs.				
			O I did not attach documentation/costs. Below,	explain why:			
CBI? □Yes	C2-23	. Has the pl	ant encountered any unscheduled o	utages on this gener	rating unit caused by the fly ash handling system in the last five years?		
□ 163		O Yes	(Continue)				
		O No	(Skip to Section 2.2)				

C-8 Approved: May XX, 2010

C-9

CBI?

☐ Yes

C2-24. In Table C-5, provide information on unscheduled generating unit outages caused by fly ash handling for each of the last five years.

Table C-5. Unscheduled Generating Unit Outages Caused by Fly Ash Handling

V	A - la I I - u all'an a		Table C-5. Unscheduled Generating Unit Outages	
Year	Ash Handling	Total Days of Outage	Reason(s) for outage(s)	Method(s) Used to Resolve Outage(s)
2005	Dry			
	Wet			
2006	Dry			
2000	Wet			
2007	Dry			
2007	Wet			
2000	Dry			
2008	Wet			
	Dry			
2009	Wet			

Approved: May XX, 2010

Plant ID: Insert Plant ID
Plant Name: Insert Plant Name

Part: C

Section Title: 2.2. Fly Ash Handling - Storage and Use Data

Instructions: Complete Section 2.2 (Questions C2-25 through C2-29). Provide information for fly ash handling and fly ash storage at the plant.

CBI?

☐ Yes

C2-25. For each storage destination reported in Table C-4, provide the distance the fly ash is transported from the generating unit to intermediate storage or from intermediate storage to the final disposal/destination, the amount of fly ash transported in 2009, and the percent moisture of the fly ash entering storage, if transported dry. Additionally, for each destination indicate how the fly ash is transported by entering one of the following options: conveyor belt, pipe, truck, barge, rail, or other (provide a description). If the fly ash is sold to more than one destination (e.g., some fly ash is sold for cement manufacturing and some is sold for structural fill) enter the average percent moisture for all fly ash sold in Table C-8 and C-9 will request information by market.

Table C-6. Fly Ash Storage Information Distance from the Generating Unit to Tons of Fly Ash How is Fly Ash Transported to Percent Moisture of the Fly Ash **Storage Destination ID** Intermediate Storage or from the Transported to Destination? **Entering Destination (if** Intermediate Storage to the Final Destination in 2009 transported dry) Disposal/Destination (dry weight basis) ▼ Storage Destination Table Storage Transport miles tons % Other: f other, explain: NA, transported wet _ % Storage Destination Table miles Storage Transport tons Other: f other, explain: NA, transported wet Storage Destination Table • miles tons Storage Transport % Other: If other, explain: ☐ NA, transported wet Storage Destination Table miles % tons Storage Transport Other: If other, explain: NA, transported wet % miles tons Storage Destination Table Storage Transport Other: If other, explain: NA, transported wet miles tons Storage Transport % Storage Destination Table Other: If other, explain: NA, transported wet Storage Destination Table miles tons Storage Transport % Other: If other, explain: NA, transported wet miles % Storage Destination Table tons Storage Transport Other: f other, explain: NA, transported wet % Storage Destination Table miles tons Storage Transport Other: If other, explain: NA, transported wet

CBI? ☐Yes C2-26. Is water used to moisten the fly ash?

○ Yes (Continue)

O_{No} (Skip to Question C2-28)

For each storage destination reported in Table C-4, provide information on water used to moisten the fly ash.

Table C-7. Water Used to Moisten the Fly Ash

01	Table C-7, water used to		M' O - I' d -	Other Order
Storage Destination ID	Source of the Water Used	Maximum Chlorides Concentration of Water Used to Moisten the Ash (ppm)	Maximum Solids Percentage of Water Used to Moisten the Ash (%)	Other Criteria
Storage Destination Table	Raw Intake Water Intake water that has been treated on site prior to use			
	☐ Process Wastewaters ▼			
Other:	Other:	ppm	%	
	□ Process Wastewaters □			
	Other:			
Storage Destination Table ▼	Raw Intake Water Intake water that has been treated on site prior to use			
	Process Wastewaters ▼			
Other:	Other:	ppm	<u> </u>	
	☐ Process Wastewaters	1		
	Other:			
Storage Destination Table ▼	Raw Intake Water Intake water that has been treated on site prior to use			
Other:	☐ Process Wastewaters ▼ Other:	222	%	
Otrier.		ppm		
	☐ Process Wastewaters ▼			
	Other:			
Storage Destination Table	Raw Intake Water Intake water that has been treated on site prior to use			
_	☐ Process Wastewaters ▼			
Other:	Other:	ppm	%	
	Process Wastewaters ▼			
	Other:			

C-11 Approved: May XX, 2010

C-12

	Raw Intake Water			
Storage Destination Table	☐ Intake water that has been treated on site prior to use ☐ Process Wastewaters ▼			
Other:	Other:	ppm	%	
outer.	□ Process Wastewaters ▼	ββιτι	78	
	Other:			
Storage Destination Table	Raw Intake Water Intake water that has been treated on site prior to use			
Storage Destination Table	☐ Process Wastewaters ▼			
Other:	Other:	ppm	%	
	Process Wastewaters			
	Other:			
	Raw Intake Water			
Storage Destination Table	☐ Intake water that has been treated on site prior to use			
	Process Wastewaters			
Other:	Other:	ppm	%	
	Process Wastewaters			
	Other:			
	Raw Intake Water			
Storage Destination Table	☐ Intake water that has been treated on site prior to use ☐ Process Wastewaters ▼			
Other:	Other:	ppm	%	
		ррпп	70	
	Other:			
	Raw Intake Water			
Storage Destination Table ▼	☐ Intake water that has been treated on site prior to use			
Storage Description Table	☐ Process Wastewaters			
Other:	Other:	ppm	%	
	☐ Process Wastewaters			
	Other:			
	I control of the cont		1	1

Approved: May XX, 2010

CI	31?	

C2-27. Indicate the criteria that the plant uses to determine if a water source is unacceptable for use (recycle/reuse) to moisten the ash. If the criteria are dictated by engineering design, provide specific elements of the design that dictate use.

CBI? ☐ Yes

Yes

C2-28. Does the plant market, sell, and/or give away fly ash from the dry ash handling system?

O Yes (Continue)

○ No (Skip to Question C2-29)

Complete Table C-8 if the plant markets, sells, and/or gives away fly ash from the dry fly ash handling system. For each destination, provide the tons of fly ash marketed, sold, and/or given away, the gross revenue generated from marketing/selling the dry fly ash for calendar years 2005, 2007, and 2009. Additionally, provide the typical percent moisture of the fly ash during calendar years 2005, 2007, and 2009. If the typical percent moisture of the fly ash was not constant during calendar years 2005, 2007, and 2009, note this information (include all typical percent moisture values for each year) in the Comments page.

Table C-8. Fly Ash from the Dry Fly Ash Handling System Marketed/Sold in Calendar Years 2005, 2007, and 2009

Destination Destination	Typical Percent Moisture of		2005		2007	20	009
	Fly Ash	Tons (dry basis)	Gross Revenue Generated \$	Tons (dry basis)	Gross Revenue Generated \$	Tons (dry basis)	Gross Revenue Generated \$
Concrete/Concrete Products/Grout	%						
Blended Cement/Raw Feed for Clinker	%						
Flowable Fill	%						
Structural Fills/Embankments	%						
Road Base/Sub-base	%						
Soil Modification/ Stabilization	%						
Mineral Filler in Asphalt	%						
Snow and Ice Control	%						
Blasting Grit/Roofing Granules	%						
Mining Applications	%						
Waste Stabilization/ Solidification	%						
Agriculture	%						
Aggregate	%						
Other:	%						
Other:	%						

CBI? ☐ Yes C2-29. Does the plant market, sell, and/or give away fly ash from the wet ash handling system?

○ Yes (Continue)

O_{No} (Skip to Section 2.3)

Complete Table C-9 if the plant currently markets, sells, and/or gives away fly ash transported by wet sluicing from the fly ash handling system. For each destination, provide the tons, on a dry basis, of fly ash transported by wet sluicing that is marketed, sold, and/or given away. Also provide the gross revenue generated from marketing/selling the fly ash transported by wet sluicing for each destination.

Table C-9. Fly Ash Transported by Wet Sluicing from the Fly Ash Handling System Marketed/Sold in Calendar Years 2005, 2007, and 2009

Destination	Typical Percent Moisture of		2005		2007		109
	Fly Ash	Tons (dry	Gross Revenue Generated	• •		Tons (dry basis)	
		basis)	\$	basis)	Generated		Generated
					\$		\$
Concrete/Concrete Products/Grout	%						
Blended Cement/Raw Feed for Clinker	%						
Flowable Fill	%						
Structural Fills/Embankments	%						
Road Base/Sub-base	%						
Soil Modification/ Stabilization	%						
Mineral Filler in Asphalt	%						
Snow and Ice Control	%						
Blasting Grit/Roofing Granules	%						
Mining Applications	%						
Waste Stabilization/ Solidification	%						
Agriculture	%						
Aggregate	%						
Other:	%						
Other:	%						

C-14

Approved: May XX, 2010

Plant ID: Insert Plant ID
Plant Name: Insert Plant Name
Unit ID: Insert Unit ID

Part: C

Section Title: 2.3. Fly Ash Cost Information - Conveyance

Instructions: Complete Section 2.3 (Questions C2-30 through C2-36) for the conveyance of fly ash (wet or dry) from each unit identified in Table A-8. Provide these data for each fly ash handling system that began operating or was converted after January 1, 2000. Enter the Unit ID (use Unit IDs assigned in Table A-8) in the space provided above.

If you indicated in Question C2-17 or C2-18 that the plant is either installing or planning to install dry fly ash handling for this unit, complete Section 2.3, and check the "Planned" checkbox below.



Make copies of Section 2.3 for each wet and dry fly ash handling system conveying ash from this unit that was operated in 2009, that began operating on or after January 1, 2000, is being installed, or planned to be installed by December 31, 2020 using the "Copy Section 2.3" button below.

The conveyance portion of the fly ash handling system refers to the part of the system that conveys fly ash from the fly ash collection equipment (ESP or baghouse) of the generating unit to intermediate or final storage (e.g., storage silos or ponds/impoundments). Common dry fly ash conveyance components include filter/separators, vacuum/pressure transfer stations, blowers, and associated high pressure piping (note that conveyance does NOT include storage or loading silos nor does it include movement between intermediate and final storage). Common wet fly ash conveyance components include sluicing equipment, associated piping, and pumps (note that conveyance does NOT include ponds/impoundments).

Note: If any components of the conveyance portion of the fly ash handling system are shared with one or more other generating units, only report those components and corresponding costs once.

Copy Section 2.3

CBI?

C2-30. Identify the major components of the conveyance portion of the fly ash handling system, in particular those components that represent a <u>significant</u> portion of the capital or O&M costs for the system. Provide the type of component and the number of each type of component in the system. Additionally, provide the total system capacity of each type of unit component (i.e., volume of clarifying tanks). Total system capacity should equal the sum of the capacity of each individual component within that type.

Table C-10. Fly Ash System Components - Conveyance

Type of Component		Number of Components in the System	Total System Capacity of Components
Fly Ash Conveyance Components	▼		Component Units ▼
Other:			If other, specify:
Fly Ash Conveyance Components	-		Component Units ▼
Other:			If other, specify:
Fly Ash Conveyance Components	▼		Component Units ▼
Other:			If other, specify:
Fly Ash Conveyance Components	-		Component Units ▼
Other:			If other, specify:
Fly Ash Conveyance Components	▼		Component Units
Other:			If other, specify:
Fly Ash Conveyance Components	-		Component Units ▼
Other:			If other, specify:
Fly Ash Conveyance Components	▼		Component Units
Other:	·		If other, specify:
Fly Ash Conveyance Components			Component Units ▼
Other:	,		If other, specify:

CBI? C2-31. Attach a block diagram that shows the entire fly ash handling system operations for this generating unit. Label the conveyance, intermediate storage (see Part C Section 2.4) and transport/disposal Yes (see Part C Section 2.5) portions of the system. The diagram should include all major components indicated in Tables C-10 and C-13, if applicable, and identify all intermediate and final ash storage destinations. Indicate the movement of ash as well as water through the system. If ash from other generating units is combined with ash from this unit, indicate where the ash is combined and the portions of the ash handling system involved. Provide as many diagrams as necessary to convey this information. Include the plant name, plant ID, and unit ID in the upper right hand corner of the diagram. Note: If the respondent indicates that the ash is transported to a pond/impoundment, in Question C2-38, the intermediate storage and disposal information will be provided in Part D. Therefore, the block diagram should only include the conveyance system(s). Diagram attached. CBI? C2-32. List all of the major components of this fly ash conveyance system that a contractor(s) constructed/installed (or will construct/install, for planned systems) at the contractor's expense (i.e., not at the Yes plant's expense). Contractor installed/will install ALL components identified in Table C-10 at the contractor's expense. CBI? C2-33. List all of the operation and maintenance activities of this fly ash conveyance system that a contractor(s) oversees (or will oversee, for planned systems) at the contractor's expense (i.e., not at the Yes plant's expense).

Contractor oversees/will oversee ALL operation and maintenance activities dealing with the conveyance portion of the fly ash handling system at the contractor's expense .

Steam Electric Questionnaire

C-16 Approved: May XX, 2010

Part C. Ash Handling

Steam Electric Questionnaire

CBI?

Yes

C2-34. In Table C-11, provide costs incurred for this fly ash conveyance system since January 1, 2000, both for the conveyance as originally installed and for any modifications to the conveyance. Include all conveyance costs including costs for components in Table C-10 as well as control systems, pads, and foundations, and all other ancillary equipment. For planned fly ash conveyance systems, provide expected costs. Provide the best engineering estimates when actual data are not readily available. For all costs, do not adjust for inflation. For example, if the plant incurred a land cost in 2002, enter the cost in the "Cost" column and enter "2002" in the "Year on which Cost is Based" column.

Note: Provide only the costs incurred by the PLANT, not the costs paid for by the contractor. For example, if an outside contractor purchased and installed all equipment for the conveyance portion of the fly ash handling system at the contractor's expense, the plant should fill out "\$ 0" for the cost of "Purchased Equipment". Any contractor costs/fees incurred by the plant should be accounted for in the "Engineering Contract Firm Costs" and "Other Contractor's Fees" categories.

Table C-11. Capital Cost for Conveyance of Fly Ash Handling

Table C-11. Cap	ital Cost for Conveyance of Fly Asi	n manuling	Voor on Which	Cost is Based
Project	Cost for System as Originally	Cost for Modifications		Modification
·	Installed	to System	Original Cost	Cost
Direct Costs				
Purchased equipment (including all equipment for the installation or the	\$	\$		
upgrade: mechanical equipment; piping; instrumentation; electrical				
equipment; spare parts; freight charges; taxes; insurance; and duties)				
Purchased equipment installation (including installation of all	\$	\$		
equipment; piping; instrumentation/calibration; electrical equipment;				
mechanical equipment; structural supports, insulation, and paint)				
Buildings (including buildings constructed to house ash handling	\$	\$		
system components, operator rooms, or other operations associated				
with the system; as well as plumbing, heating, ventilation, dust				
collection, air conditioning, lighting, telephones, intercoms, painting,				
sprinklers, fire alarms)				
Site preparation (including site clearing, all demolition, grading, roads,	\$	\$		
walking areas, fences)				
<u>Land</u> (including property costs and survey fees)	\$	\$		
Total Direct Costs	\$	\$		
Indirect Costs				
Engineering Costs (including process design and general engineering,				
cost engineering, consulting fees, supervision, inspection for each				
category below)				
a. Engineering Contract Firm Costs	\$	\$		
b. Owner's Overhead Engineering Costs	\$	\$		
b. Owner's Overhead Engineering Oosts	Ψ	Ψ		
Hired outside engineering firm to oversee design and/or installation of the system.				
Construction expenses (including temporary construction offices,	\$	\$		
roads, communications, fencing; construction tools and equipment;				
permits, taxes, insurance)				
Other Contractor's Fees	\$	\$		
Continganou actually expanded (to company to far unavadi-t-l-l-	(¢	\$		
Contingency actually expended (to compensate for unpredictable events such as storms, floods, strikes, price changes, errors in	\$	Ψ		
estimates, design changes, etc.)				
Total Indirect Costs	\$	\$		
Total Control Cont				
Total Capital Cost	\$	\$		

Steam Electric Questionnaire

CBI?	C2-35. Are all major	components of the conveyance portion of the fly ash handling system included in the capital costs reported in Table C-11?			
Yes	○ Yes	(Skip to Question C2-36)			
	O № (Continue)				
		tin what system components are included in the capital costs listed in Table C-11. Additionally, identify the key components of the conveyance portion of the fly system that are <u>not</u> included in the capital costs reported in Table C-11.			

CBI?

☐ Yes

C2-36. Provide annual (2009) O&M costs data in Table C-12 for this fly ash conveyance system, if it began operating or was converted on or after January 1, 2000. Provide best engineering estimates when actual data are not readily available. If you provide an estimate, note the methods that were used to make the estimates in the Comments page.

Note: Provide only the cost data incurred by the PLANT, not the costs paid for by the contractor. For example, if an outside contractor operates and maintains the intermediate storage portion of the fly ash handling system at the contractor's expense, the plant should fill out "\$ 0" for O&M costs. Any contractor costs/fees incurred by the plant should be accounted for in the Table C-11 "Engineering Contract Firm Costs" and "Other Contractor's Fees" categories.

Table C-12. O&M Cost for Conveyance of Fly Ash Handling for 2009

O&M Cost Category	2009 Annual Cost	2009 Rate	2009 Staffing/Consumption
Operating Labor	\$	Per hour (average rate of labor)	No. of workers hpd dpy
Maintenance Labor	\$	Per hour (average rate of labor)	
Maintenance Materials	\$		
Energy	\$	\$per kWh	kWh/hr
Other:	\$		
Other:	\$		
Total O&M Cost (2009)	\$		

Plant ID: Insert Plant ID
Plant Name: Insert Plant Name
Storage ID Insert Storage ID

Part: C

Section Title: 2.4. Fly Ash Cost Information - Intermediate Storage

Instructions: Complete Section 2.4 (Questions C2-37 through C2-44) for each intermediate storage destination identified in Table C-6 that began operating or was modified after January 1, 2000. Enter the storage ID in the space provided above (use the storage IDs assigned in Table C-6).

If you indicated in Question C2-17 or C2-18 that the plant is either installing or planning to install dry fly ash handling for this unit, complete Section 2.4, and check the "Planned" checkbox below.



Make copies of Section 2.4 for each fly ash handling system operated in 2009, that began operating on or after January 1, 2000, is being installed, or planned to be installed by December 31, 2020 using the "Copy Section 2.4" button below.

If you are instructed to skip forward to another section while completing this section for one fly ash storage destination, be sure to complete this section for all other fly ash storage destinations operated in 2009, being installed, or planned to be installed by December 31, 2020.

The intermediate storage portion of the fly ash handling system refers to the facility/site where collected fly ash is stored after conveyance, prior to the ash being transported to final disposal. Dry fly ash intermediate storage typically consists of storage silos. Wet fly ash intermediate storage typically consists of ponds/impoundments.

Note that intermediate storage includes all equipment and operations associated with loading dry or moisture-conditioned ash into trucks or rail cars for transport (but does not include the actual transport). Intermediate storage also includes all ash dust suppression activities at the plant, expect those at a pond/impoundment or landfill.

Copy Section 2.4

(Continue)

O No

CBI? C2-37. Does this storage component store both fly and bottom ash together? For example, if bottom ash and fly ash are conveyed separately but stored in a common silo, the silo is considered a shared component.

O Yes Provide unit IDs, as assigned in A-8, contributing bottom ash to this storage component.

O No

CBI? C2-38. Is this storage destination a pond/impoundment?

O Yes (Skip to Section 2.5)

C-19 Approved: May XX, 2010

С	BI?
	Yes

C2-39. Identify the major components of the intermediate storage portion of the fly ash handling system, in particular those components that represent a <u>significant</u> portion of the capital or O&M costs for the system. Provide the type of component and the number of each type of component in the system. Additionally, provide the total system capacity of each component (i.e., volume of silos). Total system capacity should equal the sum of the capacity of each individual component within that type.

Table C-13. Fly Ash Handling System Components - Intermediate Storage

Type of Component		Number of Components in the System	Total System Capacity of Components
Fly Ash Intermediate Storage Components	▼		Component Units ▼
Other:			If other, specify:
Fly Ash Intermediate Storage Components	▼		Component Units ▼
Other:			If other, specify:
Fly Ash Intermediate Storage Components	▼		Component Units ▼
Other:			If other, specify:
Fly Ash Intermediate Storage Components	▼		Component Units
Other:			If other, specify:
Fly Ash Intermediate Storage Components	▼		Component Units ▼
Other:			If other, specify:
Fly Ash Intermediate Storage Components	▼		Component Units ▼
Other:			If other, specify:
Fly Ash Intermediate Storage Components	▼		Component Units
Other:			If other, specify:
Fly Ash Intermediate Storage Components	▼		Component Units ▼
Other:			If other, specify:

CBI? □ Yes	C2-40. List all of the major components of this intermediate storage destination that a contractor(s) constructed/installed (or will construct/install, for planned systems) at the contractor's expense (i.e., not at the plant's expense).
	Contractor installed/will install ALL components identified in Table C-13 at the contractor's expense.
CBI? □Yes	C2-41. List all of the operation and maintenance activities associated with this intermediate storage destination that a contractor(s) oversees (or will oversee, for planned systems) at the contractor's expense (i.e., not at the plant's expense).

Contractor oversees/will oversee ALL operation and maintenance activities dealing with the intermediate storage portion of the fly ash handling system at the contractor's expense .

C-20 Approved: May XX, 2010

CBI? ☐ Yes C2-42. Provide cost data in Table C-14 for this intermediate storage destination, both for the storage as originally installed and for any modifications to the storage system, since January 1, 2000. Include all intermediate storage costs including costs for components in Table C-13 as well as control systems, pads and foundations, and all other ancillary equipment. For planned storage systems, provide expected costs. Provide the best engineering estimates when actual data are not readily available. For all costs, do not adjust for inflation. For example, if the plant incurred a land cost in 2002, enter the cost in the "Cost" column and enter "2002" in the "Year on which Cost is Based" column.

Note: Capital costs associated with ponds/impoundments are requested in Part D and capital costs associated with landfills/landfilling are requested in Part F. Do NOT include the costs for ponds and landfills in Table C-14.

Note: Provide only the cost data incurred by the PLANT, not the costs paid for by the contractor. For example, if an outside contractor purchased all rail cars and/or trucks for the transportation of the fly ash at the contractor's expense, the plant should fill out "\$ 0" for the cost of "Purchased Equipment". Any contractor costs/fees incurred by the plant should be accounted for in the "Engineering Contract Firm Costs" and "Other Contractor's Fees" categories.

Table C-14. Capital Cost for Intermediate Storage of Fly Ash Handling

Project		Cost for System as Originally	Cost for Modifications	Year on Which	Cost is Based
		Installed	to System	Original Cost	Modification Cost
Direct Costs					
Purchased equipment (including all equipment for the installation or	\$		\$		
the upgrade: mechanical equipment; piping; instrumentation;					
electrical equipment; spare parts; freight charges; taxes; insurance;					
and duties)					
Purchased equipment installation (including installation of all	\$		\$		
equipment; piping; instrumentation/calibration; electrical equipment;					
mechanical equipment; structural supports, insulation, and paint)					
Buildings (including buildings constructed to house ash handling	\$		\$		
system components, operator rooms, or other operations associated	-				
with the system; as well as plumbing, heating, ventilation, dust					
collection, air conditioning, lighting, telephones, intercoms, painting,					
sprinklers, fire alarms)					
Site preparation (includes site clearing, all demolition, grading, roads,	\$		\$		
walking areas, fences)					
Land (includes property costs and survey fees)	\$		\$		
Total Direct Costs	\$		\$		
Indirect Costs					
Engineering Costs (including process design and general	T				
engineering, cost engineering, consulting fees, supervision,					
inspection for each category below)					
a. Engineering Contract Firm Costs	¢.		\$		
b. Owner's Overhead Engineering Costs	\$		\$		
	Ψ		Φ		
Hired outside engineering firm to oversee design and/or installation of the system. Construction expenses (including temporary construction offices,	Φ		\$		
roads, communications, fencing; construction tools and equipment;	Ψ.		Φ		
permits, taxes, insurance)					
Other Contractor's Fees	\$		\$		
Outer Contractor's Fees	Φ		Ψ		
	Α.				
Contingency actually expended (to compensate for unpredictable	\$		\$		
events such as storms, floods, strikes, price changes, errors in estimates, design changes, etc.)					
	1				
Total Indirect Costs	\$		\$		
Total Capital Cost	\$		\$		
Total Suprial Sost	Ψ		Ψ		

C-21 Approved: May XX, 2010

CBI?	C2-43. Are all majo	or components of the intermediate storage destination included in the capital costs reported in Table C-14?
Yes	○ Yes	(Skip to Question C2-44)
	○ No	(Continue)
		lain what system components are included in the capital costs listed in Table C-14. Additionally, identify the key components intermediate storage destination that uded in the capital costs reported in Table C-14.

CBI? ☐ Yes **C2-44.** Provide annual O&M costs data in Table C-15 for this intermediate storage destination, if it began operating or was modified on or after January 1, 2000. Provide best engineering estimates when actual data are not readily available. If you provide an estimate, note the methods that were used to make the estimates in the Comments page.

Note: O&M costs associated with ponds/impoundments are requested in Part D and O&M costs associated with landfills/landfilling are requested in Part F. Do NOT include the costs for ponds and landfills costs in Table C-15.

Note: Provide only the cost data incurred by the PLANT, not the costs paid for by the contractor. For example, if an outside contractor operates and maintains the intermediate storage portion of the fly ash handling system at the contractor's expense, the plant should fill out "\$ 0" for O&M costs. Any contractor costs/fees incurred by the plant should be accounted for in the Table C-14 "Engineering Contract Firm Costs" and "Other Contractor's Fees" categories.

Table C-15. O&M Cost for Intermediate Storage of Fly Ash Handling for 2009

O&M Cost Category	2009 Annual Cost	2009 Rate	2009 Staffing/Consumption
		Per hour (average	No. of workers
Operating Labor (Water Trucks Only)	\$	\$rate of labor)	hpd
			dpy
		Per hour (average	
Operating Labor (All other operating costs)	\$	\$rate of labor)	hpd
		Day hour (overese	dpy No. of workers
Maintenance Labor	¢	Per hour (average rate of labor)	hpd
invaline labor	Ψ	Tate of labor)	dpy
			Фр
Maintenance Materials	\$		
Energy	\$	\$per kWh	kWh/hr
Oth and	0		
Other:	\$	<mark>-</mark>	
Other:	\$		
	*		
Total O&M Cost (2009)	\$		

Plant ID: Insert Plant ID
Plant Name: Insert Plant Name

Part: C

Section Title: 2.5. Fly Ash Cost Information - Transport/Disposal

Instructions: Complete Section 2.5 (Questions C2-45 through C2-52) for all transport/disposal of fly ash from fly ash handling systems that began operating or was modified after January 1, 2000, and those systems being installed, or planned to be installed by December 31, 2020.

The transport/disposal portion of the fly ash handling system refers to the transportation of fly ash from intermediate storage to final disposal.

An example of ash transport/disposal is transportation used to haul ash off site (e.g., ash that is marketed and shipped off site to a reuse application). Ash transport typically consists of roads and vehicles that are used to transport the ash. The capital and O&M costs for ash transport/disposal may include the road or rail infrastructure (roads, tracks, lights), the trucks and rail cars, the operation and maintenance costs associated with the trucks and rail cars, and ash disposal fees.

Note that capital and operation and maintenance costs associated with ponds/impoundments and landfills/landfilling are requested in Parts D and F, respectively, and they should not be provided here in Section 2.5.

CBI? □Yes	C2-45.	Does the plant use the considered a shared co	same transport and disposal equipment for both fly and bottom ash? For example, if fly ash and bottom ash are transported using the same trucks, the trucks are imponent.
		○ Yes	Provide unit IDs, as assigned in A-8, and storage IDs, provided in Table C-6, contributing bottom ash to the transport and disposal system.
		O No	(Continue)
CBI? □Yes	C2-46.	Is a pond/impoundmen	t unit or pond/impoundment system the final destination of all fly ash collected by the plant?
		○ Yes	(Skip to Section 3.1)
		○ No	(Continue)

C-23 Approved: May XX, 2010

Steam Electric Questionnaire

CBI? □Yes	C2-47.	What methods are use	d to transport the collected fly ash to the final disposal? [Check all boxes that apply.]
		Trucks	How many trucks does the plant use for the transportation and disposal of dry fly ash?
			Indicate whether the trucks were bought, leased or contracted out. Bought Leased Contracted out
		Rail cars	How many rail cars does the plant use for the transportation and disposal of dry fly ash?
			Indicate whether the rail cars were bought, leased or contracted out. Bought Leased Contracted out
		Other, specify (e.g., barge):	
CBI? □Yes		List all of the major con plant's expense).	apponents for transport/disposal of fly ash that a contractor(s) constructed/installed (or will construct/install, for planned systems) at the contractor's expense (i.e., not at the
		Contractor installed/will install	ALL ash transport/disposal equipment and/or infrastructure at the contractor's expense.
CBI? □Yes		List all of the operation plant's expense).	and maintenance activities for transport/disposal of fly ash that a contractor(s) oversees (or will oversee, for planned systems) at the contractor's expense (i.e., not at the
		Contractor oversees/will overse	e ALL transport/disposal activities at the contractor's expense.

C-24 Approved: May XX, 2010

CBI?

C2-50. Provide cost data in Table C-16 for the transport/disposal of the collected fly ash, both for the transport/disposal as originally installed and for any modifications, since January 1, 2000. For planned transport/disposal systems, provide expected costs. Provide the best engineering estimates when actual data are not readily available. For all costs, do not adjust for inflation. For example, if the plant incurred a land cost in 2002, enter the cost in the "Cost" column and enter "2002" in the "Year on which Cost is Based" column.

Note: Capital costs associated with ponds/impoundments are requested in Part D and capital costs associated with landfills/landfilling are requested in Part F. Do NOT include the costs for ponds and landfills in Table C-16.

Note: Provide only the cost data incurred by the PLANT, not the costs paid for by the contractor. For example, if an outside contractor purchased all rail cars and/or trucks for the transportation of the fly ash at the contractor's expense, the plant should fill out "\$ 0" for the cost of "Purchased Equipment". Any contractor costs/fees incurred by the plant should be accounted for in the "Engineering Contract Firm Costs" and "Other Contractor's Fees" categories.

Table C-16, Capital Cost for Transport/Disposal of Collected Fly Ash

Table C-16. Capital Cost for Transport/Disposal of Collected Fly Ash Vear on Which Cost is Base								
	Ι.	Cook for Custom		Cost for	Year on Which Cost is Based			
Project		Cost for System as Originally Installed	N	Modifications to System	Original Cost	Modification Cost		
Direct Costs								
<u>Purchased equipment</u> (including all equipment for the installation or the upgrade: mechanical equipment; piping; instrumentation; electrical equipment; spare parts; freight charges; taxes; insurance; and duties)	\$		\$					
Purchased equipment installation (including installation of all equipment; piping; instrumentation/calibration; electrical equipment; mechanical equipment; structural supports, insulation, and paint)	\$		\$					
<u>Buildings</u> (including buildings constructed to house ash handling system components, operator rooms, or other operations associated with the system; as well as plumbing, heating, ventilation, dust collection, air conditioning, lighting, telephones, intercoms, painting, sprinklers, fire alarms)	\$		\$					
Site preparation (including site clearing, all demolition, grading, roads, walking areas, fences)	\$		\$					
Land (includes property costs and survey fees)	\$		\$					
Total Direct Costs	\$		\$					
Indirect Costs								
Engineering Costs (including process design and general engineering, cost engineering, consulting fees, supervision, inspection for each category below:								
a. Engineering Contract Firm Costs	\$		\$					
b. Owner's Overhead Engineering Costs	\$		\$					
☐ Hired outside engineering firm to oversee design and/or installation of the system.	1		1					
Construction expenses (includes temporary construction offices, roads, communications, fencing; construction tools and equipment; permits, taxes, insurance)	\$		\$					
Other Contractor's Fees	\$		\$					
Contingency actually expended (to compensate for unpredictable events such as storms, floods, strikes, price changes, errors in estimates, design changes, etc.)	\$		\$					
Total Indirect Costs	\$		\$					
Total Capital Cost	\$		\$					
	•		•					

C-25 Approved: May XX, 2010

CBI?	C2-51. Are all major of	components of transport/disposal for the fly ash handling system included in the capital costs reported in Table C-16?
Yes	O Yes	(Skip to Question C2-52)
	○ No	(Continue)

Please explain what system components are included in the capital costs listed in Table C-16. Additionally, identify the key components of transport/disposal for the fly ash handling system that are not included in the capital costs reported in Table C-16.

CBI? ☐ Yes

C2-52. Provide annual O&M costs data in Table C-17 for the transport/disposal of the collected fly ash from ash handling systems that began operating on or after January 1, 2000. Provide best engineering estimates when actual data are not readily available. If you provide an estimate, note the methods that were used to make the estimates in the Comments page.

Note: O&M costs associated with ponds/impoundments are requested in Part D and O&M costs associated with landfills/landfilling are requested in Part F. Do NOT include the costs for ponds and landfills in Table C-17.

Note: Provide only the cost data incurred by the PLANT, not the costs paid for by the contractor. For example, if an outside contractor operates the transportation and disposal of the ash at the contractor's expense, the plant should fill out "\$ 0" for the cost of all operating O&M costs. Any contractor costs/fees incurred by the plant should be accounted for in the Table C-16 "Engineering Contract Firm Costs" and "Other Contractor's Fees" categories.

Table C-17. O&M Cost for Transport/Disposal of the Fly Ash for 2009

O&M Cost Category	2009 Annual Cost	2009 Rate	2009 Staffing/Consumption	Transport Rate
Operating Labor (Trucks/Rail Cars/Other Transport)		Per hour	No. of workers	·
	\$	\$(average rate	hpd	Loads per day
		of labor)	dpy	dpy
Operating Labor (All other operating costs)		Per hour	No. of workers	
	\$	\$ (average rate	hpd	
		of labor)	dpy	
Maintenance Labor		Per hour	No. of workers	
	\$	\$(average rate	hpd	
		of labor)	dpy	
Maintenance Materials				
	\$			
_				
Energy	Φ.	s per kWh	1-101 h /h /r	
	Ф	\$per kWh	kWh/hr	
Ash Removal/Disposal Fees				
Asit Hemova/Disposari ees	\$			
	Ψ			
Other:	\$			
Other:	\$			
Total O&M Cost (2009)	\$			

Plant ID: Insert Plant ID
Plant Name: Insert Plant ID
SE Unit ID: Insert Unit ID

Part: C

CBI? □Yes Section Title: 3.1. Bottom Ash Handling - Generating Unit Level Information

Instructions: Throughout Section 3.1 (Questions C3-1 through C3-31), provide ash handling information for each steam electric generating unit operated at any time in 2009, including units that may have been idle for an extended period of time. Make copies of Section 3.1 for each steam electric generating unit using the "Copy Section 3.1" button below. Enter the steam electric generating Unit ID (use Unit IDs assigned in Table A-8) in the space above titled "SE Unit ID".

Copy Section 3.1

CBI? C3-1. Is bottom ash generated in any fossil-fueled steam electric generating units at the plant? See Part A Section 8 for steam electric generating unit fuel classifications.

O Yes (Continue)
O No (Skip to Section 4)

C3-2. Provide bottom ash handling information in Table C-18, for each steam electric generating unit reported in Table A-8, following these instructions:

- Provide bottom ash handling information at the steam electric generating unit level. For the purpose of this questionnaire, more than one type of bottom ash handling (e.g., wet sluicing, SCC) may be selected for one generating unit. Check all types of bottom ash handling that apply to this steam electric generating unit.
- Refer to the glossary and the "Part C Instructions" tab for definitions related to wet and dry bottom ash handling systems.

Table C-18. Bottom Ash Handling Systems Operated in 2009 by Generating Unit

Type of Boiler		Type of Bottom Ash Handling System	(Dry weig	d in 2009 ght basis)	of Bottom	Ash in 2009	Design Ash H	ht basis)	Number of Days Ash was Handled by the Bottom Ash Handling System in 2009		Loss on Ignition of Bottom Ash Produced (Provide typical range for 2009)	
			Wet Conveyed	Dry Conveyed	Wet Conveyed	Dry Conveyed	Wet Conveyed	Dry Conveyed	Wet Conveyed	Dry Conveyed	Wet Conveyed	Dry Conveyed
Wet-bottom Other:	▼	Wet sluicing Mechanical drag system □ Dry vacuum □ Dry pressure □ Other:	1,500 tpd 365 dpy	0 tpd 0 dpy	%	% ☑ na	5 tpd 5 dpy	0 tpd 0 dpy	<i>365</i> days	0 days		to%
Type of Boiler Other:	▼	☐ Wet sluicing ☐ Mechanical drag system ☐ Dry vacuum ☐ Dry pressure ☐ Other: ☐ Other:	tpd dpy	tpd dpy	%	% □na	tpd dpy	tpd dpy	days		to %	to%

CBI?	
—	

C3-3. Is wet sluicing used to collect bottom ash for this steam electric generating unit?

O Yes (Continue)

O No (Skip to Question C3-11)

Provide information for the wet bottom ash handling system in Table C-19. For the source of sluice water, you may enter more than one source from the following options:

- "IN" if raw intake water is used;
- "IN-Makeup" if raw intake water is only used as makeup;
- "TR" for use of intake water that has been treated on site prior to use;
- "TR-Makeup" if treated intake water is used only as makeup; and/or
- Process wastewater and/or treated wastewater described the code tables on the "Code Tables" tab provided at the end of this workbook.

An example is provided in Table C-19 for a plant that uses the effluent from its ash pond (WWT-1, as would be defined in Part A) for bottom ash sluicing and also makes up for losses with untreated river water (which is code IN-Makeup as shown above).

Table C-19. Process Wastewater Generated from Wet Bottom Ash Handling in 2009 Typical Duration Average Sluice Water Flow Rate (gpd) Source(s) of Sluice Water Percent Contribution AND Frequency of of Source to Sluice Sluicing (hpd AND Water Flow dpy) EXAMPLE: WWT-1 Effluent T-IN-Makeup 14,400,000 apd hpd $| \mathbf{v} |$ Sluice Water Source 365 _dpy Other: ▼ Sluice Water Source -Sluice Water Source hpd \blacksquare Sluice Water Source dpy

	L				Other.		//		
CBI? □ Yes			ces that may be used as a soulble for the water to be used for				ater), indicate the maximu	m chlorides concentration and the maximum solids percentage	
			Chlorides concentration, less th	nan:		_ppm			
			Solids percentage, less than:			<u> </u> %			
			Other:			_ppm			
CBI?	C3-5.	Is any of the w	ret <i>bottom ash sluice</i> water imm	nediately recycled (e.	.g., without treatn	nent such as a pond) back to pla	nt process?		
∏ Yes		O Yes	(Continue)						
		O No	(Skip to Question C3-6)						
	1	Describe how t	the wet <i>hottom ash sluice</i> is re	ised.					

C-28 Approved: May XX, 2010

CBI? C3-6. Is any of the wet bottom ash sluice indirectly discharged to a publicly or privately owned treatment works?

O Yes
O No

CBI? C3-7. Does solids removal (other than in pond(s)/impoundment(s)) occur at the plant?

O Yes
O No
O No
O No
O (Skip to Question C3-11)

C3-8. In Table C-20 provide solids removal information, on a dry ton basis, for the wet ash sluice system. For the purpose of Table C-20, solids removal does NOT include ash ponds.

Table C-20. Wet Ash Sluice Systems Operated in 2009 Solids Removal Bottom Ash Disposal [Check all boxes that apply] Amount (tons) Typical [Check all of Solids Percent Moisture of Disposed (Dry boxes that weight basis) **Bottom Ash** apply] Disposed Dewatering bin Sold or given away without further treatment tons Sold or given away after further treatment Hydrocyclones tons Centrifuges Stored in/transferred to a pond/impoundment reported in Table A-4 tons Filters Stored in landfills reported in Table A-6 tons Other: Stored in landfills NOT reported in Table A-6 tons Other: tons

CBI?

Yes

CBI? □ Yes	C3-9. Provide the amount of wastewater overflow from solids removal (e.g., dewatering bins) for the wet ash sluice system.
	gpdgpd
CBI? □ Yes	C3-10. What is the destination(s) of the wastewater overflow from solids removal? If the plant recycles the wastewater, indicate the amount and the plant process to which this waste is recycled. [Check all boxes that apply.]
	Immediately recycled back to plant process.
	Provide the amount of wastewater overflow that is recycled.
	gpd
	Describe how the wastewater overflow is reused:

C-29 Approved: May XX, 2010

CBI? C3-11. Does the plant use a mechanical drag system (e.g., submerged chain conveyor (SCC)) to remove bottom ash from this generating unit boiler? Yes (Continue) O Yes (Skip to Question C3-15) O No Name the type and describe the process of removing bottom ash from the generating unit boiler(s). C3-12. Is any process wastewater generated from overflow, or other means, from the mechanical drag system? CBI? Yes O Yes (Continue) O No (Skip to Question C3-15) CBI? C3-13. Provide the amount of wastewater overflow from the mechanical drag system. Yes CBI? C3-14. What is the destination(s) of the wastewater overflow from the mechanical drag system? If the plant recycles the wastewater, indicate the amount and the plant process to which this waste is recycled. [Check Yes Yes all boxes that apply.] ☐ Immediately recycled back to plant process. Provide the amount of wastewater overflow that is recycled. gpd Describe how the wastewater overflow is reused: ☐ Transferred to on-site treatment system. Identify the type of treatment system below. [Check all boxes that apply.] Settling pond Constructed wetlands pH adjustment Other, specify: ☐ Discharged to surface water. Provide NPDES permitted outfall number (from Part A Section 2.2): ☐ Indirect discharge to a publicly or privately owned treatment works

Steam Electric Questionnaire

Other, explain:

C-30 Approved: May XX, 2010

Part C. Ash Handling

Steam Electric Questionnaire

CBI? □Yes C3-15. In Table C-21, identify the destination(s) for wet and dry bottom ash transferred from the hopper(s) of this steam electric generating unit. Provide the distribution of the wet and dry ash by destination and whether the storage indentified is an intermediate or final destination.

Note: The sum of the percentage of ash distribution should equal 100% for the dry and wet bottom ash, separately.

Table C-21. Storage Destinations that Receive Bottom Ash

Dry Conve	yed Bottom Ash	Ť	Wet Convey	ed Bottom Ash	Bottom Ash			
Storage Destination(s)	Percent of Dry Conveyed Bottom Ash to this Destination	Destination Type	Storage Destination(s)	Percent of Wet Conveyed Bottom Ash to this Destination	Destination Type			
Storage Destination Table	%	O Intermediate	Storage Destination Table	%	O Intermediate			
If other, explain:		O Final	If other, explain:		O Final			
Storage Destination Table	%	O Intermediate	Storage Destination Table	%	O Intermediate			
If other, explain:		O Final	If other, explain:		O Final			
Storage Destination Table	%	O Intermediate	Storage Destination Table	%	O Intermediate			
If other, explain:		O Final	If other, explain:		O Final			
Storage Destination Table	%	O Intermediate	Storage Destination Table	%	O Intermediate			
If other, explain:		O Final	If other, explain:		O Final			
Storage Destination Table	%	O Intermediate	Storage Destination Table	%	O Intermediate			
If other, explain:		O Final	If other, explain:		O Final			
Total Dr	100 %		Total We	et 100 %				

	Storage De	estination Table		%	O Intermediate	Storage Destination Table	<u> </u>	%	O Intermediate				
	If other,	explain:			O Final	If other, explain:			O Final				
			Total Dry	100 %			Total Wet	100 %					
CBI? □Yes	C3-16. Was the	e bottom ash from this s	steam electric gene	rating unit conve	yed both wet and o	dry in 2009?							
	○ Ye	s (Continue)											
	O No	(Skip to Questi	ion C3-19)										
CBI? □ Yes	C3-17. Indicate why bottom ash from the steam electric generating unit was conveyed both wet and dry in 2009. [Check all boxes that apply.] For each selection, identify the number was operated for this reason.												
	☐ Wet bot	tom ash handling system operated	d during times in which the d	ry collected bottom ash	was not marketable.			days					
	☐ Wet bot	tom ash handling system operated	d when the dry bottom ash c	ollection system was not	operational due to mainten	ance issues.		days					
	☐ Wet bot	tom ash handling system operated	d in order to maintain its fun	tion as a backup to the	dry system (i.e., wet systen	operated to ensure that it is still functional.)		days					
	☐ Wet bot	tom ash handling system operated	d because the dry bottom as	handling system does	not have the capacity to har	ndle all of the bottom ash.		days					
	Other, e	xplain:						days					
CBI? □Yes	C3-18. What modifications would be required to handle all the bottom ash with a dry bottom ash handling system? [Check all boxes that apply.]												
	☐ No syste	em modifications necessary. Proced	dural changes would be suff	cient.									
	☐ Increase	e the capacity of the silo(s).											
	☐ Increase	e the number of silos.											
	☐ Modify t	the loading silos to have the ability	to moisture condition the as	h.									
	☐ Install/ii	ncrease the capacity of landfills.											
	☐ Increase	e the capacity of the dry bottom as	sh conveying equipment.										
	☐ Design/	develop new infrastructure to dispo	ose of dry ash. Specify the n	ew infrastructure neede	i:								
	Other, e	explain:											

C-31 Approved: May XX, 2010

CBI? □Yes		urrent bottom ash handlin all boxes that apply.]	g operations for the steam electric genera	ting unit are expected to significantly change by December 31, 2020, indicate how (i.e., convert to or add dry handling capability).
	Expand capacity (handling and/or storage). Decreased use of wet bottom ash handling system. (expected operating days per year for wet system)			
	☐ End use of wet bottom ash handling system. (expected end date)			date)
	☐ No char	ge expected in bottom ash handling	operations.	
	Other,	explain:		
CBI? □ Yes	C3-20. Was the dry bottom ash handling installed as a retrofit to the steam electric generating unit?			
	O NA	, this unit does not use dry bottom a	sh handling (Skip to Question C3-24)	
	O No O Yes	(-	23-24)	
		Year Built:		
	Shutdown time (days) required to bring dry bottom ash handling system on line:			
	Was a generating unit outage(s), outside of regularly scheduled outages, required to bring the dry bottom ash handling system on line?			
		O Yes		
		○ No		
CBI? □Yes	C3-21. What type of retrofit was the dry bottom ash handling system?			
	O The retrofit was made to an existing dry system.			(Skip to Question 3-29)
	O A dry bottom ash handling system was installed (for operation in addition to the wet fly ash handling system).			system). (Continue)
	O The retrofit was a complete conversion from a wet to dry bottom ash handling system.		from a wet to dry bottom ash handling system.	(Continue)
CBI? □Yes	C3-22. Describe the changes that were required to retrofit (for a retrofit to an existing dry system, an installation of a dry system, or a complete conversion from wet to dry). [Check all boxes that apply.]			
	☐ Physical changes to facility			
			Installation of pressure/vacuum system	n and piping
			Boiler alteration to accommodate the n	nechanical drag system
			Expansion of pressure/vacuum system	n and piping
			Installation of storage silos	
			Modification of the silos to moisture-co	ndition the ash
			Modification of the silos for ash transfe	er to rail cars
			Modification of the silos for marketable	ash
			Construction of haul roads	
			Construction of rail track	
			Construction of landfill. Provide the lan	dfill ID(s) from Table A-6:
			Increasing landfill capacity. Provide the	e landfill ID(s) from Table A-6:
			Changes to air permit	
			Other, explain:	
	☐ Changes in personnel/training, explain:			
	Changes in ash disposal practices			
			Storage of ash in landfills. Provide the	landfill ID(s) from Table A-6:
			Marketing of ash	
			Hauling ash to off-site storage	
		_	Dust suppression activities	
			Other, explain:	

G-32 Approved: May XX, 2010

Steam Electric Questionnaire CBI? C3-23. Attach an engineering process diagram(s) for the dry bottom ash handling system retrofit that depicts (with dimensions) the conveyance portion of the system Yes (e.g., a diagram(s) that depicts how the dry bottom ash system is configured within the building to convey bottom ash from the boiler(s) to the building exit). Diagram attached. CBI? C3-24. Is the plant in the process of installing a dry bottom ash handling system to handle some or all of the ash currently handled by the wet bottom ash handling system? Yes O Yes Estimated shutdown time (days) required to bring dry bottom ash handling system online: (Skip to Question C3-26) O No (Continue to Question C3-25) CBI? C3-25. Is the plant planning to install a dry bottom ash handling system to handle some or all of the ash currently handled by the wet bottom ash handling system? Yes O Yes (Continue to Question C3-26) Estimated shutdown time (days) required to bring dry bottom ash handling system online: O No (Skip to Question C3-29) CBI? C3-26. If the plant is in the process of installing, or planning to install, a dry bottom ash handing system by December 31, 2020, provide the cost estimates that have □Yes been developed for such a conversion/installation. O Yes (Provide documentation/costs, for example, bid proposals or internal plant engineering estimates.) (Skip to Question C3-29) O No Note: All bid proposals and/or other documentation/costs originally submitted to the plant as CBI, should be marked CBI for the purpose of this collection request. O I have attached documentation/costs. O I did not attach documentation/costs. Below, explain why: CBI? C3-27. Describe the modifications that will be required to install the dry bottom ash handling system. [Check all boxes that apply.] □Yes Physical changes to facility Installation of mechanical drag system Boiler alteration to accommodate the mechanical drag system Installation of completely dry bottom ash handling system П Installation of storage silos Modification of the silos to moisture-condition the ash Modification of the silos for ash transfer to rail cars Modification of the silos for marketable ash Construction of haul roads Construction of rail track П Construction of landfill. Provide the landfill ID(s) from Table A-6: Increasing landfill capacity. Provide the landfill ID(s) from Table A-6: Changes to air permit

Other, explain:

Marketing of ash

Other, explain:

Hauling ash to off-site storage Dust suppression activities

Storage of ash in landfill. Provide the landfill ID(s) from Table A-6:

C-33

Changes in personnel/training, explain:

Changes in ash disposal practices

П

Approved: May XX, 2010

Part C. Ash Handling

Steam Electric Questionnaire

CBI? □ Yes	C3-28. Ir	ndicate the ty	pes of destinations expected fo	r the dry bottom ash from the p	e planned system and the percentage of the dry bottom ash that is expected to go to each destination. [Check all boxes that apply.]
			Marketed, sold, and/or given	▼	% of the dry bottom ash
			If other, specify:		
			Market Destinations	<u>▼</u>	% of the dry bottom ash
			If other, specify:		
			Market Destinations	▼	% of the dry bottom ash
			If other, specify:		
			Stored in landfills reported in T	able A-6	% of the dry bottom ash
			Stored in landfills NOT reporter	d in Table A-6	% of the dry bottom ash
	С		Other, specify:		% of the dry bottom ash
CBI? □Yes	C3-29 . If	f the plant is	not in the process of installing o	r planning to install a dry bottor	tom ash handling system, have cost estimates been obtained/developed since January 1, 1995, for such a conversion/installation?
			O Yes	(Provide documentation/costs,	ts, for example, bid proposals or internal plant engineering estimates.)
			○ No	(Skip to Question C3-30)	
	N	Note: All bid	proposals and/or other docui	mentation/costs originally su	submitted to the plant as CBI, should be marked CBI for the purpose of this collection request.
			O I have attached documentation/costs.		
			O I did not attach documentation/costs. Below	w, explain why:	
CBI? □Yes	C3-30. ⊢	las the plant	encountered any unscheduled of	outages on this generating unit	nit caused by the bottom ash handling system in the last five years?
_ 16		O Yes O No	(Continue) (Skip to Section 3.2)		
		O 140	(ONIP to Occitoff 3.2)		

C-34 Approved: May XX, 2010

Steam Electric Questionnaire

CBI? □Yes

C3-31. In Table C-22, provide information on unscheduled generating unit outages caused by bottom ash handling for each of the last five years.

Table C-22. Unscheduled Generating Unit Outages Caused by Bottom Ash Handling

Year	Ash Handling	Total Days of Outage	Reason(s) for outage(s)	Method(s) Used to Resolve Outage(s)
		, ,		
2005	Dry			
2003	Wet			
2006	Dry			
2006	Wet			
	Dry			
2007	Wet			
	Dry			
2008	Wet			
	Dry			
2009	Wet			

C-35 Approved: May XX, 2010

Plant ID: Insert Plant ID
Plant Name: Insert Plant Name

Part: C

Section Title: 3.2 Bottom Ash Handling - Storage and Use Data

Instructions: Complete Section 3.2 (Questions C3-32 through C3-34). Provide information for bottom ash handling and bottom ash storage at the plant.

CBI? □Yes C3-32. For each storage destination reported in Table C-21, provide the distance the bottom ash is transported from the generating unit to intermediate storage or from intermediate storage to the final disposal/destination, the amount of bottom ash transported in 2009, and the percent moisture of the bottom ash entering storage, if transported dry. Additionally, for each destination indicate how the bottom ash is transported by entering one of the following options: conveyor belt, pipe, truck, barge, rail, or other (provide a description). If the bottom ash is sold to more than one destination (e.g., some bottom ash is sold for cement manufacturing and some is sold for structural fill) enter the average percent moisture for all bottom ash sold in Table C-23. Tables C-24 and C-25 will request information by market.

Table C-23. Bottom Ash Storage Information

Storaç	ge Destination ID	Distance from the Generating Unit to Intermediate Storage or from the Intermediate Storage to the Final Disposal/Destination	Tons of Bottom Ash Transported to Destination in 2009 (dry weight basis)	How is Bottom Ash Transported to Destination?	Percent Moisture of the Bottom Ash Entering Destination		
Storage Destination	Table $ extstyle extstyle$	miles	tons	Storage Transport	%		
Other:				If other, explain:			
Storage Destination	Table <u>▼</u>	miles	tons	Storage Transport	%		
Other:				If other, explain:			
Storage Destination	Table $ extstyle extstyle$	miles	tons	Storage Transport	<u></u> %		
Other:				If other, explain:			
Storage Destination	Table ▼	miles	tons	Storage Transport	%		
Other:				If other, explain:			
Storage Destination	Table ▼	miles	tons	Storage Transport	%		
Other:				If other, explain:			
Storage Destination	Table ▼	miles	tons	Storage Transport ▼	%		
Other:				If other, explain:			
Storage Destination	Table ▼	miles	tons	Storage Transport	%		
Other:				If other, explain:			
Storage Destination	Table ▼	miles	tons	Storage Transport ▼	%		
Other:				If other, explain:			
Storage Destination	Table ▼	miles	tons	Storage Transport ▼	%		
Other:				If other, explain:			

CBI? □ Yes

C3-33. Does the plant market, sell, and/or give away dry bottom ash from the dry ash handling system?

O Yes (Continue)

O_{No} (Skip to Question C3-34)

Complete Table C-24 if the plant markets, sells, and/or gives away dry bottom ash from the bottom ash handling system. For each destination, provide the tons of dry bottom ash marketed, sold, and/or given away, the gross revenue generated from marketing/selling the dry bottom ash for calendar years 2005, 2007, and 2009. Additionally, provide the typical percent moisture of the bottom ash during calendar years 2005, 2007, and 2009. If the typical percent moisture of the bottom ash was not constant during calendar years 2005, 2007, and 2009, note this information (include all typical percent moisture values for each year) in the Comments page.

Table C-24. Dry Bottom Ash from the Bottom Ash Handling System Marketed/Sold in Calendar Years 2005, 2007, and 2009

Destination	Typical Percent	2005		l cars zo	2007		2009	
	Moisture of Bottom Ash	Tons (dry basis)	Gross Revenue Generated \$	Tons (dry basis)	Gross Revenue Generated \$	Tons (dry basis)	Gross Revenue Generated \$	
Concrete/Concrete Products/Grout	%							
Blended Cement/Raw Feed for Clinker	%							
Flowable Fill	%							
Structural Fills/Embankments	%							
Road Base/Sub-base	%							
Soil Modification/ Stabilization	%							
Mineral Filler in Asphalt	%							
Snow and Ice Control	%							
Blasting Grit/Roofing Granules	%							
Mining Applications	%							
Waste Stabilization/ Solidification	%							
Agriculture	%							
Aggregate	%							
Other:	%							
Other:	%							

C-37

Approved: May XX, 2010

CBI? ☐ Yes C3-34. Does the plant market, sell, and/or give away wet bottom ash from the wet ash handling system?

O yes (Continue)

O No (Skip to Section 3.3)

Complete Table C-25 if the plant currently markets, sells, and/or gives away bottom ash transported by wet sluicing from the bottom ash handling system. For each destination, provide the tons, on a dry basis, of bottom ash transported by wet sluicing that is marketed, sold, and/or given away. Also provide the gross revenue generated from marketing/selling the bottom ash transported by wet sluicing for each destination.

Table C-25. Bottom Ash Transported by Wet Sluicing from the Bottom Ash Handling System Marketed/Sold in Calendar Years 2005, 2007, and 2009

Destination	Typical Percent	2005			2007	2009	
	Moisture of Bottom Ash	Tons (dry basis)	Gross Revenue Generated	Tons (dry basis)	Gross Revenue Generated \$	Tons (dry basis)	Gross Revenue Generated \$
Concrete/Concrete Products/Grout	%						
Blended Cement/Raw Feed for Clinker	%						
Flowable Fill	%						
Structural Fills/Embankments	%						
Road Base/Sub-base	%						
Soil Modification/ Stabilization	%						
Mineral Filler in Asphalt	%						
Snow and Ice Control	%						
Blasting Grit/Roofing Granules	%						
Mining Applications	%						
Waste Stabilization/ Solidification	%						
Agriculture	%						
Aggregate	%						
Other:	%						
Other:	%						

C-38

Approved: May XX, 2010

Plant ID: Insert Plant ID
Plant Name: Insert Plant Name
Unit ID: Insert Unit ID

Part: C

Section Title: 3.3. Bottom Ash Cost Information - Conveyance

Instructions: Complete Section 3.3 (Questions C3-35 through C3-41) for the conveyance of bottom ash (wet or dry) from each unit identified in Table A-8. Provide these data for each bottom ash handling system that began operating or was converted after January 1, 2000. Enter the Unit ID in the space provided above.

If you indicated in Question C3-24 or C3-25 that the plant is either installing or planning to install dry bottom ash handling for this unit, complete Section 3.3, and check the "Planned" checkbox below.

Planned

Make copies of Section 3.3 for each bottom ash handling system operated in 2009, that began operating on or after January 1, 2000, is being installed, or planned to be installed by December 31, 2020 using the "Copy Section 3.3" button below.

The conveyance portion of the bottom ash handling system refers to the part of the system that conveys bottom ash from the boiler(s) of the unit to the intermediate or final storage of the bottom ash. Dry bottom ash handling includes systems that collect and convey the bottom ash without any use of water, as well as systems in which bottom ash is conveyed mechanically or pneumatically away from a quench water bath (e.g., submerged chain conveyor systems). Wet bottom ash conveyance uses water (i.e., a sluice) to convey bottom ash away from the boiler to intermediate/final storage (e.g., ponds/impoundments). Note that dewatering bins are considered part of bottom ash conveyance.

Note: Bottom ash conveyance includes all capital and O&M costs required to dredge or empty ponds, dewatering bins, and/or surge tanks to intermediate storage.

Note: If any components of the conveyance portion of the bottom ash handling system are shared with one or more other generating units, only report those components and corresponding costs once.

Copy Section 3.3

CBI?

☐ Yes

C3-35. Identify the major components of the conveyance portion of the bottom ash handling system, in particular those components that represent a significant portion of the capital or O&M costs for the system. Provide the type of component and the number of each type of component in the system. Additionally, provide the total system capacity of each type of component (i.e., volume of clarifying tanks). Total system capacity should equal the sum of the capacity of each individual component within that type.

Table C-26. Bottom Ash Handling System Components - Conveyance

Type of Components		Number of Components in the System	Total System Capacity of Components			
Bottom Ash Conveyance Components	▼		Component Units			
Other:			If other, specify:			
Bottom Ash Conveyance Components	▼		Component Units			
Other:			If other, specify:			
Bottom Ash Conveyance Components	₹		Component Units ▼			
Other:			If other, specify:			
Bottom Ash Conveyance Components	▼		Component Units ▼			
Other:			If other, specify:			
Bottom Ash Conveyance Components	▼]		Component Units ▼			
Other:			If other, specify:			
Bottom Ash Conveyance Components	▼]		Component Units ▼			
Other:			If other, specify:			
Bottom Ash Conveyance Components	▼]		Component Units ▼			
Other:			If other, specify:			
Bottom Ash Conveyance Components	▼]		Component Units ▼			
Other:			If other, specify:			

C-39 Approved: May XX, 2010

CBI? ☐ Yes		Attach a block diagram that shows the entire bottom ash handling system operations for this generating unit. Label the conveyance, intermediate storage (see Part C Section 3.4) and transport/disposal (see Part C Section 3.5) portions of the system. The diagram should include all key components indicated in Tables C-26 and C-29 and identify all intermediate and final ash storage destinations. Indicate the movement of ash as well as water through the system. If ash from other generating units is combined with ash from this unit, indicate where the ash is combined and the portions of the ash handling system involved. Provide as many diagrams as necessary to convey this information. Include the plant name, plant ID, and the unit ID in the upper right hand corner of the diagram.
		Note: If the respondent indicates that the ash is transported to a pond/impoundment, in Question C3-43, the intermediate storage and disposal information will be provided in Part D. Therefore, the block diagram should only include the conveyance system(s).
		Diagram attached.
CBI? □Yes		List all of the major components of this bottom ash conveyance system that a contractor(s) constructed/installed (or will construct/install, for planned systems) at the contractor's expense (i.e., not at the plant's expense).
		Contractor installed/will install ALL components identified in Table C-26 at the contractor's expense.
CBI? □Yes	C3-38.	List all of the operation and maintenance activities of this bottom ash conveyance system that a contractor(s) oversees (or will oversee, for planned systems) at the contractor's expense (i.e., not at the plant's expense).
		Contractor oversees/will oversee ALL operation and maintenance activities dealing with the conveyance portion of the bottom ash handling system at the contractor's expense.

C-40 Approved: May XX, 2010

CBI? ☐ Yes C3-39. In Table C-27, provide capital costs incurred since January 1, 2000, for this bottom ash conveyance system, both for the conveyance as originally installed and for any modifications to the conveyance. Include all conveyance costs including costs for components in Table C-26 as well as control systems, pads and foundations, and all other ancillary equipment. For planned bottom ash conveyance systems, provide expected costs. Provide the best engineering estimates when actual data are not readily available. For all costs, do not adjust for inflation. For example, if the plant incurred a land cost in 2002, enter the cost in the "Cost" column and enter "2002" in the "Year on which Cost is Based" column.

Note: Provide only the costs incurred by the PLANT, not the costs paid for by the contractor. For example, if an outside contractor purchased and installed all equipment for the conveyance portion of the bottom ash handling system at the contractor's expense, the plant should fill out "\$ 0" for the cost of "Purchased Equipment". Any contractor costs/fees incurred by the plant should be accounted for in the "Engineering Contract Firm Costs" and "Other Contractor's Fees" categories.

Table C-27. Capital Cost for Conveyance of Bottom Ash Handling

Project	r Conveyance of Bottom Ash Har Cost for System as Originally	Cost for Modifications	Year on Which Cost is Based		
·	Installed	to System	Original Cost	Modification Cost	
Direct Costs					
<u>Purchased equipment</u> (including all equipment for the installation or the upgrade: mechanical equipment; piping; instrumentation; electrical equipment; spare parts; freight charges; taxes; insurance; and duties)	\$	\$			
Purchased equipment installation (including installation of all equipment; piping; instrumentation/calibration; electrical equipment; mechanical equipment; structural supports, insulation, and paint)	\$	\$			
Buildings (including buildings constructed to house ash handling system components, operator rooms, or other operations associated with the system; as well as plumbing, heating, ventilation, dust collection, air conditioning, lighting, telephones, intercoms, painting, sprinklers, fire alarms)	\$	\$			
Site preparation (includes site clearing, all demolition, grading, roads, walking areas, fences)	\$	\$			
<u>Land</u> (includes property costs and survey fees)	\$	\$			
Total Direct Costs	\$	\$			
Indirect Costs					
Engineering Costs (includes process design and general engineering, cost engineering, consulting fees, supervision, inspection for each category below)					
a. Engineering Contract Firm Costs	\$	\$			
b. Owner's Overhead Engineering Costs	\$	\$			
Hired outside engineering firm to oversee design and/or installation of the system.					
Construction expenses (includes temporary construction offices, roads, communications, fencing; construction tools and equipment; permits, taxes, insurance)	\$	\$			
Other Contractor's Fees	\$	\$			
Contingency actually expended (to compensate for unpredictable events such as storms, floods, strikes, price changes, errors in estimates, design changes, etc.)	\$	\$			
Total Indirect Costs	\$	\$			
Total Capital Cost	\$	\$			

C-41 Approved: May XX, 2010

CBI?	C3-40. Are all maj	40. Are all major components of the conveyance portion of the bottom ash handling system included in the capital costs reported in Table C-27?									
Yes	○ Yes	(Skip to Question C3-41)									
	○ No	(Continue)									
		lain what system components are included in the capital costs listed in Table C-27. Additionally, identify the key components of the conveyance portion of the handling system that are not included in the capital costs reported in Table C-27.									

CBI?

Yes

C3-41. Provide annual (2009) O&M costs data in Table C-28 for this bottom ash conveyance system, if it began operating or was converted on or after January 1, 2000. Provide best engineering estimates when actual data are not readily available. If you provide an estimate, note the methods that were used to make the estimates in the Comments page.

Note: Provide only the cost data incurred by the PLANT, not the costs paid for by the contractor. For example, if an outside contractor operates and maintains the conveyance portion of the bottom ash handling system at the contractor's expense, the plant should fill out "\$ 0" for O&M costs. Any contractor costs/fees incurred by the plant should be accounted for in the Table C-27 "Engineering Contract Firm Costs" and "Other Contractor's Fees" categories.

Table C-28. O&M Cost for Conveyance of Bottom Ash Handling for 2009 **O&M Cost Category** 2009 Annual Cost 2009 Rate 2009 Staffing/Consumption Per hour No. of workers (average rate of Operating Labor hpd labor) dpy Per hour No. of workers (average rate of hpd Maintenance Labor labor) dpy Maintenance Materials kWh/hr Energy per kWh Other: Total O&M Cost (2009)

Plant ID: Insert Plant ID
Plant Name: Insert Plant Name
Storage ID: Insert Storage ID

Part: C

Section Title: 3.4. Bottom Ash Cost Information - Intermediate Storage

Instructions: Complete Section 3.4 (Questions C3-42 through C3-49) for each intermediate storage destination identified in Table C-23 that began operating or was modified after January 1, 2000. Enter the storage ID in the space provided above (use the storage IDs assigned in Table C-23).

If you indicated in Question C3-25 or C3-26 that the plant is either installing or planning to install dry bottom ash handling for this unit, complete Section 3.4, and check the "Planned" checkbox below.



Make copies of Section 3.4 for each bottom ash handling system operated in 2009, that began operating on or after January 1, 2000, is being installed, or planned to be installed by December 31, 2020 using the "Copy Section 3.4" button below.

If you are instructed to skip forward to another section while completing this section for one bottom ash storage destination, be sure to complete this section for all other bottom ash storage destinations operated in 2009, being installed, or planned to be installed by December 31, 2020.

The intermediate storage of bottom ash handling refers to the facility/site where collected bottom ash is stored after conveyance, prior to the ash being transported to final disposal. Dry bottom ash intermediate storage typically consists of storage silos. Wet bottom ash intermediate storage typically consists of ponds/impoundments.

Note that intermediate storage includes all equipment and operations associated with loading dry or moisture-conditioned ash into trucks or rail cars for transport. Intermediate storage also includes all ash dust suppression activities at the plant.

Copy Section 3.4

CBI? C3-42. Does this storage component store both fly and bottom ash together? For example, if bottom ash and fly ash are conveyed separately but stored in a common silo, the silo is considered a shared component. Yes O Yes Provide unit IDs, as assigned in A-8, contributing fly ash to this storage component. (Skip to Section 3.5) (Continue) O No CBI? C3-43. Is this storage destination a pond/impoundment? Yes O Yes (Skip to Section 4) O No (Continue)

C-43 Approved: May XX, 2010

CBI? ☐ Yes C3-44. Identify the major components of the intermediate storage portion of the bottom ash handling system, in particular those components that represent a <u>significant</u> portion of the capital or O&M costs for the system. Provide the type of component and the number of each type of component in the system. Additionally, provide the total capacity of each component (i.e., volume of silos). Total system capacity should equal the sum of the capacity of each individual component within that type.

Table C-29. Bottom Ash Handling System Components - Intermediate Storage

Individual Components		Number of Components in the System	Total System Capacity of Components				
Bottom Ash Intermediate Storage Components	▼		Component Units				
Other:			If other, specify:				
Bottom Ash Intermediate Storage Components	▼		Component Units				
Other:			If other, specify:				
Bottom Ash Intermediate Storage Components	▼		Component Units				
Other:			If other, specify:				
Bottom Ash Intermediate Storage Components	▼		Component Units				
Other:			If other, specify:				
Bottom Ash Intermediate Storage Components	▼		Component Units				
Other:			If other, specify:				
Bottom Ash Intermediate Storage Components	▼		Component Units				
Other:			If other, specify:				
Bottom Ash Intermediate Storage Components	▼		Component Units				
Other:			If other, specify:				
Bottom Ash Intermediate Storage Components	▼		Component Units				
Other:			If other, specify:				

CBI?
Yes

C3-45. List all of the major components of this intermediate storage destination that a contractor(s) constructed/installed (or will construct/install, for planned systems) at the contractor's expense (i.e., not at the plant's expense).

Contractor installed/will install	AΠ	components	identified in	Table	C-29 a	t the	contractor's	s expense.

CBI? ☐ Yes

C3-46. List all of the operation and maintenance activities of this intermediate storage destination that a contractor(s) oversees (or will oversee, for planned systems) at the contractor's expense (i.e., not at the plant's expense).

C-44 Approved: May XX, 2010

Contractor oversees/will oversee ALL operation and maintenance activities dealing with the intermediate storage portion of the bottom ash handling system at the contractor's expense.

CBI? ☐ Yes C3-47. Provide cost data in Table C-30 for this intermediate storage destination, both for the storage as originally installed and for any modifications to the storage system. Include all intermediate storage costs including costs for components in Table C-29 as well as control systems, pads and foundations, and all other ancillary equipment. For planned storage, provide expected costs. Provide the best engineering estimates when actual data are not readily available. For all costs, do not adjust for inflation. For example, if the plant incurred a land cost in 2002, enter the cost in the "Cost" column and enter "2002" in the "Year on which Cost is Based" column.

Note: Capital costs associated with ponds/impoundments are requested in Part D and capital costs associated with landfills/landfilling are requested in Part F. Do NOT include the costs for ponds and landfills in Table C-30.

Note: Provide only the cost data incurred by the PLANT, not the costs paid for by the contractor. For example, if an outside contractor purchased all rail cars and/or trucks for the transportation of the bottom ash at the contractor's expense, the plant should fill out "\$ 0" for the cost of "Purchased Equipment". Any contractor costs/fees incurred by the plant should be accounted for in the "Engineering Contract Firm Costs" and "Other Contractor's Fees" categories.

Table C-30. Capital Cost for Intermediate Storage of Bottom Ash Handling

			Year on Which Cost is Based		
Project	Cost for System as Originally Installed	Cost for Modifications to System	Original Cost	Modification Cost	
Direct Costs					
<u>Purchased equipment</u> (including all equipment for the installation or the upgrade: mechanical equipment; piping; instrumentation; electrical equipment; spare parts; freight charges; taxes; insurance; and duties)	\$	\$			
Purchased equipment installation (including installation of all equipment; piping; instrumentation/calibration; electrical equipment; mechanical equipment; structural supports, insulation, and paint)	\$	\$ <u> </u>			
<u>Buildings</u> (including buildings constructed to house ash handling system components, operator rooms, or other operations associated with the system; as well as plumbing, heating, ventilation, dust collection, air conditioning, lighting, telephones, intercoms, painting, sprinklers, fire alarms)	\$	\$			
Site preparation (including site clearing, all demolition, grading, roads, walking areas, fences)	\$	\$			
Land (including property costs and survey fees)	\$	\$			
Total Direct Costs	\$	\$			
Indirect Costs Engineering Costs (including process design and general engineering, cost engineering, consulting fees, supervision, inspection for each category below)					
a. Engineering Contract Firm Costs	\$	\$			
b. Owner's Overhead Engineering Costs	\$	\$			
Hired outside engineering firm to oversee design and/or installation of the system.					
Construction expenses (including temporary construction offices, roads, communications, fencing, construction tools and equipment; permits, taxes, insurance)	\$	\$			
Other Contractor's Fees	\$	\$			
Contingency actually expended (to compensate for unpredictable events such as storms, floods, strikes, price changes, errors in estimates, design changes, etc.)	\$	\$			
Total Indirect Costs	\$	\$			
Total Capital Cost	\$	\$			

CBI?	C3-48. Are all major components of the intermediate storage destination included in the capital costs reported in Table C-30?						
Yes	○ Yes	(Skip to Question C3-49)					
	○ No	(Continue)					
		ain what system components are included in the capital costs listed in Table C-30. Additionally, identify the key components intermediate storage destination included in the capital costs reported in Table C-30.					

CBI? ☐ Yes C3-49. Provide annual O&M costs data in Table C-31 for this intermediate storage destination, if it began operating or was modified on or after January 1, 2000. Provide best engineering estimates when actual data are not readily available. If you provide an estimate, note the methods that were used to make the estimates in the Comments page.

Note: O&M costs associated with ponds/impoundments are requested in Part D and O&M costs associated with landfills/landfilling are requested in Part F. Do NOT include the costs for ponds and landfills costs in Table C-31.

Note: Provide only the cost data incurred by the PLANT, not the costs paid for by the contractor. For example, if an outside contractor operates and maintains the intermediate storage portion of the bottom ash handling system at the contractor's expense, the plant should fill out "\$ 0" for O&M costs. Any contractor costs/fees incurred by the plant should be accounted for in the Table C-30 "Engineering Contract Firm Costs" and "Other Contractor's Fees" categories.

Table C-31. O&M Cost for Intermediate Storage of Bottom Ash Handling for 2009

O&M Cost Category	2009 Annual Cost	2009 Rate	2009 Staffing/Consumption
Operating Labor (Water Trucks Only)	\$	Per hour (average rate of labor)	No. of workers hpd dpy
Operating Labor (All other operating costs)	\$	Per hour (average rate of labor)	No. of workers hpd dpy
Maintenance Labor	\$	Per hour (average rate of labor)	No. of workers hpd dpy
Maintenance Materials	\$		
Energy	\$	\$per kWh	kWh/hr
Other:	\$		
Other:	\$		
Total O&M Cost (2009)	\$		

Plant ID: Insert Plant ID
Plant Name: Insert Plant Name

Da		
	ITI:	

Section Title: 3.5. Bottom Ash Cost Information - Transport/Disposal

Instructions: Complete Section 3.5 (Questions C3-50 through C3-57) for all transport and disposal of bottom ash from ash handling systems that began operating or was modified after January 1, 2000, and those systems being installed, or planned to be installed by December 31, 2020.

The transport/disposal portion of the bottom ash handling system refers to the transportation of bottom ash from intermediate storage to final disposal.

An example of ash transport/disposal is transportation used to haul ash off site (e.g., ash that is marketed and shipped off site to a reuse application). Ash transport typically consists of roads and vehicles that are used to transport the ash. The capital and O&M costs for ash transport/disposal may include the road or rail infrastructure (roads, tracks, lights), the trucks and rail cars, the operation and maintenance costs associated with the trucks and rail cars, and ash disposal fees.

Note that capital and operation and maintenance costs associated with ponds/impoundments and landfills/landfilling are requested in Parts D and F, respectively, and they should not be provided here in Section 3.5.

CBI? □Yes	•	Does the plant use the same transport and disposal methods for both fly and bottom ash? For example, if fly ash and bottom ash are transported using the same trucks, the trucks are considered shared component.					
	○ Yes	Provide unit IDs, as assigned in A-8, and storage IDs, provided in Table 6, contributing fly ash to the transport and disposal system.					
	○ No	(Skip to Section 4)					
CBI? □Yes	C3-51. Is a pond/impound	ment unit or pond/impoundment system the final destination of all bottom ash collected by the plant?					
	○ Yes	(Skip to Section 4)					
	○ No	(Continue)					

C-47 Approved: May XX, 2010

CBI? □Yes	C3-52.	What methods are use	ed to transport the collected bottom ash to the final disposal? [Check all boxes that apply.]
		Trucks	How many trucks does the plant use for the transportation and disposal of dry bottom ash? Indicate whether the trucks were bought, leased or contracted out. Bought Leased Contracted out
		Rail cars	How many rail cars does the plant use for the transportation and disposal of dry bottom ash?
			Indicate whether the rail cars were bought, leased or contracted out. Bought Leased Contracted out
		Other, specify (e.g., barge):	
CBI? □Yes		List all of the major co the plant's expense).	mponents for transport/disposal of the bottom ash that a contractor(s) constructed/installed (or will construct/install, for planned systems) at the contractor's expense (i.e., not at
		Contractor installed/will insta	Il ALL ash transport/disposal equipment and/or infrastructure at the contractor's expense.
CBI? □Yes		List all of the operation the plant's expense).	and maintenance activities for transport/disposal of the bottom ash that a contractor(s) oversees (or will oversee, for planned systems) at the contractor's expense (i.e., not at
		Contractor oversees/will overs	see ALL transport/disposal activities at the contractor's expense.

C-48 Approved: May XX, 2010

CBI?

☐ Yes

C3-55. Provide cost data in Table C-32 for the transport/disposal of the collected bottom ash, both for the transport/disposal as originally installed and for any modifications. For transport/disposal systems, provide expected costs. Provide the best engineering estimates when actual data are not readily available. For all costs, do not adjust for inflation. For example, if the plant incurred a land cost in 2002, enter the cost in the "Cost" column and enter "2002" in the "Year on which Cost is Based" column.

Note: Capital costs associated with ponds/impoundments are requested in Part D and capital costs associated with landfills/landfilling are requested in Part F. Do NOT include the costs for ponds and landfills in Table C-32.

Note: Provide only the cost data incurred by the PLANT, not the costs paid for by the contractor. For example, if an outside contractor purchased all rail cars and/or trucks for the transportation of the fly ash at the contractor's expense, the plant should fill out "\$ 0" for the cost of "Purchased Equipment". Any contractor costs/fees incurred by the plant should be accounted for in the "Engineering Contract Firm Costs" and "Other Contractor's Fees" categories.

Table C-32. Capital Cost for Transport/Disposal of Collected Bottom Ash

Table C-32. Capital Cost to	r Tı	ansport/Disposal of Collect	ed	Bottom Ash		
Project		ost for System as Originally Installed	Modifications		Year on Which Cost is Based Original	
		installed		to System	Cost	Modification Cost
Direct Costs						
<u>Purchased equipment</u> (including all equipment for the installation or the upgrade: mechanical equipment; piping; instrumentation; electrical equipment; spare parts; freight charges; taxes; insurance; and duties)	\$		\$			
Purchased equipment installation (including installation of all equipment; piping; instrumentation/calibration; electrical equipment; mechanical equipment; structural supports, insulation, and paint)	\$		\$			
Buildings (including buildings constructed to house ash handling system components, operator rooms, or other operations associated with the system; as well as plumbing, heating, ventilation, dust collection, air conditioning, lighting, telephones, intercoms, painting, sprinklers, fire alarms)	\$		\$			
<u>Site preparation</u> (including site clearing, all demolition, grading, roads, walking areas, fences)	\$		\$			
<u>Land</u> (includes property costs and survey fees)	\$		\$			
Total Direct Costs	\$		\$			
Indirect Costs						
Engineering Costs (including process design and general engineering, cost engineering, consulting fees, supervision, inspection for each category below)						
a. Engineering Contract Firm Costs	\$		\$			
b. Owner's Overhead Engineering Costs	\$		\$			
Hired outside engineering firm to oversee design and/or installation of the system.						
Construction expenses (including temporary construction offices, roads, communications, fencing; construction tools and equipment; permits, taxes, insurance)	\$		\$			
Other Contractor's Fees	\$		\$			
Contingency actually expended (to compensate for	\$		\$			
unpredictable events such as storms, floods, strikes, price changes, errors in estimates, design changes, etc.)			+			
Total Indirect Costs	\$		\$			
Total Capital Cost	\$		\$			

C-49 Approved: May XX, 2010

CBI?	C3-56. Are all major components of transport/disposal for the bottom ash handling system included in the capital costs reported in Table C-32?	Are all major compone
Yes	O Yes (Skip to Question C3-57)	O Yes (Skip to
	O № (Continue)	O No (Continu

Please explain what system components are included in the capital costs listed in Table C-32. Additionally, identify the key components of transport/disposal for the bottom ash handling system that are not included in the capital costs reported in Table C-32.

CBI?

☐ Yes

C3-57. Provide annual O&M costs data in Table C-33 for the transport/disposal of the collected bottom ash from ash handling systems that began operating on or after January 1, 2000. Provide best engineering estimates when actual data are not readily available. If you provide an estimate, note the methods that were used to make the estimates in the Comments page.

Note: O&M costs associated with ponds/impoundments are requested in Part D and O&M costs associated with landfills/landfilling are requested in Part F. Do NOT include the costs for ponds and landfills in Table C-33.

Note: Provide only the cost data incurred by the PLANT, not the costs paid for by the contractor. For example, if an outside contractor operates the transportation and disposal of the ash at the contractor's expense, the plant should fill out "\$ 0" for the cost of all operating O&M costs. Any contractor costs/fees incurred by the plant should be accounted for in the Table C-32 "Engineering Contract Firm Costs" and "Other Contractor's Fees" categories.

Table C-33. O&M Cost for Transport/Disposal of the Bottom Ash for 2009

O&M Cost Category	2009 Annual Cost	2009 Rate	2009 Staffing/Consumption	Transport Rate
Operating Labor (Trucks/Rail Cars/Other Transport)	\$	Per hour (average rate of labor)	No. of workers hpd dpy	Loads per day dpy
Operating Labor (All other operating costs)	\$	Per hour (average rate of labor)	No. of workers hpd dpy	
Maintenance Labor	\$	Per hour (average rate of labor)	No. of workers hpd dpy	
Maintenance Materials	\$	1		
Energy	\$	\$per kWh	kWh/hr	
Ash Removal/Disposal Fee	\$			
Other:	\$			
Other:	\$			
Total O&M Cost (2009)	\$			

> Plant ID: Insert Plant ID Plant Name: Insert Plant Name SE Unit ID: Insert SE Unit ID

Part: C

Section Title: 4. Economizer Ash Handling Information

Instructions: Make copies of Section 4 (Questions C4-1 through C4-6) for each fossil-fueled steam electric generating unit at your plant that generates economizer ash using the "Copy Section 4" button below. See Part A Section 8 for steam electric generating unit fuel classifications. Enter the steam electric generating unit IDs assigned in Table A-8) in the space above titled "SE Unit ID".

		Copy Section 4							
CBI? ☐ Yes	C4-1. Is economizer ash from this fossil-fueled steam electric generating unit collected with air heater ash?								
□ res	0,	Yes (Complete the rema	inder of Section 4 for economizer ar	nd air heater ash together.	Do NOT complete Section 5.)				
	01	No (Continue)							
CBI? □ Yes	C4-2. Ind	licate the method of handli	ng the economizer ash.						
	Os	Segregated from fly and bottom ash							
		Describe	e how the segregated ash was handled:		(Skip to Question C4-4)				
	00	Combined with fly and/or bottom ash			(Continue)				
CBI? ☐ Yes	C4-3. Ide	entify how the economizer a	ash is combined with fly ash and/or b	pottom ash.					
	Он	Handled wet, with fly ash							
	Он	Handled wet, with bottom ash							
	Он	Handled dry, with fly ash							
	Он	Handled dry, with bottom ash							
	O c	Other, explain:							
CBI? □ Yes	C4-4. Pro	ovide the average amount	of dry economizer ash produced.						
		tpd (dr	y weight basis)						
		dpy							

C-51 Approved: May XX, 2010

CBI?	C4-5. Is	process wastewater	generated from the handling of	economizer	ash?				
Yes	С) Yes	(Continue)						
	С) No	(Skip to Section 5)						
	Pr	ovide the volume of	economizer ash wastewater ger	nerated in 20	09 (gpd) and the frequen	ncy of economizer a	ash wastewater genera	ation (days).	
			gpd	Over		days			
	Pr	ovide the destination	n of the economizer ash wastew	ater generate	ed: Destinat	tion Codes Table			
CBI? ☐ Yes		hat is the final dispo	sition/destination of the collected	d economize	r ash? [Check all boxes t	hat apply.] Indicate	the percentage of ec	onomizer ash transporte	ed to each
		Stored in a landfill reported in	n Table A-6				% of economizer ash		
		Stored in a pond/impoundme	ent reported in Table A-4				% of economizer ash		
		Stored in a landfill NOT repo	rted in Table A-6				% of economizer ash		
		Hauled off site (to be market	ted)				% of economizer ash		
		Hauled off site (to be given a	away)				% of economizer ash		
		Other:					% of economizer ash		

C-52 Approved: May XX, 2010

Plant ID: Insert Plant ID
Plant Name: Insert Plant Name
SE Unit ID: Insert SE Unit ID

Part: C

Section Title: 5. Air Heater Ash Handling Information

Instructions: Make copies of Section 5 (Questions C5-1 through C5-5) for each fossil-fueled steam electric generating unit at your plant that generates air heater ash using the "Copy Section 5" button below. See Part A Section 8 for steam electric generating unit fuel classifications. Enter the steam electric generating unit ID (use unit IDs assigned in Table A-8) in the space above titled "SE Unit ID".

		Copy Section 5			
CBI? □ Yes	C5-1.	Indicate the method of hand	ling the air heater ash.		
		O Segregated from fly and bottom ash			
		Describ	be how the segregated ash was handled:		(Skip to Question C5-3)
		O Combined with fly and/or bottom ash			(Continue)
CBI? □Yes	C5-2.	Identify how the air heater as	sh is combined with fly ash and/or bottom	ash.	
		O Handled wet, with fly ash			
		O Handled wet, with bottom ash			
		O Handled dry, with fly ash			
		O Handled dry, with bottom ash			
		Other, explain:			
CBI? ☐ Yes	C5-3.	Provide the average amount	of dry air heater ash produced.		
		tpd (d	ry weight basis)		
		dpy			

C-53

CBI? ☐ Yes	C5-4. Is proces	ss wastewater generated from the han	idling of air heater ash?			
	○ Yes	(Continue)				
	○ No	(Skip to next Questionnaire Part)				
	Provide	the volume of air heater ash wastewat	er generated in 2009 (gpd)	and the frequency of air heater	r ash wastewater generation (d	ays).
		gpd	Over	days		
	Provide	the destination of the air heater ash wa	astewater generated:	Destination Codes Table	.▼	
CBI? □Yes	C5-5. What is destinati	the final disposition/destination of the cion.	collected air heater ash? [0	Check all boxes that apply.] Indic	cate the percentage of air heate	er ash transported to each
	Stored in	n a landfill reported in Table A-6			% of air heater ash	
	Stored in	n a pond/impoundment reported in Table A-4			% of air heater ash	
	Stored in	n a landfill NOT reported in Table A-6			% of air heater ash	
	☐ Hauled o	off site (to be marketed)			% of air heater ash	
	☐ Hauled o	off site (to be given away)			% of air heater ash	
	Other:				% of air heater ash	

Plant ID: Insert Plant ID
Plant Name: Insert Plant Name

Part: C

Section Title: Part C Comments

Instructions: Cross reference your comments by question number and indicate the confidential status of your comment by checking the box

next to "Yes" under "CBI?" (Confidential Business Information).

	Question Number	Comment
CBI?		
CBI? ☐ Yes		
CBI? ☐ Yes		
CBI? ☐ Yes		
CBI? ☐ Yes		
CBI?		
CBI?		
CBI? ☐ Yes		
CBI? ☐ Yes		
CBI? ☐ Yes		

CBI?	
CBI?	
CBI?	
CBI? ☐ Yes	
CBI? ☐ Yes	
CBI?	
CBI?	
CBI?	
CBI?	
CBI? ☐ Yes	
CBI?	
CBI? ☐ Yes	
CBI?	
CBI?	

Steam Electric Questionnaire Code Tables

Process Wastewaters		
For Use in Tables and Questions throughout Parts A, B, C, D, and F.		
Air heater cleaning water	AHCW	
Ash pile runoff	APR	
Boiler blowdown	BB	
Boiler fireside cleaning water	BFCW	
Boiler tube cleaning water	BTCW	
Bottom ash sluice	BAS	
Carbon capture wastewater	CCAPW	
Coal pile runoff	CPR	
Combined ash sluice	CAS	
Combustion turbine cleaning (combustion gas portion of	COMBCW	
turbine) water		
Combustion turbine cleaning (compressor portion of the	COMPRCW	
turbine) water		
Combustion turbine evaporative coolers blowdown	TECB	
Cooling tower blowdown	CTB	
FGD scrubber purge	SCRBP	
FGD slurry blowdown	FGDB	
Filter Backwash	FLTBW	
Floor drain wastewater	FDW	
Flue gas mercury control system wastewater	FGMCW	
Fly ash sluice	FAS	
General runoff	GR	
Gypsum pile runoff	GPR	
Gypsum wash water	GYPWW	
lon exchange wastewater	IXW	
Landfill runoff - capped landfill	LRC	
Landfill runoff - uncapped landfill	LRUC	
Leachate	LEACH	
Limestone pile runoff	LPR	
Mill reject sluice	MRS	

Treated Wastewaters		
For Use as Effluents from Pond/Impoundment Systems and/or Wastewater Treatment Systems in Part D, Table D-4.		
Effluent - 1	EFF-1	
Effluent - 2	EFF-2	
Effluent - 3	EFF-3	
Effluent - 4	EFF-4	
Effluent - 5	EFF-5	
Effluent - 6	EFF-6	
Filter backwash	FItBW	
Sludge	SLDG	
For Use as Influents to Pond/Impou	ındment Systems and/or	
Wastewater Treatment Systems in		
Recycled Waters Throughout		
POND-1 Effluent	POND-1-EFF	
POND-2 Effluent	POND-2-EFF	
POND-3 Effluent	POND-3-EFF	
POND-4 Effluent	POND-4-EFF	
POND-5 Effluent	POND-5-EFF	
POND-6 Effluent	POND-6-EFF	
POND-7 Effluent	POND-7-EFF	
POND-8 Effluent	POND-8-EFF	
POND-9 Effluent	POND-9-EFF	
POND-10 Effluent	POND-10-EFF	
POND-A Effluent	POND-A-EFF	
POND-B Effluent	POND-B-EFF	
POND-C Effluent	POND-C-EFF	
WWT-1 Effluent	WWT-1-EFF	
WWT-2 Effluent	WWT-2-EFF	
WWT-3 Effluent	WWT-3-EFF	
WWT-4 Effluent	WWT-4-EFF	
WWT-5 Effluent	WWT-5-EFF	

Process Wastewaters		
For Use in Tables and Questions throughout	t Parts A, B, C, D, and F.	
Once -through cooling water	CW	
Reverse osmosis reject water	RORW	
SCR catalyst regeneration wastewater	SCRRW	
SCR catalyst washing wastewater SCRWW		
Soot blowing wash water SOOTW		
Steam turbine cleaning water STCW		
Yard drain wastewater YARDW		

Treated Wastewaters		
For Use as Influents to Pond/Impoundment Systems and/or Wastewater Treatment Systems in Part D, Table D-3, AND Recycled Waters Throughout Questionnaire.		
WWT-6 Effluent WWT-6-EFF		
WWT-A Effluent WWT-A-EFF		
WWT-B Effluent	WWT-B-EFF	
WWT-C-EFF WWT-C-EFF		

Wastewater Treatment Units		
For Use in Tables and Questions Throughout Parts D and F.		
Adsorptive media	ADSORB	
Aerobic Biological Reactor	AERBIO	
Anaerobic Biological Reactor	ANBIO	
Aerobic/Anaerobic Biological Reactor	AER/ANBIO	
Chemical Precipitation Reaction Tank 1 - 1	CP-1-1	
Chemical Precipitation Reaction Tank 1 - 2	CP-1-2	
Chemical Precipitation Reaction Tank 2 - 1	CP-2-1	
Chemical Precipitation Reaction Tank 2 - 2	CP-2-2	
Chemical Precipitation Reaction Tank 3 - 1	CP-3-1	
Chemical Precipitation Reaction Tank 3 - 2	CP-3-2	
Clarification, Primary - 1	CL-P-1	
Clarification, Primary - 2	CL-P-2	
Clarification, Secondary - 1	CL-S-1	
Clarification, Secondary - 2	CL-S-2	
Clarification, Tertiary - 1	CL-T-1	
Clarification, Tertiary - 2	CL-T-2	
Constructed wetland - Cell 1	CWL -1	
Constructed wetland - Cell 2	CWL -2	
Constructed wetland - Cell 3	CWL -3	
Constructed wetland - Cell 4	CWL -4	
Constructed wetland - Cell 5	CWL -5	
Constructed wetland - Cell 6	CWL -6	
Constructed wetland system	CWTS	
Equalization, Primary EQ-P		
Equalization, Secondary	EQ-S	
Filter, Microfiltration - 1 FLT-M-1		
Filter, Microfiltration - 2 FLT-M-2		

Destinations		
For Use in Tables and Questions Throughout Parts A, C, D,		
and F.		
Burned on site	BURN	
Deep-well injection	DWELL	
Discharge to POTW	POTW	
Discharge to PrOTW	PrOTW	
Discharge to surface water	SW	
Evaporation	EVAP	
Hauled off site for reuse	HAULR - RF	
(removal fee)		
Hauled off site for reuse (given	HAULR - GA	
away)		
Hauled off site for reuse	SOLD	
(marketed and sold)		
Hauled off site for disposal	HAUL	
Mixed with fly ash for disposal	MFA	
On-site landfill (as reported in	LANDF	
Table A-6)		
POND-1	POND-1	
POND-2	POND-2	
POND-3	POND-3	
POND-4	POND-4	
POND-5	POND-5	
POND-6	POND-6	
POND-7	POND-7	
POND-8	POND-8	
POND-9	POND-9	
POND-10	POND-10	
POND-A	POND-A	
POND-B	POND-B	
POND-C	POND-C	
WWT-1	WWT-1	
WWT-2	WWT-2	

Wastewater Treatment Units		
For Use in Tables and Questions Throughout Parts D and F.		
Filter, Microfiltration - 3	FLT-M-3	
Filter, Microfiltration - 4	FLT-M-4	
Filter, Sand/Gravity - 1	FLT-S-1	
Filter, Sand/Gravity - 2	FLT-S-2	
Filter, Sand/Gravity - 3	FLT-S-3	
Filter, Sand/Gravity - 4	FLT-S-4	
Filter, Ultrafiltration - 1	FLT-U-1	
Filter, Ultrafiltration - 2	FLT-U-2	
Filter, Ultrafiltration - 3	FLT-U-3	
Filter, Ultrafiltration - 4	FLT-U-4	
Filter press - 1	FP-1	
Filter press - 2	FP-2	
Holding tank	HT	
lon exchange	IX	
Natural wetlands	NW	
pH adjustment - 1	PH-1	
pH adjustment - 2	PH-2	
pH adjustment - 3	PH-3	
Reverse osmosis	ROS	
Pond Unit - 1	SPD-1	
Pond Unit - 2	SPD-2	
Pond Unit - 3	SPD-3	
Pond Unit - 4	SPD-4	
Pond Unit - 5	SPD-5	
Pond Unit - 6	SPD-6	
Pond Unit - 7 SPD-7		
Pond Unit - 8	SPD-8	
Pond Unit - 9	SPD-9	

Destinations		
For Use in Tables and Questions Throughout Parts A, C, D,		
and F.		
WWT-3	WWT-3	
NAME 4	1404 T	
WWT-4	WWT-4	
WWT-5	WWT-5	
WWT-6	WWT-6	
WWT-A	WWT-A	
WWT-B	WWT-B	
WWT-C	WWT-C	
Reuse as boiler water	RECYC - BW	
Reuse as bottom ash sluice	RECYC - BAS	
Reuse as combined ash sluice	RECYC - CAS	
Reuse as FGD slurry	RECYC - FGDP	
preparation water		
Reuse as FGD absorber	RECYC - FGDAB	
makeup		
Reuse as fly ash sluice	RECYC - FAS	
Reuse as mill reject sluice	RECYC - MRS	
Reuse in cooling towers	RECYC - CW	

Wastewater Treatment Units		
For Use in Tables and Questions Throughout Parts D and F.		
Pond Unit - 10	SPD-10	
Pond Unit - 11	SPD-11	
Pond Unit - 12	SPD-12	
Pond Unit - 13	SPD-13	
Pond Unit - 14	SPD-14	
Settling tank - 1	ST-1	
Settling tank - 2	ST-2	
Settling tank - 3	ST-3	
Settling tank - 4	ST-4	
Settling tank - 5	ST-5	
Thickener - 1	TH-1	
Thickener - 2	TH-2	
Vacuum drum filter - 1	VF-1	
Vacuum drum filter - 2 VF-2		
Vacuum filter belt - 1	VFB-1	
Vacuum filter belt - 2 VFB-2		

Solids Handling	
For Use as Planned Solids Handling for the FGD Slurry Blowdown in Part B Table B-2.	
Centrifuge - 1 Centrifuge - 2	CENT-1 CENT-2
Centrifuge - 3	CENT-3
Centrifuge - 4 Hydrocyclones - 1	CENT-4 HYC-1
Hydrocyclones - 2 Hydrocyclones - 3	HYC-2 HYC-3
Hydrocyclones - 4 Filter press - 1	HYC-4
Filter press - 2	FP-2
Thickener - 1 Thickener - 2	TH-1 TH-2
Vacuum drum filter - 1 Vacuum drum filter - 2	VF-1 VF-2
Vacuum filter belt - 1	VFB-1
Vacuum filter belt - 2	VFB-2

Part C Drop Downs

Wet/Dry	
Wet/Dry	
Select	
Wet	
Dry	

	Type of Boiler
Type of Boiler	
Select	
Wet-bottom	
Dry-bottom	
Other	

Storage Destination Table
Storage Destination Table
Select
Silo 1
Silo 2
Silo 3
Silo 4
Silo 5
Outdoor Pile 1
Outdoor Pile 2
Outdoor Pile 3
Outdoor Pile 4
Outdoor Pile 5
POND-1
POND-2
POND-3
POND-4
POND-5
POND-6
POND-7
POND-8
POND-9
POND-10
POND-A
POND-B
POND-C
LANDFILL-1
LANDFILL-2
LANDFILL-3
LANDFILL-4
LANDFILL-A
LANDFILL-B

LANDFILL-C	
LANDFILL-D	
Marketed, sold or given away	
Stored in landfills NOT reported in Table A-6	
Other	

Destination Codes Table
Destination Codes Table
Select
Burned on site
Deep-well injection
Discharge to POTW
Discharge to PrOTW
Discharge to surface water
Evaporation
Hauled off site for reuse (removal fee)
Hauled off site for reuse (given away)
Hauled off site for reuse (marketed and sold)
Hauled off site for disposal
Mixed with fly ash for disposal
On-site landfill (as reported in Table A-6)
POND-1
POND-2
POND-3
POND-4
POND-5
POND-6
POND-7
POND-8
POND-9
POND-10
POND-A
POND-B
POND-C
WWT-1
WWT-2
WWT-3
WWT-4
WWT-5
WWT-6
WWT-A
WWT-B
WWT-C
Reuse as boiler water
Reuse as bottom ash sluice
Reuse as combined ash sluice
Reuse as FGD slurry preparation water

Reuse as FGD absorber makeup
nease as i ab absorber makeup
Reuse as fly ash sluice
Reuse as mill reject sluice
Reuse in cooling towers

Trease in cooling towers
Sluice Water Source
Sluice Water Source
Select
IN
IN-Makeup
TR
TR-Makeup
Air heater cleaning water
Ash pile runoff
Boiler blowdown
Boiler fireside cleaning water
Boiler tube cleaning water
Bottom ash sluice
Carbon capture wastewater
Coal pile runoff
Combined ash sluice
Combustion turbine cleaning (combustion gas portion of
turbine) water
Combustion turbine cleaning (compressor portion of the
turbine) water
Combustion turbine evaporative coolers blowdown
Cooling tower blowdown
FGD scrubber purge
FGD slurry blowdown
Filter Backwash
Floor drain wastewater
Flue gas mercury control system wastewater
Fly ash sluice
General runoff
Gypsum pile runoff
Gypsum wash water
Ion exchange wastewater
Landfill runoff - capped landfill
Landfill runoff - uncapped landfill
Leachate
Limestone pile runoff
Mill reject sluice
Once -through cooling water
Reverse osmosis reject water
SCR catalyst regeneration wastewater
SCR catalyst washing wastewater
Soot blowing wash water

Steam turbine cleaning water
Yard drain wastewater
POND-1 Effluent
POND-2 Effluent
POND-3 Effluent
POND-4 Effluent
POND-5 Effluent
POND-6 Effluent
POND-7 Effluent
POND-8 Effluent
POND-9 Effluent
POND-10 Effluent
POND-A Effluent
POND-B Effluent
POND-C Effluent
WWT-1 Effluent
WWT-2 Effluent
WWT-3 Effluent
WWT-4 Effluent
WWT-5 Effluent
WWT-6 Effluent
WWT-A Effluent
WWT-B Effluent
WWT-C Effluent

Process Wastewaters
Process Wastewaters
Select
Air heater cleaning water
Ash pile runoff
Boiler blowdown
Boiler fireside cleaning water
Boiler tube cleaning water
Bottom ash sluice
Carbon capture wastewater
Coal pile runoff
Combined ash sluice
Combustion turbine cleaning (combustion gas portion of
turbine) water
Combustion turbine cleaning (compressor portion of the
turbine) water
Combustion turbine evaporative coolers blowdown
Cooling tower blowdown
FGD scrubber purge
FGD slurry blowdown
Filter Backwash
Floor drain wastewater

Fly Ash Conveyance Components
Fly Ash Conveyance Components
Select
Conveyor
Dewatering bin
Pressure blower
Transfer hopper
Wet vacuum equipment (e.g., hydroveyor)
Other

Fly Ash Intermediate Storage Components
Fly Ash Intermediate Storage Components
Select
Conveyor system (e.g., air slide, bucket conveyor)
Loading silo
Pug mill/pin mixer
Storage silo
Other

Bottom Ash Conveyance Components	
Bottom Ash Conveyance Components	
Select	
Clarifying tank	
Conveyor	
Dewatering bin	
Surge tank	

Wet vacuum equipment (e.g., hydroveyor)
Other

Bottom Ash Intermediate Storage Components Bottom Ash Intermediate Storage Components Select Conveyor system (e.g., air slide, bucket conveyor) Loading silo Pug mill/pin mixer Storage silo Other

Market Destinations
Market Destinations
Select
Aggregate
Agriculture
Blasting Grit/Roofing Granules
Blended Cement/Raw Feed for Clinker
Concrete/Concrete Products/Grout
Flowable Fill
Mineral Filler in Asphalt
Mining Applications
Road Base/Sub-base
Snow and Ice Control
Soil Modification/Stabilization
Structural Fills/Embankments
Waste Stabilization/Solidification
Other

	Units	
Units		
Select		
gpd		
gpy		

	Component Units
Component Units Select	
Select	
gal	
hp	
in	
Other	

Combined Intermediate Storage Components Combined Intermediate Storage Components

Select
Air slide
Baghouse for silos
Bin vent filter
Bucket conveyor
Conditioned load out spout with dust collection system
Conveyor system
Dust suppression (e.g., water truck)
Dry load out spout
Loading silo
Pug mill/pin mixer
Stackout/holding areas
Storage bin
Storage hopper
Storage silo
Vacuum loading equipment
Other

Storage Transport
Storage Transport
Select
Barge
Conveyor Belt
Pipe
Rail
- Truck
Other