



United States  
**ENVIRONMENTAL PROTECTION AGENCY**  
Washington, D.C. 20460

**ENERGY STAR External Power Supplies Partner**  
**Unit Shipment Data**  
Office of Atmospheric Programs

NAME OF MANUFACTURER: \_\_\_\_\_  
DATE OF SUBMISSION: \_\_\_\_\_  
SUBMITTED BY (NAME): \_\_\_\_\_

Reporting Period: CALENDAR YEAR 2007 (JAN. TO DEC.)

External Power Supplies (Output Power)	ENERGY STAR® U.S. Unit Shipments (REQUIRED)	ENERGY STAR® Non-U.S. Unit Shipments (REQUIRED)	Total U.S. Unit Shipments (ENERGY STAR + Non-ENERGY STAR) (REQUESTED)	Total Non-U.S. Unit Shipments (ENERGY STAR + Non-ENERGY STAR) (REQUESTED)
Single Voltage External Ac-Dc Power Supply:				
0-1 Watt				
1-2.5 Watts				
2.5-4.5 Watts				
4.5-6 Watts				
6-10 Watts				
10-24 Watts				
24-49 Watts				
>49 Watts				
Single Voltage External Ac-Ac Power Supply				
<b>Total</b>				

**DEFINITIONS**

1. Single Voltage External Power Supply:
  - a) is designed to convert line voltage ac input into lower voltage ac or dc output;
  - b) is able to convert to only one output voltage at a time;
  - c) is sold with, or intended to be used with, a separate end-use product that constitutes the primary load;
  - d) is contained in a separate physical enclosure<sup>1</sup> from the end-use product;
  - e) is connected to the end-use product via a removable or hard-wired male/female electrical connection, cable, cord, or other wiring;
  - f) does not have batteries or battery packs that physically attach directly (including those that are removable) to the power supply unit;
  - g) does not have a battery chemistry or type selector switch AND an indicator light or state of charge meter (e.g., a product with a type selector switch AND a state of charge meter is excluded from this specification; a product with only an indicator light is still covered by this specification); and
  - h) has nameplate output power less than or equal to 250 watts.

<sup>1</sup> "Physical enclosure" refers to the housing of the products themselves, not their retail packaging.

2. The definition above applies to both ac-dc and ac-ac power supplies respectively.

**Submission Deadline: March 31, 2008**

**Please submit by mail, email, or fax to:**

Elliott Rector  
ICF International  
1725 Eye Street, NW  
Suite 1000  
Washington, DC 20006  
[unitshipmentdata@icfi.com](mailto:unitshipmentdata@icfi.com)  
Fax: (202) 862-1144

Any information submitted to EPA for which a claim of confidentiality is made will be safeguarded according to the Agency policies set forth in Title 40, chapter 1, part 1, subpart B - Confidentiality of Business Information (see 40 CFR part 2; 41 FR 36902, September 1, 1976; amended by 43 FR 40000, September 8, 1978; 43 FR 42251, September 20, 1978; 44 FR 17674, March 23, 1979).

The public reporting and recordkeeping burden for this collection of information is estimated to average 6.7 hours per response. Send comments on the Agency's need for this information, the accuracy of the provided burden estimates, and any suggested methods for minimizing respondent burden, including through the use of automated collection techniques to the Director, Collection Strategies Division, U.S. Environmental Protection Agency (2822T), 1200 Pennsylvania Ave., NW, Washington, D.C. 20460. Include the OMB control number in any correspondence. Do not send the completed form to this address.