

Event Roster Begin Date Pop-Up Specifications

Version 03.01.0000
12/20/2007

Roster Pop-Up Window Display:

Add Event Date -- Web Page Dialog

DontKnow | Refusal
ENTER THE EVENT DATE.

Event Date:
MM DD YY

Add-And-Stay **Add-And-Exit** **Cancel**

Overview of display:

Display “ENTER THE EVENT DATE.” and “Event Date:” in the same blue font used for interviewer instructions.

Input fields:

Field #1	EVNT.EVBEGMM
Field #2	EVNT.EVBEGDD
Field #3	EVNT.EVBEGYY

See Event Roster Begin Date Pop-Up Window .pdf for additional specifications.

Background Variable Assignments:

If adding event:

Create a new Event for each visit/event added. Events are stored on EVNT:
EVNT key = EVNT.EVNTBASE + EVNT.EVNTNUM

BASE.LASTEVT holds the highest EVNT.EVNTNUM prior to fielding cases. Not all EVNT records are fielded. The first time an EVNT record is generated in the field, BASE.LASTEVT should be \geq to the highest EVNT.EVNTNUM fielded. The new EVNT.EVNTNUM should be calculated based on BASE.LASTEVT + 001. Each time an EVNT record is generated in the field, BASE.LASTEVT will be updated to match the highest EVNT.EVNTNUM in the field. Therefore, each time an EVNT record is generated in the field, the new EVNT.EVNTNUM should be calculated based on BASE.LASTEVT + 001. See detailed instructions below.

EVNT.EVNTBASE	=	BASE.BASEID
EVNT.EVNTNUM	=	EVNT.EVNTNUM = BASE.LASTEVT + 001. This assumes that BASE.LASTEVT is incremented each time an EVNT record is generated in the field.
EVNT.EVNTNRDC	=	Current round
EVNT.EVNTTYPE	=	Specified at Question level specification. Stores Type of Event.
EVNT.STEVTTYPE	=	Specified at Question level specification. Stores Type of Event used in Statement Series. N/A for all Event Roster Questions.
EVNT.EVNTPROV	=	Specified at Question level specification. Stores Provider number linked to event. N/A for all Event Roster Questions.
BASE.LASTEVT	=	Highest EVNT.EVNTNUM. Set BASE.LASTEVT = EVNT.EVNTNUM just added.

See Background Variable .pdf for additional specifications.