



US Department of Transportation
Federal Railroad Administration

Sample Car Inspection Checklist For: S-2044 Appendix D-2
Safety Appliances for Cars of Well or Spine Construction
with Side Mounted Hand Brakes

OMB No. 2130-0565
F6180.161d 12/15

ITEM	Number - Dimensions - Location - Manner of Application	Appendix Reference	Notes
<p>Manner of Application</p> <p>Sill Steps Number</p> <p>Dimensions</p>	<p>The center of the hand brake shaft of vertical-wheel hand brakes shall be located in the longitudinal direction not more than 21 in. from the inside face of the inboard vertical leg of the sill step and shall be not less than 26 in. above the lowest sill step tread nor more than 46 in. above the highest sill step tread. In addition, the center of the hand brake shaft shall be not more than 61 in. above the top of rail.</p>	<p>Appendix D2, 2.2.3</p>	
	<p>Clearance around the rim of the hand brake wheel or the grip portion of the hand brake operating lever throughout its full range of travel shall be not less than 4 in. Clearance between the grip portion of the release lever, if used, throughout its full range of travel and any part of the car shall be not less than 2 ½ in.</p>	<p>Appendix D2, 2.2.4</p>	
	<p>If the hand brake application is such that the requirements of paragraph 2.2.4 can be met only with hand brakes having short hand brake release levers or only with long release levers, but not both, the car shall be marked adjacent to the hand brake in 1 ½ in. high letters "SHORT (LONG) RELEASE LEVER BRAKE ONLY".</p>	<p>Appendix D2, 2.2.5</p>	
	<p>The hand brake housing shall be securely fastened. The hand brake application, including bolt hole pattern, shall conform to MSRP Section E, Standard S-475.</p>	<p>Appendix D2, 2.3.1</p>	
	<p>The hand brake chain shall conform to the requirements of S-475, but in any event shall have minimum working load of 5,875 lb and minimum proof test of 11,750 lb.</p>	<p>Appendix D2, 2.3.2</p>	
	<p>Hand brake rods shall be not less than ¾ in. diameter.</p>	<p>Appendix D2, 2.3.3</p>	
	<p>There shall be four sill steps.</p>	<p>Appendix D2, 3.1</p>	
<p>Sill steps shall conform to the requirements of Standard S-2042. Minimum usable length of tread shall be 14 in.</p>	<p>Appendix D2, 3.2.1</p>		
<p>Sill steps shall be of steel not less than ½ in. thick, shall be not less than 4 in. wide, and shall be provided with an antiskid surface.</p>	<p>Appendix D2, 3.2.2</p>		



US Department of Transportation
Federal Railroad Administration

Sample Car Inspection Checklist For: S-2044 Appendix D-2
Safety Appliances for Cars of Well or Spine Construction
with Side Mounted Hand Brakes

OMB No. 2130-0565
F6180.161d 12/15

ITEM	Number - Dimensions - Location - Manner of Application	Appendix Reference	Notes
Location	<p>Sill steps shall have sufficient treads such that the top tread is not more than 21 in. below the lowest adjacent horizontal side handhold, if the car is so equipped. If there are no horizontal side handholds, sill steps shall have sufficient treads such that the top tread is not more than 21 in. below the walking surface of the adjacent walkway, if the car is equipped with an adjacent walkway, and not more than 21 in. below the deck of the car. Sill step treads shall be spaced not more than 21 in. apart.</p>	Appendix D2, 3.2.3	
	<p>The clear depth above the entire usable length of all sill step treads shall be not less than 8 in. and the clear width of the lowest sill step tread shall be not less than 6 in. for both loaded and empty conditions with the trucks rotated to simulate the maximum curvature specified for the uncoupled car.</p>	Appendix D2, 3.2.4	
	<p>One sill step shall be applied near each end of each side of the car. The sill steps shall be located in the longitudinal direction such that the inside face of neither vertical leg of the sill step extends more than 2 in. into the space between the vertical side handholds or the space between the vertical handhold supports, whichever space is smaller.</p>	Appendix D2, 3.3.1	
	<p>In the transverse direction, the outside edge of any sill step tread shall be not more than 6 in. inboard or outboard of the inside surface of the adjacent side handholds. In addition, the outside edge of any sill step tread shall be no more than 4 in. inboard of any car structure below the adjacent side handholds in the area between the side handholds. With the exception of the side handholds and their supports, no part of the car below 66 in. above the top of the rail shall extend farther than 6 in. outboard of the outboard edge of the lowest sill step tread.</p>	Appendix D2, 3.3.2	
	<p>The lowest tread shall be not more than 20 in. above the top of rail.</p>	Appendix D2, 3.3.3	
Manner of Application	<p>When applied, sill steps adjacent to articulated connectors or drawbar connections of multi-unit cars shall conform to the requirements of paragraphs 3.2.1, 3.2.3, and 3.2.4. These sill steps shall be of steel not less than ½ in. thick and shall be not less than 2 in. wide. The sill steps shall be located in a longitudinal direction such that the inside face of neither vertical leg of the sill step extends more than 2 in. into the space between the vertical side handholds or the space between the vertical handhold supports, whichever space is smaller. Sill steps adjacent to hand brakes shall also comply with the requirements of paragraph 3.2.2.</p>	Appendix D2, 3.3.4	
	<p>Sill steps shall be securely fastened.</p>	Appendix D2, 3.4	



US Department of Transportation
Federal Railroad Administration

Sample Car Inspection Checklist For: S-2044 Appendix D-2
Safety Appliances for Cars of Well or Spine Construction
with Side Mounted Hand Brakes

OMB No. 2130-0565
F6180.161d 12/15

ITEM	Number - Dimensions - Location - Manner of Application	Appendix Reference	Notes
<p>Side Handholds Number Dimensions</p> <p>Location</p> <p>Manner</p>	<p>There shall be not less than eight side handholds, two at each corner.</p> <p>Handholds shall be of steel not less than ¾ in. diameter or pipe of 1 ¼ in. nominal pipe size with Schedule 40 minimum wall thickness. Handhold material shall conform to the requirements of Standard S-224. Minimum clear length shall be 16 in. Minimum clearance shall be 2 in., preferably 2 ½ in.</p> <p>Vertical side handholds shall have an uninterrupted span between the upper and lower clearance points.</p> <p>Horizontal side handholds below the car deck or adjacent walkway, if applied, shall have foot guards or upward projections not less than 2 in. in height at both ends.</p> <p>Two vertical handholds, one at either end of each sill step, shall be applied.</p> <p>The inboard surface of the outboard vertical handhold shall be not more than 14 in. from the inside surface of the nearest end handhold. The clear opening between the vertical handholds and their supports shall be not less than 18 in. The width over the vertical handholds shall be not more than 30 in.</p> <p>The clearance points of the bottom end of the vertical handholds shall be not more than 42 in. above the top of rail. The clearance points of the top end shall be not less than 33 in. above the adjacent walking surface of the walkway, if so equipped. If not equipped with an adjacent walkway, the clearance points of the top end shall be not less than 33 in. above the car deck.</p> <p>Spacing between horizontal side handholds, if applied, shall be not more than 19 in. Spacing from the highest horizontal side handhold to the adjacent walking surface of the walkway, if so equipped, shall be not more than 19 in. If not equipped with an adjacent walkway, spacing from the highest horizontal side handhold to the car deck shall be not more than 19 in.</p> <p>If the car is equipped with horizontal side handholds, the outboard clearance points of the handholds shall be not more than 2 in. inboard of the inside surface of the outboard vertical leg of the sill step, and the inboard clearance points of the handholds shall be not more than 2 in. outboard of the inside surface of the inboard vertical leg of the sill step.</p> <p>Side handholds shall be securely fastened.</p>	<p>Appendix D2, 4.1</p> <p>Appendix D2, 4.2.1</p> <p>Appendix D2, 4.2.2</p> <p>Appendix D2, 4.2.3</p> <p>Appendix D2, 4.3.1</p> <p>Appendix D2, 4.3.2</p> <p>Appendix D2, 4.3.3</p> <p>Appendix D2, 4.3.4</p> <p>Appendix D2, 4.3.5</p> <p>Appendix D2, 4.4</p>	



US Department of Transportation
Federal Railroad Administration

Sample Car Inspection Checklist For: S-2044 Appendix D-2
Safety Appliances for Cars of Well or Spine Construction
with Side Mounted Hand Brakes

OMB No. 2130-0565
F6180.161d 12/15

ITEM	Number - Dimensions - Location - Manner of Application	Appendix Reference	Notes
Side Handholds Adjacent to the Articulated Connectors or Drawbar Connections of Multi-Unit Cars	When side handholds are applied adjacent to articulated connectors or drawbar connections of multi-unit cars, sufficient vertical and horizontal handholds shall be applied to provide access from the ground to the deck or adjacent walkways.	Appendix D2, 5.1	
Dimensions	Handholds shall be of steel not less than ¾ in. diameter or pipe of 1 ¼ in. nominal pipe size with Schedule 40 minimum wall thickness. Handhold material shall conform to the requirements of Standard S-224. Minimum clear length shall be 16 in. Minimum clearance shall be 2 in., preferably 2 ½ in.	Appendix D2, 5.2.1	
	Vertical side handholds shall have an uninterrupted span between the upper and lower clearance points.	Appendix D2, 5.2.2	
	Horizontal side handholds below the car deck or adjacent walkway, if applied, shall have foot guards or upward projections not less than 2 in. in height at both ends.	Appendix D2, 5.2.3	
Location	Two vertical handholds, one at either end of the sill step, shall be applied.	Appendix D2, 5.3.1	
	The clear opening between the surfaces of the vertical handholds and their supports shall be not less than 18 in. The width over the outside surfaces of the vertical handholds shall be not more than 30 in.	Appendix D2, 5.3.2	
	The clearance points of the bottom ends of vertical handholds shall be not more than 16 in. above the highest horizontal side handhold. If there are no horizontal handholds, the clearance points shall be not more than 16 in. above the highest sill step tread. The clearance points at the top ends shall be not less than 33 in. above the walking surface of the adjacent walkway.	Appendix D2, 5.3.3	
	Spacing between horizontal side handholds, if applied, shall be not more than 19 in. Spacing from the highest horizontal side handhold to the adjacent walking surface of the walkway, if so equipped, shall be not more than 19 in. If not equipped with an adjacent walkway, spacing from the highest horizontal side handhold to the car deck shall be not more than 19 in.	Appendix D2, 5.3.4	
	If the car is equipped with horizontal side handholds, the outboard clearance points of the handholds shall be not more than 2in. inboard of the inside surface of the outboard vertical leg of the sill step, and the inboard clearance points of the handholds shall be not more than 2 in, outboard of the inside surface of the inboard vertical leg of the sill step.	Appendix D2, 5.3.5	



US Department of Transportation
Federal Railroad Administration

Sample Car Inspection Checklist For: S-2044 Appendix D-2
Safety Appliances for Cars of Well or Spine Construction
with Side Mounted Hand Brakes

OMB No. 2130-0565
F6180.161d 12/15

ITEM	Number - Dimensions - Location - Manner of Application	Appendix Reference	Notes
Manner of Application	<p>Handholds adjacent to the articulated connectors of cars equipped to carry both highway trailers and double-stacked intermodal containers need not extend higher than the top of the adjacent walkways.</p> <p>Side handholds shall be securely fastened.</p>	<p>Appendix D2, 5.3.6</p> <p>Appendix D2, 5.4</p>	
End Handholds	<p>There shall be four end handholds.</p>	<p>Appendix D2, 6.1</p>	
Dimensions	<p>Handholds shall be of steel not less than ¾ in. diameter and shall conform to the requirements of Standard S-224. Minimum clear length shall be 16 in. Minimum clearance shall be 2 in., preferably 2 ½ in.</p>	<p>Appendix D2, 6.2</p>	
Location	<p>The end handholds shall be oriented horizontally, one near each side of each end of the car on the face of the end sill.</p> <p>The clearance points of the outer end of the end handholds shall be not more than 16 in. from the inside surface of the nearest side handhold.</p> <p>The end handholds shall be not more than 45 in. above the top of rail.</p>	<p>Appendix D2, 6.3.1</p> <p>Appendix D2, 6.3.2</p> <p>Appendix D2, 6.3.3</p>	
Manner of Application	<p>End handholds shall be securely fastened.</p>	<p>Appendix D2, 6.4</p>	
Clearance at End of Car	<p>No part of the car above the end sill more than 30 in. from the longitudinal centerline of the car, except the hand brake wheel, hand brake shaft, bell crank, sheave wheel, end platform or horizontal end handholds, shall extend beyond the striker or end of the center sill with the draft gear or cushioning device (if used) at full buff. No other part of the car end or fixtures on the end above the end sill and less than 84 in. above the car deck or walking surface of the end walkway, if the car is so equipped, other than the exceptions herein noted, shall extend beyond the outer face of the striker or end of the center sill.</p>	<p>Appendix D2, 7.0</p>	
Walkways Number	<p>Cars not having full-width flooring at ends of the car adjacent to a coupler shall be equipped with transverse walkways at those locations.</p> <p>Cars having full-width metal flooring and no transverse walkways adjacent to the couplers shall be provided with an antiskid surface on the flooring.</p>	<p>Appendix D2, 8.1.1.</p> <p>Appendix D2, 8.1.2</p>	



US Department of Transportation
Federal Railroad Administration

Sample Car Inspection Checklist For: S-2044 Appendix D-2
Safety Appliances for Cars of Well or Spine Construction
with Side Mounted Hand Brakes

OMB No. 2130-0565
F6180.161d 12/15

ITEM	Number - Dimensions - Location - Manner of Application	Appendix Reference	Notes
Ground Access	Transverse walkways at ends of the car adjacent to a coupler shall provide access to the ground at both sides of the car. When transverse walkways are applied to the carbodies at both ends of articulated or drawbar connections, access to the ground shall be provided on both sides of the car from the left of the connection as viewed from the side of the car.	Appendix D2, 8.5	
Uncoupling Devices	There shall be a minimum of two uncoupling devices that conform to the requirements of the base standard.	Appendix D2, 9.0	
	Uncoupling devices and their application shall conform to MSRP Section S, Part III, Standard S-129, S-131, S-133, or S-134; or Specification M-961.	S-2044 6.1 (Base Standard)	
	One uncoupling device shall be applied at the left side of the B end of the car (BL corner) and one at the right side of the A end of the car (AR corner).	S-2044 6.2	
	Under all operating conditions, the outside surface of the uncoupling device handles shall be not more than 12 in. closer to the car center than the inside surface of the adjacent side handholds.	S-2044 6.3	
	There shall be not less than 2 in. clearance, preferably 2 ½ in., around the uncoupling device handles for a length not less than the lowest 4 in. of straight handles and not less than 4 in. in the grip portion of handles having clearly defined grip portions. The lower ends of the handles shall be not less than 12 in. nor more than 15 in. below the top surface of the uncoupling device at the device support and not less than 15 in. above the top of rail.	S-2044 6.4	
	Uncoupling device mounting brackets shall be securely fastened to the car with fasteners not less than 5/8 in. diameter.	S-2044 6.5	
Stenciling	Car initial, numbers and built date stenciled on the car.	49 CFR Part 215.301	
Reflectorization.	Reflectorization must meet all requirements. Attached Drawing	49 CFR Part 224	
Coupler Height	Verify coupler height 31½ inch minimum, 34½ inch maximum.	49 CFR Part 231.31(a)(1)	
Power Brakes	Except for cars equipped with nominal 12-inch stroke (8 ½ and 10-inch diameters) brake cylinders, all cars shall have a legible decal, stencil, or sticker affixed to the car or shall be equipped with a badge plate displaying the permissible brake cylinder piston travel range for the car at Class I brake tests and the length at which the piston travel renders the brake ineffective, if different from Class I brake test limits. The decal, stencil, sticker, or badge plate shall be located so that it may be easily read and understood by a person positioned safely beside the car.	49 CFR Part 232. 103	



US Department of Transportation
Federal Railroad Administration

Sample Car Inspection Checklist For: S-2044 Appendix D-2
Safety Appliances for Cars of Well or Spine Construction
with Side Mounted Hand Brakes

OMB No. 2130-0565
F6180.161d 12/15

ITEM	Number - Dimensions - Location - Manner of Application	Appendix Reference	Notes
SCT	<p>All equipment ordered on or after August 1, 2002, or placed in service for the first time on or after April 1, 2004, shall have train brake systems designed so that an inspector can observe from a safe position either the piston travel, an accurate indicator which shows piston travel, or any other means by which the brake system is actuated. The design shall not require the inspector to place himself or herself on, under, or between components of the equipment to observe brake actuation or release.</p> <p>A single car air brake test shall be performed on each new car prior to placing or using the car in revenue service.</p>	49 CFR Part 232.305	

Miscellaneous Check for any sharp or protruding objects or areas on the equipment that may create a safety concern or personal injury.

 Check for potential pinch points at all safety appliance arrangements.

Digital Photos General Arrangement Photo Sheet (six photos minimum, A & B ends, each corner at 45 degree angle)

 Deviation Photo Sheet ~As many photos as necessary to fully depict, document and illustrate deviations of S-2044 Appendix D2 or CFR Parts (e.g. 215, 224 & 232)

Public reporting burden for this information collection is estimated to average 60 minutes per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. According to the Paperwork Reduction Act of 1995, a federal agency may not conduct or sponsor, and a person is not required to respond to, nor shall a person be subject to a penalty for failure to comply with, a collection of information unless it displays a currently valid OMB control number. The valid OMB control number for this information collection is **2130-0565**. All responses to this collection of information are mandatory.