

ACCESSION
NUMBER

9200266

DATA DOCUMENTATION FORM

A01617

NOAA FORM 24-13
(2-85)

U.S. DEPARTMENT OF COMMERCE
NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION
NATIONAL OCEANOGRAPHIC DATA CENTER
RECORDS SECTION
WASHINGTON, DC 20235

FORM APPROVED
O.M.B. No. 0648-0024
EXPIRES 2/29/87

(While you are not required to use this form, it is the most desirable mechanism for providing the required ancillary information enabling the NODC and users to obtain the greatest benefit from your data.)

This form should accompany all data submissions to NODC. Section A, Originator Identification, must be completed when the data are submitted. It is highly desirable for NODC to also receive the remaining pertinent information at that time. This may be most easily accomplished by attaching reports, publications, or manuscripts which are readily available describing data collection, analysis, and format specifics. Readable, handwritten submissions are acceptable in all cases. All data shipments should be sent to the above address.

A. ORIGINATOR IDENTIFICATION

THIS SECTION MUST BE COMPLETED BY DONOR FOR ALL DATA TRANSMITTALS



1. NAME AND ADDRESS OF INSTITUTION, LABORATORY, OR ACTIVITY WITH WHICH SUBMITTED DATA ARE ASSOCIATED			
NOAA/PMEL/R/E/PM Bin C15700/Bldg. 3 7600 Sand Point Way N.E. Seattle, WA 98115-0070			
2. EXPEDITION, PROJECT, OR PROGRAM DURING WHICH DATA WERE COLLECTED		3. CRUISE NUMBER(S) USED BY ORIGINATOR TO IDENTIFY DATA IN THIS SHIPMENT	
EPOCS		ARRMS 20 & 21	
4. PLATFORM NAME(S)	5. PLATFORM TYPE(S) (E.G., SHIP, BUOY, ETC.)	6. PLATFORM AND OPERATOR NATIONALITY(IES)	7. DATES
EC 75, 76, 77, 78 CC 3, 4	Buoy	PLATFORM OPERATOR	FROM: MO, DAY, YR TO: MO, DAY, YR
		US US	4/16/89 5/4/90
8. ARE DATA PROPRIETARY? <input checked="" type="checkbox"/> NO <input type="checkbox"/> YES IF YES, WHEN CAN THEY BE RELEASED FOR GENERAL USE? YEAR ___ MONTH ___		11. PLEASE DARKEN ALL MARSDEN SQUARES IN WHICH ANY DATA CONTAINED IN YOUR SUBMISSION WERE COLLECTED.	
9. ARE DATA DECLARED NATIONAL PROGRAM (DNP)? (I.E., SHOULD THEY BE INCLUDED IN WORLD DATA CENTERS HOLDINGS FOR INTERNATIONAL EXCHANGE?) <input type="checkbox"/> NO <input checked="" type="checkbox"/> YES <input type="checkbox"/> PART (SPECIFY BELOW)		GENERAL AREA	
10. PERSON TO WHOM INQUIRIES CONCERNING DATA SHOULD BE ADDRESSED WITH TELEPHONE NUMBER (AND ADDRESS IF OTHER THAN IN ITEM-1) PAUL FREITAS 206-526-6727			

B. SCIENTIFIC CONTENT

NAME OF DATA FIELD	REPORTING UNITS OR CODE	METHODS OF OBSERVATION AND INSTRUMENTS USED (SPECIFY TYPE AND MODEL)	ANALYTICAL METHODS (INCLUDING MODIFICATIONS) AND LABORATORY PROCEDURES	DATA PROCESSING TECHNIQUES WITH FILTERING AND AVERAGING
Wind Vector	m/s	VANR	Modified EG&G VACM with Climat cup anemometer	Hourly vector average
Wind Vector	m/s	AMP	FMEL manufactured with RM Young propeller/vane	2-hour vector average
Current Vector	cm/s	EG&G VACM model 610	Savonius rotor and vane	Hourly vector average
Current Vector	cm/s	EG&G VMCM model 630	Orthogonal rotors	1 or 2-hour vector average
Air Temperature	degrees C	VANR or AMP	YSI thermistor	1 or 2-hour scalar average
Sea Surface Temp.	degrees C	VANR or AMP	YSI thermistor	1 or 2-hour scalar average
Water Temperature	degrees C	VACM or VMCM	YSI thermistor	1 or 2-hour scalar average

C. DATA FORMAT

COMPLETE THIS SECTION FOR PUNCHED CARDS OR TAPE, MAGNETIC TAPE, OR DISC SUBMISSIONS.

**1. LIST RECORD TYPES CONTAINED IN THE TRANSMITTAL OF YOUR FILE
GIVE METHOD OF IDENTIFYING EACH RECORD TYPE**

Header record: 1st record of each file. Contains array name (8 bytes), buoy name (4 bytes), instrument s/n (4 bytes), instrument code (2 bytes), minutes between records (6 bytes), instrument depth in meters (6 bytes).

Data records: All subsequent records. Time, date, 1 to 6 data values, record number.

2. GIVE BRIEF DESCRIPTION OF FILE ORGANIZATION

67 files. One per instrument.
Max block size = 3000 bytes
Record size = 60 bytes

3. ATTRIBUTES AS EXPRESSED IN PL-1 ALGOL COBOL
 FORTRAN _____ LANGUAGE

4. RESPONSIBLE COMPUTER SPECIALIST:

NAME AND PHONE NUMBER PAUL FREITAS
ADDRESS SEE A1

COMPLETE THIS SECTION IF DATA ARE ON MAGNETIC TAPE

<p>5. RECORDING MODE</p> <p><input type="checkbox"/> BCD <input type="checkbox"/> BINARY</p> <p><input checked="" type="checkbox"/> ASCII <input type="checkbox"/> EBCDIC</p> <p><input type="checkbox"/> _____</p>	<p>9. LENGTH OF INTER-RECORD GAP (IF KNOWN) <input type="checkbox"/> 3/4 INCH <input type="checkbox"/> _____</p>
<p>6. NUMBER OF TRACKS (CHANNELS)</p> <p><input type="checkbox"/> SEVEN</p> <p><input checked="" type="checkbox"/> NINE</p> <p><input type="checkbox"/> _____</p>	<p>10. END OF FILE MARK</p> <p><input type="checkbox"/> OCTAL 17</p> <p><input type="checkbox"/> _____</p>
<p>7. PARITY</p> <p><input checked="" type="checkbox"/> ODD</p> <p><input type="checkbox"/> EVEN</p>	<p>11. PASTE-ON-PAPER LABEL DESCRIPTION (INCLUDE ORIGINATOR NAME AND SOME LAY SPECIFICATIONS OF DATA TYPE)</p> <p>EPOCS current meter, wind & sea temp. data sets. 4/16/89 to 5/14/90 Tape specs. - 9 track, ASCII, 6250 bpi, odd parity, block length = 3000</p>
<p>8. DENSITY</p> <p><input type="checkbox"/> 200 BPI <input type="checkbox"/> 1600 BPI</p> <p><input type="checkbox"/> 556 BPI</p> <p><input type="checkbox"/> 800 BPI</p> <p><input checked="" type="checkbox"/> 6250</p>	<p>12. PHYSICAL BLC</p> <p style="text-align: center;">3000</p> <p>13. LENGTH OF BYTES IN BITS</p> <p style="text-align: center;">8</p>

D. INSTRUMENT CALIBRATION

This calibration information will be utilized by NOAA's National Oceanographic Instrumentation Center in their efforts to develop calibration standards for voluntary acceptance by the oceanographic community. Identify the instruments used by your organization to obtain the scientific content of the DDF (i.e., STD, temperature and pressure sensors, salinometers, oxygen meters, velocimeters, etc.) and furnish the calibration data requested by completing and/or checking ("✓") the appropriate spaces. Add the interval time (i.e., 3 months, 6 months, 9 months, etc.) if the fixed interval calibration cycle is checked.

INSTRUMENT TYPE (MFR., MODEL NO.)	DATE OF LAST CALIBRATION	INSTRUMENT WAS CALIBRATED BY		CHECK ONE: INSTRUMENT IS CALIBRATED					INSTRUMENT IS NOT CALI- BRATED (✓)
		YOUR ORGANIZATION (✓)	OTHER ORGANIZATION (GIVE NAME)	AT FIXED INTERVALS (✓)	BEFORE OR AFTER USE (✓)	BEFORE AND AFTER USE (✓)	ONLY AFTER REPAIR (✓)	ONLY WHEN NEW (✓)	
EG&G VMCM 610 CURRENT ROTOR	1972		WHOI						✓
VMCM TEMP	1990	✓	NWRCC			✓			
SEA DATA TEMP	"	✓	"			✓			
EG&G VMCM 630			EG&G						✓
VMCM TEMP	1990	✓	NWRCC			✓			