

§ 39.6009

46 CFR Ch. I (10-1-16 Edition)

Chemical compatibility must be determined in accordance with the procedures contained in 46 CFR part 150, part A.

TABLE 1—MINIMUM OPEN AREA FOR BARGE CLEANING HATCHES

Air flow (CFM) (cubic feet/minute)	Air flow (CFS) (cubic feet/ second)	Open area (square inches)	Diameter opening (inches)	Square opening (inches)
500	8.3	10.7	3.7	3.3
600	10.0	12.8	4.0	3.6
700	11.7	15.0	4.4	3.9
800	13.3	17.1	4.7	4.1
900	15.0	19.3	5.0	4.4
1000	16.7	21.4	5.2	4.6
1100	18.3	23.6	5.5	4.9
1200	20.0	25.7	5.7	5.1
1300	21.7	27.8	6.0	5.3
1400	23.3	30.0	6.2	5.5
1500	25.0	32.1	6.4	5.7
1600	26.7	34.3	6.6	5.9
1700	28.3	36.4	6.8	6.0
1800	30.0	38.5	7.0	6.2
1900	31.7	40.7	7.2	6.4
2000	33.3	42.8	7.4	6.5
2100	35.0	45.0	7.6	6.7
2200	36.7	47.1	7.7	6.9
2300	38.3	49.3	7.9	7.0
2400	40.0	51.4	8.1	7.2
2500	41.7	53.5	8.3	7.3
2600	43.3	55.7	8.4	7.5
2700	45.0	57.8	8.6	7.6
2800	46.7	60.0	8.7	7.7
2900	48.3	62.1	8.9	7.9
3000	50.0	64.2	9.0	8.0
3100	51.7	66.4	9.2	8.1
3200	53.3	68.5	9.3	8.3
3300	55.0	70.7	9.5	8.4
3400	56.7	72.8	9.6	8.5
3500	58.3	75.0	9.8	8.7
3600	60.0	77.1	9.9	8.8
3700	61.7	79.2	10.0	8.9
3800	63.3	81.4	10.2	9.0
3900	65.0	83.5	10.3	9.1
4000	66.7	85.7	10.4	9.3

§ 39.6009 Barge person in charge: Designation and qualifications—B/ALL.

The designation and qualification requirements contained in 33 CFR 155.700

and 33 CFR 155.710(a)(2) apply to the barge person in charge.

PART 40 [RESERVED]