



Department of Defense Integrated Data Dictionary (IDD)

May 2016

Version 6.0 Amendment 1

DIN: DFBA-STD-IDD-15-001

May 2016

UNCLASSIFIED - DISTRIBUTION UNLIMITED

Revision History

Version	Date	Document Status	Comments
Draft 0.0	2-12-15	Rough Draft	Contains Type 1, Type 2 and Type 11
Draft 0.1	3-9-15	Draft	Added separate code and Type 10 and 20 and moved to a separate Appendix A for Code lists
Draft 0.2	5-4-14	Working Draft	Continued to add types – Still performing clean up and adding types.
Draft 0.3	5-21-15	Working Draft	Completed addition of all types to be included in this version (Types: 1, 2, 9, 10, 11, 13, 14, 15, 17, 18, 20, 21, 98, 99). Performed cursory formatting revision.
Draft 0.4	6-5-15	Working Draft	Refined formatting and performed error fixes.
Draft 0.9	8-10-15	Draft Release	Review and revision of all Record Types and incorporation of comments from the enterprise.
Draft 1.0	9-21-15	Final Draft	Incorporation of comments from Army and Joint Staffing
Amd 1	5-26-16	Amendment 1	Formatting revision and full xml incorporation.

Table of Contents

1.0	Overview	iv
2.0	Intended Audience	iv
3.0	IDD Organization and Structure	v
3.1	Field Status States	v
3.2	IDD Subject Areas	vi
3.3	IDD Data Element Characteristics	viii
3.4	New IDD Conventions	x
4.0	Authoritative Sources	xi
5.0	Date and Time Fields	xiii
6.0	Contact Information	xiv
7.0	IDD Element Definitions by Type	xv
	Type-1: Transaction Information Record.....	001
	Type-2: User-Defined Descriptive Text Record.....	019
	Type-9: Minutiae Data Record.....	315
	Type-10: Facial, Other Body Part and SMT Image Record.....	488
	Type-11: Forensic and Investigatory Voice Record.....	579
	Type-13: Variable- Resolution Latent Image Record.....	678
	Type-14: Variable-Resolution Fingerprint Image Record.....	724
	Type-15: Variable-Resolution Palmprint Image Record.....	778
	Type-17: Iris Image Record.....	820
	Type-18: DNA Record.....	873
	Type-20: Source Representation Record.....	934
	Type-21: Associated Context Record.....	974
	Type-98: Information Assurance Record.....	1004
	Type-99: CBEFF Biometric Data Record.....	1012

Table of Figures

Figure 1: Data Element Statuses	v
Figure 2: IDD Data Element Transition Path	vi
Figure 3: ANSI/NIST-ITL Record Types	vi
Figure 4: IDD Data Element Characteristics	viii

1.0 Overview

The Department of Defense Integrated Data Dictionary (IDD) is one of the Biometrics Data Products published by the Defense Forensics and Biometrics Agency (DFBA). The IDD defines the data standards that are to be used when data is exchanged across DoD Biometric Systems, and is the authoritative source for DoD biometrics data elements. As Part of DFBA's mission to lead, consolidate, and coordinate forensics and biometrics activities, it requires definition and promotion of transmission data standards for us by the DoD Biometrics Community.

The IDD is one of the key components of the Electronic Biometrics Transmission Specification (EBTS) Information Exchange Package (IEP), and serves the following functions: identifies the high-value data exchanged across DoD biometric systems (both current and future), establishes authoritative definitions for that data, and documents standards for data in order to ensure accurate and efficient data flow.

New features to this version of the IDD include:

- New field definition structures facilitate the construction and exchange of data in either extensible mark-up language (XML) or binary format.
- Separation of field code lists into an Appendix A to provide adequate information to clarify encoding.

2.0 Intended Audience

The intended audience for the Integrated Data Dictionary spans across the DoD Biometrics Community, other United States Government (USG) agencies, and Foreign Partners with a need to understand DoD EBTS transactions. This includes, but is not limited to, those responsible for biometric system design and development.

3.0 IDD Organization and Structure

3.1 Field Status States

As Standards and data usages evolve over time, the IDD must reflect the transition and retirement of certain data elements. The IDD does this by tracking the lifecycle of the data elements through the states as shown in Figure 1 below. The “NEW” prefix will be added to the Status to indicate that it is an element that was added as a result of the EBTS v4.0 release (i.e. “NEW – Active”).

State	Description
Active	Currently viable and fully usable data element.
Deprecated	Element is still usable in current implementations, but it should not be used going forward. It will gradually be phased out with a new element(s) that incorporates the functionality of the deprecated element. The IDD will clearly mark if an element is deprecated. The IDD will also provide the superseding element(s) and any qualifying condition.
Sunset	Used for alerting the user community that an element may be retired in the future. IDD will provide indicator to clearly mark if an element is in the sunset state and the reason why.
Retired	Used to alert the user community that the data element shall not be used for current and future applications. The IDD will clearly mark if an element is retired.
Emerging	An element that can be considered for future capability. It has not yet been approved by FBSWG for use and can be subject to change.

Figure 1: Data Element Statuses

Figure 2 illustrates how an IDD data element transitions from one state to another. For example, a DoD data element which is Emerging may become Active after approval of the Forensics and Biometrics Standards Working Group and adoption by the biometric systems in use.




Figure 2: IDD Data Element Transition Path

3.2 IDD Subject Areas

The IDD is divided into sections based on the subject area in order to provide the context in which the data elements are used. The IDD contains data elements categorized within the subject areas that are listed in the table below.

Record	Subject Area	Description
Type-1	Transaction Information Record	Contains useful/required information items regarding the use or purpose of the transaction.
Type-2	User-Defined Descriptive Text Record	Contains contextual/situational/processing information (i.e. identification, biographic, and descriptive, information) regarding the subject, the encounter, response, sample and the transaction itself.
Type-4	High-Resolution Grayscale Fingerprint Image (Deprecated)	The use of this logical record for the binary Fingerprint image has been deprecated by Type-14 Variable-Resolution Fingerprint Image Record.

Figure 3: ANSI/NIST-ITL Record Types

Record	Subject Area	Description
Type-7	Latent Image Binary Latent Image (Deprecated)	The use of this logical record for the binary Latent Fingerprint image has been deprecated by Type-13 Variable-Resolution Latent Image Record.
Type-9	Minutiae Data Record (Common)	Includes fields 9.001 – 9.004. These common data elements shall be included for any minutiae features within a Type-9 record. Also includes fields 9.901- 9.904 for the universal latent workstation annotations and workstation identifiers.
Type-9	Minutiae Data Record (Standard Features – Legacy)	Includes fields 9.005 through 9.012. These fields are marked as legacy in ANSI/NIST ITL 1-2011.
Type-9	Minutiae Data Record (IAFIS Features)	Includes fields 9.013 – 9.030. Used for exchanging geometric and topological minutiae templates and information encoded from a finger or palm based on the FBI IAFIS standard.
Type-9	Minutiae Data Record (INCITS M1-378 Features)	Includes fields 9.126 – 9.150. Used for exchanging geometric and topological minutiae templates and information encoded from a finger or palm based on the ANSI/INCITS standard.
Type-9	Extended Feature Set (EFS)	Includes fields 9.300 – 9.399. The EFS defines additional types of fingerprint features, which allows Latent Print Examiners to document latent prints in much greater detail. These features are standardized to enhance interoperability between the various federal, state, and local agencies.
Type-10	Facial, Other Body Part and SMT Image Record	Used for exchanging facial, other body parts and image data from scars, marks, and tattoos (SMT) with textual information.
Type-11	Forensic and Investigatory Voice	Focused upon the analysis of voice signals for forensic and investigatory purposes. This type is new in EBTS 4.0.
Type-13	Variable Resolution Latent Image Record	Used for exchanging latent fingerprint or palmprint image data with textual information.
Type-14	Variable Resolution Fingerprint Image	Used for exchanging variable-resolution fingerprint image data, segmented flat fingerprint data, or major case print data with textual information.
Type-15	Variable-Resolution Palm Print Image	Used for exchanging variable-resolution palm print image data with textual information.
Type-16	Interim Support for Iris Image (Deprecated)	Used as an interim support for Iris Image for DoD EBTS 1.2 with ANSI/NIST ITL 1-2000. The use of this logical record for Iris Image has been deprecated by Type-17 Iris Image.
Type-17	Iris Image	Used for exchanging iris image data.
Type-18	DNA Record	Used for exchange of DNA data.

Figure 3: ANSI/NIST-ITL Record Types (Cont.)

Record	Subject Area	Description
Type-20	Source Representation Record	The source representation(s) from which other Record Types were derived. Examples are an image of multiple latent prints, of which one or more is of interest. Those would be segmented and prepared for sending in a Type-13 record.
Type-21	Associated Context Record	Contains an associated context record. This information does NOT contain information used to derive biometric information contained in other records. Record Type-20 serves that function. Record Type-21 may be used to convey contextual information, such as an image of the area where latent fingerprints were captured.
Type-98	Information Assurance Record	Contain security information that assures the authenticity and/or integrity of the transaction.
Type-99	CBEFF Biometric Data Record	Common Biometric Exchange Formats Framework (CBEFF). Used for exchanging biometric data not supported by other ANSI/NIST ITL logical record types.

Figure 3: ANSI/NIST-ITL Record Types (Cont.)

3.3 IDD Data Element Characteristics

The following figure lists the data element characteristics and describes the types of information represented by those characteristics.

Name	Description
Field ID	The Field ID number assigned by the transmission specifications (DoD EBTS or FBI EBTS) or Application Profile or ANSI/NIST ITL standard.
Element Name	Name of the data element containing the Category and Subcategory names. The element name is intended to be human readable.
Mnemonic	The Mnemonic is an abbreviated Element name which is assigned by the transmission specifications (DoD EBTS or FBI EBTS) or Application Profile or ANSI/NIST ITL standard.
Optional	Consists of Mandatory (M), Optional (O), and Dependent (D) codes which indicate the normal state of the field or component. An arrow indicator may be present to indicate hierarchical dependency.
Status	Indicates the current lifecycle status of the field (i.e. emerging, retired, active, etc.)

Figure 4: IDD Data Element Characteristics

Name	Description		
Description	Textual description or definition for the dictionary element.		
Field Min/Max	Defines the number of characters allowed in the data element. For example, for some date fields the format will be YYYYMMDD, so therefore both the Field Min and Field Max will be equal to 8.		
Occur Min/Max	The occurrence minimum and maximum indicate the number of times a data element is allowed to occur within the transaction.		
Char Types	A	Alphabetic	26 English letters (both upper and lower case) within the 7-bit ASCII character set.
	AN	Alphanumeric	Alphabetic and numeric 1 2 3 4 5 6 7 8 9 0 within the 7-bit ASCII character set.
	ANS	Alphanumeric and special characters	Alphanumeric character set plus those special characters which are specifically stated in the description of the data, within the 7-bit ASCII character set.
	AS	Alphanumeric and special characters	Alphabetic character set plus those special characters which are specifically stated in the description of the data, within the 7-bit ASCII character set.
	B	Binary	See the ANSI/NIST-ITL for rules regarding binary encoding for traditional encoding (See Annex B: Traditional encoding) or Base64 for XML (See Annex C: NIEM-conformant encoding rules).
	Base64	Base-64	Encoded (exclusively)
	H	Hexadecimal	Representation: 0 1 2 3 4 5 6 7 8 9 A B C D E F
	N	Numeric	1 2 3 4 5 6 7 8 9 0
	NS	Numeric	Numeric character set plus those special characters which are specifically stated in the description of the data, within the 7-bit ASCII character set.
	U	Unicode	Characters available in UTF-8: Latin and extended Latin characters like ü, Ñ, ç, Þ, ß, †, ð, and/or special characters like £, €, ™, +, * and ‡, and/or non-Latin characters like □, ◦, , Δ, ॐ ,ж , ρ , 旬, ت , ν , and の.
Special Chars	Allowable characters that are neither alphanumeric nor binary, such as punctuation characters. For example: Period, Comma, Minus, Plus, Hyphen. 7-bit ASCII characters shall be used for special characters when Character Type is either AS, ANS or NS. UTF-8 character encoding shall be used for special characters when Character type is U.		

Figure 4: IDD Data Element Characteristics (Cont.)

Name	Description
Format	The Format field defines the data format for the element (e.g. YYYYMMDD for date).
Value Constraints	Identifies the value constraints that shall be applied to the content within the element (e.g. specific codes from the look up codes list, integer value of certain range, etc.).
Code List	Name of the code list located in Appendix A of this document containing the allowable codes for the data element.
Source	The authoritative source the dictionary element is completely or partially extracted or derived from.
XML Levels	Contains the default namespace prefix and XML field name. The level indicates the elements hierarchical appearance in the XML document.
Cardinality	Indicates the Minimum and maximum numbers of allowed occurrences for the referenced XML element. (1...1)
DoD EBTS vX	Indicator that the dictionary element was referenced by the DoD EBTS in v1.2, 2.0, 3.0, or 4.0.

Figure 4: IDD Data Element Characteristics (Cont.)

3.4 New IDD Conventions

There are several conventions used in the construction of the document that were added to make the document more technically viable with the addition of the Extensible Markup Language (XML).

Repeating Subfields Designator

In the ANSI (American National Standards Institute) NIST (National Institute of Standards and Technology) 1-2011: Update 2013 field guidance table a new field was introduced to designate repeating subfields of information. The repeating subfield ID and Mnemonic will be indicated with and _0 designator.

Hierarchical Arrows

New in the ANSI NIST 1-2011: Update 2013 field tables are hierarchical dependency arrow indicators located in the Optional field. The DoD EBTS IDD page construct has also chosen to include this new morphological field construct.

Traditional vs XML Encoding Designation

Where the content or structure of a field or information item would differ between Traditional (Binary) and XML encodings, they are differentiated by a “T =” or “X =” preceding the information.

XML Levels

Fields to contain XML level 1 through 4 have been added to indicate the names of the hierarchy of XML components and their cardinality.

4.0 Authoritative Sources

The “Source” characteristic within the dictionary element indicates the authoritative source the element is either completely or partially extracted or derived from. The following is a list of primary authoritative sources used to develop the Integrated Data Dictionary:

- **[ITL 1-2011]:** ANSI/NIST-ITL 1-2011: Update 2013, “American National Standard for Information Systems – Data Format for the Interchange of Fingerprint, Facial, & Other Biometric Information” (NIST Special Publication 500-290 Rev 1 2013).
- **[W3C XML Schema Part 1]:** XML Schema Part 1: Structures Second Edition, W3C Recommendation 28 October 2004.
- **[W3C XML Schema Part 1]:** XML Schema Part 2: Datatypes Second Edition, W3C Recommendation 28 October 2004.
- **[NIEM Conform]:** National Information Exchange Model Conformance Specification Version 3.0, NIEM Technical Architecture Committee (NTAC), August 15, 2014.

- **[NIEM NDR 3.0]:** *NIEM Naming and Design Rules*, Version 3.0, NIEM Technical Architecture Committee (NTAC), 31 July 2014.
- **[NIEM-EM]:** National Information Exchange Model — Model Package Description Specification, NIEM Technical Architecture Committee (NTAC), Version 3.0.1, April 27, 2015.
- **[NGI 10.0]:** Electronic Biometric Transmission Specification (EBTS) NGI-DOC-01078-10.0, Federal Bureau of Investigation, Criminal Justice Information Services Division, July 2, 2013.
- **[NGI TOU 10.0.3]:** Electronic Biometric Transmission Specification (EBTS) Technical and Operational Update (TOU) 10.0.3, FBI CJIS/NGI EBTS TOU 10.0.3, Federal Bureau of Investigation, Criminal Justice Information Services Division, September 30, 2014.
- **[GENC 2.0]:** NGA Standardization Document Geopolitical Entities, Names, and Codes (GENC) Standard 2.0, National Center For Geospatial Intelligence Standards, March 31, 2014.
- **[ISO 639-2]:** Codes for the Representation of Names of Languages Part 2: Alpha-3 Code (ISO 639-2 Language Codes), Technical Committees ISO/TC 37, Terminology and other language and content resources, Subcommittee SC 2, Layout of vocabularies and ISO/TC 46, Information and documentation, Subcommittee SC 4, Computer applications in information and documentation, April 8, 2011.
- **[XML 1]:** Extensible Markup Language (XML) 1.0, Second Edition. World Wide Web Consortium (W3C), 6 October 2000.
- **[NIST Schema 2013] ANSI/NIST-ITL 1-2011 Update: 2013 XML Schema, June 28, 2015.** http://biometrics.nist.gov/cs_links/standard/ansi_2015/schema-MRT/ANSI-NIST-ITL-2013_FINAL.zip .

5.0 Date and Time Fields

Date fields must be valid dates and in accordance with the requirements stated below. In general, the format for date fields are follows:

- A date is shown as an 8-digit numeric field of the format YYYYMMDD (YYYY- MM-DD for XML encoding), where:
 - YYYY (Year) must be 0000 to 9999
 - MM (Month) must be 01 to 12
 - DD (Day) must be 01 to the limit defined by the month and year (e.g., DD may be 29 for MM = 02 in leap years).

Gregorian calendar is default if not specified. For example 19921201 represents December 1, 1992.

Date-Time fields must be valid dates and time fields in coordinated universal time format (UTC), also known as “Zulu Time.” UTC is reflected as YYYYMMDDHHMMSSZ in Traditional Encoding and YYYY-MM-DDTHH:MM:SSZ in XML Encoding. The “Z” at the end of the date-time string indicates the time zone, which is always set to UTC time. The format for the date is the same as above. The format for time is as follows:

- HH (Hour) must be 00 to 23
- MM (Minute) must be 00 to 59
- SS (Second) must be 00 to 59

For example 19921201103015Z represents December 1, 1992 at 10:30:15AM.

Since dates and time find a variety of uses in EBTS transactions, each use may have specific format restrictions or special edits. For specific format restrictions or special edits, see the individual date field entries for detail.

6.0 Contact Information

Mr. Stevenson Cuffee

DFBA Standards Branch Manager

Desk: +1 703-571-0406

Mail: stevenson.cuffee.civ@mail.mil

Mr. Brian Harrig

DFBA Standards Branch Lead

Desk: +1 703-571-0415

Mail: brian.w.harrig.ctr@mail.mil

Mr. Adam Dale

DFBA Forensics Standards Analyst

Desk: +1 703-571-0424

Mail: adam.j.dale.ctr@mail.mil

Mr. Kuldip Acharya

DFBA Biometrics Standards Analyst

Desk: +1 703-571-0254

Mail: kuldip.acharya.ctr@mail.mil

Ms. Miriam Boussouf

DFBA Biometrics Standards Analyst

Desk: +1 703-571-0425

Mail: miriam.h.boussouf.ctr@mail.mil

7.0 IDD Element Definitions by Type

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

1.001

Record Header

Mnemonic	LEN	Conditionality	M
		Status	Active
Description	The record header appears as the first field (xx.001) in each Record Type. It contains information particular to the encoding format chosen, in order to enable proper reading of the record. In Traditional encoding, this field contains the record length in bytes (including all information separators). In NIEM-conformant XML encoding, this field contains the RecordCategoryCode, which is the numeric representation of the Record Type.		
Field Min	Encoding Specific	Occur Min	1
Field Max	Encoding Specific	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	Depending Upon Encoding
Code List			
Source	ANSI/NIST ITL 1-2011 (Type-1)		
XML Level 1		Cardinality	
XML Level 2	biom:RecordCategoryCode	Cardinality	1..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

1.002

Version Number

Mnemonic	VER	Conditionality	M
		Status	Active
Description	This mandatory four-character ASCII value shall be used to specify the current version number of the standard implemented by the software or system creating the transaction. The format of this field shall consist of four numeric characters. The first two characters shall specify the major version number. The last two characters shall be used to specify the minor revision number. The 2011 version of the standard without any of the record types or fields introduced for the 2013 Update has the entry "0500". The 2013 Update uses "0501". In XML, nist-itl:TransactionMajorVersionValue is 5, and nist-itl:TransactionMinorVersionValue is 1.		
Field Min	T = 4 ; X = 3	Occur Min	1
Field Max	4	Occur Max	1
Char Types	N	Special Chars	None
Format	####	Constraints	VER = 0500 or 0501
Code List			
Source	ANSI/NIST ITL 1-2011 (Type-1)		
XML Level 1	biom:Transaction	Cardinality	
XML Level 2	biom:TransactionMajorVersionValue or biom_2:TransactionMinorVersionValue	Cardinality	XML
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

1.003

Transaction Content

Mnemonic	CNT			Conditionality	M
				Status	Active
Description	This mandatory field shall list and identify each of the records in the transaction by record type and its IDC value. It also specifies the order in which the remaining records shall appear in the file. It shall consist of two or more subfields. The first subfield shall relate to this Type-1 record. Each of the remaining subfields corresponds to a single Type-2 through Type-99 record contained in the transaction.				
Field Min	n/a	Occur Min	1		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-1)				
XML Level 1	biom:Transaction			Cardinality	
XML Level 2	biom:TransactionContentSummary			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

1.003_0

Transaction Content

Subfield: Single set of information items

Mnemonic	CNT_0			Conditionality	M
				Status	New-Active
Description	This field indicates repeating subsets of the Transaction Content field.				
Field Min	n/a	Occur Min	1		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format		Constraints	n/a		
Code List					
Source	ANSI/NIST 2011: Update 2013				
XML Level 1	biom:Transaction			Cardinality	
XML Level 2	biom:TransactionContentSummary			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

1.003_1a

Transaction Content

First Record Category Code

Mnemonic	FRC	Conditionality	M
		Status	Active
Description	The first information item (record category code / REC) within the first subfield shall be "1". This indicates that the first record in the transaction is a Type-1 record consisting of header information.		
Field Min	1	Occur Min	1
Field Max	1	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	FRC = 1 integer
Code List			
Source	ANSI/NIST ITL 1-2011 (Type-1)		
XML Level 1	biom:Transaction	Cardinality	
XML Level 2	biom:TransactionContentSummary	Cardinality	1..1
XML Level 3	biom:ContentFirstRecordCategoryCode	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

1.003_1b

Transaction Content

Content Record Count

Mnemonic	CRC	Conditionality	M
		Status	Active
Description	The second information item of the first subfield of Field 1.003 File Content shall be the sum of the Type-2 through Type-99 logical records contained in this file. This number is also equal to the count of the remaining subfields of Field 1.003. The maximum value for CRC is 999.		
Field Min	1	Occur Min	1
Field Max	3	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	CRC = count of record types 2 through 99; min = 1; max = 999; positive integer
Code List			
Source	ANSI/NIST ITL 1-2011 (Type-1)		
XML Level 1	biom:Transaction	Cardinality	
XML Level 2	biom:TransactionContentSummary	Cardinality	1..1
XML Level 3	biom:ContentRecordQuantity	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

1.003_2

Transaction Content

Content Record Summary

Mnemonic	REC	Conditionality	M
		Status	New-Active
Description	This record reflects a subsets of the Content Record Summary.		
Field Min	n/a	Occur Min	1
Field Max	n/a	Occur Max	*
Char Types	n/a	Special Chars	n/a
Format		Constraints	n/a
Code List			
Source	ANSI/NIST 2011: Update 2013		
XML Level 1	biom:Transaction	Cardinality	
XML Level 2	biom:TransactionContentSummary	Cardinality	1..1
XML Level 3	biom:ContentRecordSummary	Cardinality	1..*
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes

1.003_2a

Transaction Content

Subfield: Single set of information items

Mnemonic	REC_0	Conditionality	M
		Status	New-Active
Description	This field indicates repeating subsets of the Transaction Content field.		
Field Min	n/a	Occur Min	1
Field Max	n/a	Occur Max	*
Char Types	n/a	Special Chars	n/a
Format	n/a	Constraints	n/a
Code List			
Source	ANSI/NIST 2011: Update 2013		
XML Level 1	biom:Transaction	Cardinality	
XML Level 2	biom:TransactionContentSummary	Cardinality	1..1
XML Level 3	biom:ContentRecordSummary	Cardinality	1..*
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-1: Transaction Information

Page 5 of 1037

1.003_2a

Transaction Content

Record Category Code

Mnemonic	REC	Conditionality	M
		Status	Active
Description	The first information item of the second and remaining subfields of Field 1.003 File Content shall be the record identifier character(s) chosen from the look up codes below that identifies the record type approved by DoD EBTS.		
Field Min	1	Occur Min	1
Field Max	2	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	REC = 2 or 4; or 7 ≤ REC ≤ 22; or REC = or 99; integer
Code List	DOD EBTS APPROVED LOGICAL RECORD NUMBER CODES		
Source	ANSI/NIST ITL 1-2011 (Type-1), BIMA- STB-STD-11-001		
XML Level 1	biom:Transaction	Cardinality	
XML Level 2	biom:TransactionContentSummary	Cardinality	1..1
XML Level 3	biom:ContentRecordSummary	Cardinality	1..*
XML Level 4	biom:RecordCategoryCode	Cardinality	1..1
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

1.003_2b

Transaction Content

Information Designation Character

Mnemonic	IDC	Conditionality	M
		Status	Active
Description	The second information item (information designation character / IDC) shall be an integer equal to or greater than zero and less than or equal to 99.		
Field Min	1	Occur Min	1
Field Max	2	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	0 ≤ IDC ≤ 99
Code List			
Source	ANSI/NIST ITL 1-2011 (Type-1)		
XML Level 1	biom:Transaction	Cardinality	
XML Level 2	biom:TransactionContentSummary	Cardinality	1..1
XML Level 3	biom:ContentRecordSummary	Cardinality	1..*
XML Level 4	biom:ImageReferenceIdentification/nc:IdentificationType	Cardinality	1..1
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

1.004

Type of Transaction

Mnemonic	TOT			Conditionality	M
				Status	Active
Description	This mandatory field shall contain an identifier, which designates the type of transaction and subsequent processing that this file should be given. The TOT shall be in accordance with definitions provided by the Domain and/or Application Profile.				
Field Min	Encoding Specific		Occur Min	1	
Field Max	Encoding Specific		Occur Max	1	
Char Types	A		Special Chars	None, TransactionCategoryCodeType	
Format	n/a		Constraints	See the specific Domain and/or Application Profile referenced	
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-1)				
XML Level 1	biom:Transaction			Cardinality	
XML Level 2	biom:TransactionCategory			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

1.005

Date

Mnemonic	DAT			Conditionality	M
				Status	Active
Description	This mandatory field shall contain the local date when the transaction was submitted. Reference Annex B (traditional encoding) and Annex C (xml encoding) from ANSI/NIST ITL 1-2011 for more detail.				
Field Min	Encoding Specific		Occur Min	1	
Field Max	Encoding Specific		Occur Max	1	
Char Types	N		Special Chars	None	
Format	YYYYMMDD - for Traditional Encoding or NEIM Conformant Encoding			Constraints	Dependent upon encoding. Default is YYYYMMDD.
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-1)				
XML Level 1	biom:Transaction			Cardinality	
XML Level 2	biom:TransactionDate/nc:date			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

1.006

Priority

Mnemonic	PRY			Conditionality	0
				Status	Active
Description	This optional field shall contain a single information character to designate the urgency with which a response is desired. See the specific Application Profile for any defaults that may apply.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	DoD ABIS: 1 ≤ PRY ≤ 4. Default: 1 ≤ PRY ≤ 9 positive integer		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-1), BIMA- STB-STD-11-001				
XML Level 1	biom:Transaction	Cardinality			
XML Level 2	biom:TransactionPriorityValue	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

1.007

Destination Agency Identifier

Mnemonic	DAI			Conditionality	M
				Status	Active
Description	This mandatory field shall contain the identifier of the administration or organization designated to receive the transmission.				
Field Min	1	Occur Min	1		
Field Max	Unlimited	Occur Max	1		
Char Types	ANS	Special Chars	Any character with type A, N or S.		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-1)				
XML Level 1	biom:Transaction	Cardinality			
XML Level 2	biom:TransactionDestinationOrganization	Cardinality	1..1		
XML Level 3	nc:OrganizationIdentification/nc:IdentificationType	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

1.008

Originating Agency Identifier

Mnemonic	ORI	Conditionality	M
		Status	Active
Description	The origination field shall contain the ORI identifying the agency or organization submitting the transaction.		
Field Min	1	Occur Min	1
Field Max	Unlimited	Occur Max	1
Char Types	ANS	Special Chars	Any character with type A, N or S.
Format	n/a	Constraints	None
Code List			
Source	ANSI/NIST ITL 1-2011 (Type-1), BIMA- STB-STD-11-001		
XML Level 1	biom:Transaction	Cardinality	
XML Level 2	biom:TransactionOriginatingOrganization	Cardinality	1..1
XML Level 3	nc:OrganizationIdentification/nc:IdentificationType	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

1.009

Transaction Control Number

Mnemonic	TCN	Conditionality	M
		Status	Active
Description	This mandatory field shall contain the Transaction Control Number (TCN) as assigned by the originating agency. The TCN is a unique identifier generated by the system that submits the transaction and carried through on the response for tracing purposes. When a transaction is sent to a system that receives and generates responses, the Transaction Control Reference (TCR) in the response(s) will be the TCN used in the submission. A TCN is mandatory for a submission, and a TCR is mandatory for a response. The DoD EBTS requires a 40-byte TCN that contains the following 5 pieces of information, each separated by a single hyphen: 1: The Originating Agency Identifier (ORI) (9 bytes) 2: Greenwich Mean (a.k.a. Zulu or UTC) date/time stamp (14 bytes) 3: A code for the software used at the point of collection/transmission (4 bytes) 4: An indicator of the software version used at the point of collection/transmission (4 bytes) 5: A random or sequential alphanumeric string (5 bytes). For any transaction that requires a response, the respondent shall refer to this number in communicating with the originating agency. Greenwich Mean (a.k.a. Zulu or UTC) date/time stamp is formatted as follows: YYYYMMDDhhmmss		
Field Min	1	Occur Min	1
Field Max	Unlimited	Occur Max	1
Char Types	ANS	Special Chars	Hyphen. Default: Any character with type A, N or S.
Format		Constraints	See Format
Code List			
Source	ANSI/NIST ITL 1-2011 (Type-1), BIMA- STB-STD-11-001		
XML Level 1	biom:Transaction	Cardinality	
XML Level 2	biom:TransactionControlIdentification/nc:IdentificationID	Cardinality	1..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

1.01

Transaction Control Reference

Mnemonic	TCR			Conditionality	0
				Status	Active
Description	This optional field shall be used for responses that refer to the TCN of a previous transaction involving an inquiry or other action that required a response.				
Field Min	1	Occur Min	0		
Field Max	Unlimited	Occur Max	1		
Char Types	ANS	Special Chars	Hyphen. Default: Any character with type A, N or S.		
Format	See 1.009 TCN	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-1)				
XML Level 1	biom:Transaction	Cardinality			
XML Level 2	biom:TransactionControlReferenceIdentification/nc:IdentificationID	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

1.011

Native Scanning Resolution

Mnemonic	NSR			Conditionality	M
				Status	Active
Description	This mandatory field shall be set to "00.00" if there are no Type-4 records in the transaction. When there are Type-4 records present, this field is used to specify the native scanning resolution of the friction ridge image capture device. This field shall specify the resolution in pixels per millimeter. The resolution shall be expressed as two numeric characters followed by a decimal point and two more numeric characters. If Record Type-4 is used and images are scanned at greater than the class of 500 ppi, they shall be subsampled, scaled down, or interpolated down to produce a class resolution of 500 ppi for transmission. Users shall utilize Record Type-14 if transmitting a fingerprint image at greater than the limits of the 500 ppi class. Images with scanning resolution greater than or equal to the 1000 ppi class should not be transmitted using Record Type-4 unless being transmitted at 500 ppi class to a system incapable of receiving Type-14 records at 1000 ppi class or greater.				
Field Min	T = 5; X = 4	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	NS	Special Chars	Period		
Format	##.##	Constraints	NSR = 00.00 if no Type-4 records in transaction; otherwise xx.xx		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-1)				
XML Level 1	biom:Transaction	Cardinality			
XML Level 2	biom:TransactionImageResolutionDetails	Cardinality	1..1		
XML Level 3	biom:NativeScanningResolutionValue	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

1.012

Nominal Resolution

Mnemonic	NTR	Conditionality	M
		Status	Active
Description	This mandatory field shall be set to "00.00" if there are no Type-4 records in the transaction. When there are Type-4 records present, this field specifies the nominal resolution for the image(s) being exchanged. This field shall specify the resolution in pixels per millimeter. The resolution shall be within the range 19.30 ppmm (490 ppi) to 20.08 ppmm (510 ppi). For example, a sensor that scans natively at 508 ppi would show both NSR and NTR as 20 ppmm (508 ppi). These images should not be sampled down to exactly 500 ppi. This field may be used to apply to Type-7 records if specified by the domain or application profile.		
Field Min	T = 5; X = 4	Occur Min	1
Field Max	5	Occur Max	1
Char Types	NS	Special Chars	Period
Format	##.##	Constraints	NTR = 00.00 if no Type-4 records in transaction; otherwise xx.xx
Code List			
Source	ANSI/NIST ITL 1-2011 (Type-1)		
XML Level 1	biom:Transaction	Cardinality	
XML Level 2	biom:TransactionImageResolutionDetails	Cardinality	1..1
XML Level 3	biom:NominalTransmittingResolutionValue	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

1.013

Domain Name

Mnemonic	DOM	Conditionality	O
		Status	Active
Description	This optional field identifies the domain name for the user-defined Type-2 record implementation. The domain name may only appear once within a transaction. It shall consist of one or two information items. The domain shall be registered with the BIMA. It consists of a Domain Name Implementation and a Domain Name Implementation Version. The BIMA is the domain registrar for domain names used in DoD EBTS transactions. For transactions that use a different implementation, the Domain Name shall be populated according to the Application Profile that transaction belongs to.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	n/a
Format	n/a	Constraints	n/a
Code List			
Source	ANSI/NIST ITL 1-2011 (Type-1), BIMA- STB-STD-11-001		
XML Level 1	biom:Transaction	Cardinality	
XML Level 2	biom:TransactionDomain	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

1.013_1

Domain Name

Domain Name Implementation

Mnemonic	DNM			Conditionality	M↑
				Status	Active
Description	The mandatory first information item (domain name / DNM) will uniquely identify the agency, entity, or implementation used for formatting the fields in the Type-2 record. The default value for the field shall be the North American Domain implementation (NORAM). For transactions that use an implementation other than DoD EBTS, the Domain Name shall be populated according to the Application Profile that that transaction belongs to.				
Field Min	1	Occur Min	1		
Field Max	Unlimited	Occur Max	1		
Char Types	ANS	Special Chars	Any character with type A, N or S.		
Format	n/a	Constraints	For DoD EBTS, DNM = DoD EBTS		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-1), BIMA- STB-STD-11-001				
XML Level 1	biom:Transaction	Cardinality			
XML Level 2	biom:TransactionDomain	Cardinality	0..1		
XML Level 3	biom:TransactionDomainName	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

1.013_2

Domain Name

Domain Name Implementation Version

Mnemonic	DVN			Conditionality	O↑
				Status	Active
Description	An optional second information item shall contain the unique version of the particular implementation. Ex: "EBTS 4.0"				
Field Min	1	Occur Min	0		
Field Max	Unlimited	Occur Max	1		
Char Types	ANS	Special Chars	Any character with type A, N or S.		
Format	n/a	Constraints	For DoD EBTS 4.0, DVN = 4.0		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-1), BIMA- STB-STD-11-001				
XML Level 1	biom:Transaction	Cardinality			
XML Level 2	biom:TransactionDomain	Cardinality	0..1		
XML Level 3	biom:DomainVersionNumberIdentification/ nc:IdentificationID	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

1.014

Greenwich Mean Time

Mnemonic	GMT		Conditionality	0	
			Status	Active	
Description	This optional field provides a mechanism for expressing the date and time in terms of universal Greenwich Mean Time (GMT) units. This time is independent of the actual time zone where the time and date is recorded. The data is YYYYMMDDhhmmssZ, where the Z indicates the zone description of 0 hours. If used, the GMT field contains the universal date that will be in addition to the local date contained in Field 1.005 (DAT).				
Field Min	Dependent upon encoding		Occur Min	0	
Field Max	Dependent upon encoding		Occur Max	1	
Char Types	AN		Special Chars	None	
Format	YYYYMMDDhhmmssZ - for Traditional Encoding		Constraints	Dependent upon encoding	
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-1)				
XML Level 1	biom:Transaction		Cardinality		
XML Level 2	biom:TransactionUTCDate/nc:DateTime		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

1.015

Application Profile Specifications

Character Encoding

Mnemonic	DCS		Conditionality	0	
			Status	Active	
Description	This optional field specifies the character encoding that may appear within this transaction for data with the character type listed as "U" or 'user-defined' in "Char Types". The default character encoding for the Traditional Encoding is 7-bit ASCII. For XML, it is UTF-8.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a, TransactionCharacterSetType	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-1)				
XML Level 1	biom:Transaction		Cardinality		
XML Level 2	biom:TransactionCharacterSetDirectory		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

1.015_0

Application Profile Specifications

Subfield: A single set of information items

Mnemonic	DCS_0			Conditionality	M↑
				Status	New-Active
Description	Subfield of Character Encoding contains a single set of information items with this version.				
Field Min	n/a			Occur Min	0
Field Max	n/a			Occur Max	1
Char Types	n/a			Special Chars	n/a
Format	n/a			Constraints	n/a
Code List					
Source	ANSI/NIST ITL 2011: UPDATE 2013				
XML Level 1	biom:Transaction			Cardinality	
XML Level 2	biom:TransactionCharacterSetDirectory			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

1.015_1

Character Encoding

Character Encoding Set Index

Mnemonic	CSI			Conditionality	M↑
				Status	Active
Description	This first information item of Field 1.015 DCS is the identifier for the character set index number that references an associated character set throughout the transaction file. Index Code '1' for 8 bit Latin has been deprecated and should not be used. DoD EBTS 3.0 default character encoding is 7-bit ASCII; UTF-8 is also allowed.				
Field Min	1			Occur Min	0
Field Max	3			Occur Max	1
Char Types	N			Special Chars	None
Format	n/a			Constraints	0 ≤ CSI ≤ 4 or 128 ≤ CSI ≤ 999 non-negative integer
Code List	TRANSACTION CHARACTER SET INDEX CODES				
Source	ANSI/NIST ITL 1-2011 (Type-1), BIMA- STB-STD-11-001				
XML Level 1	biom:Transaction			Cardinality	
XML Level 2	biom:TransactionCharacterSetDirectory			Cardinality	0..1
XML Level 3	biom:CharacterSetIndexCode			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

1.015_2

Character Encoding

Character Encoding Set Name

Mnemonic	CSN			Conditionality	M↑
				Status	Active
Description	The second information item of Field 1.015 DCS shall be the common name for the character set associated with that index number. Character Set Name '8-bit Latin' has been deprecated and should not be used. DoD EBTS 4.0 default character encoding is 7-bit ASCII; UTF-8 is also allowed.				
Field Min	1	Occur Min	1		
Field Max	16	Occur Max	1		
Char Types	ANS	Special Chars	Any		
Format	n/a	Constraints	CSN = ASCII or UTF-8		
Code List	TRANSACTION CHARACTER SET INDEX CODES				
Source	ANSI/NIST ITL 1-2011 (Type-1), BIMA- STB-STD-11-001				
XML Level 1	biom:Transaction	Cardinality			
XML Level 2	biom:TransactionCharacterSetDirectory	Cardinality	0..1		
XML Level 3	biom:CharacterSetCommonNameCode	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

1.015_3

Character Encoding

Character Encoding Set Version

Mnemonic	CSV			Conditionality	O
				Status	Active
Description	The optional third information item of Field 1.015 DCS is the specific version of the character set used. In the case of the use of UTF-8, this information item can be used to hold the specific version of the character set used with UTF-8, so that the display terminal can be switched to the correct font family.				
Field Min	1	Occur Min	1		
Field Max	16	Occur Max	1		
Char Types	ANS	Special Chars	Any character with type A, N or S.		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-1)				
XML Level 1	biom:Transaction	Cardinality			
XML Level 2	biom:TransactionCharacterSetDirectory	Cardinality	0..1		
XML Level 3	biom:CharacterSetVersionIdentification/nc:IdentificationID	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

1.016

Application Profile Specifications

Mnemonic	APS		Conditionality	0	
			Status	Active	
Description	DoD EBTS Type-1 records are defined in ITL 1-2011. Every application profile shall define values in the Application Profile Specifications field (1.016). The BIMA Baseline Application Profile shall be the default value in field 1.016 if no other value is provided. The Baseline Application Profile specifies the common transactions occurring between DoD collection devices that have direct or indirect transaction ties to the DoD authoritative biometric repository. The Baseline Application Profile enables the user to conform to DoD EBTS v4.0.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-1), BIMA- STB-STD-11-001				
XML Level 1	biom:Transaction		Cardinality		
XML Level 2	biom:TransactionApplicationProfile		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

1.016_0

Application Profile Specifications

Subfields: Repeating sets of information items

Mnemonic	APS_0		Conditionality	M↑	
			Status	New-Active	
Description	Mandatory Subfields of Application Profile Specifications: Repeating sets of information items 1 to 100				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	99	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST 2011: Update 2013				
XML Level 1	biom:Transaction		Cardinality		
XML Level 2	biom:TransactionApplicationProfile		Cardinality	0..99	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

1.016_1

Application Profile Specifications

Application Profile Specifications

Mnemonic	APO			Conditionality	M↑
				Status	Active
Description	The first information item of the Application Profile Specifications field. It uniquely identifies the agency or entity responsible for the specification.				
Field Min	1	Occur Min	0		
Field Max	Unlimited	Occur Max	99		
Char Types	ANS	Special Chars	Any character with type A, N or S.		
Format	n/a	Constraints	For DoD EBTS, APO = DFBA		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-1), BIMA- STB-STD-11-001				
XML Level 1	biom:Transaction	Cardinality			
XML Level 2	biom:TransactionApplicationProfile	Cardinality	0..99		
XML Level 3	biom:ApplicationProfileOrganizationName	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

1.016_2

Application Profile Specifications

Application Profile Name

Mnemonic	APN			Conditionality	M↑
				Status	Active
Description	The second information item of the Application Profile Specifications field. It shall contain the name of the specification.				
Field Min	1	Occur Min	0		
Field Max	Unlimited	Occur Max	99		
Char Types	ANS	Special Chars	Any character with type A, N or S.		
Format	n/a	Constraints	For Baseline Application Profile, APN = Baseline Application Profile		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-1), BIMA- STB-STD-11-001				
XML Level 1	biom:Transaction	Cardinality			
XML Level 2	biom:TransactionApplicationProfile	Cardinality	0..99		
XML Level 3	biom:ApplicationProfileName	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

1.016_3

Application Profile Specifications

Application Profile Version Number

Mnemonic	APV			Conditionality	M↑
				Status	Active
Description	The third information item of the Application Profile Specifications field. It shall contain the specific version of the specification.				
Field Min	1	Occur Min	0		
Field Max	Unlimited	Occur Max	99		
Char Types	ANS	Special Chars	Any character with type A, N or S.		
Format	n/a	Constraints	For Baseline Application Profile, APV = 1.0		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-1), BIMA- STB-STD-11-001				
XML Level 1	biom:Transaction	Cardinality			
XML Level 2	biom:TransactionApplicationProfile	Cardinality	0..99		
XML Level 3	biom1:ApplicationProfileVersionIdentification/nc:IdentificationID	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

1.017

Agency Names

Mnemonic	ANM			Conditionality	0
				Status	Active
Description	This optional field is comprised of two optional information items. The first is the destination agency name / DAN. This corresponds to the agency listed in Field 1.007 Destination agency identifier / DAI. The second optional information item is the originating agency name / OAN. This corresponds to the agency listed in Field 1.008. Originating agency identifier / ORI. Both information items are alphanumeric and can have any special characters in the names.				
Field Min	n/a	Occur Min	1		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-1)				
XML Level 1	biom:Transaction	Cardinality			
XML Level 2	biom:TransactionOriginatingOrganization	Cardinality	1..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-1: Transaction Information

Page 18 of 1037

1.017_1

Agency Names

Destination Agency Name

Mnemonic	DAN			Conditionality	O↑
				Status	Active
Description	The name of the administration or organization designated to receive the transmission.				
Field Min	1	Occur Min	0		
Field Max	Unlimited	Occur Max	1		
Char Types	ANS	Special Chars	Any character with type A, N or S, nc:TextType		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-1)				
XML Level 1	biom:Transaction	Cardinality			
XML Level 2	biom:TransactionDestinationOrganization	Cardinality	1..1		
XML Level 3	nc:OrganizationName	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

1.017_2

Agency Names

Originating Agency Name

Mnemonic	OAN			Conditionality	O↑
				Status	Active
Description	The name of the administration or organization that originated the transmission.				
Field Min	1	Occur Min	0		
Field Max	Unlimited	Occur Max	1		
Char Types	ANS	Special Chars	Any character with type A, N or S, nc:TextType		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-1)				
XML Level 1	biom:Transaction	Cardinality			
XML Level 2	biom:TransactionOriginatingOrganization	Cardinality	1..1		
XML Level 3	nc:OrganizationName	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

1.018

Geographic Name Set

Mnemonic	GNS			Conditionality	0		
				Status	New-Active		
Description	This optional field is used if the transaction uses GENC in lieu of ISO 3166-1 as a code set for country code specifications. ISO 3166-1 is the default country code set used for the transaction when this field is not contained in Record Type-1. DoD EBTS 4.0 default is GENC.						
Field Min	3			Occur Min	0		
Field Max	4			Occur Max	1		
Char Types	AN			Special Chars	None		
Format	n/a			Constraints	GNS = GENC		
Code List	GEOGRAPHIC NAME SET CODES						
Source	ANSI/NIST ITL 1-2011 (Type-1): Update 2013						
XML Level 1	biom:Transaction				Cardinality		
XML Level 2	dod-ebts:TransactionGeographicNameSetCode				Cardinality	0..1	
XML Level 3					Cardinality		
XML Level 4					Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.001

Record Header

Mnemonic	LEN			Conditionality	M		
				Status	Active		
Description	The record header appears as the first field (xx.001) in each Record Type. It contains information particular to the encoding format chosen, in order to enable proper reading of the record. In Traditional encoding, this field contains the record length in bytes (including all information separators). In NIEM-conformant XML encoding, this field contains the RecordCategoryCode, which is the numeric representation of the Record Type.						
Field Min	T = 2; X = 1			Occur Min	1		
Field Max	T = 8; X = 2			Occur Max	1		
Char Types	N			Special Chars			
Format	n/a			Constraints	positive integer; X = <RecordCategoryCode>		
Code List							
Source	ANSI/NIST ITL 1-2011 Type-2						
XML Level 1	nist-itl:RecordCategoryCode				Cardinality	1..1	
XML Level 2					Cardinality		
XML Level 3					Cardinality		
XML Level 4					Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.002

Information Designation Character

Mnemonic	IDC	Conditionality	M
		Status	Active
Description	Each of the records present in a transaction, with the exception of the Type-1 record, shall include a field (xx.002) containing the information designation character / IDC. The value of the IDC shall be a sequentially assigned positive integer starting from zero and incremented by one up to a maximum of 99. IDC references are stated in Type-1 Field 1.003 Transaction content (CNT) and shall be used to relate information items in the CNT field of the Type-1 record to the other records in the transaction. Two or more records may share a single IDC solely to identify and link together records that pertain to different representations of the same biometric trait.		
Field Min	1	Occur Min	1
Field Max	2	Occur Max	1
Char Types	N	Special Chars	
Format	n/a	Constraints	0 <= IDC <= 99; integer
Code List			
Source	ANSI/NIST ITL 1-2011 Type-2		
XML Level 1	nist-itl:ImageReferenceIdentification/nc:IdentificationID	Cardinality	1...1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

2.003

FBI File Number

Mnemonic	FFN	Conditionality	n/a
		Status	Sunset
Description	This is a 10-byte numeric representing the FBI Investigative File Number. This is not the FBI Number specified by the mnemonic "FBI." Since it is used for FBI LFPS record keeping purposes, it is imperative that the user transmit this number if known.		
Field Min	10	Occur Min	0
Field Max	10	Occur Max	1
Char Types	N	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	NGI-DOC-01078-10.0		
XML Level 1	fbi: ebts:RecordTransactionActivity	Cardinality	0...1
XML Level 2	fbi-ebts:FBIFileNumber/nc:IdentificationID	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.005

Retention Code

Mnemonic	RET	Conditionality	0
		Status	Active
Description	This field indicates whether the information submitted as a part of a transaction is to be retained as a permanent part of the FBI's Master File. Submit a 'Y' for yes or an 'N' for no.		
Field Min	1	Occur Min	0
Field Max	1	Occur Max	1
Char Types	A	Special Chars	
Format	n/a	Constraints	n/a
Code List	YES NO CODE		
Source	NGI-DOC-01078-10.0		
XML Level 1	ansi-nist:RecordRetentionIndicator	Cardinality	0...1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

2.006

Attention Indicator

Mnemonic	ATN	Conditionality	0
		Status	Active
Description	This alphanumeric-special field shall contain a designation of the individual to whose attention a response is to be directed. Periods shall not be used e.g., Det. J. Q. Public shall be entered as DET J Q PUBLIC. The value of ATN returned to the submitter is the value submitted.		
Field Min	3	Occur Min	0
Field Max	30	Occur Max	1
Char Types	ANS	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	NGI-DOC-01078-10.0		
XML Level 1	dod-ebts:AttentionIndicator	Cardinality	0...1
XML Level 2	nc:TextType	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.007

Send Copy to

Mnemonic	SCO		Conditionality	0
			Status	Active
Description	The purpose of this 9-to-19-character alphanumeric-special ANS field is to indicate that additional electronic responses need to be forwarded to agencies other than the contributor by the State Identification Bureau. The first nine characters shall be alphanumeric and shall contain the NCIC-assigned Originating Agency Identifier ORI for an agency who is to receive a copy of the response. At the option of the transmitting agency, the ORI may be expanded to a size of 19 characters, with 10 characters of alphanumeric-special (ANS) data appended to the end to assist in proper routing of the responses. listed in the "SEND COPY TO" block			
Field Min	9	Occur Min	0	
Field Max	19	Occur Max	9	
Char Types	ANS	Special Chars		
Format	n/a	Constraints	n/a	
Code List	SEARCH RESULT CODE			
Source	NGI-DOC-01078-10.0			
XML Level 1	dod-ebts:RecordForwardOrganizations	Cardinality	0...1	
XML Level 2	nc:OrganizationIdentification/nc:IdentificationID	Cardinality	0...9	
XML Level 3		Cardinality		
XML Level 4		Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0
			Yes	DoD EBTS 4.0
				Yes

2.009

Originating Agency Case Number

Mnemonic	OCA		Conditionality	0
			Status	Active
Description	This field contains the one-to-twenty character Originating Agency Case Identifier OCA assigned by the originating agency. This alphanumeric-special ANS field may contain any printable 7-bit ASCII character with the exception of the period. The OCA must not begin with a blank.			
Field Min	1	Occur Min	0	
Field Max	20	Occur Max	1	
Char Types	ANS	Special Chars		
Format	n/a	Constraints	n/a	
Code List				
Source	NGI-DOC-01078-10.0			
XML Level 1	fbi: ebts:RecordTransactionActivity	Cardinality	0...1	
XML Level 2	fbi-ebts:RecordTransactionActivity	Cardinality	0...1	
XML Level 3	nc:CaseTrackingID	Cardinality	0...1	
XML Level 4		Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0
			Yes	DoD EBTS 4.0
				Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.01

Contributor Case Identifier Number

Mnemonic	CIN			Conditionality	0
				Status	Active
Description	This grouped free-text field is a 48-byte maximum alphanumeric-special assigned by the contributor to uniquely identify a latent case. It consists of: a literal subfield Contributor Case Prefix CIN_PRE of up to 24 characters e.g., "Incident #, "Laboratory Number," "Investigation No."				
Field Min	n/a	Occur Min	1		
Field Max	n/a	Occur Max	5		
Char Types	n/a	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi: ebts:RecordTransactionActivity			Cardinality	0..11
XML Level 2	fbi-ebts:ContributorCaselDentificationNumber			Cardinality	1..5
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.010_0

Contributor Case Identifier Number

Subfields: Repeating sets of information items

Mnemonic	CIN_0			Conditionality	M↑
				Status	New-Active
Description	Repeating subfield for Contributor Case Identifier Number				
Field Min	n/a	Occur Min	1		
Field Max	n/a	Occur Max	5		
Char Types	n/a	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	EBTS 4.0				
XML Level 1	fbi: ebts:RecordTransactionActivity			Cardinality	0..11
XML Level 2	fbi-ebts:ContributorCaselDentificationNumber			Cardinality	1..5
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.010_1

Contributor Case Identifier Number

Contributor Case Identifier Prefix

Mnemonic	CIN_PRE			Conditionality	M↑
				Status	Active
Description	Literal subfield Contributor Case Prefix (CIN_PRE) of up to 24 characters (e.g., "Incident #," "Laboratory Number," "Investigation No.")				
Field Min	1	Occur Min	1		
Field Max	24	Occur Max	1		
Char Types	ANS	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi: ebts:RecordTransactionActivity	Cardinality	0..1		
XML Level 2	fbi-ebts:ContributorCaseIdentificationNumber	Cardinality	1..5		
XML Level 3	fbi-ebts:ContributorCasePrefixIdentification/nc:IdentificationID	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

2.010_2

Contributor Case Identifier Number

Contributor Case Identifier

Mnemonic	CIN_ID			Conditionality	M↑
				Status	Active
Description	The Contributor Case Identifier subfield (CIN_ID) of up to 24 characters.				
Field Min	1	Occur Min	1		
Field Max	24	Occur Max	1		
Char Types	ANS	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi: ebts:RecordTransactionActivity	Cardinality	0..1		
XML Level 2	fbi-ebts:ContributorCaseIdentificationNumber	Cardinality	1..5		
XML Level 3	fbi-ebts:ContributorCaseIdentification/nc:IdentificationID	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.013

Latent Case Number Extension

Mnemonic	LCX	Conditionality	0
		Status	Active
Description	Defines extensions assigned by the FBI for each submission related to a Latent Case Number. The LCX shall be a five-digit extension starting with "00000" for the first submission and incrementing by one for each subsequent submission. The LCX shall be used only in conjunction with LCN. As this field is for FBI LPS internal use only, this response field will be used for record-keeping purposes only.		
Field Min	5	Occur Min	1
Field Max	5	Occur Max	1
Char Types	N	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	NGI-DOC-01078-10.0		
XML Level 1	fbi: ebts:RecordTransactionActivity	Cardinality	0..1
XML Level 2	fbi-ebts:FBIlatentCaseIdentification	Cardinality	1..1
XML Level 3	fbi- ebts:FBIlatentCaseNumberExtensionIdentification/nc:IdentificationID	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No
		DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes

2.014

FBI Number UCN

Mnemonic	FBI	Conditionality	0
		Status	Active
Description	This field is used to uniquely specify Identities contained in the NGI database, and shall be no more than nine alphanumeric characters. This Universal Control Number (UCN) is used to identify records in the criminal, civil, ULF and other repositories. The UCN number returned in a response is dependent upon the search results. The Legacy Subject Control Number (SCNA) used for ULF records may be provided in this field where designated in the message definition.		
Field Min	1	Occur Min	0
Field Max	9	Occur Max	1000
Char Types	AN	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	NGI-DOC-01078-10.0		
XML Level 1	fbi-ebts:RecordSubject	Cardinality	0..1
XML Level 2	j:PersonFBIIdentification/nc:IdentificationID	Cardinality	0..1000
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.015

State Identification Number

Mnemonic	SID		Conditionality	0	
			Status	Active	
Description	This field contains any known state identification number. The native encoding format is the standard two-character abbreviation of the state name followed by the number. Embedded blanks are not permitted. SIDs from New York, Oregon, or Pennsylvania may contain a hyphen in the last position. The SID returned in a response is dependent upon the search results. FBI IAFIS expects the format to be the standard two-character abbreviation of the state name followed by the number.				
Field Min	3		Occur Min	0	
Field Max	10		Occur Max	1000	
Char Types	ANS		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordSubject		Cardinality	0...1	
XML Level 2	nc:PersonStateIdentification/nc:IdentificationID		Cardinality	0...1000	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

2.016

Social Security Account Number

Mnemonic	SOC		Conditionality	0	
			Status	Active	
Description	This field contains the subject's social security number, if known. This number shall be entered as nine consecutive digits with no embedded punctuation characters. No foreign social security numbers shall be used.				
Field Min	9		Occur Min	0	
Field Max	9		Occur Max	4	
Char Types	N		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordSubject		Cardinality	0...1	
XML Level 2	nc:PersonSSNIidentification/nc:IdentificationID		Cardinality	0...4	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.017

Miscellaneous Identification Number

Mnemonic	MNU	Conditionality	O
		Status	Active
Description	If there are any miscellaneous identification numbers, they shall be entered in this field. The format of the data shall be a two-letter identifying code, followed by a hyphen -, followed by the number itself. The size of the MNU is limited to 15 characters and as many as four miscellaneous numbers may be included in this field. Each MNU shall be separated from the next by the {RS} separator character. See look up type and associated codes for th list of acceptable two-letter identifying codes. If "AF" or "AS" is entered, all characters following the hyphen must be numeric. Interspersed blanks are invalid. Types of numbers not listed in the MISCELLANEOUS IDENTIFICATION NUMBER CODE table shall not be entered. Only U.S. passport numbers shall be entered; foreign numbers shall be ignored. For the list of 2 letter identifying code, see look up codes below.		
Field Min	4	Occur Min	0
Field Max	15	Occur Max	4
Char Types	ANS	Special Chars	
Format	n/a	Constraints	n/a
Code List	MISCELLANEOUS IDENTIFICATION NUMBER CODE		
Source	NGI-DOC-01078-10.0		
XML Level 1	fbi-ebts:RecordSubject	Cardinality	0...1
XML Level 2	nc:PersonOtherIdentification	Cardinality	0...4
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

2.018

Name Legacy

Mnemonic	NAM	Conditionality	O
		Status	Active
Description	This alpha-special field contains the names of the subject. The format shall be the surname followed by a comma, followed by the given names, which are separated by a space. Part IV of the NCIC Code Manual describes in greater detail the manner in which each name is to be entered. Hyphens, commas, and blanks are all allowed as special characters. Numerics are not allowed. Special values of NAM to be entered in cases where the subject's name is not known are listed in the NAME look up code table.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1
Char Types	AS	Special Chars	
Format	NCIC Name Format: <surname>,<given name1>,<given name2> ...	Constraints	n/a
Code List	NAME		
Source	NGI-DOC-01078-10.0		
XML Level 1	fbi-ebts:RecordSubject	Cardinality	0...1
XML Level 2	fbi-ebts:PersonName	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-2: User-Defined Descriptive Text

Page 28 of 1037

2.018_1

Name Legacy

Surname

Mnemonic	NAM1			Conditionality	0		
				Status	New-Active		
Description	A last name or family name of a person.						
Field Min	3		Occur Min	1			
Field Max	50		Occur Max	1			
Char Types	AS		Special Chars				
Format	n/a		Constraints	n/a			
Code List							
Source	NGI-DOC-01078-10.0						
XML Level 1	fbi-ebts:RecordSubject			Cardinality	0...1		
XML Level 2	fbi-ebts:PersonName			Cardinality	0...1		
XML Level 3	nc:PersonSurName			Cardinality	1...1		
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.018_2

Name Legacy

Given Name

Mnemonic	NAM2			Conditionality	0		
				Status	New-Active		
Description	A first name of a person.						
Field Min	3		Occur Min	0			
Field Max	50		Occur Max	1			
Char Types	AS		Special Chars				
Format	n/a		Constraints	n/a			
Code List							
Source	NGI-DOC-01078-10.0						
XML Level 1	fbi-ebts:RecordSubject			Cardinality	0...1		
XML Level 2	fbi-ebts:PersonName			Cardinality	0...1		
XML Level 3	nc:PersonGivenName			Cardinality	0...1		
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.018_3

Name Legacy

Middle Name

Mnemonic	NAM3			Conditionality	O
				Status	New-Active
Description	A middle name of a person.				
Field Min	3	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	AS	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordSubject	Cardinality	0...1		
XML Level 2	fbi-ebts:PersonName	Cardinality	0...1		
XML Level 3	nc:PersonMiddleName	Cardinality	0...1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.019

Aliases Legacy

Mnemonic	AKA			Conditionality	O
				Status	Active
Description	This 3-to-30 alpha-special AS field contains alias names of the subject. Up to ten aliases may be provided, separated from one another by the {RS} character. AKA may contain a comma, hyphen, or blank as special characters. The format shall be the surname followed by a comma, followed by the given names separated by a space. The following restrictions and exceptions to the general format apply (the first three apply only to the traditional encoding): 1. Minimum length is three bytes in the following sequence: alpha or ampersand, comma, or alphabetic. 2. A comma must be followed by a minimum of one alphabetic character. 3. A blank before or after comma is invalid. 4. A hyphen in first and last position of any name segment is invalid. 5. Two consecutive blanks or hyphens between characters are invalid.				
Field Min	3	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	AS	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordSubject	Cardinality	0...1		
XML Level 2	fbi-ebts:PersonAlternateName	Cardinality	0...10		
XML Level 3	nc:PersonGivenName, nc:PersonMiddleName, nc:PersonSurName, fbi-ebts:PersonFourthImportanceName ,fbi-ebts:PersonFifthImportanceName	Cardinality	0...1		
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.02

Place of Birth

Mnemonic	POB		Conditionality	O	
			Status	Active	
Description	The subject's place of birth shall be entered in this field. Indicate in this POB field the state Mexican, United States, territorial possession, province Canadian, or country of birth. The appropriate two-letter abbreviation shall be used as listed in Part IV of the NCIC State and Country Data Code Table (Appendix O NGI-DOC-01078-10.0).				
Field Min	2		Occur Min	0	
Field Max	2		Occur Max	1	
Char Types	A		Special Chars		
Format	n/a		Constraints	n/a	
Code List	PLACE OF BIRTH CONDITIONS and Appendix O NGI-DOC-01078-10.0				
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordSubject		Cardinality	0...1	
XML Level 2	fbi-ebts:PersonBirthPlaceCode		Cardinality	0...1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.021

Country of Citizenship

Mnemonic	CTZ		Conditionality	O	
			Status	Active	
Description	This field contains two-letter abbreviation for the name of the country of which the subject is a citizen. Entry must be a valid country code from the NCIC State and Country Data Code Table found in Appendix O [of FBI EBTS10.0].				
Field Min	2		Occur Min	0	
Field Max	2		Occur Max	10	
Char Types	A		Special Chars		
Format	n/a		Constraints	n/a	
Code List	Appendix O NGI-DOC-01078-10.0				
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordSubject		Cardinality	0...1	
XML Level 2	fbi-ebts:PersonCitizenshipCode		Cardinality	0...10	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.022

Date of Birth

Mnemonic	DOB		Conditionality	0	
			Status	Active	
Description	This field contains the date of birth. It is entered as an eight-digit number in the same format as specified in Section 1.1 of this appendix [in FBI EBTS 9.1]. If DOB is completely unknown, enter as 00000000. Partial DOBs are not allowed. DOB shall not exceed date of submission after time zone adjustment. When a submission contains an unknown DOB and is a non-ident retained, that submission will be rejected, as IAFIS will not allow a master record to be created with an unknown DOB.				
Field Min	8		Occur Min	0	
Field Max	8		Occur Max	5	
Char Types	N		Special Chars		
Format	YYYYMMDD		Constraints	n/a	
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordSubject		Cardinality	0...1	
XML Level 2	nc:PersonBirthDate/nc:Date		Cardinality	0...5	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.023

Age Range

Mnemonic	AGR		Conditionality	0	
			Status	Active	
Description	An estimated age range may be entered using a pair of two-digit numbers. The first two digits shall represent the minimum age, and the second two the maximum. There shall be no separator character used between the ages.				
Field Min	4		Occur Min	0	
Field Max	4		Occur Max	1	
Char Types	N		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordSubject		Cardinality	0...1	
XML Level 2	nc:PersonAgeMeasure		Cardinality	0...1	
XML Level 3	nc:MeasureIntegerRange/nc:RangeMinimumValue/nc:RangeMaximumValue		Cardinality	0...1	
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.024

Sex

Mnemonic	SEX		Conditionality	0	
			Status	Active	
Description	This field is used to report the gender of the subject. The entry is a single character selected from the GENDER CODES table in Appendix A of the EBTS IDD v6.0.				
Field Min	1		Occur Min	0	
Field Max	1		Occur Max	1	
Char Types	A		Special Chars		
Format	n/a		Constraints	n/a	
Code List	GENDER CODES				
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordSubject		Cardinality	0...1	
XML Level 2	fbi-ebts:PersonSexCode		Cardinality	0...1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

2.025

Race Legacy

Mnemonic	RAC		Conditionality	0	
			Status	Active	
Description	This field is used to indicate the race of the subject. Use the predominant race code from the [look up codes].				
Field Min	1		Occur Min	0	
Field Max	1		Occur Max	1	
Char Types	A		Special Chars		
Format	n/a		Constraints	n/a	
Code List	RACE				
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordSubject		Cardinality	0...1	
XML Level 2	nc:PersonRace		Cardinality	0...1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.026

Scars, Marks and Tattoos

Mnemonic	SMT		Conditionality	0	
			Status	Active	
Description	For each scar, mark, or tattoo present on the subject, the appropriate NCIC code shall be used in this information item. Blanks are allowed as special characters.				
Field Min	3		Occur Min	0	
Field Max	10		Occur Max	10	
Char Types	AS		Special Chars		
Format	n/a		Constraints	n/a	
Code List	NCIC DESTINATION				
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordSubject		Cardinality	0...1	
XML Level 2	fbi-ebts:PersonPhysicalFeature		Cardinality	0...1	
XML Level 3	nc:PhysicalFeatureCategoryText		Cardinality	0...10	
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.027

Height Legacy

Mnemonic	HGT		Conditionality	0	
			Status	Active	
Description	This field contains the subject's height as a three-character value. If reported in feet and inches, the first leftmost digit is used to show feet while the two rightmost digits are used to show the inches between 00 and 11. If reported in inches then the left most character is "N" followed by two digits. If height is unknown, 000 is entered. The allowable range is 400 to 711. Heights outside this range will be clamped at these limits.				
Field Min	3		Occur Min	1	
Field Max	3		Occur Max	1	
Char Types	AN		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordSubject		Cardinality	0...1	
XML Level 2	nc:PersonHeightMeasure		Cardinality	0...1	
XML Level 3	nc:MeasureValue/nc:MeasureUnitText		Cardinality	1...1	
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.028

Height Range

Mnemonic	HTR		Conditionality	0	
			Status	Active	
Description	This field will be used to give an estimated height range to be expressed as two three-character values formatted as described for mnemonic HGT, indicating the shortest and tallest heights of the subject. For the native encoding of this field, the first three characters shall represent the minimum height and the second three the maximum height. There shall be no separator character used between the heights. The allowable range is 400 to 711 or N48 to N95				
Field Min	6		Occur Min	1	
Field Max	6		Occur Max	1	
Char Types	AS		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordSubject		Cardinality	0...1	
XML Level 2	nc:PersonHeightMeasure		Cardinality	0...1	
XML Level 3	nc:MeasureRangeValue/nc:RangeMinimumValue/nc:RangeMinimumValue/		Cardinality	1...1	
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.029

Weight Legacy

Mnemonic	WGT		Conditionality	0	
			Status	Active	
Description	In this field, the subject's weight in pounds is entered. If weight is unknown, 000 is entered. All weights in excess of 499 pounds will be set to 499 lbs. WGT must be in the range 050 to 499 lbs. however, there is no minimum range limit for missing persons or unknown persons.				
Field Min	3		Occur Min	1	
Field Max	3		Occur Max	1	
Char Types	N		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordSubject		Cardinality	0...1	
XML Level 2	nc:PersonWeightMeasure		Cardinality	0...1	
XML Level 3	nc:MeasureValue		Cardinality	1...1	
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.03

Weight Range

Mnemonic	WTR		Conditionality	0	
			Status	Active	
Description	If a range of weight is given, it shall be expressed as two 3-digit numbers indicating the minimum and maximum weights in pounds of the subject. There shall be no separator character used between the weights. WTR must be in the range 050 to 499 lbs however, there is no minimum range limit for missing persons or unknown persons.				
Field Min	6		Occur Min	1	
Field Max	6		Occur Max	1	
Char Types	N		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordSubject		Cardinality	0...1	
XML Level 2	nc:PersonWeightMeasure		Cardinality	0...1	
XML Level 3	nc:PersonWeightMeasure/ nc:MeasureRangeValue or nc:RangeMaximumValue		Cardinality	1...1	
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.031

Color Eyes

Mnemonic	EYE		Conditionality	0	
			Status	Active	
Description	For this field, the three-letter code from the following table is used to indicate the subject's color of eyes.				
Field Min	3		Occur Min	0	
Field Max	3		Occur Max	1	
Char Types	A		Special Chars		
Format	n/a		Constraints	n/a	
Code List	ALPHA EYE COLOR CODES				
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordSubject		Cardinality	0...1	
XML Level 2	nc:PersonEyeColorCode		Cardinality	0...1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.032

Hair Color

Mnemonic	HAI		Conditionality	0	
			Status	Active	
Description	In this field, the three-letter code is used to indicate the subject's color of hair.				
Field Min	3		Occur Min	0	
Field Max	3		Occur Max	1	
Char Types	AS		Special Chars		
Format	n/a		Constraints	n/a	
Code List	HAIR COLOR				
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordSubject		Cardinality	0...1	
XML Level 2	nc:PersonHairColorCode		Cardinality	0...1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.034

Pattern Level Classifications

Mnemonic	PAT		Conditionality	0	
			Status	Active	
Description	This grouped field contains pattern classification information about the latent finger(s) image. As such, this field shall only be included when one or more of finger positions 0-10 are being searched. PAT shall consist of two-character finger position code followed by the primary pattern type code as chosen from the following table. Up to two reference pattern classifications per finger are also allowed, thereby making the total number of pattern classes allowable per finger equal to three. For traditional encoding, if multiple pattern types are used for reference for the same finger, they shall be separated from each other by the {US} separator. Multiple fingers shall be separated by the {RS} separator. If submitting a Latent Fingerprint whose actual finger position is unknown, the PAT and FGP (2.074) fields are used in conjunction as follows to supply guesses for which finger position the latent print might be: place a "00" in the FGP subfield of PAT to indicate the actual position is unknown; place the actual pattern in the PATCL subfield; place one or more finger number guesses in the FGP field (2.074).				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordSubject		Cardinality	0...1	
XML Level 2	fbi-ebts:PersonFingerprintSet		Cardinality	0...1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.034_0

Pattern Level Classifications

Subfields: Repeating sets of information items

Mnemonic	PAT_0			Conditionality	M↑
				Status	New-Active
Description	Repeating subfield for Pattern Level Classifications				
Field Min	n/a	Occur Min	1		
Field Max	n/a	Occur Max	10		
Char Types	n/a	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	EBTS 4.0				
XML Level 1	fbi-ebts:RecordSubject			Cardinality	0...1
XML Level 2	fbi-ebts:PersonFingerprintSet			Cardinality	1...10
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.034_1

Pattern Level Classifications

Finger Number

Mnemonic	FGP			Conditionality	M↑
				Status	Active
Description	This two-byte field shall contain a character designating the finger position.				
Field Min	2	Occur Min	1		
Field Max	2	Occur Max	10		
Char Types	N	Special Chars			
Format	n/a	Constraints	n/a		
Code List	FINGERPRINT TEN FINGER NUMBER PLUS UNKNOWN				
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordSubject			Cardinality	0...1
XML Level 2	fbi-ebts:PersonFingerprintSet			Cardinality	1...10
XML Level 3	fbi-ebts:FingerprintImageFinger			Cardinality	0...10
XML Level 4	biom_1:FingerPositionCode			Cardinality	1...10
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.034_2

Pattern Level Classifications

Pattern Classification Code

Mnemonic	PATCL			Conditionality	M↑
				Status	Active
Description	The list of acceptable CJIS pattern level fingerprint classifications.				
Field Min	2	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	n/a		
Code List	FINGERPRINT CJIS PATTERN CLASSIFICATION				
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordSubject	Cardinality	0...1		
XML Level 2	fbi-ebts:PersonFingerprintSet	Cardinality	1...10		
XML Level 3	fbi-ebts:PersonFingerprintSet/ fbi-ebts:FingerprintImageFinger/ fbi-ebts:RidgeCoreDelta/fbi-ebts:FingerprintPatternClassificationCode	Cardinality	1...1		
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.035

Palmprints Available Indicator

Mnemonic	PPA			Conditionality	0
				Status	Active
Description	If palm prints are available, this field shall contain a "Y"; otherwise, the field shall be omitted.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	n/a		
Code List	PALM PRINT AVAILABLE INDICATOR				
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordSubject	Cardinality	0...1		
XML Level 2	fbi-ebts:PersonPalmPrintAvailableIndicator	Cardinality	0...1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.038

Date Printed

Mnemonic	DPR		Conditionality	O	
			Status	Active	
Description	This field contains the date that the subject was printed. This date field shall contain the local date for the region submitting the request. DPR shall not exceed the date of submission.				
Field Min	8		Occur Min	0	
Field Max	8		Occur Max	1	
Char Types	N		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordSubject		Cardinality	0...1	
XML Level 2	fbi-ebts:PersonGeneralizedFrictionRidgePositions/ or fbi-ebts:PersonFingerprintSet/		Cardinality	0...1	
XML Level 3	nc:BiometricCaptureDate/nc:Date		Cardinality	0...1	
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.039

Employer and Address

Mnemonic	EAD		Conditionality	O	
			Status	Active	
Description	The name and address of the subject's primary employer may be entered into this free-text field. The EAD returned in a response is the same as the one submitted. For the native encoding, this field is a free form text field.				
Field Min	1		Occur Min	0	
Field Max	120		Occur Max	1	
Char Types	ANS		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordSubject		Cardinality	0...1	
XML Level 2	nc:Employer		Cardinality	0...1	
XML Level 3	nc:EntityOrganization/nc:OrganizationName		Cardinality	0...1	
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.04

Occupation

Mnemonic	OCP		Conditionality	0	
			Status	Active	
Description	This free-text field contains the person's occupation. The OCP returned in a response is the same as the one submitted.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordSubject	Cardinality	0...1		
XML Level 2	nc:EmployeeOccupationText	Cardinality	0...1		
XML Level 3	nc:EmploymentLocation/ nc:LocationAddress/nc:StructuredAddress/nc:LocationStreet/ nc:StreetNumberText or nc:StreetName, nc:EmploymentLocation/ nc:LocationAddress/ nc:StructuredAddress/ nc:LocationStreet/nc:StreetName, nc:EmploymentLocation/ nc:LocationAdd	Cardinality	0...1		
XML Level 4					Cardinality
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.041

Residence of Person Fingerprinted

Mnemonic	RES		Conditionality	0	
			Status	Active	
Description	This is a free-text field, including printable special characters and formatting characters (CR, LF, TAB) that is used for the residential address of the person fingerprinted. The RES returned in a response is the same as the one submitted.				
Field Min	1	Occur Min	0		
Field Max	120	Occur Max	1		
Char Types	ANS	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordSubject	Cardinality	0...1		
XML Level 2	fbi-ebts:PersonResidenceLocation	Cardinality	0...1		
XML Level 3	fbi-ebts:PersonResidenceLocation/ nc:LocationAddress/ nc:StructuredAddress/ nc:LocationStreet/nc:StreetNumberText or nc:StreetName, fbi-ebts:PersonResidenceLocation/ nc:LocationAddress/ nc:StructuredAddress/nc:LocationCityName or nc:LocationStateNCICLSTAC	Cardinality	0...1		
XML Level 4					Cardinality
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.042

Military Code

Mnemonic	MIL	Conditionality	0
		Status	Active
Description	A one-letter code from the following table shall be entered in this field to indicate which branch of the United States Military submitted the enlistment transaction.		
Field Min	1	Occur Min	0
Field Max	1	Occur Max	1
Char Types	A	Special Chars	
Format	n/a	Constraints	n/a
Code List	MILITARY		
Source	NGI-DOC-01078-10.0		
XML Level 1	fbi-ebts:RecordTransactionData	Cardinality	0...1
XML Level 2	dod-ebts:TransactionSubmissionMilitaryCode	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No
		DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes

2.043

Type of Search Requested

Mnemonic	TSR	Conditionality	0
		Status	Active
Description	A one-byte code shall be entered in this field from the Type of Search Codelist to indicate the type of record being submitted. The field is applicable to the NFUF, CPDR, FNDR, NNDR, CPNU, DOCE, EMUF, NFAP, and NFUE transactions.		
Field Min	1	Occur Min	0
Field Max	1	Occur Max	1
Char Types	A	Special Chars	
Format	n/a	Constraints	n/a
Code List	TYPE OF SEARCH		
Source	NGI-DOC-01078-10.0		
XML Level 1	fbi-ebts:RecordTransactionData	Cardinality	0...1
XML Level 2	fbi-ebts:TransactionSearchRequestCategoryCode	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.045

Date of Arrest

Mnemonic	DOA		Conditionality	0	
			Status	Active	
Description	This field contains the date of arrest. The date shall appear as an eight-digit number. DOA shall not exceed date of submission except when the submission originates from an international contributor located in a time zone earlier than the Eastern Time Zone. This date field shall contain the local date for the region submitting the request.				
Field Min	8		Occur Min	0	
Field Max	8		Occur Max	1	
Char Types	N		Special Chars		
Format	YYYYMMDD		Constraints	n/a	
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionData		Cardinality	0..1	
XML Level 2	fbi-ebts:ArrestDate/nc:Date		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

2.046

Date of Arrest - Suffix

Mnemonic	DOS		Conditionality	0	
			Status	Active	
Description	This field contains a code representing the sequence of the subject's arrests within a given date. The code also indicates the type of fingerprint card on which the Date of Arrest was contained. This field is for internal use within the FBI only.				
Field Min	1		Occur Min	0	
Field Max	1		Occur Max	1	
Char Types	A		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionActivity		Cardinality	0..1	
XML Level 2	fbi-ebts:ArrestDateSuffixCode		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

2.047

Arrest Segment Literal

Mnemonic	ASL			Conditionality	0
				Status	Active
Description	This field is made up of the following subfields: Date of Offense DOO Arrest Offense Literal AOL.				
Field Min	n/a			Occur Min	0
Field Max	n/a			Occur Max	1
Char Types	n/a			Special Chars	
Format	n/a			Constraints	n/a
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionActivity			Cardinality	0...1
XML Level 2	fbi-ebts:CriminalCycle			Cardinality	0...1
XML Level 3	fbi-ebts:ArrestOffenseData			Cardinality	0...1
XML Level 4				Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.047_0

Arrest Segment Literal

Subfields: Repeating sets of information items

Mnemonic	ASL_0			Conditionality	M↑
				Status	New-Active
Description	Repeating subfield for Arrest Segment Literal				
Field Min	n/a			Occur Min	0
Field Max	n/a			Occur Max	40
Char Types	n/a			Special Chars	
Format	n/a			Constraints	n/a
Code List					
Source	EBTS 4.0				
XML Level 1	fbi-ebts:RecordTransactionActivity			Cardinality	0...1
XML Level 2	fbi-ebts:CriminalCycle			Cardinality	0...40
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.047_1

Arrest Segment Literal

Date of Offense

Mnemonic	DOO			Conditionality	O
				Status	Active
Description	The DOO shall appear as an eight-digit number. The DOO shall not exceed the current date except when the submission originates from an international contributor located in a time zone earlier than the Eastern Time Zone. This date field shall contain the local date for the region submitting the request. CJIS has edit checks in place to allow for the acceptance of the local date as valid up to 24 hours in advance to accommodate the variance between international time zones. The DOO shall be separated from the AOL by the {US} separator character. A DOO is prohibited without a corresponding AOL offense. If a DOO is not present, a {US} character separator shall still be used.				
Field Min	8	Occur Min	0		
Field Max	8	Occur Max	1		
Char Types	N	Special Chars			
Format	YYYYMMDD	Constraints	n/a		
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionActivity			Cardinality	0...1
XML Level 2	fbi-ebts:CriminalCycle			Cardinality	0...40
XML Level 3	fbi-ebts:OffenseDate/nc:Date			Cardinality	0...1
XML Level 4				Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

2.047_2

Arrest Segment Literal

Arrest Offense Literal

Mnemonic	AOL			Conditionality	M↑
				Status	Active
Description	A free text description of an offense charged on an arrest. The first character of the AOL text must not be blank. Each AOL should have a corresponding DOO.				
Field Min	1	Occur Min	1		
Field Max	300	Occur Max	1		
Char Types	ANS	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionActivity			Cardinality	0...1
XML Level 2	fbi-ebts:CriminalCycle			Cardinality	0...40
XML Level 3	j:ChargeText			Cardinality	1...1
XML Level 4				Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.051

Court Segment Literal

Mnemonic	CSL		Conditionality	0	
			Status	Active	
Description	The CSL field is made up of the Court Disposition Date CDD, the Court Offense Literal COL, Other CourtSentence Provision Literal CPL, Court Disposition (CDN) and Court Count Number (CCT). A CDD (if available), followed by a COL, followed by a CPL, followed by a CDN, followed by CCT (if available), each separated by a {US} separator character must be present for each occurrence of the CSL field.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionActivity		Cardinality	0...1	
XML Level 2	fbi-ebts:CriminalCycle		Cardinality	0...40	
XML Level 3	fbi-ebts:CourtDispositionData		Cardinality	0...1	
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.051_0

Court Segment Literal- Subfields: Repeating sets of information items

Mnemonic	CSL_0		Conditionality	0	
			Status	New-Active	
Description	Repeating subfield for Court Segment Literal				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	40	
Char Types	n/a		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	EBTS 4.0				
XML Level 1	fbi-ebts:RecordTransactionActivity		Cardinality	0...1	
XML Level 2	fbi-ebts:CriminalCycle		Cardinality	0...40	
XML Level 3	fbi-ebts:CourtDispositionData		Cardinality	0...40	
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.051_1

Court Segment Literal

Court Disposition Date

Mnemonic	CDD	Conditionality	O
		Status	Active
Description	The date a court count was disposed of by the court. The CDD shall appear as an eight-digit number. The CDD shall not exceed the current date except when the submission originates from an international contributor located in a time zone earlier than the Eastern Time Zone. This date field shall contain the local date for the region submitting the request.		
Field Min	8	Occur Min	0
Field Max	8	Occur Max	1
Char Types	N	Special Chars	
Format	YYYYMMDD	Constraints	n/a
Code List			
Source	NGI-DOC-01078-10.0		
XML Level 1	fbi-ebts:RecordTransactionActivity	Cardinality	0...1
XML Level 2	fbi-ebts:CriminalCycle	Cardinality	0...40
XML Level 3	fbi-ebts:CourtDispositionData	Cardinality	0...40
XML Level 4	nc:DispositionDate/nc:Date	Cardinality	0...1
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

2.051_2

Court Segment Literal

Court Offense Literal

Mnemonic	COL	Conditionality	M↑
		Status	Active
Description	A freeform text description of an offense charged in a court count. The first character of the COL must not be a blank.		
Field Min	1	Occur Min	1
Field Max	300	Occur Max	1
Char Types	ANS	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	NGI-DOC-01078-10.0		
XML Level 1	fbi-ebts:RecordTransactionActivity	Cardinality	0...1
XML Level 2	fbi-ebts:CriminalCycle	Cardinality	0...40
XML Level 3	fbi-ebts:CourtDispositionData	Cardinality	0...40
XML Level 4	j:ChargeText	Cardinality	1...1
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.051_3

Court Segment Literal

Other Court Sentence Provision Literal

Mnemonic	CPL			Conditionality	M↑
				Status	Active
Description	The freeform text containing information on sentence provisions.				
Field Min	1	Occur Min	1		
Field Max	300	Occur Max	1		
Char Types	ANS	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionActivity	Cardinality	0...1		
XML Level 2	fbi-ebts:CriminalCycle	Cardinality	0...40		
XML Level 3	fbi-ebts:CourtDispositionData	Cardinality	0...40		
XML Level 4	nc:DispositionText	Cardinality	1...1		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.051_4

Court Segment Literal

Court Disposition

Mnemonic	CDN			Conditionality	M↑
				Status	New-Emerging
Description	A code from Table 12 of NGI-DOC-01078-10.0 representing the definitive disposition information about a Subject for a particular charge. This element must contain a value most closely associated with the disposition type.				
Field Min	1	Occur Min	1		
Field Max	32	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionActivity	Cardinality	0...1		
XML Level 2	fbi-ebts:CriminalCycle	Cardinality	0...40		
XML Level 3	fbi-ebts:CourtDispositionData	Cardinality	0...40		
XML Level 4	fbi-ebts:DispositionCategoryCodeText	Cardinality	1...1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.051_5

Court Segment Literal

Court Count Number

Mnemonic	CCT			Conditionality	O		
				Status	New-Emerging		
Description	A two-byte sequential number assigned to each court count, with the valid value range from 01 to 40.						
Field Min	2		Occur Min	0			
Field Max	2		Occur Max	1			
Char Types	N			Special Chars			
Format	n/a			Constraints	>1 and <= 40		
Code List							
Source	NGI-DOC-01078-10.0						
XML Level 1	fbi-ebts:RecordTransactionActivity			Cardinality	0...1		
XML Level 2	fbi-ebts:CriminalCycle			Cardinality	0...40		
XML Level 3	fbi-ebts:CourtDispositionData			Cardinality	0...40		
XML Level 4	fbi-ebts:CourtCountNumber			Cardinality	0...1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.053

Offense Category

Mnemonic	OFC			Conditionality	O		
				Status	Sunset		
Description	The category for a crime committed by the biometric subject.						
Field Min	1		Occur Min	0			
Field Max	1		Occur Max	1			
Char Types	N			Special Chars			
Format	n/a			Constraints	n/a		
Code List	OFFENSE CATEGORY						
Source	NGI-DOC-01078-10.0						
XML Level 1	fbi-ebts:RecordTransactionActivity			Cardinality	0...1		
XML Level 2	fbi-ebts:OffenseCategoryCode			Cardinality	0...1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.054

Custody or Supervisory Status Start Date

Mnemonic	SSD		Conditionality	0
			Status	Active
Description	This field contains the start date for the subject's indicated custody or supervisory status. The date shall appear as an eight-digit number. The SSD may not be less than Date Of Arrest. The SSD shall not exceed the current date except when the submission originates from an international contributor located in a time zone earlier than the Eastern Time Zone. This date field shall contain the local date for the region submitting the request. The SSD may not be less than DOA. The SSD shall not exceed the current date.			
Field Min	8	Occur Min	0	
Field Max	8	Occur Max	1	
Char Types	N	Special Chars		
Format	YYYYMMDD	Constraints	n/a	
Code List				
Source	NGI-DOC-01078-10.0			
XML Level 1	fbi-ebts:RecordTransactionActivity	Cardinality	0...1	
XML Level 2	fbi-ebts:CriminalCycle	Cardinality	0...40	
XML Level 3	fbi-ebts:CustodySupervisoryData	Cardinality	0...1	
XML Level 4	nc:StartDate/nc:Date	Cardinality	0...1	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0 Yes DoD EBTS 4.0 Yes

2.055

Custody or Supervisory Literal

Mnemonic	SLE		Conditionality	0
			Status	Active
Description	This field contains the free-text description of the subject's custody or supervision status. The first character must not be blank. Entry of SLE requires that SSD also be entered.			
Field Min	1	Occur Min	0	
Field Max	300	Occur Max	1	
Char Types	ANS	Special Chars		
Format	n/a	Constraints	n/a	
Code List				
Source	NGI-DOC-01078-10.0			
XML Level 1	fbi-ebts:RecordTransactionActivity	Cardinality	0...1	
XML Level 2	fbi-ebts:CriminalCycle	Cardinality	0...40	
XML Level 3	fbi-ebts:CustodySupervisoryData	Cardinality	0...1	
XML Level 4	fbi-ebts:SupervisionStatus(0...1)/nc:StatusText(0...1)	Cardinality	0...1	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0 Yes DoD EBTS 4.0 Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.056

Identification Comments

Mnemonic	ICO		Conditionality	0	
			Status	Active	
Description	Additional miscellaneous identification remarks. The reason for caution may be entered in this free-text field. The first character may not be a blank.				
Field Min	1		Occur Min	0	
Field Max	50		Occur Max	1	
Char Types	ANS		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionActivity		Cardinality	0...1	
XML Level 2	j:SubjectOffenderNoticeText		Cardinality	0...1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

2.057

Finger Numbers Requested

Mnemonic	FNR		Conditionality	0	
			Status	Active	
Description	This numeric field is used in transactions involving a request for fingerprint image information. The finger numbers for which image information is requested are selected from Table, "Finger Position Code," in the ANSI/NIST-ITL. Up to 13 individual finger image numbers may be listed, separated from one another by the <RS> separator. For traditional encoding, the finger codes being requested shall appear as 01{RS}02{RS} ... {RS}10{GS}. This field may also include the supplemental position code of 19 and/or the palm position codes outlined in the associated codelist.				
Field Min	2		Occur Min	0	
Field Max	2		Occur Max	13	
Char Types	N		Special Chars		
Format	n/a		Constraints	n/a	
Code List	PALM POSITION and FINGER POSITION CODE				
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionData		Cardinality	0...1	
XML Level 2	fbi-ebts:TransactionFingerprintImagesRequested/biom_2:FingerPositionCode		Cardinality	0...13	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.059

Search Results Findings

Mnemonic	SRF		Conditionality	0	
			Status	Active	
Description	This field is used in responses to submissions and contains a single character indicating the results of a comparison. See Look Up Codes, which outlines the valid values, their meanings, and transactions which may contain those values. SRF values that are specific to a single request TOT reflect the request and response TOTs with a dash between them (e.g., FDSP-SRE), where only the response TOT contains the SRF field.				
Field Min	1		Occur Min	0	
Field Max	1		Occur Max	1	
Char Types	A		Special Chars		
Format	n/a		Constraints	n/a	
Code List	SEARCH RESULT FINDING				
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionData		Cardinality	0...1	
XML Level 2	fbi-ebts:TransactionResponseData		Cardinality	0...1	
XML Level 3	fbi-ebts:TransactionSearchResultsCode		Cardinality	0...1	
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.06

Status/Error Message

Mnemonic	MSG		Conditionality	0	
			Status	Active	
Description	This free-text field will contain reason, status, or error messages that are generated as a result of the processing of a transaction and will be sent back to the submitter. For example, an Unsolicited Unsolved Latent Delete transaction will contain the reason for the deletion of a record. For native encoding, each message will be separated by the RS separator character.				
Field Min	1		Occur Min	0	
Field Max	300		Occur Max	1000	
Char Types	ANS		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionData		Cardinality	0...1	
XML Level 2	fbi-ebts:TransactionResponseData		Cardinality	0...1	
XML Level 3	fbi-ebts:TransactionStatusText		Cardinality	0...1000	
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.061

Case Title

Mnemonic	CST			Conditionality	0		
				Status	Active		
Description	This field identifies the Latent Case. It will include information concerning the case, and it must include the offense type.						
Field Min	1			Occur Min	0		
Field Max	50			Occur Max	1		
Char Types	AS			Special Chars			
Format	n/a			Constraints	n/a		
Code List							
Source	NGI-DOC-01078-10.0						
XML Level 1	fbi-ebts:RecordTransactionActivity				Cardinality	0...1	
XML Level 2	nc:CaseTitleText				Cardinality	0...1	
XML Level 3					Cardinality		
XML Level 4					Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

2.062

Image Type

Mnemonic	IMT			Conditionality	0		
				Status	Active		
Description	This field identifies the type of image e.g., palmprints, toe prints included in an electronic submittal. The list of IMT values to be used in an electronic latent submittal to identify the Type-7 or Type-13 records present. The field definition has been modified to allow multiple occurrences in one transaction. The following table is a list of IMT values to be used to identify the records present or biometric sets being referenced in the submission or response. Note that the value of 2 is deprecated in favor of the new value of 6, and the values 4 and 5 are deprecated in favor of the new value of 7.						
Field Min	1			Occur Min	0		
Field Max	2			Occur Max	1000		
Char Types	N			Special Chars			
Format	n/a			Constraints	n/a		
Code List	BIOMETRIC IMAGE						
Source	NGI-DOC-01078-10.0						
XML Level 1	fbi-ebts:RecordBiometricImageCategoryCode				Cardinality	0...1000	
XML Level 2					Cardinality		
XML Level 3					Cardinality		
XML Level 4					Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.064

Candidate List

Mnemonic	CAN	Conditionality	0
		Status	Active
Description	This grouped field shall contain a candidate list. It is composed of two subfields: Universal Control Number / UCN and Name / NAM. For traditional encoding, each field will be separated by a {US} separator and will be provided for each candidate in the list. Commas, hyphens, and blanks are allowed in the NAM subfield as specified in the NCIC Message Book, Part 1. Each UCN and NAM set shall be separated from the next by the {RS} separator character. Note: The UCN can contain an FBI number if appropriate for that record.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	NGI-DOC-01078-10.0		
XML Level 1	fbi-ebts:RecordTransactionData (0...1)/ fbi-ebts:TransactionResponseData (0...1)	Cardinality	0...1
XML Level 2	fbi-ebts:TransactionCandidateList	Cardinality	0...3
XML Level 3	fbi-ebts:Candidate	Cardinality	0...1
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

2.064_0

Candidate List

Subfields: Repeating sets of information items

Mnemonic	CAN_0	Conditionality	0
		Status	New-Active
Description	Repeating subfield for Candidate List.		
Field Min	n/a	Occur Min	1
Field Max	n/a	Occur Max	99
Char Types	n/a	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	EBTS 4.0		
XML Level 1	fbi-ebts:RecordTransactionData (0...1)/fbi-ebts:TransactionResponseData (0...1)	Cardinality	0...1
XML Level 2	fbi-ebts:TransactionCandidateList (0...3)/fbi-ebts:Candidate (1...99)	Cardinality	1...99
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.064_1

Candidate List

Universal Control Number

Mnemonic	SI	Conditionality	M↑
		Status	Active
Description	This conditional alphanumeric text field is used to identify the record with which the photos or images being requested are associated, to identify candidates in a candidate list, or otherwise identify individual subject records. The UCN can contain an FBI number FNU if appropriate for that record.		
Field Min	1	Occur Min	1
Field Max	9	Occur Max	1
Char Types	AN	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	NGI-DOC-01078-10.0		
XML Level 1	fbi-ebts:RecordTransactionData (0...1)/fbi-ebts:TransactionResponseData (0...1)	Cardinality	0...1
XML Level 2	fbi-ebts:TransactionCandidateList (0...3)/fbi-ebts:Candidate (1...99)	Cardinality	1...99
XML Level 3	j:PersonFBIIdentification/nc:IdentificationID	Cardinality	1...1
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

2.064_2

Candidate List

Name

Mnemonic	NAM	Conditionality	M↑
		Status	Active
Description	This alpha-special field contains the names of the subject. The format shall be the surname followed by a comma , followed by the given names, which are separated by a space. Part IV of the NCIC Code Manual describes in greater detail the manner in which each name is to be entered. Numerics are not allowed.		
Field Min	3	Occur Min	1
Field Max	30	Occur Max	1
Char Types	AS	Special Chars	
Format	NCIC Name Format: <surname>,<given name1><given name2> ...	Constraints	n/a
Code List			
Source	NGI-DOC-01078-10.0		
XML Level 1	fbi-ebts:RecordTransactionData (0...1)/fbi-ebts:TransactionResponseData (0...1)	Cardinality	0...1
XML Level 2	fbi-ebts:TransactionCandidateList (0...3)/fbi-ebts:Candidate (1...99)	Cardinality	1...99
XML Level 3	fbi-ebts:PersonName	Cardinality	0...1
XML Level 4	nc:PersonGivenName (0...1), nc:PersonMiddleName (0...1), nc:PersonSurName (1...1)	Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.065

Repository Statistics Response

Mnemonic	RSR	Conditionality	O
		Status	Active
Description	This field contains a file generated by the NGI Latent Friction Ridge system that provides detailed statistics that can be used to estimate the level of penetration of the repository given a set of search parameters defined in the search request. This field is in the form of a large ASCII file that can contain up to 96,000 bytes of alphanumeric-special (ANS) data. This field contains five items separated by tab characters: 1. Parameter name 2. Parameter Value 3. The fraction of the Criminal file having that value of the parameter 4. The fraction of the Civil file having that value of the parameter 5. The fraction of the combined Criminal and Civil files having the value of the parameter. In the traditional encoding formatting, the fields are separated with "whitespace" (spaces and/or tabs) with MS DOS end-of-line convention (CR/LR). A period character is used as a decimal point in the fraction values. The value should be interpreted as the proportion of records matching that category and code. Data rows containing all zeroes will not be returned.		
Field Min	1	Occur Min	0
Field Max	96000	Occur Max	1
Char Types	ANS	Special Chars	
Format	n/a	Constraints	n/a
Code List	REPOSITORY STATISTICS RESPONSE		
Source	NGI-DOC-01078-10.0		
XML Level 1	fbi-ebts:RecordTransactionData (0...1)/ fbi-ebts:TransactionResponseData (0...1)	Cardinality	0...1
XML Level 2	fbi-ebts:TransactionRepositoryResponse	Cardinality	0...1
XML Level 3	fbi-ebts:TransactionRepositoryResponseRecord	Cardinality	1...*
XML Level 4	fbi-ebts:RepositoryParameterText (1...1), fbi-ebts:RepositoryParameterValueText (1...1), fbi-ebts:RepositoryCriminalParameterPercent (1...1), fbi-ebts:RepositoryCivilParameterPercent (1...1), fbi-ebts:RepositoryCombinedParameterPercent1 (1...1)	Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes

2.067

Image Capture Equipment

Mnemonic	IMA	Conditionality	O
		Status	Active
Description	This free text field is used to log the make, model, and serial number of the equipment used to acquire images. It is a grouped field, comprised of three subfields: the Make MAK, Model MODL, and Serial Number SERNO of the acquisition device, separated by the {US} separator character.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	NGI-DOC-01078-10.0		
XML Level 1	fbi-ebts:RecordImageCaptureDetail	Cardinality	0...1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No
		DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.067_1

Image Capture Equipment

Image Capture Equipment Legacy Derivable

Mnemonic	MAK			Conditionality	M↑
				Status	Active
Description	The Make of the acquisition device.				
Field Min	1	Occur Min	1		
Field Max	25	Occur Max	1		
Char Types	ANS	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordImageCaptureDetail			Cardinality	0...1
XML Level 2	biom_1:CaptureDeviceMakeText			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.067_2

Image Capture Equipment

Originating Fingerprint Reading System Model Legacy Derivable

Mnemonic	MODL			Conditionality	M↑
				Status	Active
Description	The Model of the acquisition device.				
Field Min	1	Occur Min	0		
Field Max	25	Occur Max	1		
Char Types	ANS	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordImageCaptureDetail			Cardinality	0...1
XML Level 2	biom_1:CaptureDeviceModelText			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.067_3

Image Capture Equipment

Originating Fingerprint Reading System Model Legacy Derivable

Mnemonic	SERNO	Conditionality	M↑
		Status	Active
Description	The Serial Number of the acquisition device.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	ANS	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	NGI-DOC-01078-10.0		
XML Level 1	fbi-ebts:RecordImageCaptureDetail	Cardinality	0...1
XML Level 2	biom_1:CaptureDeviceSerialNumberText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No
		DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes

2.07

Request for Electronic Rap Sheet

Mnemonic	RAP	Conditionality	0
		Status	Active
Description	The purpose of this field is to allow the contributor to optionally request an electronic identity history summary (IdHS) of the identity. An NIDR is returned if the submission results in a nonidentification. A 'Y' in this field indicates that an IdHS is desired, while an omitted field or an 'N' in this field indicates that no IdHS should be returned with the response.		
Field Min	1	Occur Min	0
Field Max	1	Occur Max	1
Char Types	A	Special Chars	
Format	n/a	Constraints	n/a
Code List	YES NO CODES		
Source	NGI-DOC-01078-10.0		
XML Level 1	ansi-nist:RecordRapSheetRequestIndicator	Cardinality	0...1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.071

Action to be Taken

Mnemonic	CAN	Conditionality	0
		Status	Active
Description	This field is used to include text answers to submission requests to indicate that a latent case will be established or to indicate recommendations for further actions in either latent or tenprint responses. This field will also be used to indicate action taken by the FBI in response to electronic document e.g., disposition submissions. For the native encoding of this field, commas, hyphens, ampersands, slashes, number signs, and blanks are all allowed as special characters.		
Field Min	0	Occur Min	0
Field Max	300	Occur Max	1
Char Types	ANS	Special Chars	T = Comma, Hyphen, Ampersand, Slash, Number Sign, Blanks
Format	n/a	Constraints	n/a
Code List			
Source	NGI-DOC-01078-10.0		
XML Level 1	fbi-ebts:RecordTransactionData	Cardinality	0..1
XML Level 2	fbi-ebts:TransactionResponseData	Cardinality	0..1
XML Level 3	fbi-ebts:TransactionActionText	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

2.072

Fingerprint Images Updated

Mnemonic	FIU	Conditionality	0
		Status	Active
Description	This field contains the finger positions that were updated in the FBI's Fingerprint Image Master File as a result of an electronic request to update fingerprint images. The finger numbers for which image information is requested are selected from Table, "Finger Position Code," in the ANSI/NISTITL. Up to 13 individual finger numbers may be listed. For encoding, each finger number will be separated from one another by the {RS} separator. If images of all 14 fingers were updated, the single character "A" is shown instead of individual finger numbers. If no images were updated, an 'N' will be returned.		
Field Min	1	Occur Min	0
Field Max	2	Occur Max	13
Char Types	AN	Special Chars	
Format	n/a	Constraints	n/a
Code List	FINGERPRINT IMAGE UPDATED CODES		
Source	NGI-DOC-01078-10.0		
XML Level 1	fbi-ebts:RecordTransactionData/ebts:TransactionFingerprintImagesUpdated	Cardinality	0..1
XML Level 2	biom_2:FingerPositionCode	Cardinality	0..13
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.073

Controlling Agency Identifier

Mnemonic	CRI	Conditionality	O
		Status	Active
Description	In Criminal and Civil transactions, the first instance of this field (CRI1) shall contain the Originating Agency Identifier (ORI) of the organization controlling the transaction. The CRI may be different from the submitting agency's ORI (e.g., the CSA), which shall be placed in the ORI field. When the controlling agency is also the submitting agency, both the ORI and CRI fields shall be submitted with the same identifier. (See Appendix B for definition of ORI.) In criminal transactions, the CRI will usually refer to the booking station that has submitted the subject's fingerprints to be transmitted through the CSA to the FBI. The FBI uses the first instance of CRI (CRI1) in any transaction that would modify criminal records as the authority to do so. When a Civil transaction matches a criminal record and the CRI1 is not authorized to receive the data, the ORI of the State Identification Bureau that submitted the transaction will be used instead. The second and third instances of CRI, when sent, are treated as user-defined fields.		
Field Min	9	Occur Min	0
Field Max	9	Occur Max	99
Char Types	ANS	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	NGI-DOC-01078-10.0		
XML Level 1	fbi-ebts:RecordTransactionActivity	Cardinality	0...1
XML Level 2	fbi-ebts:RecordControllingAgency or fbi-ebts:PersonFingerprintSet	Cardinality	0...3
XML Level 3	nc:OrganizationIdentification/nc:IdentificationID	Cardinality	1...1
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.074

Finger Numbers Requested

Finger Position

Mnemonic	FGP			Conditionality	O
				Status	Active
Description	This field is used for latent submissions and searches and contains the fingerprint position code of the latent prints submitted. If more than one finger is submitted with native encoding, then the codes will be separated by the {RS} character separator. For latent searches, if multiple fingerprint images are included in one search, finger position is mandatory for all images. If finger position is unknown, the search may contain only a single image, and the field FGP will be omitted or may contain multiple guesses at the correct finger position in the FGP field. In this case, the PAT field must contain "00" in its Finger Number subfield to indicate that the actual position is unknown (see also PAT entry). If the submitter cannot determine what portion of the hand the latent image was derived from, then the position code should be omitted or "18" to spawn a search of all friction ridge areas (fingerprints, palm prints, supplemental prints) within the FBI/CJIS repository. If the submitter cannot determine what portion of the hand the latent image was derived from, then the position code should be omitted or "18" to spawn a search of all friction ridge areas (fingerprints, palm prints, supplemental prints) within the FBI/CJIS repository.				
Field Min	2	Occur Min	1		
Field Max	2	Occur Max	10		
Char Types	N	Special Chars			
Format	n/a	Constraints	n/a		
Code List	FRICTION RIDGE GENERALIZED POSITION				
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordSubject	Cardinality	1...10		
XML Level 2	fbi-ebts:PersonGeneralizedFrictionRidgePositions	Cardinality	1...10		
XML Level 3	biom_2:FrictionRidgePositionCode/biom_2:FingerPositionCode or fbi-ebts:FingerprintImageFinger/biom_2:FingerPositionCode	Cardinality	1...10		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.075

Electronic Rap Sheet

Mnemonic	ERS			Conditionality	O
				Status	Active
Description	This field shall contain the Electronic Identity History Summary (IdHS) of an identified subject. In the case of a non-identification, the IdHS will consist of the Non-Identification Response (NIDR). For a TPRR transaction that contains multiple candidates, the IdHS for each candidate will be concatenated into this field.				
Field Min	4	Occur Min	0		
Field Max	200000	Occur Max	1		
Char Types	ANS	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	DOD_BTFS_TS_EBTS_Nov06_01.02.00				
XML Level 1	fbi-ebts:RecordTransactionData	Cardinality	0...1		
XML Level 2	fbi-ebts:TransactionResponseData	Cardinality	0..1		
XML Level 3	fbi-ebts:TransactionElectronicRapSheetText	Cardinality	0...1		
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.078

Penetration Query Response

Mnemonic	PEN			Conditionality	O
				Status	Sunset
Description	This field provides a response to the penetration query that includes a set of search parameters for a new search. The response will be an estimated size, in percentage, of the repository that will be searched given the input parameters.				
Field Min	2	Occur Min	0		
Field Max	0	Occur Max	1		
Char Types	N	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionData	Cardinality	0..1		
XML Level 2	fbi-ebts:TransactionResponseData	Cardinality	0..1		
XML Level 3	fbi-ebts:TransactionPenetrationQueryResponsePercent	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	No
		DoD EBTS 4.0	No		

2.079

Number of Candidates' Images Returned

Mnemonic	NCR			Conditionality	O
				Status	Active
Description	This field contains the number of candidates the submitter desires to receive in response to a biometric Investigative Search request per ranked candidate list, with a maximum of 99. If multiple candidate lists are to be returned in a search request, the If the NIR in the request is greater than NCR in the request, CJIS will set NIR to the NCR value. This field is also found in the responses to a biometric Investigative Search where it reflects the actual total number of candidates returned in the CNL for the entire concatenated list. For EQRR, this field identifies the number of Identity History Summary reports that are be returned in response to an EQHR.				
Field Min	1	Occur Min	0		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionData	Cardinality	0..1		
XML Level 2	fbi-ebts:TransactionImagesRequestedQuantity	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.08

Response Explanation

Mnemonic	EXP		Conditionality	0	
			Status	Active	
Description	This field is free-form text to elaborate on the Response Code field for the Type-10 Photo record requested.				
Field Min	1		Occur Min	0	
Field Max	50		Occur Max	1	
Char Types	ANS		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionData			Cardinality	0..1
XML Level 2	fbi-ebts:TransactionResponseData			Cardinality	0..1
XML Level 3	dod-ebts:TransactionReasonText			Cardinality	0..1
XML Level 4				Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.082

Response Code

Mnemonic	REC		Conditionality	0	
			Status	Active	
Description	Natively, this one-byte alpha field will contain allowable values of "Y" or "N." This field is used in the PDR and PRR transactions to indicate the status of the corresponding request. If the request contains any errors, the response code REC will be set to "N." Otherwise it will be set to "Y."				
Field Min	1		Occur Min	0	
Field Max	1		Occur Max	1	
Char Types	A		Special Chars		
Format	n/a		Constraints	n/a	
Code List	YES NO CODES				
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionData			Cardinality	0..1
XML Level 2	fbi-ebts:TransactionResponseData			Cardinality	0..1
XML Level 3	fbi-ebts:TransactionResponseIndicator			Cardinality	0..1
XML Level 4				Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.083

Unsolved Latent File

Mnemonic	ULF		Conditionality	O	
			Status	Active	
Description	This one-character alpha field is used to designate whether a latent image or features record in a search should be added to the Unsolved Latent File. Submit a "Y" for yes. If negative, submit "N". If the field is omitted, the default behavior will be 'N'.				
Field Min	1		Occur Min	0	
Field Max	1		Occur Max	1	
Char Types	A		Special Chars		
Format	n/a		Constraints	n/a	
Code List	YES NO CODES				
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionData		Cardinality	0...1	
XML Level 2	fbi-ebts:TransactionUnsolvedLatentFileIndicator		Cardinality	0...1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.084

Amputated or Bandaged

Mnemonic	AMP		Conditionality	O	
			Status	Active	
Description	This repeating field contains information about amputated or bandaged fingerprints in a submission. The field is composed of repeating sets of two subfields: Finger Position / FGP and Amputated Or Bandaged Code / AMPCD. This field is to be used any time there are fewer than ten printable fingers in a tenprint submission for finger positions 1 – 10 or positions 11–15 to specify when no slap fingerprint images are provided in the finger positions. A partially amputated finger should be printed and be marked amputated, XX. If the finger's image is missing for any reason, the UP code should be used. This field is used to tell the AFIS which finger positions need to be characterized. The UP code should only be used when the entire image is not provided for fingerprints in the submission. This code will indicate that the AFIS matcher should ignore this image and not include the image in the matching process. For the traditional encoding, the two-character finger position code is followed by the {US} separator and the amputated or bandaged code. Each set of fingers/amp codes shall be separated by the {RS} separator.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordSubject		Cardinality	0...1	
XML Level 2	fbi-ebts:PersonFingerprintSet		Cardinality	0...1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.084_0

Amputated or Bandaged

Subfields: Repeating sets of information items

Mnemonic	AMP_0			Conditionality	0		
				Status	New-Active		
Description	Repeating sub field for Amputated or Bandaged.						
Field Min	n/a			Occur Min	0		
Field Max	n/a			Occur Max	13		
Char Types	n/a			Special Chars			
Format	n/a			Constraints	n/a		
Code List							
Source	EBTS 4.0						
XML Level 1	fbi-ebts:RecordSubject			Cardinality	0...1		
XML Level 2	fbi-ebts:PersonFingerprintSet			Cardinality	0...13		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.084_1

Amputated or Bandaged

Finger Position Code

Mnemonic	FGP			Conditionality	M↑		
				Status	Active		
Description	The two-character finger position code.						
Field Min	2			Occur Min	1		
Field Max	2			Occur Max	1		
Char Types	N			Special Chars			
Format	n/a			Constraints	01 <= FGP <= 15		
Code List	FINGER POSITION CODE						
Source	NGI-DOC-01078-10.0						
XML Level 1	fbi-ebts:RecordSubject			Cardinality	0...1		
XML Level 2	fbi-ebts:PersonFingerprintSet			Cardinality	0...13		
XML Level 3	biom_2:FingerprintImageFingerMissing			Cardinality	0...13		
XML Level 4	biom_2:FingerPositionCode			Cardinality	1...1		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.084_2

Amputated or Bandaged

Amputated or Bandaged Code

Mnemonic	AMPCD			Conditionality	M↑
				Status	Active
Description	This information item provides the code that describes the reason the finger's image is missing.				
Field Min	2	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	n/a		
Code List	AMPUTATED OR BANDAGED CODE				
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordSubject	Cardinality	0...1		
XML Level 2	fbi-ebts:PersonFingerprintSet	Cardinality	0...13		
XML Level 3	biom_2FingerprintImageFingerMissing	Cardinality	0...13		
XML Level 4	biom_2:FingerMissingCode	Cardinality	1...1		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.086

AFIS Segment Control Number

Mnemonic	SCNA			Conditionality	O
				Status	Active
Description	This field contains an identifier used to track or reference unsolved records. Legacy records that were deposited in the ULF prior to NGI Increment 3 will be referenced with their legacy SCNA. All other unsolved records will be referenced with a UCN in this field. The SCNA field is used, for example, to reference records in the ULF or UPF in the response to a latent or facial investigative search respectively.				
Field Min	1	Occur Min	0		
Field Max	10	Occur Max	1		
Char Types	AN	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionActivity	Cardinality	0...1		
XML Level 2	fbi-ebts:AFISSegmentControlID	Cardinality	0...1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.087

Treat As Adult

Mnemonic	TAA		Conditionality	0	
			Status	Active	
Description	A one-byte optional field to indicate whether a juvenile is to be processed as an adult. A "Y" indicates yes; an omitted field indicates no. The TAA returned in a response is the same as the one submitted.				
Field Min	1		Occur Min	0	
Field Max	1		Occur Max	1	
Char Types	A		Special Chars		
Format	n/a		Constraints	If Yes, this field shall contain "Y," if No, the field is omitted.	
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordSubject		Cardinality	0...1	
XML Level 2	fbi-ebts:PersonAdultTreatmentIndicator		Cardinality	0...1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.088

Note Field

Mnemonic	NOT		Conditionality	0	
			Status	Active	
Description	This free-text field is used to provide additional information regarding electronic latent submissions. For latent search identification results feedback, the NOT field will be used to indicate the candidate from the SRL that matched the search image. For UHN transactions, the NOT field will contain case related information about the search transaction with the hit that generated the unsolicited notification. For ULM transactions, the NOT field will provide information related to latent search images that are candidates for comparison with the unsolved latent (e.g., case-related identifiers or point of contact information).				
Field Min	1		Occur Min	0	
Field Max	1000		Occur Max	1	
Char Types	ANS		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionData		Cardinality	0...1	
XML Level 2	fbi-ebts:TransactionDescriptionText		Cardinality	0...1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.089

Match Score

Mnemonic	MSC		Conditionality	0
			Status	Active
Description	This field contains the match score from NGI for each candidate listed in the 2.064 CAN field.			
Field Min	1	Occur Min	0	
Field Max	6	Occur Max	1	
Char Types	N	Special Chars		
Format	n/a	Constraints	n/a	
Code List				
Source	NGI-DOC-01078-10.0			
XML Level 1	fbi-ebts:RecordTransactionData	Cardinality	0...1	
XML Level 2	fbi-ebts:TransactionResponseData (0...1)/fbi-ebts:TransactionCandidateList(0...3)	Cardinality	0...1	
XML Level 3	fbi-ebts:Candidate	Cardinality	0...1	
XML Level 4	fbi-ebts:CandidateMatchScoreValue	Cardinality	0...1	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0 Yes DoD EBTS 4.0 Yes

2.091

Ridge Core Delta One for Subpattern Classification

Mnemonic	RCD1		Conditionality	0
			Status	Active
Description	This grouped field contains information about the finger(s) ridge counts and is used for Native Mode searches in conjunction with the Pattern Level Classification (PAT 2.034).			
Field Min	n/a	Occur Min	0	
Field Max	n/a	Occur Max	1	
Char Types	n/a	Special Chars		
Format	n/a	Constraints	n/a	
Code List				
Source	NGI-DOC-01078-10.0			
XML Level 1	fbi-ebts:RecordSubject	Cardinality	0...1	
XML Level 2	fbi-ebts:PersonFingerprintSet	Cardinality	0...1	
XML Level 3		Cardinality		
XML Level 4		Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0 Yes DoD EBTS 4.0 Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.091_0

Ridge Core Delta One for Subpattern Classification

Subfields: Repeating sets of information items

Mnemonic	RCD1_0		Conditionality	M↑	
			Status	New-Active	
Description	Repeating subfield for Ridge Core Delta One for Subpattern Classification.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	EBTS 4.0				
XML Level 1	fbi-ebts:RecordSubject		Cardinality	0...1	
XML Level 2	fbi-ebts:PersonFingerprintSet		Cardinality	0...1	
XML Level 3	fbi-ebts:FingerprintImageFinger		Cardinality	0...1	
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.091_1

Ridge Core Delta One for Subpattern Classification

Finger Position Code

Mnemonic	FGP		Conditionality	M↑	
			Status	Active	
Description	The two-character finger position code. The two-character finger position code as specified for the related Pattern Level Classification PAT.				
Field Min	2		Occur Min	1	
Field Max	2		Occur Max	10	
Char Types	N		Special Chars		
Format	n/a		Constraints	n/a	
Code List	FINGER POSITION CODE				
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordSubject		Cardinality	0...1	
XML Level 2	fbi-ebts:PersonFingerprintSet		Cardinality	0...1	
XML Level 3	fbi-ebts:FingerprintImageFinger		Cardinality	0...10	
XML Level 4	biom_2:FingerPositionCode		Cardinality	1...10	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.091_2

Ridge Core Delta One for Subpattern Classification

First Subpattern Ridge Count

Mnemonic	RCN1		Conditionality	M↑	
			Status	Active	
Description	The Ridge Count Number (RCN1 and RCN2) represents the number of ridges between the core and the delta. For right and left slant loops, this count identifies the ridges crossed on a line between the core and the delta. For whorls, both the RCN1 and the RCN2 values have meaning. Permissible values are 1 to 30 for actual ridge counts and 30 if there are more than 30 ridges. The count of 31 indicates an unknown number of ridges, and 0 indicates that the ridge count is not applicable.				
Field Min	1	Occur Min	0		
Field Max	2	Occur Max	2		
Char Types	N	Special Chars			
Format	n/a	Constraints	n/a		
Code List	RIDGE COUNT NUMBER				
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordSubject		Cardinality	0...1	
XML Level 2	fbi-ebts:PersonFingerprintSet		Cardinality	0...1	
XML Level 3	fbi-ebts:FingerprintImageFinger		Cardinality	0...10	
XML Level 4	biom_2:RidgeCountValue		Cardinality	0...2	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.092

Ridge Core Delta Two for Subpattern Classification

Mnemonic	RCD2		Conditionality	O	
			Status	Active	
Description	This grouped field contains information about the finger(s) ridge counts and is used for Native Mode searches in conjunction with the Pattern Level Classification (PAT 2.034).				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordSubject		Cardinality	0...1	
XML Level 2	fbi-ebts:PersonFingerprintSet/ fbi-ebts:FingerprintImageFinger		Cardinality	0...1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.092_0

Ridge Core Delta Two for Subpattern Classification

Subfields: Repeating sets of information items

Mnemonic	RCD2_0		Conditionality	M↑	
			Status	New-Active	
Description	Repeating subfield for Ridge Core Delta Two for Subpattern Classification.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	EBTS 4.0				
XML Level 1	fbi-ebts:RecordSubject			Cardinality	0...1
XML Level 2	fbi-ebts:PersonFingerprintSet/ fbi-ebts:FingerprintImageFinger			Cardinality	0...1
XML Level 3	fbi-ebts:FingerprintImageFinger			Cardinality	0...1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.092_1

Ridge Core Delta Two for Subpattern Classification

Finger Position Code

Mnemonic	FGP		Conditionality	M↑	
			Status	Active	
Description	The two-character finger position code. The two-character finger position code as specified for the related Pattern Level Classification PAT.				
Field Min	2		Occur Min	1	
Field Max	2		Occur Max	10	
Char Types	N		Special Chars		
Format	n/a		Constraints	n/a	
Code List	FINGER POSITION CODE				
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordSubject			Cardinality	0...1
XML Level 2	fbi-ebts:PersonFingerprintSet/ fbi-ebts:FingerprintImageFinger			Cardinality	0...1
XML Level 3	fbi-ebts:FingerprintImageFinger			Cardinality	0...10
XML Level 4	biom_2:FingerPositionCode			Cardinality	1...10
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.092_2

Ridge Core Delta Two for Subpattern Classification

Second Subpattern Ridge Count

Mnemonic	RCN2		Conditionality	M↑	
			Status	Active	
Description	The Ridge Count Number (RCN1 and RCN2) represents the number of ridges between the core and the delta. For right and left slant loops, this count identifies the ridges crossed on a line between the core and the delta. For whorls, both the RCN1 and the RCN2 values have meaning. Permissible values are 1 to 30 for actual ridge counts and 30 if there are more than 30 ridges. The count of 31 indicates an unknown number of ridges, and 0 indicates that the ridge count is not applicable. <i>Deprecated for this set only.</i>				
Field Min	1	Occur Min	0		
Field Max	2	Occur Max	2		
Char Types	N	Special Chars			
Format		Constraints	n/a		
Code List	RIDGE COUNT NUMBER				
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordSubject		Cardinality	0...1	
XML Level 2	fbi-ebts:PersonFingerprintSet/ fbi-ebts:FingerprintImageFinger		Cardinality	0...1	
XML Level 3	fbi-ebts:RidgeCoreDelta		Cardinality	0...10	
XML Level 4	biom_2:RidgeCountValue		Cardinality	0...2	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.095

Repository Statistics Response

Mnemonic	RFR		Conditionality	0	
			Status	Active	
Description	This one-character alpha field is used to indicate a user's desire to have CJIS return a Type-9 features record associated with an image requested via IRQ, LFIS, and LFFS transactions. For the Latent Investigative Search, the features and matched minutiae will be returned to allow for an overlay on the image for comparison purposes. A features record will be returned if the RFR value equals "Y." A features record will not be returned if the field is omitted, its use is optional or if the value of RFR equals "N."				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	RFR = 'Y' or 'N'		
Code List	YES NO CODES				
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordFeaturesRequestIndicator		Cardinality	0...1	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.096

Request Photo Record

Mnemonic	RPR	Conditionality	O
		Status	Sunset
Description	This one-character alpha field is used to indicate a user's desire to have the repository return a Type-10 photo record if one is on file and disseminable. This field is used in conjunction with a Rapid Fingerprint Identification Search transaction RPIS.		
Field Min	1	Occur Min	0
Field Max	1	Occur Max	1
Char Types	A	Special Chars	
Format	n/a	Constraints	n/a
Code List	Y = Photo Record Requested or N = Photo Record Not Requested		
Source	NGI-DOC-01078-10.0		
XML Level 1	fbi-ebts:RecordPhotoRequestIndicator	Cardinality	0...1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes

2.098

Name of Designated Repository

Mnemonic	NDR	Conditionality	O
		Status	Active
Description	This field contains the numerical designation of the repository to be searched. Repository numbers are assigned by the CJIS Division. Multiple entries in this field will indicate a desire to search more than one repository.		
Field Min	1	Occur Min	0
Field Max	3	Occur Max	10
Char Types	N	Special Chars	
Format	n/a	Constraints	n/a
Code List	DESIGNATED REPOSITORY NAME		
Source	NGI-DOC-01078-10.0		
XML Level 1	fbi-fbi-ebts:RecordFBIRepositoryCode	Cardinality	0...10
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

2.3

BAT Global Unique Identifier

Mnemonic	GUID		Conditionality	0	
			Status	Active	
Description	This optional field shall contain the Biometrics Automated Toolset BAT Global Unique Identifier GUID as assigned to the subject by the BAT.				
Field Min	36		Occur Min	0	
Field Max	38		Occur Max	1	
Char Types	ANS		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	DOD_BTF_TS_EBTS_Nov06_01.02.00				
XML Level 1	dod-ebts:BATGlobalUniqueIdentification/nc:IdentificationID		Cardinality	0...1	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.302

Internment Serial Number

Mnemonic	ISN		Conditionality	0	
			Status	Active	
Description	The internment serial number (ISN) is a unique identification number assigned to each EPW, RP and CI taken into the custody of the U.S. Armed Forces. The ISN will consist of three components, with the first two separated by a dash as follows: A. First Component. The first component will contain five characters. The first two will be the alpha-characters 'US'. The third character will be either the alpha or numeric designation for the command/theater under which the EPW, RP and CI came into the custody of the U.S. The fourth and fifth positions are alpha-characters designating the EPW, RP and CI serving power. B. Second Component. The second component is a six character numeric identifier. These numbers will be assigned consecutively to all EPW, RP and CI processed through ISN assigning organizations. The Branch PWIC will assign blocks of numbers to ISN assigning organization/elements in the supported theater. c. Third Component. The third component will consist of an acronym identifying the classification of the individual: either EPW, RP, or CI, to represent Enemy Prisoner of War, Retained Person, or Civilian Internee, respectively. Should an individual that was initially classified as an EPW later determined to be a medically or religiously qualified retained person, the classification may be changed to "RP" with the approval of the EPW command/brigade.				
Field Min	15		Occur Min	0	
Field Max	16		Occur Max	1	
Char Types	ANS		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	Army Regulation 190-8				
XML Level 1	dod-ebts:Internment Serial Number/nc:IdentificationID		Cardinality	0...1	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.303

DoD Number

Mnemonic	DOD_NO		Conditionality	0			
			Status	Active			
Description	Number assigned to the enrollment by a DoD repository.						
Field Min	1	Occur Min	0				
Field Max	9	Occur Max	5				
Char Types	AN	Special Chars					
Format	n/a	Constraints	n/a				
Code List							
Source	DOD_BTF_TS_EBTS_Nov06_01.02.00						
XML Level 1	dod-ebts:DoDNumber/nc:IdentificationID		Cardinality	0...5			
XML Level 2			Cardinality				
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

2.308

Electronic Data Interchange Personal Identifier

Mnemonic	EDIPI		Conditionality	0			
			Status	Active			
Description	The identifier for the dossier collection of documents about the subject.						
Field Min	1	Occur Min	0				
Field Max	50	Occur Max	1				
Char Types	ANS	Special Chars					
Format	n/a	Constraints	n/a				
Code List							
Source	DOD_BTF_TS_EBTS_Nov06_01.02.00						
XML Level 1	dod-ebts:ElectronicDataInterchangePersonalIdentification/nc:IdentificationID		Cardinality	0...1			
XML Level 2			Cardinality				
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

2.309

Defense Biometric Identification System Identifier

Mnemonic	DBIDS_ID		Conditionality	0	
			Status	Active	
Description	This optional field shall contain the DBIDS ID unique identifier for a DBIDS user.				
Field Min	10		Occur Min	0	
Field Max	50		Occur Max	1	
Char Types	ANS		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	DOD_BTF_TS_EBTS_Nov06_01.02.00				
XML Level 1	dod-ebts:DBIDSIdentification/nc:IdentificationID		Cardinality	0...1	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.31

Biometric Subject Personnel Type

Mnemonic	PER_TYPE		Conditionality	0	
			Status		
Description	Contains a code that describes a general category or classification of a biometric subject by the reason they are of interest when encountered.				
Field Min	3		Occur Min	0	
Field Max	50		Occur Max	47	
Char Types	AS		Special Chars		
Format	n/a		Constraints	n/a	
Code List	PERSON CATEGORY CODES				
Source	DOD_BTF_TS_EBTS_Nov06_01.02.00				
XML Level 1	dod-ebts:PersonCategoryCode		Cardinality	0...1	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.316

Request Mug Shot

Mnemonic	RMS			Conditionality	0		
				Status	Active		
Description	An indicator that requests a return of the most recent mug shot frontal pose on file with DoD for the given biometric subject. Otherwise, this field may be omitted.						
Field Min	1			Occur Min	0		
Field Max	1			Occur Max	1		
Char Types	A			Special Chars			
Format	n/a			Constraints	n/a		
Code List	YES NO CODES						
Source	DOD_BTF_TS_EBTS_Nov06_01.02.00						
XML Level 1	dod-ebts:MugShotRequestIndicator				Cardinality	0...1	
XML Level 2					Cardinality		
XML Level 3					Cardinality		
XML Level 4					Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

2.317

Request IAFIS Search

Mnemonic	RIS			Conditionality	0		
				Status	Active		
Description	This optional field shall indicate a request to search IAFIS in addition to the DoD ABIS.						
Field Min	1			Occur Min	0		
Field Max	1			Occur Max	1		
Char Types	A			Special Chars			
Format	n/a			Constraints	n/a		
Code List	YES NO CODES						
Source	DOD_BTF_TS_EBTS_Nov06_01.02.00						
XML Level 1	dod-ebts:IAFISSearchRequestIndicator				Cardinality	0...1	
XML Level 2					Cardinality		
XML Level 3					Cardinality		
XML Level 4					Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.318

XML-based Rap Sheet

Mnemonic	XML			Conditionality	0		
				Status	Active		
Description	An electronic rap sheet for the biometric subject in XML format. Notes: The electronic rap sheet shall consist of lines with a maximum of 174 characters per line. The response formatting shall conform to a future DoD standard.						
Field Min	4		Occur Min	0			
Field Max	400000		Occur Max	1			
Char Types	ANS		Special Chars				
Format	n/a		Constraints	n/a			
Code List							
Source	DOD_BTF_TS_EBTS_Nov06_01.02.00						
XML Level 1	dod-ebts:TransactionXMLRapSheetText			Cardinality	0...1		
XML Level 2				Cardinality			
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

2.334

Submission Color Code

Mnemonic	SCC			Conditionality	0		
				Status	Active		
Description	The color classification of the biometric subject. Red Force includes persons that are Enemy Prisoners of War and Enemy Combatants. Blue Force includes persons that are U.S. Military, DoD Contractors, or DoD civilians. Grey Force includes person that are local nationals, Third Country Nationals or Contractors, or Coalition.						
Field Min	3		Occur Min	0			
Field Max	3		Occur Max	1			
Char Types	A		Special Chars				
Format	n/a		Constraints	n/a			
Code List	COLOR CLASSIFICATION CODES						
Source	DOD_BTF_TS_EBTS_Nov06_01.02.00						
XML Level 1	dod-ebts:PersonSubmissionColorCode			Cardinality	0...1		
XML Level 2				Cardinality			
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.335

Dossier Number

Mnemonic	DOSSIER			Conditionality	0
				Status	Active
Description	The identifier for the dossier collection of documents about the subject.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	ANS	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	DOD_BTF_TS_EBTS_Nov06_01.02.00				
XML Level 1	dod-ebts:DossierNumber/nc:IdentificationID			Cardinality	0...1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.35

Alert

Mnemonic	ALERT			Conditionality	0
				Status	Active
Description	This field contains alert information that will be used in the case where a new submission into the system results in an IDENTED response against the submission containing the alert data. This field contains five information items and all five must be completed if this field is used. It consists of Alert Function, Alert Category, Alert Value, Alert Contact and Alert Detail.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	DOD_BTF_TS_EBTS_Nov06_01.02.00				
XML Level 1	dod-ebts:Alert			Cardinality	0...1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.350_0

Alert

Subfields: Repeating sets of information items

Mnemonic	ALERT_0	Conditionality	M↑
		Status	New-Active
Description	Repeating subfield for Alert.		
Field Min	n/a	Occur Min	1
Field Max	n/a	Occur Max	*
Char Types	n/a	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	EBTS 4.0		
XML Level 1	dod-ebts:Alert	Cardinality	0...*
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.350_1

Alert

Alert Function

Mnemonic	ALERT_FUN	Conditionality	M↑
		Status	Active
Description	An Indication of whether the alert on a biometric subject is currently set ON or OFF.		
Field Min	1	Occur Min	1
Field Max	1	Occur Max	1
Char Types	N	Special Chars	
Format	n/a	Constraints	n/a
Code List	ON/OFF CODES		
Source	DOD_BTF_TS_EBTS_Nov06_01.02.00		
XML Level 1	dod-ebts:Alert	Cardinality	0...*
XML Level 2	dod-ebts:AlertFunctionCode (0 = OFF, 1 = ON)	Cardinality	1...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.350_2

Alert

Alert Category

Mnemonic	ALERT_CAT	Conditionality	M↑
		Status	Active
Description	The alert category assigned to a biometric subject indicating what action, if any, should be taken regarding the biometric subject if he/she is encountered. BEWL Categorical Watchlist has changed - need to resolve and update (48 categories). Coordinate with BIMA.		
Field Min	1	Occur Min	1
Field Max	1	Occur Max	1
Char Types	N	Special Chars	
Format	n/a	Constraints	n/a
Code List	ALERT CATEGORY CODES		
Source	DOD_BTF_TS_EBTS_Nov06_01.02.00		
XML Level 1	dod-ebts:Alert	Cardinality	0...*
XML Level 2	dod-ebts:AlertCategoryCode	Cardinality	1...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

2.350_3

Alert

Alert Value

Mnemonic	ALERT_VAL	Conditionality	M↑
		Status	Active
Description	The level of interest in a given biometric subject who has been flagged for alert.		
Field Min	1	Occur Min	1
Field Max	1	Occur Max	1
Char Types	N	Special Chars	
Format	n/a	Constraints	n/a
Code List	VALUE CODES		
Source	DOD_BTF_TS_EBTS_Nov06_01.02.00		
XML Level 1	dod-ebts:Alert	Cardinality	0...*
XML Level 2	dod-ebts:AlertLevelCode	Cardinality	1...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.350_4

Alert

Alert Contact

Mnemonic	ALERT_CONTACT			Conditionality	M↑
				Status	Active
Description	The agency and individual contact reference responsible for establishing the alert.				
Field Min	1	Occur Min	1		
Field Max	80	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	DOD_BTF_TS_EBTS_Nov06_01.02.00				
XML Level 1	dod-ebts:Alert			Cardinality	0...*
XML Level 2	dod-ebts:AlertContactName			Cardinality	0...1
XML Level 3	nc:PersonDescriptionText			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.350_5

Alert

Alert Detail

Mnemonic	ALERT_DETAIL			Conditionality	M↑
				Status	Active
Description	Special handling instructions or other information about the individual identified in an alert.				
Field Min	1	Occur Min	0		
Field Max	255	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	DOD_BTF_TS_EBTS_Nov06_01.02.00				
XML Level 1	dod-ebts:Alert			Cardinality	0...*
XML Level 2	dod-ebts:AlertDetailDescriptionText			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.351

Encounter Protection

Mnemonic	EP	Conditionality	O
		Status	Active
Description	The encounter protection fields defined below allow for an incoming submission to identify and conceal associations made with other previously submitted transactions. This set of fields can be used by an individual ORI to either protect or unprotect a single associated match or all associated matches. This field contains information that will be used in the case where a new submission wants the subject's association(s) to be protected or unprotected. Protection of either an individual encounter or multiple encounters will be decided based on the entries in this field. This field contains two subfields and both must be completed if this field is used. DoD EBTS v3.0 identifies Field 2.351 for Encounter Protection. However, Field 2.351 Encounter Protection shall not be configurable by the user or the biometric capturing device i.e., Encounter Protection is for internal use only at this time. Submissions from organizations that must use Encounter Protection should contact BIMA operations and coordinate the use of Encounter Protection with them. It is the responsibility of ABIS to follow the Encounter Protection business rules based on the ORI		
Field Min	Encoding Specific	Occur Min	0
Field Max	Encoding Specific	Occur Max	1
Char Types	n/a	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	DOD_BTF_TS_EBTS_Nov06_01.02.00		
XML Level 1	dod-ebts:EncounterProtection	Cardinality	0...1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

2.351_1

Encounter Protection

Encounter Protection Function

Mnemonic	EP_FUN	Conditionality	M↑
		Status	Active
Description	This field contains information that will be used to determine the action to be taken. It will contain a single numeric value 0=Unprotect, 1=Protect.		
Field Min	1	Occur Min	1
Field Max	1	Occur Max	1
Char Types	N	Special Chars	
Format	n/a	Constraints	n/a
Code List	ENCOUNTER PROTECTION FUNCTION CODES		
Source	DOD_BTF_TS_EBTS_Nov06_01.02.00		
XML Level 1	dod-ebts:EncounterProtection	Cardinality	0...1
XML Level 2	dod-ebts:EncounterProtectionFunctionCode	Cardinality	1...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.351_2

Encounter Protection

Encounter Protection Level

Mnemonic	EP_LEVEL			Conditionality	M↑
				Status	Active
Description	This field contains information that will be used to determine the level of protection being assigned to the subject being searched. This field will contain a single numeric value 0 = Single Encounter, 1 = All Encounter.				
Field Min	1	Occur Min	1		
Field Max	1	Occur Max	1		
Char Types	N	Special Chars			
Format	n/a	Constraints	n/a		
Code List	ENCOUNTER PROTECTION LEVEL CODES				
Source	DOD_BTF_TS_EBTS_Nov06_01.02.00				
XML Level 1	dod-ebts:EncounterProtection			Cardinality	0...1
XML Level 2	dod-ebts:EncounterProtectionLevelCode			Cardinality	1...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.85

Biometric Modality Available

Mnemonic	BIO_MOD_0			Conditionality	0
				Status	Emerging
Description	List the biometric modalities available within a specific designated repository and the identifier assigned to it by the repository if applicable. Part of a response from a submission or search.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	Developed for Blue Force capability. Pending approval				
XML Level 1	dod-ebts:BiometricModality			Cardinality	0...1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.850_0

Biometric Modality Available

Subfields: Repeating sets of information items

Mnemonic	BIO_MOD	Conditionality	O
		Status	Emerging
Description	Repeating subfield for Biometric Modality Available.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	*
Char Types	n/a	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	EBTS 4.0		
XML Level 1	dod-ebts:BiometricModality	Cardinality	0...*
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes

2.850_1

Biometric Modality Available

Modality Type

Mnemonic	MOD_TYPE	Conditionality	O
		Status	Emerging
Description	The type of biometric modality indicated.		
Field Min	3	Occur Min	0
Field Max	6	Occur Max	1
Char Types	A	Special Chars	
Format	n/a	Constraints	n/a
Code List	MODALITY TYPE CODES		
Source	Developed for Blue Force capability. Pending approval		
XML Level 1	dod-ebts:BiometricModality	Cardinality	0...*
XML Level 2	dod-ebts:ModalityTypeCode	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.850_2

Biometric Modality Available

Modality Sub-Type

Mnemonic	MOD_STYPE	Conditionality	O
		Status	Emerging
Description	A more specific type of the particular biometric modality being referenced. For example, finger position code is the Modality Sub-Type of Fingerprint Image, the left or right position of the eye is the Biometric Sub-Type of Iris Image, and subject pose code is the Biometric Sub-Type of a Facial Photo Image.		
Field Min	1	Occur Min	0
Field Max	5	Occur Max	1
Char Types	AN	Special Chars	
Format	n/a	Constraints	n/a
Code List	MODALITY SUB-TYPE CODES		
Source	Developed for Blue Force capability. Pending approval		
XML Level 1	dod-ebts:BiometricModality	Cardinality	0..*
XML Level 2	dod-ebts:ModalitySubTypeCode	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.850_3

Biometric Modality Available

Name of Designated Repository

Mnemonic	MOD_REPO	Conditionality	O
		Status	Emerging
Description	This field contains the numerical designation of the repositories to be searched. Repository numbers are assigned by the CJIS Division. Multiple entries will be separated by the {RS} separator. This information item indicates the repository where the modality is located.		
Field Min	1	Occur Min	0
Field Max	3	Occur Max	1
Char Types	N	Special Chars	
Format	n/a	Constraints	n/a
Code List	DESIGNATED REPOSITORY NAME		
Source	Developed for Blue Force capability. Pending approval		
XML Level 1	dod-ebts:BiometricModality	Cardinality	0..*
XML Level 2	FBI:"ebts:RecordFBIRepositoryCode" /nc:IdentificationID	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.850_4

Biometric Modality Available

Modality Location Originating Agency Identifier

Mnemonic	MOD_LOC	Conditionality	O
		Status	Emerging
Description	The Originating Agency Identifier of the location which has the biometric modality available for the identified biometric subject.		
Field Min	9	Occur Min	1
Field Max	9	Occur Max	1
Char Types	AN	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Developed for Blue Force capability. Pending approval		
XML Level 1	dod-ebts:BiometricModality	Cardinality	0..*
XML Level 2	nc:Agency	Cardinality	0..1
XML Level 3	nc:OrganizationDescriptionText	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.850_5

Biometric Modality Available

Modality Retrieval Identifier Type

Mnemonic	MOD_ID_TYPE	Conditionality	O
		Status	Emerging
Description	The type of identifier used to retrieve the biometric modality e.g. TCN, FNU, DOD, SSN, ISN, GUID, etc. It is up to the Application Profile to determine what the appropriate identifier types should be.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	A	Special Chars	
Format	n/a	Constraints	n/a
Code List	IDENTIFIER TYPE CODES		
Source	Developed for Blue Force capability. Pending approval		
XML Level 1	dod-ebts:BiometricModality	Cardinality	0..*
XML Level 2	dod-ebts:ModalityIdentifierTypeCode	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.850_6

Biometric Modality Available

Modality Retrieval Identifier

Mnemonic	MOD_ID	Conditionality	O
		Status	Emerging
Description	The identifier used to retrieve the biometric modality.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Developed for Blue Force capability. Pending approval		
XML Level 1	dod-ebts:BiometricModality	Cardinality	0..*
XML Level 2	dod-ebts:RetrievalID/nc:IdentificationID	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.850_7

Biometric Modality Available

Comment

Mnemonic	MOD_COM	Conditionality	O
		Status	Emerging
Description	The optional Comment field appears in many record types and may be used to insert free text information. It is not reserved exclusively for log-related information but has historically often been used for this purpose. It is limited to a maximum of 126 characters. This maximum size was established in order to maintain consistency across encodings. The maximum size differed in the 2007 and 2008 versions of the standard.		
Field Min	1	Occur Min	0
Field Max	126	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Developed for Blue Force capability. Pending approval		
XML Level 1	dod-ebts:BiometricModality	Cardinality	0..*
XML Level 2	nc:CommentText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.851

Biometric Modality Request

Mnemonic	BIO_MODR	Conditionality	0
		Status	Emerging
Description	Specify the biometric modality being requested.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Developed for Blue Force capability. Pending approval		
XML Level 1	dod-ebts:BiometricModalityRequest	Cardinality	0...1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes

2.851_1

Biometric Modality Request

Modality Type

Mnemonic	MODR_TYPE	Conditionality	M↑
		Status	Emerging
Description	The type of biometric modality indicated.		
Field Min	3	Occur Min	1
Field Max	6	Occur Max	1
Char Types	A	Special Chars	
Format	n/a	Constraints	n/a
Code List	MODALITY TYPE CODES		
Source	Developed for Blue Force capability. Pending approval		
XML Level 1	dod-ebts:BiometricModalityRequest	Cardinality	0...1
XML Level 2	dod-ebts:ModalityTypeCode	Cardinality	1...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.851_2

Biometric Modality Request

Modality Sub-Type

Mnemonic	MODR_SUBTYPE	Conditionality	O
		Status	Emerging
Description	A more specific type of the particular biometric modality being referenced.		
Field Min	1	Occur Min	0
Field Max	5	Occur Max	1
Char Types	AN	Special Chars	
Format	n/a	Constraints	n/a
Code List	MODALITY SUB-TYPE CODES		
Source	Developed for Blue Force capability. Pending approval		
XML Level 1	dod-ebts:BiometricModalityRequest	Cardinality	0..1
XML Level 2	dod-ebts:SubTypeCode	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.851_3

Biometric Modality Request

Name of Designated Repository

Mnemonic	MODR_REPO	Conditionality	O
		Status	Emerging
Description	This field contains the numerical designation of the repositories to be searched. Repository numbers are assigned by the CJIS Division. Multiple entries will be separated by the {RS} separator. This information item indicates the repository where the modality is located.		
Field Min	1	Occur Min	0
Field Max	3	Occur Max	1
Char Types	N	Special Chars	
Format		Constraints	n/a
Code List	DESIGNATED REPOSITORY NAME		
Source	Developed for Blue Force capability. Pending approval		
XML Level 1	dod-ebts:BiometricModalityRequest	Cardinality	0..1
XML Level 2	dod-ebts:RespositoryCode	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.851_4

Biometric Modality Request

Modality Location Originating Agency Identifier

Mnemonic	MODR_AGENCY	Conditionality	O
		Status	Emerging
Description	The Originating Agency Identifier of the location which has the biometric modality available for the identified biometric subject.		
Field Min	9	Occur Min	1
Field Max	9	Occur Max	1
Char Types	AN	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Developed for Blue Force capability. Pending approval		
XML Level 1	dod-ebts:BiometricModalityRequest	Cardinality	0..1
XML Level 2	nc:Agency	Cardinality	0..1
XML Level 3	nc:OrganizationDescriptionText	Cardinality	1.1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.851_5

Biometric Modality Request

Modality Retrieval Identifier Type

Mnemonic	MODR_ID_TYPE	Conditionality	O
		Status	Emerging
Description	The type of identifier used to retrieve the biometric modality e.g. TCN, FNU, DOD, SSN, ISN, GUID, etc. It is up to the Application Profile to determine what the appropriate identifier types should be.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	A	Special Chars	
Format	n/a	Constraints	n/a
Code List	IDENTIFIER TYPE CODES		
Source	Developed for Blue Force capability. Pending approval		
XML Level 1	dod-ebts:BiometricModalityRequest	Cardinality	0..1
XML Level 2	dod-ebts:ModalityIdentifierCode	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.851_6

Biometric Modality Request

Modality Retrieval Identifier

Mnemonic	MODR_ID	Conditionality	O		
		Status	Emerging		
Description	The identifier used to retrieve the biometric modality.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	Developed for Blue Force capability. Pending approval				
XML Level 1	dod-ebts:BiometricModalityRequest		Cardinality	0...1	
XML Level 2	dod-ebts:ModalityRetrievalID/nc:IdentificationID		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.851_7

Biometric Modality Request

Requested Image Quantity

Mnemonic	MODR_QUAL	Conditionality	O		
		Status	Emerging		
Description	The maximum number of images the requester desires to receive.				
Field Min	0	Occur Min	0		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	Developed for Blue Force capability. Pending approval				
XML Level 1	dod-ebts:BiometricModalityRequest		Cardinality	0...1	
XML Level 2	dod-ebts:ImageQuantity		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.852

Biometric Subject Body Build

Mnemonic	SUBJ_BUILD		Conditionality	0	
			Status	Emerging	
Description	The physique of an individual.				
Field Min	1		Occur Min	0	
Field Max	1		Occur Max	1	
Char Types	A		Special Chars		
Format	n/a		Constraints	n/a	
Code List	BODY BUILD CODES				
Source	Developed for BAT V5 AP. Pending approval.				
XML Level 1	nc:PersonBuild		Cardinality	0...1	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.853

Biometric Subject Education

Mnemonic	SUBJ_ED		Conditionality	0	
			Status	Emerging	
Description	The highest level of education the biometric subject has obtained.				
Field Min	2		Occur Min	0	
Field Max	2		Occur Max	1	
Char Types	N		Special Chars		
Format	n/a		Constraints	n/a	
Code List	EDUCATION CODES				
Source	Developed for BAT V5 AP. Pending approval.				
XML Level 1	dod-ebts:BiometricSubjEducation		Cardinality	0...1	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.854

Collection Unit

Mnemonic	SUBJ_SPEC		Conditionality	0			
			Status	Emerging			
Description	Information regarding the unit that collected the biometric sample.						
Field Min	n/a	Occur Min	0				
Field Max	n/a	Occur Max	1				
Char Types	n/a	Special Chars					
Format	n/a	Constraints	n/a				
Code List							
Source	Developed for BAT V5 Application Profile. Pending approval.						
XML Level 1	dod-ebts:BiometricCollectionUnit		Cardinality	0...1			
XML Level 2			Cardinality				
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.854_1

Collection Unit

Superior Unit

Mnemonic	SUBJ_SPEC_VAL		Conditionality	M↑			
			Status	Emerging			
Description	The name of the superior unit.						
Field Min	1	Occur Min	1				
Field Max	50	Occur Max	1				
Char Types	U	Special Chars					
Format	n/a	Constraints	n/a				
Code List							
Source	Developed for BAT V5 Application Profile. Pending approval.						
XML Level 1	dod-ebts:BiometricCollectionUnit		Cardinality	0...1			
XML Level 2	dod-ebts:SuperiorUnitDescriptor		Cardinality	1..1			
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.854_2

Collection Unit

SubSuperior Unit

Mnemonic	SUBJ_SPEC_PRO			Conditionality	0
				Status	Emerging
Description	The name of the sub superior unit.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	Developed for BAT V5 Application Profile. Pending approval.				
XML Level 1	dod-ebts:BiometricCollectionUnit			Cardinality	0..1
XML Level 2	dod-ebts:SubSuperiorUnitDescription			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.855

Military Association

Mnemonic	MIL_ASSOC			Conditionality	0
				Status	Emerging
Description	The military branch that the subject is affiliated with. The set consists of the country that the military branch belongs in, the name of the military branch, the subject's rank/grade, and an indicator regarding if the subject is active or inactive in the military branch.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	Developed for BAT V5 Application Profile. Pending approval.				
XML Level 1	dod-ebts:MilitaryAssoc			Cardinality	0..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.855_1

Military Association

Military Branch Country Code

Mnemonic	MIL_CNTRY	Conditionality	M↑
		Status	Emerging
Description	The country the military branch belongs in.		
Field Min	2	Occur Min	1
Field Max	3	Occur Max	1
Char Types	AN	Special Chars	
Format	n/a	Constraints	n/a
Code List	GENC ALPHA3 CODES		
Source	Developed for BAT V5 Application Profile. Pending approval.		
XML Level 1	dod-ebts:MilitaryAssoc	Cardinality	0..1
XML Level 2	dod-ebts:MilitaryCountryGENCCode	Cardinality	1..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.855_2

Military Association

Military Branch Name

Mnemonic	MIL_BRNCH	Conditionality	M↑
		Status	Emerging
Description	The name of the military branch that the subject belongs in. E.G. Army, Navy, Air Force, Marine Corps. If this does not apply, then enter "Unknown".		
Field Min	1	Occur Min	1
Field Max	50	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Developed for BAT V5 Application Profile. Pending approval.		
XML Level 1	dod-ebts:MilitaryAssoc	Cardinality	0..1
XML Level 2	nc:MilitaryBranchName	Cardinality	1..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.855_3

Military Association

Rank Grade Code

Mnemonic	MIL_RANK			Conditionality	O
				Status	Emerging
Description	The military rank or civilian rank of the person. Rank/Grade Codes of the Military Branch of the Country indicated.				
Field Min	1	Occur Min	0		
Field Max	20	Occur Max	1		
Char Types	ANS	Special Chars			
Format	n/a	Constraints	n/a		
Code List	MILITARY RANK GRADE CODES				
Source	Developed for BAT V5 Application Profile. Pending approval.				
XML Level 1	dod-ebts:MilitaryAssoc			Cardinality	0...1
XML Level 2	dod-ebts:MilitaryRankCode			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.855_4

Military Association

Military Active Indicator

Mnemonic	MIL_IND			Conditionality	O
				Status	Emerging
Description	Indicator whether the subject is active or inactive in the associated military.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	n/a		
Code List	MILITARY ACTIVE INDICATOR CODES				
Source	Developed for BAT V5 Application Profile. Pending approval.				
XML Level 1	dod-ebts:MilitaryAssoc			Cardinality	0...1
XML Level 2	dod-ebts:MilitaryIndicator			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.856

Previous Transaction

Identification

Mnemonic	PREV_TRAN	Conditionality	O
		Status	Emerging
Description	The set shall contain a transaction identifier from an earlier submission. One usage might be to obtain the current transaction status. Another usage might be to request cancellation of the transaction. Different types of identifiers might be used to reference the transaction.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Developed for Blue Force capability. Pending approval.		
XML Level 1		Cardinality	0..1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.856_1

Previous Transaction

Identifier Type

Mnemonic	PREV_TRAN_1	Conditionality	M↑
		Status	Emerging
Description	The category of the identifier such as TCN, EncounterID, etc. used to identify a previous transaction.		
Field Min	1	Occur Min	1
Field Max	20	Occur Max	1
Char Types	A	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Developed for Blue Force capability. Pending approval.		
XML Level 1	dod-ebts:PreviousTransaction	Cardinality	0..1
XML Level 2	nc:ActivityCategoryText	Cardinality	1..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.856_2

Previous Transaction

Previous Transaction Identifier

Mnemonic	PREV_TRAN_2	Conditionality	M↑
		Status	Emerging
Description	The value of the identifier used to identify a previous transaction.		
Field Min	1	Occur Min	1
Field Max	100	Occur Max	1
Char Types	ANS	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Developed for Blue Force capability. Pending approval.		
XML Level 1	dod-ebts:PreviousTransaction	Cardinality	0...1
XML Level 2	dod-ebts:PreviousActivity/nc:IdentificationID	Cardinality	1..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.856_3

Previous Transaction

Transaction Association

Mnemonic	PREV_TRAN_3	Conditionality	O
		Status	New-Emerging
Description	An augmentation point for the previous activity.		
Field Min	1	Occur Min	0
Field Max	100	Occur Max	1
Char Types	ANS	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Added in NEIM Core to nc:PreviousActivity		
XML Level 1	dod-ebts:PreviousTransaction	Cardinality	0...1
XML Level 2	nc:PreviousActivityAssociationAugmentationPoint	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.858

Vendor Software

Mnemonic	SOFT_VEN		Conditionality	0			
			Status	Emerging			
Description	Information regarding the software application provided by vendor. The set consists of Software Vendor Name, Software Application Name and Software Application Version Number.						
Field Min	n/a	Occur Min	0				
Field Max	n/a	Occur Max	1				
Char Types	n/a	Special Chars					
Format	n/a	Constraints	n/a				
Code List							
Source	Developed for BAT V5 Application Profile.						
XML Level 1	dod-ebts:VendorSoftware		Cardinality	0...1			
XML Level 2			Cardinality				
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.858_0

Vendor Software

Subfields: Repeating sets of information items

Mnemonic	SOFT_VEN_0		Conditionality	M↑			
			Status	Emerging			
Description	Repeating subfield for Vendor Software.						
Field Min	n/a	Occur Min	1				
Field Max	n/a	Occur Max	99				
Char Types	n/a	Special Chars					
Format	n/a	Constraints	n/a				
Code List							
Source	EBTS 4.0						
XML Level 1	dod-ebts:VendorSoftware		Cardinality	1..99			
XML Level 2			Cardinality				
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.858_1

Vendor Software

Software Vendor Name

Mnemonic	SOFT_VEN_1			Conditionality	M↑
				Status	Emerging
Description	The name of the software vendor e.g. Microsoft.				
Field Min	1	Occur Min	1		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	Developed for BAT V5 Application Profile.				
XML Level 1	dod-ebts:VendorSoftware			Cardinality	1..1
XML Level 2	dod-ebts:SoftwareVendorNameText			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.858_2

Vendor Software

Software Application Name

Mnemonic	SOFT_VEN_2			Conditionality	O
				Status	Emerging
Description	The name of the software application e.g. Excel.				
Field Min	1	Occur Min	1		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	Developed for BAT V5 Application Profile.				
XML Level 1	dod-ebts:VendorSoftware			Cardinality	0..1
XML Level 2	nc:SoftwareName			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.858_3

Vendor Software

Software Application Version Number

Mnemonic	SOFT_VEN_3			Conditionality	0
				Status	Emerging
Description	The number that specifies the software vendor application version number. May consist the Major, Minor, Revision and Build number the vendor assigned to the application.				
Field Min	1	Occur Min	1		
Field Max	255	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	Developed for BAT V5 Application Profile.				
XML Level 1	dod-ebts:VendorSoftware			Cardinality	0..1
XML Level 2	nc:softwareVersionText			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.859

Biometric Subject Previous Residence

Mnemonic	SUBJ_PREV_RESIDE			Conditionality	0
				Status	Emerging
Description	The addresses of the previous residence of the biometric subject.				
Field Min		Occur Min	0		
Field Max		Occur Max	1		
Char Types	n/a	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	Developed for BAT V5 Application Profile.				
XML Level 1	dod-ebts:BiometricSubjectPreviousResidence			Cardinality	PersonPreviousResidenceLocation
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.859_1

Biometric Subject Previous Residence

Address Line 1

Mnemonic	SUBJ_PREV_RESIDE_1			Conditionality	0		
				Status	Emerging		
Description	The street, including both number and name.						
Field Min	1		Occur Min	0			
Field Max	50		Occur Max	1			
Char Types	U		Special Chars				
Format	n/a		Constraints	n/a			
Code List							
Source	Developed for BAT V5 Application Profile.						
XML Level 1	dod-ebts:BiometricSubjectPreviousResidence			Cardinality	0...1		
XML Level 2	nc:StreetFullText			Cardinality	0..1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.859_2

Biometric Subject Previous Residence

Address Line 2

Mnemonic	SUBJ_PREV_RESIDE_2			Conditionality	0		
				Status	Emerging		
Description	Additional information about the street e.g. apt #.						
Field Min	1		Occur Min	0			
Field Max	50		Occur Max	1			
Char Types	U		Special Chars				
Format	n/a		Constraints	n/a			
Code List							
Source	Developed for BAT V5 Application Profile.						
XML Level 1	dod-ebts:BiometricSubjectPreviousResidence			Cardinality	0...1		
XML Level 2	nc:StreetFullText			Cardinality	0..1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.859_3

Biometric Subject Previous Residence

City

Mnemonic	SUBJ_PREV_RESIDE_3			Conditionality	0		
				Status	Emerging		
Description	Name of the city.						
Field Min	1	Occur Min	0				
Field Max	50	Occur Max	1				
Char Types	U	Special Chars					
Format	n/a	Constraints	n/a				
Code List							
Source	Developed for BAT V5 Application Profile.						
XML Level 1	dod-ebts:BiometricSubjectPreviousResidence			Cardinality	0..1		
XML Level 2	nc:LocationCityName			Cardinality	0..1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.859_4

Biometric Subject Previous Residence

State / Province

Mnemonic	SUBJ_PREV_RESIDE_4			Conditionality	0		
				Status	Emerging		
Description	The state, province or subdivision of a location.						
Field Min	1	Occur Min	0				
Field Max	50	Occur Max	1				
Char Types	U	Special Chars					
Format	n/a	Constraints	n/a				
Code List							
Source	Developed for BAT V5 Application Profile.						
XML Level 1	dod-ebts:BiometricSubjectPreviousResidence			Cardinality	0..1		
XML Level 2	nc:LocationStateName			Cardinality	0..1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.859_5

Biometric Subject Previous Residence

Country Code

Mnemonic	SUBJ_PREV_RESIDE_5			Conditionality	O
				Status	Emerging
Description	The GENC alpha3 country code. The DoD EBTS 4.0 default for this field is the GENC three character alpha codelist (genc:CountryAlpha3CodeType).				
Field Min	3	Occur Min	0		
Field Max	3	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	Developed for BAT V5 Application Profile.				
XML Level 1	dod-ebts:BiometricSubjectPreviousResidence			Cardinality	0..1
XML Level 2	nc:LocationCountryGENCCode			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.859_6

Biometric Subject Previous Residence

Postal Code

Mnemonic	SUBJ_PREV_RESIDE_6			Conditionality	O
				Status	Emerging
Description	Alphanumeric code assigned to groups of addresses by various national postal systems throughout the world.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	ANS	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	Developed for BAT V5 Application Profile.				
XML Level 1	dod-ebts:BiometricSubjectPreviousResidence			Cardinality	0..1
XML Level 2	nc:LocationPostalCode			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.859_7

Biometric Subject Previous Residence

Neighborhood / District

Mnemonic	SUBJ_PREV_RESIDE_7			Conditionality	O		
				Status	Emerging		
Description	A geographically localized community within a larger city, town or suburb.						
Field Min	1		Occur Min	0			
Field Max	50		Occur Max	1			
Char Types	U		Special Chars				
Format	n/a		Constraints	n/a			
Code List							
Source	Developed for BAT V5 Application Profile.						
XML Level 1	dod-ebts:BiometricSubjectPreviousResidence			Cardinality	0...1		
XML Level 2	nc:LocaleNeighborhoodName			Cardinality	0..1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.859_8

Biometric Subject Previous Residence

Village

Mnemonic	SUBJ_PREV_RESIDE_8			Conditionality	O		
				Status	Emerging		
Description	Small population unit, typically rural, held together by common economic and political ties.						
Field Min	1		Occur Min	0			
Field Max	50		Occur Max	1			
Char Types	U		Special Chars				
Format	n/a		Constraints	n/a			
Code List							
Source	Developed for BAT V5 Application Profile.						
XML Level 1	dod-ebts:BiometricSubjectPreviousResidence			Cardinality	0...1		
XML Level 2	dod-ebts:LocationVillageName			Cardinality	0..1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.859_9

Biometric Subject Previous Residence

Address Validity

Mnemonic	SUBJ_PREV_RESIDE_9		Conditionality	O	
			Status	Emerging	
Description	This field defines the validity of the address information.				
Field Min	3		Occur Min	0	
Field Max	3		Occur Max	1	
Char Types	A		Special Chars		
Format	n/a		Constraints	n/a	
Code List	VALIDITY CODES				
Source	Developed for BAT V5 Application Profile.				
XML Level 1	dod-ebts:BiometricSubjectPreviousResidence			Cardinality	0..1
XML Level 2	dod-ebts:LocationAddressValidityCode			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.859_10

Biometric Subject Previous Residence

Start Date

Mnemonic	SUBJ_PREV_RESIDE_10		Conditionality	O	
			Status	Emerging	
Description	The date that the subject began residing at this address.				
Field Min	Encoding Specific		Occur Min	0	
Field Max	Encoding Specific		Occur Max	1	
Char Types	N		Special Chars		
Format	YYYYMMDD		Constraints	n/a	
Code List					
Source	Developed for BAT V5 Application Profile.				
XML Level 1	dod-ebts:BiometricSubjectPreviousResidence			Cardinality	0..1
XML Level 2	nc:StartDate/nc:Date			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.859_11

Biometric Subject Previous Residence

End Date

Mnemonic	SUBJ_PREV_RESIDE_11		Conditionality	0	
			Status	Emerging	
Description	The date that the subject ceased to reside at this address.				
Field Min	Encoding Specific		Occur Min	0	
Field Max	Encoding Specific		Occur Max	1	
Char Types	N		Special Chars		
Format	YYYYMMDD		Constraints	n/a	
Code List					
Source	Developed for BAT V5 Application Profile.				
XML Level 1	dod-ebts:BiometricSubjectPreviousResidence		Cardinality	0...1	
XML Level 2	nc:EndDate/nc:Date		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.201

Number of Images Requested

Mnemonic	NIR		Conditionality	0	
			Status	Emerging	
Description	This optional field contains the number of maximum candidate images the submitter desires to receive in response to a biometric Investigative search request for a given candidate list. If multiple candidate lists are to be returned the NIR value applies to each. If NIR is omitted in a biometric investigative search request, it defaults to 20. This field is also found in the responses to a biometric Investigative search where it reflects the actual number of candidates with image returned in the CNL field for the entire concatenated list.				
Field Min	1		Occur Min	0	
Field Max	2		Occur Max	1	
Char Types	N		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordImagesRequestedQuantity		Cardinality	0...1	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.2022

Contributor Assigned Identification Number

Mnemonic	CIDN		Conditionality	O	
			Status	Emerging	
Description	This field is the unique number assigned to a single biographic search by the contributor. This field shall contain ten bytes of alphanumeric data. This is a field in a Type-2 biographic search request EQHR.				
Field Min	10	Occur Min	0		
Field Max	10	Occur Max	1		
Char Types	AN	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionActivity		Cardinality	0...1	
XML Level 2	fbi-ebts:ContributorAssignedIdentificationNumber/nc:IdentificationID		Cardinality	0...1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.2023

Supplementary Identity Information

Mnemonic	SII		Conditionality	O	
			Status	Emerging	
Description	This field will contain identity information not within the scope of the standard NGI Identity History Summary. The format and content of the information in this field may vary for different transactions.				
Field Min	4	Occur Min	0		
Field Max	10000	Occur Max	1		
Char Types	ANS	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionData		Cardinality	0...1	
XML Level 2	fbi-ebts:TransactionResponseData (0...1)/fbi-ebts:TransactionCandidateList(0...3)		Cardinality	0...1	
XML Level 3	fbi-ebts:TransactionSupplementaryIdentityInformationText		Cardinality	0...1	
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.2024

Hit Type Indicator

Mnemonic	HTI		Conditionality	0	
			Status	Emerging	
Description	This field will contain a code for the type of hit that generated an unsolicited notification. In the future, a fixed list of values will be created to populate this field. This field will initially be used for the UHN TOT for RISC Notifications. The value will be "RISC" for this initial use.				
Field Min	1	Occur Min	0		
Field Max	10	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	n/a		
Code List	HIT TYPE				
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionData		Cardinality	0...1	
XML Level 2	fbi-ebts:TransactionResponseData (0...1)		Cardinality	0...1	
XML Level 3	fbi-ebts:TransactionHitCategoryCode		Cardinality	0...1	
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.2028

Biometric Image Description

Mnemonic	BID		Conditionality	0	
			Status	Emerging	
Description	This repeating set contains information about biometric images the user is requesting in the submission. Each repeating set consists of the following subfields: 1. UCN of the identity or latent record, 2. IMT image type of the image to be retrieved, 3. BSI of the biometric set to be retrieved, 4. FNR is the fingerprint or palmprint position code of the image to be retrieved, 5. PPD of the supplemental image to be retrieved, E. PPD of the supplemental image to be retrieved when FNR equals supplemental. F. POS of a face image, G. SMT code for a scar, mark, or tattoo image.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionData (0...1)/fbi-ebts:TransactionBiometricImagesRequested (0...1)		Cardinality	0...1	
XML Level 2	fbi-ebts:BiometricImageDescription		Cardinality	0...1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.2028_0

Biometric Image Description

Subfields: Repeating sets of information items

Mnemonic	BID_0			Conditionality	O
				Status	Emerging
Description	Repeating subfield for Biometric Image Description.				
Field Min	n/a	Occur Min	1		
Field Max	n/a	Occur Max	1000		
Char Types	n/a	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	EBTS 4.0				
XML Level 1	fbi-ebts:RecordTransactionData (0...1)/fbi-ebts:TransactionBiometricImagesRequested (0...1)			Cardinality	0...1
XML Level 2	fbi-ebts:BiometricImageDescription			Cardinality	0...1000
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.2028_1

Biometric Image Description

FBI Number/UCN

Mnemonic	SI			Conditionality	O
				Status	Emerging
Description	SI (Subject Identifier) of the identity or latent record.				
Field Min	1	Occur Min	1		
Field Max	50	Occur Max	1		
Char Types	ANS	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionData (0...1)/fbi-ebts:TransactionBiometricImagesRequested (0...1)			Cardinality	0...1
XML Level 2	fbi-ebts:BiometricImageDescription			Cardinality	0...1000
XML Level 3	j:PersonFBIIdentification/nc:IdentificationID			Cardinality	1...1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.2028_2

Biometric Image Description

Image Type

Mnemonic	IMT			Conditionality	M↑
				Status	Emerging
Description	The Image Type information items can be used to specify which types of biometric sets are requested. The list of IMT values to be used in an electronic latent submittal to identify the Type-7 or Type-13 records present in Biometric Image code.				
Field Min	1	Occur Min	0		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars			
Format	n/a	Constraints	IMT = 1, 2, 3 or 4; integer		
Code List	BIOMETRIC IMAGE				
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionData (0...1)/fbi-ebts:TransactionBiometricImagesRequested (0...1)			Cardinality	0...1
XML Level 2	fbi-ebts:BiometricImageDescription			Cardinality	0...1000
XML Level 3	fbi-ebts:BiometricImageCategoryCode			Cardinality	0...1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.2028_3

Biometric Image Description

Biometric Set Identifier

Mnemonic	BSI			Conditionality	O
				Status	Emerging
Description	Code used to identify the specific biometric set being requested. If the BSI (2.2028_3) information item is not present, the representative biometric set(s) are retrieved for the identity specified in the Subject Identifier (SI) item. The representative set for fingerprints will be a composite fingerprint set of images, while the representative set for palm prints or supplemental fingerprint and palm print will be the latest set enrolled.				
Field Min	4	Occur Min	0		
Field Max	24	Occur Max	1		
Char Types	N	Special Chars			
Format	n/a	Constraints	integer		
Code List	BSI				
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionData (0...1)/fbi-ebts:TransactionBiometricImagesRequested (0...1)			Cardinality	0...1
XML Level 2	fbi-ebts:BiometricImageDescription			Cardinality	0...1000
XML Level 3	fbi-ebts:BiometricSetID			Cardinality	0...1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.2028_4

Biometric Image Description

Friction Ridge Position Requested

Mnemonic	FNR			Conditionality	0		
				Status	Emerging		
Description	The friction ridge number requested.						
Field Min	2		Occur Min	0			
Field Max	2		Occur Max	1			
Char Types	N		Special Chars				
Format	n/a		Constraints	fingerprint or palmprint position code			
Code List	FINGER POSITION CODES and PALM POSITION CODES						
Source	NGI-DOC-01078-10.0						
XML Level 1	fbi-ebts:RecordTransactionData (0...1)/fbi-ebts:TransactionBiometricImagesRequested (0...1)			Cardinality	0...1		
XML Level 2	fbi-ebts:BiometricImageDescription			Cardinality	0...1000		
XML Level 3	biom_1:FrictionRidgePositionCode			Cardinality	0...1		
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.2028_5

Biometric Image Description

Print Position Descriptors

Mnemonic	PPD			Conditionality	0		
				Status	Emerging		
Description	This field is used to specify which Supplemental Fingerprint and Palm Print images are being requested. This PPD is a subfield to fields of Type Set. This subfield will be present if and only if the subfield Friction ridge Generalized Position code FGP or the Friction ridge Numbers Requested FNR code "19" appears in the Set field. These PPD subfields have no subfields unlike PPD 2.2030. This field shall consist of two mandatory information items. The first is the Probable Decimal finger Position code 0-10 taken from the ANSI/NIST-ITL specification. But for the finger position it must be a two character numeric; implying a leading zero for positions 0 thru 9. The second code information item is the Finger Image Code; it also is taken from the ANSI/NIST-ITL specification to indicate the portion of the EJI or tip image. There may be up to 8 such images for a single finger, but NGI only expects the values of EJI. Both the probable decimal friction ridge code and the image code are concatenated into 1 information item without any separator.						
Field Min	5		Occur Min	0			
Field Max	5		Occur Max	1			
Char Types	AN		Special Chars				
Format	n/a		Constraints	n/a			
Code List	FINGER POSITION CODES and PALM POSITION CODES						
Source	NGI-DOC-01078-10.0						
XML Level 1	fbi-ebts:RecordTransactionData (0...1)/fbi-ebts:TransactionBiometricImagesRequested (0...1)			Cardinality	0...1		
XML Level 2	fbi-ebts:BiometricImageDescription			Cardinality	0...1000		
XML Level 3	biom_1:FrictionRidgePositionCode			Cardinality	0...1		
XML Level 4	fbi-ebts:PrintPositionDescriptors (0...1)/biom_1:FingerPositionCode, fbi-ebts:FingerImageCodes (1...1)			Cardinality	0...1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.2028_6

Biometric Image Description

Pose Code

Mnemonic	POS	Conditionality	O
		Status	New-Emerging
Description	The POS (2.2028_6) information item specifies the subject pose code of the facial photo image to be retrieved.		
Field Min	1	Occur Min	0
Field Max	1	Occur Max	1
Char Types	A	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	NGI-DOC-01078-10.0		
XML Level 1	fbi-ebts:RecordTransactionData (0...1)/fbi-ebts:TransactionBiometricImagesRequested (0...1)	Cardinality	0...1
XML Level 2	fbi-ebts:BiometricImageDescription	Cardinality	0...1000
XML Level 3	biom_1:FacelImageSubjectPoseCode	Cardinality	0...1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.2028_7

Biometric Image Description

SMT Code

Mnemonic	SMT	Conditionality	O
		Status	New-Emerging
Description	SMT code for a scar, mark, or tattoo image. The SMT is required when an SMT image is to be retrieved.		
Field Min	3	Occur Min	0
Field Max	10	Occur Max	1
Char Types	A	Special Chars	
Format	n/a	Constraints	n/a
Code List	SMT DESCRIPTORS		
Source	NGI-DOC-01078-10.0		
XML Level 1	fbi-ebts:RecordTransactionData (0...1)/fbi-ebts:TransactionBiometricImagesRequested (0...1)	Cardinality	0...1
XML Level 2	fbi-ebts:BiometricImageDescription	Cardinality	0...1000
XML Level 3	j:PhysicalFeatureCategoryCode	Cardinality	0...1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.2029

Biometric Set Identifier

Mnemonic	BSI			Conditionality	O		
				Status	Emerging		
Description	This numeric field will uniquely identify each biometric image set or photo, such as a facial photo, a fingerprint set, a palm print set, or a supplemental print set.						
Field Min	4			Occur Min	0		
Field Max	24			Occur Max	1000		
Char Types	N			Special Chars			
Format	n/a			Constraints	n/a		
Code List							
Source	NGI-DOC-01078-10.0						
XML Level 1	fbi-ebts:BiometricSetID			Cardinality	0...1000		
XML Level 2				Cardinality			
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.2030

Print Position Descriptors

Mnemonic	PPD			Conditionality	O		
				Status	Emerging		
Description	This field will be present if and only if the finger position code "19" appears in Field 2.074. This field will consist of two mandatory information items: The first is the probable integer finger position code 0-10 taken from finger position table. The second information item is the code taken from Table P-1, found in Appendix P of NGI-DOC-01078-10.0, to indicate the portion of the EJI or tip image that is a part of the transaction.						
Field Min	n/a			Occur Min	0		
Field Max	n/a			Occur Max	10		
Char Types	n/a			Special Chars			
Format	n/a			Constraints	n/a		
Code List							
Source	NGI-DOC-01078-10.0						
XML Level 1	fbi-ebts:RecordTransactionData			Cardinality	0...1		
XML Level 2	fbi-ebts:TransactionPrintPositionDescriptors			Cardinality	0...10		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.2030_1

Print Position Descriptors

Friction Ridge Generalized Position

Mnemonic	FGP			Conditionality	M↑
				Status	Emerging
Description	This field is used in Record types dealing with friction ridges. It specifies which friction ridge biometric sample was collected. Use finger position code 0-10.				
Field Min	1	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars			
Format	n/a	Constraints	0 <= FGP <= 10; integer		
Code List	FINGER COMBINATION CODES				
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionData	Cardinality	0...1		
XML Level 2	fbi-ebts:TransactionPrintPositionDescriptors	Cardinality	0...10		
XML Level 3	biom_1:FingerPositionCode	Cardinality	1...1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.2030_2

Print Position Descriptors

Finger Image Code

Mnemonic	FIC			Conditionality	M↑
				Status	Emerging
Description	A code to indicate the portion of the EJI or tip image that is a part of the transaction. See Look Up Codes for valid entries. Only EJI, TIP, FV1, FV2, FV3, FV4, PRX, DST, MED are allowed.				
Field Min	3	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	AN	Special Chars			
Format	n/a	Constraints	n/a		
Code List	PRINT POSITION DISRIPTOR				
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionData	Cardinality	0...1		
XML Level 2	fbi-ebts:TransactionPrintPositionDescriptors	Cardinality	0...10		
XML Level 3	fbi-ebts:FingerImageCode	Cardinality	1...1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.2031

Biometric Image Available

Mnemonic	BIA			Conditionality	0
				Status	Emerging
Description	This field will indicate the existence of available biometric images (fingerprint, palmprint, supplemental print, facial photo, and SMT photo) for an Identity in the NGI AFIS/FBI repository. Allowable BIA values are listed in the codelist table. The following abbreviations are used in the table for each image type: FP – Fingerprint, PP – Palmprint, SP – Supplemental Print, PHF – Photo Facial, and PSMT – Photo Scar, Mark, & Tattoo.				
Field Min	1	Occur Min	0		
Field Max	2	Occur Max	6		
Char Types	N	Special Chars			
Format	n/a	Constraints	0 <= BIA <= 31; integer		
Code List	BIA				
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordSubject			Cardinality	0...1
XML Level 2	fbi-ebts:BiometricImageAvailableCode			Cardinality	0...6
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.2032

Audit Trail Record

Mnemonic	ATR			Conditionality	M↑
				Status	Emerging
Description	This repeating record contains the information associated with the dissemination of the owner's images. The FNR and PPD items are present in ATR to identify the image within the biometric set that was disseminated when the entire set was not returned.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionData (0...1)/fbi-ebts:TransactionResponseData (0...1)			Cardinality	0...1
XML Level 2	fbi-ebts:TransactionAuditTrailRecordList			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.2032_0

Audit Trail Record

Subfields: Repeating sets of information items

Mnemonic	ATR_0			Conditionality	M↑
				Status	Emerging
Description	Repeating subfield for Audit Trail Record.				
Field Min	n/a	Occur Min	1		
Field Max	n/a	Occur Max	100		
Char Types	n/a	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	EBTS 4.0				
XML Level 1	fbi-ebts:RecordTransactionData (0...1)/fbi-ebts:TransactionResponseData (0...1)			Cardinality	0...1
XML Level 2	fbi-ebts:TransactionAuditTrailRecordList			Cardinality	0...1
XML Level 3	fbi-ebts:AuditTrailRecord			Cardinality	1...100
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.2032_1

Audit Trail Record

Originating Agency Identifier

Mnemonic	ORI			Conditionality	M↑
				Status	Emerging
Description	The origination field shall contain the ORI identifying the agency or organization submitting the transaction.				
Field Min	9	Occur Min	1		
Field Max	9	Occur Max	1		
Char Types	AN	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionData (0...1)/fbi-ebts:TransactionResponseData (0...1)			Cardinality	0...1
XML Level 2	fbi-ebts:TransactionAuditTrailRecordList			Cardinality	0...1
XML Level 3	fbi-ebts:AuditTrailRecord			Cardinality	1...100
XML Level 4	fbi-ebts:RecordReceivingAgency/nc:IdentificationID			Cardinality	1...1
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-2: User-Defined Descriptive Text

Page 118 of 1037

2.2032_2

Audit Trail Record

Date of Dissemination

Mnemonic	DAT			Conditionality	O
				Status	Emerging
Description	Date the images were disseminated.				
Field Min	8	Occur Min	1		
Field Max	8	Occur Max	1		
Char Types	N	Special Chars			
Format	YYYYMMDD	Constraints	n/a		
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionData (0...1)/fbi-ebts:TransactionResponseData (0...1)			Cardinality	0...1
XML Level 2	fbi-ebts:TransactionAuditTrailRecordList			Cardinality	0...1
XML Level 3	fbi-ebts:AuditTrailRecord			Cardinality	1...100
XML Level 4	fbi-ebts:RecordDisseminationDate/nc:Date			Cardinality	1...1
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.2032_3

Audit Trail Record

TOT of Dissemination

Mnemonic	TOT			Conditionality	O
				Status	Emerging
Description	TOT used to acquire the image set.				
Field Min	3	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionData (0...1)/fbi-ebts:TransactionResponseData (0...1)			Cardinality	0...1
XML Level 2	fbi-ebts:TransactionAuditTrailRecordList			Cardinality	0...1
XML Level 3	fbi-ebts:AuditTrailRecord			Cardinality	1...100
XML Level 4	fbi-ebts:RecordTransactionCategoryCode			Cardinality	1...1
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-2: User-Defined Descriptive Text

Page 119 of 1037

2.2032_4

Audit Trail Record

Biometric Set Identifier Disseminated

Mnemonic	BSI			Conditionality	0		
				Status	Emerging		
Description	BSI of the image disseminated.						
Field Min	4		Occur Min	0			
Field Max	24		Occur Max	1			
Char Types	N		Special Chars				
Format	n/a		Constraints	n/a			
Code List							
Source	NGI-DOC-01078-10.0						
XML Level 1	fbi-ebts:RecordTransactionData (0...1)/fbi-ebts:TransactionResponseData (0...1)			Cardinality	0...1		
XML Level 2	fbi-ebts:TransactionAuditTrailRecordList			Cardinality	0...1		
XML Level 3	fbi-ebts:AuditTrailRecord			Cardinality	1...100		
XML Level 4	fbi-ebts:BiometricSetID			Cardinality	0...1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.2032_5

Audit Trail Record

Image Type Disseminated

Mnemonic	IMT			Conditionality	0		
				Status	Emerging		
Description	Type of image disseminated.						
Field Min	1		Occur Min	0			
Field Max	2		Occur Max	1			
Char Types	N		Special Chars				
Format	n/a		Constraints	n/a			
Code List	BIOMETRIC IMAGE						
Source	NGI-DOC-01078-10.0						
XML Level 1	fbi-ebts:RecordTransactionData (0...1)/fbi-ebts:TransactionResponseData (0...1)			Cardinality	0...1		
XML Level 2	fbi-ebts:TransactionAuditTrailRecordList			Cardinality	0...1		
XML Level 3	fbi-ebts:AuditTrailRecord			Cardinality	1...100		
XML Level 4	fbi-ebts:BiometricImageCategoryCode			Cardinality	0...1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.2032_6

Audit Trail Record

Friction Ridge Position Requested

Mnemonic	FNR			Conditionality	0		
				Status	Emerging		
Description	The friction ridge number requested.						
Field Min	2		Occur Min	0			
Field Max	2		Occur Max	1			
Char Types	N		Special Chars				
Format	n/a		Constraints	Fingerprint and Palmprint position codes			
Code List	FINGER POSITION						
Source	NGI-DOC-01078-10.0						
XML Level 1	fbi-ebts:RecordTransactionData (0...1)/fbi-ebts:TransactionResponseData (0...1)			Cardinality	0...1		
XML Level 2	fbi-ebts:TransactionAuditTrailRecordList			Cardinality	0...1		
XML Level 3	fbi-ebts:AuditTrailRecord			Cardinality	1...100		
XML Level 4	biom_1:FrictionRidgePositionCode			Cardinality	0...1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.2032_7

Audit Trail Record

Print Position Descriptors

Mnemonic	PPD			Conditionality	0		
				Status	Emerging		
Description	This PPD is an information item included within other fields. This item will be present if and only if the Friction ridge Generalized Position code (FGP) or the Friction ridge Number(s) Requested (FNR) code (19) appears in the field. These instances of PPD shall consist of a string containing two mandatory pieces of information. The first is the Probable Decimal finger Position code (0-10) taken from the ANSI/NIST-ITL specification. The finger position must include a leading zero for positions 0 through 9. Both the probable decimal friction ridge code and the image code are concatenated into 1 information item without any separator.						
Field Min	5		Occur Min	0			
Field Max	5		Occur Max	1			
Char Types	AN		Special Chars				
Format	n/a		Constraints	n/a			
Code List							
Source	NGI-DOC-01078-10.0						
XML Level 1	fbi-ebts:RecordTransactionData (0...1)/fbi-ebts:TransactionResponseData (0...1)			Cardinality	0...1		
XML Level 2	fbi-ebts:TransactionAuditTrailRecordList			Cardinality	0...1		
XML Level 3	fbi-ebts:AuditTrailRecord			Cardinality	1...100		
XML Level 4	fbi-ebts:PrintPositionDescriptors/biom_2:FingerPositionCode(1...1), fbi-ebts:PrintPositionDescriptors/fbi-ebts:FingerImageCode(1...1)			Cardinality	0...1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-2: User-Defined Descriptive Text

Page 121 of 1037

2.2032_8

Audit Trail Record

Subject Pose

Mnemonic	POS			Conditionality	O
				Status	New-Emerging
Description	POS of facial image.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionData (0...1)/fbi-ebts:TransactionResponseData (0...1)			Cardinality	0...1
XML Level 2	fbi-ebts:TransactionAuditTrailRecordList			Cardinality	0...1
XML Level 3	fbi-ebts:AuditTrailRecord			Cardinality	1...100
XML Level 4	biom_1:FacialImageSubjectPoseCode			Cardinality	0...1
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.2032_9

Audit Trail Record

NCIC SMT Code

Mnemonic	SMT			Conditionality	O
				Status	New-Emerging
Description	SMT code of SMT images.				
Field Min	3	Occur Min	0		
Field Max	10	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	n/a		
Code List	SMT DESCRIPTORS				
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionData (0...1)/fbi-ebts:TransactionResponseData (0...1)			Cardinality	0...1
XML Level 2	fbi-ebts:TransactionAuditTrailRecordList			Cardinality	0...1
XML Level 3	fbi-ebts:AuditTrailRecord			Cardinality	1...100
XML Level 4	nc:PhysicalFeatureCategoryCode			Cardinality	0...1
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.2033

Candidate Investigative List

Mnemonic	CNL / CAN	Conditionality	0
		Status	Emerging
Description	This field is added to the Investigative search response TOTs, providing a candidate list that supports a multi-biometric type and multi-event repository. The legacy CAN field in the SRL is still supported as well for Fingerprint-only candidate lists. It is possible for the CNL to contain multiple ranked lists concatenated together due to multiple biometric types being searched. For friction ridge, NGI supports three biometric types for a latent investigative search: fingerprint, upper-palm, and lower-palm. Therefore, an SRL can contain one, two, or three ranked lists where the number of candidates in each list is determined by the NCR from the request. Therefore, the maximum number of candidates for an SRL is 3 x NCR. When multiple biometric types are searched, a maximum of NIR images are returned for each type. Therefore, the maximum number of images for an SRL is 3 x NIR. Multiple candidates in traditional encoding will be separated by the {RS} separator.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	NGI-DOC-01078-10.0		
XML Level 1	fbi-ebts:RecordTransactionData (0...1)/fbi-ebts:TransactionResponseData (0...1)	Cardinality	0...1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.2033_0

Candidate Investigative List

Subfields: Repeating sets of information items

Mnemonic	CNL_0 / CAN_0	Conditionality	M↑
		Status	Emerging
Description	Repeating subfield for Candidate Investigative List.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	3
Char Types	n/a	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	EBTS 4.0		
XML Level 1	fbi-ebts:RecordTransactionData (0...1)/fbi-ebts:TransactionResponseData (0...1)	Cardinality	0...1
XML Level 2	fbi-ebts:TransactionCandidateList	Cardinality	0...3
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-2: User-Defined Descriptive Text

Page 123 of 1037

2.2033_1

Candidate Investigative List

FBI Number/UCN

Mnemonic	SI	Conditionality	M↑
		Status	Emerging
Description	The FBI or UCN number assigned by FBI.		
Field Min	1	Occur Min	1
Field Max	50	Occur Max	1
Char Types	ANS	Special Chars	
Format	n/a	Constraints	integer
Code List			
Source	NGI-DOC-01078-10.0		
XML Level 1	fbi-ebts:RecordTransactionData (0...1)/fbi-ebts:TransactionResponseData (0...1)	Cardinality	0...1
XML Level 2	fbi-ebts:TransactionCandidateList	Cardinality	0...3
XML Level 3	fbi-ebts:Candidate	Cardinality	1...99
XML Level 4	j:PersonFBIIdentification/nc:IdentificationID	Cardinality	1...1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.2033_2

Candidate Investigative List

Master Name

Mnemonic	NAM	Conditionality	O
		Status	Emerging
Description	Indicates the name of the subject.		
Field Min	3	Occur Min	0
Field Max	50	Occur Max	1
Char Types	AS	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	NGI-DOC-01078-10.0		
XML Level 1	fbi-ebts:RecordTransactionData (0...1)/fbi-ebts:TransactionResponseData (0...1)	Cardinality	0...1
XML Level 2	fbi-ebts:TransactionCandidateList	Cardinality	0...3
XML Level 3	fbi-ebts:Candidate	Cardinality	1...99
XML Level 4	fbi-ebts:PersonName (0...1), nc:PersonGivenName (0...1), nc:PersonMiddleName(0...1), nc:PersonSurName (1...1)	Cardinality	0...1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.2033_3

Candidate Investigative List

Biometric Set Identifier

Mnemonic	BSI			Conditionality	0		
				Status	Emerging		
Description	This numeric field will uniquely identify a fingerprint set, palmprint set, or a supplemental print set.						
Field Min	4		Occur Min	0			
Field Max	24		Occur Max	1			
Char Types	N		Special Chars				
Format	n/a		Constraints	integer			
Code List	BID						
Source	NGI-DOC-01078-10.0						
XML Level 1	fbi-ebts:RecordTransactionData (0...1)/fbi-ebts:TransactionResponseData (0...1)				Cardinality	0...1	
XML Level 2	fbi-ebts:TransactionCandidateList				Cardinality	0...3	
XML Level 3	fbi-ebts:Candidate				Cardinality	1...99	
XML Level 4	fbi-ebts:BiometricSetID				Cardinality	0...1	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.2033_4

Candidate Investigative List

Image Type

Mnemonic	IMT			Conditionality	0		
				Status	Emerging		
Description	This field identifies the type of image e.g., palmprints, toe prints included in an electronic submittal. The list of IMT values to be used in an electronic latent submittal to identify the Type-7 or Type-13 records present [is listed in the look up codes below].						
Field Min	1		Occur Min	0			
Field Max	2		Occur Max	1			
Char Types	N		Special Chars				
Format	n/a		Constraints	n/a			
Code List	BIOMETRIC IMAGE						
Source	NGI-DOC-01078-10.0						
XML Level 1	fbi-ebts:RecordTransactionData (0...1)/fbi-ebts:TransactionResponseData (0...1)				Cardinality	0...1	
XML Level 2	fbi-ebts:TransactionCandidateList				Cardinality	0...3	
XML Level 3	fbi-ebts:Candidate				Cardinality	1...99	
XML Level 4	fbi-ebts:RecordBiometricImageCategoryCode				Cardinality	0...1	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.2033_5

Candidate Investigative List

Friction Ridge Generalized Position

Mnemonic	FGP		Conditionality	O	
			Status	Emerging	
Description	This field is used in Record types dealing with friction ridges. It specifies which friction ridge biometric sample was collected.				
Field Min	2		Occur Min	0	
Field Max	2		Occur Max	1	
Char Types	N		Special Chars		
Format	n/a		Constraints	1 <= FGP <= 19 or FGP = 33 or 36 or 40 <= FGP <= 50; integer	
Code List	FINGER COMBINATION				
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionData (0...1)/fbi-ebts:TransactionResponseData (0...1)			Cardinality	0...1
XML Level 2	fbi-ebts:TransactionCandidateList			Cardinality	0...3
XML Level 3	fbi-ebts:Candidate			Cardinality	1...99
XML Level 4	biom_1:FrictionRidgePositionCode			Cardinality	0...1
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.2033_6

Candidate Investigative List

Print Position Descriptors [Type-2, subfield to fields of Type Set]

Mnemonic	PPD		Conditionality	O	
			Status	Emerging	
Description	This PPD is an information item included within other fields. This item will be present if and only if the Friction ridge Generalized Position code (FGP) or the Friction ridge Number(s) Requested (FNR) code (19) appears in the field. These instances of PPD shall consist of a string containing two mandatory pieces of information. The first is the Probable Decimal finger Position code (0-10) taken from the ANSI/NIST-ITL specification. The finger position must include a leading zero for positions 0 through 9. Both the probable decimal friction ridge code and the image code are concatenated into 1 information item without any separator.				
Field Min	5		Occur Min	0	
Field Max	5		Occur Max	1	
Char Types	AN		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionData (0...1)/fbi-ebts:TransactionResponseData (0...1)			Cardinality	0...1
XML Level 2	fbi-ebts:TransactionCandidateList			Cardinality	0...3
XML Level 3	fbi-ebts:Candidate			Cardinality	1...99
XML Level 4	fbi-ebts:PrintPositionDescriptors(0...1)/biom_1:FingerPositionCode (1...1), fbi-ebts:PrintPositionDescriptors(0...1)/fbi-ebts:FingerImageCode (1...1)			Cardinality	0...1
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.2033_7

Candidate Investigative List

Match Score

Mnemonic	MSC			Conditionality	O
				Status	Emerging
Description	This field contains the match score from AFIS for each candidate listed in the 2.064 CAN field.				
Field Min	1	Occur Min	0		
Field Max	6	Occur Max	1		
Char Types	N	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionData (0...1)/fbi-ebts:TransactionResponseData (0...1)			Cardinality	0...1
XML Level 2	fbi-ebts:TransactionCandidateList			Cardinality	0...3
XML Level 3	fbi-ebts:Candidate			Cardinality	1...99
XML Level 4	fbi-ebts:CandidateMatchScoreValue			Cardinality	0...1
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.2033_8

Candidate Investigative List

Biometric Image Available

Mnemonic	BIA			Conditionality	O
				Status	Emerging
Description	This field will indicate the existence of available biometric images fingerprint, palmprint, supplemental print, facial photo, and SMT photo for an Identity in the NGI AFIS/FBI repository. Allowable BIA values are shown in the table below. The following abbreviations are used in the table for each image type: FP – Fingerprint, PP – Palmprint, SP – Supplemental Print, PHF – Photo Facial, and PSMT – Photo Scar, Mark, & Tattoo. integer				
Field Min	1	Occur Min	0		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars			
Format	n/a	Constraints	<= BIA <= 31		
Code List	BIA				
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionData (0...1)/fbi-ebts:TransactionResponseData (0...1)			Cardinality	0...1
XML Level 2	fbi-ebts:TransactionCandidateList			Cardinality	0...3
XML Level 3	fbi-ebts:Candidate			Cardinality	1...99
XML Level 4	fbi-ebts:BiometricImageAvailableCode			Cardinality	0...6
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.2033_9

Candidate Investigative List

Name of Designated Repository

Mnemonic	NDR	Conditionality	O
		Status	Emerging
Description	This field contains the numerical designation of the repository to be searched. Repository numbers are assigned by the CJIS Division. Multiple entries in this field will indicate a desire to search more than one repository.		
Field Min	1	Occur Min	0
Field Max	400	Occur Max	1
Char Types	N	Special Chars	
Format	n/a	Constraints	n/a
Code List	DESIGNATED REPOSITORY NAME		
Source	NGI-DOC-01078-10.0		
XML Level 1	fbi-ebts:RecordTransactionData (0...1)/fbi-ebts:TransactionResponseData (0...1)	Cardinality	0...1
XML Level 2	fbi-ebts:TransactionCandidateList	Cardinality	0...3
XML Level 3	fbi-ebts:Candidate	Cardinality	1...99
XML Level 4	fbi-ebts:RecordFBIRepositoryCodenc:IdentificationID	Cardinality	0...100
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes

2.2033_10

Candidate Investigative List

Information Designation Character

Mnemonic	IDC	Conditionality	O
		Status	Emerging
Description	The value of the IDC shall be a sequentially assigned positive integer starting from zero and incremented by one up to a maximum of 99. IDC references are stated in Type-1 Field 1.003 Transaction content (CNT) and shall be used to relate information items in the CNT field of the Type-1 record to the other records in the transaction. Two or more records may share a single IDC solely to identify and link together records that pertain to different representations of the same biometric trait.		
Field Min	2	Occur Min	0
Field Max	2	Occur Max	1
Char Types	N	Special Chars	
Format	n/a	Constraints	0 < IDC < 99; integer
Code List			
Source	NGI-DOC-01078-10.0		
XML Level 1	fbi-ebts:RecordTransactionData (0...1)/fbi-ebts:TransactionResponseData (0...1)	Cardinality	0...1
XML Level 2	fbi-ebts:TransactionCandidateList	Cardinality	0...3
XML Level 3	fbi-ebts:Candidate	Cardinality	1...99
XML Level 4	biom_1:ImageReferencelntification/nc:IdentificationID	Cardinality	0...1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-2: User-Defined Descriptive Text

Page 128 of 1037

2.2033_11

Candidate Investigative List

Note Field

Mnemonic	NOT			Conditionality	0
				Status	Emerging
Description	NOT provides owning ORI information when no image is available for candidate				
Field Min	1	Occur Min	0		
Field Max	1000	Occur Max	1		
Char Types	ANS	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionData (0...1)/fbi-ebts:TransactionResponseData (0...1)			Cardinality	0...1
XML Level 2	fbi-ebts:TransactionCandidateList			Cardinality	0...3
XML Level 3	fbi-ebts:Candidate			Cardinality	1...99
XML Level 4	fbi-ebts:ORIPointOfContactText			Cardinality	0...1
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.2033_12

Candidate Investigative List

Subject Pose

Mnemonic	POS			Conditionality	0
				Status	New-Emerging
Description	A pose of a subject.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	ANS	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionData (0...1)/fbi-ebts:TransactionResponseData (0...1)			Cardinality	0...1
XML Level 2	fbi-ebts:TransactionCandidateList			Cardinality	0...3
XML Level 3	fbi-ebts:Candidate			Cardinality	1...99
XML Level 4	biom_1:FacelImageSubjectPoseCode			Cardinality	0...1
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.2033_13

Candidate Investigative List

SMT Code

Mnemonic	SMT			Conditionality	0
				Status	New-Emerging
Description	SMT provides SMT codes for SMT images.				
Field Min	3	Occur Min	0		
Field Max	10	Occur Max	1		
Char Types	ANS	Special Chars			
Format	n/a	Constraints	n/a		
Code List	SMT DESCRIPTORS				
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionData (0...1)/fbi-ebts:TransactionResponseData (0...1)			Cardinality	0...1
XML Level 2	fbi-ebts:TransactionCandidateList			Cardinality	0...3
XML Level 3	fbi-ebts:Candidate			Cardinality	1...99
XML Level 4	nc:PhysicalFeatureCategoryCode			Cardinality	0...1
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.2034

Unsolved Latent Retained

Mnemonic	ULR			Conditionality	0
				Status	Emerging
Description	This field is used in a Biometric Decision BDEC when the decision is a positive identification and the user requests that the unsolved record is to be retained in the unsolved file. A value of "Y" indicates that the latent record should be retained in the ULF. No value or a value of "N" indicates that the user does not want the unsolved record retained.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	ULR = Y or N		
Code List	Y - Yes or N = No				
Source	NGI-DOC-01078-10.0				
XML Level 1	fbi-ebts:RecordTransactionData			Cardinality	0..1
XML Level 2	fbi-ebts:TransactionUnsolvedLatentFileIndicator			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8003

Biometric Subject Birth Date

Mnemonic	SUBJ_BIRTHDATE		Conditionality	0			
			Status	Active			
Description	The biometric subject's complete date of birth.						
Field Min	n/a	Occur Min	0				
Field Max	n/a	Occur Max	1				
Char Types	n/a	Special Chars					
Format	n/a	Constraints	n/a				
Code List							
Source	BSWG						
XML Level 1	dod-ebts:PersonBirthDate		Cardinality	0...1			
XML Level 2			Cardinality				
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

2.8003_0

Biometric Subject Birth Date

Subfields: Repeating sets of information items

Mnemonic	SUBJ_BIRTHDATE_0		Conditionality	0			
			Status	New-Active			
Description	Repeating subfield for Biometric Subject Birth Date.						
Field Min	n/a	Occur Min	0				
Field Max	n/a	Occur Max	5				
Char Types	n/a	Special Chars					
Format	n/a	Constraints	n/a				
Code List							
Source	EBTS 4.0						
XML Level 1	dod-ebts:PersonBirthDate		Cardinality	0...5			
XML Level 2			Cardinality				
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8003_1

Biometric Subject Birth Date

Birth Date

Mnemonic	DOB		Conditionality	M↑
			Status	Active
Description	The 8 digit calendar date for the person's birth date. Pad any portion of the date with zero's when unknown or not used. For example, 00000000 when the field is mandatory, but the date is unknown. 20100000 when the year is known but month and day are unknown or not used.			
Field Min	Dependent on Encoding	Occur Min	0	
Field Max	Dependent on Encoding	Occur Max	1	
Char Types	ANS	Special Chars		
Format	YYYYMMDD	Constraints	n/a	
Code List				
Source	BSWG			
XML Level 1	dod-ebts:PersonBirthDate	Cardinality	0..5	
XML Level 2	dod-ebts:PersonBirthDate/nc:Date	Cardinality	0..1	
XML Level 3		Cardinality		
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0 Yes DoD EBTS 4.0 Yes

2.8003_2

Biometric Subject Birth Date

Date Validity

Mnemonic	DATEVLD		Conditionality	O
			Status	Active
Description	This field defines the validity of the date. When any part of the date value is padded with zero's, the date validity shall be set to 'EST' for estimated.			
Field Min	3	Occur Min	0	
Field Max	3	Occur Max	1	
Char Types	A	Special Chars		
Format	n/a	Constraints	See Look Up Codes	
Code List	VALIDITY CODES			
Source	BSWG			
XML Level 1	dod-ebts:PersonBirthDate	Cardinality	0..5	
XML Level 2	dod-ebts:DateValidityCode	Cardinality	0..1	
XML Level 3		Cardinality		
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0 Yes DoD EBTS 4.0 Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8003_3

Biometric Subject Birth Date

Calendar Type

Mnemonic	CALTYP	Conditionality	O
		Status	Active
Description	The type of calendar the date is being specified in e.g. Gregorian and Islamic.		
Field Min	1	Occur Min	0
Field Max	1	Occur Max	1
Char Types	A	Special Chars	
Format	n/a	Constraints	See Look Up Codes
Code List	CALENDAR TYPE CODES		
Source	BSWG		
XML Level 1	dod-ebts:PersonBirthDate	Cardinality	0..5
XML Level 2	dod-ebts:CalendarCategoryCode	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

2.8005

Biometric Subject Death Date

Mnemonic	SUBJ_DEATHDATE	Conditionality	O
		Status	Active
Description	The biometric subject's complete date of death. Pad any portion of the date with zero's when unknown or not used. For example, 00000000 when the field is mandatory, but the date is unknown. 20100000 when the year is known but month and day are unknown or not used.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:PersonDeathDate	Cardinality	0..1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8005_1

Biometric Subject Death Date

Death Date

Mnemonic	DOD			Conditionality	M↑
				Status	Active
Description	The 8 digit calendar date for the person's death date.			Dependent on Profile	
Field Min	Dependent on Encoding			Occur Min	1
Field Max	Dependent on Encoding			Occur Max	1
Char Types	ANS			Special Chars	
Format	YYYYMMDD			Constraints	n/a
Code List					
Source	BSWG				
XML Level 1	dod-ebts:PersonDeathDate			Cardinality	0...1
XML Level 2	nc:PersonDeathDate/nc:Date			Cardinality	1...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8005_2

Biometric Subject Death Date

Date Validity

Mnemonic	DATEVLD			Conditionality	O
				Status	Active
Description	This field defines the validity of the date.				
Field Min	3			Occur Min	0
Field Max	3			Occur Max	1
Char Types	A			Special Chars	
Format	n/a			Constraints	See Look Up Codes
Code List	VALIDITY CODES				
Source	BSWG				
XML Level 1	dod-ebts:PersonDeathDate			Cardinality	0...1
XML Level 2	dod-ebts:CalendarValidCode			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8005_3

Biometric Subject Death Date

Calendar Type

Mnemonic	CALTYP	Conditionality	0
		Status	Active
Description	The type of calendar the date is being specified in e.g. Gregorian and Islamic.		
Field Min	1	Occur Min	0
Field Max	1	Occur Max	1
Char Types	A	Special Chars	
Format	n/a	Constraints	See Look Up Codes
Code List	CALENDAR TYPE CODES		
Source	BSWG		
XML Level 1	dod-ebts:PersonDeathDate	Cardinality	0..1
XML Level 2	dod-ebts:CalendarCategoryCode	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

2.8007

Biometric Subject Citizenship

Mnemonic	SUBJ_CTZ	Conditionality	0
		Status	Active
Description	The country of which the biometric subject is a citizen. GENC alpha3 country codes are used. The DoD EBTS 4.0 default for this field is the GENC three character alpha codelist (genc:CountryAlpha3CodeType).		
Field Min	3	Occur Min	0
Field Max	3	Occur Max	1
Char Types	A	Special Chars	
Format		Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	nc:PersonCitizenship	Cardinality	0..5
XML Level 2	nc:LocationCountryGENCCode	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8008

Biometric Subject Ethnic/Racial Characteristic

Mnemonic	SUBJ_RAC		Conditionality	0	
			Status	Active	
Description	The observed or reported ethnic/racial physical characteristic of the biometric subject. Code Mappings from DoD EBTS 3.0 to/from FBI EBTS 9.3. DoD Field 2.8008 Biometric Subject Ethnic/Racial Characteristic map to FBI Field 2.025 Race: A <-> A B <-> B I <-> I W <-> W U <-> U P I -> A H L -> W A R -> U A I -> A A S -> A N A -> I X X -> U				
Field Min	1	Occur Min	0		
Field Max	2	Occur Max	3		
Char Types	A	Special Chars			
Format	n/a	Constraints	n/a		
Code List	ETHNIC/RACIAL CODES				
Source	BSWG				
XML Level 1	dod-ebts:PersonEthnicRacialCharacteristicCode		Cardinality	0...3	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

2.8013

Biometric Subject Blood Type

Mnemonic	SUBJ_BLOOD		Conditionality	0	
			Status	Active	
Description	The blood type of the biometric subject. It consists of Blood Type Value and Blood Type Validity.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:PersonBloodGroup		Cardinality	0...1	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8013_0

Biometric Subject Blood Type

Subfields: Repeating sets of information items

Mnemonic	SUBJ_BLOOD_0			Conditionality	0
				Status	New-Active
Description	Repeating subfield for Biometric Subject Blood Type.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	3		
Char Types	n/a	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	EBTS 4.0				
XML Level 1	dod-ebts:PersonBloodGroup			Cardinality	0...3
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.8013_1

Biometric Subject Blood Type

Blood Type Code

Mnemonic	BLTCD			Conditionality	M↑
				Status	Active
Description	The biometric subject's blood type/classification. Notes: Any of the four main types into which human blood is divided: A, B, AB, and O. Blood types are based on the presence or absence of specific antigens on red blood cells. Also called blood group.				
Field Min	4	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	See Look Up Codes		
Code List	BLOOD TYPE CODES				
Source	BSWG				
XML Level 1	dod-ebts:PersonBloodGroup			Cardinality	0...3
XML Level 2	j:PersonBloodTypeCodeType			Cardinality	1...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8013_2

Biometric Subject Blood Type

Blood Type Validity

Mnemonic	BLTVLD			Conditionality	0
				Status	Active
Description	This field defines the validity of the biometric subject blood type.				
Field Min	3	Occur Min	0		
Field Max	3	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	See Look Up Codes		
Code List	VALIDITY CODES				
Source	BSWG				
XML Level 1	dod-ebts:PersonBloodGroup			Cardinality	0...3
XML Level 2	dod-ebts:PersonBloodTypeValidityCode			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8014

Biometric Subject Vital Status

Mnemonic	SUBJ_VITAL_0			Conditionality	0
				Status	Active
Description	The set of fields to indicate the condition of the biometric subject at the time of biometric sample collection.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:PersonVitalStatus			Cardinality	0...1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8014_0

Biometric Subject Vital Status

Subfields: Repeating sets of information items

Mnemonic	SUBJ_VITAL			Conditionality	0
				Status	New-Active
Description	Repeating subfield for Biometric Subject Vital Status.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	3		
Char Types	n/a	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	EBTS 4.0				
XML Level 1	dod-ebts:PersonVitalStatus			Cardinality	0...3
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.8014_1

Biometric Subject Vital Status

Vital Status Validity

Mnemonic	VSULD			Conditionality	M↑
				Status	Active
Description	This field defines the validity of the vital status of the biometric subject.				
Field Min	3	Occur Min	0		
Field Max	3	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	n/a		
Code List	VALIDITY CODES				
Source	BSWG				
XML Level 1	dod-ebts:PersonVitalStatus			Cardinality	0...3
XML Level 2	dod-ebts:PersonVitalValidityCode			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8014_2

Biometric Subject Vital Status

Vital Status Code

Mnemonic	VSCD			Conditionality	0
				Status	Active
Description	The condition alive, dead of the biometric subject at the time of biometric sample collection. This field should be used only when taking biometric sample of the subject and not for latent sample.				
Field Min	1	Occur Min	1		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	n/a		
Code List	SUBJECT STATUS CODES				
Source	BSWG				
XML Level 1	dod-ebts:PersonVitalStatus			Cardinality	0...3
XML Level 2	dod-ebts:PersonVitalCode			Cardinality	1...1
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8016

Biometric Subject Marital Status

Mnemonic	SUBJ_MARITAL			Conditionality	0
				Status	Active
Description	Marital status of the biometric subject.				
Field Min	3	Occur Min	0		
Field Max	3	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	n/a		
Code List	MARITAL STATUS CODES				
Source	BSWG				
XML Level 1	dod-ebts:PersonMaritalStatusCode			Cardinality	0...1
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8019

Collected Identification

Mnemonic	COL_IDENT		Conditionality	0			
			Status	Active			
Description	Information about an identification issued by an agency. It is a set of fields that consists of Identification Type, Identification Identifier, Issuance Organization, Issuance Office, Issuance Date, Expiration Date, and Comment.						
Field Min	n/a	Occur Min	0				
Field Max	n/a	Occur Max	1				
Char Types	n/a	Special Chars					
Format	n/a	Constraints	n/a				
Code List							
Source	BSWG						
XML Level 1	dod-ebts:CollectedIdentification		Cardinality	0...1			
XML Level 2			Cardinality				
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

2.8019_0

Collected Identification

Subfields: Repeating sets of information items

Mnemonic	COL_IDENT_0		Conditionality	0			
			Status	New-Active			
Description	Repeating subfield for Collected Identification.						
Field Min	n/a	Occur Min	0				
Field Max	n/a	Occur Max	100				
Char Types	n/a	Special Chars					
Format	n/a	Constraints	n/a				
Code List							
Source	EBTS 4.0						
XML Level 1	dod-ebts:CollectedIdentification		Cardinality	0...100			
XML Level 2			Cardinality				
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8019_1

Collected Identification

Collected Identification Type

Mnemonic	CITYP			Conditionality	0
				Status	Active
Description	The category of the collected identification, such as passport, employee id, and internment serial number.				
Field Min	2	Occur Min	0		
Field Max	6	Occur Max	4		
Char Types	A	Special Chars			
Format	n/a	Constraints	n/a		
Code List	IDENTIFICATION CODES				
Source	BSWG				
XML Level 1	dod-ebts:CollectedIdentification			Cardinality	0...100
XML Level 2	dod-ebts:CollectedIdentificationTypeCode			Cardinality	0..4
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8019_2

Collected Identification

Collected Identification Identifier

Mnemonic	CIID			Conditionality	0
				Status	Active
Description	The identifying value for the issued identification. Examples include passport number, ssn, or drivers license number. This field is free form text.				
Field Min	1	Occur Min	0		
Field Max	100	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:CollectedIdentification			Cardinality	0...100
XML Level 2	nc:PersonOtherIdentification/nc:IdentificationID			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8019_3

Collected Identification

Collected Identification Issuance Organization

Mnemonic	CII			Conditionality	O
				Status	Active
Description	The organization or system that issued the identification collected. This field is free form text and contains values such as "US Government", a country name, a state name, an agency name.				
Field Min	1	Occur Min	0		
Field Max	100	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:CollectedIdentification			Cardinality	0...100
XML Level 2	nc:OrganizationName			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8019_4

Collected Identification

Collected Identification Issuance Date

Mnemonic	CISSDT			Conditionality	O
				Status	Active
Description	The date when the collected identification was issued.				
Field Min	Encoding Specific	Occur Min	0		
Field Max	Encoding Specific	Occur Max	1		
Char Types	ANS	Special Chars			
Format	YYYYMMDD	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:CollectedIdentification			Cardinality	0...100
XML Level 2	nc:IdentificationEffectiveDate/nc:Date			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8019_5

Collected Identification

Collected Identification Expiration Date

Mnemonic	CIEXPDT	Conditionality	O
		Status	Active
Description	The date the issued identification expires.		
Field Min	Encoding Specific	Occur Min	0
Field Max	Encoding Specific	Occur Max	1
Char Types	ANS	Special Chars	
Format	YYYYMMDD	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:CollectedIdentification	Cardinality	0...100
XML Level 2	nc:IdentificationExpirationDate/nc:Date	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

2.8019_6

Collected Identification

Collected Identification Issuance Office

Mnemonic	CISSOFF	Conditionality	O
		Status	Active
Description	A location or branch identifier for the office or system which issued the identification. This field is free form text. E.G. The location where the biometric subject receives their card after verification.		
Field Min	1	Occur Min	0
Field Max	100	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:CollectedIdentification	Cardinality	0...100
XML Level 2	dod-ebts:IdentificationIssuranceOfficeText	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8019_7

Collected Identification

Collected Identification Comment

Mnemonic	CICOM			Conditionality	0
				Status	Active
Description	The notes and comments concerning the issued identification collected.				
Field Min	1	Occur Min	0		
Field Max	250	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:CollectedIdentification			Cardinality	0...100
XML Level 2	nc:CommentText			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8021

Biometric Subject Clearance

Mnemonic	SUBJ_CLEAR			Conditionality	0
				Status	Active
Description	The set of fields to indicate the biometric subject clearance level and validity.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:PersonSecurityClearance			Cardinality	0...1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8021_1

Biometric Subject Clearance

Clearance Code

Mnemonic	CLRCD			Conditionality	M↑
				Status	Active
Description	The clearance level that the biometric subject claims to have. This field is not authoritative.				
Field Min	0	Occur Min	1		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	n/a		
Code List	CLEARANCE CODES				
Source	BSWG				
XML Level 1	dod-ebts:PersonSecurityClearance			Cardinality	0...1
XML Level 2	dod-ebts:ClearanceCategoryCode			Cardinality	1...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8021_2

Biometric Subject Clearance

Clearance Validity

Mnemonic	CLRVLDD			Conditionality	0
				Status	Active
Description	The state or quality of being valid of the clearance level that the biometric subject claims to hold.				
Field Min	0	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	n/a		
Code List	VALIDITY CODES				
Source	BSWG				
XML Level 1	dod-ebts:PersonSecurityClearance			Cardinality	0...1
XML Level 2	dod-ebts:ClearanceValidityCode			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8022

Biometric Subject Compartments

Mnemonic	SUBJ_COMPART		Conditionality	0	
			Status	Active	
Description	A freeform text to describe the compartments or section of information that might bear special community controls and might require restricted handling that the biometric subject claims to be cleared for.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	50	
Char Types	n/a		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	BSWG				
XML Level 1	dod-ebts:PersonCompartment		Cardinality	0...50	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

2.8022_1

Biometric Subject Compartments

Compartment Description

Mnemonic	CMPDESC		Conditionality	M↑	
			Status	Active	
Description	A freeform text to describe the compartments or section of information that might bear special community controls and might require restricted handling that the biometric subject claims to be cleared for.				
Field Min	1		Occur Min	1	
Field Max	50		Occur Max	1	
Char Types	U		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	BSWG				
XML Level 1	dod-ebts:PersonCompartment		Cardinality	0...50	
XML Level 2	dod-ebts:PersonCompartmentValueText		Cardinality	1...1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8022_2

Biometric Subject Compartments

Compartments Validity

Mnemonic	CMPVLD			Conditionality	0
				Status	Active
Description	The state or quality of being valid for the compartments that the biometric subject claims to hold.				
Field Min	3	Occur Min	0		
Field Max	3	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	n/a		
Code List	VALIDITY CODES				
Source	BSWG				
XML Level 1	dod-ebts:PersonCompartment			Cardinality	0..50
XML Level 2	dod-ebts:PersonCompartmentValidityCode			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8023

Biometric Subject Comment

Mnemonic	SUBJ_COM			Conditionality	0
				Status	Active
Description	The comments or remarks on the biometric subject for which the biometric sample was collected.				
Field Min	1	Occur Min	0		
Field Max	120	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:PersonCommentText			Cardinality	0..1
XML Level 2	nc:CommentText			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8024

Biometric Subject Specialty

Biometric Subject US Person Indicator

Mnemonic	US_IND			Conditionality	0
				Status	Active
Description	The indicator of whether a biometric subject is a citizen of the United States, an alien lawfully admitted for permanent residence in the United States, or a member of the U.S. Armed Forces.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	n/a		
Code List	YES NO CODE				
Source	BSWG				
XML Level 1	dod-ebts:USPersonIndicator			Cardinality	0...1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8025

Biometric Subject Derogatory Comment

Mnemonic	DEROG_COM			Conditionality	0
				Status	Active
Description	The derogatory notes and comments concerning a biometric subject.				
Field Min	1	Occur Min	0		
Field Max	120	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:PersonDerogatoryCommentText			Cardinality	0...1
XML Level 2	nc:CommentText			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8026

Biometric Subject Alternate Name

Mnemonic	SUBJ_AKA		Conditionality	0			
			Status	Active			
Description	An alternate name used by the biometric subject.		Can also be used to capture the subject's full maiden name.				
Field Min	n/a	Occur Min	0				
Field Max	n/a	Occur Max	1				
Char Types	n/a	Special Chars					
Format	n/a	Constraints	n/a				
Code List							
Source	BSWG						
XML Level 1	dod-ebts:PersonAlternateName		Cardinality	0...1			
XML Level 2			Cardinality				
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

2.8026_0

Biometric Subject Alternate Name

Subfields: Repeating sets of information items

Mnemonic	SUBJ_AKA_0		Conditionality	0			
			Status	New-Active			
Description	Repeating subfield for Biometric Subject Alternate Name.		Can also be used to capture the subject's full maiden name.				
Field Min	n/a	Occur Min	0				
Field Max	n/a	Occur Max	10				
Char Types	n/a	Special Chars					
Format	n/a	Constraints	n/a				
Code List							
Source	EBTS 4.0						
XML Level 1	dod-ebts:PersonAlternateName		Cardinality	0...10			
XML Level 2			Cardinality				
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8026_1

Biometric Subject Alternate Name

Person Alternate Name Category Code

Mnemonic	NAMCATCD			Conditionality	M↑
				Status	Active
Description	Defines the type of name such as maiden name, nickname, alias.				
Field Min	3	Occur Min	1		
Field Max	4	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	n/a		
Code List	ALTERNATE NAME CATEGORY CODES				
Source	BSWG				
XML Level 1	dod-ebts:PersonAlternateName			Cardinality	0...10
XML Level 2	dod-ebts:PersonAlternateNameCategoryCode			Cardinality	1...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8026_2

Biometric Subject Alternate Name

Name - One

Mnemonic	NAM1			Conditionality	M↑
				Status	Active
Description	The last name, surname or the family name of the person. Enter "UNKNOWN" if this information item is required and not available at the time of collection. Can be mapped to the Arabic Nasab name, a patronymic or series of patronymics.				
Field Min	1	Occur Min	1		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:PersonAlternateName			Cardinality	0...10
XML Level 2	nc:PersonSurName			Cardinality	1...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8026_3

Biometric Subject Alternate Name

Name - Two

Mnemonic	NAM2			Conditionality	M↑
				Status	Active
Description	The personal name of a person. It is typically the first name in western culture. Enter "UNKNOWN" if this information item is required and not available at the time of collection.				
Field Min	1	Occur Min	1		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:PersonAlternateName			Cardinality	0...10
XML Level 2	nc:PersonGivenName			Cardinality	1...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8026_4

Biometric Subject Alternate Name

Name - Three

Mnemonic	NAM3			Conditionality	O
				Status	Active
Description	The middle name of a person. It is placed between the first given name and the surname. Enter "UNKNOWN" if this information item is required and not available at the time of collection. Can be mapped to the Arabic Kunya name, the person's first-born son is used as a substitute for the ism.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:PersonAlternateName			Cardinality	0...10
XML Level 2	nc:PersonMiddleName			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8026_5

Biometric Subject Alternate Name

Name - Four

Mnemonic	NAM4			Conditionality	0
				Status	Active
Description	A name of a person to represent the fourth name for a culture using four or five names e.g., a tribal or village name. It will be given the ranking of fourth importance of naming in the culture from which the person is associated. Enter "UNKNOWN" if this information item is required and not available at the time of collection. Can be mapped to the Arabic Nisbah name, describes a person's occupation, geographic home area, or descent tribe, family, etc..				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:PersonAlternateName			Cardinality	0...10
XML Level 2	fbi-ebts:PersonFourthImportanceName			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8026_6

Biometric Subject Alternate Name

Name - Five

Mnemonic	NAM5			Conditionality	0
				Status	Active
Description	A name of a person to represent the fifth name for a culture using four or five names e.g., a tribal or village name. It will be given the ranking of fifth importance of naming in the culture from which the person is associated. Enter "UNKNOWN" if this information item is required and not available at the time of collection. Can be mapped to the Arabic Laqab name, intended as a description of the person. Also can be used for the honorific title.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:PersonAlternateName			Cardinality	0...10
XML Level 2	fbi-ebts:PersonFifthImportanceName			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8026_7

Biometric Subject Alternate Name

Name Validity

Mnemonic	NAME_VLD		Conditionality	0	
			Status	Active	
Description	This field defines the validity of the individual's name.				
Field Min	3		Occur Min	0	
Field Max	3		Occur Max	1	
Char Types	A		Special Chars		
Format	n/a		Constraints	n/a	
Code List	VALIDITY CODES				
Source	BSWG				
XML Level 1	dod-ebts:PersonAlternateName			Cardinality	0...10
XML Level 2	dod-ebts:PersonNameValidityCode			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8026_8

Biometric Subject Alternate Name

Transliteration Code

Mnemonic	TRANSLIT_CD		Conditionality	0	
			Status	Active	
Description	An encoding to transcribe from one alphabet to another.				
Field Min	4		Occur Min	0	
Field Max	6		Occur Max	1	
Char Types	A		Special Chars		
Format	n/a		Constraints	n/a	
Code List	TRANSLITERATION CODES				
Source	BSWG				
XML Level 1	dod-ebts:PersonAlternateName			Cardinality	0...10
XML Level 2	dod-ebts:TransliterationCode			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8026_9

Biometric Subject Alternate Name

Comment

Mnemonic	COM	Conditionality	O
		Status	Active
Description	The optional Comment field appears in many record types and may be used to insert free text information. It is not reserved exclusively for log-related information but has historically often been used for this purpose. It is limited to a maximum of 126 characters. This maximum size was established in order to maintain consistency across encodings. The maximum size differed in the 2007 and 2008 versions of the standard.		
Field Min	1	Occur Min	0
Field Max	126	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:PersonAlternateName	Cardinality	0...10
XML Level 2	nc:CommentText	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

2.8028

Employment

Mnemonic	EMPLOY	Conditionality	O
		Status	Active
Description	The information about the biometric subject's employment.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:PersonEmploymentSummary	Cardinality	0...1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8028_0

Employment

Subfields: Repeating sets of information items

Mnemonic	EMPLOY_0			Conditionality	0
				Status	New-Active
Description	Repeating subfield for Employment.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	5		
Char Types	n/a	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	EBTS 4.0				
XML Level 1	dod-ebts:PersonEmploymentSummary			Cardinality	0...5
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.8028_1

Employment

Employer Name

Mnemonic	EMPNAM			Conditionality	M↑
				Status	Active
Description	The organization name of the employer, such as company name or corporate name.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:PersonEmploymentSummary			Cardinality	0...5
XML Level 2	nc:Employer or nc:EntityOrganization			Cardinality	1...1
XML Level 3	nc:OrganizationName			Cardinality	0...1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-2: User-Defined Descriptive Text

Page 156 of 1037

2.8028_2

Employment

Employee Position Name

Mnemonic	POSNAM			Conditionality	0		
				Status	Active		
Description	A job title or position of an employee.						
Field Min	1		Occur Min	0			
Field Max	50		Occur Max	1			
Char Types	U		Special Chars				
Format	n/a		Constraints	n/a			
Code List							
Source	BSWG						
XML Level 1	dod-ebts:PersonEmploymentSummary			Cardinality	0...5		
XML Level 2	nc:EmployeePositionName			Cardinality	0...1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

2.8028_3

Employment

Address Line 1

Mnemonic	ADD1			Conditionality	0		
				Status	Active		
Description	The street, including both number and name.						
Field Min	1		Occur Min	0			
Field Max	50		Occur Max	1			
Char Types	U		Special Chars				
Format	n/a		Constraints	n/a			
Code List							
Source	BSWG						
XML Level 1	dod-ebts:PersonEmploymentSummary			Cardinality	0...5		
XML Level 2	dod-ebts:LocationAddress			Cardinality	0...1		
XML Level 3	nc:StreetFullText			Cardinality	0...1		
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-2: User-Defined Descriptive Text

Page 157 of 1037

2.8028_4

Employment

Address Line 2

Mnemonic	ADD2	Conditionality	0
		Status	Active
Description	Additional information about the street e.g. apt #.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:PersonEmploymentSummary	Cardinality	0...5
XML Level 2	dod-ebts:LocationAddress	Cardinality	0...1
XML Level 3	nc:StreetFullText	Cardinality	0...1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

2.8028_5

Employment

City

Mnemonic	CITY	Conditionality	0
		Status	Active
Description	Name of the city.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:PersonEmploymentSummary	Cardinality	0...5
XML Level 2	dod-ebts:LocationAddress	Cardinality	0...1
XML Level 3	nc:LocationCityName	Cardinality	0...1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-2: User-Defined Descriptive Text

Page 158 of 1037

2.8028_6

Employment

State / Province

Mnemonic	STATE	Conditionality	O
		Status	Active
Description	The state, province or subdivision of a location.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:PersonEmploymentSummary	Cardinality	0...5
XML Level 2	dod-ebts:LocationAddress	Cardinality	0...1
XML Level 3	nc:LocationStateName	Cardinality	0...1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

2.8028_7

Employment

Country Code

Mnemonic	CTRY	Conditionality	O
		Status	Active
Description	The GENC alpha3 country code. The DoD EBTS Default for this field is the GENC three character alpha codelist (genc:CountryAlpha3CodeType).		
Field Min	3	Occur Min	0
Field Max	3	Occur Max	1
Char Types	A	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:PersonEmploymentSummary	Cardinality	0...5
XML Level 2	dod-ebts:LocationAddress	Cardinality	0...1
XML Level 3	nc:LocationCountryGENCCode	Cardinality	0...1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-2: User-Defined Descriptive Text

Page 159 of 1037

2.8028_8

Employment

Postal Code

Mnemonic	POSTAL			Conditionality	0
				Status	Active
Description	Alphanumeric code assigned to groups of addresses by various national postal systems throughout the world.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	ANS	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:PersonEmploymentSummary			Cardinality	0...5
XML Level 2	dod-ebts:LocationAddress			Cardinality	0...1
XML Level 3	nc:LocationPostalCode			Cardinality	0...1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8028_9

Employment

Village

Mnemonic	VLG			Conditionality	0
				Status	Active
Description	Small population unit, typically rural, held together by common economic and political ties.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:PersonEmploymentSummary			Cardinality	0...5
XML Level 2	dod-ebts:LocationAddress			Cardinality	0...1
XML Level 3	dod-ebts:LocationVillageName			Cardinality	0...1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-2: User-Defined Descriptive Text

Page 160 of 1037

2.8028_10

Employment

Phone Number

Mnemonic	PHNUM			Conditionality	O
				Status	Active
Description	The full telephone number including international country code and area code. Space and hyphen are allowed.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	ANS	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:PersonEmploymentSummary			Cardinality	0..5
XML Level 2	nc:TelephoneNumberFullID			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8028_11

Employment

Email Address

Mnemonic	EMAIL			Conditionality	O
				Status	Active
Description	Identifies an email box to which email messages are delivered. Application Profile might be more specific to what characters are allowed to be entered for the email address.				
Field Min	1	Occur Min	0		
Field Max	254	Occur Max	1		
Char Types	ANS	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:PersonEmploymentSummary			Cardinality	0..5
XML Level 2	nc>ContactEmailID			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8028_12

Employment

Clearance Code

Mnemonic	CLRCD	Conditionality	O
		Status	Active
Description	The clearance level that the biometric subject claims to have. This field is not authoritative.		
Field Min	3	Occur Min	0
Field Max	3	Occur Max	1
Char Types	A	Special Chars	
Format	n/a	Constraints	n/a
Code List	CLEARANCE CODES		
Source	BSWG		
XML Level 1	dod-ebts:PersonEmploymentSummary	Cardinality	0..5
XML Level 2	dod-ebts:PersonSecurityClearance	Cardinality	0..1
XML Level 3	dod-ebts:PersonSecurityClearanceCode	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

2.8028_13

Employment

Job Duties

Mnemonic	DUTY	Conditionality	O
		Status	Active
Description	A list of tasks performed at a job.		
Field Min	1	Occur Min	0
Field Max	126	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:PersonEmploymentSummary	Cardinality	0..5
XML Level 2	dod-ebts:EmployeeJobDutyText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-2: User-Defined Descriptive Text

Page 162 of 1037

2.8028_14

Employment

Job Description

Mnemonic	JOBDESC			Conditionality	O
				Status	Active
Description	Freeform text to describe a job such as responsibilities, expected outcome, etc.				
Field Min	1	Occur Min	0		
Field Max	126	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:PersonEmploymentSummary			Cardinality	0...5
XML Level 2	nc:EmployeeOccupationText			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8028_15

Employment

Supervisor Name

Mnemonic	SUPV			Conditionality	O
				Status	Active
Description	The name of the person who is in charge of a particular department or unit.				
Field Min	1	Occur Min	0		
Field Max	100	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:PersonEmploymentSummary			Cardinality	0...5
XML Level 2	nc:EmployeeSupervisor			Cardinality	0...1
XML Level 3	nc:PersonName			Cardinality	0...1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-2: User-Defined Descriptive Text

Page 163 of 1037

2.8028_16

Employment

Start Date

Mnemonic	STARTDATE	Conditionality	O
		Status	Active
Description	The begin date.		
Field Min	Encoding Specific	Occur Min	0
Field Max	Encoding Specific	Occur Max	1
Char Types	ANS	Special Chars	
Format	YYYYMMDD	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:PersonEmploymentSummary	Cardinality	0...5
XML Level 2	nc:StartDate/nc:Date	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

2.8028_17

Employment

Start Date

Mnemonic	ENDDATE	Conditionality	O
		Status	Active
Description	The end date.		
Field Min	Encoding Specific	Occur Min	0
Field Max	Encoding Specific	Occur Max	1
Char Types	ANS	Special Chars	
Format	YYYYMMDD	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:PersonEmploymentSummary	Cardinality	0...5
XML Level 2	nc:EndDate/nc:Date	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8028_18

Employment

Comment

Mnemonic	COM	Conditionality	0
		Status	Active
Description	The optional Comment field appears in many record types and may be used to insert free text information. It is not reserved exclusively for log-related information but has historically often been used for this purpose. It is limited to a maximum of 126 characters. This maximum size was established in order to maintain consistency across encodings. The maximum size differed in the 2007 and 2008 versions of the standard.		
Field Min	1	Occur Min	0
Field Max	126	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:PersonEmploymentSummary	Cardinality	0..5
XML Level 2	nc:CommentText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

2.8029

Biometric Subject Contact Email

Mnemonic	SUBJ_EMAIL	Conditionality	0
		Status	Active
Description	The email address of the biometric subject. This field was previously part of 2.8002 SUBJ_CNTCT in DoD EBTS 2.0. To achieve better harmonization with other agencies as well to improve alignment to the NIEM XML, the subject's email address has been split out into a new Field with ID 2.8029, as assigned in DoD EBTS 3.0.		
Field Min	1	Occur Min	0
Field Max	254	Occur Max	1
Char Types	ANS	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:BiometricSubjectContactEMail	Cardinality	0..10
XML Level 2	nc:ContactEmailID	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8031

Biometric Subject Current Residence

Mnemonic	SUBJ_ADDR		Conditionality	0	
			Status	Active	
Description	The address of the current residence of the biometric subject. This field was previously 2.8001 SUBJ_ADDR in DoD EBTS 2.0. To achieve better harmonization with other agencies as well to improve alignment to the NIEM XML, the previous normalized field has been restructured and a new Field ID 2.8031 was assigned in DoD EBTS 3.0. In addition, Village, Neighborhood and Address Validity are also supported. This field has been updated the various parts of a street address with GENC Alpha3 country codes.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars		
Format			Constraints	n/a	
Code List					
Source	BSWG				
XML Level 1	dod-ebts:PersonCurrentResidenceLocation		Cardinality	0...1	
XML Level 2	dod-ebts:LocationAddress or nc:StructuredAddress		Cardinality	0...1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

2.8031_1

Biometric Subject Current Residence

Address Line 1

Mnemonic	ADD1		Conditionality	0	
			Status	Active	
Description	The street, including both number and name.				
Field Min	1		Occur Min	0	
Field Max	50		Occur Max	1	
Char Types	U		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	BSWG				
XML Level 1	dod-ebts:PersonCurrentResidenceLocation		Cardinality	0...1	
XML Level 2	nc:StreetFullText		Cardinality	0...1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-2: User-Defined Descriptive Text

Page 166 of 1037

2.8031_2

Biometric Subject Current Residence

Address Line 2

Mnemonic	ADD2	Conditionality	O
		Status	Emerging
Description	Additional information about the street e.g. apt #.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:PersonCurrentResidenceLocation	Cardinality	0...1
XML Level 2	nc:StreetFullText	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
			DoD EBTS 4.0
			Yes

2.8031_3

Biometric Subject Current Residence

City

Mnemonic	CITY	Conditionality	O
		Status	Active
Description	Name of the city.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:PersonCurrentResidenceLocation	Cardinality	0...1
XML Level 2	nc:LocationCityName	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
			DoD EBTS 4.0
			Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8031_4

Biometric Subject Current Residence

State / Province

Mnemonic	STATE	Conditionality	O
		Status	Active
Description	The state, province or subdivision of a location.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:PersonCurrentResidenceLocation	Cardinality	0...1
XML Level 2	nc:LocationStateName	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

2.8031_5

Biometric Subject Current Residence

Country Code

Mnemonic	CTRY	Conditionality	O
		Status	Active
Description	The GENC alpha3 country code. The DoD EBTS 4.0 Default for this field is the GENC three character alpha codelist (genc:CountryAlpha3CodeType).		
Field Min	3	Occur Min	0
Field Max	3	Occur Max	1
Char Types	A	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:PersonCurrentResidenceLocation	Cardinality	0...1
XML Level 2	nc:LocationCountryGENCCode	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8031_6

Biometric Subject Current Residence

Postal Code

Mnemonic	POSTAL	Conditionality	O
		Status	Active
Description	Alphanumeric code assigned to groups of addresses by various national postal systems throughout the world.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	ANS	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:PersonCurrentResidenceLocation	Cardinality	0...1
XML Level 2	nc:LocationPostalCode	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

2.8031_7

Biometric Subject Current Residence

Neighborhood / District

Mnemonic	NEIG	Conditionality	O
		Status	Active
Description	A geographically localized community within a larger city, town or suburb.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:PersonCurrentResidenceLocation	Cardinality	0...1
XML Level 2	nc:LocaleNeighborhoodName	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8031_8

Biometric Subject Current Residence

Village

Mnemonic	VLG			Conditionality	O
				Status	Active
Description	Small population unit, typically rural, held together by common economic and political ties.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:PersonCurrentResidenceLocation			Cardinality	0...1
XML Level 2	dod-ebts:LocationVillageName			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8031_9

Biometric Subject Current Residence

Address Validity

Mnemonic	ADDR_VLD			Conditionality	O
				Status	Active
Description	This field defines the validity of the address information.				
Field Min	3	Occur Min	0		
Field Max	3	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	n/a		
Code List	VALIDITY CODES				
Source	BSWG				
XML Level 1	dod-ebts:PersonCurrentResidenceLocation			Cardinality	0...1
XML Level 2	dod-ebts:LocationAddressValidityCode			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8032

Biometric Subject Contact Telephone

Mnemonic	SUBJ_PHONE		Conditionality	0			
			Status	Active			
Description	The telephone number including extension (if available) that you might contact the biometric subject. Different categories of telephone number (e.g. cell, home, work, etc.) are supported. This field was previously part of 2.8002 SUBJ_CNTCT in DoD EBTS 2.0. To achieve better harmonization with other agencies as well to improve alignment to the NIEM XML, the subject's telephone number(s) has been split out into a new Field with ID 2.8032 has been assigned in DoD EBTS 3.0. This field continue to support the various categories of telephone that the subject can be contacted by. The telephone number and extension are supported.						
Field Min	n/a	Occur Min	0				
Field Max	n/a	Occur Max	1				
Char Types	n/a	Special Chars					
Format	n/a	Constraints	n/a				
Code List							
Source	BSWG						
XML Level 1	nc:ContactTelephoneNumber	Cardinality	0...1				
XML Level 2		Cardinality					
XML Level 3		Cardinality					
XML Level 4		Cardinality					
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

2.8032_1

Biometric Subject Contact Telephone

Telephone Category Code

Mnemonic	PH_TYP		Conditionality	0			
			Status	Active			
Description	The method of contact for the individual e.g. phone, email.						
Field Min	2	Occur Min	0				
Field Max	2	Occur Max	1				
Char Types	A	Special Chars					
Format	n/a	Constraints	n/a				
Code List	TELEPHONE CATEGORY CODES						
Source	BSWG						
XML Level 1	nc:ContactTelephoneNumber	Cardinality	0...1				
XML Level 2	nc:TelephoneNumberCategoryText	Cardinality	0...1				
XML Level 3		Cardinality					
XML Level 4		Cardinality					
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8032_2

Biometric Subject Contact Telephone

Phone Number

Mnemonic	PHNUM			Conditionality	O
				Status	Active
Description	The full telephone number including international country code and area code. Space and hyphen are allowed.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	ANS	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	nc:ContactTelephoneNumber	Cardinality	0...1		
XML Level 2	nc:TelephoneNumberFullID	Cardinality	0...1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

2.8032_3

Biometric Subject Contact Telephone

Phone Extension

Mnemonic	PHEXT			Conditionality	O
				Status	Active
Description	The number for an additional telephone wired to the same telephone line as another.				
Field Min	1	Occur Min	0		
Field Max	20	Occur Max	1		
Char Types	N	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	nc:ContactTelephoneNumber	Cardinality	0...1		
XML Level 2	dod-ebts:PhoneExtension	Cardinality	0...1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8033

Biometric Subject Birth Location

Mnemonic	SUBJ_POB		Conditionality	0			
			Status	Active			
Description	Information identifying where the biometric subject was born. This field was previously 2.8004 POB in DoD EBTS 2.0. To achieve better harmonization with other agencies as well as to improve alignment to the NIEM XML, the previously normalized field has been renamed and restructured. A new Field with ID 2.8033 has been assigned in DoD EBTS 3.0. For all location type field, city, state/province, village and comment are supported. This field has been updated to contain the GENC 3166-1 Alpha3 country code.						
Field Min	n/a	Occur Min	0				
Field Max	n/a	Occur Max	1				
Char Types	n/a	Special Chars					
Format	n/a	Constraints	n/a				
Code List							
Source	BSWG						
XML Level 1	dod-ebts:PersonBirthLocation		Cardinality	0...1			
XML Level 2	nc:PersonBirthLocation		Cardinality	0...1			
XML Level 3	nc:AddressFullText		Cardinality	0...1			
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

2.8033_1

Biometric Subject Birth Location

City

Mnemonic	CITY		Conditionality	0			
			Status	Active			
Description	Name of the city.						
Field Min	1	Occur Min	0				
Field Max	50	Occur Max	1				
Char Types	U	Special Chars					
Format	n/a	Constraints	n/a				
Code List							
Source	BSWG						
XML Level 1	dod-ebts:PersonBirthLocation		Cardinality	0...1			
XML Level 2	nc:PersonBirthLocation		Cardinality	0...1			
XML Level 3	nc:LocationCityName		Cardinality	0...1			
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8033_2

Biometric Subject Birth Location

State / Province

Mnemonic	STATE			Conditionality	O
				Status	Active
Description	The state, province or subdivision of a location.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:PersonBirthLocation			Cardinality	0...1
XML Level 2	nc:PersonBirthLocation			Cardinality	0...1
XML Level 3	nc:LocationStateName			Cardinality	0...1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8033_3

Biometric Subject Birth Location

Country Code

Mnemonic	CTRY			Conditionality	O
				Status	Active
Description	The GENC alpha3 country code. The DoD EBTS 4.0 default for this field is the GENC three character alpha codelist (genc:CountryAlpha3CodeType).				
Field Min	3	Occur Min	0		
Field Max	3	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:PersonBirthLocation			Cardinality	0...1
XML Level 2	nc:PersonBirthLocation			Cardinality	0...1
XML Level 3	nc:LocationCountryGENCCode			Cardinality	0...1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8033_4

Biometric Subject Birth Location

Village

Mnemonic	VLG		Conditionality	0	
			Status	Active	
Description	Small population unit, typically rural, held together by common economic and political ties.				
Field Min	1		Occur Min	0	
Field Max	50		Occur Max	1	
Char Types	U		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	BSWG				
XML Level 1	dod-ebts:PersonBirthLocation		Cardinality	0...1	
XML Level 2	nc:PersonBirthLocation		Cardinality	0...1	
XML Level 3	dod-ebts:LocationVillageName		Cardinality	0...1	
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8033_5

Biometric Subject Birth Location

Comment

Mnemonic	COM		Conditionality	0	
			Status	Active	
Description	The optional Comment field appears in many record types and may be used to insert free text information. It is not reserved exclusively for log-related information but has historically often been used for this purpose. It is limited to a maximum of 126 characters. This maximum size was established in order to maintain consistency across encodings. The maximum size differed in the 2007 and 2008 versions of the standard.				
Field Min	1		Occur Min	0	
Field Max	126		Occur Max	1	
Char Types	U		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	BSWG				
XML Level 1	dod-ebts:PersonBirthLocation		Cardinality	0...1	
XML Level 2	nc:PersonBirthLocation		Cardinality	0...1	
XML Level 3	nc:LocationDescriptionText		Cardinality	0...1	
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8034

Biometric Subject Death Location

Mnemonic	SUBJ_POD		Conditionality	0	
			Status	Active	
Description	Defines the biometric subject's place of death. This field was previously 2.8006 POD in DoD EBTS 2.0. To achieve better harmonization with other agencies as well to improve alignment to the NIEM XML, the previously normalized field has been renamed and restructured. A new Field with ID 2.8034 has been assigned in DoD EBTS 3.0. For all location type field, city, state/province, village and comment are supported. The GENC Alpha3 country code should now be used in place of the ISO 3166-1 Alpha3 country code.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	BSWG				
XML Level 1	dod-ebts:PersonDeathLocation		Cardinality	0...1	
XML Level 2	dod-ebts:LocationAddress		Cardinality	0...1	
XML Level 3	nc:AddressFullText		Cardinality	0...1	
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

2.8034_1

Biometric Subject Death Location

City

Mnemonic	CITY		Conditionality	0	
			Status	Active	
Description	Name of the city.				
Field Min	1		Occur Min	0	
Field Max	50		Occur Max	1	
Char Types	U		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	BSWG				
XML Level 1	dod-ebts:PersonDeathLocation		Cardinality	0...1	
XML Level 2	nc:LocationCityName		Cardinality	0...1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8034_2

Biometric Subject Death Location

State / Province

Mnemonic	STATE	Conditionality	O
		Status	Active
Description	The state, province or subdivision of a location.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:PersonDeathLocation	Cardinality	0...1
XML Level 2	nc:LocationStateName	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

2.8034_3

Biometric Subject Death Location

Country Code

Mnemonic	CTRY	Conditionality	O
		Status	Active
Description	The GENC alpha3 country code. The DoD EBTS 4.0 default for this field is the GENC three character alpha codelist (genc:CountryAlpha3CodeType).		
Field Min	3	Occur Min	0
Field Max	3	Occur Max	1
Char Types	A	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:PersonDeathLocation	Cardinality	0...1
XML Level 2	nc:LocationCountryGENCCode	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8034_4

Biometric Subject Death Location

Village

Mnemonic	VLG			Conditionality	O		
				Status	Active		
Description	Small population unit, typically rural, held together by common economic and political ties.						
Field Min	1		Occur Min	0			
Field Max	50		Occur Max	1			
Char Types	U		Special Chars				
Format	n/a		Constraints	n/a			
Code List							
Source	BSWG						
XML Level 1	dod-ebts:PersonDeathLocation			Cardinality	0...1		
XML Level 2	dod-ebts:LocationVillageName			Cardinality	0...1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

2.8034_5

Biometric Subject Death Location

Biometric Subject Death Location

Mnemonic	COM			Conditionality	O		
				Status	Active		
Description	Comment						
Field Min	0		Occur Min	0			
Field Max	126		Occur Max	1			
Char Types	U		Special Chars				
Format	n/a		Constraints	n/a			
Code List							
Source	BSWG						
XML Level 1	dod-ebts:PersonDeathLocation			Cardinality	0...1		
XML Level 2	nc:LocationDescriptionText			Cardinality	0...1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8035

Biometric Subject Height Measurement

Mnemonic	SUBJ_HEIGHT		Conditionality	0	
			Status	Active	
Description	The set of data describing the height measurement including measurement range of a biometric subject. This field was previously 2.8009 HGT. Measurement Type has been removed from the set. A new field ID, 2.8035 SUBJ_HEIGHT has been assigned by DoD EBTS 3.0. For measurement range, provide 2 subfields of the same measurement type where validity is set to estimated.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	BSWG				
XML Level 1	dod-ebts:PersonHeightMeasure		Cardinality	0...1	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

2.8035_1

Biometric Subject Height Measurement

Height Value

Mnemonic	HGT		Conditionality	0	
			Status	Active	
Description	The value of the height measurement. Minimum height shall be 4'0" and maximum height shall be 7'11". The metric equivalent is also allowed min = 1.22M, max = 2.41M. The following rules apply when measuring an individual's height: Height FTIN - Three-character value, the first leftmost digit is used to show feet while the two rightmost digits are used to show inches between 00 and 11. Height IN - Two-character value. Height M - Four-character value, the first leftmost digit is used.				
Field Min	2		Occur Min	0	
Field Max	4		Occur Max	1	
Char Types	NS		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	BSWG				
XML Level 1	dod-ebts:PersonHeightMeasure		Cardinality	0...1	
XML Level 2	nc:RangeMaximumIntegerValue and/or nc:RangeMaximumIntegerValue		Cardinality	0...1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8035_2

Biometric Subject Height Measurement

Length Unit

Mnemonic	LENUNIT			Conditionality	O
				Status	Active
Description	The units of measure associated with a given height measurement e.g., inches, centimeters, etc				
Field Min	1	Occur Min	0		
Field Max	4	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	n/a		
Code List	UNIT OF MEASURE CODES				
Source	BSWG				
XML Level 1	dod-ebts:PersonHeightMeasure			Cardinality	0...1
XML Level 2	nc:MeasureUnitText			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8035_3

Biometric Subject Height Measurement

Measurement Validity

Mnemonic	MEASVLD			Conditionality	O
				Status	Active
Description	Captures the validity of the measurement.				
Field Min	3	Occur Min	0		
Field Max	3	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	n/a		
Code List	VALIDITY CODES				
Source	BSWG				
XML Level 1	dod-ebts:PersonHeightMeasure			Cardinality	0...1
XML Level 2	dod-ebts:PersonMeasureValidityCode			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8036

Biometric Subject Weight Measurement

Mnemonic	SUBJ_WEIGHT		Conditionality	0	
			Status	Active	
Description	The set of data describing the weight measurement including measurement range of a biometric subject. This field was previously 2.8010 WGT. Measurement Type has been removed from the set. A new field ID, 2.8036 SUBJ_WEIGHT has been assigned by DoD EBTS 3.0. For measurement range, provide 2 subfields of the same measurement type where validity is set to estimated.				
Field Min	n/a		Occur Min	1	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	BSWG				
XML Level 1	dod-ebts:PersonWeightMeasure		Cardinality	0...1	
XML Level 2	nc:RangeMaximumIntegerValue and/or nc:RangeMaximumIntegerValue		Cardinality	1...1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

2.8036_1

Biometric Subject Weight Measurement

Weight Value

Mnemonic	WGT		Conditionality	0	
			Status	Active	
Description	The value of the weight measurement. The minimum weight shall be 0 LB/KG. The maximum weight shall be 499 LB or 227 KG. Measurement shall be rounded up to the nearest pound or kilogram. Note: If the measurement is unknown but mandatory, use "000" to represent unknown measurement.				
Field Min	1		Occur Min	0	
Field Max	3		Occur Max	1	
Char Types	N		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	BSWG				
XML Level 1	dod-ebts:PersonWeightMeasure		Cardinality	0...1	
XML Level 2	nc:PersonWeightMeasure/nc:MeasureValue		Cardinality	0...1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

2.8036_2

Biometric Subject Weight Measurement

Mass Unit

Mnemonic	MASSUNIT			Conditionality	M↑
				Status	Active
Description	The units of measure associated with a given weight measurement e.g., pounds.				
Field Min	2	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	n/a		
Code List	UNIT OF MEASURE CODES				
Source	BSWG				
XML Level 1	dod-ebts:PersonWeightMeasure			Cardinality	0...1
XML Level 2	nc:measureunitText			Cardinality	1...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8036_3

Biometric Subject Weight Measurement

Measurement Validity

Mnemonic	MEASVLD			Conditionality	M↑
				Status	Active
Description	Captures the validity of the measurement.				
Field Min	3	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	n/a		
Code List	VALIDITY CODES				
Source	BSWG				
XML Level 1	dod-ebts:PersonWeightMeasure			Cardinality	0...1
XML Level 2	od-ebts:PersonMeasureValidityCode			Cardinality	1...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8037

Biometric Subject Eye Color

Mnemonic	SUBJ_EYE_0		Conditionality	0			
			Status	Active			
Description	The color of the biometric subject's eyes.						
Field Min	n/a	Occur Min	0				
Field Max	n/a	Occur Max	1				
Char Types	n/a	Special Chars					
Format	n/a	Constraints	n/a				
Code List							
Source	BSWG						
XML Level 1	dod-ebts:PersonEyeColor		Cardinality	0..1			
XML Level 2			Cardinality				
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

2.8037_0

Biometric Subject Eye Color

Subfields: Repeating sets of information items

Mnemonic	SUBJ_EYE		Conditionality	0			
			Status	New-Active			
Description	Repeating subfield for Biometric Subject Eye Color.						
Field Min	n/a	Occur Min	0				
Field Max	n/a	Occur Max	2				
Char Types	n/a	Special Chars					
Format	n/a	Constraints	n/a				
Code List							
Source	EBTS 4.0						
XML Level 1	dod-ebts:PersonEyeColor		Cardinality	0..2			
XML Level 2			Cardinality				
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8037_1

Biometric Subject Eye Color

Eye Position

Mnemonic	EPOS			Conditionality	M↑
				Status	Active
Description	The position of the eye.				
Field Min	1	Occur Min	1		
Field Max	1	Occur Max	1		
Char Types	N			Special Chars	
Format	n/a			Constraints	EPOS = 0, 1, or 2, biom_2:EyePositionCodeType
Code List	FEATURE IDENTIFIER CODE				
Source	BSWG				
XML Level 1	dod-ebts:PersonEyeColor			Cardinality	0...2
XML Level 2	biom_2:IrisEyePositionCode			Cardinality	1...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8037_2

Biometric Subject Eye Color

Mnemonic	ECOL			Conditionality	M↑
				Status	Active
Description	This field shall specify the subject's eye color.				
Field Min	3	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	A			Special Chars	
Format	n/a			Constraints	n/a
Code List	ALPHA EYE COLOR CODES				
Source	BSWG				
XML Level 1	dod-ebts:PersonEyeColor			Cardinality	0...2
XML Level 2	j:PersonEyeColorCode			Cardinality	1...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8038

Biometric Subject Group Membership

Mnemonic	GRPMBR		Conditionality	0	
			Status	Active	
Description	This set of fields identifies the names, gender, roles, address information and contact information of an individual who is associated with the biometric subject. This field was previously 2.8017 IASSOC in DoD EBTS 2.0. To achieve better harmonization with other agencies as well to improve alignment to the NIEM XML, the previous normalized field has been restructured and a new Field ID 2.8038 has been assigned in DoD EBTS 3.0. This field continues to support the associated individual gender, role, name, address and contact phone. The associated individual birth date, occupation and comment have been added to the set.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	BSWG				
XML Level 1	dod-ebts:AssociatedIndividual		Cardinality	0..1	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8038_0

Biometric Subject Group Membership

Subfields: Repeating sets of information items

Mnemonic	GRPMBR_0		Conditionality	0	
			Status	New-Active	
Description	Repeating subfield for Biometric Subject Group Membership.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	100	
Char Types	n/a		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	EBTS 4.0				
XML Level 1	dod-ebts:AssociatedIndividual		Cardinality	0..100	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8038_1

Biometric Subject Associated Individual

Associated Individual Gender

Mnemonic	IASSOC_SEX			Conditionality	O
				Status	Active
Description	This field is used to report the gender of the associated individual. The entry is a single character selected from the look-up code list.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	see Look Up Codes		
Code List	GENDER CODES				
Source	BSWG				
XML Level 1	dod-ebts:AssociatedIndividual			Cardinality	0...100
XML Level 2	j:PersonSexCode			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8038_2

Biometric Subject Associated Individual

Associated Individual Role

Mnemonic	IASSOC_ROLE			Conditionality	M↑
				Status	Active
Description	The role of an individual who is affiliated with the biometric subject.				
Field Min	1	Occur Min	1		
Field Max	1	Occur Max	1		
Char Types	N	Special Chars			
Format	n/a	Constraints	see Look Up Codes		
Code List	ASSOCIATED INDIVIDUAL ROLE CODES				
Source	BSWG				
XML Level 1	dod-ebts:AssociatedIndividual			Cardinality	0...100
XML Level 2	dod-ebts:AssociatedIndividualCategoryCode			Cardinality	1...1
XML Level 3	dod-ebts:AssociatedIndividualName			Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8038_3

Biometric Subject Associated Individual

Name - One

Mnemonic	NAM1			Conditionality	M↑
				Status	Emerging
Description	The last name, surname or the family name of the person. Enter "UNKNOWN" if this information item is required and not available at the time of collection. Can be mapped to the Arabic Nasab name, a patronymic or series of patronymics.				
Field Min	1	Occur Min	1		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:AssociatedIndividual			Cardinality	0...100
XML Level 2	nc:PersonFullName			Cardinality	1...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8038_4

Biometric Subject Associated Individual

Name - Two

Mnemonic	NAM2			Conditionality	M↑
				Status	Active
Description	The personal name of a person. It is typically the first name in western culture. Enter "UNKNOWN" if this information item is required and not available at the time of collection.				
Field Min	1	Occur Min	1		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:AssociatedIndividual			Cardinality	0...100
XML Level 2	nc:PersonGivenName			Cardinality	1...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8038_5

Biometric Subject Associated Individual

Name - Three

Mnemonic	NAM3			Conditionality	0
				Status	Active
Description	The middle name of a person. It is placed between the first given name and the surname. Enter "UNKNOWN" if this information item is required and not available at the time of collection. Can be mapped to the Arabic Kunya name, the person's first-born son is used as a substitute for the ism.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:AssociatedIndividual			Cardinality	0...100
XML Level 2	nc:PersonMiddleName			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8038_6

Biometric Subject Associated Individual

Name - Four

Mnemonic	NAM4			Conditionality	0
				Status	Active
Description	A name of a person to represent the fourth name for a culture using four or five names e.g., a tribal or village name. It will be given the ranking of fourth importance of naming in the culture from which the person is associated. Enter "UNKNOWN" if this information item is required and not available at the time of collection. Can be mapped to the Arabic Nisbah name, describes a person's occupation, geographic home area, or descent tribe, family, etc..				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:AssociatedIndividual			Cardinality	0...100
XML Level 2	fbi-ebts:PersonFourthImportanceName			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-2: User-Defined Descriptive Text

Page 188 of 1037

2.8038_7

Biometric Subject Associated Individual

Name - Five

Mnemonic	NAM5		Conditionality	O	
			Status	Active	
Description	A name of a person to represent the fifth name for a culture using four or five names e.g., a tribal or village name. It will be given the ranking of fifth importance of naming in the culture from which the person is associated. Enter "UNKNOWN" if this information item is required and not available at the time of collection. Can be mapped to the Arabic Laqab name, intended as a description of the person. Also can be used for the honorific title.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	U		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	BSWG				
XML Level 1	dod-ebts:AssociatedIndividual		Cardinality	0...100	
XML Level 2	fbi-ebts:PersonFifthImportanceName		Cardinality	0...1	
XML Level 3	dod-ebts:PersonCurrentResidenceLocationdod-ebts:LocationAddress nc:StructuredAddress		Cardinality	0...1	
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8038_8

Biometric Subject Associated Individual

Address Line 1

Mnemonic	ADD1		Conditionality	O	
			Status	Active	
Description	The street, including both number and name.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	U		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	BSWG				
XML Level 1	dod-ebts:AssociatedIndividual		Cardinality	0...100	
XML Level 2	dod-ebts:LocationAddress		Cardinality	0...1	
XML Level 3	nc:StreetFullText		Cardinality	0...1	
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8038_9

Biometric Subject Associated Individual

Address Line 2

Mnemonic	ADD2	Conditionality	O
		Status	Active
Description	Additional information about the street e.g. apt #.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:AssociatedIndividual	Cardinality	0...100
XML Level 2	dod-ebts:LocationAddress	Cardinality	0...1
XML Level 3	nc:StreetFullText	Cardinality	0...1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

2.8038_10

Biometric Subject Associated Individual

City

Mnemonic	CITY	Conditionality	O
		Status	Active
Description	Name of the city.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:AssociatedIndividual	Cardinality	0...100
XML Level 2	nc:LocationCityName	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8038_11

Biometric Subject Associated Individual

State / Province

Mnemonic	STATE	Conditionality	O
		Status	Active
Description	The state, province or subdivision of a location.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:AssociatedIndividual	Cardinality	0...100
XML Level 2	nc:LocationStateName	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

2.8038_12

Biometric Subject Associated Individual

Country Code

Mnemonic	CTRY	Conditionality	O
		Status	Active
Description	The GENC alpha3 country code. The DoD EBTS 4.0 default for this field is the GENC three character alpha codelist (genc:CountryAlpha3CodeType).		
Field Min	3	Occur Min	0
Field Max	3	Occur Max	1
Char Types	A	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:AssociatedIndividual	Cardinality	0...100
XML Level 2	nc:LocationCountryGENCCode	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8038_13

Biometric Subject Associated Individual

Postal Code

Mnemonic	POSTAL	Conditionality	O
		Status	Active
Description	Alphanumeric code assigned to groups of addresses by various national postal systems throughout the world.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	ANS	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:AssociatedIndividual	Cardinality	0...100
XML Level 2	nc:LocationPostalCode	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

2.8038_14

Biometric Subject Associated Individual

Village

Mnemonic	VLG	Conditionality	O
		Status	Active
Description	Small population unit, typically rural, held together by common economic and political ties.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:AssociatedIndividual	Cardinality	0...100
XML Level 2	nc:LocaleNeighborhoodName	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8038_15

Biometric Subject Associated Individual

Phone Number

Mnemonic	PHNUM			Conditionality	O
				Status	Active
Description	The full telephone number including international country code and area code. Space and hyphen are allowed.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	ANS	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:AssociatedIndividual			Cardinality	0...100
XML Level 2	dod-ebts:LocationVillageName			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8038_16

Biometric Subject Associated Individual

Birth Date

Mnemonic	DOB			Conditionality	O
				Status	Active
Description	The 8 digit calendar date for the person's birth date.				
Field Min	Dependent on Encoding	Occur Min	0		
Field Max	Dependent on Encoding	Occur Max	1		
Char Types	ANS	Special Chars			
Format	YYYYMMDD	Constraints	8 digit date		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:AssociatedIndividual			Cardinality	0...100
XML Level 2	dod-ebts:PersonBirthDate/nc:Date			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8038_17

Biometric Subject Associated Individual

Occupation

Mnemonic	OCP			Conditionality	O
				Status	Active
Description	This free-text field contains the person's occupation. The OCP returned in a response is the same as the one submitted.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:AssociatedIndividual			Cardinality	0...100
XML Level 2	nc:EmployeeOccupationText			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8038_18

Biometric Subject Associated Individual

Comment

Mnemonic	COM			Conditionality	O
				Status	Active
Description	The optional Comment field appears in many record types and may be used to insert free text information. It is not reserved exclusively for log-related information but has historically often been used for this purpose. It is limited to a maximum of 126 characters. This maximum size was established in order to maintain consistency across encodings. The maximum size differed in the 2007 and 2008 versions of the standard.				
Field Min	1	Occur Min	0		
Field Max	126	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:AssociatedIndividual			Cardinality	0...100
XML Level 2	nc:CommentText			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8039

Biometric Subject Group Membership

Biometric Subject Group Membership Biometric Subject Group Membership

Mnemonic	GRPMBR	Conditionality	O
		Status	Active
Description	Provide summary information on organizations the biometric subject is a member of. This field was previously 2.8018 GRPMBR in DoD EBTS 2.0.To achieve better harmonization with other agencies as well to improve alignment to the NIEM XML, the previous normalized field has been restructured and a new Field ID 2.8039 has been assigned in DoD EBTS 3.0. This field continues to support the group name, type, member role, address, contact phone and comment.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:OrganizationMembership	Cardinality	0...1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

2.8039_0

Biometric Subject Group Membership

Subfields: Repeating sets of information items

Mnemonic	GRPMBR_0	Conditionality	O
		Status	New-Active
Description	Repeating subfield for Biometric Subject Group Membership.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	100
Char Types	n/a	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	EBTS 4.0		
XML Level 1	dod-ebts:OrganizationMembership	Cardinality	0...100
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8039_1

Biometric Subject Group Membership

Group Name

Mnemonic	GMNAM			Conditionality	M↑
				Status	Active
Description	The name of the group that the biometric subject is associated with.				
Field Min	1	Occur Min	1		
Field Max	100	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:OrganizationMembership			Cardinality	0...100
XML Level 2	nc:OrganizationName			Cardinality	1...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8039_2

Biometric Subject Group Membership

Group Type

Mnemonic	GMTYP			Conditionality	M↑
				Status	Active
Description	The type of group that the biometric subject is associated with.				
Field Min	3	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	see Look Up Codes		
Code List	GROUP TYPE CODES				
Source	BSWG				
XML Level 1	dod-ebts:OrganizationMembership			Cardinality	0...100
XML Level 2	dod-ebts:OrganizationCategoryCode			Cardinality	1...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8039_3

Biometric Subject Group Membership

Group Member Role

Mnemonic	GMRL			Conditionality	O
				Status	Active
Description	The role within the associated group that the biometric subject is acting as.				
Field Min	1	Occur Min	0		
Field Max	100	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:OrganizationMembership			Cardinality	0...100
XML Level 2	nc:AddressFullText			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8039_4

Biometric Subject Group Membership

Address Line 1

Mnemonic	ADD1			Conditionality	O
				Status	Active
Description	The street, including both number and name.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:OrganizationMembership			Cardinality	0...100
XML Level 2	nc:StreetFullText			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8039_5

Biometric Subject Group Membership

Address Line 2

Mnemonic	ADD2	Conditionality	O
		Status	Active
Description	Additional information about the street e.g. apt #.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:OrganizationMembership	Cardinality	0...100
XML Level 2	nc:StreetFullText	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
			DoD EBTS 4.0
			Yes

2.8039_6

Biometric Subject Group Membership

City

Mnemonic	CITY	Conditionality	O
		Status	Active
Description	Name of the city.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:OrganizationMembership	Cardinality	0...100
XML Level 2	nc:LocationCityName	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
			DoD EBTS 4.0
			Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8039_7

Biometric Subject Group Membership

State / Province

Mnemonic	STATE	Conditionality	O
		Status	Active
Description	The state, province or subdivision of a location.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:OrganizationMembership	Cardinality	0...100
XML Level 2	nc:LocationStateName	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

2.8039_8

Biometric Subject Group Membership

Country Code

Mnemonic	CTRY	Conditionality	O
		Status	Active
Description	The GENC alpha3 country code. The DoD EBTS 4.0 default for this field is the GENC three character alpha codelist (genc:CountryAlpha3CodeType).		
Field Min	3	Occur Min	0
Field Max	3	Occur Max	1
Char Types	A	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:OrganizationMembership	Cardinality	0...100
XML Level 2	Genc:countryAlpha3CodeType	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8039_9

Biometric Subject Group Membership

Postal Code

Mnemonic	POSTAL	Conditionality	O
		Status	Active
Description	Alphanumeric code assigned to groups of addresses by various national postal systems throughout the world.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	ANS	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:OrganizationMembership	Cardinality	0...100
XML Level 2	nc:LocationPostalCode	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
			DoD EBTS 4.0
			Yes

2.8039_10

Biometric Subject Group Membership

Village

Mnemonic	VLG	Conditionality	O
		Status	Active
Description	Small population unit, typically rural, held together by common economic and political ties.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:OrganizationMembership	Cardinality	0...100
XML Level 2	dod-ebts:LocationVillageName	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
			DoD EBTS 4.0
			Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8039_11

Biometric Subject Group Membership

Phone Number

Mnemonic	PHNUM			Conditionality	O
				Status	Active
Description	The full telephone number including international country code and area code. Space and hyphen are allowed.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	ANS	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:OrganizationMembership			Cardinality	0...100
XML Level 2	nc:TelephoneNumberFullID			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8039_12

Biometric Subject Group Membership

Comment

Mnemonic	COM			Conditionality	O
				Status	Active
Description	The optional Comment field appears in many record types and may be used to insert free text information. It is not reserved exclusively for log-related information but has historically often been used for this purpose. It is limited to a maximum of 126 characters. This maximum size was established in order to maintain consistency across encodings. The maximum size differed in the 2007 and 2008 versions of the standard.				
Field Min	1	Occur Min	0		
Field Max	126	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:OrganizationMembership			Cardinality	0...100
XML Level 2	nc:CommentText			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.804

Biometric Subject Name

Mnemonic	SUBJ_NAME		Conditionality	0	
			Status	Active	
Description	The name of the biometric subject. This field was previously 2.8000 SUBJ_NAM in DoD EBTS 2.0. To achieve better harmonization with other agencies as well to improve alignment to the NIEM XML, the previous normalized field has been restructured and a new Field ID 2.8030 has been assigned in DoD EBTS 3.0. This field continues to support Arabic names. For aliases, see Field 2.8206 SUBJ_AKA for Biometric Subject Alternate Name.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	BSWG				
XML Level 1	dod-ebts:PersonName		Cardinality	0...1	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

2.8040_1

Biometric Subject Name

Name - One

Mnemonic	NAM1		Conditionality	0	
			Status	Active	
Description	The last name, surname or the family name of the person. Enter "UNKNOWN" if this information item is required and not available at the time of collection. Can be mapped to the Arabic Nasab name, a patronymic or series of patronymics.				
Field Min	1		Occur Min	0	
Field Max	50		Occur Max	1	
Char Types	U		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	BSWG				
XML Level 1	dod-ebts:PersonName		Cardinality	0...1	
XML Level 2	nc:PersonSurName		Cardinality	0...1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8040_2

Biometric Subject Name

Name - Two

Mnemonic	NAM2			Conditionality	M↑
				Status	Active
Description	The personal name of a person. It is typically the first name in western culture. Enter "UNKNOWN" if this information item is required and not available at the time of collection. Can be mapped to the Arabic Ism name, the main name of an Arab person; his or her personal name e.g. "Kareem" or "Fatimah".				
Field Min	1	Occur Min	1		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:PersonName	Cardinality	0...1		
XML Level 2	nc:PersonGivenName	Cardinality	1...1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

2.8040_3

Biometric Subject Name

Name - Three

Mnemonic	NAM3			Conditionality	O
				Status	Active
Description	The middle name of a person. It is placed between the first given name and the surname. Enter "UNKNOWN" if this information item is required and not available at the time of collection. Can be mapped to the Arabic Kunya name, the person's first-born son is used as a substitute for the ism.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:PersonName	Cardinality	0...1		
XML Level 2	nc:PersonMiddleName	Cardinality	0...1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8040_4

Biometric Subject Name

Name - Four

Mnemonic	NAM4		Conditionality	0	
			Status	Active	
Description	A name of a person to represent the fourth name for a culture using four or five names e.g., a tribal or village name. It will be given the ranking of fourth importance of naming in the culture from which the person is associated. Enter "UNKNOWN" if this information item is required and not available at the time of collection. Can be mapped to the Arabic Nisbah name, describes a person's occupation, geographic home area, or descent tribe, family, etc..				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	U		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	BSWG				
XML Level 1	dod-ebts:PersonName		Cardinality	0...1	
XML Level 2	fbi-ebts:PersonFourthImportanceName		Cardinality	0...1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8040_5

Biometric Subject Name

Name - Five

Mnemonic	NAM5		Conditionality	0	
			Status	Active	
Description	A name of a person to represent the fifth name for a culture using four or five names e.g., a tribal or village name. It will be given the ranking of fifth importance of naming in the culture from which the person is associated. Enter "UNKNOWN" if this information item is required and not available at the time of collection. Can be mapped to the Arabic Laqab name, intended as a description of the person. Also can be used for the honoric title.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	U		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	BSWG				
XML Level 1	dod-ebts:PersonName		Cardinality	0...1	
XML Level 2	fbi-ebts:PersonFifthImportanceName		Cardinality	0...1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8040_6

Biometric Subject Name

Name Validity

Mnemonic	NAME_VLD			Conditionality	0
				Status	Active
Description	This field defines the validity of the individual's name.				
Field Min	3	Occur Min	0		
Field Max	3	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	see Look Up Codes		
Code List	VALIDITY CODES				
Source	BSWG				
XML Level 1	dod-ebts:PersonName			Cardinality	0..1
XML Level 2	dod-ebts:PersonNameValidityCode			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8040_7

Biometric Subject Name

Transliteration Code

Mnemonic	TRANSLIT_CD			Conditionality	0
				Status	Active
Description	An encoding to transcribe from one alphabet to another.				
Field Min	4	Occur Min	0		
Field Max	6	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	see Look Up Codes		
Code List	TRANSLITERATION CODES				
Source	BSWG				
XML Level 1	dod-ebts:PersonName			Cardinality	0..1
XML Level 2	dod-ebts:TransliterationCode			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-2: User-Defined Descriptive Text

Page 205 of 1037

2.8102

Encounter Mission Type

Mnemonic	ENCTR_MSN		Conditionality	0
			Status	Active
Description	The kind of mission under which the biometric subject's data was collected.			
Field Min	2	Occur Min	0	
Field Max	5	Occur Max	1	
Char Types	A	Special Chars		
Format	n/a	Constraints	see Look Up Codes	
Code List	MISSION CODES			
Source	BSWG			
XML Level 1	dod-ebts:EncounterMissionCategoryCode		Cardinality	0...1
XML Level 2			Cardinality	
XML Level 3			Cardinality	
XML Level 4			Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0 Yes DoD EBTS 4.0 Yes

2.8103

Collection Reason

Mnemonic	COL_RSN		Conditionality	0
			Status	Active
Description	The purpose for which a biometric sample was obtained from the biometric subject.			
Field Min	1	Occur Min	0	
Field Max	300	Occur Max	1	
Char Types	U	Special Chars		
Format	n/a	Constraints	n/a	
Code List				
Source	BSWG			
XML Level 1	dod-ebts:CollectionReasonText		Cardinality	0...1
XML Level 2			Cardinality	
XML Level 3			Cardinality	
XML Level 4			Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0 Yes DoD EBTS 4.0 Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8106

Triggering Event

Mnemonic	EVENT		Conditionality	0			
			Status	Active			
Description	Something that happens at a given place and time that triggers subsequent collection encounter.						
Field Min	n/a	Occur Min	0				
Field Max	n/a	Occur Max	Unlimited				
Char Types	n/a	Special Chars					
Format	n/a	Constraints	n/a				
Code List							
Source	Referenced by DoD EBTS 2.0. Coordination with DoD ABIS required. Pending approval.						
XML Level 1	dod-ebts:TriggeringEvent		Cardinality	0..1			
XML Level 2			Cardinality				
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

2.8106_0

Triggering Event

Subfields: Repeating sets of information items

Mnemonic	EVENT_0		Conditionality	0			
			Status	New-Active			
Description	Repeating subfield for Triggering Event.						
Field Min	n/a	Occur Min	0				
Field Max	n/a	Occur Max	*				
Char Types	n/a	Special Chars					
Format	n/a	Constraints	n/a				
Code List							
Source	EBTS 4.0						
XML Level 1	dod-ebts:TriggeringEvent		Cardinality	0..*			
XML Level 2			Cardinality				
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-2: User-Defined Descriptive Text

Page 207 of 1037

2.8106_1

Triggering Event

Triggering Event Identifier

Mnemonic	EVENT_ID	Conditionality	O
		Status	Active
Description	The unique identifier for the triggering event.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	ANS	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Referenced by DoD EBTS 2.0. Coordination with DoD ABIS required. Pending approval.		
XML Level 1	dod-ebts:TriggeringEvent	Cardinality	0..*
XML Level 2	nc:Activity	Cardinality	0..1
XML Level 3	nc:ActivityIdentification/nc:IdentificationID	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

2.8106_2

Triggering Event

Address Line 1

Mnemonic	ADD1	Conditionality	O
		Status	Active
Description	The street, including both number and name.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Referenced by DoD EBTS 2.0. Coordination with DoD ABIS required. Pending approval.		
XML Level 1	dod-ebts:TriggeringEvent	Cardinality	0..*
XML Level 2	nc:Activity	Cardinality	0..1
XML Level 3	nc:AddressFullText	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-2: User-Defined Descriptive Text

Page 208 of 1037

2.8106_3

Triggering Event

Address Line 2

Mnemonic	ADD2	Conditionality	0
		Status	Active
Description	Additional information about the street e.g. apt #.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Referenced by DoD EBTS 2.0. Coordination with DoD ABIS required. Pending approval.		
XML Level 1	dod-ebts:TriggeringEvent	Cardinality	0..*
XML Level 2	nc:Activity	Cardinality	0...1
XML Level 3	nc:StreetFullText	Cardinality	0...1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

2.8106_4

Triggering Event

City

Mnemonic	CITY	Conditionality	0
		Status	Active
Description	Name of the city.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Referenced by DoD EBTS 2.0. Coordination with DoD ABIS required. Pending approval.		
XML Level 1	dod-ebts:TriggeringEvent	Cardinality	0..*
XML Level 2	nc:Activity	Cardinality	0...1
XML Level 3	nc:LocationCityName	Cardinality	0...1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8106_6

Triggering Event

Country Code

Mnemonic	CTRY			Conditionality	O
				Status	Active
Description	The GENC alpha3 country code. The DoD EBTS 4.0 default for this field is the GENC three character alpha codelist (genc:CountryAlpha3CodeType).				
Field Min	3	Occur Min	0		
Field Max	3	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	Referenced by DoD EBTS 2.0. Coordination with DoD ABIS required. Pending approval.				
XML Level 1	dod-ebts:TriggeringEvent	Cardinality	0..*		
XML Level 2	nc:Activity	Cardinality	0...1		
XML Level 3	Genc:countryAlpha3CodeType	Cardinality	0...1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8106_7

Triggering Event

Village

Mnemonic	VLG			Conditionality	O
				Status	Active
Description	Small population unit, typically rural, held together by common economic and political ties.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	Referenced by DoD EBTS 2.0. Coordination with DoD ABIS required. Pending approval.				
XML Level 1	dod-ebts:TriggeringEvent	Cardinality	0..*		
XML Level 2	nc:Activity	Cardinality	0...1		
XML Level 3	dod-ebts:village	Cardinality	0...1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8106_8

Triggering Event

Event Description

Mnemonic	EVENT_DESC	Conditionality	O
		Status	Active
Description	The textual description of an event that triggers subsequent collection encounter.		
Field Min	1	Occur Min	0
Field Max	255	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Referenced by DoD EBTS 2.0. Coordination with DoD ABIS required. Pending approval.		
XML Level 1	dod-ebts:TriggeringEvent	Cardinality	0..*
XML Level 2	nc:Activity	Cardinality	0..1
XML Level 3	nc:ActivityName	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

2.8106_9

Triggering Event

Comment

Mnemonic	COM	Conditionality	O
		Status	Active
Description	The optional Comment field appears in many record types and may be used to insert free text information. It is not reserved exclusively for log-related information but has historically often been used for this purpose. It is limited to maximum of 126 characters. This maximum size was established in order to maintain consistency across encodings. The maximum size differed in the 2007 and 2008 versions of the standard.		
Field Min	1	Occur Min	0
Field Max	126	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Referenced by DoD EBTS 2.0. Coordination with DoD ABIS required. Pending approval.		
XML Level 1	dod-ebts:TriggeringEvent	Cardinality	0..*
XML Level 2	nc:Activity	Cardinality	0..1
XML Level 3	nc:ActivityDescriptionText	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8106_10

Triggering Event

Event Status

Mnemonic	EVENT-STATUS		Conditionality	0
			Status	New-Emerging
Description	The status of the related actions, events, or process steps.			
Field Min	1	Occur Min	0	
Field Max	50	Occur Max	1	
Char Types	AN	Special Chars		
Format	n/a	Constraints	n/a	
Code List				
Source	ANSI NIST ITL 2011: Update 13 Type 11 Field Addition and NIEM 3.0			
XML Level 1	dod-ebts:TriggeringEvent	Cardinality	0..*	
XML Level 2	nc:Activity	Cardinality	0..1	
XML Level 3	nc:StatusCommentText	Cardinality	0..1	
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0 No DoD EBTS 4.0 Yes

2.8106_11

Triggering Event

Event Date

Mnemonic	EVENT_DATE		Conditionality	0
			Status	New-Emerging
Description	The date for related actions, events, or process steps.			
Field Min	Encoding Specific	Occur Min	0	
Field Max	Encoding Specific	Occur Max	1	
Char Types	ANS	Special Chars		
Format	n/a	Constraints	n/a	
Code List				
Source	ANSI NIST ITL 2011: Update 13 Type 11 Field Addition and NIEM 3.0			
XML Level 1	dod-ebts:TriggeringEvent	Cardinality	0..*	
XML Level 2	nc:Activity	Cardinality	0..1	
XML Level 3	nc:ActivityDateRepresentation/nc:Date	Cardinality	0..1	
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0 No DoD EBTS 4.0 Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8107

Biometric Subject Privacy Act Indicator

Mnemonic	PRI_ACT	Conditionality	0
		Status	Active
Description	This field indicates whether U.S. citizens or U.S. persons who are being enrolled have signed a privacy act disclosure that would allow their biometrics to be captured.		
Field Min	1	Occur Min	0
Field Max	1	Occur Max	1
Char Types	A	Special Chars	
Format	n/a	Constraints	See Look Up Codes
Code List	YES NO CODE		
Source	BSWG		
XML Level 1	dod-ebts:PersonPrivacyActIndicator	Cardinality	0..1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

2.8108

Employment

Encounter Comment

Mnemonic	ENCTR_COM	Conditionality	0
		Status	Active
Description	The comments or notes on the encounter mission in which the biometric sample was collected including any extenuating circumstances of the encounter.		
Field Min	1	Occur Min	0
Field Max	1000	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:EncounterCommentText	Cardinality	0..1
XML Level 2	nc:CommentText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8109

Repository Candidate List

Mnemonic	REPO_CAN		Conditionality	0			
			Status	Active			
Description	This grouped field shall contain a candidate list. It is composed of four information items: Name of DesignatedRepository, Candidate Identifier Type, Candidate Identifier and Candidate Name. These fields will be provided for each candidate in the list.						
Field Min	n/a	Occur Min	0				
Field Max	n/a	Occur Max	1				
Char Types	n/a	Special Chars					
Format	n/a	Constraints	n/a				
Code List							
Source	Referenced by DoD EBTS 2.0.Coordination with DoD ABIS required.Pending approval.						
XML Level 1	dod-ebts:RepositoryCandidateList		Cardinality	0..1			
XML Level 2			Cardinality				
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

2.8109_0

Repository Candidate List

Subfields: Repeating sets of information items

Mnemonic	REPO_CAN_0		Conditionality	0			
			Status	New-Active			
Description	Repeating subfield for Repository Candidate List.						
Field Min	n/a	Occur Min	0				
Field Max	n/a	Occur Max	*				
Char Types	n/a	Special Chars					
Format	n/a	Constraints	n/a				
Code List							
Source	EBTS 4.0						
XML Level 1	dod-ebts:RepositoryCandidateList		Cardinality	0..*			
XML Level 2			Cardinality				
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8109_1

Repository Candidate List

Name of Designated Repository

Mnemonic	NDR			Conditionality	O
				Status	Active
Description	This field contains the numerical designation of the repository to be searched. Repository numbers are assigned by the CJIS Division. Multiple entries in this field will indicate a desire to search more than one repository.				
Field Min	1	Occur Min	0		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars			
Format	n/a	Constraints	n/a		
Code List	DESIGNATED REPOSITORY NAME				
Source	Referenced by DoD EBTS 2.0.				
XML Level 1	dod-ebts:RepositoryCandidateList			Cardinality	0...*
XML Level 2	nc:RepositoryID/nc:IdentificationID			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8109_2

Repository Candidate List

Repository Candidate Identifier Category Code

Mnemonic	CAN_ID_CAT_CD			Conditionality	O
				Status	Active
Description	The category of the candidate identification such as DoD Number, FBI Number, etc.				
Field Min	3	Occur Min	0		
Field Max	3	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	n/a		
Code List	IDENTIFIER TYPE CODES				
Source	Referenced by DoD EBTS 2.0.				
XML Level 1	dod-ebts:RepositoryCandidateList			Cardinality	0...*
XML Level 2	dod-ebts:RepositoryCandidateCode			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8109_3

Repository Candidate List

Repository Candidate Identifier

Mnemonic	CAN_ID	Conditionality	O
		Status	Active
Description	The identifying value for the candidate's identification.		
Field Min	1	Occur Min	0
Field Max	100	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Referenced by DoD EBTS 2.0.		
XML Level 1	dod-ebts:RepositoryCandidateList	Cardinality	0..*
XML Level 2	dod-ebts:CandidateID/nc:IdentificationID	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

2.8109_4

Repository Candidate List

Repository Candidate Name

Mnemonic	CAN_NAM	Conditionality	O
		Status	Active
Description	The name of a person included in a Repository Candidate List. For DoD Candidate List/Candidate Name, use the "UNKNOWN, XX" when the name of the subject is unknown and is mandatory.		
Field Min	1	Occur Min	0
Field Max	100	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Referenced by DoD EBTS 2.0.		
XML Level 1	dod-ebts:RepositoryCandidateList	Cardinality	0..*
XML Level 2	nc:PersonFullName	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

2.811

Iris Image Omitted Reason

Mnemonic	IOMITTED		Conditionality	0	
			Status	Active	
Description	Reason why the iris image aka Type-17 record is not present in the associated file.				
Field Min	1		Occur Min	0	
Field Max	1		Occur Max	1	
Char Types	A		Special Chars		
Format	n/a		Constraints	n/a	
Code List	IRIS IMAGE OMITTED REASON CODES				
Source	BSWG				
XML Level 1	dod-ebts:IrisImageOmittedReasoncode		Cardinality	0..1	
XML Level 2	dod-ebts:IrisImageOmittedReason		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

2.8114

Collection Location

Mnemonic	COLL_BLO		Conditionality	0	
			Status	Active	
Description	The field is used to capture the geographic location where the biometric sample was collected for the entire submission. This field can also be used to capture the geographic location where the Type-2 data was collected if it is captured at a different location. This field was previously 2.301 BLO in DoD EBTS 1.2 and 2.8100 COLL_BLO with extended size in DoD EBTS 2.0. With ANSI/NIST ITL 1-2011, many logical records have included a field X.998 GEO that captures the geographic location where the data was collected. A Type-2 field is still needed for response transactions.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	BSWG				
XML Level 1	dod-ebts:CollectionLocationDetail		Cardinality	0..1	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8114_0

Collection Location

Subfields: Repeating sets of information items

Mnemonic	COLL_BLO_0	Conditionality	O
		Status	New-Active
Description	Repeating subfield for Collection Location.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	*
Char Types	n/a	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	EBTS 4.0		
XML Level 1	dod-ebts:CollectionLocationDetail	Cardinality	0...*
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.8114_01

Collection Location

Universal Time Entry

Mnemonic	UTE	Conditionality	O
		Status	Active
Description	The coordinated universal time (UTC) where the biometric sample was collected. This time is independent of the actual time zone where the time and date is recorded. The date is YYYYMMDDhhmmssZ, where the Z is indicates the zone description of 0 hours. If sample collection time is unknown, set it to "00000000000000Z."		
Field Min	15	Occur Min	0
Field Max	15	Occur Max	1
Char Types	ANS	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:CollectionLocationDetail	Cardinality	0...*
XML Level 2	biom_2:CaptureUTCDateTime/nc:DateTime	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8114_02

Collection Location

Latitude Degree Value

Mnemonic	LTD	Conditionality	M↑
		Status	Active
Description	The second information item is latitude degree value (LTD). This is a value that specifies the degree of latitude. The value shall be between -90 (inclusive) and +90 (inclusive). The degrees may be expressed as an integer (without a decimal) or a real number including decimals. If decimals are present, then minutes and seconds shall be empty. Examples: Buenos Aires, Argentina: -34 (with minutes LTM = 36) NIST, Gaithersburg, Maryland: 39.137627 (no LTM or LTS)		
Field Min	1	Occur Min	1
Field Max	9	Occur Max	1
Char Types	NS	Special Chars	
Format	n/a	Constraints	=90 <= LTD <= 90
Code List			
Source	BSWG		
XML Level 1	dod-ebts:CollectionLocationDetail	Cardinality	0...*
XML Level 2	nc:LatitudeDegreeValue	Cardinality	1...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

2.8114_03

Collection Location

Latitude Minute Value

Mnemonic	LTM	Conditionality	O
		Status	Active
Description	This information item is latitude minute value (LTM). This is a value that specifies a minute of a degree. The value shall be between 0 (inclusive) to 60 (exclusive). The minute value may be expressed as an integer (without a decimal) or as a real number including decimals. If decimals are present then seconds shall be empty. Thus, the allowed special character is a period. The minute value can be empty, even if the degree value is an integer. LTM and LGM are co-conditional, so they shall both be present if either is present.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	NS	Special Chars	
Format	n/a	Constraints	0 <= LTM < 60
Code List			
Source	BSWG		
XML Level 1	dod-ebts:CollectionLocationDetail	Cardinality	0...*
XML Level 2	nc:LatitudeMinuteValue	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8114_04

Collection Location

Latitude Second Value

Mnemonic	LTS	Conditionality	O
		Status	Active
Description	The fourth information item is the latitude second value (LTS). This is a value that specifies a second of a minute. The integer shall be 0 (inclusive) to 60 (exclusive). The second value is empty, even if the minute value is an integer.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	N	Special Chars	
Format	n/a	Constraints	0 <= LTS < 60
Code List			
Source	BSWG		
XML Level 1	dod-ebts:CollectionLocationDetail	Cardinality	0...*
XML Level 2	nc:LatitudeSecondValue	Cardinality	0...1
XML Level 3	nc:GeographicCoordinateLongitude	Cardinality	0...1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

2.8114_05

Collection Location

Longitude Degree Value

Mnemonic	LGD	Conditionality	M↑
		Status	Active
Description	The fifth information item is the longitude degree value (LGD). It is a value that specifies the degree of a longitude. The value shall be between -180 (inclusive) and +180 (inclusive). If LTD is present, then LGD shall be present. The degrees may be expressed as whole numbers (without a decimal) or real numbers including decimals. If decimals are present, then minutes and seconds are empty. Examples: Buenos Aires, Argentina: -58 (with minutes LGM = 22), NIST, Gaithersburg, Maryland: -77.216032 (no LGM or LGS)		
Field Min	1	Occur Min	1
Field Max	10	Occur Max	1
Char Types	NS	Special Chars	
Format	n/a	Constraints	=-80 <= LGD <= 180
Code List			
Source	BSWG		
XML Level 1	dod-ebts:CollectionLocationDetail	Cardinality	0...*
XML Level 2	nc:LongitudeDegreeValue	Cardinality	1...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8114_06

Collection Location

Longitude Minute Value

Mnemonic	LGM	Conditionality	0
		Status	Active
Description	The sixth information item is the longitude minute value (LGM). It is a value that specifies a minute of a degree. The value shall be from 0 (inclusive) to 60 (exclusive). The minute value may be expressed as an integer (without a decimal) or as a real number including decimals. If decimals are present then seconds shall not appear. The minute value is empty, even if the degree value is an integer. If LTM is present, then LGM shall be present.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	NS	Special Chars	
Format	n/a	Constraints	0 <=LGS<60
Code List			
Source	BSWG		
XML Level 1	dod-ebts:CollectionLocationDetail	Cardinality	0...*
XML Level 2	nc:LongitudeMinuteValue	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

2.8114_07

Collection Location

Longitude Second Value

Mnemonic	LGS	Conditionality	0
		Status	Active
Description	The seventh information item is the longitude second value (LGS). This is a value that specifies a second of a minute. The integer shall be 0 (inclusive) to 60 (exclusive). The second value is empty, even if the minute value is an integer. If LTS is present, then LGS shall be present.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	N	Special Chars	
Format	n/a	Constraints	0 <=LGM<60
Code List			
Source	BSWG		
XML Level 1	dod-ebts:CollectionLocationDetail	Cardinality	0...*
XML Level 2	nc:LongitudeSecondValue	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8114_08

Collection Location

Elevation

Mnemonic	ELE	Conditionality	O
		Status	Active
Description	The eighth information item is elevation (ELE). It is expressed in meters. It is a numeric value. It is between -422 meters (Dead Sea) and 8848 meters (Mount Everest). Allowed special characters are the negative sign and the period.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	NS	Special Chars	
Format	n/a	Constraints	-422.000 <ELE< 8848.000; real number
Code List			
Source	BSWG		
XML Level 1	dod-ebts:CollectionLocationDetail	Cardinality	0...*
XML Level 2	nc:LocationElevation	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

2.8114_09

Collection Location

Geodetic Datum Code

Mnemonic	GDC	Conditionality	O
		Status	Active
Description	The ninth information item is the geodetic datum code (GDC11). It is an alphanumeric value of 3 to 6 characters in length. This information item is used to indicate which coordinate system was used to represent the values in information items 2 through 7. If no entry is made in this information item, then the basis for the values entered in the first eight information items shall be WGS84, the code for the World Geodetic Survey 1984 version - WGS 84 (G873). See look up codes for values. If no entry is made in this information item, then the basis for the values entered in the first eight information items shall be WGS84, the code for the World Geodetic Survey 1984 version - WGS 84 (G873). See look up codes for values.		
Field Min	3	Occur Min	0
Field Max	6	Occur Max	1
Char Types	AN	Special Chars	
Format	n/a	Constraints	n/a
Code List	GEOGRAPHIC COORDINATE DATUM CODE		
Source	BSWG		
XML Level 1	dod-ebts:CollectionLocationDetail	Cardinality	0...*
XML Level 2	biom_1:GeodeticDatumCoordinateSystemCode	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8114_10

Collection Location

Geographic Coordinate Universal Transverse Mercator Zone

Mnemonic	GCM			Conditionality	M↑
				Status	Active
Description	It is an alphanumeric value of 2 to 3 characters. This is a one or two digit UTM zone number followed by the 8 degree latitudinal band designator (which is a single letter).				
Field Min	2	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	AN	Special Chars			
Format	n/a	Constraints	One or two integers followed by a single letter		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:CollectionLocationDetail			Cardinality	0...*
XML Level 2	nc:UTMZoneNumeric			Cardinality	1...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8114_11

Collection Location

Geographic Coordinate Universal Transverse Mercator Easting

Mnemonic	GCE			Conditionality	M↑
				Status	Active
Description	The eleventh information item is the geographic coordinate universal transverse Mercator easting (GCE). It is an integer of 1 to 6 digits.				
Field Min	1	Occur Min	1		
Field Max	6	Occur Max	1		
Char Types	N	Special Chars			
Format	n/a	Constraints	integer		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:CollectionLocationDetail			Cardinality	0...*
XML Level 2	nc:UTMEastingValue			Cardinality	1...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-2: User-Defined Descriptive Text

Page 223 of 1037

2.8114_12

Collection Location

Geographic Coordinate Universal Transverse Mercator Northing

Mnemonic	GCN			Conditionality	M↑
				Status	Active
Description	The twelfth information item is the geographic coordinate universal transverse Mercator northing (GCN). It is an integer of 1 to 8 digits.				
Field Min	1	Occur Min	1		
Field Max	8	Occur Max	1		
Char Types	N	Special Chars			
Format	n/a	Constraints	integer		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:CollectionLocationDetail			Cardinality	0...*
XML Level 2	nc:UTMNorthingValue			Cardinality	1...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8114_13

Collection Location

Geographic Reference Text

Mnemonic	GRT			Conditionality	O
				Status	Active
Description	It is a free form text describing a street address or other physical location (such as 'Corner of Washington and Madison, Geneva, NY').				
Field Min	1	Occur Min	0		
Field Max	150	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:CollectionLocationDetail			Cardinality	0...*
XML Level 2	nc:LocationDescriptionText			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8114_14

Collection Location

Geographic Coordinate Other System Identifier

Mnemonic	OSI			Conditionality	M↑
				Status	Active
Description	A fourteenth optional information item geographic coordinate other system identifier (OSI) allows for other coordinate systems. This information items specifies the system identifier. It is up to 10 characters in length. Examples are: • MGRS (Militar Grid Reference System), • USNG (United States National Grid), • GARS (Global Area Reference System), • GEOREF (World Geographic Reference), • LANDMARK landmark (e.g. hydant) and position relative to the landmark.				
Field Min	1	Occur Min	1		
Field Max	10	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:CollectionLocationDetail			Cardinality	0...*
XML Level 2	biom_1:GeographicLocationSystemName			Cardinality	1...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8114_15

Collection Location

Geographic Coordinate Other System Value

Mnemonic	OCV			Conditionality	M↑
				Status	Active
Description	A fifteenth optional information item, is the geographic coordinate other system value (OCV). It shall only be present if OSI is present in the record. It can be up to 126 characters in length. If OSI is LANDMARK, OCV is free text and may be up to 126 characters. For details on the formatting of OCV for the other coordinate systems shown in OSI as examples, see http://earth-info.nga.mil/GandG/coordsys/grids/referencesys.html .				
Field Min	1	Occur Min	1		
Field Max	126	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:CollectionLocationDetail			Cardinality	0...*
XML Level 2	biom_2:GeographicLocationText			Cardinality	1...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-2: User-Defined Descriptive Text

Page 225 of 1037

2.8114_16

Collection Location

City

Mnemonic	CITY	Conditionality	O
		Status	Active
Description	Name of the city.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:CollectionLocationDetail	Cardinality	0...*
XML Level 2	nc:LocationCityName	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

2.8114_17

Collection Location

State / Province

Mnemonic	STATE	Conditionality	O
		Status	Active
Description	The state, province or subdivision of a location.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:CollectionLocationDetail	Cardinality	0...*
XML Level 2	nc:LocationStateName	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-2: User-Defined Descriptive Text

Page 226 of 1037

2.8114_18

Collection Location

Country Code

Mnemonic	CTRY			Conditionality	M↑
				Status	Active
Description	The GENC alpha3 country code.				
Field Min	3	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	n/a		
Code List	GENC ALPHA3 CODES				
Source	BSWG				
XML Level 1	dod-ebts:CollectionLocationDetail			Cardinality	0...*
XML Level 2	Genc:countryAlpha3CodeType			Cardinality	1...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8114_19

Collection Location

Village

Mnemonic	VLG			Conditionality	O
				Status	Active
Description	Small population unit, typically rural, held together by common economic and political ties.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:LocationVillageName			Cardinality	0...*
XML Level 2	dod-ebts:village			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-2: User-Defined Descriptive Text

Page 227 of 1037

2.8114_20

Collection Location

Record Category Code Referenced

Mnemonic	REC	Conditionality	0
		Status	Active
Description	The code for the logical record referenced.		
Field Min	1	Occur Min	0
Field Max	1	Occur Max	1
Char Types	N	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:RecordCategoryCode	Cardinality	0..*
XML Level 2		Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

2.8115

Operational Personnel

Mnemonic	OPER	Conditionality	0
		Status	Active
Description	This set of fields shall identify the name information, contact information, unit/organization, role, rank/grade, identification type and the identification identifier of the personnel assigned to specific day-to-day responsibility for program activities.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:OperationalPersonnel	Cardinality	0..1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8115_0

Operational Personnel

Subfields: Repeating sets of information items

Mnemonic	OPER_0			Conditionality	O
				Status	New-Active
Description	Repeating subfield for Operational Personnel.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	*		
Char Types	n/a	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	EBTS 4.0				
XML Level 1	dod-ebts:OperationalPersonnel			Cardinality	0...*
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.8115_1

Operational Personnel

Operational Personnel Unit/Organization

Mnemonic	OPORG			Conditionality	O
				Status	Active
Description	The name or identifier for the operational unit or organization the Operational Personnel belongs to.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:OperationalPersonnel			Cardinality	0...*
XML Level 2	dod-ebts:OperationalUnitName			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8115_2

Operational Personnel

Operational Personnel Role

Mnemonic	OPRL			Conditionality	M↑
				Status	Active
Description	The role of the Operational Personnel.				
Field Min	1	Occur Min	1		
Field Max	50	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	n/a		
Code List	OPERATIONAL PERSONNEL CODES				
Source	BSWG				
XML Level 1	dod-ebts:OperationalPersonnel			Cardinality	0...*
XML Level 2	dod-ebts:OperationalPersonnelCategoryCode			Cardinality	1...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8115_3

Operational Personnel

Rank Grade Code

Mnemonic	RANK			Conditionality	0
				Status	Active
Description	The military rank or civilian rank of the person.				
Field Min	1	Occur Min	0		
Field Max	20	Occur Max	1		
Char Types	ANS	Special Chars			
Format	n/a	Constraints	n/a		
Code List	MILITARY RANK GRADE CODES				
Source	BSWG				
XML Level 1	dod-ebts:OperationalPersonnel			Cardinality	0...*
XML Level 2	dod-ebts:RankGradeCode			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8115_4

Operational Personnel

US Person Indicator

Mnemonic	USIND		Conditionality	O			
			Status	Active			
Description	The indicator of whether an individual is a citizen of the United States, an alien lawfully admitted for permanent residence in the United States, or a member of the U.S. Armed Forces.						
Field Min	1	Occur Min	0				
Field Max	1	Occur Max	1				
Char Types	A	Special Chars					
Format	n/a	Constraints	n/a				
Code List	YES NO CODE						
Source	BSWG						
XML Level 1	dod-ebts:OperationalPersonnel		Cardinality	0...*			
XML Level 2	dod-ebts:USPersonIndicator or od-ebts:OperationalPersonnelIdentification		Cardinality	0...1			
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

2.8115_5

Operational Personnel

Operational Personnel Identifier Type

Mnemonic	OPIDCATCD		Conditionality	M↑			
			Status	Active			
Description	The type of unique identifier of the Operational Personnel, such as Social Security Number.						
Field Min	3	Occur Min	1				
Field Max	7	Occur Max	1				
Char Types	A	Special Chars					
Format	n/a	Constraints	n/a				
Code List	OPERATIONAL PERSONNEL IDENTIFIER CODES						
Source	BSWG						
XML Level 1	dod-ebts:OperationalPersonnel		Cardinality	0...*			
XML Level 2	dod-ebts:OperationalPersonnelIDCategoryCode		Cardinality	1...1			
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8115_6

Operational Personnel

Operational Personnel Identifier

Mnemonic	OPID			Conditionality	M↑
				Status	Active
Description	The value of the unique identifier of the Operational Personnel, such as Social Security Number.				
Field Min	1	Occur Min	1		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:OperationalPersonnel			Cardinality	0...*
XML Level 2	dod-ebts:OperationalPersonnelID/nc:IdentificationID			Cardinality	1...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8115_7

Operational Personnel

Name - One

Mnemonic	NAM1			Conditionality	M↑
				Status	Active
Description	The last name, surname or the family name of the person. Enter "UNKNOWN" if this information item is required and not available at the time of collection. Can be mapped to the Arabic Nasab name, a patronymic or series of patronymics.				
Field Min	1	Occur Min	1		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:OperationalPersonnel			Cardinality	0...*
XML Level 2	nc:PersonSurName			Cardinality	1...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8115_8

Operational Personnel

Name - Two

Mnemonic	NAM2			Conditionality	M↑
				Status	Active
Description	The personal name of a person. It is typically the first name in western culture. Enter "UNKNOWN" if this information item is required and not available at the time of collection. Can be mapped to the Arabic Ism name, the main name of an Arab person; his or her personal name e.g. "Kareem" or "Fatimah".				
Field Min	1	Occur Min	1		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:OperationalPersonnel			Cardinality	0...*
XML Level 2	nc:PersonGivenName			Cardinality	1...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8115_9

Operational Personnel

Name - Three

Mnemonic	NAM3			Conditionality	M↑
				Status	Active
Description	The middle name of a person. It is placed between the first given name and the surname. Enter "UNKNOWN" if this information item is required and not available at the time of collection. Can be mapped to the Arabic Kunya name, the person's first-born son is used as a substitute for the ISM.				
Field Min	1	Occur Min	1		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:OperationalPersonnel			Cardinality	0...*
XML Level 2	nc:PersonMiddleName			Cardinality	1...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8115_10

Operational Personnel

Name - Four

Mnemonic	NAM4		Conditionality	0	
			Status	Active	
Description	A name of a person to represent the fourth name for a culture using four or five names e.g., a tribal or village name. It will be given the ranking of fourth importance of naming in the culture from which the person is associated. Enter "UNKNOWN" if this information item is required and not available at the time of collection. Can be mapped to the Arabic Nisbah name, describes a person's occupation, geographic home area, or descent tribe, family, etc..				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:OperationalPersonnel		Cardinality	0...*	
XML Level 2	ebts:PersonFourthImportanceName		Cardinality	0...1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8115_11

Operational Personnel

Name - Five

Mnemonic	NAM5		Conditionality	0	
			Status	Active	
Description	A name of a person to represent the fifth name for a culture using four or five names e.g., a tribal or village name. It will be given the ranking of fifth importance of naming in the culture from which the person is associated. Enter "UNKNOWN" if this information item is required and not available at the time of collection. Can be mapped to the Arabic Laqab name, intended as a description of the person. Also can be used for the honorific title.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:OperationalPersonnel		Cardinality	0...*	
XML Level 2	ebts:PersonFifthImportanceName		Cardinality	0...1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8115_12

Operational Personnel

Phone Number

Mnemonic	PHNUM			Conditionality	O
				Status	Active
Description	The full telephone number including international country code and area code. Space and hyphen are allowed.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	ANS	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:OperationalPersonnel			Cardinality	0...*
XML Level 2	nc:ContactTelephoneNumber or nc:FullTelephoneNumber or nc:TelephoneNumberFullID			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8115_13

Operational Personnel

Email Address

Mnemonic	EMAIL			Conditionality	O
				Status	Active
Description	Identifies an email box to which email messages are delivered. Application Profile might be more specific to what characters are allowed to be entered for the email address.				
Field Min	1	Occur Min	0		
Field Max	254	Occur Max	1		
Char Types	ANS	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:OperationalPersonnel			Cardinality	0...*
XML Level 2	nc:ContactEmailID			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8116

Transportation

Mnemonic	TRANSPORT			Conditionality	0
				Status	Active
Description	A set of fields for capturing the method of transportation on which the biometric subject was encountered, the type of identification and identifier assigned to the conveyance. This field was previously 2.8105 CONVEY in DoD EBTS 2.0.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	n/a	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:TransportCategoryCode			Cardinality	0...*
XML Level 2	dod-ebts:Transportation			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8116_1

Transportation

Transport Type

Mnemonic	TRANSPORT_TYP			Conditionality	0
				Status	Active
Description	The category of transportation on which the biometric subject was encountered. Additional valid values for TRUCK, BUS, BIKE, MTRB, ANML, and TRAIN have been added.				
Field Min	3	Occur Min	0		
Field Max	6	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	n/a		
Code List	TRANSPORTATION TYPE CODES				
Source	BSWG				
XML Level 1	dod-ebts:TransportCategoryCode			Cardinality	0...1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8116_2

Transportation

Transport Identifier Category Code

Mnemonic	TRANSPORT_IDCATCD			Conditionality	O
				Status	Active
Description	The type of identification assigned to a conveyance.				
Field Min	2	Occur Min	0		
Field Max	20	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	n/a		
Code List	TRANSPORTATION IDENTIFIER TYPE CODES				
Source	BSWG				
XML Level 1	dod-ebts:TransportCategoryCode			Cardinality	0...1
XML Level 2	dod-ebts:TransportIdentificationCategoryCode			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8116_3

Transportation

Transport Identifier

Mnemonic	TRANSPORT_ID			Conditionality	O
				Status	Active
Description	The identifier assigned to a conveyance.				
Field Min	1	Occur Min	0		
Field Max	20	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:TransportCategoryCode			Cardinality	0...1
XML Level 2	dod-ebts:TransportIdentification/nc:IdentificationID			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-2: User-Defined Descriptive Text

Page 237 of 1037

2.8116_4

Transportation

Transport Make

Mnemonic	TRANSPORT_MAK			Conditionality	O
				Status	Active
Description	The manufacturer of the transportation device.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:TransportCategoryCode			Cardinality	0...1
XML Level 2	dod-ebts:TransportMakeName			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8116_5

Transportation

Transport Model

Mnemonic	TRANSPORT_MOD			Conditionality	O
				Status	Active
Description	The model number of the transportation device.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:TransportCategoryCode			Cardinality	0...1
XML Level 2	dod-ebts:TransportModelName			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-2: User-Defined Descriptive Text

Page 238 of 1037

2.8116_6

Transportation

Transport Model Year

Mnemonic	TRANSPORT_MODYR			Conditionality	O
				Status	Active
Description	The model year of the transportation device.				
Field Min	4	Occur Min	0		
Field Max	4	Occur Max	1		
Char Types	N	Special Chars			
Format	YYYY	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:TransportCategoryCode			Cardinality	0...1
XML Level 2	dod-ebts:TransportModelYear			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8116_7

Transportation

Transport Color

Mnemonic	TRANSPORT_COL			Conditionality	O
				Status	Active
Description	The primary color of the transportation device.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	AN	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:TransportCategoryCode			Cardinality	0...1
XML Level 2	dod-ebts:TransportColorDescriptionText			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8116_8

Transportation

Comment

Mnemonic	COM	Conditionality	O
		Status	Active
Description	The optional Comment field appears in many record types and may be used to insert free text information. It is not reserved exclusively for log-related information but has historically often been used for this purpose. It is limited to a maximum of 126 characters. This maximum size was established in order to maintain consistency across encodings. The maximum size differed in the 2007 and 2008 versions of the standard. The FBI field 2.067 Image Capture Equipment is only used with fingerprint image capture equipment. A new field 2.8118 has been created to close the gap to capture the MMS information for Type-2 or the entire submission. An information item for Record Category Code has also been added to allow designation which logical record the information does pertain to, either the entire submission or just the Type-2 data only.		
Field Min	1	Occur Min	0
Field Max	126	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:TransportCategoryCode	Cardinality	0..1
XML Level 2	nc:CommentText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

2.8117

Facial Image Omitted Reason

Mnemonic	FOMITTED	Conditionality	O
		Status	Active
Description	Reason why the facial image aka as full frontal pose Type-10 record is not present in the associated file.		
Field Min	2	Occur Min	0
Field Max	2	Occur Max	1
Char Types	A	Special Chars	
Format	n/a	Constraints	n/a
Code List	FACIAL IMAGE OMITTED REASON		
Source	BSWG		
XML Level 1	dod-ebts:FacialImageOmittedReason	Cardinality	
XML Level 2	biom_2:FacialImageMissingReasonCode	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8118

Collection Equipment Make/Model/Serial Number

Mnemonic	COLL_MMS_0	Conditionality	0
		Status	Active
Description	This field is used to capture the Make, Model and Serial Number MMS of the equipment used to collect data for the entire submission. This field can also be used to indicate of the equipment used to capture just the Type-2 data. With ANSI/NIST ITL 1-2011, many logical records include a field X.904 MMS and 17.019 MMS that capture the make/model/serial number of the equipment the sample was collected with. A Type-2 field is still needed to capture the MMS information for just the Type-2 data or for the entire submission.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	biom_2:ImageCaptureType	Cardinality	0..1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

2.8118_0

Collection Equipment Make/Model/Serial Number

Subfields: Repeating sets of information items

Mnemonic	COLL_MMS	Conditionality	0
		Status	New-Active
Description	Repeating subfield for Collection Equipment Make/Model/Serial Number.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	*
Char Types	n/a	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	EBTS 4.0		
XML Level 1	biom_2:ImageCaptureType	Cardinality	0..*
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-2: User-Defined Descriptive Text

Page 241 of 1037

2.8118_1

Collection Equipment Make/Model/Serial Number

Make

Mnemonic	MAK	Conditionality	O
		Status	Active
Description	The name of the manufacturer for the capture device.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	biom_2:ImageCaptureType	Cardinality	0..*
XML Level 2	biom_2:CaptureDeviceMakeText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

2.8118_2

Collection Equipment Make/Model/Serial Number

Model

Mnemonic	MOD	Conditionality	O
		Status	Active
Description	The model number for the capture device.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	biom_2:ImageCaptureType	Cardinality	0..*
XML Level 2	biom_2:CaptureDeviceModelText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8118_3

Collection Equipment Make/Model/Serial Number

Serial Number

Mnemonic	SER	Conditionality	O
		Status	Active
Description	The serial number for the capture device.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	biom_2:ImageCaptureType	Cardinality	0..*
XML Level 2	biom_2:CaptureDeviceSerialNumberText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

2.8118_4

Collection Equipment Make/Model/Serial Number

Record Category Code Referenced

Mnemonic	REC	Conditionality	O
		Status	Active
Description	The code for the logical record referenced.		
Field Min	1	Occur Min	0
Field Max	1	Occur Max	1
Char Types	N	Special Chars	
Format	n/a	Constraints	n/a
Code List	RECORD CATEGORY CODE REFERENCED CODES		
Source	BSWG		
XML Level 1	biom_2:ImageCaptureType	Cardinality	0..*
XML Level 2	dod-ebts:RecordCategoryCode	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8118_5

Collection Equipment Make/Model/Serial Number

Capture Location

Mnemonic	CAPT_LOC			Conditionality	O
				Status	New-Emerging
Description	A location where a biometric sample was collected.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	NIEM Biometric Domain				
XML Level 1	biom_2:ImageCaptureType	Cardinality	0..*		
XML Level 2	biom_2:CaptureLocation	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.8118_6

Collection Equipment Make/Model/Serial Number

Capture UTC

Mnemonic	CAPT.UTC			Conditionality	O
				Status	New-Emerging
Description	A UTC date and time for the capture of a biometric sample.				
Field Min	Encoding Specific	Occur Min	0		
Field Max	Encoding Specific	Occur Max	1		
Char Types	ANS	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	NIEM Biometric Domain				
XML Level 1	biom_2:ImageCaptureType	Cardinality	0..*		
XML Level 2	biom_2:CaptureUTCDateTime/nc:DateTime	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8118_7

Collection Equipment Make/Model/Serial Number

Capture Date

Mnemonic	CAPT_DATE			Conditionality	O
				Status	New-Emerging
Description	A date that an image was captured.				
Field Min	Encoding Specific		Occur Min	0	
Field Max	Encoding Specific		Occur Max	1	
Char Types	ANS		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	NIEM Biometric Domain				
XML Level 1	biom_2:ImageCaptureType			Cardinality	0..*
XML Level 2	biom_2:CaptureDate/nc:Date			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.8118_8

Collection Equipment Make/Model/Serial Number

Device Identification

Mnemonic	CAPT_ID			Conditionality	O
				Status	New-Emerging
Description	An identification of a capture device or source of an image.				
Field Min	1		Occur Min	0	
Field Max	50		Occur Max	1	
Char Types	U		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	NIEM Biometric Domain				
XML Level 1	biom_2:ImageCaptureType			Cardinality	0..*
XML Level 2	biom_2:CaptureDeviceIdentification/nc:IdentificationID			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8118_9

Collection Equipment Make/Model/Serial Number

Capture Organization

Mnemonic	CAPT_ORG			Conditionality	0		
				Status	New-Emerging		
Description	An organization that originally captured an image.						
Field Min	1			Occur Min	0		
Field Max	50			Occur Max	1		
Char Types	U			Special Chars			
Format	n/a			Constraints	n/a		
Code List							
Source	NIEM Biometric Domain						
XML Level 1	biom_2:ImageCaptureType				Cardinality	0..*	
XML Level 2	biom_2:CaptureOrganization				Cardinality	0..1	
XML Level 3	nc:OrganizationDescriptionText				Cardinality	0..1	
XML Level 4					Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.8118_10

Collection Equipment Make/Model/Serial Number

Capture Resolution

Mnemonic	CAPT_RESOL			Conditionality	0		
				Status	New-Emerging		
Description	A data concept for a minimum or native resolution.						
Field Min	1			Occur Min	0		
Field Max	25			Occur Max	1		
Char Types	U			Special Chars			
Format	n/a			Constraints	n/a		
Code List							
Source	NIEM Biometric Domain						
XML Level 1	biom_2:ImageCaptureType				Cardinality	0..*	
XML Level 2	biom_2:CaptureResolution				Cardinality	0..1	
XML Level 3					Cardinality		
XML Level 4					Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8118_11

Collection Equipment Make/Model/Serial Number

Capture Vertical Pixel Density Value

Mnemonic	CAPT_PIXEL			Conditionality	O
				Status	New-Emerging
Description	A scanned pixel density in the vertical direction.				
Field Min	1	Occur Min	0		
Field Max	25	Occur Max	1		
Char Types	N	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	NIEM Biometric Domain				
XML Level 1	biom_2:ImageCaptureType	Cardinality	0..*		
XML Level 2	biom_2:CaptureVerticalPixelDensityValue	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.8118_12

Collection Equipment Make/Model/Serial Number

Capture Device Monitoring Mode

Mnemonic	CAPT_MONITOR			Conditionality	O
				Status	New-Emerging
Description	A data concept for a level of human monitoring for an image capture device.				
Field Min	1	Occur Min	0		
Field Max	25	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	NIEM Biometric Domain				
XML Level 1	biom_2:ImageCaptureType	Cardinality	0..*		
XML Level 2	biom_2:CaptureDeviceMonitoringMode	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.8203

Template Extraction Algorithm

Mnemonic	TEA			Conditionality	0
				Status	Active
Description	The algorithm used to extract template data from an existing biometric image. It consists of Template Extraction Algorithm Name and Template Extraction Algorithm Version.				
Field Min	n/a			Occur Min	0
Field Max	n/a			Occur Max	1
Char Types	n/a			Special Chars	
Format	n/a			Constraints	n/a
Code List					
Source	Developed for Blue Force capability.Pending approval.				
XML Level 1	dod-ebts: TemplateExtractionAlgorithm			Cardinality	0..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8203_1

Template Extraction Algorithm Name

Template Extraction Algorithm Version

Mnemonic	TEA_NAME			Conditionality	M↑
				Status	Active
Description	The name of the algorithm used to extract template data from an existing biometric image.				
Field Min	1			Occur Min	1
Field Max	100			Occur Max	1
Char Types	AN			Special Chars	
Format	n/a			Constraints	n/a
Code List					
Source	Developed for Blue Force capability.Pending approval.				
XML Level 1	dod-ebts:TemplateExtractionAlgorithm			Cardinality	0..1
XML Level 2	dod-ebts:ExtractionAlgorithmName			Cardinality	1...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8203_2

Template Extraction Algorithm

Template Extraction Algorithm Version

Mnemonic	TEA_VER			Conditionality	0
				Status	Active
Description	The version of the algorithm used to extract template data from an existing biometric image.				
Field Min	1	Occur Min	0		
Field Max	10	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	Developed for Blue Force capability. Pending approval.				
XML Level 1	dod-ebts:TemplateExtractionAlgorithm			Cardinality	0..1
XML Level 2	dod-ebts:ExtractionAlgorithmVersion			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8206

Additional Response

Mnemonic	ARSP			Conditionality	0
				Status	Active
Description	This set of fields shall be used in responses when an additional repository has been searched. It contains information received from the repository that generated an additional response. Multiple repositories may be searched, therefore multiple occurrences of this field shall be allowed. It consists of Response Source, Response Result, Response Identifier, and Response Rap Sheet.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	Referenced by DoD EBTS 2.0. Coordination with DoD ABIS required. Pending approval				
XML Level 1	dod-ebts:AdditionalReponse			Cardinality	0..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8206_0

Additional Response

Subfields: Repeating sets of information items

Mnemonic	ARSP_0	Conditionality	O
		Status	New-Active
Description	Repeating subfield for Additional Response.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	*
Char Types	n/a	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	EBTS 4.0		
XML Level 1	dod-ebts:AdditionalReponse	Cardinality	0..*
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.8206_1

Additional Response

Name of Designated Repository

Mnemonic	NDR	Conditionality	O
		Status	Active
Description	This field contains the numerical designation of the repository to be searched. Repository numbers are assigned by the CJIS Division. Multiple entries in this field will indicate a desire to search more than one repository. This field identifies the repository that generated the additional response.		
Field Min	1	Occur Min	0
Field Max	3	Occur Max	1
Char Types	N	Special Chars	
Format	n/a	Constraints	n/a
Code List	DESIGNATED REPOSITORY NAME		
Source	Referenced by DoD EBTS 2.0. Coordination with DoD ABIS required.		
XML Level 1	dod-ebts:AdditionalReponse	Cardinality	0..*
XML Level 2	nc:RepositoryID/nc:IdentificationID	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8206_2

Additional Response

Additional Response Result Code

Mnemonic	RSLTCD			Conditionality	O
				Status	Active
Description	This field contains the result generated by the repository that generated the additional response.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	n/a		
Code List	ADDITIONAL RESPONSE RESULT CODES				
Source	Referenced by DoD EBTS 2.0. Coordination with DoD ABIS required.				
XML Level 1	dod-ebts:AdditionalReponse			Cardinality	0..*
XML Level 2	dod-ebts:ResultCode/nc:IdentificationID			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8206_3

Additional Response

Additional Response Identifier Category Code

Mnemonic	ARIDCATCD			Conditionality	O
				Status	Active
Description	The category of the additional response identification such as DoD Number, FBI Number, etc.				
Field Min	3	Occur Min	0		
Field Max	3	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	n/a		
Code List	IDENTIFIER TYPE CODES				
Source	Referenced by DoD EBTS 2.0. Coordination with DoD ABIS required.				
XML Level 1	dod-ebts:AdditionalReponse			Cardinality	0..*
XML Level 2	dod-ebts:ResponseIdentifierCategoryCode			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8206_4

Additional Response

Additional Response Identifier

Mnemonic	ARID	Conditionality	O
		Status	Active
Description	This conditional field shall contain the unique identifier used or generated by the repository that generated the additional response.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	ANS	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Referenced by DoD EBTS 2.0. Coordination with DoD ABIS required.		
XML Level 1	dod-ebts:AdditionalReponse	Cardinality	0..*
XML Level 2	dod-ebts:ReponseID/nc:IdentificationID	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

2.8206_5

Additional Response

Additional Response Rap Sheet

Mnemonic	ERS	Conditionality	O
		Status	Active
Description	This conditional field contains the electronic rap sheet generated by the Secondary Search Repository in the case of an Ident. In the case of an error, this field shall contain the error message returned by the repository that generated the additional response.		
Field Min	1	Occur Min	0
Field Max	200,000	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Referenced by DoD EBTS 2.0. Coordination with DoD ABIS required.		
XML Level 1	dod-ebts:AdditionalReponse	Cardinality	0..*
XML Level 2	j:RapSheet	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8207

Request Secondary Search

Mnemonic	SCND_SRCH		Conditionality	0	
			Status	Active	
Description	This set of fields, if provided, shall indicate which repository, the transaction type and secondary search retention indicator for a secondary search. The default is NOT to send the EBTS file to any other repository, unless secondary search is requested. Coordination required with DFBA Standards Branch before uage.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	Referenced by DoD EBTS 2.0. Coordination with DoD ABIS required.				
XML Level 1	dod-ebts:SecondarySearch		Cardinality	0..1	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

2.8207_1

Request Secondary Search

Name of Designated Repository

Mnemonic	NDR		Conditionality	0	
			Status	Active	
Description	This field contains the numerical designation of the repository to be searched. Repository numbers are assigned by the CJIS Division. Multiple entries in this field will indicate a desire to search more than one repository. A submission will be submitted to the primary repository via the DoD EBTS. This field indicates which additional repository should be searched using the same information.				
Field Min	1		Occur Min	0	
Field Max	3		Occur Max	1	
Char Types	N		Special Chars		
Format	n/a		Constraints	n/a	
Code List	DESIGNATED REPOSITORY NAME				
Source	Referenced by DoD EBTS 2.0. Coordination with DoD ABIS required.				
XML Level 1	dod-ebts:SecondarySearch		Cardinality	0..1	
XML Level 2	nc:RepositoryID/nc:IdentificationID		Cardinality	0...1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8207_2

Request Secondary Search

Request Secondary Search Transaction Type

Mnemonic	TOT			Conditionality	O
				Status	Active
Description	This field contains an identifier, designating the type of transaction to secondary search and subsequent processing that the logical file should be given.				
Field Min	3	Occur Min	0		
Field Max	100	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	see DFBA before implementation		
Code List					
Source	Referenced by DoD EBTS 2.0. Coordination with DoD ABIS required.				
XML Level 1	dod-ebts:SecondarySearch	Cardinality	0..1		
XML Level 2	dod-ebts:TransactionType	Cardinality	0...1		
XML Level 3	Note: Said : look for BIMA before Implement	Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

2.8207_3

Request Secondary Search

Secondary Search Retention Indicator

Mnemonic	RET			Conditionality	O
				Status	Active
Description	A value of "Y" means retention is acceptable, a value of "N" means the secondary repository should not retain the submission. Secondary repositories are not necessarily bound by this field and policy may override the value present.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	see Look Up Codes		
Code List	SEARCH RETENTION CODES				
Source	Referenced by DoD EBTS 2.0. Coordination with DoD ABIS required.				
XML Level 1	dod-ebts:SecondarySearch	Cardinality	0..1		
XML Level 2	dod-ebts:RetentionIndicator	Cardinality	0...1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8399

Caveat

Mnemonic	CAV	Conditionality	0
		Status	Active
Description	The Caveat set allows an EBTS file to be annotated with caveat, usage or handling instructions, disclaimer or general information. The set consists of 6 information items: Caveat Originator Country Code, Caveat Originating Agency Name, Caveat Originating Agency Identifier, Caveat Date, Caveat Type and Caveat Text. Example: **For US DoD training purposes only** This data is provided by Freedomian Forces to your forces//agency//department in confidence, for internal use only. It can only be used to support Operation Global Mission mandates and must not be used in a manner inconsistent with international law. Data must be extinguished from any record under the control of your forces//agency//department 5 years after input the latest, unless the individual poses a current threat. Any use of this data for purposes outside of the above mandate requires prior approval by the Government of Freedomia. **For US DoD training purposes only**		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	
Format	ge	Constraints	n/a
Code List			
Source	BSWG		
XML Level 1	dod-ebts:Caveat	Cardinality	0..1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
			DoD EBTS 4.0
			Yes

2.8399_0

Caveat

Subfields: Repeating sets of information items

Mnemonic	CAV_0	Conditionality	0
		Status	New-Active
Description	Repeating subfield for Caveat.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	4
Char Types	n/a	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	EBTS 4.0		
XML Level 1	dod-ebts:Caveat	Cardinality	0..4
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	No
			DoD EBTS 4.0
			Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8399_1

Caveat

Caveat Originating Agency Country Code

Mnemonic	CAV_CNTRY_CD		Conditionality	M↑			
			Status	Active			
Description	The GENC alpha3 country code of the organization originating the caveat. The DoD EBTS Default for this field is the GENC three character alpha codelist (genc:CountryAlpha3CodeType).						
Field Min	3	Occur Min	0				
Field Max	3	Occur Max	1				
Char Types	A	Special Chars					
Format	n/a	Constraints	n/a				
Code List							
Source	BSWG						
XML Level 1	dod-ebts:Caveat		Cardinality	0..4			
XML Level 2	nc:LocationCountryGENCCode		Cardinality	0..1			
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

2.8399_2

Caveat

Caveat Originating Agency Name

Mnemonic	CAV_ORI_NAME		Conditionality	M↑			
			Status	Active			
Description	The name of the administration or organization originating the caveat.						
Field Min	1	Occur Min	0				
Field Max	100	Occur Max	1				
Char Types	U	Special Chars					
Format	n/a	Constraints	n/a				
Code List							
Source	BSWG						
XML Level 1	dod-ebts:Caveat		Cardinality	0..4			
XML Level 2	dod-ebts:CaveatOriginatingAgencyName		Cardinality	0..1			
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8399_3

Caveat

Caveat Originating Agency Identifier

Mnemonic	CAV_ORI			Conditionality	M↑
				Status	Active
Description	The identifier of the administration or organization originating the caveat. In some cases, the Caveat Originating Agency is not the same as the Transaction Originating Agency specified in Field 1.008. The Caveat ORI might not be known. Enter 'XXXXXXXX' if the identifier is not applicable.				
Field Min	9	Occur Min	0		
Field Max	9	Occur Max	1		
Char Types	AN	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:Caveat			Cardinality	0..4
XML Level 2	dod-ebts:CaveatOriginatingAgencyIdentification/nc:IdentificationID			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

2.8399_4

Caveat

Caveat Date

Mnemonic	CAV_DT			Conditionality	M↑
				Status	Active
Description	The date when the caveat is published.				
Field Min	Encoding Specific	Occur Min	0		
Field Max	Encoding Specific	Occur Max	1		
Char Types	ANS	Special Chars			
Format	YYYYMMDD	Constraints	n/a		
Code List					
Source	BSWG				
XML Level 1	dod-ebts:Caveat			Cardinality	0..4
XML Level 2	dod-ebts:CaveatDate/nc:Date			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8399_5

Caveat

Caveat Category Code

Mnemonic	CAV_CAT_CD		Conditionality	M↑			
			Status	Active			
Description	The kind of caveat described in the text field. Ex: CAVEAT / USAGE / INFO / DISCLAIMER / HANDELING.						
Field Min	1	Occur Min	0				
Field Max	10	Occur Max	1				
Char Types	A	Special Chars					
Format	n/a	Constraints	n/a				
Code List	CAVEAT CATEGORY CODES						
Source	BSWG						
XML Level 1	dod-ebts:Caveat		Cardinality	0..4			
XML Level 2	dod-ebts:CaveatCategoryCode		Cardinality	0..1			
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

2.8399_6

Caveat

Caveat Text

Mnemonic	CAV_TXT		Conditionality	M↑			
			Status	Active			
Description	The specific text for the type of caveat including retention and restriction requirements. For example, words describing the retention, non-releasability and searching restriction may be in the 'Caveat Text' information item. The first 1500 characters should be used for the Caveat Text itself. The remaining portion is opened for other usage						
Field Min	1	Occur Min	0				
Field Max	30000	Occur Max	1				
Char Types	U	Special Chars					
Format	n/a	Constraints	n/a				
Code List							
Source	BSWG						
XML Level 1	dod-ebts:Caveat		Cardinality	0..4			
XML Level 2	nc:CaveatText		Cardinality	0..1			
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8399_7

Caveat

Caveat Releasability

Mnemonic	CAV_REL			Conditionality	M↑
				Status	New-Active
Description	This text contains the releasability requirements for the data in the transmission.				
Field Min	1	Occur Min	0		
Field Max	30000	Occur Max	1		
Char Types	ANS	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	FBSWG				
XML Level 1	dod-ebts:Caveat			Cardinality	0..4
XML Level 2	nc:CaveatText			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.8399_8

Caveat

Caveat Originating Country POC Information

Mnemonic	CAV_CNT_POC			Conditionality	M↑
				Status	New-Active
Description	Point of Contact information for the country or agency which originating the caveat.				
Field Min	1	Occur Min	0		
Field Max	30000	Occur Max	1		
Char Types	ANS	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	FBSWG				
XML Level 1	dod-ebts:Caveat			Cardinality	0..4
XML Level 2	nc:CaveatText			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8399_9

Caveat

Caveat Adjudicator POC Information

Mnemonic	CAV_ADJ_POC			Conditionality	M↑
				Status	New-Active
Description	Point of Contact information for the individual adjudicating the data to generate caveat information.				
Field Min	1	Occur Min	0		
Field Max	30000	Occur Max	1		
Char Types	ANS	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	FBSWG				
XML Level 1	dod-ebts:Caveat			Cardinality	0..4
XML Level 2	nc:CaveatText			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.8399_10

Caveat

Caveat Source Reliability

Mnemonic	CAV_SRC			Conditionality	M↑
				Status	New-Active
Description	A code describing the reliability of the source of the information provided, ranging from "Reliable" (A) to "Unreliable" (E). In every instance the reporting is based on previous reporting from the source. If there has been no previous reporting, the source must be rated as "Cannot Be Judged" (F). An "F" rating does not necessarily mean that the source cannot be trusted, but that there is no reporting history and therefore no basis for making a determination. See Look Up Codes for valid entries.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars			
Format	X	Constraints	See Look Up Codes		
Code List	SOURCE RELIABILITY CODES				
Source	FBSWG				
XML Level 1	dod-ebts:Caveat			Cardinality	0..4
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8399_11

Caveat

Caveat Content Reliability

Mnemonic	CAV_CON			Conditionality	M↑
				Status	New-Active
Description	A code describing the reliability of the content of the information provided. The highest degree of confidence in reported information is given to that which has been confirmed by outside sources. The degree of confidence decreases if the information is not confirmed, and/or does not make logical sense. The lowest evaluation rating of "5" means that the information is considered to be false. A rating of "6" does not necessarily mean false information, but is generally used to indicate that no determination can be made since the information is completely new. See Look Up Codes for valid entries.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars			
Format	X	Constraints	See Look Up Codes		
Code List	INFORMATION CONTENT RELIABILITY CODES				
Source	FBSWG				
XML Level 1	dod-ebts:Caveat			Cardinality	0..4
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.8502

Access Location Badge Color

Mnemonic	BADGE_CLR			Conditionality	0
				Status	Active
Description	The subject's level of badge color. The set consists of the badge color and the authority approval status code.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	Developed for Base Access capability.				
XML Level 1	dod-ebts:AccessLocationBadgeColor			Cardinality	0..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8502_1

Access Location Badge Color

Badge Color Code

Mnemonic	BADGE_CLR_CD	Conditionality	O
		Status	Active
Description	The badge color assigned to subject.		
Field Min	3	Occur Min	0
Field Max	3	Occur Max	1
Char Types	A	Special Chars	
Format	n/a	Constraints	n/a
Code List	BADGE COLOR CODES		
Source	Developed for Base Access capability.		
XML Level 1	dod-ebts:AccessLocationBadgeColor	Cardinality	0..1
XML Level 2	dod-ebts:BadgeColorCode	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes

2.8502_2

Access Location Badge Color

Badge Clearance Code

Mnemonic	BADGE_CLR_AUTH_CD	Conditionality	O
		Status	Active
Description	The level of the authority and approval status obtained.		
Field Min	6	Occur Min	0
Field Max	6	Occur Max	1
Char Types	AS	Special Chars	
Format	n/a	Constraints	n/a
Code List	AUTHORITY APPROVAL STATUS CODES		
Source	Developed for Base Access capability.		
XML Level 1	dod-ebts:AccessLocationBadgeColor	Cardinality	0..1
XML Level 2	dod-ebts:BadgeClearanceCode	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8505

Screening Document Requirement Indicator

Mnemonic	LEP			Conditionality	0		
				Status	Emerging		
Description	An indicator for the Locally Employed Personnel LEP Screening Document is required for applicants for the type of badge requested. As a general guideline, the LEP Screening Document is required for applicants wanting a Red, Yellow, or Orange badge; however the requirement can be overridden based on local security requirements.						
Field Min	1			Occur Min	0		
Field Max	1			Occur Max	1		
Char Types	A			Special Chars			
Format	n/a			Constraints	n/a		
Code List	SCREENING DOCUMENT REQUIREMENT INDICATOR CODES						
Source	Developed for Base Access capability.						
XML Level 1	dod-ebts:LocallyEmployedIndicator				Cardinality	0..1	
XML Level 2	nc:DocumentTitleText				Cardinality	0..1	
XML Level 3					Cardinality		
XML Level 4					Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.8507

Project Name

Mnemonic	PROJ			Conditionality	0		
				Status	Emerging		
Description	The name of the project under which employment access is being requested.						
Field Min	2			Occur Min	0		
Field Max	30			Occur Max	1		
Char Types	U			Special Chars			
Format	n/a			Constraints	n/a		
Code List							
Source	Developed for Blue Force capability.						
XML Level 1	dod-ebts:Project				Cardinality	0..*	
XML Level 2	nc:ActivityName				Cardinality	0..1	
XML Level 3					Cardinality		
XML Level 4					Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-2: User-Defined Descriptive Text

Page 263 of 1037

2.8508

Contract

Mnemonic	CONTRACT			Conditionality	0
				Status	Emerging
Description	The set consists of the contract number and the contract expiration date.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	Developed for Blue Force capability.				
XML Level 1				Cardinality	
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.8508_0

Contract

Subfields: Repeating sets of information items

Mnemonic	CONTRACT_0			Conditionality	0
				Status	Emerging
Description	Repeating subfield for Contract.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	*		
Char Types	n/a	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	EBTS 4.0				
XML Level 1	dod-ebts:Contract			Cardinality	0..*
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-2: User-Defined Descriptive Text

Page 264 of 1037

2.8508_1

Contract

Contract Number

Mnemonic	CNTRACT_NUM	Conditionality	O		
		Status	Emerging		
Description	The number identifying the legal agreement with an employer.				
Field Min	1	Occur Min	0		
Field Max	58	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	Developed for Blue Force capability.				
XML Level 1	dod-ebts:Contract	Cardinality	0..*		
XML Level 2	nc:DocumentIdentification/nc:IdentificationID	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes		

2.8508_2

Contract

Contract Expiration Date

Mnemonic	CNTRACT_EXPDT	Conditionality	O		
		Status	Emerging		
Description	The date on which the contract with the employer expires.				
Field Min	Encoding Specific	Occur Min	0		
Field Max	Encoding Specific	Occur Max	1		
Char Types	N	Special Chars			
Format	YYYYMMDD	Constraints	n/a		
Code List					
Source	Developed for Blue Force capability.				
XML Level 1	dod-ebts:Contract	Cardinality	0..*		
XML Level 2	dod-ebts:ContractExpirationDate/nc:Date	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8509

Access Location Badge

Mnemonic	BADGE	Conditionality	0
		Status	Emerging
Description	The subject's badge for an access location. The set consists of the badge number, badge color code, badge status code, issue date, expiration date, issuance organization, and issuance office.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Developed for Base Access capability.		
XML Level 1	dod-ebts:AccessLocationBadge	Cardinality	0..1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.8509_0

Access Location Badge

Subfields: Repeating sets of information items

Mnemonic	BADGE_0	Conditionality	0
		Status	Emerging
Description	Repeating subfield for Access Location Badge.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	*
Char Types	n/a	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	EBTS 4.0		
XML Level 1	dod-ebts:AccessLocationBadge	Cardinality	0..*
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8509_1

Access Location Badge

Access Location Badge Number

Mnemonic	BADGE_NUM	Conditionality	O		
		Status	Emerging		
Description	The designated number on the badge.				
Field Min	1	Occur Min	0		
Field Max	100	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	Developed for Base Access capability.				
XML Level 1	dod-ebts:AccessLocationBadge		Cardinality	0..*	
XML Level 2	dod-ebts:BadgeNumber		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.8509_2

Access Location Badge

Access Location Badge Color Code

Mnemonic	BADGE_CLR_CD	Conditionality	O		
		Status	Emerging		
Description	The badge color assigned to subject.				
Field Min	3	Occur Min	0		
Field Max	3	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	n/a		
Code List	BADGE COLOR CODES				
Source	Developed for Base Access capability.				
XML Level 1	dod-ebts:AccessLocationBadge		Cardinality	0..*	
XML Level 2	dod-ebts:BadgeColorCode		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8509_3

Access Location Badge

Access Location Badge Status Code

Mnemonic	BADGE_STAT_CD		Conditionality	0	
			Status	Emerging	
Description	The status of an identification badge, such as valid, replaced, expired.				
Field Min	1		Occur Min	0	
Field Max	1		Occur Max	1	
Char Types	A		Special Chars		
Format	n/a		Constraints	n/a	
Code List	BADGE STATUS CODES				
Source	Developed for Base Access capability.				
XML Level 1	dod-ebts:AccessLocationBadge			Cardinality	0..*
XML Level 2	dod-ebts:BadgeStatusCode			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.8509_4

Access Location Badge

Access Location Badge Issue Date

Mnemonic	BADGE_ISSDT		Conditionality	0	
			Status	Emerging	
Description	The date the badge was issued.				
Field Min	Encoding Specific		Occur Min	0	
Field Max	Encoding Specific		Occur Max	1	
Char Types	ANS		Special Chars		
Format	YYYYMMDD		Constraints	n/a	
Code List					
Source	Developed for Base Access capability.				
XML Level 1	dod-ebts:AccessLocationBadge			Cardinality	0..*
XML Level 2	nc:IdentificationEffectiveDate/nc:Date			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8509_5

Access Location Badge

Access Location Badge Expiration Date

Mnemonic	BADGE_EXPDT	Conditionality	O		
		Status	Emerging		
Description	A date after which the badge is no longer valid.				
Field Min	Encoding Specific	Occur Min	0		
Field Max	Encoding Specific	Occur Max	1		
Char Types	ANS	Special Chars			
Format	YYYYMMDD	Constraints	n/a		
Code List					
Source	Developed for Base Access capability.				
XML Level 1	dod-ebts:AccessLocationBadge	Cardinality	0..*		
XML Level 2	nc:IdentificationExpirationDate/nc:Date	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes		

2.8509_6

Access Location Badge

Access Location Badge Issuance Organization Name

Mnemonic	BADGE_ISSORG	Conditionality	O		
		Status	Emerging		
Description	The name of the organization or system that issued the badge.				
Field Min	1	Occur Min	0		
Field Max	100	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	Developed for Base Access capability.				
XML Level 1	dod-ebts:AccessLocationBadge	Cardinality	0..*		
XML Level 2	OrganizationName/nc:TextType	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.851

Access Location

Mnemonic	ACC_LOC_APT_PERM			Conditionality	0
				Status	Emerging
Description	The subject's level of airport installation access. The set consists of the airport installation type, the force protection condition and the authority approval status code.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	Developed for Base Access capability. Pending approval.				
XML Level 1	dod-ebts:AccessLocationInstalationPermission			Cardinality	0..1
XML Level 2				Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.8510_0

Access Location

Subfields: Repeating sets of information items

Mnemonic	ACC_LOC_APT_PERM_0			Conditionality	0
				Status	Emerging
Description	Repeating subfield for Access Location.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	*	
Char Types	n/a		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	EBTS 4.0				
XML Level 1	dod-ebts:AccessLocationInstalationPermission			Cardinality	0..*
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8510_1

Access Location

Access Location Airport Installation Category Code

Mnemonic	ACC_LOC_APT_PERM_APT_LOC_TYP		Conditionality	O	
			Status	Emerging	
Description	The type of airport installation at an access location.				
Field Min	3		Occur Min	0	
Field Max	7		Occur Max	1	
Char Types	AN		Special Chars		
Format	n/a		Constraints	n/a	
Code List	AIRPORT INSTALLATION CODES				
Source	Developed for Base Access capability. Pending approval.				
XML Level 1	dod-ebts:AccessLocationInstalationPermission		Cardinality	0..*	
XML Level 2	dod-ebts:AirportInstallationCode"		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.8510_2

Access Location

Force Protection Condition Code

Mnemonic	ACC_LOC_APT_PERM_FP_CD		Conditionality	O	
			Status	Emerging	
Description	A DoD-approved system standardizing DoD's identification of and recommended preventive actions and responses to terrorist threats against U.S. personnel and facilities. The system is the principal means for a commander to apply an operational decision on how to protect against terrorism and facilitates coordination among DoD Components and support for antiterrorism activities.				
Field Min	11		Occur Min	0	
Field Max	13		Occur Max	1	
Char Types	AS		Special Chars		
Format	n/a		Constraints	n/a	
Code List	FORCE PROTECTION CONDITION CODES				
Source	Developed for Base Access capability. Pending approval. Codes are source from DoD Instructions 2000.17.				
XML Level 1	dod-ebts:AccessLocationInstalationPermission		Cardinality	0..*	
XML Level 2	dod-ebts:ForceProtectionConditionCode		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-2: User-Defined Descriptive Text

Page 271 of 1037

2.8510_3

Access Location

Authority Approval Status Code

Mnemonic	ACC_LOC_APT_PERM_AUTH_CD		Conditionality	0	
			Status	Emerging	
Description	The level of the authority and approval status obtained.				
Field Min	6		Occur Min	0	
Field Max	6		Occur Max	1	
Char Types	AS		Special Chars		
Format	n/a		Constraints	n/a	
Code List	AUTHORITY APPROVAL STATUS CODES				
Source	Developed for Base Access capability. Pending approval.				
XML Level 1	dod-ebts:AccessLocationInstalationPermission		Cardinality	0..*	
XML Level 2	dod-ebts:AuthorityApprovalStatusCode		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.8511

Access Location Required Month

Mnemonic	ACC_LOC_MONTH		Conditionality	0	
			Status	Emerging	
Description	The subject's level of months access required for a location. The set consists of the months the access is required and the authority approval status code.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	Developed for Base Access capability. Pending approval.				
XML Level 1	dod-ebts:AccessLocationRequiredMonth		Cardinality	0..1	
XML Level 2			Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8511_0

Access Location Required Month

Subfields: Repeating sets of information items

Mnemonic	ACC_LOC_MONTH_0			Conditionality	O
				Status	Emerging
Description	Repeating subfield for Access Location Required Month.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	*		
Char Types	n/a	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	EBTS 4.0				
XML Level 1	dod-ebts:AccessLocationRequiredMonth			Cardinality	0..*
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.8511_1

Access Location Required Month

Month Number

Mnemonic	ACC_LOC_MONTH_VAL			Conditionality	O
				Status	Emerging
Description	A two-digit month of the year, 01 through 12.				
Field Min	2	Occur Min	0		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars			
Format	MM - 2 digit month	Constraints	n/a		
Code List					
Source	Developed for Base Access capability. Pending approval.				
XML Level 1	dod-ebts:AccessLocationRequiredMonth			Cardinality	0..*
XML Level 2	dod-ebts:MonthNumber			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8511_2

Access Location Required Month

Authority Approval Status Code

Mnemonic	ACC_LOC_MONTH_AUTH_CD		Conditionality	0	
			Status	Emerging	
Description	The level of the authority and approval status obtained.				
Field Min	6		Occur Min	0	
Field Max	6		Occur Max	1	
Char Types	AS		Special Chars		
Format	n/a		Constraints	n/a	
Code List	AUTHORITY APPROVAL STATUS CODES				
Source	Developed for Base Access capability. Pending approval.				
XML Level 1	dod-ebts:AccessLocationRequiredMonth		Cardinality	0..*	
XML Level 2	dod-ebts: Authority Approval Status Code/nc:IdentificationType		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.8512

Access Location Required Day of the Week

Mnemonic	ACC_LOC_WKDAY		Conditionality	0	
			Status	Emerging	
Description	The subject's level of days of the week access is required for a location. The set consists of the weekdays access is required and the authority approval status code.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	Developed for Base Access capability. Pending approval.				
XML Level 1	dod-ebts:AccessLocationRequiredDay		Cardinality	0..1	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-2: User-Defined Descriptive Text

Page 274 of 1037

2.8512_1

Access Location Required Day of the Week

Weekday Number

Mnemonic	ACC_LOC_WKDAY_NUM		Conditionality	O			
			Status	Emerging			
Description	The weekday number, from 1 through 7, beginning with Monday and ending with Sunday.						
Field Min	1	Occur Min	0				
Field Max	1	Occur Max	1				
Char Types	N	Special Chars					
Format	n/a	Constraints	n/a				
Code List							
Source	Developed for Base Access capability. Pending approval.						
XML Level 1	dod-ebts:AccessLocationRequiredDay		Cardinality	0..1			
XML Level 2	dod-ebts:WeekdayNumber		Cardinality	0..1			
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.8512_2

Access Location Required Day of the Week

Authority Approval Status Code

Mnemonic	ACC_LOC_WKDAY_AUTH_CD		Conditionality	O			
			Status	Emerging			
Description	The level of the authority and approval status obtained.						
Field Min	6	Occur Min	0				
Field Max	6	Occur Max	1				
Char Types	AS	Special Chars					
Format	n/a	Constraints	n/a				
Code List	AUTHORITY APPROVAL STATUS CODES						
Source	Developed for Base Access capability. Pending approval.						
XML Level 1	dod-ebts:AccessLocationRequiredDay		Cardinality	0..1			
XML Level 2	dod-ebts:AuthorityApprovalStatusCode		Cardinality	0..1			
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.8513

Access Location Badge Replacement

Mnemonic	BADGE_RPL	Conditionality	0
		Status	Emerging
Description	The subject's badge replacement information. The set contains the replacement reason code and the badge number that is being replaced.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Developed for Base Access capability. Pending approval.		
XML Level 1	dod-ebts:AccessLocationBadgeReplace	Cardinality	0..1
XML Level 2		Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.8513_1

Access Location Badge Replacement

Access Location Badge Replacement Reason Code

Mnemonic	BADGE_RPL_REASON_CD	Conditionality	0
		Status	Emerging
Description	The code indicating the reason the badge is being replaced.		
Field Min	1	Occur Min	0
Field Max	1	Occur Max	1
Char Types	A	Special Chars	
Format	n/a	Constraints	n/a
Code List	BADGE REPLACEMENT REASON CODES		
Source	Developed for Base Access capability. Pending approval.		
XML Level 1	dod-ebts:AccessLocationBadgeReplace	Cardinality	0..1
XML Level 2	dod-ebts:BadgeReplacementReasonCode	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8513_2

Access Location Badge Replacement

Access Location Replaced Badge Number

Mnemonic	BADGE_RPL_BADGE_NUM			Conditionality	0
				Status	Emerging
Description	The number of the badge being replaced.				
Field Min	1	Occur Min	0		
Field Max	100	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	Developed for Base Access capability. Pending approval.				
XML Level 1	dod-ebts:AccessLocationBadgeReplace			Cardinality	0..1
XML Level 2	dod-ebts:ReplacedBadgeNumber			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.8514

Access Location Privilege

Mnemonic	ACC_LOC_PRV			Conditionality	0
				Status	Emerging
Description	The subject's level of access privileges. The set consists of the privilege type, the privilege value, the force protection condition and the authority approval status code.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	Developed for Base Access capability. Pending approval.				
XML Level 1	dod-ebts:AccessLocationPrivilege			Cardinality	0..1
XML Level 2				Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8514_0

Access Location Privilege

Subfields: Repeating sets of information items

Mnemonic	ACC_LOC_PRIV_0			Conditionality	O
				Status	Emerging
Description	Repeating subfield for Access Location Privilege.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	*		
Char Types	n/a	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	EBTS 4.0				
XML Level 1	dod-ebts:AccessLocationPrivilege			Cardinality	0..*
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.8514_1

Access Location Privilege

Access Location Privilege Category Code

Mnemonic	ACC_LOC_PRIV_TYP			Conditionality	O
				Status	Emerging
Description	The type of privilege allowed at an access location.				
Field Min	1	Occur Min	0		
Field Max	20	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	n/a		
Code List	ACCESS LOCATION PRIVILEGE CODES				
Source	Developed for Base Access capability. Pending approval.				
XML Level 1	dod-ebts:AccessLocationPrivilege			Cardinality	0..*
XML Level 2	dod-ebts:AccessLocationPrivilegeCategoryCode			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8514_2

Access Location Privilege

Access Location Privilege Value

Mnemonic	ACC_LOC_PRIV_VAL			Conditionality	O
				Status	Emerging
Description	The value of the assigned privilege. e.g. When the Access Location Privilege Category Code = LA for Lane Access, the value might be 'Military' or 'Priority' or 'Regular'				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	Developed for Base Access capability. Pending approval.				
XML Level 1	dod-ebts:AccessLocationPrivilege			Cardinality	0..*
XML Level 2	dod-ebts:AccessLocationPrivilegeValue			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.8515

Access Location

Mnemonic	ACC_LOC			Conditionality	O
				Status	Emerging
Description	Specifies the location for access. The set consists of the Location Name, Address Value Type, Address Value, Latitude Degree/Minute/Second, Longitude Degree/Minute/Second and Location Description.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	Developed for Base Access capability.				
XML Level 1	dod-ebts:AccessLocation			Cardinality	0..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8515_0

Access Location

Subfields: Repeating sets of information items

Mnemonic	ACC_LOC_0	Conditionality	O
		Status	Emerging
Description	Repeating subfield for Access Location.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	*
Char Types	n/a	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	EBTS 4.0		
XML Level 1	dod-ebts:AccessLocation	Cardinality	0..*
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.8515_1

Access Location

Location Name

Mnemonic	ACC_LOC	Conditionality	O
		Status	Emerging
Description	The name of a geographical location. e.g. Fort Belvoir		
Field Min	1	Occur Min	0
Field Max	250	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Developed for Base Access capability.		
XML Level 1	dod-ebts:AccessLocation	Cardinality	0..*
XML Level 2	dod-ebts:LocationAddress	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-2: User-Defined Descriptive Text

Page 280 of 1037

2.8515_2

Access Location

Country Code

Mnemonic	ACC_LOC_CNTRY_CD			Conditionality	O
				Status	Emerging
Description	The GENC alpha3 country code. The DoD EBTS 4.0 default for this field is the GENC three character alpha codelist (genc:CountryAlpha3CodeType).				
Field Min	3	Occur Min	0		
Field Max	3	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	Developed for Base Access capability.				
XML Level 1	dod-ebts:AccessLocation			Cardinality	0..*
XML Level 2	nc:LocationCountryGENCCode			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.8515_3

Access Location

State / Province

Mnemonic	ACC_LOC_STATE			Conditionality	O
				Status	Emerging
Description	The state, province or subdivision of a location.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	free text		
Code List					
Source	Developed for Base Access capability.				
XML Level 1	dod-ebts:AccessLocation			Cardinality	0..*
XML Level 2	nc:LocationStateName			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-2: User-Defined Descriptive Text

Page 281 of 1037

2.8515_4

Access Location

City

Mnemonic	ACC_LOC_CITY			Conditionality	O		
				Status	Emerging		
Description	The name of the city or geographical location. e.g. Fort Belvoir.						
Field Min	1		Occur Min	0			
Field Max	50		Occur Max	1			
Char Types	U		Special Chars				
Format	n/a		Constraints	n/a			
Code List							
Source	Developed for Base Access capability.						
XML Level 1	dod-ebts:AccessLocation			Cardinality	0..*		
XML Level 2	nc:LocationCityName			Cardinality	0..1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.8515_5

Access Location

Village

Mnemonic	ACC_LOC_VLG			Conditionality	O		
				Status	Emerging		
Description	Small population unit, typically rural, held together by common economic and political ties.						
Field Min	1		Occur Min	0			
Field Max	50		Occur Max	1			
Char Types	U		Special Chars				
Format	n/a		Constraints	n/a			
Code List							
Source	Developed for Base Access capability.						
XML Level 1	dod-ebts:AccessLocation			Cardinality	0..*		
XML Level 2	dod-ebts:LocationVillageName			Cardinality	0..1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-2: User-Defined Descriptive Text

Page 282 of 1037

2.8515_6

Access Location

Latitude Degree

Mnemonic	ACC_LOC_GEO_CORD_LAT_DEG	Conditionality	M↑
		Status	Emerging
Description	This field contains the latitude at which the submission was collected. The data is in degrees in the range +90 to -90. The plus sign may be omitted. Decimal values are allowed.		
Field Min	1	Occur Min	1
Field Max	9	Occur Max	1
Char Types	NS	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Developed for Base Access capability.		
XML Level 1	dod-ebts:AccessLocation	Cardinality	0..*
XML Level 2	biom_1:LocationTwoDimensionalGeographicCoordinate (0..1)/nc:GeographicCoordinateLatitude	Cardinality	0..1
XML Level 3	nc:LatitudeDegreeValue	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	No

2.8515_7

Access Location

Latitude Minute

Mnemonic	ACC_LOC_GEO_CORD_LAT_MIN	Conditionality	O
		Status	Emerging
Description	This field contains the geographic location latitude. The data is in minutes in the range from 0 to less than 60.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	NS	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Developed for Base Access capability.		
XML Level 1	dod-ebts:AccessLocation	Cardinality	0..*
XML Level 2	biom_1:LocationTwoDimensionalGeographicCoordinate (0..1)/nc:GeographicCoordinateLatitude	Cardinality	0..1
XML Level 3	nc:LatitudeMinuteValue	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	No

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8515_8

Access Location

Latitude Second

Mnemonic	ACC_LOC_GEO_CORD_LAT_SEC	Conditionality	O
		Status	Emerging
Description	This field contains the geographic location latitude. The data is in seconds in the range from 0 to less than 60. Decimal values are allowed.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	NS	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Developed for Base Access capability.		
XML Level 1	dod-ebts:AccessLocation	Cardinality	0..*
XML Level 2	biom_1:LocationTwoDimensionalGeographicCoordinate (0..1)/nc:GeographicCoordinateLatitude	Cardinality	0..1
XML Level 3	nc:LatitudeSecondValue	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	No

2.8515_9

Access Location

Longitude Degree

Mnemonic	ACC_LOC_GEO_CORD_LONG_DEG	Conditionality	M↑
		Status	Emerging
Description	This field contains the geographic location longitude. The data is in the range of +180 to -180. The plus sign may be omitted. Decimal values are allowed.		
Field Min	1	Occur Min	1
Field Max	10	Occur Max	1
Char Types	NS	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Developed for Base Access capability.		
XML Level 1	dod-ebts:AccessLocation	Cardinality	0..*
XML Level 2	biom_1:LocationTwoDimensionalGeographicCoordinate (0..1)/nc:GeographicCoordinateLatitude	Cardinality	0..1
XML Level 3	nc:LongitudeDegreeValue	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	No

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-2: User-Defined Descriptive Text

Page 284 of 1037

2.8515_10

Access Location

Longitude Minute

Mnemonic	ACC_LOC_GEO_CORD_LONG_MIN	Conditionality	O
		Status	Emerging
Description	This field contains the geographic location longitude. The data is in minutes in the range from 0 to less than 60. Decimal values are allowed.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	NS	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Developed for Base Access capability.		
XML Level 1	dod-ebts:AccessLocation	Cardinality	0..*
XML Level 2	biom_1:LocationTwoDimensionalGeographicCoordinate (0..1)/nc:GeographicCoordinateLatitude	Cardinality	0..1
XML Level 3	nc:LongitudeMinuteValue	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	No

2.8515_11

Access Location

Longitude Second

Mnemonic	ACC_LOC_GEO_CORD_LONG_SEC	Conditionality	O
		Status	Emerging
Description	This field contains the geographic location latitude. The data is in seconds in the range from 0 to less than 60. Decimal values are allowed.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	NS	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Developed for Base Access capability.		
XML Level 1	dod-ebts:AccessLocation	Cardinality	0..*
XML Level 2	biom_1:LocationTwoDimensionalGeographicCoordinate (0..1)/nc:GeographicCoordinateLatitude	Cardinality	0..1
XML Level 3	nc:LongitudeSecondValue	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	No

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8515_12

Access Location

Location Description

Mnemonic	ACC_LOC_DESC	Conditionality	0
		Status	Emerging
Description	Remarks		
Field Min	1	Occur Min	0
Field Max	255	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Developed for Base Access capability.		
XML Level 1	dod-ebts:AccessLocation	Cardinality	0..*
XML Level 2	nc:AreaDescriptionText	Cardinality	0..1
XML Level 3		Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	No

2.8516

Access Location Expiration

Mnemonic	ACC_LOC_EXP	Conditionality	0
		Status	Emerging
Description	The subject's expiration for the access location. The set is comprised of 2 information items: Access Location Expiration Date and Authority Approval Status Code.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Developed for Base Access capability.		
XML Level 1	dod-ebts:AccessLocationExpiration	Cardinality	0..1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8516_0

Access Location Expiration

Subfields: Repeating sets of information items

Mnemonic	ACC_LOC_EXP_0		Conditionality	0	
			Status	Emerging	
Description	Repeating subfield for Access Location Expiration.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	*	
Char Types	n/a		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	EBTS 4.0				
XML Level 1	dod-ebts:AccessLocationExpiration			Cardinality	0..*
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.8516_1

Access Location Expiration

Access Location Expiration Date

Mnemonic	ACC_LOC_EXPDT		Conditionality	0	
			Status	Emerging	
Description	The subject's assigned expiration date for the access location.				
Field Min	Encoding Specific		Occur Min	0	
Field Max	Encoding Specific		Occur Max	1	
Char Types	ANS		Special Chars		
Format	YYYYMMDD		Constraints	n/a	
Code List					
Source	Developed for Base Access capability.				
XML Level 1	dod-ebts:AccessLocationExpiration			Cardinality	0..*
XML Level 2	dod-ebts:AccessLocationExpirationDate			Cardinality	0..1
XML Level 3	niem-xsd:date			Cardinality	0..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8516_2

Access Location Expiration

Authority Approval Status Code

Mnemonic	ACC_LOC_EXP_AUTH_CD		Conditionality	0	
			Status	Emerging	
Description	The level of the authority and approval status obtained.				
Field Min	6		Occur Min	0	
Field Max	6		Occur Max	1	
Char Types	AS		Special Chars		
Format	n/a		Constraints	n/a	
Code List	AUTHORITY APPROVAL STATUS CODES				
Source	Developed for Base Access capability.				
XML Level 1	dod-ebts:AccessLocationExpiration		Cardinality	0..*	
XML Level 2	dod-ebts:AuthorityApprovalStatusCode		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.8517

Access Location Facility Permission

Mnemonic	ACC_LOC_PAC_PERM		Conditionality	0	
			Status	Emerging	
Description	The subject's level of facility access. The set consists of the facility type, the force protection condition and the authority approval status code.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	Developed for Base Access capability.				
XML Level 1	dod-ebts:AccessLocationFacilityPermission		Cardinality	0..1	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8517_0

Access Location Facility Permission

Subfields: Repeating sets of information items

Mnemonic	ACC_LOC_PAC_PERM_0			Conditionality	O
				Status	Emerging
Description	Repeating subfield for Access Location Facility Permission.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	*		
Char Types	n/a	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	EBTS 4.0				
XML Level 1	dod-ebts:AccessLocationFacilityPermission			Cardinality	0..*
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.8517_1

Access Location Facility Permission

Access Location Facility Category Code

Mnemonic	ACC_LOC_PAC_PERM_FAC_TYP			Conditionality	O
				Status	Emerging
Description	The types of facility at an access location.				
Field Min	1	Occur Min	0		
Field Max	20	Occur Max	1		
Char Types	A	Special Chars			
Format	n/a	Constraints	n/a		
Code List	FACILITY CODES				
Source	Developed for Base Access capability.				
XML Level 1	dod-ebts:AccessLocationFacilityPermission			Cardinality	0..*
XML Level 2	dod-ebts:AccessLocationFacilityCategoryCode			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8517_2

Access Location Facility Permission

Force Protection Condition Code

Mnemonic	ACC_LOC_PAC_PERM_FP_CD	Conditionality	0
		Status	Emerging
Description	A DoD-approved system standardizing DoD's identification of and recommended preventive actions and responses to terrorist threats against U.S. personnel and facilities. The system is the principal means for a commander to apply an operational decision on how to protect against terrorism and facilitates coordination among DoD Components and support for antiterrorism activities.		
Field Min	11	Occur Min	0
Field Max	13	Occur Max	1
Char Types	AS	Special Chars	
Format	n/a	Constraints	n/a
Code List	FORCE PROTECTION CONDITION CODES		
Source	Developed for Base Access capability.		
XML Level 1	dod-ebts:AccessLocationFacilityPermission	Cardinality	0..*
XML Level 2	dod-ebts:ForceProtectionConditionCode	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.8517_3

Access Location Facility Permission

Authority Approval Status Code

Mnemonic	ACC_LOC_PAC_PERM_AUTH_CD	Conditionality	0
		Status	Emerging
Description	The level of the authority and approval status obtained.		
Field Min	6	Occur Min	0
Field Max	6	Occur Max	1
Char Types	AS	Special Chars	
Format	XX-YYY where XX is the authority and YYY is the status code	Constraints	n/a
Code List	AUTHORITY APPROVAL STATUS CODES		
Source	Developed for Base Access capability.		
XML Level 1	dod-ebts:AccessLocationFacilityPermission	Cardinality	0..*
XML Level 2	dod-ebts:AuthorityApprovalStatusCode	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8518

Access Application Number

Mnemonic	ACC_APP_NUM		Conditionality	0	
			Status	Emerging	
Description	The unique identifier for an application to obtain access to a facility or base.				
Field Min	16		Occur Min	0	
Field Max	16		Occur Max	1	
Char Types	AN		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	Developed for Base Access capability.				
XML Level 1	dod-ebts:AccessApplicationNumber/nc:IdentificationID		Cardinality	0..1	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.8548

Biometric Subject Specialty

Mnemonic	SUBJ_SPEC		Conditionality	0	
			Status	Emerging	
Description	This set of elements describes the specialty and/or skills of the biometric subject, the proficiency level and the validity of the information provided.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	Developed for Base Access capability.				
XML Level 1	dod-ebts:BiometricSubjectSpecialty		Cardinality	0..1	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8548_0

Biometric Subject Specialty

Subfields: Repeating sets of information items

Mnemonic	SUBJ_SPEC_0			Conditionality	O
				Status	Emerging
Description	Repeating subfield for Biometric Subject Specialty.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	*		
Char Types	n/a	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	EBTS 4.0				
XML Level 1	dod-ebts:BiometricSubjectSpecialty			Cardinality	0..*
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.8548_1

Biometric Subject Specialty

Biometric Subject Specialty Value

Mnemonic	SUBJ_SPEC_VAL			Conditionality	O
				Status	Emerging
Description	The specialty and/or skills of the biometric subject. e.g. nuclear explosives, accounting, etc.				
Field Min	1	Occur Min	0		
Field Max	100	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	Developed for Base Access capability.				
XML Level 1	dod-ebts:BiometricSubjectSpecialty			Cardinality	0..*
XML Level 2	dod-ebts:BiometricSubjectSpecialtyValue			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8548_2

Biometric Subject Specialty

Biometric Subject Specialty Proficiency

Mnemonic	SUBJ_SPEC_PRO		Conditionality	0	
			Status	Emerging	
Description	The field contains the subject proficiency level of the specialty and or skills of the biometric subject.				
Field Min	1		Occur Min	0	
Field Max	1		Occur Max	1	
Char Types	N		Special Chars		
Format	n/a		Constraints	n/a	
Code List	PROFICIENCY CODES				
Source	Developed for Base Access capability.				
XML Level 1	dod-ebts:BiometricSubjectSpecialty			Cardinality	0..*
XML Level 2	dod-ebts:BiometricSubjectSpecialtyProficiencyCode			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.8548_3

Biometric Subject Specialty

Biometric Subject Specialty Validity

Mnemonic	SUBJ_SPEC_VALID		Conditionality	0	
			Status	Emerging	
Description	This information item defines the validity of the specialty and or skills of the biometric subject.				
Field Min	3		Occur Min	0	
Field Max	3		Occur Max	1	
Char Types	A		Special Chars		
Format	n/a		Constraints	n/a	
Code List	VALIDITY CODES				
Source	Developed for Base Access capability.				
XML Level 1	dod-ebts:BiometricSubjectSpecialty			Cardinality	0..*
XML Level 2	dod-ebts:BiometricSubjectSpecialtyValidityCode			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8549

Response Maximum Count

Mnemonic	RESP_CNT			Conditionality	M
				Status	New - Emerging
Description	This field specifies the maximum number of encounters desired to receive in the response. This number shall not exceed the upper limit set by the repository or the service level agreement. The Application Profile shall document the upper limit allowed.				
Field Min	1	Occur Min	0		
Field Max	Unlimited	Occur Max	1		
Char Types	N	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	New - Emerging				
XML Level 1	dod-ebts: ResponseMaximumCount			Cardinality	0..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.8600

Reference System Identifier

Mnemonic	ENTITY_ID_0			Conditionality	M
				Status	New - Emerging
Description	Identifier for an entity.				
Field Min	n/a	Occur Min	1		
Field Max	n/a	Occur Max	*		
Char Types	U	Special Chars			
Format	n/a	Constraints	free text		
Code List					
Source	Addition for Voice Type 11				
XML Level 1	dod-ebts:ReferenceSystemIdentifier			Cardinality	1..*
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8600_0

Reference System Identifier

Subfields: Repeating sets of information items

Mnemonic	ENTITY_ID		Conditionality	O	
			Status	New- Emerging	
Description	Repeating subfield for Reference System Identifier.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	*	
Char Types	n/a		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	EBTS 4.0				
XML Level 1	dod-ebts:ReferenceSystemIdentifier			Cardinality	0...*
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.8600_1

Reference System Identifier

Identifier

Mnemonic	ENTITY_NO		Conditionality	O	
			Status	New - Emerging	
Description	Identifier assigned by the entity.				
Field Min	1		Occur Min	0	
Field Max	50		Occur Max	1	
Char Types	U		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	Addition for Voice Type 11				
XML Level 1	dod-ebts:ReferenceSystemIdentifier			Cardinality	0...*
XML Level 2	dod-ebts:ReferenceSystemID/nc:IdentificationID			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-2: User-Defined Descriptive Text

Page 295 of 1037

2.8600_2

Reference System Identifier

Jurisdiction

Mnemonic	ENITITY_JURIS			Conditionality	0		
				Status	New - Emerging		
Description	Jurisdiction of the identifier.						
Field Min	1		Occur Min	0			
Field Max	50		Occur Max	1			
Char Types	U		Special Chars				
Format	n/a		Constraints	n/a			
Code List							
Source	Addition for Voice Type 11						
XML Level 1	dod-ebts:ReferenceSystemIdentifier			Cardinality	0...*		
XML Level 2	nc:JurisdictionIdentification			Cardinality	0...1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.8600_3

Reference System Identifier

Category

Mnemonic	ENTITY_CATEGORY			Conditionality	0		
				Status	New - Emerging		
Description	Category of the identifier.						
Field Min	1		Occur Min	0			
Field Max	50		Occur Max	1			
Char Types	U		Special Chars				
Format	n/a		Constraints	n/a			
Code List							
Source	Addition for Voice Type 11						
XML Level 1	dod-ebts:ReferenceSystemIdentifier			Cardinality	0...*		
XML Level 2	nc:IdentificationCategory			Cardinality	0...1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8600_4

Reference System Identifier

Description

Mnemonic	ENITITY_DESC			Conditionality	0		
				Status	New - Emerging		
Description	Description of the identifier.						
Field Min	1		Occur Min	0			
Field Max	50		Occur Max	1			
Char Types	U		Special Chars				
Format	n/a		Constraints	n/a			
Code List							
Source	Addition for Voice Type 11						
XML Level 1	dod-ebts:ReferenceSystemIdentifier			Cardinality	0...*		
XML Level 2	nc:IdentificationCategoryDescriptionText			Cardinality	0...1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.8600_5

Reference System Identifier

Effective Date

Mnemonic	ENTITY_EFF			Conditionality	0		
				Status	New - Emerging		
Description	Effective date of the identifier.						
Field Min	Encoding Specific		Occur Min	0			
Field Max	Encoding Specific		Occur Max	1			
Char Types	ANS		Special Chars				
Format	n/a		Constraints	n/a			
Code List							
Source	Addition for Voice Type 11						
XML Level 1	dod-ebts:ReferenceSystemIdentifier			Cardinality	0...*		
XML Level 2	nc:IdentificationEffectiveDate/nc:Date			Cardinality	0...1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-2: User-Defined Descriptive Text

Page 297 of 1037

2.8600_6

Reference System Identifier

Expiration Date

Mnemonic	ENITITY_EXP			Conditionality	O		
				Status	New - Emerging		
Description	Expiration date of the identifier.						
Field Min	Encoding Specific		Occur Min	0			
Field Max	Encoding Specific		Occur Max	1			
Char Types	ANS		Special Chars				
Format	n/a		Constraints	n/a			
Code List							
Source	Addition for Voice Type 11						
XML Level 1	dod-ebts:ReferenceSystemIdentifier			Cardinality	0...*		
XML Level 2	nc:IdentificationExpirationDate/nc:Date			Cardinality	0...1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.8600_7

Reference System Identifier

Source

Mnemonic	ENTITY_SOURCE			Conditionality	O		
				Status	New - Emerging		
Description	Entity that generated the identifier.						
Field Min	1		Occur Min	0			
Field Max	50		Occur Max	1			
Char Types	U		Special Chars				
Format	n/a		Constraints	n/a			
Code List							
Source	Addition for Voice Type 11						
XML Level 1	dod-ebts:ReferenceSystemIdentifier			Cardinality	0...*		
XML Level 2	nc:IdentificationSourceText			Cardinality	0...1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8600_8

Reference System Identifier

Status

Mnemonic	ENTITY_STATUS			Conditionality	0		
				Status	New - Emerging		
Description	Current Status of the Identifier.						
Field Min	1		Occur Min	0			
Field Max	50		Occur Max	1			
Char Types	U		Special Chars				
Format	n/a		Constraints	n/a			
Code List							
Source	Addition for Voice Type 11						
XML Level 1	dod-ebts:ReferenceSystemIdentifier			Cardinality	0...*		
XML Level 2	nc:IdentificationStatus			Cardinality	0...1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.8600_9

Reference System Identifier

Augmentation Point

Mnemonic	ENTITY_AUGMENTATION			Conditionality	0		
				Status	New - Emerging		
Description	Description of changes to the Identifier.						
Field Min	1		Occur Min	0			
Field Max	50		Occur Max	1			
Char Types	U		Special Chars				
Format	n/a		Constraints	n/a			
Code List							
Source	Addition for Voice Type 11						
XML Level 1	dod-ebts:ReferenceSystemIdentifier			Cardinality	0...*		
XML Level 2	nc:IdentificationAugmentationPoint			Cardinality	0...1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8601

Response Maximum Count

Mnemonic	RESP_CNT			Conditionality	0
				Status	New - Emerging
Description	This field specifies the maximum number of candidate encounters desired to receive in the response. This number shall not exceed the upper limit set by the repository or the service level agreement (i.e. Top 10 candidates or Single ID).				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	N	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	Addition for Voice Type 11				
XML Level 1	dod-ebts:ResponseMaxCount			Cardinality	0..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.8602

Enhanced Status Message

Mnemonic	EMSU			Conditionality	M
				Status	New - Emerging
Description	To facilitate multiple status responses instead of using a single FBU 2.060 Status/Error Message (MSG).				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	Requested by IC				
XML Level 1	dod-ebts:EnhancedStatusMessage			Cardinality	0..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8602_0

Enhanced Status Message

Subfields: Repeating sets of information items

Mnemonic	EMSU_0			Conditionality	O		
				Status	New- Emerging		
Description	Repeating subfield for Enhanced Status Message.						
Field Min	n/a		Occur Min	0			
Field Max	n/a		Occur Max	*			
Char Types	n/a		Special Chars				
Format	n/a		Constraints	n/a			
Code List							
Source	EBTS 4.0						
XML Level 1	dod-ebts:AssignedIdentification			Cardinality	0...*		
XML Level 2				Cardinality			
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.8602_1

Enhanced Status Message

Comment

Mnemonic	EMSU_1			Conditionality	O		
				Status	New - Emerging		
Description	A comment regarding a status.						
Field Min	1		Occur Min	0			
Field Max	255		Occur Max	1			
Char Types	U		Special Chars				
Format	n/a		Constraints	n/a			
Code List							
Source	Requested by IC						
XML Level 1	dod-ebts:EnhancedStatusMessage			Cardinality	0...*		
XML Level 2	nc:StatusCommentText			Cardinality	0...1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8602_2

Enhanced Status Message

Date

Mnemonic	EMSU_2	Conditionality	O
		Status	New - Emerging
Description	A date concept for a date a status is given.		
Field Min	Encoding Specific	Occur Min	0
Field Max	Encoding Specific	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Requested by IC		
XML Level 1	dod-ebts:EnhancedStatusMessage	Cardinality	0...*
XML Level 2	nc:StatusDate/nc:Date	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.8602_3

Enhanced Status Message

Designator

Mnemonic	EMSU_3	Conditionality	O
		Status	New - Emerging
Description	A data concept for a status or condition of something or someone.		
Field Min	1	Occur Min	0
Field Max	255	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Requested by IC		
XML Level 1	dod-ebts:EnhancedStatusMessage	Cardinality	0...*
XML Level 2	nc:StatusDesignator	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8602_4

Enhanced Status Message

Description

Mnemonic	EMSU_4			Conditionality	O
				Status	New - Emerging
Description	A description of a status or condition of something or someone.				
Field Min	1	Occur Min	0		
Field Max	255	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	Requested by IC				
XML Level 1	dod-ebts:EnhancedStatusMessage			Cardinality	0...*
XML Level 2	nc:StatusDescriptionText			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.8602_5

Enhanced Status Message

Issuer Identification

Mnemonic	EMSU_5			Conditionality	O
				Status	New - Emerging
Description	An identification of a person or organization which assigns a status.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	Requested by IC				
XML Level 1	dod-ebts:EnhancedStatusMessage			Cardinality	0...*
XML Level 2	nc:StatusIssuerIdentification/nc:IdentificationID			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8602_6

Enhanced Status Message

Issuer

Mnemonic	EMSU_6			Conditionality	O		
				Status	New - Emerging		
Description	A name, identifier, or other reference of a person or organization which assigns a status.						
Field Min	1		Occur Min	0			
Field Max	50		Occur Max	1			
Char Types	U		Special Chars				
Format	n/a		Constraints	n/a			
Code List							
Source	Requested by IC						
XML Level 1	dod-ebts:EnhancedStatusMessage			Cardinality	0...*		
XML Level 2	nc:StatusIssuerText			Cardinality	0...1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.8602_7

Enhanced Status Message

Augmentation Point

Mnemonic	EMSU_7			Conditionality	O		
				Status	New - Emerging		
Description	An augmentation point for StatusType.						
Field Min	1		Occur Min	0			
Field Max	50		Occur Max	1			
Char Types	U		Special Chars				
Format	n/a		Constraints	n/a			
Code List							
Source	Requested by IC						
XML Level 1	dod-ebts:EnhancedStatusMessage			Cardinality	0...*		
XML Level 2	nc:StatusAugmentationPoint			Cardinality	0...1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8603

Primary Language

Mnemonic	PRIM_LANG		Conditionality	0	
			Status	New - Emerging	
Description	Primary system of words or symbols used for communication by a subject.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	U		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	Addition for Voice Type 11				
XML Level 1	dod-ebts:PrimaryLanguage		Cardinality	0...1	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.8603_1

Primary Language

Primary Language Code

Mnemonic	PRIM_LANG_1		Conditionality	0	
			Status	New - Emerging	
Description	A name of a system of words or symbols used for communication of a primary language that utilizes the alpha 3 iso_639-3 code set.				
Field Min	3		Occur Min	0	
Field Max	3		Occur Max	1	
Char Types	U		Special Chars		
Format	n/a		Constraints	n/a	
Code List					
Source	Addition for Voice Type 11				
XML Level 1	dod-ebts:PrimaryLanguage		Cardinality	0...1	
XML Level 2	nc:PersonLanguage		Cardinality	0...1	
XML Level 3	nc:LanguageCode		Cardinality	0...1	
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8603_2

Primary Language

Primary Language Description

Mnemonic	PRIM_LANG_2	Conditionality	O
		Status	New - Emerging
Description	A capacity of a person for a language with which that person has the strongest familiarity.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Addition for Voice Type 11		
XML Level 1	dod-ebts:PrimaryLanguage	Cardinality	0...1
XML Level 2	nc:PersonPrimaryLanguage	Cardinality	0...1
XML Level 3	nc:LanguageName	Cardinality	0...1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes

2.8603_3

Primary Language

Primary Language Dialect

Mnemonic	PRIM_LANG_3	Conditionality	O
		Status	New - Emerging
Description	Description of the primary language dialect.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Addition for Voice Type 11		
XML Level 1	dod-ebts:PrimaryLanguage	Cardinality	0...1
XML Level 2	dod-ebts:PrimaryLanguageDialect	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8603_4

Primary Language

Primary Language Subject Reads

Mnemonic	PRIM_LANG_4	Conditionality	O
		Status	New - Emerging
Description	True if a person is able to read the primary language; false otherwise.		
Field Min	1	Occur Min	0
Field Max	1	Occur Max	1
Char Types	N	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Addition for Voice Type 11		
XML Level 1	dod-ebts:PrimaryLanguage	Cardinality	0...1
XML Level 2	nc:PersonReadsLanguageIndicator	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.8603_5

Primary Language

Primary Language Subject Speaks

Mnemonic	PRIM_LANG_5	Conditionality	O
		Status	New - Emerging
Description	True if a person is able to speak the primary language; false otherwise.		
Field Min	1	Occur Min	0
Field Max	1	Occur Max	1
Char Types	N	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Addition for Voice Type 11		
XML Level 1	dod-ebts:PrimaryLanguage	Cardinality	0...1
XML Level 2	nc:PersonSpeaksLanguageIndicator	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8603_6

Primary Language

Primary Language Subject Writes

Mnemonic	PRIM_LANG_6	Conditionality	0
		Status	New - Emerging
Description	True if a person is able to write the primary language; false otherwise.		
Field Min	1	Occur Min	0
Field Max	1	Occur Max	1
Char Types	N	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Addition for Voice Type 11		
XML Level 1	dod-ebts:PrimaryLanguage	Cardinality	0...1
XML Level 2	nc:PersonWritesLanguageIndicator	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.8604

Secondary Language

Mnemonic	SECOND_LANG_0	Conditionality	0
		Status	New - Emerging
Description	Description of the Secondary Language.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Addition for Voice Type 11		
XML Level 1	dod-ebts:SecondaryLanguage	Cardinality	0...1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-2: User-Defined Descriptive Text

Page 308 of 1037

2.8604_0

Secondary Language

Subfields: Repeating sets of information items

Mnemonic	SECOND_LANG	Conditionality	O
		Status	New- Emerging
Description	Repeating subfield for Secondary Language.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	*
Char Types	n/a	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	EBTS 4.0		
XML Level 1	dod-ebts:SecondaryLanguage	Cardinality	0...*
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.8604_1

Secondary Language

Secondary Language Code

Mnemonic	SECOND_LANG_1	Conditionality	O
		Status	New - Emerging
Description	A name of a system of words or symbols used for communication of a secondary language that utilizes the alpha 3 iso_639-3 code set.		
Field Min	3	Occur Min	0
Field Max	3	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Addition for Voice Type 11		
XML Level 1	dod-ebts:SecondaryLanguage	Cardinality	0...*
XML Level 2	nc:PersonSecondaryLanguage	Cardinality	0...1
XML Level 3	nc:LanguageCode	Cardinality	0...1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8604_2

Secondary Language

Secondary Language Description

Mnemonic	SECOND_LANG_2		Conditionality	0	
			Status	New - Emerging	
Description	Description of the secondary language.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	Addition for Voice Type 11				
XML Level 1	dod-ebts:SecondaryLanguage		Cardinality	0...*	
XML Level 2	nc:PersonSecondaryLanguage		Cardinality	0...1	
XML Level 3	nc:LanguageName		Cardinality	0...1	
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.8604_3

Secondary Language

Secondary Language Dialect

Mnemonic	SECOND_LANG_3		Conditionality	0	
			Status	New - Emerging	
Description	Description of the secondary language dialect.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	*		
Char Types	U	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	Addition for Voice Type 11				
XML Level 1	dod-ebts:SecondaryLanguage		Cardinality	0...*	
XML Level 2	dod-ebts:SecondaryLanguageDialect		Cardinality	0...*	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8604_4

Secondary Language

Secondary Language Subject Reads

Mnemonic	SECOND_LANG_4			Conditionality	O
				Status	New - Emerging
Description	True if a person is able to read the secondary language; false otherwise.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	N	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	Addition for Voice Type 11				
XML Level 1	dod-ebts:SecondaryLanguage			Cardinality	0...*
XML Level 2	nc:PersonReadsLanguageIndicator			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.8604_5

Secondary Language

Secondary Language Subject Speaks

Mnemonic	SECOND_LANG_5			Conditionality	O
				Status	New - Emerging
Description	True if a person is able to speak the secondary language; false otherwise.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	N	Special Chars			
Format	n/a	Constraints	n/a		
Code List					
Source	Addition for Voice Type 11				
XML Level 1	dod-ebts:SecondaryLanguage			Cardinality	0...*
XML Level 2	nc:PersonSpeaksLanguageIndicator			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

2.8604_6

Secondary Language

Secondary Language Subject Writes

Mnemonic	SECOND_LANG_6		Conditionality	0
			Status	New - Emerging
Description	True if a person is able to write the secondary language; false otherwise.			
Field Min	1	Occur Min	0	
Field Max	1	Occur Max	1	
Char Types	N	Special Chars		
Format	n/a	Constraints	n/a	
Code List				
Source	Addition for Voice Type 11			
XML Level 1	dod-ebts:SecondaryLanguage		Cardinality	0...*
XML Level 2	nc:PersonWritesLanguageIndicator		Cardinality	0...1
XML Level 3			Cardinality	
XML Level 4			Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0
			No	DoD EBTS 4.0
				Yes

2.8605

Speaker Identification Engine Response

Mnemonic	ENG_RESP		Conditionality	0
			Status	New - Emerging
Description	Information set returned with the Speaker Candidate Results (SCR) response TOT as a result of the SID - Speaker Identification request TOT. The information set contains results information regarding matches against the stored voice engine model.			
Field Min	n/a	Occur Min	0	
Field Max	n/a	Occur Max	1	
Char Types	U	Special Chars		
Format	n/a	Constraints	n/a	
Code List				
Source	Addition for Voice Type 11			
XML Level 1	dod-ebts:SpeakerIdentificationEngineResponse		Cardinality	0...1
XML Level 2			Cardinality	
XML Level 3			Cardinality	
XML Level 4			Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0
			No	DoD EBTS 4.0
				Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8605_1

Speaker Identification Engine Response

Voice Engine Software Version

Mnemonic	ENG_RESP_1	Conditionality	O
		Status	New - Emerging
Description	Software version of the voice model engine generating the model and running the voice match comparison algorithm.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Addition for Voice Type 11		
XML Level 1	dod-ebts:SpeakerIdentificationEngineResponse	Cardinality	0...*
XML Level 2	nc:softwareVersionText	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.8605_2

Speaker Identification Engine Response

Voice Engine Software Name

Mnemonic	ENG_RESP_2	Conditionality	O
		Status	New - Emerging
Description	Name of the software voice model engine generating the model and running the voice match comparison algorithm.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Addition for Voice Type 11		
XML Level 1	dod-ebts:SpeakerIdentificationEngineResponse	Cardinality	0...*
XML Level 2	nc:SoftwareName	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.8605_3

Speaker Identification Engine Response

Voice Engine Vendor

Mnemonic	ENG_RESP_3	Conditionality	O
		Status	New - Emerging
Description	Text that specifies the software code vendor name.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Addition for Voice Type 11		
XML Level 1	dod-ebts:SpeakerIdentificationEngineResponse	Cardinality	0...*
XML Level 2	dod-ebts:SoftwareVendorNameText	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes

2.8605_4

Speaker Identification Engine Response

Detected Speaker Number

Mnemonic	ENG_RESP_4	Conditionality	O
		Status	New - Emerging
Description	Identifying number of the speaker assigned by the voice model engine.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Addition for Voice Type 11		
XML Level 1	dod-ebts:SpeakerIdentificationEngineResponse	Cardinality	0...*
XML Level 2	dod-ebts:DetectedSpeakerNumber	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

2.8605_5

Speaker Identification Engine Response

Voice Engine Rank

Mnemonic	ENG_RESP_5	Conditionality	O
		Status	New - Emerging
Description	Rank Score assigned to the voice file submitted as part of the Speaker Identification (SID) TOT.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	N	Special Chars	
Format	n/a	Constraints	n/a
Code List			
Source	Addition for Voice Type 11		
XML Level 1	dod-ebts:SpeakerIdentificationEngineResponse	Cardinality	0...*
XML Level 2	dod-ebts:EngineRank/nc:MeasureDecimalValue	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

2.8605_6

Speaker Identification Engine Response

Match Level

Mnemonic	ENG_RESP_6	Conditionality	O
		Status	New - Emerging
Description	Code indicating the voice engines level of confidence regarding the submission of the voice file in the Speaker Identification (SID) TOT comparison to the stored voice model.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	
Format	n/a	Constraints	n/a
Code List	SPEAKER MATCH LEVEL		
Source	Addition for Voice Type 11		
XML Level 1	dod-ebts:SpeakerIdentificationEngineResponse	Cardinality	0...*
XML Level 2	dod-ebts:MatchLevel	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.001

Record Header

Mnemonic	LEN			Conditionality	M
				Status	Active
Description	The record header appears as the first field (xx.001) in each Record Type. It contains information particular to the encoding format chosen, in order to enable proper reading of the record. In Traditional encoding, this field contains the record length in bytes (including all information separators). In NIEM-conformant XML encoding, this field contains the RecordCategoryCode, which is the numeric representation of the Record Type.				
Field Min	T = 4; X = 1		Occur Min	1	
Field Max	T = 8; X = 2		Occur Max	1	
Char Types	N		Special Chars	None	
Format	n/a		Constraints	positive integer	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ContentRecordSummary			Cardinality	1..1
XML Level 2	biom_1:RecordCategoryCode			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

9.002

Information Designation Character

Mnemonic	IDC			Conditionality	M
				Status	Active
Description	Each of the records present in a transaction, with the exception of the Type-1 record, shall include a field (xx.002) containing the information designation character / IDC. The value of the IDC shall be a sequentially assigned positive integer starting from zero and incremented by one up to a maximum of 99. IDC references are stated in Type-1 Field 1.003 Transaction content (CNT) and shall be used to relate information items in the CNT field of the Type-1 record to the other records in the transaction. Two or more records may share a single IDC solely to identify and link together records that pertain to different representations of the same biometric trait.				
Field Min	1		Occur Min	1	
Field Max	2		Occur Max	1	
Char Types	N		Special Chars	None	
Format	n/a		Constraints	0 <= IDC <= 99; integer	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ContentRecordSummary			Cardinality	1..1
XML Level 2	biom_1:ImageReferenceIdentification/nc:identificationID			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.003

Impression Type

Mnemonic	IMP		Conditionality	M
			Status	Active
Description	This mandatory field shall indicate the manner by which the friction ridge print was obtained.			
Field Min	1	Occur Min	1	
Field Max	2	Occur Max	1	
Char Types	N	Special Chars	None	
Format	n/a	Constraints	see Look Up Codes	
Code List	FRICTION RIDGE IMPRESSION CODES			
Source	ANSI/NIST ITL 1-2013 (Type-9)			
XML Level 1	biom_1:MinutiaeImpressionCaptureCategoryCode		Cardinality	1..1
XML Level 2			Cardinality	
XML Level 3			Cardinality	
XML Level 4			Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0 Yes DoD EBTS 4.0 Yes

9.004

Minutia Format

Mnemonic	FMT		Conditionality	M
			Status	Active
Description	This mandatory field is retained only for backward compatibility. It was a mandatory field in previous versions of the standard. This field shall always have a value "U", unless including legacy records 9.005 through 9.012 (described in ANSI/NIST-ITL 1-2007 and ANSI/NIST-ITL 2-2008), when this field shall contain "S".			
Field Min	1	Occur Min	1	
Field Max	1	Occur Max	1	
Char Types	A	Special Chars	None	
Format	n/a	Constraints	FMT = U	
Code List	MINUTIA FORMAT CODES			
Source	ANSI/NIST ITL 1-2013 (Type-9)			
XML Level 1	biom_1:MinutiaeFormatNISTStandardIndicator		Cardinality	1..1
XML Level 2			Cardinality	
XML Level 3			Cardinality	
XML Level 4			Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0 Yes DoD EBTS 4.0 Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.013

AFIS Feature Vector

Mnemonic	AFV			Conditionality	0
				Status	Active
Description	This field is a bit-packed field on the minutiae, the nearest neighbors, pattern class, and ridge counts. Its presence in the Type-9 record is allowed by including a "U" in the tagged field MINUTIAE FORMAT. It possesses sufficient features data to replace the rest of the Type-9 native mode record.				
Field Min	2048	Occur Min	0		
Field Max	2048	Occur Max	1		
Char Types	B	Special Chars	None		
Format	n/a	Constraints	n/a		
Code List					
Source	IAFIS-DOC-01078-9.3 (Type-9)				
XML Level 1	fbi-ebts:Minutiae	Cardinality	0..*		
XML Level 2	nc:BinaryBase64Object	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

9.014

Finger Number

Mnemonic	FGN			Conditionality	M
				Status	Active
Description	This two-byte field shall contain a character designating the finger position. Multiple codes are not allowed. Possible finger positions for a single latent characterization are specified in the accompanying Type-2 logical record. If multiple latents from the same person are transmitted, the particular position corresponding to the Type-9 record must be identified with the Type-9 record.				
Field Min	2	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	n/a		
Code List	FINGERPRINT TEN FINGER NUMBER PLUS UNKNOWN CODES				
Source	IAFIS-DOC-01078-9.3 (Type-9)				
XML Level 1	fbi-ebts:Minutiae	Cardinality	0..*		
XML Level 2	biom_1:MinutiaeFingerPositionCode	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.015

Number of Minutiae

Mnemonic	NMN			Conditionality	M
				Status	Active
Description	This field shall contain the count of the number of minutiae recorded for this fingerprint. The number should not exceed 254. If the number of minutiae provided in this field exceeds the number of minutiae the system can accommodate, the list will be truncated according to the reported minutiae quality. Minutiae below the proximal crease generally are not included.				
Field Min	2	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	n/a		
Code List					
Source	IAFIS-DOC-01078-9.3 (Type-9)				
XML Level 1	fbi-ebts:Minutiae	Cardinality	0..*		
XML Level 2	ansi-nist:MinutiaeQuantity	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

9.016

Fingerprint Characterization Process

Mnemonic	FCP			Conditionality	C
				Status	Active
Description	This field of three information items identifies the characterization equipment and the amount of manual intervention employed in the characterization process. This field is optional if the 9.013 AFIS Feature Vector field is completed.				
Field Min	n/a	Occur Min	1		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	IAFIS-DOC-01078-9.3 (Type-9)				
XML Level 1	fbi-ebts:Minutiae	Cardinality	0..*		
XML Level 2	fbi-ebts:MinutiaeReadingSystem	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

9.016_1

Fingerprint Characterization Process

Fingerprint Characterization Equipment

Mnemonic	VEN			Conditionality	M↑
				Status	Active
Description	The name of the organization (VEN) providing the fingerprint characterization process software.				
Field Min	3	Occur Min	1		
Field Max	12	Occur Max	1		
Char Types	A	Special Chars	None		
Format	n/a	Constraints	n/a		
Code List					
Source	IAFIS-DOC-01078-9.3 (Type-9)				
XML Level 1	fbi-ebts:Minutiae	Cardinality	0...*		
XML Level 2	fbi-ebts:MinutiaeReadingSystem	Cardinality	0..1		
XML Level 3	biom_1:ReadingSystemName	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

9.016_2

Fingerprint Characterization Process

Fingerprint Characterization Version Identifier

Mnemonic	VID			Conditionality	M↑
				Status	Active
Description	The vendor-supplied, alphanumeric character pair representing the model and/or version of the automatic process used in fingerprint characterization.				
Field Min	2	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	AN	Special Chars	None		
Format	n/a	Constraints	n/a		
Code List					
Source	IAFIS-DOC-01078-9.3 (Type-9)				
XML Level 1	fbi-ebts:Minutiae	Cardinality	0...*		
XML Level 2	fbi-ebts:MinutiaeReadingSystem	Cardinality	0..1		
XML Level 3	biom_1:ReadingSystemSubsystemIdentification	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.016_3

Fingerprint Characterization Process

Fingerprint Characterization Method

Mnemonic	MET			Conditionality	M↑
				Status	Active
Description	An ordered sequence of three characters indicating the degree of automation in the fingerprint characterization process.				
Field Min	3	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	A	Special Chars	None		
Format	n/a	Constraints	n/a		
Code List					
Source	IAFIS-DOC-01078-9.3 (Type-9)				
XML Level 1	fbi-ebts:Minutiae	Cardinality	0...*		
XML Level 2	fbi-ebts:MinutiaeReadingSystem	Cardinality	0..1		
XML Level 3	fbi-ebts:ReadingSystemCodingMethodCode	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

9.017

AFIS/FBI Pattern Classification

Mnemonic	APC			Conditionality	0
				Status	Active
Description	This field contains one to three information items with each composed of three information items. Each information item reports a possible basic pattern class (APAT) and the ridge counts (RCN1, RCN2) defining its subpattern class. It further subdivides the basic pattern classes of loops and whorls according to the count of ridges crossed or touched along a straight line joining the core(s) to the delta(s). The count is one more than the number of intervening ridges. For latents, the AFIS/ FBI will apply a suitable tolerance to the specified ridge count for search space penetration.				
Field Min	n/a	Occur Min	1		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	IAFIS-DOC-01078-9.3 (Type-9)				
XML Level 1	fbi-ebts:Minutiae	Cardinality	0...*		
XML Level 2	fbi-ebts:MinutiaeFingerPattern	Cardinality	1..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.017_1

AFIS/FBI Pattern Classification

Pattern Classification Code

Mnemonic	APAT			Conditionality	M↑
				Status	Active
Description	The list of acceptable CJIS pattern level fingerprint classifications.				
Field Min	2	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	A	Special Chars	None		
Format	n/a	Constraints	n/a		
Code List	FINGERPRINT CJIS PATTERN CLASSIFICATION				
Source	IAFIS-DOC-01078-9.3 (Type-9)				
XML Level 1	fbi-ebts:Minutiae	Cardinality	0...*		
XML Level 2	fbi-ebts:MinutiaeFingerPattern	Cardinality	1..1		
XML Level 3	fbi-ebts:FingerprintPatternClassificationCode	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

9.017_2

AFIS/FBI Pattern Classification

First Subpattern Ridge Count

Mnemonic	RCN1			Conditionality	C
				Status	Active
Description	The First Subpattern Ridge Count/Ridge Count Number (RCN1) represents the number of ridges between the core and the delta. For right and left slant loops, this count identifies the ridges crossed on a line between the core and the delta. For whorls, both the RCN1 and the RCN2 values have meaning. Permissible values are 1 to 30 for actual ridge counts and 30 if there are more than 30 ridges. The count of 31 indicates an unknown number of ridges, and 0 indicates that the ridge count is not applicable. If field 9.017 "APC" is present, at least one pattern classification must be provided. Up to two additional reference classes may be provided for a maximum of three total possible patterns.				
Field Min	1	Occur Min	0		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	n/a		
Code List	FINGERPRINT RIDGE NUMBER CODES				
Source	IAFIS-DOC-01078-9.3 (Type-9)				
XML Level 1	fbi-ebts:Minutiae	Cardinality	0...*		
XML Level 2	fbi-ebts:MinutiaeFingerPattern	Cardinality	1..1		
XML Level 3	biom_1:RidgeCountValue	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.017_3

AFIS/FBI Pattern Classification

Second Subpattern Ridge Count

Mnemonic	RCN2			Conditionality	C
				Status	Active
Description	The Second Subpattern Ridge Count/Ridge Count Number (RCN2) represents the number of ridges between the core and the delta. For right and left slant loops, this count identifies the ridges crossed on a line between the core and the delta. For whorls, both both the RCN1 and the RCN2 values have meaning. Permissible values are 1 to 30 for actual ridge counts and 30 if there are more than 30 ridges. The count of 31 indicates an unknown number of ridges, and 0 indicates that the ridge count is not applicable. If field 9.017 "APC" is present, at least one pattern classification must be provided. Up to two additional reference classes may be provided for a maximum of three total possible patterns.				
Field Min	1	Occur Min	0		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	n/a		
Code List	FINGERPRINT RIDGE NUMBER CODES				
Source	IAFIS-DOC-01078-9.3 (Type-9)				
XML Level 1	fbi-ebts:Minutiae	Cardinality	0..*		
XML Level 2	fbi-ebts:MinutiaeFingerPattern	Cardinality	1..1		
XML Level 3	biom_1:RidgeCountValue	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

9.018

Region of Value Polygon

Mnemonic	ROV			Conditionality	O
				Status	Active
Description	The complete, unparsed information defining the 3 to 20 vertices of a polygon that bound the region of the image from which the characterization products have been extracted. The order of the vertices must be in their consecutive order around the perimeter of the polygon, either clockwise or counterclockwise. The polygon side defined by the last information item and the first information item shall complete the polygon. The polygon shall be a simple, plane figure with no sides crossing and no interior holes.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	IAFIS-DOC-01078-9.3 (Type-9)				
XML Level 1	fbi-ebts:Minutiae	Cardinality	0..*		
XML Level 2	fbi-ebts:MinutiaPolygonalVerticesPositions	Cardinality	0..1		
XML Level 3	biom_1:PositionPolygonVertex	Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.018_1

Region of Value Polygon

Vertex

Mnemonic	XYM	Conditionality	M↑
		Status	Active
Description	One of the vertices of a polygon that bounds the region of the image from which the characterization products have been extracted. It consists of the combination of the row and column coordinates (XYM), with the first four digits representing the column and the second four digits representing the row in the XXXXYYYY structure. The vertices shall be identified in the same coordinate system as the minutiae, cores, and deltas in units of 10 micrometers and padded on the left with zeros as appropriate.		
Field Min	8	Occur Min	1
Field Max	8	Occur Max	1
Char Types	N	Special Chars	None
Format	XXXXYYYY	Constraints	n/a
Code List			
Source	IAFIS-DOC-01078-9.3 (Type-9)		
XML Level 1	fbi-ebts:Minutiae	Cardinality	0..*
XML Level 2	fbi-ebts:MinutiaPolygonalVerticesPositions	Cardinality	0..1
XML Level 3	biom_1:PositionPolygonVertex	Cardinality	3..20
XML Level 4	biom_1:PositionHorizontalCoordinateValue + biom_1:PositionVerticalCoordinateValue	Cardinality	1..1
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

9.019

Coordinate Offsets

Mnemonic	COF	Conditionality	O
		Status	Active
Description	This field allows the recording of translation, rotation, and image cropping employed in the characterization process to allow the examiner or analyst to overlay onto the original or intermediate image the features reported in this record. The units are in original image pixels and degrees using standard image processing coordinates; that is, (0,0) origin at the upper left, column index increasing from left to right, and row index increasing from top to bottom. For the native encoding, the column and row coordinate indexes (XYP) shall be coded as a single eight-digit integer number composed of a four-digit column coordinate (X) connected to a four-digit row coordinate (Y) using a format of XXXXYYYY. The column and row coordinate indexes (XYP) shall be coded as a minus sign is permitted in the leftmost digit of a four-digit group.		
Field Min	8	Occur Min	0
Field Max	8	Occur Max	1
Char Types	n/a	Special Chars	n/a
Format	n/a	Constraints	n/a
Code List			
Source	IAFIS-DOC-01078-9.3 (Type-9)		
XML Level 1	fbi-ebts:Minutiae	Cardinality	0..*
XML Level 2	fbi-ebts:MinutiaCoordinateOffsets	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.019_1

Coordinate Offsets

Offset to Upper Left Corner Subimage

Mnemonic	XYP			Conditionality	M↑
				Status	Active
Description	The offset to the upper left corner of a non-rotated subimage used subsequently in image processing.				
Field Min	8	Occur Min	1		
Field Max	8	Occur Max	1		
Char Types	N	Special Chars	Minus Sign		
Format	XXXXYYYY	Constraints	n/a		
Code List					
Source	IAFIS-DOC-01078-9.3 (Type-9)				
XML Level 1	fbi-ebts:Minutiae	Cardinality	0...*		
XML Level 2	fbi-ebts:MinutiaCoordinateOffsets	Cardinality	0..1		
XML Level 3	fbi-ebts:OffsetUpperLeftCoordinates	Cardinality	1..1		
XML Level 4	biom_1:PositionHorizontalCoordinateValue + biom_1:PositionVerticalCoordinateValue	Cardinality	1..1		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

9.019_2

Coordinate Offsets

Center of Rotation in Subimage

Mnemonic	XYP			Conditionality	C
				Status	Active
Description	The coordinates of the center of rotation within the Subimage about which the Subimage is rotated. If no rotation has been applied, the second, third, and fourth information item positions may be empty, but the intervening <US> Seperators must remain.				
Field Min	8	Occur Min	1		
Field Max	8	Occur Max	1		
Char Types	N	Special Chars	Minus Sign		
Format	XXXXYYYY	Constraints	n/a		
Code List					
Source	IAFIS-DOC-01078-9.3 (Type-9)				
XML Level 1	fbi-ebts:Minutiae	Cardinality	0...*		
XML Level 2	fbi-ebts:MinutiaCoordinateOffsets	Cardinality	0..1		
XML Level 3	fbi-ebts:OffsetCenterOfRotation	Cardinality	0..1		
XML Level 4	biom_1:PositionHorizontalCoordinateValue + biom_1:PositionVerticalCoordinateValue	Cardinality	1..1		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.019_3

Coordinate Offsets

Rotation Angle Clock Wise Degrees

Mnemonic	THET			Conditionality	C
				Status	Active
Description	The clockwise rotation angle (THET) in ten-thousandths of a degree resolution (e.g., 072.2342) including the decimal point. If no rotation has been applied, the second, third, and fourth information item positions may be empty, but the intervening <US> Separators must remain.				
Field Min	8	Occur Min	0		
Field Max	8	Occur Max	1		
Char Types	N	Special Chars	Period		
Format	n/a	Constraints	n/a		
Code List					
Source	IAFIS-DOC-01078-9.3 (Type-9)				
XML Level 1	fbi-ebts:Minutiae	Cardinality	0..*		
XML Level 2	fbi-ebts:MinutiaCoordinateOffsets	Cardinality	0..1		
XML Level 3	biom_1::PositionThetaAngleMeasure	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

9.019_4

Coordinate Offsets

Rotation Center in Rotated Subimage

Mnemonic	XYP			Conditionality	C
				Status	Active
Description	The item contains the coordinates of the center of rotation within the subimage about which the subimage is rotated. If no rotation has been applied, the second, third, and fourth information item positions may be empty, but the intervening <US> Separators must remain.				
Field Min	8	Occur Min	1		
Field Max	8	Occur Max	1		
Char Types	N	Special Chars	Minus Sign		
Format	XXXXYYYY	Constraints	n/a		
Code List					
Source	IAFIS-DOC-01078-9.3 (Type-9)				
XML Level 1	fbi-ebts:Minutiae	Cardinality	0..*		
XML Level 2	fbi-ebts:MinutiaCoordinateOffsets	Cardinality	0..1		
XML Level 3	fbi-ebts:OffsetTranslatedCenterOfRotation	Cardinality	0..1		
XML Level 4	biom_1::PositionHorizontalCoordinateValue + biom_1::PositionVerticalCoordinateValue	Cardinality	1..1		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.019_5

Coordinate Offsets

Offset to Upper Left Corner Final Subimage

Mnemonic	XYP			Conditionality	C
				Status	Active
Description	The fifth information item contains the upper-left-corner column and row offsets to a cropped subimage taken from the rotated image once adjusted to eliminate negative coordinate values. If no second sub-image is generated, this field may be left empty.				
Field Min	8	Occur Min	1		
Field Max	8	Occur Max	1		
Char Types	N	Special Chars	Minus Sign		
Format	XXXXYYYY	Constraints	n/a		
Code List					
Source	IAFIS-DOC-01078-9.3 (Type-9)				
XML Level 1	fbi-ebts:Minutiae	Cardinality	0..*		
XML Level 2	fbi-ebts:MinutiaCoordinateOffsets	Cardinality	0..1		
XML Level 3	fbi-ebts:OffsetTranslatedUpperLeftCoordinates	Cardinality	0..1		
XML Level 4	biom_1::PositionHorizontalCoordinateValue + biom_1::PositionVerticalCoordinateValue	Cardinality	1..1		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

9.02

Orientation Uncertainty

Mnemonic	ORN			Conditionality	M
				Status	Active
Description	The orientation uncertainty is a substantial contribution for AFIS/FBI latent characterizations and is not used for tenprint searches. This one-to-three character field contains an estimate of the deviation in degrees of the latent image (after rotation and translation to support editing and characterization) relative to fingertip up. The uncertainty would be zero if the impression were made with the extended finger aligned with the vertical of the displayed image. It is expected to be a human visual estimate of “the final image is aligned tip up within about X-degrees.” If the examiner does not provide an estimate, the default value shall be 180. This field is optional if the 9.013 AFIS Feature Vector field is completed.				
Field Min	1	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	n/a		
Code List					
Source	IAFIS-DOC-01078-9.3 (Type-9)				
XML Level 1	fbi-ebts:Minutiae	Cardinality	0..*		
XML Level 2	biom_1:PositionUncertaintyValue	Cardinality	1..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.021

Core Attributes

Mnemonic	CRA		Conditionality	O	
			Status	Active	
Description	The complete, unparsed information for cores that can be perceived in the fingerprint (both ten-print and latent). If there is no core perceived in the fingerprint image, the tagged field should be omitted.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	2	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	IAFIS-DOC-01078-9.3 (Type-9)				
XML Level 1	fbi-ebts:Minutiae		Cardinality	0..*	
XML Level 2	fbi-ebts:MinutiaeFingerCoreAttributePosition		Cardinality	0..2	
XML Level 3	fbi-ebts:MinutiaeFingerCoreAttributePosition		Cardinality	0..2	
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

9.021_1

Core Attributes

Core Location

Mnemonic	XYM		Conditionality	C	
			Status	Active	
Description	The X and Y coordinates of the core in units of 10 micrometers with the origin at the upper left of the fingerprint image. Note: Also called Core Position. Maximum of two cores reported. If only one core, the first subfield shall be terminated with the G/S separator instead of the R/S separator, and the second subfield shall be deleted.				
Field Min	8		Occur Min	1	
Field Max	8		Occur Max	1	
Char Types	N		Special Chars	None	
Format	XXXXYYYY		Constraints	n/a	
Code List					
Source	IAFIS-DOC-01078-9.3 (Type-9)				
XML Level 1	fbi-ebts:Minutiae		Cardinality	0..*	
XML Level 2	fbi-ebts:MinutiaeFingerCoreAttributePosition		Cardinality	0..2	
XML Level 3	biom_1:PositionHorizontalCoordinateValue		Cardinality	1..1	
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.021_2

Core Attributes

Core Direction in Degrees

Mnemonic	DID			Conditionality	C
				Status	Active
Description	The direction in integer degrees counterclockwise from horizontal right of the core opening through the center of the curvature for the innermost recurve at maximum curvature. Maximum of two cores reported. If only one core, the first subfield shall be terminated with the G/S separator instead of the R/S separator, and the second subfield shall be deleted.				
Field Min	3	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	n/a		
Code List					
Source	IAFIS-DOC-01078-9.3 (Type-9)				
XML Level 1	fbi-ebts:Minutiae	Cardinality	0..*		
XML Level 2	fbi-ebts:MinutiaeFingerCoreAttributePosition	Cardinality	0..2		
XML Level 3	biom_1:PositionDirectionDegreeValue	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

9.021_3

Core Attributes

Core Position Uncertainty

Mnemonic	PUM			Conditionality	C
				Status	Active
Description	The radius in integer units of 10 micrometers of the position uncertainty in the manual or automatic placement of the core. Maximum of two cores reported. If only one core, the first subfield shall be terminated with the G/S separator instead of the R/S separator, and the second subfield shall be deleted.				
Field Min	4	Occur Min	1		
Field Max	4	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	n/a		
Code List					
Source	IAFIS-DOC-01078-9.3 (Type-9)				
XML Level 1	fbi-ebts:Minutiae	Cardinality	0..*		
XML Level 2	fbi-ebts:MinutiaeFingerCoreAttributePosition	Cardinality	0..2		
XML Level 3	biom_1:PositionUncertaintyValue	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.022

Delta Attributes

Mnemonic	DLA		Conditionality	O	
			Status	Active	
Description	The complete, unparsed information for deltas that can be perceived in the fingerprint for both AFIS/FBI latent and ten-print characterizations.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	2	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	IAFIS-DOC-01078-9.3 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae		Cardinality	0...1	
XML Level 2	biom_1:MinutiaeFingerDeltaAttributePosition		Cardinality	0...*	
XML Level 3	fbi-ebts:MinutiaeFingerDeltaAttributePosition		Cardinality	0..2	
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

9.022_1

Delta Attributes

Delta Location

Mnemonic	XYM		Conditionality	C	
			Status	Active	
Description	The X and Y coordinates of the delta in units of 10 micrometers with the origin at the upper left of the fingerprint image. Note: Also called Delta Position. Maximum of two cores reported. If only one core, the first subfield shall be terminated with the G/S separator instead of the R/S separator, and the second subfield shall be deleted.				
Field Min	8		Occur Min	1	
Field Max	8		Occur Max	1	
Char Types	N		Special Chars	None	
Format	XXXXYYYY		Constraints	n/a	
Code List					
Source	IAFIS-DOC-01078-9.3 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae		Cardinality	0...1	
XML Level 2	biom_1:MinutiaeFingerDeltaAttributePosition		Cardinality	0...*	
XML Level 3	biom_1:PositionHorizontalCoordinateValue		Cardinality	1..1	
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.022_2

Delta Attributes

Upward Flow Direction

Mnemonic	DIDU			Conditionality	C
				Status	Active
Description	The direction in integer degrees counterclockwise from horizontal right of the direction of the ridge flow upward from the delta. Direction angles shall be reported between "001" and "360" degrees only. The value "000" shall be reserved for "direction not provided" while "360" shall be equivalent to zero degrees. Maximum of two cores reported. If only one core, the first subfield shall be terminated with the G/S separator instead of the R/S separator, and the second subfield shall be deleted.				
Field Min	3	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	n/a		
Code List					
Source	IAFIS-DOC-01078-9.3 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeFingerDeltaAttributePosition	Cardinality	0..*		
XML Level 3	biom_1:PositionDirectionDegreeValue	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

9.022_3

Delta Attributes

Leftward Flow Direction

Mnemonic	DIDL			Conditionality	C
				Status	Active
Description	The direction in integer degrees counterclockwise from horizontal right of the direction of the ridge flow outward from the delta and to the left. Direction angles shall be reported between "001" and "360" degrees only. The value "000" shall be reserved for "direction not provided" while "360" shall be equivalent to zero degrees. Maximum of two cores reported. If only one core, the first subfield shall be terminated with the G/S separator instead of the R/S separator, and the second subfield shall be deleted.				
Field Min	3	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	n/a		
Code List					
Source	IAFIS-DOC-01078-9.3 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeFingerDeltaAttributePosition	Cardinality	0..*		
XML Level 3	biom:MinutiaeDeltaDirectionLeftUncertaintyValue	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.022_4

Delta Attributes

Rightward Flow Direction

Mnemonic	DIDR			Conditionality	C
				Status	Active
Description	The direction in integer degrees counterclockwise from horizontal right of the direction of the ridge flow outward from the delta and to the right. Direction angles shall be reported between "001" and "360" degrees only. The value "000" shall be reserved for "direction not provided" while "360" shall be equivalent to zero degrees. Maximum of two cores reported. If only one core, the first subfield shall be terminated with the G/S separator instead of the R/S separator, and the second subfield shall be deleted.				
Field Min	3	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	n/a		
Code List					
Source	IAFIS-DOC-01078-9.3 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeFingerDeltaAttributePosition	Cardinality	0..*		
XML Level 3	biom_1:PositionDirectionDegreeValue	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

9.022_5

Delta Attributes

Delta Position Uncertainty

Mnemonic	PUM			Conditionality	C
				Status	Active
Description	The radius of position uncertainty in the manual or automatic placement of the delta in integer units of 10 micrometers. Maximum of two cores reported. If only one core, the first subfield shall be terminated with the G/S separator instead of the R/S separator, and the second subfield shall be deleted.				
Field Min	4	Occur Min	1		
Field Max	4	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	n/a		
Code List					
Source	IAFIS-DOC-01078-9.3 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeFingerDeltaAttributePosition	Cardinality	0..*		
XML Level 3	biom_1:PositionUncertaintyValue	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

9.023

Minutiae and Ridge Count Data

Mnemonic	MAT		Conditionality	M
			Status	Active
Description	This field shall contain all of the individual minutiae and ridge count data associated with the current fingerprint impression. It shall be composed of as many information items as there are minutiae stated in field 9.015 (NMN). Each subfield shall be devoted to a single minutia and shall consist of multiple information items. For traditional encoding, subfields shall be separated by the separator character and all information items within a subfield shall be separated by the designated separator character. The minutiae shall be indexed from one to NMN and need not be ordered according to any particular attribute. The first two information items are required, and the others are used to achieve best possible candidate list performance. An information item may be omitted, but its separator character must remain, except all ridge count data must be present with special values designating missing or omitted data.			
Field Min	n/a	Occur Min	1	
Field Max	n/a	Occur Max	254	
Char Types	n/a	Special Chars	n/a	
Format	n/a	Constraints	n/a	
Code List				
Source	IAFIS-DOC-01078-9.3 (Type-9)			
XML Level 1	biom_1:MinutiaRidgeCount	Cardinality	0...*	
XML Level 2	fbi-ebts:MinutiaDetail	Cardinality	1..254	
XML Level 3		Cardinality		
XML Level 4		Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0
			Yes	DoD EBTS 4.0
				Yes

9.023_1

Minutiae and Ridge Count Data

Minutiae Index Number

Mnemonic	MDX		Conditionality	M
			Status	Active
Description	This information item is the minutiae index number, which shall be initialized to "1" and incremented by "1" for each additional minutia in the fingerprint. This index number serves to identify each individual minutia.			
Field Min	3	Occur Min	1	
Field Max	3	Occur Max	1	
Char Types	N	Special Chars	None	
Format	n/a	Constraints	n/a	
Code List				
Source	IAFIS-DOC-01078-9.3 (Type-9)			
XML Level 1	biom_1:MinutiaRidgeCount	Cardinality	0...*	
XML Level 2	biom_1:MinutiaIdentification	Cardinality	1..1	
XML Level 3		Cardinality		
XML Level 4		Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0
			Yes	DoD EBTS 4.0
				Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.023_2

Minutiae and Ridge Count Data

Location Direction

Mnemonic	XYT			Conditionality	M
				Status	Active
Description	The X and Y coordinates are values ranging from zero upward, and the theta direction value, between 000 and 360, shall comprise the second required information item. These three values shall be coded and recorded as a single 11-digit integer corresponding to the connected X, Y, and theta values, in that order. If the minutiae is of Type D, the theta value shall be recorded as "000." The origin of the coordinate system shall be the upper left corner of the image with X increasing to the right and Y increasing downward. The coordinate system units shall be units of 0.01mm (10 micrometers). The direction of an ending shall be into the ending ridge and the direction of a bifurcation shall be into the white space created by the dividing ridge. Angles shall be in integer degrees measured positive counterclockwise from a reference horizontal and to the right. The XY coordinates shall be applied after all rotation and translation of the image has been accomplished.				
Field Min	11	Occur Min	1		
Field Max	11	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	n/a		
Code List					
Source	IAFIS-DOC-01078-9.3 (Type-9)				
XML Level 1	biom_1:MinutiaRidgeCount			Cardinality	0...*
XML Level 2	biom_1:PositionHorizontalCoordinateValue and biom_1::PositionVerticalCoordinateValue			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

9.023_3

Minutiae and Ridge Count Data

Quality Measure

Mnemonic	QMS			Conditionality	O
				Status	Active
Description	This information item is the minutiae quality measure. The two-digit values shall range from 0 to 63. The value zero Description shall indicate a manually encoded minutia. The value "1" shall indicate that no method of indicating a confidence level is available. Values between 2 and 63 shall indicate decreasing levels of confidence, with 2 denoting the greatest confidence.				
Field Min	2	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	n/a		
Code List					
Source	IAFIS-DOC-01078-9.3 (Type-9)				
XML Level 1	biom_1:MinutiaRidgeCount			Cardinality	0...*
XML Level 2	biom_1:MinutiaQualityValue			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.023_4

Minutiae and Ridge Count Data

Minutiae Type Designation

Mnemonic	MNT	Conditionality	O
		Status	Active
Description	A single character designating the minutiae type within the IAFIS Features for minutiae record type.		
Field Min	1	Occur Min	0
Field Max	1	Occur Max	*
Char Types	AN	Special Chars	None
Format	n/a	Constraints	n/a
Code List	IAFIS MINUTIAE CODES		
Source	IAFIS-DOC-01078-9.3 (Type-9)		
XML Level 1	biom_1:MinutiaRidgeCount	Cardinality	0...*
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

9.023_5

Minutiae and Ridge Count Data

Ridge Count Data Octant 0

Mnemonic	MRO	Conditionality	C
		Status	Active
Description	The ridge count data for the nearest neighboring minutia of the indexed minutia. This subfield contains information for Octant 0 and shall consist of a minutiae index number and a ridge count combined to form a five digit number. Up to eight neighboring minutiae can be recorded, each being the nearest neighbor in an angular sector of 45 degrees (octant) with the zeroth octant centered (+/- 22.5 degrees) and aligned with the direction of the minutiae and increasing in octant index in the counterclockwise direction. If a minutia does not have a neighbor in a particular octant, the value "25515" should be used for the sub-item in native encoding. For XML encoding, this information item is represented in separate fields for the index and ridge count.		
Field Min	5	Occur Min	1
Field Max	5	Occur Max	1
Char Types	N	Special Chars	None
Format	NNNNN	Constraints	n/a
Code List			
Source	IAFIS-DOC-01078-9.3 (Type-9)		
XML Level 1	biom_1:MinutiaRidgeCount	Cardinality	0...*
XML Level 2	biom_1::RidgeCountReferenceIdentification/nc:IdentificationID + biom_1:RidgeCountValue	Cardinality	1..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.023_6

Minutiae and Ridge Count Data

Ridge Count Data Octant 1

Mnemonic	MRO1	Conditionality	C
		Status	Active
Description	The ridge count data for the nearest neighboring minutia of the indexed minutia. This subfield contains information for Octant 1 and shall consist of a minutiae index number and a ridge count combined to form a five digit number. If a minutia does not have a neighbor in a particular octant, the value "25515" should be used for the sub-item in native encoding. Fox XML encoding, this information item is represented in separate fields for the index and ridge count.		
Field Min	5	Occur Min	1
Field Max	5	Occur Max	1
Char Types	N	Special Chars	None
Format	NNNNN	Constraints	n/a
Code List			
Source	IAFIS-DOC-01078-9.3 (Type-9)		
XML Level 1	biom_1:MinutiaRidgeCount	Cardinality	0..*
XML Level 2	biom_1:RidgeCountReferenceIdentification/nc:IdentificationID + biom_1:RidgeCountValue	Cardinality	1..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

9.023_7

Minutiae and Ridge Count Data

Ridge Count Data Octant 2

Mnemonic	MRO2	Conditionality	C
		Status	Active
Description	The ridge count data for the nearest neighboring minutia of the indexed minutia. This subfield contains information for Octant 2 and shall consist of a minutiae index number and a ridge count combined to form a five digit number. If a minutia does not have a neighbor in a particular octant, the value "25515" should be used for the sub-item in native encoding. Fox XML encoding, this information item is represented in separate fields for the index and ridge count.		
Field Min	5	Occur Min	1
Field Max	5	Occur Max	1
Char Types	N	Special Chars	None
Format	NNNNN	Constraints	n/a
Code List			
Source	IAFIS-DOC-01078-9.3 (Type-9)		
XML Level 1	biom_1:MinutiaRidgeCount	Cardinality	0..*
XML Level 2	biom_1:RidgeCountReferenceIdentification/nc:IdentificationID + biom_1:RidgeCountValue	Cardinality	1..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.023_8

Minutiae and Ridge Count Data

Ridge Count Data Octant 3

Mnemonic	MRO3			Conditionality	C
				Status	Active
Description	The ridge count data for the nearest neighboring minutia of the indexed minutia. This subfield contains information for Octant 3 and shall consist of a minutiae index number and a ridge count combined to form a five digit number. If a minutia does not have a neighbor in a particular octant, the value "25515" should be used for the sub-item in native encoding. Fox XML encoding, this information item is represented in separate fields for the index and ridge count.				
Field Min	5	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	NNNNN	Constraints	n/a		
Code List					
Source	IAFIS-DOC-01078-9.3 (Type-9)				
XML Level 1	biom_1:MinutiaRidgeCount			Cardinality	0..*
XML Level 2	biom_1:RidgeCountReferenceIdentification/nc:IdentificationID + biom_1: RidgeCountValue			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.023_9

Minutiae and Ridge Count Data

Ridge Count Data Octant 4

Mnemonic	MRO4			Conditionality	C
				Status	Active
Description	The ridge count data for the nearest neighboring minutia of the indexed minutia. This subfield contains information for Octant 4 and shall consist of a minutiae index number and a ridge count combined to form a five digit number. If a minutia does not have a neighbor in a particular octant, the value "25515" should be used for the sub-item in native encoding. Fox XML encoding, this information item is represented in separate fields for the index and ridge count.				
Field Min	5	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	NNNNN	Constraints	n/a		
Code List					
Source	IAFIS-DOC-01078-9.3 (Type-9)				
XML Level 1	biom_1:MinutiaRidgeCount			Cardinality	0..*
XML Level 2	biom_1:RidgeCountReferenceIdentification/nc:IdentificationID + biom_1: RidgeCountValue			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.023_10

Minutiae and Ridge Count Data

Ridge Count Data Octant 5

Mnemonic	MRO5			Conditionality	C
				Status	Active
Description	The ridge count data for the nearest neighboring minutia of the indexed minutia. This subfield contains information for Octant 5 and shall consist of a minutiae index number and a ridge count combined to form a five digit number. If a minutia does not have a neighbor in a particular octant, the value "25515" should be used for the sub-item in native encoding. Fox XML encoding, this information item is represented in separate fields for the index and ridge count.				
Field Min	5	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	NNNNN	Constraints	n/a		
Code List					
Source	IAFIS-DOC-01078-9.3 (Type-9)				
XML Level 1	biom_1:MinutiaRidgeCount			Cardinality	0..*
XML Level 2	biom_1:RidgeCountReferenceIdentification/nc:IdentificationID + biom_1: RidgeCountValue			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.023_11

Minutiae and Ridge Count Data

Ridge Count Data Octant 6

Mnemonic	MRO6			Conditionality	C
				Status	Active
Description	The ridge count data for the nearest neighboring minutia of the indexed minutia. This subfield contains information for Octant 6 and shall consist of a minutiae index number and a ridge count combined to form a five digit number. If a minutia does not have a neighbor in a particular octant, the value "25515" should be used for the sub-item in native encoding. Fox XML encoding, this information item is represented in separate fields for the index and ridge count.				
Field Min	5	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	NNNNN	Constraints	n/a		
Code List					
Source	IAFIS-DOC-01078-9.3 (Type-9)				
XML Level 1	biom_1:MinutiaRidgeCount			Cardinality	0..*
XML Level 2	biom_1:RidgeCountReferenceIdentification/nc:IdentificationID + biom_1: RidgeCountValue			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.023_12

Minutiae and Ridge Count Data

Ridge Count Data Octant 7

Mnemonic	MRO7			Conditionality	C
				Status	Active
Description	The ridge count data for the nearest neighboring minutia of the indexed minutia. This subfield contains information for Octant 7 and shall consist of a minutiae index number and a ridge count combined to form a five digit number. If a minutia does not have a neighbor in a particular octant, the value "25515" should be used for the sub-item in native encoding. Fox XML encoding, this information item is represented in separate fields for the index and ridge count.				
Field Min	5	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	NNNNN	Constraints	n/a		
Code List					
Source	IAFIS-DOC-01078-9.3 (Type-9)				
XML Level 1	biom_1:MinutiaRidgeCount			Cardinality	0...*
XML Level 2	biom_1:RidgeCountReferenceIdentification/nc:IdentificationID + biom_1: RidgeCountValue			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.023_13

Minutiae and Ridge Count Data

Octant Residuals

Mnemonic	RSO			Conditionality	O
				Status	Active
Description	The RSO indicates into which half of the octant each neighboring minutia lies. This subfield is beneficial for performance but not mandatory. The characters are ordered left to right according to the ascending octant index. The corresponding character shall be 1 if the neighboring minutia lies in the counterclockwise half of the octant. The corresponding character shall be 0 if the neighboring minutia lies in the clockwise half of the octant or if there is no neighboring minutiae in the octant.				
Field Min	8	Occur Min	0		
Field Max	8	Occur Max	*		
Char Types	N	Special Chars	None		
Format	NNNNNNNN	Constraints	n/a		
Code List	OCTANT RESIDUALS CODES				
Source	IAFIS-DOC-01078-9.3 (Type-9)				
XML Level 1	biom_1:MinutiaRidgeCount			Cardinality	0...*
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.024

Characterization Quality

Mnemonic	CHQ	Conditionality	O
		Status	Active
Description	This is a single information item field of three numeric characters with the possible value of 1 to 254. The principal quality parameter is the "Equivalent Number of Minutiae." The distribution of the parameter over thousands of fingerprints approximates a Gaussian distribution with a mean of about 50 and a standard deviation of about 12. The equivalent number of minutiae is calculated as the sum of the weighted normalized quality with the weighting being the number of qualified neighbors for the minutiae divided by the maximum number of neighbors (eight). The normalized minutiae quality ranges from unity (best) to zero (worst). A qualified neighbor would be another minutia with a reliable separating ridge count (less than 14) and within a reliable distance (not more than 1/5 inch).		
Field Min	1	Occur Min	0
Field Max	3	Occur Max	*
Char Types	N	Special Chars	None
Format	n/a	Constraints	n/a
Code List			
Source	IAFIS-DOC-01078-9.3 (Type-9)		
XML Level 1	fbi-ebts:Minutiae	Cardinality	0...*
XML Level 2	fbi-ebts:MinutiaCharacterizationQualityValue	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

9.025

Classifier Quality

Mnemonic	CLQ	Conditionality	O
		Status	Active
Description	This is a single information item field of seven characters representing a positive real number between one (1.0000) and 99 (99.9999) indicating the quality or confidence of the automatic classification. The presence of the information item may reduce the processing load, but its absence will not degrade performance. A value of 1.0000 indicates best possible quality or confidence; increasing values indicate progressively worse quality or confidence. The information item format shall be XX.YYYY in which XX represents the integer portion and YYYY the fractional portion to four decimal places with a decimal point (period) between.		
Field Min	6	Occur Min	0
Field Max	7	Occur Max	*
Char Types	N	Special Chars	Period
Format	XX.YYYY	Constraints	n/a
Code List			
Source	IAFIS-DOC-01078-9.3 (Type-9)		
XML Level 1	fbi-ebts:Minutiae	Cardinality	0...*
XML Level 2	fbi-ebts:MinutiaClassifierQualityValue	Cardinality	0...2
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.126

M1 CBEFF Information

Mnemonic	CBI			Conditionality	M
				Status	Active
Description	This field is mandatory if the INCITS 378 feature set is contained in the transaction. Otherwise, it shall not occur. It shall contain three information items CFO, CFT, and CPI, when present.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	INCITS 378				
XML Level 1	biom_1:INCITSMinutiae			Cardinality	0...1
XML Level 2	biom_1:INCITSMinutiae			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

9.126_1

M1 CBEFF Information

CBEFF Format Owner

Mnemonic	CFO			Conditionality	M↑
				Status	Active
Description	The information item shall contain the value "27". This is the identification of the CBEFF Format Owner assigned by the International Biometric Industry Association (IBIA) to INCITS Technical Committee M1.				
Field Min	2	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	None		
Format	NN	Constraints	CFO = 27		
Code List	CBEFF FORMAT OWNER CODES				
Source	INCITS 378				
XML Level 1	biom_1:INCITSMinutiae			Cardinality	0...1
XML Level 2	biom_1:CBEFFFormatOwnerIdentification/nc:IdentificationID			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.126_2

M1 CBEFF Information

CBEFF Format Type

Mnemonic	CFT			Conditionality	M↑
				Status	Active
Description	The second information item (CBEFF format type / CFT) is assigned a value of "513" (following INCITS 378-2004) if this record contains Field 9.137: FMD without Field 9.138: RCI, Field 9.139: CIN or Field 9.140: DIN. A value of "514" (following INCITS 378-2004) indicates the presence of one of the previously indicated fields. If INCITS 378-2009 is followed, a value of "515" is entered and does not indicate the specific presence or absence of these fields.				
Field Min	3	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	None		
Format	NNN	Constraints	CFT = 513 or 514 for INCITS 378-2004 and 515 for INCITS 378-2009		
Code List	CBEFF FORMAT TYPE CODES				
Source	INCITS 378				
XML Level 1	biom_1:INCITSMinutiae	Cardinality	0...1		
XML Level 2	biom_1:CBEFFFormatCategoryIdentification/nc:IdentificationID	Cardinality	1..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

9.126_3

M1 CBEFF Information

CBEFF Product Identifier

Mnemonic	CPI			Conditionality	M↑
				Status	Active
Description	This information item identifies the "owner" of the encoding equipment. The vendor establishes this value. It can be obtained from the IBIA website (www.ibia.org) if it is posted. If it is not posted, then use the value "0000"				
Field Min	8	Occur Min	1		
Field Max	8	Occur Max	1		
Char Types	H	Special Chars	None		
Format	HHHH	Constraints	None		
Code List					
Source	INCITS 378				
XML Level 1	biom_1:INCITSMinutiae	Cardinality	0...1		
XML Level 2	biom_1:CBEFFProductIdentification/nc:IdentificationID	Cardinality	1..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

9.127

M1 Capture Equipment Identification

Mnemonic	CEI			Conditionality	M
				Status	Active
Description	This field shall contain two information items: the Appendix F Status (AFS) and the Capture Equipment ID (CID).				
Field Min	n/a		Occur Min	1	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	INCITS 378				
XML Level 1	biom_1:INCITSMinutiae			Cardinality	0..1
XML Level 2	biom_1:ImageCaptureDetail			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

9.127_1

M1 Capture Equipment Identification

Appendix F Status

Mnemonic	AFS			Conditionality	M↑
				Status	Active
Description	This field shall contain "APPF" if the equipment used originally to acquire the image was certified to conform with Appendix F specifications. (the list of certified products at http://fbibiospecs.org). If the equipment did not conform it will contain the value of "NONE".				
Field Min	4		Occur Min	1	
Field Max	4		Occur Max	1	
Char Types	A		Special Chars	None	
Format	n/a		Constraints	AFS = APPF or NONE	
Code List					
Source	INCITS 378				
XML Level 1	biom_1:INCITSMinutiae			Cardinality	0..1
XML Level 2	biom_1:ImageCaptureDetail			Cardinality	1..1
XML Level 3	biom_1:CaptureDeviceCertificationCode			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.127_2

M1 Capture Equipment Identification

Capture Equipment Identifier

Mnemonic	CID			Conditionality	M↑
				Status	Active
Description	The information item shall contain the vendor-assigned product number/identifier (up to 30 characters) of the capture equipment. A value of "0" indicates that the capture equipment ID is unreported.				
Field Min	1	Occur Min	1		
Field Max	30	Occur Max	1		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints	None (0 = unreported)		
Code List	BIOMETRIC CAPTURE DEVICE CONFORMANCE CODES				
Source	INCITS 378				
XML Level 1	biom_1:INCITSMinutiae	Cardinality	0...1		
XML Level 2	biom_1:ImageCaptureDetail	Cardinality	1..1		
XML Level 3	biom_1:CaptureDeviceIdentification/nc:IdentificationID	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

9.128

M1 Horizontal Line Length

Mnemonic	HLL			Conditionality	M
				Status	Active
Description	The number of pixels contained on a single horizontal line of the image. The maximum horizontal size is limited to 99,999 for type 9 data. The minimum value is 10 pixels. The total image size (HLL times VLL) can be accommodated in Field 9.001 for Traditional encoding.				
Field Min	2	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	10 <= HLL <= 99,999; positive integer		
Code List					
Source	INCITS 378				
XML Level 1	biom_1:INCITSMinutiae	Cardinality	0...1		
XML Level 2	biom1:FingerImpressionImage	Cardinality	1...1		
XML Level 3	biom_1:ImageHorizontalLineLengthPixelQuantity	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.129

M1 Vertical Line Length

Mnemonic	VLL			Conditionality	M
				Status	Active
Description	The number of horizontal lines contained in the image. The maximum vertical size is limited 99,999 pixels for type 9 data. The minimum value is 10 pixels. The total image size (HLL times VLL) can be accommodated in Field 9.001 for Traditional encoding.				
Field Min	2	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	10 <= VLL <= 99,999; positive integer		
Code List					
Source	INCITS 378				
XML Level 1	biom_1:INCITSMinutiae	Cardinality	0..1		
XML Level 2	biom1:FingerImpressionImage	Cardinality	1..1		
XML Level 3	biom_1:ImageVerticalLineLengthPixelQuantity	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

9.13

Scale Units

Mnemonic	SLC			Conditionality	M
				Status	Active
Description	The image sampling frequency (pixel density). A value of "1" shall indicate pixels per inch. A value of "2" shall indicate pixels per centimeter. A value of "0" in this field indicates that no scale is provided, and the quotient of THPS/TVPS (Fields 9.131/9.132) shall provide the pixel aspect ratio.				
Field Min	1	Occur Min	1		
Field Max	1	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	SLC = 0, 1 or 2		
Code List	SCALE UNIT CODES				
Source	INCITS 378				
XML Level 1	biom_1:INCITSMinutiae	Cardinality	0..1		
XML Level 2	biom1:FingerImpressionImage	Cardinality	1..1		
XML Level 3	biom_1:ImageScaleUnitsCode	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.131

Transmitted Horizontal Pixel Scale

Mnemonic	THPS			Conditionality	M
				Status	Active
Description	This is the integer pixel density used in the horizontal direction of the image if SLC has a value of "1" or "2". If SLC has a value of "0", this information item shall contain the horizontal component of the pixel aspect ratio, up to 5 integer digits. For example, if the SLC value = 1, then the value of THPS could be '1000' for a 1000 ppi sensor.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	positive integer		
Code List					
Source	INCITS 378				
XML Level 1	biom_1:INCITSMinutiae	Cardinality	0..1		
XML Level 2	biom1:FingerImpressionImage	Cardinality	1..1		
XML Level 3	biom_1:ImageHorizontalPixelDensityValue	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

9.132

Transmitted Vertical Pixel Scale

Mnemonic	TVPS			Conditionality	M
				Status	Active
Description	This is the integer pixel density used in the vertical direction of the image if SLC has a value of "1" or "2". If SLC has a value of "0", this information item shall contain the vertical component of the pixel aspect ratio, up to 5 integer digits. If SLC is 1 or 2, then TVPS shall equal THPS.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	positive integer		
Code List					
Source	INCITS 378				
XML Level 1	biom_1:INCITSMinutiae	Cardinality	0..1		
XML Level 2	biom1:FingerImpressionImage	Cardinality	1..1		
XML Level 3	biom_1:ImageVerticalPixelDensityValue	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.133

M1 Finger View

Mnemonic	FVW			Conditionality	M
				Status	Active
Description	This mandatory field contains the view number of the finger associated with this record's data. The view number begins with "0" and increments by one to "15". Finger view differentiates multiple images of the same finger that are included in the transaction to be taken consecutively to develop an "average" template for that particular set of finger minutiae for enrollment applications.				
Field Min	1	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= FVW <= 15		
Code List	FINGERPRINT FINGER VIEW CODES				
Source	INCITS 378				
XML Level 1	biom_1:INCITSMinutiae	Cardinality	0...1		
XML Level 2	biom1:FingerImpressionImage	Cardinality	1...1		
XML Level 3	biom_1:FingerViewNumeric	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

9.134

M1 Friction Ridge Generalized Position

Mnemonic	FGP			Conditionality	M
				Status	Active
Description	This is a mandatory field. See ANSI/NIST ITL for details. Valid codes for this field are between 1 and 10, taken from Look Up Codes to indicate the finger position. (Note that codes 16 and 17 are not covered in INCITS 378).				
Field Min	1	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= FGP <= 10		
Code List	FRICTION RIDGE GENERALIZED POSITION				
Source	INCITS 378				
XML Level 1	biom_1:INCITSMinutiae	Cardinality	0...1		
XML Level 2	biom1:FingerImpressionImage	Cardinality	1...1		
XML Level 3	biom_1:FingerPositionCode	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.135

M1 Friction Ridge Quality Data

Mnemonic	FQD		Conditionality	M
			Status	Active
Description	This mandatory field shall contain the quality of the overall finger minutiae data. There may be a subfield for each algorithm and predictive performance measure. Each subfield shall contain the first information item (quality value / QVU) described in ANSI/NIST ITL. The second two information items are optional for this field. (algorithm vendor identification / QAV and algorithm product identification / QAP). The 2004 version of INCITS 378 had only 1 byte for quality with no second and third information items. The 2009 version of INCITS 378 had all three information items and all three are mandatory in that standard. The 2007 and 2008 versions of ANSI/NIST-ITL mandated the presence of all three information items. However, this version of ANSI/NIST ITL allows the second and third items to be optional, in order to accommodate those users following the 2004 version of INCITS 378.			
Field Min	n/a	Occur Min	0	
Field Max	n/a	Occur Max	1	
Char Types	n/a	Special Chars	n/a	
Format	n/a	Constraints	n/a	
Code List				
Source	INCITS 378			
XML Level 1	biom_1:INCITSMinutiae	Cardinality	0...1	
XML Level 2	biom1:FingerImpressionImage	Cardinality	1...1	
XML Level 3	biom_1:MinutiaeQuality	Cardinality	0...1	
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0 Yes
				DoD EBTS 4.0 Yes

9.135_0

M1 Friction Ridge Quality Data

Subfields: Repeating sets of information items

Mnemonic	FQD_0		Conditionality	M
			Status	New-Active
Description	This mandatory field shall contain the quality of the overall finger minutiae data. There may be a subfield for each algorithm and predictive performance measure. Each subfield shall contain the first information item (quality value / QVU) described in ANSI/NIST ITL. The second two information items are optional for this field. (algorithm vendor identification / QAV and algorithm product identification / QAP). The 2004 version of INCITS 378 had only 1 byte for quality with no second and third information items. The 2009 version of INCITS 378 had all three information items and all three are mandatory in that standard. The 2007 and 2008 versions of ANSI/NIST-ITL mandated the presence of all three information items. However, this version of ANSI/NIST ITL allows the second and third items to be optional, in order to accommodate those users following the 2004 version of INCITS 378.			
Field Min	n/a	Occur Min	1	
Field Max	n/a	Occur Max	1	
Char Types	n/a	Special Chars	n/a	
Format	n/a	Constraints	n/a	
Code List				
Source	INCITS 379			
XML Level 1	biom_1:INCITSMinutiae	Cardinality	0...1	
XML Level 2	biom1:FingerImpressionImage	Cardinality	1...1	
XML Level 3	biom_1:MinutiaeQuality	Cardinality	1..10	
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0 No
				DoD EBTS 4.0 Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.135_1

M1 Friction Ridge Quality Data

Quality Value

Mnemonic	QVU			Conditionality	M↑
				Status	Active
Description	This information item shall contain the integer image quality score between 0 and 100 (inclusive) assigned to the image data by a quality algorithm. Higher values indicate better quality. An entry of "255" shall indicate a failed attempt to calculate a quality score. An entry of "254" shall indicate that no attempt to calculate a quality score was made.				
Field Min	1	Occur Min	0		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= QVU <= 100 or QVU = 254 or QVU = 255; integer		
Code List					
Source	INCITS 378				
XML Level 1	biom_1:INCITSMinutiae	Cardinality	0...1		
XML Level 2	biom1:FingerImpressionImage	Cardinality	1...1		
XML Level 3	biom_1:MinutiaeQuality	Cardinality	1..10		
XML Level 4	biom_1:QualityValue	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

9.135_2

M1 Friction Ridge Quality Data

Algorithm Vendor Identification

Mnemonic	QAV			Conditionality	O
				Status	Active
Description	This information item shall specify the ID of the vendor of the quality algorithm used to calculate the quality score. This 4-digit hex value is assigned by IBIA and expressed as four ASCII characters. The IBIA shall maintain the Vendor Registry of CBEFF Biometric Organizations that will map the value in this field to a registered organization.				
Field Min	4	Occur Min	0		
Field Max	4	Occur Max	1		
Char Types	H	Special Chars	D		
Format	n/a	Constraints	None		
Code List					
Source	INCITS 378				
XML Level 1	biom_1:INCITSMinutiae	Cardinality	0...1		
XML Level 2	biom1:FingerImpressionImage	Cardinality	1...1		
XML Level 3	biom_1:MinutiaeQuality	Cardinality	1..10		
XML Level 4	biom_1:QualityAlgorithmVendorIdentification/nc:IdentificationID	Cardinality	0...1		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.135_3

M1 Friction Ridge Quality Data

Algorithm Product Identification

Mnemonic	QAP		Conditionality	O
			Status	Active
Description	This information item shall specify a numeric product code assigned by the vendor of the quality algorithm, and indicates which of the vendor's algorithms was used in the calculation of the quality score. Description may be registered with the IBIA, but registration is not required. This field contains the ASCII representation of the integer product code and should be within the range of 1 to 65535.			
Field Min	1	Occur Min	1	
Field Max	5	Occur Max	1	
Char Types	N	Special Chars	None	
Format	n/a	Constraints	1 <= QAP <= 65,535	
Code List				
Source	INCITS 378			
XML Level 1	biom_1:INCITSMinutiae	Cardinality	0...1	
XML Level 2	biom1:FingerImpressionImage	Cardinality	1...1	
XML Level 3	biom_1:MinutiaeQuality	Cardinality	1..10	
XML Level 4	biom_1:QualityAlgorithmProductIdentification/nc:IdentificationID	Cardinality	0..1	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0 Yes DoD EBTS 4.0 Yes

9.136

M1 Number of Minutiae

Mnemonic	NOM		Conditionality	M
			Status	Active
Description	This mandatory field shall contain a count of the number of minutiae recorded in this block.			
Field Min	1	Occur Min	1	
Field Max	4	Occur Max	1	
Char Types	N	Special Chars	None	
Format	n/a	Constraints	1 <= NOM <= 9,999; positive integer	
Code List				
Source	INCITS 378			
XML Level 1	biom_1:INCITSMinutiae	Cardinality	0...1	
XML Level 2	biom1:FingerImpressionImage	Cardinality	1...1	
XML Level 3	biom_1:MinutiaeQuality	Cardinality	1..1	
XML Level 4	biom_1:MinutiaeQuantity	Cardinality	1..1	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0 Yes DoD EBTS 4.0 Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.137

M1 Finger Minutiae Data

Mnemonic	FMD			Conditionality	M
				Status	Active
Description	The total number of minutiae information items must agree with the count found in field 9.136 (NOM). The first information item is the minutiae index number, which shall be initialized to "1" and incremented by "1" for each additional minutia in the fingerprint. The second and third information items are the 'x' coordinate and 'y' coordinates of the minutiae in pixel units. The fourth information item is recorded in units of two degrees and shall be nonnegative between 0 and 179, inclusive. The fifth information item is the minutiae type. A value of "0" is used to represent a minutia of type "OTHER", a value of "1" for a ridge ending and a value of "2" for a ridge bifurcation. The sixth information item represents the quality of each minutia. This value shall range from 1 as a minimum to 100 as a maximum. A value of "0" indicates that no quality value is available.				
Field Min	n/a	Occur Min	1		
Field Max	n/a	Occur Max	9999		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	1 <= NOM <= 9,999; positive integer		
Code List					
Source	INCITS 378				
XML Level 1	biom_1:INCITSMinutiae	Cardinality	0..1		
XML Level 2	biom_1:INCITSMinutia	Cardinality	1..9999		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

9.137_1

M1 Finger Minutiae Data

Minutia Index Number [M1-378]

Mnemonic	MAN			Conditionality	M
				Status	Active
Description	This information item is the minutiae index number, which shall be initialized to "1" and incremented by "1" for each additional minutia in the fingerprint.				
Field Min	1	Occur Min	1		
Field Max	4	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	1 <= MAN <= NOM; positive integer		
Code List					
Source	INCITS 378				
XML Level 1	biom_1:INCITSMinutiae	Cardinality	0..1		
XML Level 2	biom_1:INCITSMinutia	Cardinality	1..9999		
XML Level 3	biom_1:MinutiaIdentification/nc:IdentificationID	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.137_2

M1 Finger Minutiae Data

X Coordinate [M1-378]

Mnemonic	MXC			Conditionality	M
				Status	Active
Description	This information item is the 'x' coordinate of the minutiae in pixel units.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	1 <= MXC <= HLL; positive integer		
Code List					
Source	INCITS 378				
XML Level 1	biom_1:INCITSMinutiae	Cardinality	0...1		
XML Level 2	biom_1:INCITSMinutia	Cardinality	1..9999		
XML Level 3	biom_1:INCITSMinutiaLocation	Cardinality	1..1		
XML Level 4	biom_1:PositionHorizontalCoordinateValue	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

9.137_3

M1 Finger Minutiae Data

Y Coordinate [M1-378]

Mnemonic	MYC			Conditionality	M
				Status	Active
Description	This information item is the 'y' coordinates of the minutiae in pixel units.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	1 <= MYC <= VLL; positive integer		
Code List					
Source	INCITS 378				
XML Level 1	biom_1:INCITSMinutiae	Cardinality	0...1		
XML Level 2	biom_1:INCITSMinutia	Cardinality	1..9999		
XML Level 3	biom_1:INCITSMinutiaLocation	Cardinality	1..1		
XML Level 4	biom_1:PositionVerticalCoordinateValue	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.137_4

M1 Finger Minutiae Data

Minutiae Angle [M1-378]

Mnemonic	MAV			Conditionality	M
				Status	Active
Description	This information item is the minutiae angle recorded in units of two degrees. This value shall be nonnegative between 0 and 179.				
Field Min	1	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= MAV <= 179; positive integer		
Code List					
Source	INCITS 378				
XML Level 1	biom_1:INCITSMinutiae	Cardinality	0..1		
XML Level 2	biom_1:INCITSMinutia	Cardinality	1..9999		
XML Level 3	biom_1:INCITSMinutiaLocation	Cardinality	1..1		
XML Level 4	biom_1:ImageLocationThetaAngleMeasure	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

9.137_5

M1 Finger Minutiae Data

Minutiae Type [M1-378]

Mnemonic	M1M			Conditionality	M
				Status	Active
Description	A single numeric character designating the minutiae type within the INCITS M1-378 Features for minutiae record type.				
Field Min	1	Occur Min	1		
Field Max	1	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	MTY = 0, 1 or 2		
Code List	FINGERPRINT INCITS MINUTIAE CODES				
Source	INCITS 378				
XML Level 1	biom_1:INCITSMinutiae	Cardinality	0..1		
XML Level 2	biom_1:INCITSMinutia	Cardinality	1..9999		
XML Level 3	biom_1:INCITSMinutiaLocation	Cardinality	1..1		
XML Level 4	biom_1:INCITSMinutiaCategoryCode	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.137_6

M1 Finger Minutiae Data

Quality of Minutia [M1-378]

Mnemonic	QOM		Conditionality	M
			Status	Active
Description	This information item represents the quality of each minutia. This value shall range from 1 as a minimum to 100 as a maximum. A value of "0" indicates that no quality value is available.			
Field Min	1	Occur Min	1	
Field Max	3	Occur Max	1	
Char Types	N	Special Chars	None	
Format	n/a	Constraints	0 <= QOM <= 100; integer	
Code List				
Source	INCITS 378			
XML Level 1	biom_1:INCITSMinutiae	Cardinality	0...1	
XML Level 2	biom_1:INCITSMinutia	Cardinality	1..9999	
XML Level 3	biom_1:INCITSMinutiaLocation	Cardinality	1..1	
XML Level 4	biom_1:MinutiaQualityValue	Cardinality	1..1	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0 Yes DoD EBTS 4.0 Yes

9.138

M1 Ridge Count Information

Mnemonic	RCI		Conditionality	D
			Status	Active
Description	This optional field shall consist of subfields of three information items. It can only appear if a value of '514' or '515' is entered in CFT of Field 9.126: M1 CBEFF information / CBI. For the first subfield: The first information item of the first subfield shall indicate the ridge count extraction method. A "0" indicates that no assumption shall be made about the method used to extract ridge counts, nor their order in the record. A "1" indicates that for each center minutiae, ridge count data was extracted to the nearest neighboring minutiae in four quadrants, and ridge counts for each center minutiae are listed together. A "2" indicates that for each center minutiae, ridge count data was extracted to the nearest neighboring minutiae in eight octants, and ridge counts for each center minutiae are listed together. The remaining two information items (filler 1 / F11 and filler 2 / F12) of this first repeating subfield shall each contain "0". Subsequent subfields have three information items each: The first information item (center minutiae index / CMI) is a positive integer. The second information item (neighboring minutiae index number / NMN) is a positive integer. It shall not be equal to CMI. The third information (number of ridges crossed / NRC) is a positive integer.			
Field Min	n/a	Occur Min	0	
Field Max	n/a	Occur Max	0	
Char Types	1	Special Chars	n/a	
Format	n/a	Constraints	n/a	
Code List				
Source	INCITS 378			
XML Level 1	biom_1:INCITSMinutiae	Cardinality	0...1	
XML Level 2	biom_1:MinutiaeRidgeCountDetail	Cardinality	0...1	
XML Level 3		Cardinality		
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0 Yes DoD EBTS 4.0 Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.138_0

M1 Ridge Count Information

Subfields: Repeating sets of information items

Mnemonic	RCI_0			Conditionality	M↑
				Status	New-Active
Description	This optional field shall consist of subfields of three information items. It can only appear if a value of '514' or '515' is entered in CFT of Field 9.126: M1 CBEFF information / CBI. For the first subfield: The first information item of the first subfield shall indicate the ridge count extraction method. A "0" indicates that no assumption shall be made about the method used to extract ridge counts, nor their order in the record. A "1" indicates that for each center minutiae, ridge count data was extracted to the nearest neighboring minutiae in four quadrants, and ridge counts for each center minutia are listed together. A "2" indicates that for each center minutiae, ridge count data was extracted to the nearest neighboring minutiae in eight octants, and ridge counts for each center minutia are listed together. The remaining two information items (filler 1 / F1 and filler 2 / F2) of this first repeating subfield shall each contain "0". Subsequent subfields have three information items each: The first information item (center minutia index / CMI) is a positive integer. The second information item (neighboring minutia index number / NMN) is a positive integer. It shall not be equal to CMI. The third information (number of ridges crossed / NRC) is a positive integer.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	79993	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	INCITS 379				
XML Level 1	biom_1:INCITSMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeRidgeCountDetail			Cardinality	0..79993
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.138_1a

M1 Ridge Count Information

Ridge Count Extraction Method

Mnemonic	REM			Conditionality	M↑
				Status	Active
Description	The first information item shall indicate the ridge count extraction method. A "0" indicates that no assumption shall be made about the method used to extract ridge counts, nor their order in the record. A "1" indicates that for each center minutiae, ridge count data was extracted to the nearest neighboring minutiae in four quadrants, and ridge counts for each center minutia are listed together. A "2" indicates that for each center minutiae, ridge count data was extracted to the nearest neighboring minutiae in eight octants, and ridge counts for each center minutia are listed together.				
Field Min	1		Occur Min	1	
Field Max	1		Occur Max	1	
Char Types	N		Special Chars	None	
Format	n/a		Constraints	REM = 0, 1 or 2	
Code List	FINGERPRINT RIDGE COUNT EXTRACTION METHOD CODES				
Source	INCITS 378				
XML Level 1	biom_1:INCITSMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeRidgeCountDetail			Cardinality	0..79993
XML Level 3	biom_1:INCITSRidgeCountAlgorithmCode			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.138_1b

M1 Ridge Count Information

Center Minutia Index Number

Mnemonic	CMI			Conditionality	M↑
				Status	Active
Description	The first information item of subsequent subfields of the Ridge Count Information field is a positive integer.				
Field Min	1	Occur Min	1		
Field Max	4	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	1 <= CMI <= NOM; positive integer		
Code List					
Source	INCITS 378				
XML Level 1	biom_1:INCITSMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeRidgeCountDetail	Cardinality	0..79993		
XML Level 3	biom_1:MinutiaeRidgeCountItem	Cardinality	1..*		
XML Level 4	biom_1:MinutiaIdentification/nc:identificationID	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

9.138_2a

M1 Ridge Count Information

Filler 1

Mnemonic	FI1			Conditionality	M↑
				Status	Active
Description	The remaining two information items (filler 1 / FI1 and filler 2 / FI2) of this first repeating subfield shall each contain "0".				
Field Min	1	Occur Min	1		
Field Max	1	Occur Max	1		
Char Types		Special Chars			
Format	n/a	Constraints			
Code List					
Source	INCITS 378				
XML Level 1	biom_1:INCITSMinutiae	Cardinality			
XML Level 2		Cardinality			
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.138_2b

M1 Ridge Count Information

Neighboring Minutia Index Number

Mnemonic	NMN			Conditionality	M↑
				Status	Active
Description	The second information item of subsequent subfield of the Ridge Count Information field is a positive integer. It shall not be equal to CMI.				
Field Min	1	Occur Min	1		
Field Max	4	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	1 <= NMN <= NOM; positive integer		
Code List					
Source	INCITS 378				
XML Level 1	biom_1:INCITSMinutiae	Cardinality	0...1		
XML Level 2	biom_1:MinutiaeRidgeCountDetail	Cardinality	0..79993		
XML Level 3	biom_1:MinutiaeRidgeCountItem	Cardinality	1...*		
XML Level 4	biom_1:MinutiaReferenceIdentification/nc:IdentificationID	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

9.138_3a

M1 Ridge Count Information

Filler 2

Mnemonic	FI2			Conditionality	M↑
				Status	Active
Description	The remaining two information items (filler 1 / FI1 and filler 2 / FI2) of this first repeating subfield shall each contain "0".				
Field Min	1	Occur Min	1		
Field Max	1	Occur Max	1		
Char Types		Special Chars			
Format	n/a	Constraints			
Code List					
Source	INCITS 378				
XML Level 1	biom_1:INCITSMinutiae	Cardinality			
XML Level 2		Cardinality			
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.138_3b

M1 Ridge Count Information

Number of Ridges Crossed

Mnemonic	NRC			Conditionality	M↑
				Status	Active
Description	The third information item of subsequent subfield of the Ridge Count Information field is a positive integer.				
Field Min	1	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	1 <= NRC <= 99; positive integer		
Code List					
Source	INCITS 378				
XML Level 1	biom_1:INCITSMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeRidgeCountDetail	Cardinality	0..79993		
XML Level 3	biom_1:MinutiaeRidgeCountItem	Cardinality	1..*		
XML Level 4	biom_1:RidgeCountValue	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

9.139

M1 Core Information

Mnemonic	CIN			Conditionality	D
				Status	Active
Description	This optional field shall consist of one subfield for each core present in the original image. It can only appear if a value of '514' or '515' is entered in CFT (Field 9.126_2). Each subfield consists of three information items. The first item ('x' coordinate / XCC) is an integer in pixel units. The second item ('y' coordinate / YCC) is an integer in pixel units. The third information item (angle of the core / ANGC) is recorded in units of two degrees. The value shall be between 0 and 179, inclusive.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	INCITS 378				
XML Level 1	biom_1:INCITSMinutiae	Cardinality	0..1		
XML Level 2	biom_1:FingerprintPatternCoreLocation	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.139_0

M1 Core Information

Subfields: Repeating sets of information items

Mnemonic	CIN_0			Conditionality	M↑
				Status	New-Active
Description	This optional field shall consist of one subfield for each core present in the original image. It can only appear if a value of '514' or '515' is entered in CFT (Field 9.126_2). Each subfield consists of three information items. The first item ('x' coordinate / XCC) is an integer in pixel units. The second item ('y' coordinate / YCC) is an integer in pixel units. The third information item (angle of the core / ANGC) is recorded in units of two degrees. The value shall be between 0 and 179, inclusive.				
Field Min	n/a			Occur Min	0
Field Max	n/a			Occur Max	10
Char Types	n/a			Special Chars	n/a
Format	n/a			Constraints	n/a
Code List					
Source	INCITS 379				
XML Level 1	biom_1:INCITSMinutiae			Cardinality	0..1
XML Level 2	biom_1:FingerprintPatternCoreLocation			Cardinality	0..10
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.139_1

M1 Core Information

X Coordinate [M1 Core]

Mnemonic	XCC			Conditionality	M↑
				Status	Active
Description	The first item ('x' coordinate / XCC) is an integer in pixel units.				
Field Min	1			Occur Min	1
Field Max	5			Occur Max	1
Char Types	N			Special Chars	None
Format	n/a			Constraints	1 <= XCC <= HLL
Code List					
Source	INCITS 378				
XML Level 1	biom_1:INCITSMinutiae			Cardinality	0..1
XML Level 2	biom_1:FingerprintPatternCoreLocation			Cardinality	0..10
XML Level 3	biom_1:PositionHorizontalCoordinateValue			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.139_2

M1 Core Information

Y Coordinate [M1 Core]

Mnemonic	YCC			Conditionality	M↑
				Status	Active
Description	The second item ('y' coordinate / YCC) is an integer in pixel units.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	1 <= YCC <= VLL		
Code List					
Source	INCITS 378				
XML Level 1	biom_1:INCITSMinutiae	Cardinality	0..1		
XML Level 2	biom_1:FingerprintPatternCoreLocation	Cardinality	0..10		
XML Level 3	biom_1:PositionVerticalCoordinateValue	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

9.139_3

M1 Core Information

Angle of the Core

Mnemonic	ANGC			Conditionality	M↑
				Status	Active
Description	The third information item (angle of the core / ANGC) is recorded in units of two degrees. The value shall be between 0 and 179, inclusive.				
Field Min	1	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= ANGC <= 179		
Code List					
Source	INCITS 378				
XML Level 1	biom_1:INCITSMinutiae	Cardinality	0..1		
XML Level 2	biom_1:FingerprintPatternCoreLocation	Cardinality	0..10		
XML Level 3	biom_1:ImageLocationThetaAngleMeasure	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.14

M1 Delta Information

Mnemonic	DIN		Conditionality	D			
			Status	Active			
Description	This optional field shall consist of one subfield for each delta present in the original image. It can only appear if a value of '514' or '515' is entered in CFT (Field 9.126). Each repeating subfield consists of three information items. The first item ('x' coordinate / XCD) is an integer in pixel units. The second item ('y' coordinate / YCD) is an integer in pixel units. The third information item (first angle of the delta / ANG1) is recorded in units of two degrees. The value shall be between 0 and 179, inclusive. This is the angle closest to 90 degrees. (i.e., pointing upwards)						
Field Min	n/a	Occur Min	0				
Field Max	n/a	Occur Max	1				
Char Types	n/a	Special Chars	n/a				
Format	n/a	Constraints	n/a				
Code List							
Source	INCITS 378						
XML Level 1	biom_1:INCITSMinutiae		Cardinality	0..1			
XML Level 2	biom_1:FingerprintPatternDeltaLocation		Cardinality	0..1			
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

9.140_0

M1 Delta Information

Subfields: Repeating sets of information items

Mnemonic	DIN_0		Conditionality	M↑			
			Status	New - Active			
Description	This optional field shall consist of one subfield for each delta present in the original image. It can only appear if a value of '514' or '515' is entered in CFT (Field 9.126). Each repeating subfield consists of three information items. The first item ('x' coordinate / XCD) is an integer in pixel units. The second item ('y' coordinate / YCD) is an integer in pixel units. The third information item (first angle of the delta / ANG1) is recorded in units of two degrees. The value shall be between 0 and 179, inclusive. This is the angle closest to 90 degrees. (i.e., pointing upwards)						
Field Min	n/a	Occur Min	0				
Field Max	n/a	Occur Max	10				
Char Types	n/a	Special Chars	n/a				
Format	n/a	Constraints	n/a				
Code List							
Source	INCITS 379						
XML Level 1	biom_1:INCITSMinutiae		Cardinality	0..1			
XML Level 2	biom_1:FingerprintPatternDeltaLocation		Cardinality	0..10			
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.140_1

M1 Delta Information

X Coordinate [M1 Delta]

Mnemonic	XCD			Conditionality	M↑
				Status	Active
Description	The first item ('x' coordinate / XCD) is an integer in pixel units.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	1 <= XCD <= HLL; positive integer		
Code List					
Source	INCITS 378				
XML Level 1	biom_1:INCITSMinutiae	Cardinality	0..1		
XML Level 2	biom_1:FingerprintPatternDeltaLocation	Cardinality	0..10		
XML Level 3	biom_1:PositionHorizontalCoordinateValue	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

9.140_2

M1 Delta Information

Y Coordinate [M1 Delta]

Mnemonic	YCD			Conditionality	M↑
				Status	Active
Description	The second item ('y' coordinate / YCD) is an integer in pixel units.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	1 <= YCD <= VLL; positive integer		
Code List					
Source	INCITS 378				
XML Level 1	biom_1:INCITSMinutiae	Cardinality	0..1		
XML Level 2	biom_1:FingerprintPatternDeltaLocation	Cardinality	0..10		
XML Level 3	biom_1:PositionVerticalCoordinateValue	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.140_3

M1 Delta Information

First Angle of the Delta

Mnemonic	ANG1			Conditionality	M↑
				Status	Active
Description	The third information item (first angle of the delta / ANG1) is recorded in units of two degrees. The value shall be between 0 and 179, inclusive. This is the angle closest to 90 degrees. (i.e. pointing upwards)				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	3		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= ANG1 <= 179; positive integer		
Code List					
Source	INCITS 378				
XML Level 1	biom_1:INCITSMinutiae	Cardinality	0..1		
XML Level 2	biom_1:FingerprintPatternDeltaLocation	Cardinality	0..10		
XML Level 3	biom_1:ImageLocationThetaAngleMeasure	Cardinality	1..3		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

9.141

M1 Additional Delta Angles

Mnemonic	ADA			Conditionality	D
				Status	Active
Description	This optional field shall only appear if DIN (Field 9.140) is included in this record. This field was added to handle the two additional angle specifications of INCITS 378 while maintaing backward compatibility with the 2007 version of this standard (Traditional encoding). The subfields shall describe the same deltas in the same order as the subfields of Field 9.140: M1 delta information / DIN.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	INCITS 378				
XML Level 1	biom_1:INCITSMinutiae	Cardinality	0..1		
XML Level 2	biom_1:FingerprintPatternDeltaLocation	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.141_0

M1 Additional Delta Angles

Subfields: Repeating sets of information items

Mnemonic	ADA_0			Conditionality	M↑
				Status	New-Active
Description	This optional field shall only appear if DIN (Field 9.140) is included in this record. This field was added to handle the two additional angle specifications of INCITS 378 while maintaining backward compatibility with the 2007 version of this standard (Traditional encoding). The subfields shall describe the same deltas in the same order as the subfields of Field 9.140: M1 delta information / DIN. The first information item (second angle of the delta /ANG2) is the next angle encoded in order of appearance when moving counterclockwise. The second information item (third angle of the delta / ANG3) is the last angle encoded in order of appearance when moving counterclockwise.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	10		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	INCITS 379				
XML Level 1	biom_1:INCITSMinutiae			Cardinality	0..1
XML Level 2	biom_1:FingerprintPatternDeltaLocation			Cardinality	0..10
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.141_1

M1 Additional Delta Angles

Second Angle of the Delta

Mnemonic	ANG2			Conditionality	M↑
				Status	Active
Description	The first information item (second angle of the delta /ANG2) is the next angle encoded in order of appearance when moving counterclockwise.				
Field Min	1	Occur Min	1		
Field Max	3	Occur Max	3		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= ANG2 <= 179; positive integer		
Code List					
Source	INCITS 378				
XML Level 1	biom_1:INCITSMinutiae			Cardinality	0..1
XML Level 2	biom_1:FingerprintPatternDeltaLocation			Cardinality	0..10
XML Level 3	biom_1:ImageLocationThetaAngleMeasure			Cardinality	1..3
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.141_2

M1 Additional Delta Angles

Third Angle of the Delta

Mnemonic	ANG3			Conditionality	M↑
				Status	Active
Description	The second information item (third angle of the delta / ANG3) is the last angle encoded in order of appearance when moving counterclockwise.				
Field Min	1	Occur Min	1		
Field Max	3	Occur Max	3		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= ANG3 <= 179; positive integer		
Code List					
Source	INCITS 378				
XML Level 1	biom_1:INCITSMinutiae	Cardinality	0...1		
XML Level 2	biom_1:FingerprintPatternDeltaLocation	Cardinality	0..10		
XML Level 3	biom_1:ImageLocationThetaAngleMeasure	Cardinality	1..3		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

9.3

Region of Interest

Mnemonic	ROI			Conditionality	M
				Status	Active
Description	The Region of Interest is defined as a rectangle and/or polygon that bounds the area of the original image containing a single friction ridge impression, and separates it from the background and any other friction ridge data present in the image. All EFS features are in relation to the Region of Interest, not to the original image; all coordinates are relative to the top left corner of the ROI. With the exception of Field 9.323: EFS center point of reference / CPR, the X and Y values for an EFS feature may not equal or exceed the width and height of the ROI. The X and Y values for CPR are the only EFS values that may be negative, or greater than the ROI width or height; however, the center point of reference must be within the bounds of the overall image itself. The ROI may be identical to the dimensions of the image. When the ROI is a polygon, the ROI rectangle is simply a bounding box around that polygon: the ROI offset is defined as the minimum of the X and Y coordinates of all ROI vertices, and the ROI width and height are defined as the range (maximum – minimum) of the X and Y coordinates of all ROI vertices. It is permissible for the ROI rectangle to be expanded slightly around the ROI polygon so that its dimensions or offset are evenly divisible by 4 or 8, as long as this does not exceed the bounds of the image itself. This mandatory field defines a rectangle (and an optional polygon) that bounds the region of the image that contains the fingerprint of interest and separates it from the background and any other fingerprints present in the image. Width and height are mandatory. The other items are optional.				
Field Min	n/a	Occur Min	1		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0...1		
XML Level 2	biom_1:FrictionRidgeImageRegionOfInterest	Cardinality	1..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.300_1

Region of Interest

ROI Width

Mnemonic	EWI			Conditionality	M↑
				Status	Active
Description	The first information item (width / EWI) is the integer width of the region of interest in units of 10 micrometers (0.01 mm)				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	n/a		
Format	n/a	Constraints	1 <= EWI <=50000 ; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0...1		
XML Level 2	biom_1:FrictionRidgeImageRegionOfInterest	Cardinality	1..1		
XML Level 3	biom_1:ImageSegmentWidthMeasure	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.300_2

Region of Interest

ROI Height

Mnemonic	EHI			Conditionality	M↑
				Status	Active
Description	The second information item (height / EHI) is the height of the region of interest in units of 10 micrometers (0.01 mm).				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	n/a		
Format	n/a	Constraints	1 <= EHI <=50000 ; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0...1		
XML Level 2	biom_1:FrictionRidgeImageRegionOfInterest	Cardinality	1..1		
XML Level 3	biom_1:ImageSegmentHeightMeasure	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.300_3

Region of Interest

ROI Horizontal Offset

Mnemonic	EHO	Conditionality	0
		Status	Active
Description	The third information item (horizontal offset / EHO) is the horizontal distance in units of 10 micrometers from the left edge of the original image to the left edge of the region of interest. This information item defaults to a value of zero if absent.		
Field Min	1	Occur Min	0
Field Max	5	Occur Max	1
Char Types	N	Special Chars	n/a
Format	n/a	Constraints	0 <= EHO <= 50000 ; non-negative integer
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-9)		
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1
XML Level 2	biom_1:FrictionRidgeImageRegionOfInterest	Cardinality	1..1
XML Level 3	biom_1:ImageSegmentHorizontalOffsetMeasure	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

9.300_4

Region of Interest

ROI Vertical Offset

Mnemonic	EVO	Conditionality	0
		Status	Active
Description	The fourth information item (vertical offset / EVO) is the vertical distance in units of 10 micrometers from the top edge of the original image to the top edge of the region of interest. This information item defaults to a value of zero if absent.		
Field Min	1	Occur Min	0
Field Max	5	Occur Max	1
Char Types	N	Special Chars	n/a
Format	n/a	Constraints	0 <= EVO <= 50000 ; non-negative integer
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-9)		
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1
XML Level 2	biom_1:FrictionRidgeImageRegionOfInterest	Cardinality	1..1
XML Level 3	biom_1:ImageSegmentVerticalOffsetMeasure	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.300_5

Region of Interest

ROI Polygon

Mnemonic	ROP			Conditionality	O
				Status	Active
Description	The fifth information item (ROI Polygon / ROP) contains a polygon (closed path) that further defines the friction ridge area under consideration within the ROI. The format of polygons is described in Section 7.7.12 of the ANSI/NIST-ITL. The vertices of the polygon are relative to the ROI. In Traditional encoding, the two special characters allowed are hyphen and comma. These special characters are not used in XML Encoding.				
Field Min	1186	Occur Min	3		
Field Max	1188	Occur Max	99		
Char Types	NS	Special Chars	Hyphen and Comma		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:FrictionRidgeImageRegionOfInterest	Cardinality	1..1		
XML Level 3	biom_1:ImageSegmentPolygon	Cardinality	0..1		
XML Level 4	biom_1:ImageSegmentVertex/biom_1:ImageLocationHorizontalCoordinateMeasure + biom_1:ImageLocationVerticalCoordinateMeasure (1..1)	Cardinality	3.99		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.301

EFS Orientation

Mnemonic	ORT			Conditionality	O
				Status	Active
Description	This optional field allows the orientation (deviation from upright) and its uncertainty to be specified. If this field is omitted, the direction shall default to 0 (upright) and uncertainty shall default to 15, indicating that the image is rotated 0±15°. If orientation cannot be determined, the uncertainty value shall be set to 180.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:FingerprintImageFingerprintOrientation	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.301_1

EFS Orientation

EFS Orientation Direction

Mnemonic	EOD			Conditionality	M↑
				Status	Active
Description	This information item contains the deviation of the region of interest from upright (fingertip up) in integer degrees. Positive angles are counterclockwise, negative angles are clockwise. A value of "0" indicates an upright direction. Valid values range from "-179" through "180". The allowed special character is the negative sign.				
Field Min	1	Occur Min	1		
Field Max	4	Occur Max	1		
Char Types	NS	Special Chars	Minus Sign		
Format	n/a	Constraints	-179 <= EOD <= 180 ; integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:FingerprintImageFingerprintOrientation			Cardinality	0..1
XML Level 3	biom_1:OrientationAngleValue			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.301_2

EFS Orientation

EFS Orientation Uncertainty

Mnemonic	EUC			Conditionality	O↑
				Status	Active
Description	This information item contains the uncertainty of the orientation direction, in non-negative integer degrees; the resulting orientation is Direction± Uncertainty°. Valid values range from "0" to "180".				
Field Min	1	Occur Min	0		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	n/a		
Format	n/a	Constraints	0 <= EUC <= 180 ; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:FingerprintImageFingerprintOrientation			Cardinality	0..1
XML Level 3	biom_1:OrientationAngleUncertaintyValue			Cardinality	0..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.302

EFS Finger, Palm, Plantar Position

Mnemonic	FPP			Conditionality	M
				Status	Active
Description	This mandatory field shall contain one or more of the possible physical positions that correspond to the region of interest. For example, a region of interest that includes a finger's medial and proximal segment can note those as multiple data entries, with polygons to indicate the locations. For more information about this field, see Annex F F.6.1.3 Field 9.302: EFS finger - palm - plantar position / FPP instructions. This field may contain multiple subfields to designate different friction ridge generalized positions and/or finger segments; polygons are required in this case to delineate the locations of the positions. Polygons may overlap if appropriate.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0...1
XML Level 2	biom_1:MinutiaeFingerLocation or biom_1:MinutiaePalmLocation or biom_1:MinutiaePlantarLocation or biom_1:MinutiaeFrictionRidgeLocation			Cardinality	0...1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.302_0

EFS Finger, Palm, Plantar Position

Subfields: Repeating sets of information items

Mnemonic	FPP_0			Conditionality	M
				Status	New-Active
Description	This mandatory field shall contain one or more of the possible physical positions that correspond to the region of interest. For example, a region of interest that includes a finger's medial and proximal segment can note those as multiple data entries, with polygons to indicate the locations. For more information about this field, see Annex F F.6.1.3 Field 9.302: EFS finger - palm - plantar position / FPP instructions. This field may contain multiple subfields to designate different friction ridge generalized positions and/or finger segments; polygons are required in this case to delineate the locations of the positions. Polygons may overlap if appropriate.				
Field Min	n/a	Occur Min	1		
Field Max	n/a	Occur Max	20		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0...1
XML Level 2	biom_1:MinutiaeFingerLocation or biom_1:MinutiaePalmLocation or biom_1:MinutiaePlantarLocation			Cardinality	1..20
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.302_1

EFS Finger, Palm, Plantar Position

Friction Ridge Generalized Position

Mnemonic	FGP			Conditionality	M↑
				Status	Active
Description	This information item contains the code number corresponding to the known or most probable position shall be taken and entered as a one- or two-character value. The valid codes for FGP in this field are limited to 0 through 10 (inclusive), 16 through 18 (inclusive), 20 through 38 (inclusive) and 81 through 84 (inclusive).				
Field Min	1	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	See Look Up Codes		
Code List	FRICTION RIDGE GENERALIZED POSITION				
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeFingerLocation or biom_1:MinutiaePalmLocation or biom_1:MinutiaePlantarLocation			Cardinality	1..20
XML Level 3	biom_1:FingerPositionCode or biom_1:PalmPositionCode or biom_1:PlantarPositionCode or biom_1:FrictionRidgePositionCode			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.302_2

EFS Finger, Palm, Plantar Position

Finger Segment

Mnemonic	FSM			Conditionality	0
				Status	Active
Description	This information item is optional and only applies to fingerprints in which all or part of the medial or proximal segments (lower joints) are present in the image, in which case the 3-character code is used to indicate the finger segment position.				
Field Min	3	Occur Min	0		
Field Max	3	Occur Max	1		
Char Types	A	Special Chars	None		
Format	n/a	Constraints	See Look Up Codes		
Code List	PRINT POSITION DESCRIPTORS				
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeFingerLocation or biom_1:MinutiaePalmLocation or biom_1:MinutiaePlantarLocation			Cardinality	1..20
XML Level 3	biom_1:SegmentLocationCode			Cardinality	0..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.302_3

EFS Finger, Palm, Plantar Position

Off-Center Fingerprint

Mnemonic	OCF			Conditionality	0
				Status	Active
Description	This information item is optional and only applies to fingerprints in which the impression does not contain the central area of the fingerprint (i.e., the core or a center point of reference), in which case the 1-character codes are used to indicate the off-center position of the fingerprint image. This information item shall be omitted if Field 9.302_1, FGP - Friction Ridge Generalized Position, indicates palm or plantar.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars	None		
Format	n/a	Constraints	See Look Up Codes		
Code List	OFF-CENTER FINGERPRINT CODES				
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeFingerLocation or biom_1:MinutiaePalmLocation or biom_1:MinutiaePlantarLocation			Cardinality	1..20
XML Level 3	biom_1:FingerprintOffCenterCode			Cardinality	0..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.302_4

EFS Finger, Palm, Plantar Position

Segment Polygon

Mnemonic	SGP			Conditionality	0
				Status	Active
Description	This information item is optional and represents a closed path polygon that delineates the area that corresponds to the specified position/segment. In Traditional encoding, the two special characters allowed are hyphen and comma. These special characters are not used in XML Encoding.				
Field Min	1186	Occur Min	3		
Field Max	1188	Occur Max	99		
Char Types	NS	Special Chars	Minus Sign and Comma		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeFingerLocation or biom_1:MinutiaePalmLocation or biom_1:MinutiaePlantarLocation			Cardinality	1..20
XML Level 3	biom_1:ImageSegmentPolygon			Cardinality	0..1
XML Level 4	biom_1:ImageSegmentVertex/biom_1:ImageLocationHorizontalCoordinateMeasure + biom_1:ImageLocationVerticalCoordinateMeasure(1..1)			Cardinality	3..99
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.303

EFS Finger Set Profile

Mnemonic	FSP			Conditionality	0
				Status	Active
Description	This optional numeric field is used to indicate an EFS Profile, which defines the specific set of EFS fields incorporated in a specific transaction. Profiles can be incorporated by reference into the definition of transactions: this decoupling of feature sets from transactions enables different transactions to share a common feature set, aiding in interoperability. If a given ANSI/NIST-ITL transaction is conformant with two or more profiles, the code for each profile is entered in a separate subfield.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	N		Special Chars	None	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:ExtendedFeatureSetProfileIdentification			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.303_0

EFS Finger Set Profile

Mnemonic	FSP_0			Conditionality	M↑
				Status	New-Active
Description	This optional numeric field is used to indicate an EFS Profile, which defines the specific set of EFS fields incorporated in a specific transaction. Profiles can be incorporated by reference into the definition of transactions: this decoupling of feature sets from transactions enables different transactions to share a common feature set, aiding in interoperability. If a given ANSI/NIST-ITL transaction is conformant with two or more profiles, the code for each profile is entered in a separate subfield.				
Field Min	1		Occur Min	0	
Field Max	2		Occur Max	10	
Char Types	N		Special Chars	None	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:ExtendedFeatureSetProfileIdentification/nc:identificationID			Cardinality	0..10
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.307

EFS Pattern Classification

Mnemonic	PAT			Conditionality	D
				Status	Active
Description	This optional field contains fingerprint classification information for the image. This field shall only be used for fingerprints, and shall be omitted for other friction ridge impressions. The field consists of three information items grouped together in a subfield.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:FingerprintPatternClassification			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.307_0

EFS Pattern Classification

Subfields: Repeating sets of information items

Mnemonic	PAT_0			Conditionality	M↑
				Status	New - Active
Description	This optional field contains fingerprint classification information for the image. This field shall only be used for fingerprints, and shall be omitted for other friction ridge impressions. The field consists of three information items grouped together in a subfield.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	8		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:FingerprintPatternClassification			Cardinality	0..8
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.307_1

EFS Pattern Classification

General Class

Mnemonic	GCF			Conditionality	M↑
				Status	Active
Description	This information item is the general set of pattern classifications (arch, whorl, left & right loop) used by most current automated systems. This is a two character value selected from the specified codes.				
Field Min	2	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	A	Special Chars	n/a		
Format	n/a	Constraints	See Look Up Codes		
Code List	FINGERPRINT CJIS PATTERN CLASSIFICATION CODES				
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0...1		
XML Level 2	biom_1:FingerprintPatternGeneralClassCode	Cardinality	1..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.307_2

EFS Pattern Classification

Subclass

Mnemonic	SUB			Conditionality	D
				Status	Active
Description	This information item is the detailed sub-classification of arches and whorls that may optionally be provided by a human examiner or automated system. This information item shall only be included for arches or whorls, and only if the sub-classification can be determined precisely. This is a two character value selected from the specified codes.				
Field Min	2	Occur Min	0		
Field Max	2	Occur Max	1		
Char Types	A	Special Chars	n/a		
Format	n/a	Constraints	See Look Up Codes		
Code List	FINGERPRINT CLASSIFICATION				
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0...1		
XML Level 2	biom_1:FingerprintPatternSubClassCode	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.307_3

EFS Pattern Classification

Whorl-Delta Relationship

Mnemonic	WDR	Conditionality	D
		Status	Active
Description	This information item may optionally be used by a human examiner or automated system to provide the relationship between the deltas in a whorl. This information item shall only be included for whorls if the subclass is known, and only if the whorl delta relationship can be determined precisely.		
Field Min	1	Occur Min	0
Field Max	1	Occur Max	1
Char Types	A	Special Chars	n/a
Format	n/a	Constraints	See Look Up Codes
Code List	WHORL-DELTA RELATIONSHIP CODES		
Source	ANSI/NIST ITL 1-2013 (Type-9)		
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0...1
XML Level 2	biom_1:FingerprintPatternWhorlDeltaRelationshipCode	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

9.308

EFS Ridge Quality Map

Mnemonic	RQM	Conditionality	O
		Status	Active
Description	Local friction ridge quality (as defined in the Ridge Quality Map) is an assessment of confidence in small local areas within an image. The local quality map is used to define the confidence in all other features, and therefore is key information. In addition, when the quality map indicates a high-quality region in which features are not marked, that information can be used as “negative features” or definitive absence of features, which can be used for exclusion. For every cell in a grid superimposed on the Region of Interest, this optional field notes the local ridge quality of the friction ridge detail within that cell. Local ridge quality defines clarity in terms of the ability to discern detail in a given location. The quality of each cell will be represented with a local quality value 0 through 5 representing the quality of ridge detail in that cell, as specified in Table 33. If a region of interest is defined, cells outside of the ROI polygon shall be set to a local quality value of 0 (black). This optional field is comprised of a repeating set of values. The number of subfields corresponds to the number of cells in a column of the image. Each row value is encoded as shown in Table 34. See Field 9.309: EFS ridge quality map format / RQF for the definition of the grid size and data representation.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	n/a
Format	n/a	Constraints	See Look Up Codes
Code List	Ridge Quality Map Codes		
Source	ANSI/NIST ITL 1-2013 (Type-9)		
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0...1
XML Level 2	biom_1:MinutiaeRidgeQualityMapRowText	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.308_0

EFS Ridge Quality Map

Subfields: Repeating sets of information items

Mnemonic	RQM_0	Conditionality	M↑
		Status	New-Active
Description	Local friction ridge quality (as defined in the Ridge Quality Map) is an assessment of confidence in small local areas within an image. The local quality map is used to define the confidence in all other features, and therefore is key information. In addition, when the quality map indicates a high-quality region in which features are not marked, that information can be used as “negative features” or definitive absence of features, which can be used for exclusion. For every cell in a grid superimposed on the Region of Interest, this optional field notes the local ridge quality of the friction ridge detail within that cell. Local ridge quality defines clarity in terms of the ability to discern detail in a given location. The quality of each cell will be represented with a local quality value 0 through 5 representing the quality of ridge detail in that cell, as specified in Table 33. If a region of interest is defined, cells outside of the ROI polygon shall be set to a local quality value of 0 (black). This optional field is comprised of a repeating set of values. The number of subfields corresponds to the number of cells in a column of the image. Each row value is encoded as shown in Table 34. See Field 9.309: EFS ridge quality map format / RQF for the definition of the grid size and data representation.		
Field Min	1	Occur Min	0
Field Max	50000	Occur Max	Round Up (EHI ÷ GSZ)
Char Types	H	Special Chars	n/a
Format	n/a	Constraints	See Look Up Codes
Code List	Ridge Quality Map Codes		
Source	ANSI/NIST ITL 1-2013 (Type-9)		
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1
XML Level 2	biom_1:MinutiaeRidgeQualityMap	Cardinality	0..*
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

9.309

Ridge Quality Map Format

Mnemonic	RQF	Conditionality	D
		Status	Active
Description	This optional field defines the grid size or data representation format used in Field 9.308: EFS ridge quality/confidence map / RQM. Its use is mandatory if that field is present.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	n/a
Format	n/a	Constraints	n/a
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-9)		
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1
XML Level 2	biom_1:MinutiaeRidgeQualityMap	Cardinality	0..*
XML Level 3	biom_1:MinutiaeRidgeQualityMap	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.309_1

Ridge Quality Map Format

Grid Size

Mnemonic	GSZ			Conditionality	M↑
				Status	Active
Description	This information item shall be used to define grid sizes (both the horizontal and vertical dimensions of a single cell in the grid): valid settings range from "1" (0.01 mm) through "41" (0.41 mm). The recommended grid size is 0.20mm (0.008") – note this is 4 pixels at 500 ppi, or 8 pixels at 1000 ppi.				
Field Min	1	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	n/a		
Format	n/a	Constraints	1 <= GSZ <= 41; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeRidgeQualityMap			Cardinality	0..*
XML Level 3	biom_1:MinutiaeRidgeQualityMapCellSizeValue			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.309_2

Ridge Quality Map Format

Ridge Quality Data Format

Mnemonic	RDF			Conditionality	M↑
				Status	Active
Description	This information item defines the format used in Field 9.308. For all formats: The first cell starts at the top left corner of the Region of Interest, with cells in order left to right. All of the quality values for each row are stored in one repeating subfield. The subfields are ordered from top to bottom. If the width and/or height of the Region of Interest are not evenly divisible by the Grid Size, partial cells shall be included at the right and/or bottom of the ridge flow map.				
Field Min	3	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	A	Special Chars	n/a		
Format	n/a	Constraints	RDF = UNC or RLE; See Look Up Codes		
Code List	RIDGE QUALITY DATA FORMAT CODES				
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeRidgeQualityMap			Cardinality	0..*
XML Level 3	biom_1:MinutiaeRidgeQualityMapFormatCode			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.31

EFS Ridge Flow Map

Mnemonic	RFM		Conditionality	0			
			Status	Active			
Description	<p>This optional field contains the direction of friction ridges at sampling points throughout the region of interest. The sampling frequency is optionally defined in Field 9.311: RFF, and otherwise defaults to 0.41 mm in uncompressed format. The first sampling point in the image is the top left-most point in the region of interest. The same sampling frequency is used both horizontally and vertically. Values shall be included for all sampling points in the region of interest, even if the sampling points are at the edge of the region of interest. For each sampling point, angles shall be reported in integer degrees, with 0 degrees to the right (horizontal), increasing counterclockwise to a maximum value of 179° (since 180°=0°). Undefined angles are recorded in Field 9.311: EFS ridge flow map format / RFF. Each subfield corresponds to one row of the map in order from top to bottom. The area used for determining direction (window size) may be larger or smaller than the sampling frequency. Different window sizes may be used within a single image, at the discretion of the implementer. For example, an implementer may choose to use a uniform window size except in areas of high curvature, in which a smaller window size may be used.</p>						
Field Min	n/a	Occur Min	0				
Field Max	n/a	Occur Max	1				
Char Types	Base 64	Special Chars	n/a				
Format	n/a	Constraints	See Look Up Codes				
Code List	EFS RIDGE FLOW MAP CODES						
Source	ANSI/NIST ITL 1-2013 (Type-9)						
XML Level 1	biom_1:ExtendedFeatureSetMinutiae		Cardinality	0...1			
XML Level 2	biom_1:MinutiaeRidgeFlowMapRowText		Cardinality	0...1			
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.310_0

EFS Ridge Flow Map

Subfields: Repeating sets of information items

Mnemonic	RFM_0		Conditionality	M↑	
			Status	New - Active	
Description	This optional field contains the direction of friction ridges at sampling points throughout the region of interest. The sampling frequency is optionally defined in Field 9.311: RFF, and otherwise defaults to 0.41 mm in uncompressed format. The first sampling point in the image is the top left-most point in the region of interest. The same sampling frequency is used both horizontally and vertically. Values shall be included for all sampling points in the region of interest, even if the sampling points are at the edge of the region of interest. For each sampling point, angles shall be reported in integer degrees, with 0 degrees to the right (horizontal), increasing counterclockwise to a maximum value of 179° (since 180°=0°). Undefined angles are recorded in Field 9.311: EFS ridge flow map format / RFF. Each subfield corresponds to one row of the map in order from top to bottom. The area used for determining direction (window size) may be larger or smaller than the sampling frequency. Different window sizes may be used within a single image, at the discretion of the implementer. For example, an implementer may choose to use a uniform window size except in areas of high curvature, in which a smaller window size may be used.				
Field Min	1		Occur Min	1	
Field Max	100000		Occur Max	*	
Char Types	Base 65		Special Chars	n/a	
Format	n/a		Constraints	See Look Up Codes	
Code List	EFS RIDGE FLOW MAP CODES				
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae		Cardinality	0...1	
XML Level 2	biom_1:MinutiaeRidgeFlowMap		Cardinality	1..*	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.311

EFS Ridge Flow Map Format

Mnemonic	RFF		Conditionality	O	
			Status	Active	
Description	This optional field permits setting the sampling frequency or data representation format used in the Field 9.310: RFM to values other than the defaults. Its use is conditional on the presence of Field 9.310.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae		Cardinality	0...1	
XML Level 2	biom_1:MinutiaeRidgeFlowMap		Cardinality	1..*	
XML Level 3	biom_1:MinutiaeRidgeFlowMap		Cardinality	0..1	
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.311_1

EFS Ridge Flow Map Format

Sampling Frequency

Mnemonic	SFQ	Conditionality	M↑
		Status	Active
Description	This information item is set by default to 0.41 mm (0.016"). This information item may be used to define higher resolution sampling frequencies than the default: valid settings range from "1" (0.01 mm) through "41" (0.41 mm), inclusive.		
Field Min	1	Occur Min	1
Field Max	2	Occur Max	1
Char Types	N	Special Chars	n/a
Format	n/a	Constraints	1 <= SFQ <= 41; positive integer
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-9)		
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1
XML Level 2	biom_1:MinutiaeRidgeFlowMap	Cardinality	1..*
XML Level 3	biom_1:MinutiaeRidgeFlowMapSamplingFrequencyValue	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

9.311_2

EFS Ridge Flow Map Format

Ridge Flow Data Format

Mnemonic	RDF	Conditionality	M↑
		Status	Active
Description	This information item defines the format used in the Ridge Flow Map field. The default is the uncompressed ("UNC") format		
Field Min	3	Occur Min	1
Field Max	3	Occur Max	1
Char Types	AN	Special Chars	n/a
Format	n/a	Constraints	RDF = UNC or B64. See Look Up Codes
Code List	EFS RIDGE WAVELENGTH MAP DATA FORMAT CODES		
Source	ANSI/NIST ITL 1-2013 (Type-9)		
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1
XML Level 2	biom_1:MinutiaeRidgeFlowMap	Cardinality	1..*
XML Level 3	biom_1:MinutiaeRidgeFlowMapFormatCode	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.312

EFS Ridge Wavelength Map

Mnemonic	RWM	Conditionality	0
		Status	Active
Description	<p>This optional field contains the peak-to-peak distance between ridges at various sampling points throughout the region of interest. The sampling frequency is optionally defined in Field 9.313: RWF, and otherwise defaults to 0.41 mm in uncompressed format. The first sampling point in the image is the top left-most point. The same sampling frequency is used both horizontally and vertically. Values shall be included for all sampling points in the image, even if the sampling points are at the edge of the image. For each sampling point in the Region of Interest, distances between ridge peaks, measured perpendicular to ridge flow, shall be reported in 2-character decimal format using units of 10 micrometers (0.01 mm). The size of the area around the sampling point (window size) used to determine measurements is left to the discretion of the implementer, and may vary within an image. Unknown values shall be set to "XX". Valid values are therefore "01" (0.01 mm) through "99" (0.99 mm or greater). (In practice, the actual stored values are likely to be "30" to "70" in most cases (0.3 – 0.7 mm). The 2-character decimal wavelength values for each sampling point are concatenated left to right for all sampling points in a row. Each subfield corresponds to one row of the map, in order from top to bottom. The number of characters in one subfield is twice the number of sampling points in one row.</p>		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	n/a
Format	n/a	Constraints	String containng 2-digit positive integers or XX characters
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-9)		
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0...1
XML Level 2	biom_1:MinutiaeRidgeWavelengthMapRowText	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes

9.312_0

EFS Ridge Wavelength Map

Subfields: Repeating sets of information items

Mnemonic	RWM_0	Conditionality	M↑
		Status	New - Active
Description	This optional field contains the peak-to-peak distance between ridges at various sampling points throughout the region of interest. The sampling frequency is optionally defined in Field 9.313: RWF, and otherwise defaults to 0.41 mm in uncompressed format. The first sampling point in the image is the top left-most point. The same sampling frequency is used both horizontally and vertically. Values shall be included for all sampling points in the image, even if the sampling points are at the edge of the image. For each sampling point in the Region of Interest, distances between ridge peaks, measured perpendicular to ridge flow, shall be reported in 2-character decimal format using units of 10 micrometers (0.01 mm). The size of the area around the sampling point (window size) used to determine measurements is left to the discretion of the implementer, and may vary within an image. Unknown values shall be set to "XX". Valid values are therefore "01" (0.01 mm) through "99" (0.99 mm or greater). (In practice, the actual stored values are likely to be "30" to "70" in most cases (0.3 – 0.7 mm). The 2-character decimal wavelength values for each sampling point are concatenated left to right for all sampling points in a row. Each subfield corresponds to one row of the map, in order from top to bottom. The number of characters in one subfield is twice the number of sampling points in one row.		
Field Min	1	Occur Min	0
Field Max	100000	Occur Max	1
Char Types	AN	Special Chars	n/a
Format	n/a	Constraints	String containng 2-digit positive integers or XX characters
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-9)		
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0...1
XML Level 2	biom_1:MinutiaeRidgeWavelengthMap	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

9.313

EFS Ridge Wavelength Map Format

Mnemonic	RWF	Conditionality	O
		Status	Active
Description	This field permits setting the sampling frequency or data representation format used in Field 9.312: EFS ridge wavelength map / RWM to values other than the defaults, and is conditional on the presence of Field 9.312.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	n/a
Format	n/a	Constraints	n/a
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-9)		
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0...1
XML Level 2	biom_1:MinutiaeRidgeWavelengthMap	Cardinality	0...1
XML Level 3	biom_1:MinutiaeRidgeWavelengthMap	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.313_1

EFS Ridge Wavelength Map Format

Sampling Frequency

Mnemonic	FWS	Conditionality	M↑
		Status	Active
Description	This information item is set by default to 0.41 mm (0.016"). This information item may be used to define higher resolution sampling frequencies than the default: valid settings range from "1" (0.01 mm) through "41" (0.41 mm), inclusive.		
Field Min	1	Occur Min	1
Field Max	2	Occur Max	1
Char Types	N	Special Chars	n/a
Format	n/a	Constraints	1 <= FWS <= 41; positive integer
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-9)		
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1
XML Level 2	biom_1:MinutiaeRidgeWavelengthMap	Cardinality	0..1
XML Level 3	biom_1:MinutiaeRidgeWavelengthMapSamplingFrequencyValue	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

9.313_2

EFS Ridge Wavelength Map Format

Data Format

Mnemonic	FDF	Conditionality	M↑
		Status	Active
Description	This information item is optional and it defines the format used in Field 9.312. The default (and currently the only setting) is the uncompressed ("UNC") format.		
Field Min	3	Occur Min	1
Field Max	3	Occur Max	1
Char Types	A	Special Chars	n/a
Format	n/a	Constraints	FDF = UNC
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-9)		
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1
XML Level 2	biom_1:MinutiaeRidgeWavelengthMap	Cardinality	0..1
XML Level 3	biom_1:MinutiaeRidgeWavelengthMapFormatCode	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.314

EFS Tonal Reversal

Mnemonic	TRV	Conditionality	O
		Status	Active
Description	Ridges in friction ridge images are generally represented as dark areas, with valleys as light areas. This field indicates whether the entire image is reversed tonally (black-for-white). If all or part of the image is reversed tonally, this 1-character optional field is set to the appropriate value from Table 36. Otherwise this field is omitted. Partial tonal inversion can occur in different ways. If definable portions of the image are negative, Field 9.357: EFS local quality issues / LQI can be used to define the specific tonally reversed areas. Note that in some cases, the tonal reversal is so mixed that only portions of individual ridges are reversed, making it impractical or impossible to define the tonally reversed areas. When this field is set, the image in the Type-13 record shall be left as it was originally received (i.e., tonally reversed): setting this field and reversing the image when saving will result in inconsistent data. When this field is set, a software user interface may display the tonally corrected image, but save the image as originally received with this field set.		
Field Min	1	Occur Min	0
Field Max	1	Occur Max	1
Char Types	A	Special Chars	n/a
Format	n/a	Constraints	TRV = N, P, or U; See Look Up Codes
Code List	EFS TONAL REVERSAL CODES		
Source	ANSI/NIST ITL 1-2013 (Type-9)		
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1
XML Level 2	biom_1:FrictionRidgeImageTonalReversalCode	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

9.315

EFS Possible Lateral Reversal

Mnemonic	PLR	Conditionality	O
		Status	Active
Description	This field indicates if the original image is or may be laterally reversed (i.e., flipped leftright). In many cases, an examiner cannot tell the correct lateral direction of the image, such as latents on tape that has been closed on itself, or latents that transferred to the substrate/surface. If the image is or may be laterally reversed, this 1-character optional field is set to the appropriate value from Table 37 otherwise, this field is to be omitted. When this field is set to L (Image is known to be laterally reversed), the image in the associated Type-13 record shall be left as it was originally received (i.e., laterally reversed): setting this field and reversing the image when saving will result in inconsistent data. When this field is set a software user interface may display the laterally corrected image, but save the image as received with this field set. When this field is set to U (Image may be laterally reversed), it is incumbent on the recipient (software system or examiner) to search/compare the impression and features both as presented and flipped left-right.		
Field Min	1	Occur Min	0
Field Max	1	Occur Max	1
Char Types	A	Special Chars	n/a
Format	n/a	Constraints	PLR = L, U; See Look Up Codes
Code List	EFS POSSIBLE LATERAL REVERSAL CODES		
Source	ANSI/NIST ITL 1-2013 (Type-9)		
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1
XML Level 2	biom_1:FrictionRidgeImageLateralReversalCode	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

9.316

EFS Friction Ridge Quality Metric

Mnemonic	FQM			Conditionality	0
				Status	Active
Description	This optional field specifies one or more different metrics of friction ridge quality for the friction ridge impression corresponding to this record, as delimited by the region of interest.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:ImageQuality			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.316_0

EFS Friction Ridge Quality Metric

Subfields: Repeating sets of information items

Mnemonic	FQM_0			Conditionality	M↑
				Status	New-Active
Description	This optional field specifies one or more different metrics of friction ridge quality for the friction ridge impression corresponding to this record, as delimited by the region of interest.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	10		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:ImageQuality			Cardinality	0..10
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.316_1

EFS Friction Ridge Quality Metric

Quality Value

Mnemonic	QVU			Conditionality	M↑
				Status	Active
Description	This information item shall contain the integer image quality score between 0 and 100 (inclusive) assigned to the image data by a quality algorithm. Higher values indicate better quality. An entry of "255" shall indicate a failed attempt to calculate a quality score. An entry of "254" shall indicate that no attempt to calculate a quality score was made.				
Field Min	1	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	n/a		
Format	n/a	Constraints	0 <= QVU <= 100 or QVU = 254 or QVU = 255; integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:ImageQuality			Cardinality	0..10
XML Level 3	biom_1:QualityAlgorithmProductIdentification/nc:IdentificationID			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.316_2

EFS Friction Ridge Quality Metric

Algorithm Vendor Identification

Mnemonic	QAV			Conditionality	M↑
				Status	Active
Description	This information item shall specify the ID of the vendor of the quality algorithm used to calculate the quality score. This 4-digit hex value is assigned by IBIA and expressed as four ASCII characters. The IBIA shall maintain the Vendor Registry of CBEFF Biometric Organizations that will map the value in this field to a registered organization.				
Field Min	4	Occur Min	1		
Field Max	4	Occur Max	1		
Char Types	H	Special Chars	n/a		
Format	n/a	Constraints	000 <= QAV <= FFFF		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:ImageQuality			Cardinality	0..10
XML Level 3	biom_1:QualityValue			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.316_3

EFS Friction Ridge Quality Metric

Algorithm Product Identification

Mnemonic	QAP			Conditionality	M↑
				Status	Active
Description	This information item shall specify a numeric product code assigned by the vendor of the quality algorithm, and indicates which of the vendor's algorithms was used in the calculation of the quality score. This field contains the ASCII representation of the integer product code and should be within the range 1 to 65535.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	n/a		
Format	n/a	Constraints	1 <= QAP <= 65,535; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:ImageQuality			Cardinality	0..10
XML Level 3	biom_1:QualityAlgorithmVendorIdentification/nc:IdentificationID			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.317

EFS Possible Growth or Shrinkage

Mnemonic	PGS			Conditionality	O
				Status	Active
Description	This optional field is only used in the unusual circumstance that the friction ridge impression is believed to have changed size or scale from potential comparisons. This provides for handling of images from deceased subjects with desiccated skin, or with swollen skin due to water exposure. This also provides for handling of overall growth of subjects between capture, such as in comparing an adult's fingerprints with those taken as a child. In these cases the size of ridges and distances between ridges change to a greater extent than would ordinarily be assumed in comparisons; this field acts as a flag to indicate that greater than ordinary dimensional variation should be expected in performing subsequent comparisons. This field is to be omitted unless there is reason to believe that growth or shrinkage may have occurred.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeGrowthOrShrinkage			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-9 Minutiae Data Record (Extended Feature Set)

Page 388 of 1037

9.317_1

EFS Possible Growth or Shrinkage

Growth or Shrinkage Type

Mnemonic	TGS			Conditionality	M↑
				Status	Active
Description	The first information item is one character. See look up codes for valid values.				
Field Min	1	Occur Min	1		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars	n/a		
Format	n/a	Constraints	TGS = G, S, or B; See Look Up Codes		
Code List	EFS POSSIBLE GROWTH OR SHRINKAGE TYPE CODES				
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeGrowthOrShrinkage	Cardinality	0..1		
XML Level 3	biom_1:MinutiaeGrowthOrShrinkageCode	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.317_2

EFS Possible Growth or Shrinkage

Growth or Shrinkage Comment

Mnemonic	CGS			Conditionality	O↑
				Status	Active
Description	This information item contains optional text describing the rationale for believing that growth or shrinkage may have occurred.				
Field Min	1	Occur Min	0		
Field Max	1000	Occur Max	1		
Char Types	U	Special Chars	n/a		
Format	n/a	Constraints	none		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeGrowthOrShrinkage	Cardinality	0..1		
XML Level 3	biom_1:MinutiaeCommentText	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.32

EFS Cores

Mnemonic	COR			Conditionality	D
				Status	Active
Description	<p>A core is located at the focus of the innermost recurving ridge line of a ridge pattern: if the ridge is viewed as a section of a circle, the core is the center of that circle; if the ridge is viewed as an ellipse or parabola, the core is the focal point of that curve. Note that the core is not on the innermost recurving ridgeline itself. The direction of the core is away from the center of the curve. The core or cores of a fingerprint are defined for all pattern classifications other than plain arches, as shown in Table 39. Cores may be marked on tented arches if an innermost recurving ridge is present above the delta, so that each side of the recurving ridge extends to either side of the delta. Plain or central pocket loop whorls will only have one core if the innermost recurving ridge is circular, or two cores if elliptical. A circular whorl only has one core and does not have a defined direction. Accidentals may have any number of cores. If one or more cores are present and the feature set is from a fingerprint, Field 9.307: EFS pattern classification / PAT should be defined. Note that this does not mean that the classification has to be known definitively, but must at least be known to the extent of excluding plain arches. When no cores are present, this field shall not be used. For palm prints or other non-fingerprint friction ridge images, any number of core-like patterns may be defined using this field if such structures are present. Each core is defined in a separate subfield.</p>				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeCore			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.320_0

EFS Cores

Subfields: Repeating sets of information items

Mnemonic	COR_0			Conditionality	M↑
				Status	New-Active
Description	A core is located at the focus of the innermost recurving ridge line of a ridge pattern: if the ridge is viewed as a section of a circle, the core is the center of that circle; if the ridge is viewed as an ellipse or parabola, the core is the focal point of that curve. Note that the core is not on the innermost recurving ridgeline itself. The direction of the core is away from the center of the curve. The core or cores of a fingerprint are defined for all pattern classifications other than plain arches, as shown in Table 39. Cores may be marked on tented arches if an innermost recurving ridge is present above the delta, so that each side of the recurving ridge extends to either side of the delta. Plain or central pocket loop whorls will only have one core if the innermost recurving ridge is circular, or two cores if elliptical. A circular whorl only has one core and does not have a defined direction. Accidentals may have any number of cores. If one or more cores are present and the feature set is from a fingerprint, Field 9.307: EFS pattern classification / PAT should be defined. Note that this does not mean that the classification has to be known definitively, but must at least be known to the extent of excluding plain arches. When no cores are present, this field shall not be used. For palm prints or other non-fingerprint friction ridge images, any number of core-like patterns may be defined using this field if such structures are present. Each core is defined in a separate subfield.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	*		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0...1
XML Level 2	biom_1:MinutiaeCore			Cardinality	0..*
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.320_1

EFS Cores

X Coordinate

Mnemonic	CXC			Conditionality	M↑
				Status	Active
Description	This information item shall be expressed in integer units of 10 micrometers (0.01mm).				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	n/a		
Format	n/a	Constraints	0 <= CXC < EW1; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0...1
XML Level 2	biom_1:MinutiaeCore			Cardinality	0..*
XML Level 3	biom_1:ImageLocationHorizontalCoordinateMeasure			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.320_2

EFS Cores

Y Coordinate

Mnemonic	CYC			Conditionality	M↑
				Status	Active
Description	This information item shall be expressed in integer units of 10 micrometers (0.01mm).				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	n/a		
Format	n/a	Constraints	0 <= CYC <EHI; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0...1		
XML Level 2	biom_1:MinutiaeCore	Cardinality	0..*		
XML Level 3	biom_1:ImageLocationVerticalCoordinateMeasure	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.320_3

EFS Cores

Direction

Mnemonic	CDI			Conditionality	O↑
				Status	Active
Description	This information item is optional and shall be set to the average tangent direction of the two closest ridges as measured 1.63 mm (0.064 inches) from the focal point. This is approximately the same as the direction of the directrix of the best fitting parabola. The direction shall be omitted (left empty) for circular whorls, or if the direction is unknown.				
Field Min	1	Occur Min	0		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	n/a		
Format	n/a	Constraints	0 <= CDI <= 359; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0...1		
XML Level 2	biom_1:MinutiaeCore	Cardinality	0..*		
XML Level 3	biom_1:MinutiaeCoreDirectionMeasure	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.320_4

EFS Cores

Radius of Position Uncertainty

Mnemonic	RPU			Conditionality	O↑
				Status	Active
Description	This information item defines the radius of a circle centered at the location (X,Y) of the core; the circle is sized to include the area of other possible locations of the core, if the precise location cannot be determined (such as due to poor clarity). If the location is known precisely, the radius of position uncertainty may be omitted or set to 0. The radius of uncertainty is measured in integer units of 10 micrometers(0.01 mm), and may overlap the edge of the image.				
Field Min	1	Occur Min	0		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	n/a		
Format	n/a	Constraints	0 <= RPU <= 999; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeCore	Cardinality	0..*		
XML Level 3	biom_1:ImageLocationUncertaintyRadiusMeasure	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.320_5

EFS Cores

Direction Uncertainty

Mnemonic	DUY			Conditionality	O↑
				Status	Active
Description	This information item is optional. It contains the uncertainty of the direction of the core, in non-negative integer degrees. Valid values range from "0" to "180": a value of "0" (default) indicates a certain direction, while a value of "180" indicates an unknown orientation.				
Field Min	1	Occur Min	0		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	n/a		
Format	n/a	Constraints	0 <= DUY <= 180; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeCore	Cardinality	0..*		
XML Level 3	biom_1:MinutiaeCoreDirectionUncertaintyValue	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.321

EFS Deltas

Mnemonic	DEL			Conditionality	D
				Status	Active
Description	For fingerprints, one or more deltas are defined for all pattern classifications other than plain arches (see look up codes). For palm prints or other non-fingerprint friction ridge images, any number of delta-like patterns may be defined using this field if such structures are present. Each delta is defined in a separate subfield. When no deltas are present, this field shall not be used.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeDelta			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.321_0

EFS Deltas

Subfields: Repeating sets of information items

Mnemonic	DEL_0			Conditionality	M↑
				Status	New - Active
Description	For fingerprints, one or more deltas are defined for all pattern classifications other than plain arches (see look up codes). For palm prints or other non-fingerprint friction ridge images, any number of delta-like patterns may be defined using this field if such structures are present. Each delta is defined in a separate subfield. When no deltas are present, this field shall not be used.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	*	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeDelta			Cardinality	0..*
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.321_1

EFS Deltas

X Coordinate

Mnemonic	DXC			Conditionality	M↑
				Status	Active
Description	This information item shall be expressed in integer units of 10 micrometers (0.01mm) and is mandatory.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	n/a		
Format	n/a	Constraints	0 <= DXC < EWI; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeDelta			Cardinality	0..*
XML Level 3	biom_1:ImageLocationHorizontalCoordinateMeasure			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.321_2

EFS Deltas

Y Coordinate

Mnemonic	DYC			Conditionality	M↑
				Status	Active
Description	This information item shall be expressed in integer units of 10 micrometers (0.01mm) and is mandatory.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	n/a		
Format	n/a	Constraints	0 <= DYC < EHI; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeDelta			Cardinality	0..*
XML Level 3	biom_1:ImageLocationVerticalCoordinateMeasure			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-9 Minutiae Data Record (Extended Feature Set)

Page 395 of 1037

9.321_3

EFS Deltas

Direction Up

Mnemonic	DUP			Conditionality	0↑		
				Status	Active		
Description	This information item is optional and is expressed in degrees counterclockwise from the right.						
Field Min	1			Occur Min	0		
Field Max	3			Occur Max	1		
Char Types	N			Special Chars	n/a		
Format	n/a			Constraints	0 <= DUP <= 359; non-negative integer		
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-9)						
XML Level 1	biom_1:ExtendedFeatureSetMinutiae				Cardinality	0..1	
XML Level 2	biom_1:MinutiaeDelta				Cardinality	0..*	
XML Level 3	biom_1:MinutiaeDeltaDirectionUpMeasure				Cardinality	0..1	
XML Level 4					Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

9.321_4

EFS Deltas

Direction Left

Mnemonic	DLF			Conditionality	0↑		
				Status	Active		
Description	This information item is optional and is expressed in degrees counterclockwise from the right.						
Field Min	1			Occur Min	0		
Field Max	3			Occur Max	1		
Char Types	N			Special Chars	n/a		
Format	n/a			Constraints	0 <= DLF <= 359; non-negative integer		
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-9)						
XML Level 1	biom_1:ExtendedFeatureSetMinutiae				Cardinality	0..1	
XML Level 2	biom_1:MinutiaeDelta				Cardinality	0..*	
XML Level 3	biom_1:MinutiaeDeltaDirectionLeftMeasure				Cardinality	0..1	
XML Level 4					Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-9 Minutiae Data Record (Extended Feature Set)

Page 396 of 1037

9.321_5

EFS Deltas

Direction Right

Mnemonic	DRT			Conditionality	0↑		
				Status	Active		
Description	This information item is optional and is expressed in degrees counterclockwise from the right.						
Field Min	1			Occur Min	0		
Field Max	3			Occur Max	1		
Char Types	N			Special Chars	n/a		
Format	n/a			Constraints	0 <= DRT <= 359; non-negative integer		
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-9)						
XML Level 1	biom_1:ExtendedFeatureSetMinutiae				Cardinality	0..1	
XML Level 2	biom_1:MinutiaeDelta				Cardinality	0..*	
XML Level 3	biom_1:MinutiaeDeltaDirectionRightMeasure				Cardinality	0..1	
XML Level 4					Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

9.321_6

EFS Deltas

Type

Mnemonic	DTP			Conditionality	0↑		
				Status	Active		
Description	This information item is optional and contains the type of delta, as defined in the look up codes.						
Field Min	1			Occur Min	0		
Field Max	3			Occur Max	1		
Char Types	AN			Special Chars	n/a		
Format	n/a			Constraints	DTP = L, R, I00, I02..I05, I07..I10, I16, I17, C, NULL; See Look Up Codes		
Code List	EFS DELTA TYPE CODES						
Source	ANSI/NIST ITL 1-2013 (Type-9)						
XML Level 1	biom_1:ExtendedFeatureSetMinutiae				Cardinality	0..1	
XML Level 2	biom_1:MinutiaeDelta				Cardinality	0..*	
XML Level 3	biom_1:MinutiaeDeltaCategoryCode				Cardinality	0..1	
XML Level 4					Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.321_7

EFS Deltas

Radius of Position Uncertainty

Mnemonic	RPU			Conditionality	O↑
				Status	Active
Description	This information item is optional and it defines the radius of a circle centered at the location (X,Y) of the delta; the circle is sized to include the area of other possible locations of the delta, if the precise location cannot be determined (e.g., poor clarity). If the location is known precisely, the radius of position uncertainty may be omitted or set to 0. The radius of uncertainty is measured in integer units of 10 micrometers (0.01 mm), and may overlap the edge of the image.				
Field Min	1	Occur Min	0		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	n/a		
Format	n/a	Constraints	0 <= RPU <= 999; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeDelta	Cardinality	0..*		
XML Level 3	biom_1:ImageLocationUncertaintyRadiusMeasure	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.321_8

EFS Deltas

Direction Uncertainty Up

Mnemonic	DUU			Conditionality	O↑
				Status	Active
Description	This information item is optional and it contains the uncertainty of the delta angle up. Valid values range from "0" to "180": a value of "0" (default) indicates a certain direction, while a value of "180" indicates an unknown orientation.				
Field Min	1	Occur Min	0		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	n/a		
Format	n/a	Constraints	0 <= DUU <= 180; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeDelta	Cardinality	0..*		
XML Level 3	biom_1:MinutiaeDeltaDirectionUpUncertaintyValue	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.321_9

EFS Deltas

Direction Uncertainty Left

Mnemonic	DUL			Conditionality	O↑
				Status	Active
Description	This information item is optional and it contains the uncertainty of the delta angle left. Valid values range from "0" to "180": a value of "0" (default) indicates a certain direction, while a value of "180" indicates an unknown orientation.				
Field Min	1	Occur Min	0		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	n/a		
Format	n/a	Constraints	0 <= DUL <= 180; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeDelta	Cardinality	0..*		
XML Level 3	biom_1:MinutiaeDeltaDirectionLeftUncertaintyValue	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.321_10

EFS Deltas

Direction Uncertainty Right

Mnemonic	DUR			Conditionality	O↑
				Status	Active
Description	This information item is optional and it contains the uncertainty of the delta angle right. Valid values range from "0" to "180": a value of "0" (default) indicates a certain direction, while a value of "180" indicates an unknown orientation.				
Field Min	1	Occur Min	0		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	n/a		
Format	n/a	Constraints	0 <= DUR <= 180; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeDelta	Cardinality	0..*		
XML Level 3	biom_1:MinutiaeDeltaDirectionRightUncertaintyValue	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.322

EFS Core-Delta Ridge Counts

Mnemonic	CDR		Conditionality	0	
			Status	Active	
Description	This field contains the count of intervening ridges between each core and delta. Each ridge count has a minimum and maximum value, so that a range may be noted. If the exact value is known, then that value should be put in the minimum and maximum fields. If only a minimum is known, such as when a delta is not visible, the maximum value shall be omitted. Ridge counts may be any non-negative integer. When this field is used for fingerprints, ridge counts shall be provided between each core and each delta, unless there are more than two cores or two deltas in an accidental whorl, in which case only the leftmost and rightmost of the cores and deltas need be used for ridge counts. Each subfield represents a distinct core-delta ridge count.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae		Cardinality	0..1	
XML Level 2	biom_1:MinutiaeRidgeCountCoreToDelta		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.322_0

EFS Core-Delta Ridge Counts

Subfields: Repeating sets of information items

Mnemonic	CDR_0		Conditionality	M↑	
			Status	New - Active	
Description	This field contains the count of intervening ridges between each core and delta. Each ridge count has a minimum and maximum value, so that a range may be noted. If the exact value is known, then that value should be put in the minimum and maximum fields. If only a minimum is known, such as when a delta is not visible, the maximum value shall be omitted. Ridge counts may be any non-negative integer. When this field is used for fingerprints, ridge counts shall be provided between each core and each delta, unless there are more than two cores or two deltas in an accidental whorl, in which case only the leftmost and rightmost of the cores and deltas need be used for ridge counts. Each subfield represents a distinct core-delta ridge count.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	*	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae		Cardinality	0..1	
XML Level 2	biom_1:MinutiaeRidgeCountCoreToDelta		Cardinality	0..*	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.322_1

EFS Core-Delta Ridge Counts

Core Index

Mnemonic	CIX	Conditionality	M↑
		Status	Active
Description	The first information item (core index / CIX) is the (1-based) index of the core corresponding to this count ("1" if only one core is defined). If the relevant core is not defined, this shall be set to "U" to indicate an upper core or "L" to indicate a lower core (whorls only), permitting minimum ridge counts when cores are not in the region of interest.		
Field Min	1	Occur Min	1
Field Max	2	Occur Max	1
Char Types	AN	Special Chars	n/a
Format	n/a	Constraints	1 <= CIX <= 99; positive integer or CIX = L or U
Code List	CORE INDEX CODES		
Source	ANSI/NIST ITL 1-2013 (Type-9)		
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1
XML Level 2	biom_1:MinutiaeRidgeCountCoreToDelta	Cardinality	0..*
XML Level 3	biom_1:MinutiaeCoreIdentification/nc:IdentificationID	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

9.322_2

EFS Core-Delta Ridge Counts

Delta Index

Mnemonic	DIX	Conditionality	M↑
		Status	Active
Description	This information item is the (1-based) index of the delta corresponding to this count ("1" if only one delta is defined). If the relevant delta is not defined, this shall be set to "L" to indicate a left delta or "R" to indicate a right delta, permitting when deltas are not in the region of interest.		
Field Min	1	Occur Min	1
Field Max	2	Occur Max	1
Char Types	AN	Special Chars	n/a
Format	n/a	Constraints	1 <= DIX <= 99; positive integer or DIX = L or R
Code List	DELTA INDEX CODES		
Source	ANSI/NIST ITL 1-2013 (Type-9)		
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1
XML Level 2	biom_1:MinutiaeRidgeCountCoreToDelta	Cardinality	0..*
XML Level 3	biom_1:MinutiaeDeltaIdentification/nc:IdentificationID	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.322_3

EFS Core-Delta Ridge Counts

Min Ridge Count

Mnemonic	MNRC	Conditionality	M↑
		Status	Active
Description	This information item contains the precise ridge count, if it is known; otherwise, it contains the minimum of the range of ridge count values.		
Field Min	1	Occur Min	1
Field Max	2	Occur Max	1
Char Types	N	Special Chars	n/a
Format	n/a	Constraints	0 <= MNRC <= 99; non-negative integer
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-9)		
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1
XML Level 2	biom_1:MinutiaeRidgeCountCoreToDelta	Cardinality	0..*
XML Level 3	biom_1:RidgeCountMinimumValue	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

9.322_4

EFS Core-Delta Ridge Counts

Max Ridge Count

Mnemonic	MXRC	Conditionality	O↑
		Status	Active
Description	This information item contains the precise ridge count (if the count is known precisely), or the maximum range of ridge count values (if there is a known or estimated maximum); otherwise, it shall be omitted.		
Field Min	1	Occur Min	0
Field Max	2	Occur Max	1
Char Types	N	Special Chars	n/a
Format	n/a	Constraints	0 <= MXRC <= 99; non-negative integer
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-9)		
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1
XML Level 2	biom_1:MinutiaeRidgeCountCoreToDelta	Cardinality	0..*
XML Level 3	biom_1:RidgeCountMaximumValue	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

9.323

EFS Center Point of Reference

Mnemonic	CPR	Conditionality	0
		Status	Active
Description	<p>This field contains the location of a center point of reference of a fingerprint, which may be used to define how centered a fingerprint is, as a feature, for registration or orientation, and for quality measurements. While the core may serve some of the same purposes, a center point of reference is defined for arches and provides a single center location for complex whorls, unlike cores. The center point of reference is the sole EFS feature that can be located outside of the EFS region of interest. For example, this allows the estimated center of the finger to be marked even for an extreme side. The origin of CPR, like all other EFS features, is relative to the top left of Field 9.300: EFS region of interest / ROI. Note that this means that the X and Y values for CPR are the only EFS coordinates that may be negative, or greater than the ROI width or height. The center point of reference must be within the bounds of the overall image itself. Thus the allowed special character is the negative sign. The location of a center point of reference can be determined using different algorithms, as stored in the Method information item, in which case different center points of reference may be stored in different data entries (repeating subfield). The center point of reference is defined for fingerprints or toe prints, not for other types of friction ridge images.</p>		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	n/a
Format	n/a	Constraints	n/a
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-9)		
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1
XML Level 2	biom_1:FrictionRidgeImageCenter	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.323_0

EFS Center Point of Reference

Subfields: Repeating sets of information items

Mnemonic	CPR_0			Conditionality	M↑
				Status	New - Active
Description	This field contains the location of a center point of reference of a fingerprint, which may be used to define how centered a fingerprint is, as a feature, for registration or orientation, and for quality measurements. While the core may serve some of the same purposes, a center point of reference is defined for arches and provides a single center location for complex whorls, unlike cores. The center point of reference is the sole EFS feature that can be located outside of the EFS region of interest. For example, this allows the estimated center of the finger to be marked even for an extreme side. The origin of CPR, like all other EFS features, is relative to the top left of Field 9.300: EFS region of interest / ROI. Note that this means that the X and Y values for CPR are the only EFS coordinates that may be negative, or greater than the ROI width or height. The center point of reference must be within the bounds of the overall image itself. Thus the allowed special character is the negative sign. The location of a center point of reference can be determined using different algorithms, as stored in the Method information item, in which case different center points of reference may be stored in different data entries (repeating subfield). The center point of reference is defined for fingerprints or toe prints, not for other types of friction ridge images.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	4		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0...1
XML Level 2	biom_1:FrictionRidgeImageCenter			Cardinality	0..4
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.323_1

EFS Center Point of Reference

Method

Mnemonic	CPM			Conditionality	M↑
				Status	Active
Description	This information item is the method of determining the X, Y location. It is a one character value. See Look Up Codes for valid values.				
Field Min	1	Occur Min	1		
Field Max	1	Occur Max	1		
Char Types	AN	Special Chars	n/a		
Format	n/a	Constraints	CPM = L, 0, 1, or H		
Code List	EFS CENTER POINT OF REFERENCE METHOD CODES				
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0...1
XML Level 2	biom_1:FrictionRidgeImageCenter			Cardinality	0..4
XML Level 3	biom_1:FrictionRidgeImageCenterLocationMethodCode			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.323_2

EFS Center Point of Reference

X Coordinate

Mnemonic	PXC	Conditionality	M↑
		Status	Active
Description	This information item is in units of 10 micrometers (0.01 mm).		
Field Min	1	Occur Min	1
Field Max	5	Occur Max	1
Char Types	NS	Special Chars	Minus Sign
Format	n/a	Constraints	-EHO <= PXC <= 50000; integer, special character "-"
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-9)		
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1
XML Level 2	biom_1:FrictionRidgeImageCenter	Cardinality	0..4
XML Level 3	biom_1:ImageLocationHorizontalCoordinateMeasure	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

9.323_3

EFS Center Point of Reference

Y Coordinate

Mnemonic	PYC	Conditionality	M↑
		Status	Active
Description	This information item is in units of 10 micrometers (0.01 mm).		
Field Min	1	Occur Min	1
Field Max	5	Occur Max	1
Char Types	NS	Special Chars	n/a
Format	n/a	Constraints	-EVO <= PYC <= 50000; integer, special character "-"
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-9)		
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1
XML Level 2	biom_1:FrictionRidgeImageCenter	Cardinality	0..4
XML Level 3	biom_1:ImageLocationVerticalCoordinateMeasure	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.323_4

EFS Center Point of Reference

Radius of Position Uncertainty

Mnemonic	CRU	Conditionality	O↑
		Status	Active
Description	This information item is optional. The radius of position uncertainty is 0 (default) if the location is known precisely; otherwise the position is marked at the best estimate of position, with a radius including the area of other possible locations, in integer units of 10 micrometers (0.01 mm). The radius of uncertainty may overlap the edge of the image. The radius of uncertainty may overlap the edge of the image.		
Field Min	1	Occur Min	0
Field Max	3	Occur Max	1
Char Types	N	Special Chars	n/a
Format	n/a	Constraints	0 <= CRU <= 999; non-negative integer
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-9)		
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1
XML Level 2	biom_1:FrictionRidgeImageCenter	Cardinality	0..4
XML Level 3	biom_1:ImageLocationUncertaintyRadiusMeasure	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

9.324

EFS Distinctive Features

Mnemonic	DIS	Conditionality	D
		Status	Active
Description	This field is used to define one or more areas containing unusually discriminating features that are not fully defined using other Extended Friction Ridge features. The characteristics noted in this field are specific to the friction skin itself, as opposed to those (such as smudging) that are noted in Field 9.357: LQI. When no distinctive features are present, this field shall not be used.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	n/a
Format	n/a	Constraints	n/a
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-9)		
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1
XML Level 2	biom_1:MinutiaeDistinctiveFeature	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.324_0

EFS Distinctive Features

Subfields: Repeating sets of information items

Mnemonic	DIS_0			Conditionality	M↑
				Status	New - Active
Description	This field is used to define one or more areas containing unusually discriminating features that are not fully defined using other Extended Friction Ridge features. The characteristics noted in this field are specific to the friction skin itself, as opposed to those (such as smudging) that are noted in Field 9.357: LQI. When no distinctive features are present, this field shall not be used.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	100		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeDistinctiveFeature			Cardinality	0..100
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.324_1

EFS Distinctive Features

Distinctive Feature Type

Mnemonic	DIT			Conditionality	M↑
				Status	Active
Description	See Look Up Codes for valid values.				
Field Min	4	Occur Min	1		
Field Max	9	Occur Max	1		
Char Types	A	Special Chars	n/a		
Format	n/a	Constraints	See Look Up Codes		
Code List	EFS DISTINCTIVE FEATURES TYPE CODES				
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeDistinctiveFeature			Cardinality	0..100
XML Level 3	biom_1:MinutiaeDistinctiveFeatureCategoryCode			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.324_2

EFS Distinctive Features

Distinctive Features Polygon

Mnemonic	DFP			Conditionality	O↑
				Status	Active
Description	This information item is optional. It is a closed path polygon that outlines the area of the distinctive feature. In Traditional encoding, the two special characters allowed are hyphen and comma. These special characters are not used in XML Encoding.				
Field Min	11	Occur Min	3		
Field Max	1188	Occur Max	99		
Char Types	NS	Special Chars	Minus Sign and Comma		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeDistinctiveFeature	Cardinality	0..100		
XML Level 3	biom_1:ImageSegmentPolygon	Cardinality	0..1		
XML Level 4	biom_1:ImageSegmentVertex	Cardinality	3..99		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.324_3

EFS Distinctive Features

Distinctive Features Comment

Mnemonic	DFC			Conditionality	O↑
				Status	Active
Description	This information item shall contain optional text describing the feature. It is a maximum of 1000 characters.				
Field Min	1	Occur Min	0		
Field Max	1000	Occur Max	1		
Char Types	U	Special Chars	none		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeDistinctiveFeature	Cardinality	0..100		
XML Level 3	biom_1:MinutiaeCommentText	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.325

EFS No Cores Present

Mnemonic	NCOR			Conditionality	D
				Status	Active
Description	This optional field is used to indicate whether the analysis process has determined that no cores could be discerned in the image. If the analysis process has determined that no cores could be discerned in the image, this field shall be set to Y; otherwise, this field will be omitted.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars	none		
Format	n/a	Constraints	NCOR = Y		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeNoCoresPresentIndicator			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.326

EFS No Deltas Present

Mnemonic	NDEL			Conditionality	D
				Status	Active
Description	This optional field is used to indicate whether the analysis process has determined that no deltas could be discerned in the image. If the analysis process has determined that no deltas could be discerned in the image, this field shall be set to Y; otherwise, this field will be omitted.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars	none		
Format	n/a	Constraints	NDEL = Y		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeNoDeltasPresentIndicator			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.327

EFS No Distinctive Features Present

Mnemonic	NDIS			Conditionality	D
				Status	Active
Description	This optional field is used to indicate whether the analysis process has determined that no distinctive features could be discerned in the image. If the analysis process has determined that no distinctive features could be discerned in the image, this field shall be set to Y; otherwise, this field will be omitted.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars	none		
Format	n/a	Constraints	NDIS = Y		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeNoDistinctiveFeaturesPresentIndicator			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.331

EFS Minutiae

Mnemonic	MIN			Conditionality	D
				Status	Active
Description	The type of minutiae shall be marked if clearly identifiable as a ridge ending or bifurcation; otherwise, it shall be marked as unknown type. The location for a bifurcation shall be at the "Y" of the ridge, with the direction running down the valley. The location for a ridge ending or unknown type shall be at the "Y" of the valley, with the direction running up the ridge. If the precise location for a ridge ending cannot be ascertained, a radius of uncertainty shall be marked to include the area of possible locations. If the type is unknown, the radius of uncertainty shall be indicated. When no minutiae are present, this field shall not be used.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:EFSMinutia			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.331_0

EFS Minutiae

Subfields: Repeating sets of information items

Mnemonic	MIN_0			Conditionality	M↑
				Status	New - Active
Description	The type of minutiae shall be marked if clearly identifiable as a ridge ending or bifurcation; otherwise, it shall be marked as unknown type. The location for a bifurcation shall be at the “Y” of the ridge, with the direction running down the valley. The location for a ridge ending or unknown type shall be at the “Y” of the valley, with the direction running up the ridge. If the precise location for a ridge ending cannot be ascertained, a radius of uncertainty shall be marked to include the area of possible locations. If the type is unknown, the radius of uncertainty shall be indicated. When no minutiae are present, this field shall not be used.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1000		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:EFSSMinutia			Cardinality	0..1000
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.331_1

EFS Minutiae

X Coordinate

Mnemonic	MXC			Conditionality	M↑
				Status	Active
Description	This information item is in units of 10 micrometers (0.01 mm).				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	0 <= MXC < EWI; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:EFSSMinutia			Cardinality	0..1000
XML Level 3	biom_1:ImageLocationHorizontalCoordinateMeasure			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.331_2

EFS Minutiae

Y Coordinate

Mnemonic	MYC			Conditionality	M↑
				Status	Active
Description	This information item is in units of 10 micrometers (0.01 mm).				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	0 <= MYC < EHI; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0...1		
XML Level 2	biom_1:EFSMinutia	Cardinality	0..1000		
XML Level 3	biom_1:ImageLocationVerticalCoordinateMeasure	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.331_3

EFS Minutiae

Theta Degrees

Mnemonic	MTD			Conditionality	M↑
				Status	Active
Description	This information item is expressed in degrees in the range 0 to 359. If MDU is set to 180, MTD is undefined and should not be displayed to the user.				
Field Min	1	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	0 <= MTD <= 359; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0...1		
XML Level 2	biom_1:EFSMinutia	Cardinality	0..1000		
XML Level 3	biom_1:ImageLocationThetaAngleMeasure	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.331_4

EFS Minutiae

Minutiae Type

Mnemonic	MTY			Conditionality	M↑
				Status	Active
Description	See Look Up Codes for valid values.				
Field Min	1	Occur Min	1		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars	none		
Format	n/a	Constraints	MTY = E, B, or X		
Code List	EFS MINUTIAE TYPE CODES				
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:EFSMinutia	Cardinality	0..1000		
XML Level 3	biom_1:EFSMinutiaCategoryCode	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.331_5

EFS Minutiae

Radius of Posiiton Uncertainty

Mnemonic	MRU			Conditionality	O↑
				Status	Active
Description	This information item defines the radius of a circle centered at the location (X,Y) of the minutia.				
Field Min	1	Occur Min	0		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	0 <= MDU <= 999; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:EFSMinutia	Cardinality	0..1000		
XML Level 3	biom_1:ImageLocationUncertaintyRadiusMeasure	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.331_6

EFS Minutiae

Minutia Direction of Uncertainty

Mnemonic	MDU			Conditionality	O↑
				Status	Active
Description	This information item contains an integer from "0" (default) to "180" indicating the precision in the direction (theta) of the minutia, measured in degrees. The resulting direction is $\Theta \pm \text{Uncertainty}^\circ$. If MDU is set to 180, MTD is undefined and should not be displayed to the user.				
Field Min	1	Occur Min	0		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	0 <= MDU <= 180; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:EFSSMinutia			Cardinality	0..1000
XML Level 3	biom_1:MinutiaDirectionUncertaintyValue			Cardinality	0..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.332

EFS Minutiae Ridge Count Algorithm

Mnemonic	MRA			Conditionality	D
				Status	Active
Description	This optional field defines the algorithm used in determining how neighboring minutiae are selected for use in the ridge counts in Field 9.333: MRC. See Look Up Codes for valid values.				
Field Min	5	Occur Min	0		
Field Max	8	Occur Max	1		
Char Types	AN	Special Chars	none		
Format	n/a	Constraints	MRA = OCTANT, EFTS7, or QUADRANT		
Code List	EFS MINUTIAE RIDGE COUNT ALGORITHM CODES				
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:EFSSRidgeCountAlgorithmCode			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.333

EFS Minutiae Ridge Counts

Mnemonic	MRC			Conditionality	D
				Status	Active
Description	This field contains the counts of intervening ridges between specified minutiae. Field 9.332: MRA governs how the minutiae are selected for ridge counts, and the details of how the ridges are counted. Each ridge count is represented in a separate subfield Field 9.335: RCC may be used to indicate ridge count confidence between minutiae. If Field 9.372: SIM is used, ridge counts can be derived from that field rather than included explicitly.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:EFSRidgeCountItem			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.333_0

EFS Minutiae Ridge Counts

Subfields: Repeating sets of information items

Mnemonic	MRC_0			Conditionality	M↑
				Status	New - Active
Description	This field contains the counts of intervening ridges between specified minutiae. Field 9.332: MRA governs how the minutiae are selected for ridge counts, and the details of how the ridges are counted. Each ridge count is represented in a separate subfield Field 9.335: RCC may be used to indicate ridge count confidence between minutiae. If Field 9.372: SIM is used, ridge counts can be derived from that field rather than included explicitly.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	*		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:EFSRidgeCountItem			Cardinality	0..*
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.333_1

EFS Minutiae Ridge Counts

Minutiae Index A

Mnemonic	MIA			Conditionality	M↑
				Status	Active
Description	This information item contains the (1-based) index of the first minutia.				
Field Min	1	Occur Min	1		
Field Max	4	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	1 <= MIA <= 9999; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:EFSRidgeCountItem			Cardinality	0..*
XML Level 3	biom_1:MinutiaIdentification/nc:IdentificationID			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.333_2

EFS Minutiae Ridge Counts

Minutiae Index B

Mnemonic	MIB			Conditionality	M↑
				Status	Active
Description	This information item contains the (1-based) index of the second minutia.				
Field Min	1	Occur Min	1		
Field Max	4	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	1 <= MIB <= 9999; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:EFSRidgeCountItem			Cardinality	0..*
XML Level 3	biom_1:MinutiaReferenceIdentification/nc:IdentificationID			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.333_3

EFS Minutiae Ridge Counts

Ridge Count

Mnemonic	MIR	Conditionality	M↑
		Status	Active
Description	This information item contains the number of intervening ridges between minutiae A and B. Unknown ridge counts shall be omitted (left empty). The Field 9.332: MRA governs other details or special cases (if any).		
Field Min	1	Occur Min	1
Field Max	2	Occur Max	1
Char Types	N	Special Chars	none
Format	n/a	Constraints	0 <= MIRB <= 99; non-negative integer
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-9)		
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1
XML Level 2	biom_1:EFSRidgeCountItem	Cardinality	0..*
XML Level 3	biom_1:RidgeCountValue	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

9.333_4

EFS Minutiae Ridge Counts

Reference Number

Mnemonic	MRN	Conditionality	O↑
		Status	Active
Description	This information item is optional and, if used, contains a reference number specific to the ridge count algorithm. For the OCTANT and EFTS7 ridge count algorithms, this information item specifies the octant. For the QUADRANT ridge count algorithm, this information item specifies the quadrant.		
Field Min	1	Occur Min	0
Field Max	1	Occur Max	1
Char Types	N	Special Chars	none
Format	n/a	Constraints	0 <= MRN <= 7; non-negative integer
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-9)		
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1
XML Level 2	biom_1:EFSRidgeCountItem	Cardinality	0..*
XML Level 3	biom_1:MinutiaeRidgeCountOctantNumeric	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

9.333_5

EFS Minutiae Ridge Counts

Residual

Mnemonic	MRS			Conditionality	O↑
				Status	Active
Description	This information item is optional and is specific to the OCTANT and EFTS7 ridge count algorithms, specifying the half of the octant in which the neighboring minutia lies. The residual is 0 if the neighboring minutia lies in the clockwise half of the octant, or 1 if the minutia lies in the counterclockwise half of the octant.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	MRS = 0 or 1; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:EFSRidgeCountItem			Cardinality	0..*
XML Level 3	biom_1:MinutiaeRidgeCountResidualCode			Cardinality	0..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.334

EFS No Minutiae Present

Mnemonic	NMIN			Conditionality	D
				Status	Active
Description	This optional field indicates whether the analysis determined that no minutiae could be discerned in the image. If the analysis process has determined that no minutiae could be discerned in the image, this field shall be set to Y; otherwise, this field will be omitted.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars	none		
Format	n/a	Constraints	NMIN = Y		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeNoMinutiaePresentIndicator			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.335

EFS Ridge Count Confidence

Mnemonic	RCC		Conditionality	D			
			Status	Active			
Description	This field is optional if Field 9.333: EFS minutiae ridge counts / MRC appears in the record and should not otherwise be included. It is used to indicate confidence in intervening ridge counts between any two points. Each ridge count confidence value is represented in a separate data entry (repeating subfield). While primarily used to indicate ridge count confidence between minutiae, this confidence measure may also apply to other features such as Core/Delta ridge counts. If this field is not used, the default assumption is that the ridge counts were manually determined. This field provides a means to state when only a portion of ridge counts have been manually checked.						
Field Min	n/a	Occur Min	0				
Field Max	n/a	Occur Max	1				
Char Types	n/a	Special Chars	n/a				
Format	n/a	Constraints	n/a				
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-9)						
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1				
XML Level 2	biom_1:MinutiaeRidgeCountConfidence	Cardinality	0..1				
XML Level 3		Cardinality					
XML Level 4		Cardinality					
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

9.335_0

EFS Ridge Count Confidence

Subfields: Repeating sets of information items

Mnemonic	RCC_0		Conditionality	M↑			
			Status	New - Active			
Description	This field is optional if Field 9.333: EFS minutiae ridge counts / MRC appears in the record and should not otherwise be included. It is used to indicate confidence in intervening ridge counts between any two points. Each ridge count confidence value is represented in a separate data entry (repeating subfield). While primarily used to indicate ridge count confidence between minutiae, this confidence measure may also apply to other features such as Core/Delta ridge counts. If this field is not used, the default assumption is that the ridge counts were manually determined. This field provides a means to state when only a portion of ridge counts have been manually checked.						
Field Min	n/a	Occur Min	0				
Field Max	n/a	Occur Max	7993				
Char Types	n/a	Special Chars	n/a				
Format	n/a	Constraints	n/a				
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-9)						
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1				
XML Level 2	biom_1:MinutiaeRidgeCountConfidence	Cardinality	0..7993				
XML Level 3		Cardinality					
XML Level 4		Cardinality					
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-9 Minutiae Data Record (Extended Feature Set)

Page 419 of 1037

9.335_1

EFS Ridge Count Confidence

X Coordinate Point A

Mnemonic	ACX			Conditionality	M↑
				Status	Active
Description	This information item contains the x coordinates for Point A, in units of 10 micrometers (0.01 mm).				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	0 <= ACX < EWI; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeRidgeCountConfidence			Cardinality	0..7993
XML Level 3	biom_1:MinutiaLocationPoint			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.335_2

EFS Ridge Count Confidence

Y Coordinate Point A

Mnemonic	ACY			Conditionality	M↑
				Status	Active
Description	This information item contains the y coordinates for Point A, in units of 10 micrometers (0.01 mm).				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	0 <= ACY < EHI; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeRidgeCountConfidence			Cardinality	0..7993
XML Level 3	biom_1:MinutiaLocationPoint			Cardinality	1..1
XML Level 4	biom_1:ImageLocationVerticalCoordinateMeasure			Cardinality	1..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.335_3

EFS Ridge Count Confidence

X Coordinate Point B

Mnemonic	BCX			Conditionality	M↑
				Status	Active
Description	This information item contains the x coordinates for Point B, in units of 10 micrometers (0.01 mm).				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	0 <= BCX < EWI; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeRidgeCountConfidence	Cardinality	0..7993		
XML Level 3	biom_1:MinutiaLocationPoint	Cardinality	1..1		
XML Level 4	biom_1:ImageLocationHorizontalCoordinateMeasure	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.335_4

EFS Ridge Count Confidence

Y Coordinate Point B

Mnemonic	BCY			Conditionality	M↑
				Status	Active
Description	This information item contains the y coordinates for Point B, in units of 10 micrometers (0.01 mm).				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	0 <= BCY < EHI; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeRidgeCountConfidence	Cardinality	0..7993		
XML Level 3	biom_1:MinutiaLocationPoint	Cardinality	1..1		
XML Level 4	biom_1:ImageLocationVerticalCoordinateMeasure	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.335_5

EFS Ridge Count Confidence

Method of Ridge Counting

Mnemonic	MORC	Conditionality	M↑
		Status	Active
Description	This information item states the method by which ridge counts were determined and / or validated.		
Field Min	1	Occur Min	1
Field Max	1	Occur Max	1
Char Types	A	Special Chars	none
Format	n/a	Constraints	MORC = A, T, or M
Code List	EFS METHOD OF RIDGE COUNTING CODES		
Source	ANSI/NIST ITL 1-2013 (Type-9)		
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1
XML Level 2	biom_1:MinutiaeRidgeCountConfidence	Cardinality	0..7993
XML Level 3	biom_1:MinutiaLocationPoint	Cardinality	1..1
XML Level 4	biom_1:MinutiaeRidgeCountMethodCode	Cardinality	1..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes

9.335_6

EFS Ridge Count Confidence

Confidence Value

Mnemonic	MCV	Conditionality	M↑
		Status	Active
Description	This information item contains the integer confidence value for a ridge count from 0 to 99, with 0 indicating no confidence.		
Field Min	1	Occur Min	1
Field Max	2	Occur Max	1
Char Types	N	Special Chars	none
Format	n/a	Constraints	0 <= MCV <= 99; non-negative integer
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-9)		
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1
XML Level 2	biom_1:MinutiaeRidgeCountConfidence	Cardinality	0..7993
XML Level 3	biom_1:MinutiaLocationPoint	Cardinality	1..1
XML Level 4	biom_1:MinutiaeRidgeCountConfidenceValue	Cardinality	1..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.34

EFS Dots

Mnemonic	DOT		Conditionality	D			
			Status	Active			
Description	A dot is a single or partial ridge unit that is shorter than local ridge width. Longer ridge units are considered standard ridges and should be marked as such, with two ridge endings. Potential dots that are substantially thinner than local ridge width should be marked as incipient ridges. A dot is marked by its center point. Elongated dots may optionally have their length marked along the longest dimension. When no dots are present, this field shall not be used. This field consists of a repeating subfield (one for each dot).						
Field Min	n/a	Occur Min	0				
Field Max	n/a	Occur Max	1				
Char Types	n/a	Special Chars	n/a				
Format	n/a	Constraints	n/a				
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-9)						
XML Level 1	biom_1:ExtendedFeatureSetMinutiae		Cardinality	0..1			
XML Level 2	biom_1:MinutiaeDot		Cardinality	0..1			
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

9.340_0

EFS Dots

Subfields: Repeating sets of information items

Mnemonic	DOT_0		Conditionality	M↑			
			Status	New - Active			
Description	A dot is a single or partial ridge unit that is shorter than local ridge width. Longer ridge units are considered standard ridges and should be marked as such, with two ridge endings. Potential dots that are substantially thinner than local ridge width should be marked as incipient ridges. A dot is marked by its center point. Elongated dots may optionally have their length marked along the longest dimension. When no dots are present, this field shall not be used. This field consists of a repeating subfield (one for each dot).						
Field Min	n/a	Occur Min	0				
Field Max	n/a	Occur Max	1000				
Char Types	n/a	Special Chars	n/a				
Format	n/a	Constraints	n/a				
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-9)						
XML Level 1	biom_1:ExtendedFeatureSetMinutiae		Cardinality	0..1			
XML Level 2	biom_1:MinutiaeDot		Cardinality	0..1000			
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.340_1

EFS Dots

Dot X Coordinate

Mnemonic	DOX			Conditionality	M↑
				Status	Active
Description	This information item is the x coordinate of the center of the dot, expressed in units of 10 micrometers (0.01 mm).				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	0 <= DOX < EWI; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeDot	Cardinality	0..1000		
XML Level 3	biom_1:ImageLocationHorizontalCoordinateMeasure	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.340_2

EFS Dots

Dot Y Coordinate

Mnemonic	DOY			Conditionality	M↑
				Status	Active
Description	This information item is the y coordinate of the center of the dot, expressed in units of 10 micrometers (0.01 mm).				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	0 <= DOY < EHI; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeDot	Cardinality	0..1000		
XML Level 3	biom_1:ImageLocationVerticalCoordinateMeasure	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.340_3

EFS Dots

Dot Length

Mnemonic	DOL			Conditionality	O↑
				Status	Active
Description	This information item is an optional information item containing the length of the dot along its longest dimension in integer units of 10 micrometers.				
Field Min	1	Occur Min	0		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	1 <= DOL <= 99; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeDot	Cardinality	0..1000		
XML Level 3	biom_1:MinutiaeDotLengthMeasure	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.341

EFS Incipient Ridges

Mnemonic	INR			Conditionality	D
				Status	Active
Description	An incipient ridge is a thin ridge, substantially thinner than local ridge width. An incipient is marked as one or more line segments, each defined with the (X, Y) endpoints along its longest dimension. An incipient ridge is marked with a line segment along its longest dimension. If the incipient is composed of a series of segments: Mark the incipient ridge as a single line when the segments of the incipient are close together or the separations between segments are indistinct. Mark the incipient ridge segments individually when they are clearly separate, with distinct lines drawn for each one. Mark the incipient ridge as a series of adjoining, unbroken line segments when it curves. When no incipient ridges are present, this field shall not be used.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeIncipientRidge	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.341_0

EFS Incipient Ridges

Subfields: Repeating sets of information items

Mnemonic	INR_0	Conditionality	M↑
		Status	New - Active
Description	An incipient ridge is a thin ridge, substantially thinner than local ridge width. An incipient is marked as one or more line segments, each defined with the (X, Y) endpoints along its longest dimension. An incipient ridge is marked with a line segment along its longest dimension. If the incipient is composed of a series of segments: Mark the incipient ridge as a single line when the segments of the incipient are close together or the separations between segments are indistinct. Mark the incipient ridge segments individually when they are clearly separate, with distinct lines drawn for each one. Mark the incipient ridge as a series of adjoining, unbroken line segments when it curves. When no incipient ridges are present, this field shall not be used.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1000
Char Types	n/a	Special Chars	n/a
Format	n/a	Constraints	n/a
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-9)		
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1
XML Level 2	biom_1:MinutiaeIncipientRidge	Cardinality	0..1000
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

9.341_1

EFS Incipient Ridges

X Coordinate Point 1

Mnemonic	X1C	Conditionality	M↑
		Status	Active
Description	This information item contains the 'x' coordinate of one endpoint, in units of 10 micrometers (0.01 mm).		
Field Min	1	Occur Min	1
Field Max	5	Occur Max	1
Char Types	N	Special Chars	none
Format	n/a	Constraints	0 <= X1C < EWI; non-negative integer
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-9)		
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1
XML Level 2	biom_1:MinutiaeIncipientRidge	Cardinality	0..1000
XML Level 3	biom_1:ImageLocationHorizontalCoordinateMeasure	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-9 Minutiae Data Record (Extended Feature Set)

Page 426 of 1037

9.341_2

EFS Incipient Ridges

Y Coordinate Point 1

Mnemonic	Y1C			Conditionality	M↑
				Status	Active
Description	This information item contains the 'y' coordinate of one endpoint, in units of 10 micrometers (0.01 mm).				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	0 <= Y1C < EHI; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeIncipientRidge			Cardinality	0..1000
XML Level 3	biom_1:ImageLocationVerticalCoordinateMeasure			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.341_3

EFS Incipient Ridges

X Coordinate Point 2

Mnemonic	X2C			Conditionality	M↑
				Status	Active
Description	This information item contains the 'x' coordinate of the other endpoint, in units of 10 micrometers (0.01 mm).				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	0 <= X2C < EWI; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeIncipientRidge			Cardinality	0..1000
XML Level 3	biom_1:ImageLocationHorizontalCoordinateMeasure			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.341_4

EFS Incipient Ridges

Y Coordinate Point 2

Mnemonic	Y2C			Conditionality	M↑
				Status	Active
Description	This information item contains the 'y' coordinate of the other endpoint, in units of 10 micrometers (0.01 mm).				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	0 <= Y2C < EHI; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeIncipientRidge			Cardinality	0..1000
XML Level 3	biom_1:ImageLocationVerticalCoordinateMeasure			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.342

EFS Creases and Linear Discontinuities

Mnemonic	CLD			Conditionality	D
				Status	Active
Description	This optional field defines the permanent flexion creases, as well as linear discontinuities (minor creases, cracks, cuts, and thin or non-permanent scars). If a continuous discontinuity curves, it should be marked as a series of adjoining line segments. If a crease is feathered or composed of a series of crisscross creases, each of the short creases shall be marked separately. When no creases or linear discontinuities are present, this field shall not be used.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeFlexionCrease			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.342_0

EFS Creases and Linear Discontinuities

Subfields: Repeating sets of information items

Mnemonic	CLD_0			Conditionality	M↑
				Status	New - Active
Description	This optional field defines the permanent flexion creases, as well as linear discontinuities (minor creases, cracks, cuts, and thin or non-permanent scars). If a continuous discontinuity curves, it should be marked as a series of adjoining line segments. If a crease is feathered or composed of a series of crisscross creases, each of the short creases shall be marked separately. When no creases or linear discontinuities are present, this field shall not be used.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1000		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaLocationPoint			Cardinality	0..1000
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.342_1

EFS Creases and Linear Discontinuities

X Coordinate Point 1

Mnemonic	X1D			Conditionality	M↑
				Status	Active
Description	This information item shall contain the 'x' coordinate of one endpoint, in units of 10 micrometers (0.01 mm).				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	0 <= X1D < EW1; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaLocationPoint			Cardinality	0..1000
XML Level 3	biom_1:ImageLocationHorizontalCoordinateMeasure			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.342_2

EFS Creases and Linear Discontinuities

Y Coordinate Point 1

Mnemonic	Y1D			Conditionality	M↑
				Status	Active
Description	This information item shall contain the 'y' coordinate of one endpoint, in units of 10 micrometers (0.01 mm).				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	0 <= Y1D < EHI; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaLocationPoint			Cardinality	0..1000
XML Level 3	biom_1:ImageLocationVerticalCoordinateMeasure			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.342_3

EFS Creases and Linear Discontinuities

X Coordinate Point 2

Mnemonic	X2D			Conditionality	M↑
				Status	Active
Description	This information item shall contain the 'x' coordinate of the other endpoint, in units of 10 micrometers (0.01 mm).				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	0 <= X2D < EWI; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaLocationPoint			Cardinality	0..1000
XML Level 3	biom_1:ImageLocationHorizontalCoordinateMeasure			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.342_4

EFS Creases and Linear Discontinuities

Y Coordinate Point 2

Mnemonic	Y2D			Conditionality	M↑
				Status	Active
Description	This information item shall contain the 'y' coordinate of the other endpoint, in units of 10 micrometers (0.01 mm).				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	0 <= Y2D < EHI; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0...1		
XML Level 2	biom_1:MinutiaLocationPoint	Cardinality	0..1000		
XML Level 3	biom_1:ImageLocationVerticalCoordinateMeasure	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.342_5

EFS Creases and Linear Discontinuities

Type

Mnemonic	TPD			Conditionality	M↑
				Status	Active
Description	This information item indicates the type of crease or linear discontinuity. See Look Up Codes for valid values. If Field 9.302: FPP indicates a palm (has a value 20 through 38 (inclusive) or 81 through 84 (inclusive)), then TPD may be set to RLC, PTC, DT If Field 9.302: FPP indicates a finger or a palm that includes fingers (has a value 0 through 10 (inclusive) or 16, 17, 21, 23, 26, 28), then TPD may be set to DIP, PIP or PDC.				
Field Min	2	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	AN	Special Chars	none		
Format	n/a	Constraints	TPD = DIP, PIP, PDC00-PDC10, PDC16-17, RLC, PTC, DTC, WC		
Code List	EFS CREASE TYPE CODES				
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0...1		
XML Level 2	biom_1:MinutiaLocationPoint	Cardinality	0..1000		
XML Level 3	biom_1:MinutiaeFlexionCreaseCategoryCode	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.343

EFS Ridge Edge Features

Mnemonic	REF			Conditionality	D
				Status	Active
Description	Ridge edge features include Protrusions (abrupt increases in ridge width), Indentations (abrupt decreases in ridge width), and Discontinuities (points where a ridge stops briefly). When no ridge edges are present, this field shall not be used. Each ridge edge feature is represented as a separate subfield.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeRidgeEdgeOrDiscontinuity			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.343_0

EFS Ridge Edge Features

Subfields: Repeating sets of information items

Mnemonic	REF_0			Conditionality	M↑
				Status	New - Active
Description	Ridge edge features include Protrusions (abrupt increases in ridge width), Indentations (abrupt decreases in ridge width), and Discontinuities (points where a ridge stops briefly). When no ridge edges are present, this field shall not be used. Each ridge edge feature is represented as a separate subfield.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1000	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeRidgeEdgeOrDiscontinuity			Cardinality	0..1000
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.343_1

EFS Ridge Edge Features

X Coordinate

Mnemonic	CLX			Conditionality	M↑
				Status	Active
Description	This information item contains the 'x' coordinate of the center of the feature, in units of 10 micrometers (10 μm = 0.01 mm).				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	0 <= CLX < EWI; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0...1		
XML Level 2	biom_1:MinutiaeRidgeEdgeOrDiscontinuity	Cardinality	0..1000		
XML Level 3	biom_1:ImageLocationHorizontalCoordinateMeasure	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.343_2

EFS Ridge Edge Features

Y Coordinate

Mnemonic	CLY			Conditionality	M↑
				Status	Active
Description	This information item contains the 'y' coordinate of the center of the feature, in units of 10 micrometers (0.01 mm).				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	0 <= CLY < EHI; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0...1		
XML Level 2	biom_1:MinutiaeRidgeEdgeOrDiscontinuity	Cardinality	0..1000		
XML Level 3	biom_1:ImageLocationVerticalCoordinateMeasure	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.343_3

EFS Ridge Edge Features

Type

Mnemonic	CLT			Conditionality	M↑
				Status	Active
Description	This information item states the type of feature: P (Protrusion), I (Indentation), or D (Discontinuity).				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars	none		
Format	n/a	Constraints	CLT = P, I, or D		
Code List	EFS RIDGE EDGE FEATURES TYPE CODES				
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeRidgeEdgeOrDiscontinuity	Cardinality	0..1000		
XML Level 3	biom_1:MinutiaeRidgeEdgeOrDiscontinuityCategoryCode	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.344

EFS No Pores Present

Mnemonic	NPOR			Conditionality	D
				Status	Active
Description	This optional field is used to indicate whether the analysis process has determined that no pores could be discerned in the image. If the analysis process has determined that no pores could be discerned in the image, this field shall be set to Y; otherwise, this field will be omitted.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars	none		
Format	n/a	Constraints	NPOR = Y		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeNoPoresPresentIndicator	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.345

EFS Pores

Mnemonic	POR			Conditionality	0
				Status	Active
Description	Each pore is marked by its center point. When no pores are present, this field shall not be used. Each pore is represented as a separate repeating subfield.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaePore			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.345_0

EFS Pores

Subfields: Repeating sets of information items

Mnemonic	POR_0			Conditionality	M↑
				Status	New - Active
Description	Each pore is marked by its center point. When no pores are present, this field shall not be used. Each pore is represented as a separate repeating subfield.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1000		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaePore			Cardinality	0..1000
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.345_1

EFS Pores

X Coordinate

Mnemonic	POX			Conditionality	M↑
				Status	Active
Description	This information item contains the 'x' coordinate of the center of the pore, in units of 10 micrometers (0.01 mm).				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	0 <= POX < EWI; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaePore	Cardinality	0..1000		
XML Level 3	biom_1:ImageLocationHorizontalCoordinateMeasure	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.345_2

EFS Pores

Y Coordinate

Mnemonic	POY			Conditionality	M↑
				Status	Active
Description	This information item contains the 'y' coordinate of the center of the pore, in units of 10 micrometers (0.01 mm).				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	0 <= POY < EHI; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaePore	Cardinality	0..1000		
XML Level 3	biom_1:ImageLocationVerticalCoordinateMeasure	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.346

EFS No Dots Present

Mnemonic	NDOT			Conditionality	D
				Status	Active
Description	This optional field is used to indicate whether the analysis process has determined that no dots are present. If the analysis process has determined that no dots could be discerned in the image, this field shall be set to Y; otherwise, this field will be omitted.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars	none		
Format	n/a	Constraints	NDOT = Y		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeNoDotsPresentIndicator			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.347

EFS No Incipient Ridges Present

Mnemonic	NINR			Conditionality	D
				Status	Active
Description	This optional field is used to indicate whether the analysis process has determined that no incipient ridges could be discerned in the image. If the analysis process has determined that no incipient ridges could be discerned in the image, this field shall otherwise, this field will be omitted.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars	none		
Format	n/a	Constraints	NINR = Y		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeNoIncipientRidgesPresentIndicator			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.348

EFS No Creases Present

Mnemonic	NCLD			Conditionality	D
				Status	Active
Description	This optional field is used to indicate whether the analysis process has determined that no creases could be discerned in the image. If the analysis process has determined that no creases could be discerned in the image, this field shall be set to Y; otherwise, this field will be omitted.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars	none		
Format	n/a	Constraints	NCLD = Y		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeNoCreasesPresentIndicator			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.349

EFS No Ridge Edge Features Present

Mnemonic	NREF			Conditionality	D
				Status	Active
Description	This optional field is used to indicate whether the analysis process has determined that no ridge edge features could be discerned in the image. If the analysis process has determined that no ridge edge features could be discerned in the image, this field shall be set to Y; otherwise, this field will be omitted.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars	none		
Format	n/a	Constraints	NREF = Y		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeNoRidgeEdgeFeaturesPresentIndicator			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.35

EFS Method of Feature Detection

Mnemonic	MFD			Conditionality	0
				Status	Active
Description	This optional field states the method(s) by which the Extended Friction Ridge features were detected and/or edited. Each time fields are created or modified, the date and name of the automated algorithm or human examiner is noted in a new data entry (repeating subfield).				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeFeatureDetection			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.350_0

EFS Method of Feature Detection

Subfields: Repeating sets of information items

Mnemonic	MFD_0			Conditionality	M↑
				Status	New - Active
Description	This optional field states the method(s) by which the Extended Friction Ridge features were detected and/or edited. Each time fields are created or modified, the date and name of the automated algorithm or human examiner is noted in a new data entry (repeating subfield).				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	100	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeFeatureDetection			Cardinality	0..100
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.350_1

EFS Method of Feature Detection

Field

Mnemonic	FIE			Conditionality	M↑
				Status	Active
Description	This information item indicates which fields correspond to the method noted: it shall contain a single field (e.g., "9.331"), a comma-separated list of fields without spaces (e.g., "9.340,9.341,9.343"), or "ALL". The allowed special characters are the comma and the period.				
Field Min	3	Occur Min	1		
Field Max	999	Occur Max	1		
Char Types	ANS	Special Chars	Comma and Period		
Format	n/a	Constraints	ALL or 9.300 <= value <= 9.373; comma separated fields without a space		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeFeatureDetection			Cardinality	0..100
XML Level 3	biom_1:MinutiaeFeatureDetectionFieldListText			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.350_2

EFS Method of Feature Detection

Method

Mnemonic	FME			Conditionality	M↑
				Status	Active
Description	This information item shall state the method by which the fingerprint features were detected and encoded. See Look Up Codes for valid values.				
Field Min	3	Occur Min	1		
Field Max	4	Occur Max	1		
Char Types	A	Special Chars	none		
Format	n/a	Constraints	FME = AUTO, REV, EDIT, or MAN		
Code List	EFS METHOD OF FEATURE DETECTION METHOD CODES				
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeFeatureDetection			Cardinality	0..100
XML Level 3	biom_1:MinutiaeFeatureDetectionMethodCode			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.350_3

EFS Method of Feature Detection

Algorithm Vendor

Mnemonic	FAV			Conditionality	D
				Status	Active
Description	This information item should identify the vendor of the encoding algorithm if the method is not "MAN".				
Field Min	1	Occur Min	0		
Field Max	40	Occur Max	1		
Char Types	U	Special Chars	none		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeFeatureDetection			Cardinality	0..100
XML Level 3	biom_1:MinutiaeAlgorithmVendorIdentification/nc:IdentificationID			Cardinality	0..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.350_4

EFS Method of Feature Detection

Algorithm

Mnemonic	FAL			Conditionality	D
				Status	Active
Description	This information item should identify the algorithm by name and version for methods other than "MAN".				
Field Min	1	Occur Min	0		
Field Max	40	Occur Max	1		
Char Types	U	Special Chars	none		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeFeatureDetection			Cardinality	0..100
XML Level 3	biom_1:MinutiaeAlgorithmIdentification/nc:IdentificationID			Cardinality	0..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.350_5

EFS Method of Feature Detection

Examiner Surname

Mnemonic	ESN			Conditionality	D
				Status	Active
Description	This information item should contain the surname (last name) of the fingerprint examiner, for methods other than "AUTO".				
Field Min	1	Occur Min	0		
Field Max	40	Occur Max	1		
Char Types	U	Special Chars	none		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeFeatureDetection	Cardinality	0..100		
XML Level 3	biom:MinutiaeExaminer/nc:PersonName/	Cardinality	0..1		
XML Level 4	nc:PersonSurname	Cardinality	0..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.350_6

EFS Method of Feature Detection

Examiner Given Name

Mnemonic	EGN			Conditionality	D
				Status	Active
Description	This information item should contain the first name (given name, or first and middle names) of the fingerprint examiner for methods other than "AUTO."				
Field Min	1	Occur Min	0		
Field Max	40	Occur Max	1		
Char Types	U	Special Chars	none		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeFeatureDetection	Cardinality	0..100		
XML Level 3	biom:MinutiaeExaminer/nc:PersonName/	Cardinality	0..1		
XML Level 4	nc:PersonGivenName	Cardinality	0..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.350_7

EFS Method of Feature Detection

Examiner Affiliation

Mnemonic	EAF		Conditionality	D
			Status	Active
Description	This information item should contain the employer or organizational affiliation of the examiner, for methods other than "AUTO".			
Field Min	1	Occur Min	0	
Field Max	66	Occur Max	1	
Char Types	U	Special Chars	none	
Format	n/a	Constraints	n/a	
Code List				
Source	ANSI/NIST ITL 1-2013 (Type-9)			
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1	
XML Level 2	biom_1:MinutiaeFeatureDetection	Cardinality	0..100	
XML Level 3	biom:MinutiaeExaminer/nc:PersonName/	Cardinality	0..1	
XML Level 4	nc:OrganizationName	Cardinality	0..1	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0 No DoD EBTS 4.0 Yes

9.350_8

EFS Method of Feature Detection

Date and Time

Mnemonic	EMT		Conditionality	M↑
			Status	Active
Description	This information item should contain the date and time that the determination was made, using Greenwich Mean Time (GMT).			
Field Min	15	Occur Min	0	
Field Max	15	Occur Max	1	
Char Types	AN	Special Chars	None	
Format	YYYYMMDDHHMMSSZ - for Traditional Encoding	Constraints	Dependent upon encoding	
Code List				
Source	ANSI/NIST ITL 1-2013 (Type-9)			
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1	
XML Level 2	biom_1:MinutiaeFeatureDetection	Cardinality	0..100	
XML Level 3	biom:MinutiaeExaminer/nc:PersonName/	Cardinality	0..1	
XML Level 4	biom_1:MinutiaeFeatureDetectionDateTime	Cardinality	0..1	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0 No DoD EBTS 4.0 Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.350_9

EFS Method of Feature Detection

Notes

Mnemonic	NTS			Conditionality	O↑
				Status	Active
Description	This information item is an optional item that may contain text with additional information regarding the detection or modification of features.				
Field Min	1	Occur Min	0		
Field Max	99	Occur Max	1		
Char Types	U	Special Chars	none		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeFeatureDetection	Cardinality	0..100		
XML Level 3	biom:MinutiaeExaminer/nc:PersonName/	Cardinality	0..1		
XML Level 4	biom_1:MinutiaeCommentText	Cardinality	0..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.351

EFS Comment

Mnemonic	COM			Conditionality	O
				Status	Active
Description	This optional text field contains additional information not noted in other fields. This may include unformatted text information such as location, background information, or descriptive information. If comments need to be made about specific portions of the impression, use Field 9.324: EFS distinctive features / DIS or Field 9.332: EFS minutiae ridge count algorithm / MRA.				
Field Min	1	Occur Min	0		
Field Max	123	Occur Max	1		
Char Types	U	Special Chars	none		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeCommentText	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.352

EFS Latent Processing Method

Mnemonic	LPM	Conditionality	0
		Status	Active
Description	This optional text field contains one or more three-letter codes indicating the technique(s) used to process the latent fingerprint. Unprocessed impressions (latent images visible to the naked eye) shall be labeled VIS. Multiple methods should be marked by separate subfields. Methods should only be marked if they contributed substantively to the visualization of the image, and shall not be a compilation of all methods attempted.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	none
Format	n/a	Constraints	LPM= 12I, ADX, ALS, AMB, AY7, BAR, BLE, BLP, BPA, BRY, CBB, CDS, COG, DAB, DFO, DLP, GEN, GRP, GTV, HCA, IOD< ISR, LAS, LCV, LIQ, LQD, MBD, MBP, MGP, MPD, MRM, NIN, OTH, PDV, R6G, RAM, RUV, SAO, SDB, SGF, SPR, SSP, SVN, TEC, TID, VIS, WHP, ZIC
Code List	EFS LATENT PROCESSING METHOD CODES		
Source	ANSI/NIST ITL 1-2013 (Type-9)		
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0...1
XML Level 2	biom_1:LatentProcessingCategoryCode	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.352_0

EFS Latent Processing Method

Subfields: Repeating sets of information items

Mnemonic	LPM_0			Conditionality	M↑
				Status	New - Active
Description	This optional text field contains one or more three-letter codes indicating the technique(s) used to process the latent fingerprint. Unprocessed impressions (latent images visible to the naked eye) shall be labeled VIS. Multiple methods should be marked by separate subfields. Methods should only be marked if they contributed substantively to the visualization of the image, and shall not be a compilation of all methods attempted.				
Field Min	3	Occur Min	0		
Field Max	3	Occur Max	10		
Char Types	AN	Special Chars	none		
Format	n/a	Constraints	LPM= 12I, ADX, ALS, AMB, AY7, BAR, BLE, BLP, BPA, BRY, CBB, CDS, COG, DAB, DFO, DLP, GEN, GRP, GTV, HCA, IOD< ISR, LAS, LCV, LIQ, LQD, MBD, MBP, MGP, MPD, MRM, NIN, OTH, PDV, R6G, RAM, RUV, SAO, SDB, SGF, SPR, SSP, SVN, TEC, TID, VIS, WHP, ZIC		
Code List	EFS LATENT PROCESSING METHOD CODES				
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:LatentProcessingCategoryCode	Cardinality	0..10		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.353

EFS Examiner Analysis Assessment

Mnemonic	EAA			Conditionality	O
				Status	Active
Description	This optional text field indicates an examiner's assessment of the value of the single impression delineated by Field 9.300: EFS region of interest / ROI. See also Field 9.362: EFS examiner comparison determination / ECD for comparison determinations.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeValueAssessment	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.353_1

EFS Examiner Analysis Assessment

Value Assessment Code

Mnemonic	AAV			Conditionality	M↑
				Status	Active
Description	This information item indicates the value of the impression. See Look Up Codes for valid values.				
Field Min	5	Occur Min	1		
Field Max	8	Occur Max	1		
Char Types	A	Special Chars	none		
Format	n/a	Constraints	AAV = VALUE, LIMITED, NOVALUE, NONPRINT		
Code List	EFS EXAMINER PROCESSING METHOD VALUE ASSESSMENT CODES				
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeValueAssessment	Cardinality	0..1		
XML Level 3	biom_1:MinutiaeValueAssessmentResultCode	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.353_2

EFS Examiner Analysis Assessment

Examiner Last Name

Mnemonic	ALN			Conditionality	M↑
				Status	Active
Description	This information item shall contain the surname (last name) of the fingerprint examiner.				
Field Min	1	Occur Min	1		
Field Max	40	Occur Max	1		
Char Types	U	Special Chars	none		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeValueAssessment	Cardinality	0..1		
XML Level 3	biom_1:MinutiaeExaminer/nc:PersonName/	Cardinality	1..1		
XML Level 4	nc:PersonSurname	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-9 Minutiae Data Record (Extended Feature Set)

Page 447 of 1037

9.353_3

EFS Examiner Analysis Assessment

Examiner First Name

Mnemonic	AFN			Conditionality	M↑
				Status	Active
Description	This information item shall contain the first name (given name, or first and middle names) of the fingerprint examiner.				
Field Min	1	Occur Min	1		
Field Max	40	Occur Max	1		
Char Types	U	Special Chars	none		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeValueAssessment	Cardinality	0..1		
XML Level 3	biom_1:MinutiaeExaminer/nc:PersonName/	Cardinality	1..1		
XML Level 4	nc:PersonGivenName	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.353_4

EFS Examiner Analysis Assessment

Examiner Affiliation

Mnemonic	AAF			Conditionality	M↑
				Status	Active
Description	This information item shall contain the employer or organizational affiliation of the examiner.				
Field Min	1	Occur Min	1		
Field Max	99	Occur Max	1		
Char Types	U	Special Chars	none		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeValueAssessment	Cardinality	0..1		
XML Level 3	biom_1:MinutiaeExaminer/nc:PersonName/	Cardinality	1..1		
XML Level 4	nc:OrganizationName	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.353_5

EFS Examiner Analysis Assessment

Date and Time (GMT)

Mnemonic	AMT			Conditionality	M↑
				Status	Active
Description	This information item shall contain the date and time that the determination was made, using Greenwich Mean Time (GMT).				
Field Min	15	Occur Min	1		
Field Max	15	Occur Max	1		
Char Types	AN	Special Chars	none		
Format	YYYYMMDDHHMMSSZ - for Traditional Encoding			Constraints	Dependent upon encoding
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeValueAssessment			Cardinality	0..1
XML Level 3	biom_1:MinutiaeExaminer/nc:PersonName/			Cardinality	1..1
XML Level 4	biom_1:MinutiaeValueAssessmentDateTime			Cardinality	1..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.353_6

EFS Examiner Analysis Assessment

Comment

Mnemonic	ACM			Conditionality	O↑
				Status	Active
Description	This information item is optional and contains additional clarifying information for the examiner analysis assessment.				
Field Min	1	Occur Min	0		
Field Max	200	Occur Max	1		
Char Types	U	Special Chars	none		
Format	n/a			Constraints	n/a
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeValueAssessment			Cardinality	0..1
XML Level 3	biom_1:MinutiaeExaminer/nc:PersonName/			Cardinality	1..1
XML Level 4	biom_1:MinutiaeCommentText			Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.353_7

EFS Examiner Analysis Assessment

Analysis Complexity Flag

Mnemonic	CXF			Conditionality	0↑		
				Status	Active		
Description	This information item is optional and is only used when the examiner determines that the analysis was complex as defined in Standards for examining friction ridge impressions and resulting conclusions. In that case, an entry of "COMPLEX" is made. This decision is based on the available quality of features, low specificity of features, significant distortion, or disagreement among examiners. This information item is included for use in quality assurance / quality control processes.						
Field Min	7			Occur Min	0		
Field Max	7			Occur Max	1		
Char Types	A			Special Chars	none		
Format	n/a			Constraints	CXF = COMPLEX		
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-9)						
XML Level 1	biom_1:ExtendedFeatureSetMinutiae				Cardinality	0..1	
XML Level 2	biom_1:MinutiaeValueAssessment				Cardinality	0..1	
XML Level 3	biom_1:MinutiaeExaminer/nc:PersonName/				Cardinality	1..1	
XML Level 4	biom_1:MinutiaeAnalysisComplexityCode				Cardinality	0..1	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

9.354

EFS Evidence of Fraud

Mnemonic	EOF			Conditionality	0		
				Status	Active		
Description	This text field indicates that there is basis for determination that the image may be fraudulent.						
Field Min	n/a			Occur Min	0		
Field Max	n/a			Occur Max	1		
Char Types	n/a			Special Chars	n/a		
Format	n/a			Constraints	n/a		
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-9)						
XML Level 1	biom_1:ExtendedFeatureSetMinutiae				Cardinality	0..1	
XML Level 2	biom_1:MinutiaeFraudEvidence				Cardinality	0..1	
XML Level 3					Cardinality		
XML Level 4					Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.354_0

EFS Evidence of Fraud

Subfields: Repeating sets of information items

Mnemonic	EOF_0			Conditionality	M↑
				Status	New - Active
Description	This text field indicates that there is basis for determination that the image may be fraudulent.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	5		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeFraudEvidence			Cardinality	0..5
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.354_1

EFS Evidence of Fraud

Fraud Type

Mnemonic	FRA			Conditionality	M↑
				Status	Active
Description	This information item indicates the potential type of fraud attempted as determined from the impression. See Look Up Codes for valid values.				
Field Min	3	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	A	Special Chars	none		
Format	n/a	Constraints	FRA = EVA, SPO, FOR, or FAB		
Code List	EFS EVIDENCE OF FRAUD TYPE CODES				
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeFraudEvidence			Cardinality	0..5
XML Level 3	biom_1:MinutiaeFraudEvidenceCategoryCode			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.354_2

EFS Evidence of Fraud

Comment

Mnemonic	CFD			Conditionality	0↑
				Status	Active
Description	This information item is optional and contains text that provides clarifying information regarding the assessment of potential evidence of fraud.				
Field Min	1	Occur Min	0		
Field Max	200	Occur Max	1		
Char Types	U	Special Chars	none		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeFraudEvidence	Cardinality	0..5		
XML Level 3	biom_1:MinutiaeCommentText	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.355

EFS Latent Substrate

Mnemonic	LSB			Conditionality	0
				Status	Active
Description	This field is used to define the substrate, or surface on which the friction ridge impression was deposited. If multiple substrates are present, they are represented by separate subfields.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeLatentSubstrate	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.355_0

EFS Latent Substrate

Subfields: Repeating sets of information items

Mnemonic	LSB_0			Conditionality	M↑
				Status	New - Active
Description	This field is used to define the substrate, or surface on which the friction ridge impression was deposited. If multiple substrates are present, they are represented by separate subfields.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	4		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeLatentSubstrate			Cardinality	0..4
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.355_1

EFS Latent Substrate

Code

Mnemonic	CLS			Conditionality	M↑
				Status	Active
Description	This information item indicates the type of substrate. See Look Up Codes for valid values.				
Field Min	1	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	AN	Special Chars	none		
Format	n/a	Constraints	CLS = 1A, 1B, 1C, 1D, 2A, 2B, 2C, 2D, 2E, 2F, 2G, 2H, 2I, 3A, 3B, 3C, 3D, 3E, 3F, 3G, 4A, or 4B		
Code List	EFS LATENT SUBSTRATE CODES				
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeLatentSubstrate			Cardinality	0..4
XML Level 3	biom_1:MinutiaeLatentSubstrateCategoryCode			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.355_2

EFS Latent Substrate

Object / Substrate Description

Mnemonic	OSD			Conditionality	O↑
				Status	Active
Description	This information item is optional and may contain text that describes the object or surface on which the print was deposited, or provides clarifying information regarding the substrate. An example is "Neck of green glass beer bottle".				
Field Min	1	Occur Min	0		
Field Max	1000	Occur Max	1		
Char Types	U	Special Chars	none		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeLatentSubstrate	Cardinality	0..4		
XML Level 3	biom_1:MinutiaeLatentSubstrateDescriptionText	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.356

EFS Latent Matrix

Mnemonic	LMT			Conditionality	O
				Status	Active
Description	This field is used to define the matrix, or substance deposited by the finger that forms the impression. Each latent matrix is represented by a separate data entry (repeating subfield).				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	none		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeLatentMatrix	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.356_0

EFS Latent Matrix

Subfields: Repeating sets of information items

Mnemonic	LMT_0			Conditionality	M↑
				Status	New - Active
Description	This field is used to define the matrix, or substance deposited by the finger that forms the impression. Each latent matrix is represented by a separate data entry (repeating subfield).				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	4		
Char Types	n/a	Special Chars	none		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeLatentMatrix			Cardinality	0..4
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.356_1

EFS Latent Matrix

Code

Mnemonic	TOM			Conditionality	M↑
				Status	Active
Description	This information item is mandatory and indicates the type of matrix. All visible contaminants are apparent rather than necessarily known to certainty: for example, the substrate may be marked as blood if it appears to be blood; if known for certain that should be indicated as a comment. See Look Up Codes for valid values.				
Field Min	1	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	0 <= TOM <=10; non-negative integer		
Code List	EFS LATENT MATRIX CODES				
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeLatentMatrix			Cardinality	0..4
XML Level 3	biom_1:MinutiaeLatentMatrixCategoryCode			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.356_2

EFS Latent Matrix

Comment

Mnemonic	CLA			Conditionality	O↑
				Status	Active
Description	This information item is optional and may contain text that provides clarifying information regarding the matrix.				
Field Min	1	Occur Min	0		
Field Max	1000	Occur Max	1		
Char Types	U	Special Chars	none		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeLatentMatrix	Cardinality	0..4		
XML Level 3	biom_1:MinutiaeCommentText	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.357

EFS Local Quality Issues

Mnemonic	LQI			Conditionality	O
				Status	Active
Description	This optional field is used to define one or more areas containing quality or transfer issues that indicate that the anatomical friction ridge features may not have been accurately represented in the image. Each area with local quality issues is represented as a separate repeating subfield. The problems noted in this field apply to the specific impression under consideration; anatomical features of the friction skin itself (such as scars) are noted in (Field 9.324: EFS distinctive features / DIS).				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeLocalQualityIssues	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.357_0

EFS Local Quality Issues

Subfields: Repeating sets of information items

Mnemonic	LQI_0			Conditionality	M↑
				Status	New - Active
Description	This optional field is used to define one or more areas containing quality or transfer issues that indicate that the anatomical friction ridge features may not have been accurately represented in the image. Each area with local quality issues is represented as a separate repeating subfield. The problems noted in this field apply to the specific impression under consideration; anatomical features of the friction skin itself (such as scars) are noted in (Field 9.324: EFS distinctive features / DIS).				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	*		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0...1
XML Level 2	biom_1:MinutiaeLocalQualityIssues			Cardinality	0..*
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.357_1

EFS Local Quality Issues

Type

Mnemonic	LQT			Conditionality	M↑
				Status	Active
Description	This information item is the type of quality issue. See Look Up Codes for valid values.				
Field Min	4	Occur Min	1		
Field Max	10	Occur Max	1		
Char Types	A	Special Chars	none		
Format	n/a	Constraints	LQT = ARTIFACT, BACKGROUND, COMPRESSED, DISTORT, NEGATIVE, OVERDEV, OVERLAP, SMEAR, STRETCHED, TAPE, OTHER		
Code List	EFS QUALITY ISSUE CODES				
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0...1
XML Level 2	biom_1:MinutiaeLocalQualityIssues			Cardinality	0..*
XML Level 3	biom_1:MinutiaeLocalQualityIssuesCategoryCode			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.357_2

EFS Local Quality Issues

Polygon

Mnemonic	LQP	Conditionality	M↑
		Status	Active
Description	This information item is a closed path outlining the area of the quality issue. In Traditional encoding, the two special characters allowed are hyphen and comma. These special characters are not used in XML Encoding.		
Field Min	11	Occur Min	1
Field Max	1188	Occur Max	1
Char Types	NS	Special Chars	Minus Sign and Comma
Format	n/a	Constraints	n/a
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-9)		
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1
XML Level 2	biom_1:MinutiaeLocalQualityIssues	Cardinality	0..*
XML Level 3	biom_1:ImageSegmentPolygon(1...1)/biom_1:ImageSegmentVertex(3...99)	Cardinality	1..1
XML Level 4	biom_1:ImageLocationHorizontalCoordinateMeasure + biom_1:ImageLocationVerticalCoordinateMeasure	Cardinality	1...1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

9.357_3

EFS Local Quality Issues

Comment

Mnemonic	LQC	Conditionality	O↑
		Status	Active
Description	This information item is optional and may contain text describing the quality issue.		
Field Min	1	Occur Min	0
Field Max	1000	Occur Max	1
Char Types	U	Special Chars	none
Format	n/a	Constraints	n/a
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-9)		
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1
XML Level 2	biom_1:MinutiaeLocalQualityIssues	Cardinality	0..*
XML Level 3	biom_1:MinutiaeCommentText	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.36

EFS Area of Correspondence

Mnemonic	AOC		Conditionality	0			
			Status	Active			
Description	This field is to be used only when two or more images contained in a single EBTS transaction are compared as candidates for individualization (potential mates). The area of correspondence is a polygon enclosing the region of usable ridge detail present in both images being compared. One Type-9 record may have multiple AOCs defined that correspond to different images, each in a separate repeating subfield. Note that the AOC in a given Type-9 record contains an IDC reference for one or more other Type-9 record in a transaction. For example, a latent could have areas of correspondence with both the rolled and plain exemplars from one subject, or a latent could have areas of correspondence with candidate exemplars from two different subjects. If the area of a small print is completely enclosed by the area of a larger print so that the AOC for the small print is identical to the ROI, the AOC may be omitted for the smaller print.						
Field Min	n/a	Occur Min	0				
Field Max	n/a	Occur Max	1				
Char Types	n/a	Special Chars	n/a				
Format	n/a	Constraints	n/a				
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-9)						
XML Level 1	biom_1:ExtendedFeatureSetMinutiae		Cardinality	0..1			
XML Level 2	biom_1:FrictionRidgeImageAreaOfCorrespondence		Cardinality	0..1			
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

9.360_0

EFS Area of Correspondence

Subfields: Repeating sets of information items

Mnemonic	AOC_0		Conditionality	M↑			
			Status	New - Active			
Description	This field is to be used only when two or more images contained in a single EBTS transaction are compared as candidates for individualization (potential mates). The area of correspondence is a polygon enclosing the region of usable ridge detail present in both images being compared. One Type-9 record may have multiple AOCs defined that correspond to different images, each in a separate repeating subfield. Note that the AOC in a given Type-9 record contains an IDC reference for one or more other Type-9 record in a transaction. For example, a latent could have areas of correspondence with both the rolled and plain exemplars from one subject, or a latent could have areas of correspondence with candidate exemplars from two different subjects. If the area of a small print is completely enclosed by the area of a larger print so that the AOC for the small print is identical to the ROI, the AOC may be omitted for the smaller print.						
Field Min	n/a	Occur Min	1				
Field Max	n/a	Occur Max	*				
Char Types	n/a	Special Chars	n/a				
Format	n/a	Constraints	n/a				
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-9)						
XML Level 1	biom_1:ExtendedFeatureSetMinutiae		Cardinality	0..1			
XML Level 2	biom_1:FrictionRidgeImageAreaOfCorrespondence		Cardinality	0..*			
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.360_1

EFS Area of Correspondence

IDC Reference

Mnemonic	CIR			Conditionality	M↑
				Status	Active
Description	This information item indicates the IDC for the target image / Type-9 record for a given AOC.				
Field Min	1	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	0 <= CIR <= 99; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:FrictionRidgeImageAreaOfCorrespondence	Cardinality	0..*		
XML Level 3	biom_1:ImageReferenceIdentification/nc:IdentificationID	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.360_2

EFS Area of Correspondence

Polygon (Closed Path)

Mnemonic	AOP			Conditionality	M↑
				Status	Active
Description	This information item defines the outline of the corresponding area. It is a closed path. In Traditional encoding, the two special characters allowed are hyphen and comma. These special characters are not used in XML Encoding.				
Field Min	11	Occur Min	1		
Field Max	1188	Occur Max	1		
Char Types	NS	Special Chars	Minus Sign and Comma		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:FrictionRidgeImageAreaOfCorrespondence	Cardinality	0..*		
XML Level 3	biom_1:ImageSegmentPolygon(1..1)/biom_1:ImageSegmentVertex(3..99)	Cardinality	1..1		
XML Level 4	biom_1:ImageLocationHorizontalCoordinateMeasure + biom_1:ImageLocationVerticalCoordinateMeasure	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.360_3

EFS Area of Correspondence

Comment

Mnemonic	CAC			Conditionality	O↑
				Status	Active
Description	This information item is optional and allows a free text comment or description related to the AOC.				
Field Min	1	Occur Min	0		
Field Max	1000	Occur Max	1		
Char Types	U	Special Chars	none		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0...1		
XML Level 2	biom_1:FrictionRidgeImageAreaOfCorrespondence	Cardinality	0..*		
XML Level 3	biom_1:MinutiaeCommentText	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.361

EFS Corresponding Points or Features

Mnemonic	CPF			Conditionality	O
				Status	Active
Description	This optional field is used to label points or features for comparison of the current feature set with other Type-9 feature sets in a transaction. This field is to be used only when two or more images contained in a single transaction are compared, either as candidates for individualization (potential mates), or for annotating reasons for exclusion. For each of the images being compared, specific points or features are marked in each of the Type-9 records, with correspondence indicated by the use of the same label, each in a separate data entry (repeating subfield). Labels within a single Type-9 record shall be unique. For example, if a transaction contains one latent and multiple candidate exemplars, a feature labeled "A" in the latent's Type-9 feature set corresponds with the feature labeled "A" (if present) in all of the exemplar Type-9 feature sets. Corresponding Points or Features may refer to arbitrary points, or may refer to predefined features. The features include point features (such as minutiae, dots, or pores), but also may refer to areas (such as distinctive characteristics), lines (incipient ridges or creases), or paths (ridge path segments). Arbitrary points may be used to indicate characteristics that were not noted during analysis, or to indicate points in an exemplar that was not previously marked up.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0...1		
XML Level 2	biom_1:MinutiaeFeatureCorrespondence	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.361_0

EFS Corresponding Points or Features

Subfields: Repeating sets of information items

Mnemonic	CPF_0			Conditionality	M↑
				Status	New - Active
Description	<p>This optional field is used to label points or features for comparison of the current feature set with other Type-9 feature sets in a transaction. This field is to be used only when two or more images contained in a single transaction are compared, either as candidates for individualization (potential mates), or for annotating reasons for exclusion. For each of the images being compared, specific points or features are marked in each of the Type-9 records, with correspondence indicated by the use of the same label, each in a separate data entry (repeating subfield). Labels within a single Type-9 record shall be unique. For example, if a transaction contains one latent and multiple candidate exemplars, a feature labeled "A" in the latent's Type-9 feature set corresponds with the feature labeled "A" (if present) in all of the exemplar Type-9 feature sets. Corresponding Points or Features may refer to arbitrary points, or may refer to predefined features. The features include point features (such as minutiae, dots, or pores), but also may refer to areas (such as distinctive characteristics), lines (incipient ridges or creases), or paths (ridge path segments). Arbitrary points may be used to indicate characteristics that were not noted during analysis, or to indicate points in an exemplar that was not previously marked up.</p>				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	*		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0...1
XML Level 2	biom_1:MinutiaeFeatureCorrespondence			Cardinality	0..*
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.361_1

EFS Corresponding Points or Features

Label

Mnemonic	COL			Conditionality	M↑
				Status	Active
Description	<p>This information item is a mandatory 1-3 character alphanumeric label that is used to indicate correspondence between CPFs in different Type-9 records. The label names may be selected and assigned at the discretion of the system or the examiner. Labels within a single Type-9 record shall be unique. Note that the use of a given label in one Type-9 record means that that point or feature corresponds with any or all other features with the same label in other Type-9 records in the transaction.</p>				
Field Min	1	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	AN	Special Chars	none		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0...1
XML Level 2	biom_1:MinutiaeFeatureCorrespondence			Cardinality	0..*
XML Level 3	biom_1:MinutiaeFeatureIdentification/nc:IdentificationID			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.361_2

EFS Corresponding Points or Features

Type of Correspondence

Mnemonic	TOC			Conditionality	M↑
				Status	Active
Description	This information item is a mandatory 1- or 2-character information item (code) used to indicate the type of correspondence or non-correspondence. See Look Up Codes for valid values.				
Field Min	1	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	A	Special Chars	none		
Format	n/a	Constraints	TOC = F, P, DF, DP, X, R, or U		
Code List	EFS TYPE OF CORRESPONDENCE CODES				
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeFeatureCorrespondence	Cardinality	0..*		
XML Level 3	biom_1:MinutiaeFeatureCorrespondenceCategoryCode	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.361_3

EFS Corresponding Points or Features

Corresponding Field Number

Mnemonic	CFN			Conditionality	D
				Status	Active
Description	This information item is conditional, used only if TOC = F or DF. The Field Number information item indicates the type of field being compared, and shall correspond to the "Field Number." This is the Type-9 field number of the compared field.				
Field Min	3	Occur Min	0		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	CFN = 320, 321, 324, 331, 340, 341, 342, 343, 345, 373		
Code List	EFS CORRESPONDING FIELD NUMBER CODES				
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeFeatureCorrespondence	Cardinality	0..*		
XML Level 3	biom_1:MinutiaeFeatureCategoryCode	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.361_4

EFS Corresponding Points or Features

Corresponding Field Occurance

Mnemonic	FOC			Conditionality	D
				Status	Active
Description	This information item is conditional, used only if TOC = F or DF. This information item indicates which repeating subfield of the specified field the label is applied to. Note that this is a 1-based index, not a 0-based index. Occurrences are numbered starting with 1.				
Field Min	1	Occur Min	0		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	1 <= FOC <= 999; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeFeatureCorrespondence			Cardinality	0..*
XML Level 3	biom_1:MinutiaeFeatureReferenceIdentification/nc:IdentificationID			Cardinality	0..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.361_5

EFS Corresponding Points or Features

Corresponding X Coordinate

Mnemonic	CXC			Conditionality	D
				Status	Active
Description	This information item is mandatory if TOC = P or DP and is optional if TOC = X. It is expressed in units of 10 micrometers (0.01 mm).				
Field Min	1	Occur Min	0		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	1 <= QXC < EWI; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:MinutiaeFeatureCorrespondence			Cardinality	0..*
XML Level 3	biom_1:ImageLocationHorizontalCoordinateMeasure			Cardinality	0..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.361_6

EFS Corresponding Points or Features

Corresponding Y Coordinate

Mnemonic	CYC			Conditionality	D
				Status	Active
Description	This information item is mandatory if TOC = P or DP and is optional if TOC = X. It is expressed in units of 10 micrometers (0.01 mm).				
Field Min	1	Occur Min	0		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	1 <= QYC < EHI; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeFeatureCorrespondence	Cardinality	0..*		
XML Level 3	biom_1:ImageLocationVerticalCoordinateMeasure	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.361_7

EFS Corresponding Points or Features

Comment

Mnemonic	COC			Conditionality	O↑
				Status	Active
Description	This information item is optional and may contain a text comment or description related to the CPF.				
Field Min	1	Occur Min	0		
Field Max	1000	Occur Max	1		
Char Types	U	Special Chars	none		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeFeatureCorrespondence	Cardinality	0..*		
XML Level 3	biom_1:MinutiaeCommentText	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.362

EFS Examiner Comparison Determination

Mnemonic	ECD		Conditionality	0
			Status	Active
Description	This optional text field indicates an examiner's determination based on analysis and comparison of two specified friction ridge images. If multiple examiners' determinations are represented, each is contained separately in a repeating subfield. Comparison determinations against multiple impressions in the same transaction are specified in a separate subfield with distinct IDC references. Each subfield consists of at least seven information items. The eighth and ninth information items are optional.			
Field Min	n/a	Occur Min	0	
Field Max	n/a	Occur Max	1	
Char Types	n/a	Special Chars	n/a	
Format	n/a	Constraints	n/a	
Code List				
Source	ANSI/NIST ITL 1-2013 (Type-9)			
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1	
XML Level 2	biom_1:MinutiaeExaminerComparisonDetermination	Cardinality	0..1	
XML Level 3		Cardinality		
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0 No DoD EBTS 4.0 Yes

9.362_0

EFS Examiner Comparison Determination

Subfields: Repeating sets of information items

Mnemonic	ECD_0		Conditionality	M↑
			Status	Active
Description	This optional text field indicates an examiner's determination based on analysis and comparison of two specified friction ridge images. If multiple examiners' determinations are represented, each is contained separately in a repeating subfield. Comparison determinations against multiple impressions in the same transaction are specified in a separate subfield with distinct IDC references. Each subfield consists of at least seven information items. The eighth and ninth information items are optional.			
Field Min	n/a	Occur Min	0	
Field Max	n/a	Occur Max	*	
Char Types	n/a	Special Chars	n/a	
Format	n/a	Constraints	n/a	
Code List				
Source	ANSI/NIST ITL 1-2013 (Type-9)			
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1	
XML Level 2	biom_1:MinutiaeExaminerComparisonDetermination	Cardinality	0..*	
XML Level 3		Cardinality		
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0 No DoD EBTS 4.0 Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.362_1

EFS Examiner Comparison Determination

IDC Reference

Mnemonic	EDC			Conditionality	M↑
				Status	New - Active
Description	This information item indicates the target image for a given determination, and is used in the same way as the IDC in Field 9.360: EFS area of correspondence / AOC.				
Field Min	1	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	0 <= EDC <= 99; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeExaminerComparisonDetermination	Cardinality	0..*		
XML Level 3	biom_1:ImageReferenceIdentification	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.362_2

EFS Examiner Comparison Determination

Determination

Mnemonic	EDE			Conditionality	M↑
				Status	Active
Description	This information item indicates a comparison conclusion. The allowed special character is the underscore. See Look Up Codes for valid values				
Field Min	4	Occur Min	1		
Field Max	6	Occur Max	1		
Char Types	AS	Special Chars	none		
Format	n/a	Constraints	EDE = INDIV, INC_1, INC_C, INC_D, INC_N, EX_SRC, EX_SUB, NONE		
Code List	EFS EXAMINER COMPARISON DETERMINATION CODES				
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeExaminerComparisonDetermination	Cardinality	0..*		
XML Level 3	biom_1:MinutiaeExaminerComparisonDeterminationResultCode	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.362_3

EFS Examiner Comparison Determination

Work In Progress

Mnemonic	WIP			Conditionality	M↑
				Status	Active
Description	This information item is set to "PRELIMINARY" (default) or "FINAL". For a determination to be accepted for further processing, the status shall be set to "FINAL". The purpose of this is to allow saving work in progress.				
Field Min	5	Occur Min	1		
Field Max	11	Occur Max	1		
Char Types	A	Special Chars	none		
Format	n/a	Constraints	WIP = PRELIMINARY or FINAL		
Code List	EFS EXAMINER COMPARISON DETERMINATION WORK IN PROGRESS CODES				
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0...1		
XML Level 2	biom_1:MinutiaeExaminerComparisonDetermination	Cardinality	0..*		
XML Level 3	biom_1:MinutiaeExaminerComparisonDeterminationResultCode	Cardinality	1..1		
XML Level 4	biom_1:MinutiaeExaminerProgressCode	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.362_4

EFS Examiner Comparison Determination

Examiner Last Name

Mnemonic	ELN			Conditionality	M↑
				Status	Active
Description	This information item is the surname (last name) of the fingerprint examiner.				
Field Min	1	Occur Min	1		
Field Max	40	Occur Max	1		
Char Types	U	Special Chars	none		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0...1		
XML Level 2	biom_1:MinutiaeExaminerComparisonDetermination	Cardinality	0..*		
XML Level 3	biom_1:MinutiaeExaminerComparisonDeterminationResultCode	Cardinality	1..1		
XML Level 4	biom:MinutiaeExaminer/nc:PersonName/nc:PersonSurname	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.362_5

EFS Examiner Comparison Determination

Examiner First Name

Mnemonic	EFN			Conditionality	M↑
				Status	Active
Description	This information item is the given name (first name or first and middle names) of the fingerprint examiner.				
Field Min	1	Occur Min	1		
Field Max	40	Occur Max	1		
Char Types	U	Special Chars	none		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0...1		
XML Level 2	biom_1:MinutiaeExaminerComparisonDetermination	Cardinality	0..*		
XML Level 3	biom_1:MinutiaeExaminerComparisonDeterminationResultCode	Cardinality	1..1		
XML Level 4	biom:MinutiaeExaminer/nc:PersonName/nc:PersonGivenName	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.362_6

EFS Examiner Comparison Determination

Examiner Affiliation

Mnemonic	EAF			Conditionality	M↑
				Status	Active
Description	This information item is the employer or organizational affiliation of the examiner.				
Field Min	1	Occur Min	1		
Field Max	99	Occur Max	1		
Char Types	U	Special Chars	none		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0...1		
XML Level 2	biom_1:MinutiaeExaminerComparisonDetermination	Cardinality	0..*		
XML Level 3	biom_1:MinutiaeExaminerComparisonDeterminationResultCode	Cardinality	1..1		
XML Level 4	biom:MinutiaeExaminer/biom:MinutiaeExaminerAffiliation/nc:OrganizationName	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.362_7

EFS Examiner Comparison Determination

Date and Time (GMT)

Mnemonic	DTG			Conditionality	M↑
				Status	Active
Description	This information item is the date and time that the determination was made, in terms of Greenwich Mean Time units.				
Field Min	15	Occur Min	1		
Field Max	15	Occur Max	1		
Char Types	AN	Special Chars	none		
Format	YYYYMMDDHHMMSSZ - for Traditional Encoding	Constraints	Dependent upon encoding		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeExaminerComparisonDetermination	Cardinality	0..*		
XML Level 3	biom_1:MinutiaeExaminerComparisonDeterminationResultCode	Cardinality	1..1		
XML Level 4	biom_1:MinutiaeExaminerComparisonDeterminationDateTime/nc:Date Time	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.362_8

EFS Examiner Comparison Determination

Comment

Mnemonic	CZZ			Conditionality	O↑
				Status	Active
Description	This information item is optional and may contain text that provides clarifying or qualifying information regarding the comparison determination.				
Field Min	1	Occur Min	0		
Field Max	200	Occur Max	1		
Char Types	U	Special Chars	none		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:MinutiaeExaminerComparisonDetermination	Cardinality	0..*		
XML Level 3	biom_1:MinutiaeExaminerComparisonDeterminationResultCode	Cardinality	1..1		
XML Level 4	biom_1:MinutiaeCommentText	Cardinality	0..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.362_9

EFS Examiner Comparison Determination

Complex Comparison Flag

Mnemonic	CCF		Conditionality	0↑	
			Status	Active	
Description	This information item is optional. It is only used when the examiner determines that the comparison was complex as defined in Standards for examining friction ridge impressions and resulting conclusions based on the available quality and quantity of features, low specificity of features, significant distortion, or disagreement among examiners. In such case, the value shall be set to 'COMPLEX'. This information item is included for use in quality assurance/quality control processes.				
Field Min	7	Occur Min	0		
Field Max	7	Occur Max	1		
Char Types	A	Special Chars	none		
Format	n/a	Constraints	CCF = COMPLEX		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae		Cardinality	0..1	
XML Level 2	biom_1:MinutiaeExaminerComparisonDetermination		Cardinality	0..*	
XML Level 3	biom_1:MinutiaeExaminerComparisonDeterminationResultCode		Cardinality	1..1	
XML Level 4	biom_1:MinutiaeComparisonComplexityCode		Cardinality	0..1	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.363

EFS Relative Rotation of Corresponding Print

Mnemonic	RRC		Conditionality	0	
			Status	Active	
Description	This optional field may be used when two or more images contained in a single EBTS transaction are compared. This field indicates the relative overall rotation necessary for the prints to be compared. Each subfield consists of 2 information items. The number of subfields is limited only by the number of Type-9 records in the transaction.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae		Cardinality	0..1	
XML Level 2	biom_1:FrictionRidgeImageRelativeRotation		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.363_0

EFS Relative Rotation of Corresponding Print

Subfields: Repeating sets of information items

Mnemonic	RRC_0			Conditionality	M↑
				Status	New - Active
Description	This optional field may be used when two or more images contained in a single EBTS transaction are compared. This field indicates the relative overall rotation necessary for the prints to be compared. Each subfield consists of 2 information items. The number of subfields is limited only by the number of Type-9 records in the transaction.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	*		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:FrictionRidgeImageRelativeRotation			Cardinality	0..*
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.363_1

EFS Relative Rotation of Corresponding Print

Rotation IDC Reference

Mnemonic	RIR			Conditionality	M↑
				Status	Active
Description	This information item indicates the IDC for the Type-9 record associated with the target image/ Type-9 record for a given RRC.				
Field Min	1	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	0 <= RIR <= 99; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:FrictionRidgeImageRelativeRotation			Cardinality	0..*
XML Level 3	biom_1:ImageReferenceIdentification/nc:IdentificationID			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.363_2

EFS Relative Rotation of Corresponding Print

Relative Overall Rotation

Mnemonic	ROR			Conditionality	M↑
				Status	Active
Description	This information item defines the integer the number of Type-9 records in the transaction. number of degrees that the target image and/or features referenced by RIR shall be rotated to correspond to the data in this Type-9 record. Positive numbers indicate degrees counterclockwise; negative numbers indicate degrees clockwise: (-179 to 180 inclusive). The allowed special character is the negative sign.				
Field Min	1	Occur Min	1		
Field Max	4	Occur Max	1		
Char Types	NS	Special Chars	Minus Sign		
Format	n/a	Constraints	-179 <= ROR <= 180; integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:FrictionRidgeImageRelativeRotation			Cardinality	0..*
XML Level 3	biom_1:ImageRelativeOverallRotationValue			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.372

EFS Skeletonized Image

Mnemonic	SIM			Conditionality	O
				Status	Active
Description	This optional field contains a skeletonized image, also known as a ridge tracing, which reduces the friction ridge impression to an image with thinned representations of each ridge. Incipient ridges, dots, ridge discontinuities, and protrusions are not in the skeleton. The skeletonized image is a 2-tone image with a white background and a black single-pixelwide thinned representation of each ridge. Each black pixel may have 1, 2, or 3 neighboring black pixels; other values (0, 4-8) are errors. The same information may alternatively be represented using Field 9.373: EFS ridge path segments / RPS. Field 9.373: EFS ridge path segments / RPS. The skeletonized image is stored as a 1-bit grayscale PNG compressed image, bit-packed 6 bits per character using Base-64 representation. The entire PNG formatted image is included as a single data entry / information item. Interlacing, alpha transparency, and color palettes shall not be used. The skeletonized image's dimensions shall be identical width and height of the ROI (See Field 9.300: EFS region of interest / ROI). The resolution of the skeletonized image shall be the same as the original image, and shall be set in the PNG header.				
Field Min	8	Occur Min	0		
Field Max	Unlimited	Occur Max	1		
Char Types	Base 64	Special Chars	none		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:FrictionRidgeSkeletonizedImageBinaryObject			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.373

EFS Ridge Path Segments

Mnemonic	RPS	Conditionality	0
		Status	Active
Description	<p>This optional field contains an alternate representation of the same skeletonized image data contained in Field 9.372: EFS skeletonized image / SIM. Each ridge path segment is saved as an open path (ordered set of vertices). Multiple segments may be included in this field. Incipient ridges, dots, ridge discontinuities, and protrusions are not included in the ridge path representation. Each skeletonized ridge segment is stored as a separate subfield. Each endpoint of a ridge segment is either shared by three ridge segments (at a bifurcation) or is unique to a single ridge segment (at a ridge ending). Each ridge path segment (if completely visible) is the portion of a ridge that connects two minutiae, so each ridge path segment starts and stops either where the ridge intersects another ridge path segment (a bifurcation) or ends (a ridge ending). In the infrequent case in which a ridge segment forms a complete loop back on itself without intersecting another ridge segment (such as near the core of some plain whorls or central pocket loops), the ridge path starts and stops at a single arbitrary point on the ridge. Ridge path segments may not be visible over their entire length due to image consistency-of-presentation problems or due to being truncated by the edge of the impression, and therefore one or both ends of a ridge segment may not end at points defined as minutiae.</p>		
Field Min	n/a	Occur Min	3
Field Max	n/a	Occur Max	99
Char Types	n/a	Special Chars	n/a
Format	n/a	Constraints	n/a
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-9)		
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1
XML Level 2	biom_1:MinutiaeImageRidgePathRepresentation	Cardinality	0..1
XML Level 3	biom_1:MinutiaeRidgePathSegment	Cardinality	1..*
XML Level 4	biom_1:ImageSegmentVertex(3...99)/biom_1:ImageLocationHorizontalCoordinateMeasure + biom_1:ImageLocationVerticalCoordinateMeasure(1....1)	Cardinality	3..99
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.373_0

EFS Ridge Path Segments

Subfields: Repeating sets of information items

Mnemonic	RPS_0		Conditionality	M↑
			Status	New - Active
Description	<p>This optional field contains an alternate representation of the same skeletonized image data contained in Field 9.372: EFS skeletonized image / SIM. Each ridge path segment is saved as an open path (ordered set of vertices). Multiple segments may be included in this field. Incipient ridges, dots, ridge discontinuities, and protrusions are not included in the ridge path representation. Each skeletonized ridge segment is stored as a separate subfield. Each endpoint of a ridge segment is either shared by three ridge segments (at a bifurcation) or is unique to a single ridge segment (at a ridge ending). Each ridge path segment (if completely visible) is the portion of a ridge that connects two minutiae, so each ridge path segment starts and stops either where the ridge intersects another ridge path segment (a bifurcation) or ends (a ridge ending). In the infrequent case in which a ridge segment forms a complete loop back on itself without intersecting another ridge segment (such as near the core of some plain whorls or central pocket loops), the ridge path starts and stops at a single arbitrary point on the ridge. Ridge path segments may not be visible over their entire length due to image consistency-of-presentation problems or due to being truncated by the edge of the impression, and therefore one or both ends of a ridge segment may not end at points defined as minutiae.</p>			
Field Min	7	Occur Min	3	
Field Max	1188	Occur Max	100	
Char Types	NS	Special Chars	Comma and Dash	
Format	n/a	Constraints	n/a	
Code List				
Source	ANSI/NIST ITL 1-2013 (Type-9)			
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1	
XML Level 2	biom_1:MinutiaeImageRidgePathRepresentation	Cardinality	0..2	
XML Level 3	biom_1:MinutiaeRidgePathSegment	Cardinality	1..*	
XML Level 4	biom_1:ImageSegmentVertex(3...100)/biom_1:ImageLocationHorizontalCoordinateMeasure + biom_1:ImageLocationVerticalCoordinateMeasure(1...1)	Cardinality	3..100	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0 No
				DoD EBTS 4.0 Yes

9.38

EFS Temporary Lines

Mnemonic	TPL		Conditionality	O
			Status	Active
Description	<p>This field is used by a latent examiner to annotate a friction ridge image with temporary lines, generally for use as reference points in making a comparison. These lines are solely for the individual examiner's use and reference – there are no implied semantics through the use of this field. This field has subfields, each of which describes a line segment.</p>			
Field Min	n/a	Occur Min	0	
Field Max	n/a	Occur Max	1	
Char Types	n/a	Special Chars	n/a	
Format	n/a	Constraints	n/a	
Code List				
Source	ANSI/NIST ITL 1-2013 (Type-9)			
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1	
XML Level 2	biom_1:EFSTemporaryLine	Cardinality	0..1	
XML Level 3		Cardinality		
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0 No
				DoD EBTS 4.0 Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.380_0

EFS Temporary Lines

Subfields: Repeating sets of information items

Mnemonic	TPL_0			Conditionality	M↑
				Status	New - Active
Description	This field is used by a latent examiner to annotate a friction ridge image with temporary lines, generally for use as reference points in making a comparison. These lines are solely for the individual examiner's use and reference – there are no implied semantics through the use of this field. This field has subfields, each of which describes a line segment.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	100		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:EFSTemporaryLine			Cardinality	0..100
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.380_1

EFS Temporary Lines

X Coordinate Point A

Mnemonic	TXA			Conditionality	M↑
				Status	Active
Description	This information item is expressed in units of 10 micrometers (0.01 mm).				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	0 <= TXA < HLL; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:EFSTemporaryLine			Cardinality	0..100
XML Level 3	biom_1:ImageLocationHorizontalCoordinateMeasure			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-9 Minutiae Data Record (Extended Feature Set)

Page 476 of 1037

9.380_2

EFS Temporary Lines

Y Coordinate Point A

Mnemonic	TYA			Conditionality	M↑
				Status	Active
Description	This information item is expressed in units of 10 micrometers (0.01 mm).				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	0 <= TYA < VLL; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:EFSTemporaryLine	Cardinality	0..100		
XML Level 3	biom_1:ImageLocationVerticalCoordinateMeasure	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.380_3

EFS Temporary Lines

X Coordinate Point B

Mnemonic	TXB			Conditionality	M↑
				Status	Active
Description	This information item is expressed in units of 10 micrometers (0.01 mm).				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	0 <= TXB < HLL; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:EFSTemporaryLine	Cardinality	0..100		
XML Level 3	biom_1:ImageLocationHorizontalCoordinateMeasure	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.380_4

EFS Temporary Lines

Y Coordinate Point B

Mnemonic	TYB			Conditionality	M↑
				Status	Active
Description	This information item is expressed in units of 10 micrometers (0.01 mm).				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	0 <= TYB < VLL; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:EFSTemporaryLine	Cardinality	0..100		
XML Level 3	biom_1:ImageLocationVerticalCoordinateMeasure	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.380_5

EFS Temporary Lines

Line Color

Mnemonic	TLC			Conditionality	M↑
				Status	Active
Description	This information item is an RGB color value expressed as a hexadecimal number. There shall be a total of 6 hexadecimal characters, with leading zeros where applicable.				
Field Min	1	Occur Min	1		
Field Max	6	Occur Max	1		
Char Types	H	Special Chars	none		
Format	n/a	Constraints	000000 <= TLC <= FFFFFFFF		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:EFSTemporaryLine	Cardinality	0..100		
XML Level 3	biom_1:FeatureLineColorValue	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.380_6

EFS Temporary Lines

Line Thickness

Mnemonic	TLT			Conditionality	M↑
				Status	Active
Description	This information item is expressed as a positive integer. Thickness is expressed in units of 0.01 mm. Any value from and including 1 through and including 99 is acceptable; suggested values are 3 (thin); 6 (medium); 9 (thick), and 15 (bold).				
Field Min	1	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	1 <= TLT <= 999; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:EFSTemporaryLine			Cardinality	0..100
XML Level 3	biom_1:FeatureLineThicknessValue			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.381

EFS Feature Color

Mnemonic	FCC			Conditionality	O
				Status	Active
Description	This field enables a latent print examiner to annotate individual features with color for display and / or comment. It consists of multiple subfields, each containing four information items. The first two information items are mandatory. One or both of the third or fourth information items shall be present in each subfield.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:EFSFeatureColor			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.381_0

EFS Feature Color

Subfields: Repeating sets of information items

Mnemonic	FCC_0			Conditionality	M↑
				Status	New - Active
Description	This field enables a latent print examiner to annotate individual features with color for display and / or comment. It consists of multiple subfields, each containing four information items. The first two information items are mandatory. One or both of the third or fourth information items shall be present in each subfield.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1000		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:EFSFeatureColor			Cardinality	0..1000
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.381_1

EFS Feature Color

Feature - Field Number

Mnemonic	FTF			Conditionality	M↑
				Status	Active
Description	This information item indicates the field which is annotated with color for display and / or comment. See Look Up Codes for valid values.				
Field Min	3	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	FTF = 320, 321, 324, 331, 340, 341, 342, 343, 345, 373		
Code List	EFS CORRESPONDING FIELD NUMBER CODES				
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae			Cardinality	0..1
XML Level 2	biom_1:EFSFeatureColor			Cardinality	0..1000
XML Level 3	biom_1:FeatureColorFieldReferencedCode			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.381_2

EFS Feature Color

Feature - Field Occurrence

Mnemonic	FTO			Conditionality	M↑
				Status	Active
Description	This information item indicates which repeating subfield of the specified field the label is applied to. Occurrences are numbered starting with 1 (1-based index, not a 0-based index).				
Field Min	1	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	none		
Format	n/a	Constraints	1 <= FTO <= 999; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:EFSFeatureColor	Cardinality	0..1000		
XML Level 3	biom_1:FeatureColorFieldOccurrenceReferenced	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.381_3

EFS Feature Color

Feature- Color

Mnemonic	FTC			Conditionality	D
				Status	Active
Description	This information item is an RGB color value expressed as a hexadecimal number. There shall be a total of 6 hexadecimal characters, with leading zeros where applicable.				
Field Min	6	Occur Min	0		
Field Max	6	Occur Max	1		
Char Types	H	Special Chars	none		
Format	n/a	Constraints	000000 <= TLC <= FFFFFFFF		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:EFSFeatureColor	Cardinality	0..1000		
XML Level 3	biom_1:FeatureColorHexidecimalValue	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.381_4

EFS Feature Color

Feature - Comment

Mnemonic	COM			Conditionality	D
				Status	Active
Description	This information item allows a free text comment or description to be provided by the examiner about the referenced field and subfield in this instance of a Type-9 record.				
Field Min	1	Occur Min	0		
Field Max	1000	Occur Max	1		
Char Types	U	Special Chars	none		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ExtendedFeatureSetMinutiae	Cardinality	0..1		
XML Level 2	biom_1:EFSFeatureColor	Cardinality	0..1000		
XML Level 3	biom_1:FeatureColorCommentText	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

9.901

Universal Latent Annotation

Mnemonic	ULA			Conditionality	O
				Status	Active
Description	This optional field is used to store annotation, logging, or processing information associated with the FBI-developed Universal Latent Workstation (ULW) or compatible software. If present, this text field shall consist of one or more entries, each with up to 300 characters that describe a single processing step. Each entry shall begin with the date and time followed by a hyphen encoded as: "{M}M/{D}D/YYYY {h}h:mm:ss {AM PM}" The remainder of the entry shall contain an unformatted text string describing a process or procedure applied to the fingerprint, palmprint, or plantar print associated with this Type-9 record. Additional entries may be included, each describing a subsequent processing step.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	*		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:MinutiaeUniversalLatentWorkstationAnnotationText	Cardinality	0..*		
XML Level 2		Cardinality			
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.901_0

Universal Latent Annotation

Subfields: Repeating sets of information items

Mnemonic	ULA_0		Conditionality	M↑
			Status	New - Active
Description	This optional field is used to store annotation, logging, or processing information associated with the FBI-developed Universal Latent Workstation (ULW) or compatible software. If present, this text field shall consist of one or more entries, each with up to 300 characters that describe a single processing step. Each entry shall begin with the date and time followed by a hyphen encoded as: "{M}M/{D}D/YYYY {h}h:mm:ss {AM PM}" The remainder of the entry shall contain an unformatted text string describing a process or procedure applied to the fingerprint, palmprint, or plantar print associated with this Type-9 record. Additional entries may be included, each describing a subsequent processing step.			
Field Min	22	Occur Min	0	
Field Max	300	Occur Max	*	
Char Types	ANS	Special Chars	none	
Format	{M}M/{D}D/YYYY {h}h:mm:ss {AM PM} - <free form text>	Constraints	date concatenated with text	
Code List				
Source	ANSI/NIST ITL 1-2013 (Type-9)			
XML Level 1	biom_1:MinutiaeUniversalLatentWorkstationAnnotationText	Cardinality	0..*	
XML Level 2		Cardinality		
XML Level 3		Cardinality		
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0 Yes
				DoD EBTS 4.0 Yes

9.902

Annotated Information

Mnemonic	ANN		Conditionality	0
			Status	Active
Description	This optional field is used to store annotation, logging, or processing information associated with one or more processing algorithms, processes, or latent workstations (other than the FBI-developed ULW). If present, this text shall consist of one or more subfields comprised of a set of information items. Four mandatory items comprise a subfield.			
Field Min	n/a	Occur Min	0	
Field Max	n/a	Occur Max	1	
Char Types	n/a	Special Chars	n/a	
Format	n/a	Constraints	n/a	
Code List				
Source	ANSI/NIST ITL 1-2013 (Type-9)			
XML Level 1	biom_1:ProcessAnnotation	Cardinality	0.1	
XML Level 2		Cardinality		
XML Level 3		Cardinality		
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0 Yes
				DoD EBTS 4.0 Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.902_0

Annotated Information

Subfields: Repeating sets of information items

Mnemonic	ANN_0			Conditionality	M↑
				Status	New - Active
Description	This optional field is used to store annotation, logging, or processing information associated with one or more processing algorithms, processes, or latent workstations (other than the FBI-developed ULW). If present, this text shall consist of one or more subfields comprised of a set of information items. Four mandatory items comprise a subfield.				
Field Min	n/a			Occur Min	0
Field Max	n/a			Occur Max	*
Char Types	n/a			Special Chars	n/a
Format	n/a			Constraints	n/a
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ProcessAnnotation			Cardinality	0..*
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

9.902_1

Annotated Information

Greenwich Mean Time

Mnemonic	GMT			Conditionality	M↑
				Status	Active
Description	This information item is the Greenwich Mean Time (GMT) when the processing occurred. The data is formatted as YYYYMMDDhhmmssZ, where the Z is indicates the zone description of 0 hours. Time (GMT) units. This time is independent of the actual time zone where the time and date is recorded.				
Field Min	15			Occur Min	1
Field Max	15			Occur Max	1
Char Types	AN			Special Chars	None
Format	YYYYMMDDHHMMSSZ - for Traditional Encoding			Constraints	Dependent upon encoding
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ProcessAnnotation			Cardinality	0..*
XML Level 2	biom_1:ProcessUTCDate/nc:DateTime			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.902_2

Annotated Information

Processing Algorithm Name / Version

Mnemonic	NAV			Conditionality	M↑
				Status	Active
Description	This information item shall contain text identifying the name and version of the processing algorithm, application, procedure, or workstation.				
Field Min	1	Occur Min	1		
Field Max	Unlimited	Occur Max	1		
Char Types	U	Special Chars	n/a		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ProcessAnnotation			Cardinality	0..*
XML Level 2	biom_1:ProcessName			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

9.902_3

Annotated Information

Algorithm Owner

Mnemonic	OWN			Conditionality	M↑
				Status	Active
Description	This information item shall contain an unformatted text string of up to 64 characters with the contact information for the organization that owns the processing algorithm or latent workstation. Where there is no 'algorithm owner,' enter N/A.				
Field Min	1	Occur Min	1		
Field Max	64	Occur Max	1		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ProcessAnnotation			Cardinality	0..*
XML Level 2	biom_1:ProcessOwnerText			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.902_4

Annotated Information

Process Description

Mnemonic	PRO			Conditionality	M↑
				Status	Active
Description	This information item field shall contain text describing a process or procedure applied to the sample in this Type-9 record.				
Field Min	1	Occur Min	1		
Field Max	Unlimited	Occur Max	1		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:ProcessAnnotation	Cardinality	0..*		
XML Level 2	biom_1:ProcessDescriptionText	Cardinality	1..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

9.903

Device Unique Identifier

Mnemonic	DUI			Conditionality	0
				Status	Active
Description	The DUI shall contain a string uniquely identifying the device or source of the data. This field shall be one of the following: a Host PC MAC address (identified by the first character "M"), a Host PC processor ID (identified by the first character "P").				
Field Min	13	Occur Min	0		
Field Max	16	Occur Max	1		
Char Types	ANS	Special Chars	Any		
Format	n/a	Constraints	First character = M or P		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:BiometricCaptureDetail	Cardinality	0..1		
XML Level 2	biom_1:CaptureDeviceIdentification/nc:IdentificationID	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

9.904

Make/Model/Serial Number

Mnemonic	MMS	Conditionality	0
		Status	Active
Description	The MMS contains the make, model and serial number for the capture device. It shall consist of three information items. Each information item shall be 1 to 50 characters. Unknown information may be indicated with the value "0." Any or all information items may indicate that information is unknown with the value "0".		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	n/a
Format	n/a	Constraints	n/a
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-9)		
XML Level 1	biom_1:BiometricCaptureDetail	Cardinality	0..1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

9.904_1

Make/Model/Serial Number

Make

Mnemonic	MAK	Conditionality	M↑
		Status	Active
Description	The name of the manufacturer for the capture device.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	Any
Format	n/a	Constraints	"0" = Unknown
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-9)		
XML Level 1	biom_1:BiometricCaptureDetail	Cardinality	0..1
XML Level 2	biom_1:CaptureDeviceMakeText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-9 Minutiae Data Record (Common)

Page 487 of 1037

9.904_2

Make/Model/Serial Number

Model

Mnemonic	MOD			Conditionality	M↑
				Status	Active
Description	The model number for the capture device.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints	"0" = Unknown		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:BiometricCaptureDetail	Cardinality	0..1		
XML Level 2	biom_1:CaptureDeviceModelText	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

9.904_3

Make/Model/Serial Number

Serial Number

Mnemonic	SER			Conditionality	M↑
				Status	Active
Description	The serial number for the capture device.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints	"0" = Unknown		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-9)				
XML Level 1	biom_1:BiometricCaptureDetail	Cardinality	0 1		
XML Level 2	biom_1:CaptureDeviceSerialNumberText	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.001

Record Header

Mnemonic	LEN	Conditionality	M
		Status	Active
Description	The record header appears as the first field (xx.001) in each Record Type. It contains information particular to the encoding format chosen, in order to enable proper reading of the record. In Traditional encoding, this field contains the record length in bytes (including all information separators). In NIEM-conformant XML encoding, this field contains the RecordCategoryCode, which is the numeric representation of the Record Type.		
Field Min	T = 4; X = 1	Occur Min	1
Field Max	T = 8; X = 2	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	positive integer
Code List			
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	nist-itl:RecordCategoryCode	Cardinality	1...1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

10.002

Information Designation Character

Mnemonic	IDC	Conditionality	M
		Status	Active
Description	Each of the records present in a transaction, with the exception of the Type-1 record, shall include a field (xx.002) containing the information designation character / IDC. The value of the IDC shall be a sequentially assigned positive integer starting from zero and incremented by one up to a maximum of 99. IDC references are stated in Type-1 Field 1.003 Transaction content / CNT and shall be used to relate information items. Two or more records may share a single IDC solely to identify and link together records that pertain to different representations of the same biometric trait.		
Field Min	1	Occur Min	1
Field Max	2	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	0 <= IDC <= 99; integer
Code List			
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	nist-itl:ImageReferenceIdentification/nc:IdentificationID	Cardinality	1...1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.003

Image Type

Mnemonic	IMT		Conditionality	M
			Status	Active
Description	Indicate the type of image contained in the Type-10 record. Note that patterned injuries may be on any part of the body. Patterned injuries are not treated as a separate image type.			
Field Min	4	Occur Min	1	
Field Max	11	Occur Max	1	
Char Types	AS	Special Chars	Blank, Hyphen	
Format	n/a	Constraints	see Look Up Codes	
Code List	TYPE 10 IMAGE TYPES			
Source	ANSI/NIST ITL 2011: (Update 2013)			
XML Level 1	(ITL)biom:BiometricCaptureType	Cardinality	1..1	
XML Level 2	(ITL)biom:ImageCategoryCode	Cardinality	1..1	
XML Level 3		Cardinality		
XML Level 4		Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0 Yes DoD EBTS 4.0 Yes

10.004

Source Agency

Mnemonic	SRC		Conditionality	M
			Status	Active
Description	This is the identifier of the agency that actually created the record and supplied the information contained in it.			
Field Min	1	Occur Min	1	
Field Max	Unlimited	Occur Max	1	
Char Types	U	Special Chars	Any	
Format	n/a	Constraints		
Code List				
Source	ANSI/NIST ITL 2011: (Update 2013)			
XML Level 1	(ITL)biom:FacelImage/(ITL)biom:ImageCaptureDetail or (ITL)biom:PhysicalFeatureImage/(ITL)biom:ImageCaptureDetail	Cardinality	1..1	
XML Level 2	(ITL)biom:CaptureOrganization	Cardinality	1..1	
XML Level 3	nc:OrganizationIdentification/nc:IdentificationID	Cardinality	1..1	
XML Level 4		Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0 Yes DoD EBTS 4.0 Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.005

Photo Capture Date

Mnemonic	PHD			Conditionality	M
				Status	Active
Description	This mandatory field shall contain the date that the image contained in the record was captured.				
Field Min	Dependent on encoding		Occur Min	1	
Field Max	Dependent on encoding		Occur Max	1	
Char Types	N		Special Chars	None	
Format	YYYYMMDD		Constraints		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage/(ITL)biom:ImageCaptureDetail or (ITL)biom:PhysicalFeatureImage/(ITL)biom:ImageCaptureDetail			Cardinality	1..1
XML Level 2	(ITL)biom:CaptureDate/nc:Date			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

10.006

Horizontal Line Length

Mnemonic	HLL			Conditionality	M
				Status	Active
Description	HLL defines the number of pixels contained on a single horizontal line of the image. The maximum horizontal size is limited to 65,535 pixels in Record Types-4 and 8, and to 99,999 for other record types. The minimum value is 10 pixels. The total image size (HLL times VLL) must be able to be accommodated in Field xx.001 for Traditional encoding.				
Field Min	2		Occur Min	1	
Field Max	5		Occur Max	1	
Char Types	N		Special Chars	None	
Format	n/a		Constraints	10 <= HLL <= 99999; positive integer	
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage or (ITL)biom:PhysicalFeatureImage			Cardinality	1..1
XML Level 2	(ITL)biom:ImageHorizontalLineLengthPixelQuantity			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.007

Vertical Line Length

Mnemonic	VLL	Conditionality	M
		Status	Active
Description	VLL defines the number of horizontal lines contained in the image. The maximum vertical size is limited to 65,535 pixels in Record Types-4 and 8, and to 99,999 for other record types. The minimum value is 10 pixels.		
Field Min	2	Occur Min	1
Field Max	5	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	10 <= HLL <= 99999; positive integer
Code List			
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	(ITL)biom:FacelImage or (ITL)biom:PhysicalFeatureImage	Cardinality	1..1
XML Level 2	(ITL)biom:ImageVerticalLineLengthPixelQuantity	Cardinality	1..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

10.008

Scale Units

Mnemonic	SLC	Conditionality	M
		Status	Active
Description	The image sampling frequency (pixel density). A value of "1" shall indicate pixels per inch. A value of "2" shall indicate pixels per centimeter. A value of "0" in this field indicates that no scale is provided, and the quotient of THPS/TVPS shall provide the pixel aspect ratio.		
Field Min	1	Occur Min	1
Field Max	1	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	0 <= SLC <= 2; integer
Code List	SCALE UNIT CODE		
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	(ITL)biom:FacelImage or (ITL)biom:PhysicalFeatureImage	Cardinality	1..1
XML Level 2	(ITL)biom:ImageScaleUnitsCode	Cardinality	1..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.009

Transmitted Horizontal Pixel Scale

Mnemonic	THPS			Conditionality	M
				Status	Active
Description	This is the integer pixel density used in the horizontal direction of the image if SLC has a value of "1" or "2". If SLC has a value of "0", this information item shall contain the horizontal component of the pixel aspect ratio, up to 5 integer digits. For example, if the SLC value = 1, then the value of THPS could be '1000' for a 1000 ppi sensor. When using certain formats, such as PNG, conversion from ppm (or other scales) may result in a decimal value. Since these fields require integer values, rounding should be used.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	positive integer		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage or (ITL)biom:PhysicalFeatureImage			Cardinality	1..1
XML Level 2	(ITL)biom:ImageHorizontalPixelDensityValue			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

10.01

Transmitted Vertical Pixel Scale

Mnemonic	TVPS			Conditionality	M
				Status	Active
Description	This is the integer pixel density used in the vertical direction of the image if SLC has a value of "1" or "2". If SLC has a value of "0", this information item shall contain the vertical component of the pixel aspect ratio, up to 5 integer digits. If SLC is 1 or 2, then TVPS shall equal THPS. When using certain formats, such as PNG, conversion from ppm (or other scales) may result in a decimal value. Since these fields require integer values, rounding up at .5 should be used.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	positive integer		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage or (ITL)biom:PhysicalFeatureImage			Cardinality	1..1
XML Level 2	(ITL)biom:ImageVerticalPixelDensityValue			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.011

Compression Algorithm

Mnemonic	CGA			Conditionality	M
				Status	Active
Description	<p>This is a mandatory field. It shall specify the algorithm used to compress the transmitted color or grayscale images. For those images that are to be compressed, the method for the compression of facial and SMT images is specified by the baseline mode of the JPEG, JPEG 2000, or PNG algorithms. When Record Type-10 contains a facial image, the conditions described in ANSI NIST 2011: Update 2011 Annex E: E.6.1 Compression algorithm apply. For non-facial images contained in Record Type-10, Field 10.011: Compression algorithm / CGA may be set to any value in the COMPRESSION Code List except WSQ20. WSQ is not supported. The image shall be represented as an array of n rows by m columns by at least 8-bit pixels. Each pixel in a monochrome image shall be represented by eight or more bits. Color images shall be represented as a series of sequential samples of a red, green, and blue intensity for each pixel. The image shall be organized in row-major order, with the lowest address corresponding to the upper left corner of the image.</p>				
Field Min	3	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	AN	Special Chars	None		
Format	n/a	Constraints			
Code List	COMPRESSION CODES				
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage or (ITL)biom:PhysicalFeatureImage			Cardinality	1..1
XML Level 2	(ITL)biom:ImageCompressionAlgorithmText			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

10.012

Color Space

Mnemonic	CSP	Conditionality	M
		Status	Active
Description	Scanned images shall consist of nominal 24 to 48-bit RGB pixels. Color image data may be transmitted in either compressed or uncompressed form in certain record types. The transmission of uncompressed color images shall consist of RGB pixels, each component of which shall be quantized to at least 256 levels (8 bits). Grayscale image data may be transmitted in either compressed or uncompressed form. The transmission of uncompressed grayscale images shall consist of pixels, each of which shall normally be quantized to eight bits (256 gray levels) and held in a single unsigned byte. Black and white (binary representation) image data may be transmitted in either compressed or uncompressed form. The uncompressed binary images shall consist of pixels, each of which shall be quantized to one of two levels (binary representation). A value of zero shall be used to represent a white pixel and a value of one shall be used to represent a black pixel. See ANSI/NIST ITL 1-2011, section on Color, black-and-white, and grayscale image requirements for detail. To ensure that color images exchanged between differing systems can be correctly displayed or printed, images should be converted to the device-independent color space, sRGB, before compression or transmission to another system.		
Field Min	3	Occur Min	1
Field Max	4	Occur Max	1
Char Types	A	Special Chars	None
Format	n/a	Constraints	see Look Up Codes
Code List	COLOR SPACE CODE		
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	(ITL)biom:FacelImage or (ITL)biom:PhysicalFeatureImage	Cardinality	1..1
XML Level 2	biom:ImageColorSpaceCode	Cardinality	1..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

10.013

Subject Acquisition Profile

Mnemonic	SAP	Conditionality	D
		Status	Active
Description	To provide a general description of the criteria under which the facial image was captured. Typically, the higher the value, the stronger the acquisition requirements become. Therefore, in the text below, the SAP value will also be denoted as a "level". The Subject Acquisition Profile (SAP) is a mandatory ASCII text field when [Type-10 Image Type field 10.003] contains "FACE".		
Field Min	1	Occur Min	0
Field Max	2	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	see Look Up Codes
Code List	SUBJECT ACQUISITION PROFILES - FACE		
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	(ITL)biom:FacelImage or (ITL)biom:PhysicalFeatureImage	Cardinality	1..1
XML Level 2	(ITL)biom:FacelImageAcquisitionProfileCode	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

10.014

Face Image Bounding Box Coordinates in Full Image

Mnemonic	FIP		Conditionality	D
			Status	Active
Description	If the face image (IMT='FACE') contains more than one face, or is not cropped to a "head only" or "head and shoulders" composition, this optional field contains offsets to the location of the bounding box of the face of the subject within a larger image. This field is only appropriate for images that do not comply with SAP Levels 30, 32, 40, 42, 50, 51 or 52, because those images shall be cropped to a "head only" or "head and shoulders" composition. If the image contains more than one face, the bounding box indicates the face of interest; all associated Type-10 fields are limited to the face defined by the bounding box in the larger image.			
Field Min	n/a	Occur Min	0	
Field Max	n/a	Occur Max	1	
Char Types	N	Special Chars	n/a	
Format	n/a	Constraints		
Code List				
Source	ANSI/NIST ITL 2011: (Update 2013)			
XML Level 1	(ITL)biom:FacelImage	Cardinality	1..1	
XML Level 2	(ITL)biom:FacelImageBoundingSquare	Cardinality	0..1	
XML Level 3	(ITL)biom:FacelImageBoundingSquare	Cardinality	0..1	
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0 Yes
				DoD EBTS 4.0 Yes

10.014_1

Face Image Bounding Box Coordinates in Full Image

Left Horizontal Coordinate Value

Mnemonic	LHC		Conditionality	M↑
			Status	Active
Description	It is the horizontal offset in pixels to the left edge of the bounding box relative to the origin positioned in the upper left corner of the image.			
Field Min	1	Occur Min	1	
Field Max	5	Occur Max	1	
Char Types	N	Special Chars	n/a	
Format	n/a	Constraints	0 < LHC < HLL	
Code List				
Source	ANSI/NIST ITL 2011: (Update 2013)			
XML Level 1	(ITL)biom:FacelImage	Cardinality	1..1	
XML Level 2	(ITL)biom:FacelImageBoundingSquare	Cardinality	0..1	
XML Level 3	(ITL)biom:SegmentLeftHorizontalCoordinateValue	Cardinality	1..1	
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0 Yes
				DoD EBTS 4.0 Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.014_2

Face Image Bounding Box Coordinates in Full Image

Right Horizontal Coordinate Value

Mnemonic	RHC	Conditionality	M↑
		Status	Active
Description	It is the horizontal offset in pixels to the right edge of the bounding box relative to the origin positioned in the upper left corner of the image.		
Field Min	1	Occur Min	1
Field Max	5	Occur Max	1
Char Types	N	Special Chars	n/a
Format	n/a	Constraints	0 < RHC < LLL, RHC > LHC
Code List			
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	(ITL)biom:FacelImage	Cardinality	1..1
XML Level 2	(ITL)biom:FacelImageBoundingSquare	Cardinality	0..1
XML Level 3	(ITL)biom:SegmentRightHorizontalCoordinateValue	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

10.014_3

Face Image Bounding Box Coordinates in Full Image

Top Vertical Coordinate Value

Mnemonic	TVC	Conditionality	M↑
		Status	Active
Description	The vertical offset (pixel counts down) to the top of the bounding box.		
Field Min	1	Occur Min	1
Field Max	5	Occur Max	1
Char Types	N	Special Chars	n/a
Format	n/a	Constraints	0 < BVC < VLL, BVC > TVC
Code List			
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	(ITL)biom:FacelImage	Cardinality	1..1
XML Level 2	(ITL)biom:FacelImageBoundingSquare	Cardinality	0..1
XML Level 3	(ITL)biom:SegmentTopVerticalCoordinateValue	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

10.014_4

Face Image Bounding Box Coordinates in Full Image

Bottom Vertical Coordinate Value

Mnemonic	BVC			Conditionality	M↑
				Status	Active
Description	It is the vertical offset from the upper left corner of the image down to the bottom of the bounding box. It is counted in pixels.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	1 <= BVC <= VLL		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage	Cardinality	1..1		
XML Level 2	(ITL)biom:FacelImageBoundingSquare	Cardinality	0..1		
XML Level 3	(ITL)biom:SegmentBottomVerticalCoordinateValue	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

10.014_5

Face Image Bounding Box Coordinates in Full Image

Bounding Box Head Position Code

Mnemonic	BBC			Conditionality	O↑
				Status	Active
Description	The fifth information item of FIP is the bounding box type, indicating the contents of the bounding box. If this field is omitted, the default value shall be H (Head only).				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars	n/a		
Format	n/a	Constraints	see Look Up Codes		
Code List	FACE BOUNDING CODE				
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage	Cardinality	1..1		
XML Level 2	(ITL)biom:FacelImageBoundingSquare	Cardinality	0..1		
XML Level 3	(ITL)biom:FacelImageBoundingCategoryCode	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

10.015

Face Image Path Coordinates in Full Image

Mnemonic	FPFI		Conditionality	0	
			Status	Active	
Description	If the face image (IMT = 'FACE') contains more than one face, or is not cropped to a "head only" or "head and shoulders" composition, this optional field contains offsets to the location of the path defining a region containing the face of the subject within a larger image. This field is only appropriate for images that do not comply with SAP Levels Levels 30, 32, 40, 42, 50, 51, or 52, because those images shall be cropped to a "head only" or "head and shoulders" composition.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage		Cardinality	1..1	
XML Level 2	(ITL)biom:FacelImageBoundary		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

10.015_1

Face Image Path Coordinates in Full Image

Boundary Code

Mnemonic	BYC		Conditionality	M↑	
			Status	Active	
Description	Defines the shape of a boundary of a feature within an image.				
Field Min	1		Occur Min	1	
Field Max	1		Occur Max	1	
Char Types	A		Special Chars	n/a	
Format	n/a		Constraints	BYC = C, E or P	
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage		Cardinality	1..1	
XML Level 2	(ITL)biom:FacelImageBoundary		Cardinality	0..1	
XML Level 3	(ITL)biom:FacelImageBoundaryShapeCode		Cardinality	1..1	
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

10.015_2

Face Image Path Coordinates in Full Image

Number of Points

Mnemonic	NOP			Conditionality	M↑
				Status	Active
Description	Specifies the number of vertices.				
Field Min	1	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	n/a		
Format	n/a	Constraints	2 < NOP < 99, positive integer		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage	Cardinality	1..1		
XML Level 2	(ITL)biom:FacelImageBoundary	Cardinality	0..1		
XML Level 3	(ITL)biom:PositionPolygonVertexQuantity	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

10.015_3

Face Image Path Coordinates in Full Image

Horizontal Point Offset

Mnemonic	HPO			Conditionality	M↑
				Status	Active
Description	The pixel counts to the right. The HPO and NPO information items are repeated as pairs, in order by point following the path – for a total of NOP pairs				
Field Min	1	Occur Min	2		
Field Max	5	Occur Max	NOP		
Char Types	N	Special Chars	n/a		
Format	n/a	Constraints	0 < HPO < HLL, integer		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage	Cardinality	1..1		
XML Level 2	(ITL)biom:FacelImageBoundary	Cardinality	0..1		
XML Level 3	(ITL)biom:PositionPolygonVertex	Cardinality	2..99		
XML Level 4	(ITL)biom:PositionHorizontalCoordinateValue	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.015_4

Face Image Path Coordinates in Full Image

Vertical Point Offset

Mnemonic	VPO			Conditionality	M↑
				Status	Active
Description	The pixel counts down from the origin. The HPO and NPO information items are repeated as pairs, in order by point following the path – for a total of NOP pairs				
Field Min	1	Occur Min	2		
Field Max	5	Occur Max	NOP		
Char Types	N	Special Chars	n/a		
Format	n/a	Constraints	0 < VPO < VLL, non-negative		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage	Cardinality	1..1		
XML Level 2	(ITL)biom:FacelImageBoundary	Cardinality	0..1		
XML Level 3	(ITL)biom:PositionPolygonVertex	Cardinality	2..99		
XML Level 4	(ITL)biom:PositionVerticalCoordinateValue	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

10.016

Scanned Horizontal Pixel Scale

Mnemonic	SHPS			Conditionality	O
				Status	Active
Description	The horizontal pixel density used for the scanning of the original image / impression providing that the SLC field contains a “1” or “2”. Otherwise, this shall indicate the horizontal component of the pixel aspect ratio, up to 5 integer digits. This field is used if the transmission pixel scale differs from the original image scale, as listed in Transmitted horizontal pixel scale / THPS.				
Field Min	1	Occur Min	0		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	positive integer		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1		Cardinality	1..1		
XML Level 2	(ITL)biom:CaptureHorizontalPixelDensityValue	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.017

Scanned Vertical Pixel Scale

Mnemonic	SVPS	Conditionality	0
		Status	Active
Description	The vertical pixel density used for the scanning of the original image / impression providing that the SLC field contains a "1" or "2". Otherwise, this shall indicate the vertical component of the pixel aspect ratio, up to 5 integer digits. Note that density is directly related to resolution. If SLC is 1 or 2 and SHPS is entered, then SVPS shall equal SHPS.		
Field Min	1	Occur Min	0
Field Max	5	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	positive integer
Code List	FACE BOUNDING CODE		
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	(ITL)biom:FacelImage/(ITL)biom:ImageCaptureDetail or (ITL)biom:PhysicalFeatureImage/(ITL)biom:ImageCaptureDetail	Cardinality	1..1
XML Level 2	(ITL)biom:CaptureVerticalPixelDensityValue	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

10.018

Distortion

Mnemonic	DIST	Conditionality	0
		Status	Active
Description	This field contains the type of distortion, whether it is estimated or calculated, and its relative severity. This field contains three information items: Distortion Code (IDK), Distortion Field (IDK) and Distortion (DIS).		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	n/a
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	(ITL)biom:FacelImage or (ITL)biom:PhysicalFeatureImage	Cardinality	1..1
XML Level 2	(ITL)biom:ImageDistortion	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.018_1

Distortion

Distortion Code

Mnemonic	IDK	Conditionality	M↑
		Status	Active
Description	The first information item of the Distortion (DIST) field is the distortion code.		
Field Min	6	Occur Min	1
Field Max	10	Occur Max	1
Char Types	A	Special Chars	n/a
Format	n/a	Constraints	IDK = Barrel or Inflated or Pincushion
Code List	DISTORTION CODE		
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	(ITL)biom:FacelImage or (ITL)biom:PhysicalFeatureImage	Cardinality	1..1
XML Level 2	(ITL)biom:ImageDistortion	Cardinality	0..1
XML Level 3	(ITL)biom:ImageDistortionCategoryCode	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

10.018_2

Distortion

Distortion Measurement Code

Mnemonic	IDM	Conditionality	M↑
		Status	Active
Description	The second information item of the Distortion field (DIST) is an alphabetic code, which is a distortion measurement code (IDM), that indicates if the distortion is estimated "E" or calculated "C".		
Field Min	1	Occur Min	1
Field Max	1	Occur Max	1
Char Types	A	Special Chars	n/a
Format	n/a	Constraints	IDM = E or C
Code List	DISTORTION MEASUREMENT CODE		
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	(ITL)biom:FacelImage or (ITL)biom:PhysicalFeatureImage	Cardinality	1..1
XML Level 2	(ITL)biom:ImageDistortion	Cardinality	0..1
XML Level 3	(ITL)biom:ImageDistortionMeasurementCode	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.018_3

Distortion

Distortion Severity Code

Mnemonic	DSC			Conditionality	M↑
				Status	Active
Description	The third information item of the Distortion field (DIS) is the distortion severity code (DSC).				
Field Min	4	Occur Min	1		
Field Max	8	Occur Max	1		
Char Types	A	Special Chars	n/a		
Format	n/a	Constraints	DSC = Mild, Moderate or Severe		
Code List	DISTORTION SEVERITY CODE				
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage or (ITL)biom:PhysicalFeatureImage	Cardinality	1..1		
XML Level 2	(ITL)biom:ImageDistortion	Cardinality	0..1		
XML Level 3	(ITL)biom:ImageDistortionSeverityCode	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

10.019

Lighting Artifacts

Mnemonic	LAF			Conditionality	D
				Status	Active
Description	This optional field (contains the type of lighting artifacts found in the Type-10 image record. It is only applicable to face images (IMT = 'FACE'). Multiple lighting artifacts may be repeated as separate subfields.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	A	Special Chars	None		
Format	n/a	Constraints	see Look Up Codes		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage	Cardinality	1..1		
XML Level 2	biom:FacelImageLightingArtifactsCode	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.019_0

Lighting Artifacts

Subfields: Repeating values

Mnemonic	LAF_0			Conditionality	M↑
				Status	New - Active
Description	This optional field (contains the type of lighting artifacts found in the Type-10 image record. It is only applicable to face images (IMT = 'FACE'). Multiple lighting artifacts may be repeated as separate subfields.				
Field Min	1	Occur Min	1		
Field Max	1	Occur Max	3		
Char Types	A	Special Chars	n/a		
Format	n/a	Constraints	value = F, H or R		
Code List	LIGHTING ARTIFACTS CODE				
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage	Cardinality	1...1		
XML Level 2	biom:FacelImageLightingArtifactsCode	Cardinality	0..3		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

10.02

Subject Pose

Mnemonic	POS			Conditionality	D
				Status	Active
Description	This field is to be used for the exchange of facial image data. When included, this field shall contain one ASCII character code selected from [possible codes below] to describe the pose of the subject. For the angled pose entry "A", [10.025 SPA Pose Offset Angle field] shall contain the offset angle from the full face orientation. For the determined 3D pose entry "D", [Type-10 Subject Post Angles field] shall contain a set of determined 3D pose angles. Note that the offset angle in [Type-10 Pose Offset Angle field] is opposite from the yaw angle in [Type-10 Subject Post Angles field] as indicated by a minus sign. A value of POS = D does not imply that the image itself is a 3D image, such as a point cloud. 3D imagery shall be transmitted in a Type-22 record.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars	None		
Format	n/a	Constraints	see Look Up Codes		
Code List	SUBJECT POSE CODE				
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage	Cardinality	1...1		
XML Level 2	biom:FacelImageSubjectPoseCode	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.021

Pose Offset Angle

Mnemonic	POA		Conditionality	D	
			Status	Active	
Description	This shall only be used for the exchange of facial image data (IMT = "FACE"). It may be used if Field 10.020: Subject pose / POS contains an "A" to indicate an angled pose of the subject. The field shall not be used if the entry in POS is an "F", "R", "L" or "D". This field shall be omitted for a full face or a profile. This field specifies the pose direction of the subject at any possible orientation within a circle. Its value shall be to the nearest degree. The offset angle shall be measured from the full-face pose position and have a range of values from -180 degrees to +180 degrees. A positive angle is used to express the angular offset as the subject rotates from a full-face pose to their left (approaching a right profile). The allowed special characters are the plus sign and minus sign.				
Field Min	1		Occur Min	0	
Field Max	4		Occur Max	1	
Char Types	NS		Special Chars	Minus Sign, Plus Sign	
Format	n/a		Constraints	-180 <= POA <= 180; integer	
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage		Cardinality	1..1	
XML Level 2	biom:FacelImagePoseOffsetAngleMeasure		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

10.023

Photo Acquisition Source

Mnemonic	PAS		Conditionality	D	
			Status	Active	
Description	This field shall specify the classification of the source of the image contained in this record. This field is required if the SAP entry [10.013 Subject Acquisition Profile field] is "40" or greater (IMT=FACE only). When included, this field shall contain an ASCII character code selected to describe the source of captured image data.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage		Cardinality	1..1	
XML Level 2	(ITL)biom:FacelImageAcquisitionSource		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-10: Photographic Body Part Imagery (including Face and S

Page 506 of 1037

10.023_1

Photo Acquisition Source

Photo Attribute Code

Mnemonic	PAC			Conditionality	M↑
				Status	Active
Description	The first information item in the Photo Acquisition Source (PAS) field shall contain an attribute code to describe the source of captured image data.				
Field Min	6	Occur Min	1		
Field Max	14	Occur Max	1		
Char Types	ANS	Special Chars	n/a		
Format	n/a	Constraints	see Look Up Codes		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage	Cardinality	1..1		
XML Level 2	(ITL)biom:FacelImageAcquisitionSource	Cardinality	0..1		
XML Level 3	(ITL)biom:ImageAcquisitionSourceCode	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

10.023_2

Photo Acquisition Source

Vendor-Specific Description

Mnemonic	VSD			Conditionality	D
				Status	Active
Description	When "VENDOR" is specified in photo attribute code / PAC, a second free-format information item (vendorspecific description / VSD) may be entered with up to 64 characters to describe the vendor-specific source of the captured image or to enter unlisted or miscellaneous source attributes for the facial image.				
Field Min	1	Occur Min	0		
Field Max	64	Occur Max	1		
Char Types	U	Special Chars	n/a		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage	Cardinality	1..1		
XML Level 2	(ITL)biom:FacelImageAcquisitionSource	Cardinality	0..1		
XML Level 3	(ITL)biom:CaptureSourceDescriptionText	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

10.024

Subject Quality Score

Mnemonic	SQS		Conditionality	D			
			Status	Active			
Description	This optional field shall specify quality score data for facial images (IMT = 'FACE') stored in this record. There may be subfields for different quality scores and algorithms.						
Field Min	n/a	Occur Min	0				
Field Max	n/a	Occur Max	1				
Char Types	n/a	Special Chars	n/a				
Format	n/a	Constraints					
Code List							
Source	ANSI/NIST ITL 2011: (Update 2013)						
XML Level 1	(ITL)biom:FacelImage or (ITL)biom:PhysicalFeatureImage		Cardinality	1..1			
XML Level 2	(ITL)biom:ImageQuality		Cardinality	0..1			
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

10.024_0

Subject Quality Score

Subfields: Repeating sets of information items

Mnemonic	SQS_0		Conditionality	M↑			
			Status	Active			
Description	This optional field shall specify quality score data for facial images (IMT = 'FACE') stored in this record. There may be subfields for different quality scores and algorithms.						
Field Min	n/a	Occur Min	1				
Field Max	n/a	Occur Max	9				
Char Types	n/a	Special Chars	n/a				
Format	n/a	Constraints	n/a				
Code List							
Source	ANSI/NIST ITL 2011: (Update 2013)						
XML Level 1	(ITL)biom:FacelImage or (ITL)biom:PhysicalFeatureImage		Cardinality	1..1			
XML Level 2	(ITL)biom:ImageQuality		Cardinality	0..9			
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

10.024_1

Subject Quality Score

Quality Value

Mnemonic	QVU	Conditionality	M↑
		Status	Active
Description	This information item shall contain the integer image quality score between 0 and 100 (inclusive) assigned to the image data by a quality algorithm. Higher values indicate better quality. An entry of "255" shall indicate a failed attempt to calculate a quality score. An entry of "254" shall indicate that no attempt to calculate a quality score was made.		
Field Min	1	Occur Min	1
Field Max	3	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	0 < QVU < 100, non-negative integer or QVU = 254 or 255
Code List			
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	(ITL)biom:FacelImage or (ITL)biom:PhysicalFeatureImage	Cardinality	1..1
XML Level 2	(ITL)biom:ImageQuality	Cardinality	0..9
XML Level 3	(ITL)biom:QualityValue	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

10.024_2

Subject Quality Score

Algorithm Vendor Identification

Mnemonic	QAV	Conditionality	M↑
		Status	Active
Description	This information item shall specify the ID of the vendor of the quality algorithm used to calculate the quality score. This 4-digit hex value is assigned by IBIA and expressed as four ASCII characters. The IBIA shall maintain the Vendor Registry of CBEFF Biometric Organizations that will map the value in this field to a registered organization.		
Field Min	4	Occur Min	1
Field Max	4	Occur Max	1
Char Types	H	Special Chars	None
Format	n/a	Constraints	0000 < QAV < FFFF
Code List			
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	(ITL)biom:FacelImage or (ITL)biom:PhysicalFeatureImage	Cardinality	1..1
XML Level 2	(ITL)biom:ImageQuality	Cardinality	0..9
XML Level 3	(ITL)biom:QualityAlgorithmVendorIdentification/nc:IdentificationID	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

10.024_3

Subject Quality Score

Algorithm Product Identification

Mnemonic	QAP			Conditionality	M↑
				Status	Active
Description	This information item shall specify a numeric product code assigned by the vendor of the quality algorithm, which may be registered with the IBIA, but it is not required to be registered. It indicates which of the vendor's algorithms was used in the calculation of the quality score. This field contains the ASCII representation of the integer product code and should be within the range 1 to 65535.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	1 < QAP < 65535, positive integer		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage or (ITL)biom:PhysicalFeatureImage	Cardinality	1..1		
XML Level 2	(ITL)biom:ImageQuality	Cardinality	0..9		
XML Level 3	(ITL)biom:QualityAlgorithmProductIdentification/nc:IdentificationID	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

10.025

Subject Pose Angles

Mnemonic	SPA			Conditionality	D
				Status	Active
Description	This ASCII set shall be present when [10.020 Subject Pose field] (POS) contains a "D" to indicate a set of determined 3D pose angles of the same subject for a facial image (IMT = 'FACE'). When present, this information shall be entered as three or six information items. The first three items specify the pose of the subject estimated or measured at constrained possible orientations within a sphere. If this field is used, the first three are mandatory. Notes: ANSI/NIST ITL 1-2011: Update 2013 Subject Pose (POS) and subject pose angles (SPA) contains, additional information, details, and examples of the subject pose angles.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage	Cardinality	1..1		
XML Level 2	(ITL)biom:FacelImage3DPoseAngle	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.025_1

Subject Pose Angles

Yaw Angle

Mnemonic	YAW			Conditionality	M↑
				Status	Active
Description	This information item is the Yaw angle (rotation about the vertical 'y' axis).				
Field Min	1	Occur Min	1		
Field Max	4	Occur Max	1		
Char Types	NS	Special Chars	Minus Sign		
Format	n/a	Constraints	-180 < YAW < 180, integer		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage	Cardinality	1...1		
XML Level 2	(ITL)biom:FacelImage3DPoseAngle	Cardinality	0..1		
XML Level 3	(ITL)biom:PoseYawAngleMeasure	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

10.025_2

Subject Pose Angles

Pitch Angle

Mnemonic	PIT			Conditionality	M↑
				Status	Active
Description	This information item is the Pitch angle (rotation about 'x' horizontal axis).				
Field Min	1	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	NS	Special Chars	Minus Sign		
Format	n/a	Constraints	-90 < PIT < 90, integer		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage	Cardinality	1...1		
XML Level 2	(ITL)biom:FacelImage3DPoseAngle	Cardinality	0..1		
XML Level 3	(ITL)biom:PosePitchAngleMeasure	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

10.025_3

Subject Pose Angles

Roll Angle

Mnemonic	ROL			Conditionality	M↑
				Status	Active
Description	This information Item is the Roll angle (rotation about the 'z' axis).				
Field Min	1	Occur Min	1		
Field Max	4	Occur Max	1		
Char Types	NS	Special Chars	Minus Sign		
Format	n/a	Constraints	180 < PIT < 180, integer		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage	Cardinality	1...1		
XML Level 2	(ITL)biom:FacelImage3DPoseAngle	Cardinality	0..1		
XML Level 3	(ITL)biom:PoseRollAngleMeasure	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

10.025_4

Subject Pose Angles

Uncertainty in Degrees for Yaw

Mnemonic	YAWU			Conditionality	O↑
				Status	Active
Description	The measure of uncertainty concerning the rotation about the vertical or Y axis of the pose.				
Field Min	1	Occur Min	0		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	n/a		
Format	n/a	Constraints	0 < YAWU < 90, non-negative, integer		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage	Cardinality	1...1		
XML Level 2	(ITL)biom:FacelImage3DPoseAngle	Cardinality	0..1		
XML Level 3	(ITL)biom:PoseYawUncertaintyValue	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.025_5

Subject Pose Angles

Uncertainty in Degrees for Pitch

Mnemonic	PITU			Conditionality	0↑		
				Status	New - Active		
Description	The fifth information item is the uncertainty in degrees for pitch / PITU.						
Field Min	1		Occur Min	0			
Field Max	2		Occur Max	1			
Char Types	N		Special Chars	n/a			
Format	n/a		Constraints	0 < PITU < 90, non-negative, integer			
Code List							
Source	ANSI/NIST ITL 2011: (Update 2013)						
XML Level 1	(ITL)biom:FacelImage			Cardinality	1...1		
XML Level 2	(ITL)biom:FacelImage3DPoseAngle			Cardinality	0..1		
XML Level 3	(ITL)biom:PosePitchUncertaintyValue			Cardinality	0..1		
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

10.025_6

Subject Pose Angles

Uncertainty in Degrees for Roll

Mnemonic	ROLU			Conditionality	0↑		
				Status	Active		
Description	The measure of uncertainty concerning the rotation about the Z axis of the pose.						
Field Min	1		Occur Min	0			
Field Max	2		Occur Max	1			
Char Types	N		Special Chars	n/a			
Format	n/a		Constraints	0 < ROLU < 90, non-negative, integer			
Code List							
Source	ANSI/NIST ITL 2011: (Update 2013)						
XML Level 1	(ITL)biom:FacelImage			Cardinality	1...1		
XML Level 2	(ITL)biom:FacelImage3DPoseAngle			Cardinality	0..1		
XML Level 3	(ITL)biom:PoseRollUncertaintyValue			Cardinality	0..1		
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.026

Subject Facial Description

Mnemonic	SXS		Conditionality	D
			Status	Active
Description	This field is mandatory if the SAP entry for a facial image (Field 10.013: Subject acquisition profile / SAP) is "30" or greater. (IMT = FACE only). In other cases, this field is optional for facial images. When present, it shall describe attributes associated with the subject's captured facial image. This version maintains the upper limit of 50 repeating subfields for all encodings from the 2007 version. (The 2008 version was unrestricted). In the 2007 version, the minimum character count for this was listed as 5; however, there was an entry of "HAT" which has 3 characters. Thus, the minimum character count in this version is set at 3.			
Field Min	n/a	Occur Min	0	
Field Max	n/a	Occur Max	1	
Char Types	D	Special Chars	None	
Format	n/a	Constraints		
Code List				
Source	ANSI/NIST ITL 2011: (Update 2013)			
XML Level 1	(ITL)biom:FacelImage	Cardinality	1...1	
XML Level 2	(ITL)biom:FacelImageDescription	Cardinality	0..1	
XML Level 3		Cardinality		
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0 Yes DoD EBTS 4.0 Yes

10.026_0

Subject Facial Description

Subfields: repeating values

Mnemonic	SXS_0		Conditionality	M↑
			Status	New - Active
Description	This field is mandatory if the SAP entry for a facial image (Field 10.013: Subject acquisition profile / SAP) is "30" or greater. (IMT = FACE only). In other cases, this field is optional for facial images. When present, it shall describe attributes associated with the subject's captured facial image. This version maintains the upper limit of 50 repeating subfields for all encodings from the 2007 version. (The 2008 version was unrestricted). In the 2007 version, the minimum character count for this was listed as 5; however, there was an entry of "HAT" which has 3 characters. Thus, the minimum character count in this version is set at 3.			
Field Min	3	Occur Min	1	
Field Max	20	Occur Max	50	
Char Types	AS	Special Chars	n/a	
Format	n/a	Constraints	see Look Up Codes	
Code List	SUBJECT FACIAL DESCRIPTION CODES			
Source	ANSI/NIST ITL 2011: (Update 2013)			
XML Level 1	(ITL)biom:FacelImage	Cardinality	1...1	
XML Level 2	(ITL)biom:FacelImageDescription	Cardinality	0..50	
XML Level 3		Cardinality		
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0 No DoD EBTS 4.0 Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.027

Subject Eye Color - Repeating values.

Mnemonic	SEC		Conditionality	D
			Status	Active
Description	Describe the eye color of the subject as seen in the photograph. If unusual or unnatural such as may be the case when colored contact lenses are present and the "real" eye color cannot be ascertained, then the color should be labeled as "XXX". Eye color attributes and attribute codes are given by possible codes.			
Field Min	3	Occur Min	0	
Field Max	3	Occur Max	1	
Char Types	A	Special Chars	None	
Format	n/a	Constraints	see Look Up Codes	
Code List	ALPHA EYE COLOR CODE			
Source	ANSI/NIST ITL 2011: (Update 2013)			
XML Level 1	(ITL)biom:FacelImage	Cardinality	1...1	
XML Level 2	(ITL)biom:FacelImageEyeColorAttributeCode	Cardinality	0..1	
XML Level 3		Cardinality		
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0 Yes DoD EBTS 4.0 Yes

10.028

Subject Hair Color

Mnemonic	SHC		Conditionality	D
			Status	Active
Description	Describes the hair color of the subject as seen in the photograph.			
Field Min	n/a	Occur Min	0	
Field Max	n/a	Occur Max	1	
Char Types	n/a	Special Chars	None	
Format	n/a	Constraints		
Code List				
Source	ANSI/NIST ITL 2011: (Update 2013)			
XML Level 1	(ITL)biom:FacelImage	Cardinality	1...1	
XML Level 2	(ITL)biom:FacelImageHairColorAttributeCode	Cardinality	0..1	
XML Level 3		Cardinality		
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0 Yes DoD EBTS 4.0 Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.028_0

Subject Hair Color

Subfields: Repeating values

Mnemonic	SHC_0			Conditionality	M↑
				Status	New - Active
Description	Describes the hair color of the subject as seen in the photograph.				
Field Min	3	Occur Min	1		
Field Max	3	Occur Max	2		
Char Types	A	Special Chars	n/a		
Format	n/a	Constraints	see Look Up Codes		
Code List	HAIR COLOR				
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage	Cardinality	1...1		
XML Level 2	(ITL)biom:FacelImageHairColorAttributeCode	Cardinality	0..2		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

10.029

2D Facial Feature Points

Mnemonic	FFP			Conditionality	M↑
				Status	Active
Description	The ASCII set shall be used for the exchange of facial image data. When present, it shall describe special attributes of manually or automatically detected facial feature points of the captured facial image. The optional field shall be used for the exchange of facial (IMT = 'FACE', 'HEAD', 'LIP', 'EXTRAORAL' and 'CONDITION') feature points or landmarks. This information shall be entered as a four-information item feature point block in a repeating subfield.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage or (ITL)biom:PhysicalFeatureImage	Cardinality	1...1		
XML Level 2	(ITL)biom:FacelImageFeaturePoint	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.029_0

2D Facial Feature Points

Subfields: Repeating sets of information items

Mnemonic	FFP_0			Conditionality	M↑
				Status	Active
Description	The ASCII set shall be used for the exchange of facial image data. When present, it shall describe special attributes of manually or automatically detected facial feature points of the captured facial image. The optional field shall be used for the exchange of facial (IMT = 'FACE', 'HEAD', 'LIP', 'EXTRAORAL' and 'CONDITION') feature points or landmarks. This information shall be entered as a four-information item feature point block in a repeating subfield.				
Field Min	n/a	Occur Min	1		
Field Max	n/a	Occur Max	88		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage or (ITL)biom:PhysicalFeatureImage			Cardinality	1..1
XML Level 2	(ITL)biom:FacelImageFeaturePoint			Cardinality	0..88
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

10.029_1

2D Facial Feature Points

Feature Point Type

Mnemonic	FPT			Conditionality	M↑
				Status	Active
Description	The first information item of 2D Facial Feature Points (FFP) or 3D Facial Feature Points (3DF) is a one character value. It is mandatory. It shall be either: 1 = Denoting an MPEG4 Feature point, or 2 = Anthropometric landmark.				
Field Min	1	Occur Min	1		
Field Max	1	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	FPT = 1 or 2		
Code List	FEATURE POINT TYPE CODE				
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage or (ITL)biom:PhysicalFeatureImage			Cardinality	1..1
XML Level 2	(ITL)biom:FacelImageFeaturePoint			Cardinality	0..88
XML Level 3	(ITL)biom:FeaturePointCategoryCode			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-10: Photographic Body Part Imagery (including Face and S

Page 517 of 1037

10.029_2

2D Facial Feature Points

Feature Point Code

Mnemonic	FPC			Conditionality	M↑
				Status	Active
Description	If FPT is 1, this information item shall be "A.B" with A and B defined. If FPT is 2, the codes are entered as shown in the Feature Point ID column of the Feature Point ID Code table.				
Field Min	3	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	ANS	Special Chars	Period		
Format	n/a	Constraints	Format: N.N, N.NN, NN.N, NN.NN, a, aa, aaa or aaaa		
Code List	FEATURE POINT ID CODE / EYE AND NOSTRIL CENTER FEATURE POINT CODE				
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage or (ITL)biom:PhysicalFeatureImage	Cardinality	1..1		
XML Level 2	(ITL)biom:FacelImageFeaturePoint	Cardinality	0..88		
XML Level 3	(ITL)biom:FeaturePointIdentification/nc:IdentificationID	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

10.029_3

2D Facial Feature Points

X Coordinate

Mnemonic	HCX			Conditionality	M↑
				Status	Active
Description	The third information item of the 2D Facial Feature Points (FFD) or 3D Facial Feature Points (3DF). It is 1 to 5 characters, denoting the pixel count horizontally to the right from the upper left pixel, which is set to 0.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 < HCX < HLL, non-negative		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage or (ITL)biom:PhysicalFeatureImage	Cardinality	1..1		
XML Level 2	(ITL)biom:FacelImageFeaturePoint	Cardinality	0..88		
XML Level 3	(ITL)biom:FeaturePointHorizontalCoordinateValue	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.029_4

2D Facial Feature Points

Y Coordinate

Mnemonic	HCY			Conditionality	M↑
				Status	Active
Description	The fourth information item of the 2D Facial Feature Points (FFD) or 3D Facial Feature Points (3DF). It is 1 to 5 characters, denoting the pixel count vertically down from the upper left pixel, which is set to 0.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 < HCY < VLL, non-negative		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage or (ITL)biom:PhysicalFeatureImage			Cardinality	1..1
XML Level 2	(ITL)biom:FacelImageFeaturePoint			Cardinality	0..88
XML Level 3	(ITL)biom:FeaturePointVerticalCoordinateValue			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

10.03

Device Monitoring Mode

Mnemonic	DMM			Conditionality	0
				Status	Active
Description	This field provides information describing the human monitoring operation of the image capture device, and will contain an entry from the Device Monitoring Mode Code list to indicate the monitoring mode of the biometric sample capture device.				
Field Min	7	Occur Min	0		
Field Max	10	Occur Max	1		
Char Types	A	Special Chars	None		
Format	n/a	Constraints	see Look Up Codes		
Code List	CAPTURE DEVICE MONITORING MODE CODE				
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:ImageCapture			Cardinality	1..1
XML Level 2	(ITL)biom:CaptureDeviceMonitoringModeCode			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.031

Tiered Markup Collection

Mnemonic	TMC			Conditionality	D
				Status	Active
Description	This optional field describes the specific facial (IMT = 'FACE') feature points contained in Field 10.029: 2D Facial feature points / FFP and if level 5, contours shall be contained in Field 10.033: Feature contours / FEC.				
Field Min	1	Occur Min	0		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	integer; see Look Up Codes		
Code List	TIERED MARKUP COLLECTION CODE				
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage/(ITL)biom:ImageCaptureDetail or (ITL)biom:PhysicalFeatureImage/(ITL)biom:ImageCaptureDetail			Cardinality	1..1
XML Level 2	biom:FacelImageFeaturePointTierCode / biom:FacelImageFeaturePointTierNumeric			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

10.032

3D Facial Feature Points

Mnemonic	3DF			Conditionality	D
				Status	Active
Description	Each subfield refers to a specific contour on the image and contains a minimum of three points. This field shall appear if TMC = 5, otherwise, it is optional.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:PhysicalFeatureImage			Cardinality	1..1
XML Level 2	biom:FacelImage3DFeaturePoint			Cardinality	1..88
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.032_0

3D Facial Feature Points

Subfields: Repeating sets of information items

Mnemonic	FFP_0			Conditionality	M↑
				Status	New - Active
Description	Each subfield refers to a specific contour on the image and contains a minimum of three points. This field shall appear if TMC = 5, otherwise, it is optional.				
Field Min	n/a			Occur Min	1
Field Max	n/a			Occur Max	88
Char Types	n/a			Special Chars	n/a
Format	n/a			Constraints	
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:PhysicalFeatureImage			Cardinality	1..1
XML Level 2	biom:FacelImage3DFeaturePoint			Cardinality	1..88
XML Level 3	biom:FeaturePointHorizontalCoordinateValue			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

10.032_1

3D Facial Feature Points

Feature Point Type

Mnemonic	FPT			Conditionality	M↑
				Status	Active
Description	The first information item of 2D Facial Feature Points (FFP) or 3D Facial Feature Points (3DF) is a one character value. It is mandatory. It shall be either: 1 = Denoting an MPEG4 Feature point, or 2 = Anthropometric landmark. The allowed special character is a period. If FPT is 2, the codes are entered as shown in the "Feature Point ID" column of Table 65. Note that this entry is one to four alphabetic characters.				
Field Min	1			Occur Min	1
Field Max	1			Occur Max	1
Char Types	N			Special Chars	None
Format	n/a			Constraints	FPT = 1 or 2
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:PhysicalFeatureImage			Cardinality	1..1
XML Level 2	biom:FacelImage3DFeaturePoint			Cardinality	1..88
XML Level 3	biom:FeaturePointCategoryCode			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

10.032_2

3D Facial Feature Points

Feature Point Code

Mnemonic	FPC			Conditionality	M↑
				Status	Active
Description	The second information item, feature point code / FPC is 3 to 5 characters. If FPT is 1, this information item shall be "A.B" with A and B defined ANSI/NIST ITL 1-2011: Update 2013. If FPT is 2, the codes are entered as shown in the "Feature Point ID" column Feature Point ID Code and Eye and Nostril Center Feature Point Code lists.				
Field Min	3	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	ANS	Special Chars	Period		
Format	N.N, N.NN, NN.N, NN.NN, a, aa, aaa or aaaa			Constraints	Format: N.N, N.NN, NN.N, NN.NN, a, aa, aaa or aaaa
Code List	FEATURE POINT ID CODE / EYE AND NOSTRIL CENTER FEATURE POINT CODE				
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1..1		
XML Level 2	biom:FacelImage3DFeaturePoint	Cardinality	1..88		
XML Level 3	biom:FeaturePointIdentification/nc:IdentificationType	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

10.032_3

3D Facial Feature Points

X Coordinate

Mnemonic	HCX			Conditionality	M↑
				Status	Active
Description	The third information item of the 2D Facial Feature Points (FFD) or 3D Facial Feature Points (3DF). It is 1 to 5 characters, denoting the pixel count horizontally to the right from the upper left pixel, which is set to 0.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 < HCX < HLL, non-negative, integer		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1..1		
XML Level 2	biom:FacelImage3DFeaturePoint	Cardinality	1..88		
XML Level 3	biom:FeaturePointHorizontalCoordinateValue	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.032_4

3D Facial Feature Points

Y Coordinate

Mnemonic	HCY			Conditionality	M↑
				Status	Active
Description	The fourth information item of the 2D Facial Feature Points (FFD) or 3D Facial Feature Points (3DF). It is 1 to 5 characters, denoting the pixel count vertically down from the upper left pixel, which is set to 0.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 < HCY < VLL, non-negative, integer		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1..1		
XML Level 2	biom:FacelImage3DFeaturePoint	Cardinality	1..88		
XML Level 3	biom:FeaturePointVerticalCoordinateValue	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

10.032_5

3D Facial Feature Points

Z Coordinate

Mnemonic	HCZ			Conditionality	M↑
				Status	Active
Description	The fifth information item of the 3D Facial Feature Points (3DF) field. It is 1 to 5 characters, denoting the pixel count from the X-Y plane, which is set to 0.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 < HCZ < 99999, nonnegative, integer		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1..1		
XML Level 2	biom:FacelImage3DFeaturePoint	Cardinality	1..88		
XML Level 3	biom:FeaturePointZCoordinateValue	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.033

Feature Contours

Mnemonic	FEC			Conditionality	D
				Status	Active
Description	Each subfield refers to a specific contour on the image and contains a minimum of three points. This field shall appear if TMC = 5. It is optional otherwise.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage			Cardinality	1..1
XML Level 2	biom:FacelImageContour			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

10.033_0

Feature Contours

Subfields: Repeating sets of information items

Mnemonic	FEC_0			Conditionality	M↑
				Status	New - Active
Description	Each subfield refers to a specific contour on the image and contains a minimum of three points. This field shall appear if TMC = 5. It is optional otherwise.				
Field Min	n/a	Occur Min	1		
Field Max	n/a	Occur Max	12		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage			Cardinality	1..1
XML Level 2	biom:FacelImageContour			Cardinality	0..12
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-10: Photographic Body Part Imagery (including Face and S

Page 524 of 1037

10.033_1

Feature Contours

Feature Contour Code

Mnemonic	FCC			Conditionality	M↑
				Status	Active
Description	The first information item of the Feature Contour (FEC).				
Field Min	4	Occur Min	1		
Field Max	14	Occur Max	1		
Char Types	A	Special Chars	n/a		
Format	n/a	Constraints	see Look Up Codes		
Code List	FEATURE CONTOUR CODE				
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage	Cardinality	1..1		
XML Level 2	biom:FacelImageContour	Cardinality	0..12		
XML Level 3	biom:FacelImageContourCategoryCode	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

10.033_2

Feature Contours

Number of Points

Mnemonic	NOP			Conditionality	M↑
				Status	Active
Description	Specifies the number of vertices.				
Field Min	1	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	n/a		
Format	n/a	Constraints	3 < NOP < 99		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage	Cardinality	1..1		
XML Level 2	biom:FacelImageContour	Cardinality	0..12		
XML Level 3	biom:PositionPolygonVertexQuantity	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.033_3

Feature Contours

Horizontal Point Offset

Mnemonic	HPO			Conditionality	M↑
				Status	Active
Description	The pixel counts to the right. The HPO and VPO information items are repeated as pairs, in order by point following the path, up to the final point - for a total of NOP pairs.				
Field Min	1	Occur Min	3		
Field Max	5	Occur Max	NOP		
Char Types	N	Special Chars	n/a		
Format	n/a	Constraints	0 < HPO < HLL		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage	Cardinality	1..1		
XML Level 2	biom:FacelImageContour	Cardinality	0..12		
XML Level 3	biom:PositionPolygonVertex	Cardinality	3..99		
XML Level 4	biom:PositionHorizontalCoordinateValue	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

10.033_4

Feature Contours

Vertical Point Offset

Mnemonic	VPO			Conditionality	M↑
				Status	Active
Description	The pixel counts down from the origin. The HPO and VPO information items are repeated as pairs, in order by point following the path, up to the final point - for a total of NOP pairs.				
Field Min	1	Occur Min	3		
Field Max	5	Occur Max	NOP		
Char Types	N	Special Chars	n/a		
Format	n/a	Constraints	0 < VPO < VLL		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage	Cardinality	1..1		
XML Level 2	biom:FacelImageContour	Cardinality	0..12		
XML Level 3	biom:PositionPolygonVertex	Cardinality	3..99		
XML Level 4	biom:PositionVerticalCoordinateValue	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.034

IMAGE CAPTURE DATE RANGE ESTIMATE

Mnemonic	ICDR			Conditionality	0
				Status	New - Active
Description	It is possible to enter only a year, month and/or day range, such as D5, meaning that the actual date of collection is estimated to be 5 days plus or minus from that specified in PHD. Leading zeros need not be entered.				
Field Min	3	Occur Min	0		
Field Max	9	Occur Max	1		
Char Types	AN	Special Chars	n/a		
Format	YYMMDD	Constraints	Time measure indicator followed by 1 or 2 digits.		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage/(ITL)biom:ImageCaptureDetail or (ITL)biom:PhysicalFeatureImage/(ITL)biom:ImageCaptureDetail			Cardinality	1...1
XML Level 2	biom:ImageCaptureDateEstimateRange			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

10.038

Comment

Mnemonic	COM			Conditionality	0
				Status	Active
Description	The optional Comment field appears in many record types and may be used to insert free text information. It is not reserved exclusively for log-related information but has historically often been used for this purpose. It is limited to a maximum of 126 characters. This maximum size was established in order to maintain consistency across encodings. The maximum size differed in the 2007 and 2008 versions of the standard.				
Field Min	1	Occur Min	0		
Field Max	126	Occur Max	1		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage/(ITL)biom:ImageCaptureDetail or (ITL)biom:PhysicalFeatureImage/(ITL)biom:ImageCaptureDetail			Cardinality	1...1
XML Level 2	(ITL)biom:ImageCommentText			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.039

Type-10 Reference Number

Mnemonic	T10	Conditionality	D
		Status	Active
Description	<p>Cheiloscopy image data / CID or dental visual image comparison descriptive text / VICD is present in Field 10.050: Dental visual image data information / VID. The same T10 is used when referring to a particular image. This field shall only be present if multiple Type-10 records in the transaction contain the same SMT or body part. It can be used for any image type specified in Field 10.003: Image type / IMT. T10 is a positive integer. The only requirement is that a value for T10 only links related images. An example would be to assign a value of 1 to two different Type-10 records, the first of which has an image of a tattoo over the entire chest of a male. A second image of a small portion of the tattoo on the chest showing a gang symbol is contained in another Type-10 with the same value of 1 for T10. No other Type-10 records (in this example) would have a value of 1 for T10. This is an optional field. It is used when several images cover either the entire scar, (needle) mark, tattoo (SMT) or portions of it. This field shall be present if lip print comparison descriptive text / LPCT is present in Field 10.049: The same T10 is used when referring to a particular image. This field shall only be present if multiple Type-10 records in the transaction contain the same SMT or body part.</p>		
Field Min	1	Occur Min	0
Field Max	3	Occur Max	1
Char Types	AN	Special Chars	None
Format	n/a	Constraints	1 <= T10 <= 255
Code List			
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	(ITL)biom:FacelImage or (ITL)biom:PhysicalFeatureImage	Cardinality	1..1
XML Level 2	(ITL)biom:PhysicalFeatureReferenceIdentification/nc:IdentificationID	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.04

NCIC SMT Code

Mnemonic	SMT		Conditionality	D
			Status	Active
Description	This field shall be used only when Field 10.003: Image type / IMT = "SCAR", "MARK", or "TATTOO". It is not used for other images. It is used to identify a general location of the captured scar, mark, tattoo, or other characteristic (including piercings) in an image. The contents of this field shall be from the NCIC code. The captured image may encompass an area larger than that specified by a single NCIC body part code for the particular image type. This situation may be accommodated by listing multiple NCIC codes, each in a separate subfield. In this case the primary code is listed first. There need not be more than one subfield. For the "marks" category, the NCIC manual lists the common locations for needle track marks. For other body part locations not listed under the "marks" category, use the body location codes listed for scars.			
Field Min	n/a	Occur Min	0	
Field Max	n/a	Occur Max	1	
Char Types	n/a	Special Chars	None	
Format	n/a	Constraints	Values from Annex D of ANSI/NIST ITL 1-2011 (Update 2013)	
Code List				
Source	ANSI/NIST ITL 2011: (Update 2013)			
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1..1	
XML Level 2	biom:PhysicalFeatureNCICCode	Cardinality	0..1	
XML Level 3		Cardinality		
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0 Yes DoD EBTS 4.0 Yes

10.040_0

NCIC SMT Code

Subfields: Repeating values

Mnemonic	SMT_0		Conditionality	M↑
			Status	New - Active
Description	This field shall be used only when Field 10.003: Image type / IMT = "SCAR", "MARK", or "TATTOO". It is not used for other images. It is used to identify a general location of the captured scar, mark, tattoo, or other characteristic (including piercings) in an image. The contents of this field shall be from the NCIC code. The captured image may encompass an area larger than that specified by a single NCIC body part code for the particular image type. This situation may be accommodated by listing multiple NCIC codes, each in a separate subfield. In this case the primary code is listed first. There need not be more than one subfield. For the "marks" category, the NCIC manual lists the common locations for needle track marks. For other body part locations not listed under the "marks" category, use the body location codes listed for scars.			
Field Min	3	Occur Min	1	
Field Max	10	Occur Max	3	
Char Types	AS	Special Chars	n/a	
Format	n/a	Constraints	n/a	
Code List				
Source	ANSI/NIST ITL 2011: (Update 2013)			
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1..1	
XML Level 2	biom:PhysicalFeatureNCICCode	Cardinality	0..3	
XML Level 3		Cardinality		
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0 No DoD EBTS 4.0 Yes

10.041

SMT SIZE OR SIZE OF INJURY OR IDENTIFYING CHARACTERISTIC

Mnemonic	SMS			Conditionality	D
				Status	Active
Description	This set shall contain the dimensions of the portion of image contained in this record (it may be the entire scar, mark, tattoo, injury or identifying characteristic). Each dimension shall be entered to the nearest centimeter.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1..1		
XML Level 2	(ITL)biom:PhysicalFeatureSize	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

10.041_1

SMT SIZE OR SIZE OF INJURY OR IDENTIFYING CHARACTERISTIC

Height

Mnemonic	HGT			Conditionality	M↑
				Status	Active
Description	The height of the scar, mark or tattoo in nearest centimeter.				
Field Min	1	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1..1		
XML Level 2	(ITL)biom:PhysicalFeatureSize	Cardinality	1..1		
XML Level 3	(ITL)biom:PhysicalFeatureHeightMeasure	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.041_2

SMT SIZE OR SIZE OF INJURY OR IDENTIFYING CHARACTERISTIC

Width

Mnemonic	WID			Conditionality	M↑
				Status	Active
Description	The width of the scar, mark or tattoo in the nearest centimeter.				
Field Min	1	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1...1		
XML Level 2	(ITL)biom:PhysicalFeatureSize	Cardinality	1..1		
XML Level 3	(ITL)biom:PhysicalFeatureWidthMeasure	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

10.042

SMT Descriptors

Mnemonic	SMD			Conditionality	M↑
				Status	Active
Description	This field is used to describe the content of the SMT image to an extent greater than documented in Field 10.040: NCIC SMT code / SMT. It shall consist of one or more subfields. This version maintains the upper limit of 9 for all encodings. This field shall be used only when Field 10.003: Image type / IMT= "SCAR", "MARK", or "TATTOO". An SMT image consisting of several parts or sub-images shall use subfields to fully describe the various parts or features found in the total image.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1...1		
XML Level 2	(ITL)biom:PhysicalFeatureDescriptionDetail	Cardinality	0...1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.042_0

SMT Descriptors

Subfields: Repeating values

Mnemonic	SMD_0			Conditionality	M↑
				Status	New - Active
Description	This field is used to describe the content of the SMT image to an extent greater than documented in Field 10.040: NCIC SMT code / SMT. It shall consist of one or more subfields. This version maintains the upper limit of 9 for all encodings. This field shall be used only when Field 10.003: Image type / IMT= "SCAR", "MARK", or "TATTOO". An SMT image consisting of several parts or sub-images shall use subfields to fully describe the various parts or features found in the total image.				
Field Min	n/a			Occur Min	1
Field Max	n/a			Occur Max	9
Char Types	n/a			Special Chars	n/a
Format	n/a			Constraints	n/a
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:PhysicalFeatureImage			Cardinality	1..1
XML Level 2	(ITL)biom:PhysicalFeatureDescriptionDetail			Cardinality	0..9
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

10.042_1

SMT Descriptors

SMT code indicator

Mnemonic	SMI			Conditionality	M↑
				Status	Active
Description	This information item shall identify the source of the image as being a scar, a mark or a tattoo.				
Field Min	3			Occur Min	1
Field Max	8			Occur Max	1
Char Types	A			Special Chars	None
Format	n/a			Constraints	
Code List	SMT DESCRIPTORS				
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:PhysicalFeatureImage			Cardinality	1..1
XML Level 2	(ITL)biom:PhysicalFeatureDescriptionDetail			Cardinality	0..9
XML Level 3	(ITL)biom:PhysicalFeatureCategoryCode			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.042_2

SMT Descriptors

Tattoo Class

Mnemonic	TAC			Conditionality	D
				Status	Active
Description	This information item shall be the general class code of tattoo chosen. For each general class of tattoo, there are several defined subclasses.				
Field Min	4	Occur Min	0		
Field Max	8	Occur Max	1		
Char Types	A	Special Chars	None		
Format	n/a	Constraints			
Code List	TATTOO CLASSES CODE				
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1..1		
XML Level 2	(ITL)biom:PhysicalFeatureDescriptionDetail	Cardinality	0..9		
XML Level 3	(ITL)biom:PhysicalFeatureClassCode	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

10.042_3

SMT Descriptors

Tattoo Subclass

Mnemonic	TSC			Conditionality	D
				Status	Active
Description	This information item of the subfield shall be the appropriate subclass code selected from the various subclasses of tattoos for each of the general classes.				
Field Min	3	Occur Min	0		
Field Max	11	Occur Max	1		
Char Types	A	Special Chars	None		
Format	n/a	Constraints			
Code List	TATTOO CLASSES CODE				
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1..1		
XML Level 2	(ITL)biom:PhysicalFeatureDescriptionDetail	Cardinality	0..9		
XML Level 3	(ITL)biom:PhysicalFeatureSubClassCode	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.042_4

SMT Descriptors

Tattoo Description

Mnemonic	TDS		Conditionality	D
			Status	Active
Description	This information item in the subfield shall be an ASCII text string that provides additional qualifiers to describe the image or portion of the image.			
Field Min	1	Occur Min	0	
Field Max	256	Occur Max	1	
Char Types	U	Special Chars	Any	
Format	n/a	Constraints		
Code List				
Source	ANSI/NIST ITL 2011: (Update 2013)			
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1...1	
XML Level 2	(ITL)biom:PhysicalFeatureDescriptionDetail	Cardinality	0..9	
XML Level 3	(ITL)biom:PhysicalFeatureDescriptionText	Cardinality	0..1	
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0 Yes DoD EBTS 4.0 Yes

10.043

Tattoo Color

Mnemonic	COL		Conditionality	D
			Status	Active
Description	This field is optional, but it can only be used when Field 10.042: SMT descriptors / SMD is in the record. It shall contain one subfield corresponding to each subfield contained in Field 10.042: SMT descriptors / SMD. Each subfield shall contain up to 6 information items that state the color(s) of the tattoo or part of the tattoo. For each subfield entry, the first one shall be the predominant color. Additional colors may be entered as optional subsequent information items of the form tattoo color code 1 through tattoo code 6. There need not be more than one information item. This field can only be used when Field 10.042: SMT descriptors / SMD is in the record.			
Field Min	n/a	Occur Min	0	
Field Max	n/a	Occur Max	1	
Char Types	D	Special Chars	n/a	
Format	n/a	Constraints	n/a	
Code List				
Source	ANSI/NIST ITL 2011: (Update 2013)			
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1...1	
XML Level 2	(ITL)biom:PhysicalFeatureDescriptionDetail	Cardinality	0..9	
XML Level 3	(ITL)biom:PhysicalFeatureColorDetail	Cardinality	0..1	
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0 Yes DoD EBTS 4.0 Yes

10.043_0

Tattoo Color

Subfields: repeating values in the same order as those of SMD

Mnemonic	COL_0	Conditionality	M↑
		Status	New - Active
Description	This field is optional, but it can only be used when Field 10.042: SMT descriptors / SMD is in the record. It shall contain one subfield corresponding to each subfield contained in Field 10.042: SMT descriptors / SMD. Each subfield shall contain up to 6 information items that state the color(s) of the tattoo or part of the tattoo. For each subfield entry, the first one shall be the predominant color. Additional colors may be entered as optional subsequent information items of the form tattoo color code 1 through tattoo code 6. There need not be more than one information item.		
Field Min	n/a	Occur Min	1
Field Max	n/a	Occur Max	9
Char Types	n/a	Special Chars	n/a
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1..1
XML Level 2	(ITL)biom:PhysicalFeatureDescriptionDetail	Cardinality	0..9
XML Level 3	(ITL)biom:PhysicalFeatureColorDetail	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

10.043_1

Tattoo Color

Tattoo Color Code 1

Mnemonic	TC1	Conditionality	O↑
		Status	Active
Description	This first information item is part of the Tattoo Color (COL) field. It lists the predominant color of the tattoo or part of the tattoo.		
Field Min	3	Occur Min	1
Field Max	7	Occur Max	1
Char Types	A	Special Chars	None
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1..1
XML Level 2	(ITL)biom:PhysicalFeatureDescriptionDetail	Cardinality	0..9
XML Level 3	(ITL)biom:PhysicalFeatureColorDetail	Cardinality	0..1
XML Level 4	(ITL)biom:PhysicalFeaturePrimaryColorCode	Cardinality	1..1
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.043_2

Tattoo Color

Tattoo Color Code 2

Mnemonic	TC2			Conditionality	O↑
				Status	Active
Description	This second information item is part of the Tattoo Color (COL) field. It lists the additional color of the tattoo or part of the tattoo.				
Field Min	3	Occur Min	0		
Field Max	7	Occur Max	1		
Char Types	A	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1...1		
XML Level 2	(ITL)biom:PhysicalFeatureDescriptionDetail	Cardinality	0..9		
XML Level 3	(ITL)biom:PhysicalFeatureColorDetail	Cardinality	0..1		
XML Level 4	(ITL)biom:PhysicalFeatureSecondaryColorCode	Cardinality	0..5		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

10.043_3

Tattoo Color

Tattoo Color Code 3

Mnemonic	TC3			Conditionality	O↑
				Status	Active
Description	This third information item is part of the Tattoo Color (COL) field. It lists the additional color of the tattoo or part of the tattoo.				
Field Min	3	Occur Min	0		
Field Max	7	Occur Max	1		
Char Types	A	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1...1		
XML Level 2	(ITL)biom:PhysicalFeatureDescriptionDetail	Cardinality	0..9		
XML Level 3	(ITL)biom:PhysicalFeatureColorDetail	Cardinality	0..1		
XML Level 4	(ITL)biom:PhysicalFeatureSecondaryColorCode	Cardinality	0..5		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.043_4

Tattoo Color

Tattoo Color Code 4

Mnemonic	TC4			Conditionality	O↑
				Status	Active
Description	This fourth information item is part of the Tattoo Color (COL) field. It lists the additional color of the tattoo or part of the tattoo.				
Field Min	3	Occur Min	0		
Field Max	7	Occur Max	1		
Char Types	A	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1...1		
XML Level 2	(ITL)biom:PhysicalFeatureDescriptionDetail	Cardinality	0..9		
XML Level 3	(ITL)biom:PhysicalFeatureColorDetail	Cardinality	0..1		
XML Level 4	(ITL)biom:PhysicalFeatureSecondaryColorCode	Cardinality	0..5		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

10.043_5

Tattoo Color

Tattoo Color Code 5

Mnemonic	TC5			Conditionality	O↑
				Status	Active
Description	This fifth information item is part of the Tattoo Color (COL) field. It lists the additional color of the tattoo or part of the tattoo.				
Field Min	3	Occur Min	0		
Field Max	7	Occur Max	1		
Char Types	A	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1...1		
XML Level 2	(ITL)biom:PhysicalFeatureDescriptionDetail	Cardinality	0..9		
XML Level 3	(ITL)biom:PhysicalFeatureColorDetail	Cardinality	0..1		
XML Level 4	(ITL)biom:PhysicalFeatureSecondaryColorCode	Cardinality	0..5		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-10: Photographic Body Part Imagery (including Face and S

Page 537 of 1037

10.043_6

Tattoo Color

Tattoo Color Code 6

Mnemonic	TC6			Conditionality	O↑
				Status	Active
Description	This sixth information item is part of the Tattoo Color (COL) field. It lists the additional color of the tattoo or part of the tattoo.				
Field Min	3	Occur Min	0		
Field Max	7	Occur Max	1		
Char Types	A	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1...1		
XML Level 2	(ITL)biom:PhysicalFeatureDescriptionDetail	Cardinality	0..9		
XML Level 3	(ITL)biom:PhysicalFeatureColorDetail	Cardinality	0..1		
XML Level 4	(ITL)biom:PhysicalFeatureSecondaryColorCode	Cardinality	0..5		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

10.044

Image Transform

Mnemonic	ITX			Conditionality	O
				Status	Active
Description	This optional field is used in the case when the image in this Type-10 record has been transformed from the original image. The untransformed image(s) (optionally) may be included in a Type-20 record. The information item in this field may be repeated if multiple transforms were performed. It can be used for any image type specified in Field 10.003: Image type / IMT .				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage/(ITL)biom:ImageCaptureDetail or (ITL)biom:PhysicalFeatureImage/(ITL)biom:ImageCaptureDetail	Cardinality	1...1		
XML Level 2	(ITL)biom:ImageTransformationCode	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.044_0

Image Transform

Subfields: Repeating values

Mnemonic	ITX_0			Conditionality	M↑
				Status	New - Active
Description	This optional field is used in the case when the image in this Type-10 record has been transformed from the original image. The untransformed image(s) (optionally) may be included in a Type-20 record. The information item in this field may be repeated if multiple transforms were performed. It can be used for any image type specified in Field 10.003: Image type / IMT .				
Field Min	3	Occur Min	1		
Field Max	11	Occur Max	18		
Char Types	A	Special Chars	None		
Format	n/a	Constraints	see Look Up Codes		
Code List	IMAGE TRANSFORM VALUES CODE				
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage/(ITL)biom:ImageCaptureDetail or (ITL)biom:PhysicalFeatureImage/(ITL)biom:ImageCaptureDetail			Cardinality	1..1
XML Level 2	(ITL)biom:ImageTransformationCode			Cardinality	0..18
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

10.045

Occlusions

Mnemonic	OCC			Conditionality	D
				Status	Active
Description	This optional field defines the outline and contents of any occlusions that partially or totally blocks the image of the face (IMT = 'FACE'). This is a contour or a polygon. Each point on the polygon is represented by a pair of information items.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage			Cardinality	1..1
XML Level 2	biom:FacelImageOcclusion			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.045_0

Occlusions

Subfields: Repeating values

Mnemonic	OCC_0			Conditionality	M↑
				Status	New - Active
Description	This optional field defines the outline and contents of any occlusions that partially or totally blocks the image of the face (IMT = 'FACE'). This is a contour or a polygon. Each point on the polygon is represented by a pair of information items.				
Field Min	n/a	Occur Min	1		
Field Max	n/a	Occur Max	16		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage	Cardinality	1..1		
XML Level 2	biom:FacelImageOcclusion	Cardinality	0..16		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

10.045_1

Occlusions

Occlusion Opacity

Mnemonic	OCY			Conditionality	M↑
				Status	Active
Description	This field contains a code from the Occlusion Opacity Code table.				
Field Min	1	Occur Min	1		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars	n/a		
Format	n/a	Constraints	OCY = T, I, L or S		
Code List	OCCLUSION OPACITY CODE				
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage	Cardinality	1..1		
XML Level 2	biom:FacelImageOcclusion	Cardinality	0..16		
XML Level 3	biom:FacelImageOcclusionOpacityCode	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.045_2

Occlusions

Occlusion Type

Mnemonic	OCT			Conditionality	M↑
				Status	Active
Description	This field contains a code from the Occlusion Type Code table.				
Field Min	1	Occur Min	1		
Field Max	1	Occur Max	1		
Char Types	N	Special Chars	n/a		
Format	n/a	Constraints	OCT = H, S, C, R, or O		
Code List	OCCLUSION TYPE CODE				
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage	Cardinality	1..1		
XML Level 2	biom:FacelImageOcclusion	Cardinality	0..16		
XML Level 3	biom:FacelImageOcclusionCategoryCode	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

10.045_3

Occlusions

Number of Points

Mnemonic	NOP			Conditionality	M↑
				Status	Active
Description	This field shall specify the number of vertices.				
Field Min	1	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	n/a		
Format	n/a	Constraints	3 <= NOP <=99		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage	Cardinality	1..1		
XML Level 2	biom:FacelImageOcclusion	Cardinality	0..16		
XML Level 3	biom:PositionPolygonVertexQuantity	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-10: Photographic Body Part Imagery (including Face and S

Page 541 of 1037

10.045_4

Occlusions

Horizontal Point Offset

Mnemonic	HPO			Conditionality	M↑
				Status	Active
Description	This field contains information items are pairs of x and y coordinates of vertices. The horizontal offsets (X) are the pixel counts to the right. Pairings are inserted for each vertex, up to the NOP. The HPO and VPO two information items are repeated as pairs, in order by point following the path, up to the final point - for a total of NOP pairs				
Field Min	1	Occur Min	3		
Field Max	5	Occur Max	NOP		
Char Types	N	Special Chars	n/a		
Format	n/a	Constraints	0 <= HPO <= HLL		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage	Cardinality	1..1		
XML Level 2	biom:FacelImageOcclusion	Cardinality	0..16		
XML Level 3	biom:PositionPolygonVertex	Cardinality	3..99		
XML Level 4	biom:PositionHorizontalCoordinateValue	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

10.045_5

Occlusions

Vertical Point Offset

Mnemonic	VPO			Conditionality	M↑
				Status	Active
Description	This field contains information items are pairs of x and y coordinates of vertices. The vertical offsets (Y) are the pixel counts down from the origin. Pairings are inserted for each vertex, up to the NOP. The HPO and VPO two information items are repeated as pairs, in order by point following the path, up to the final point - for a total of NOP pairs				
Field Min	1	Occur Min	3		
Field Max	5	Occur Max	NOP		
Char Types	N	Special Chars	n/a		
Format	n/a	Constraints	0 <= VPO <= VLL		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage	Cardinality	1..1		
XML Level 2	biom:FacelImageOcclusion	Cardinality	0..16		
XML Level 3	biom:PositionPolygonVertex	Cardinality	3..99		
XML Level 4	biom:PositionVerticalCoordinateValue	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

10.046

Image Subject Condition

Mnemonic	SUB		Conditionality	D	
			Status	New - Active	
Description	This field is optional. This field is particularly useful if the image is obtained from a deceased person. However, its use is not limited to such circumstances. Some implementation domains support the submission of fingerprints taken from deceased individuals as latent prints, due to the quality of the friction ridges and the resulting images. In such cases, SSC is specified as D. For latent images taken from a surface, the value is typically X.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage/(ITL)biom:ImageCaptureDetail/biom:SubjectExistentialDetails or (ITL)biom:PhysicalFeatureImage/(ITL)biom:ImageCaptureDetail/biom:SubjectExistentialDetails		Cardinality	1...1	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

10.046_1

Image Subject Condition

Subject Status Code

Mnemonic	SSC		Conditionality	M↑	
			Status	New - Active	
Description	The first information item is mandatory if this field is present. It is subject status code (SSC).				
Field Min	1		Occur Min	1	
Field Max	1		Occur Max	1	
Char Types	A		Special Chars	n/a	
Format	n/a		Constraints	SSC = X, A or D	
Code List	SUBJECT STATUS CODE				
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage/(ITL)biom:ImageCaptureDetail/biom:SubjectExistentialDetails or (ITL)biom:PhysicalFeatureImage/(ITL)biom:ImageCaptureDetail/biom:SubjectExistentialDetails		Cardinality	1...1	
XML Level 2	biom:SubjectExistentialStatusCode		Cardinality	1..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

10.046_2

Image Subject Condition

Subject Body Status Code

Mnemonic	SBSC			Conditionality	M↑
				Status	New - Active
Description	The second information item shall be entered if and only if SSC is D. It is subject body status code (SBSC). Its purpose is to indicate whether the information relates to an entire corpse or a separate body part.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	N	Special Chars	n/a		
Format	n/a	Constraints	SBSC = 1 or 2, positive integer		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage/(ITL)biom:ImageCaptureDetail/biom:SubjectExistentialDetails or (ITL)biom:PhysicalFeatureImage/(ITL)biom:ImageCaptureDetail/biom:SubjectExistentialDetails			Cardinality	1...1
XML Level 2	biom:SubjectBodyStatusCode			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

10.046_3

Image Subject Condition

Subject Body Class Code

Mnemonic	SBCC			Conditionality	M↑
				Status	New - Active
Description	The third information item shall be entered if and only if SSC is D. It is subject body class code (SBCC).				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	N	Special Chars	n/a		
Format	n/a	Constraints	SBCC = 1, 2, or 3, positive integer		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage/(ITL)biom:ImageCaptureDetail/biom:SubjectExistentialDetails or (ITL)biom:PhysicalFeatureImage/(ITL)biom:ImageCaptureDetail/biom:SubjectExistentialDetails			Cardinality	1...1
XML Level 2	biom:SubjectBodyClassCode			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.047

Capture Organization Name

Mnemonic	CON		Conditionality	0	
			Status	New - Active	
Description	Describes the agency that created the record. Since the record may have been forwarded by another agency to the final destination, Field 1.008: Originating agency identifier / ORI is used to indicate the transmitting organization. In many implementation domains, there are a limited number of transmission organizations that can send data. Therefore, the agency listed in SRC may send the transaction to another location that has access rights to the final destination. This intermediary may add information to the transaction, as well. The final transmitting organization code is listed in Field 1.008: Originating agency identifier / ORI. Its name may be entered in Originating agency name /OAN in Field 1.017: Agency names				
Field Min	1	Occur Min	0		
Field Max	Unlimited	Occur Max	1		
Char Types	U	Special Chars	n/a		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage/biom:ImageCaptureDetail/(ITL)biom:CaptureOrga nization or (ITL)biom:PhysicalFeatureImage/(ITL)biom:ImageCaptureDetail/(ITL)bio m:CaptureOrganization	Cardinality	1...1		
XML Level 2	nc:OrganizationUnitName	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

10.048

Suspected Patterned Injury Detail

Mnemonic	PID		Conditionality	0	
			Status	New - Active	
Description	This field contains information concerning suspected patterned injuries. This optional field defines the outline and contents of any occlusions that partially or totally blocks the image of the face (IMT = 'FACE'). This is a contour or a polygon. Values for Field 10.003: Image type / IMT of SCAR, MARK, TATTOO, MISSING, OTHER and CONDITION shall not be used for patterned injuries, and thus this field shall not appear if IMT is set to any of those values. Field 10.041: SMT size or size of injury or identifying characteristic / SMS should be included in the record if this field is present.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage or (ITL)biom:PhysicalFeatureImage	Cardinality	1...1		
XML Level 2	biom:PatternedInjuryDetail	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

10.048_0

Suspected Patterned Injury Detail

Subfields: Repeating sets of information items

Mnemonic	PID_0			Conditionality	M↑
				Status	New - Active
Description	This field contains information concerning suspected patterned injuries. This optional field defines the outline and contents of any occlusions that partially or totally blocks the image of the face (IMT = 'FACE'). This is a contour or a polygon. Values for Field 10.003: Image type / IMT of SCAR, MARK, TATTOO, MISSING, OTHER and CONDITION shall not be used for patterned injuries, and thus this field shall not appear if IMT is set to any of those values. Field 10.041: SMT size or size of injury or identifying characteristic / SMS should be included in the record if this field is present.				
Field Min	n/a	Occur Min	1		
Field Max	n/a	Occur Max	Unlimited		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage or (ITL)biom:PhysicalFeatureImage			Cardinality	1...1
XML Level 2	biom:PatternedInjuryDetail			Cardinality	0...*
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

10.048_1

Suspected Patterned Injury Detail

ADA Reference Code List

Mnemonic	PARC			Conditionality	O↑
				Status	New - Active
Description	This field contains a code value characterizing a patterned injury in ANSI/ADA Standard No. 1077 – Dental Biometric Descriptors.				
Field Min	1	Occur Min	0		
Field Max	30	Occur Max	1		
Char Types	NS	Special Chars	n/a		
Format	n/a	Constraints	Valid Code from ANSI/ADA Standard No. 1077		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:FacelImage or (ITL)biom:PhysicalFeatureImage			Cardinality	1...1
XML Level 2	biom:PatternedInjuryDetail			Cardinality	0...*
XML Level 3	biom:PatternedInjuryADAResponseCodeList/biom:PatternedInjuryADAReferenceCodeText			Cardinality	0...*
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

10.048_2

Suspected Patterned Injury Detail

Additional Descriptive Text

Mnemonic	PADT	Conditionality	O↑
		Status	New - Active
Description	This field contains a Unicode free text information item description of the patterned injury.		
Field Min	1	Occur Min	0
Field Max	Unlimited	Occur Max	1
Char Types	U	Special Chars	n/a
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	(ITL)biom:FacelImage or (ITL)biom:PhysicalFeatureImage	Cardinality	1...1
XML Level 2	biom:PatternedInjuryDetail	Cardinality	0...*
XML Level 3	biom:PatternedInjuryDescriptiveText	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

10.049

Cheilosopic Image Description

Mnemonic	CID	Conditionality	D
		Status	New - Active
Description	This field contains a set of subfield relaying information about the Cheilosopic Image. If this field is encoded in Traditional format, each of the values in information items designated as a 'list' shall be separated by ' ' (vertical bar). For XML each value in a list should be entered as a separate element. This field may be used only if Field 10.003: Image type / IMT is LIP. The vertical bar " " is used in Traditional format in a list as a separating character. In XML encoding, each value (including <>) is a separate element and the vertical bar does not appear.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	n/a
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1...1
XML Level 2	biom:CheilosopicImageInformation	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.049_1

Cheiloscopic Image Description

Lip Print Width

Mnemonic	LPW			Conditionality	O↑
				Status	New - Active
Description	It corresponds to the distance from feature point code 8.4 to feature point code 8.3 on the MOUTH in Feature point codes defined in ISO/IEC 14496-2 FEATURE POINT CODES. It is measured in millimeters.				
Field Min	1	Occur Min	0		
Field Max	4	Occur Max	1		
Char Types	N	Special Chars	n/a		
Format	n/a	Constraints	positive integer		
Code List	ISO/IEC 14496-2 FEATURE POINT CODES				
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1...1		
XML Level 2	biom:CheiloscopicalImageInformation	Cardinality	0..1		
XML Level 3	biom:LipPrintWidth	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

10.049_2

Cheiloscopic Image Description

Lip Print Height

Mnemonic	LPH			Conditionality	O↑
				Status	New - Active
Description	It contains the distance from feature points 8.2 to feature point 2.3 PLUS the distance from feature point 2.2 to feature 8.1 on the MOUTH in Feature point codes defined ISO/IEC 14496-2 FEATURE POINT CODES. It is measured in millimeters.				
Field Min	1	Occur Min	0		
Field Max	4	Occur Max	1		
Char Types	N	Special Chars	n/a		
Format	n/a	Constraints	positive integer		
Code List	ISO/IEC 14496-2 FEATURE POINT CODES				
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1...1		
XML Level 2	biom:CheiloscopicalImageInformation	Cardinality	0..1		
XML Level 3	biom:LipPrintHeight	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

10.049_3

Cheiloscopic Image Description

Philtrum Width

Mnemonic	PHW			Conditionality	O↑
				Status	New - Active
Description	It is the distance from feature point 8.9 to 8.10 as shown in Feature point codes defined in ISO/IEC 14496-2 FEATURE POINT CODES. It is measured in millimeters.				
Field Min	1	Occur Min	0		
Field Max	4	Occur Max	1		
Char Types	N	Special Chars	n/a		
Format	n/a	Constraints	positive integer		
Code List	ISO/IEC 14496-2 FEATURE POINT CODES				
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1..1		
XML Level 2	biom:CheiloscopicalImageInformation	Cardinality	0..1		
XML Level 3	biom:PhiltrumWidth	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

10.049_4

Cheiloscopic Image Description

Philtrum Height

Mnemonic	PHH			Conditionality	O↑
				Status	New - Active
Description	PHH is the distance in millimeters from feature point 8.1 to 9.15 (on the nose).				
Field Min	1	Occur Min	0		
Field Max	4	Occur Max	1		
Char Types	N	Special Chars	n/a		
Format	n/a	Constraints	positive integer		
Code List	CHEILIOSCOPIC CHARACTERIZATION CODES				
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1..1		
XML Level 2	biom:CheiloscopicalImageInformation	Cardinality	0..1		
XML Level 3	biom:PhiltrumHeight	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

10.049_5

Cheiloscopic Image Description

Upper Lip Characterization List

Mnemonic	ULCL	Conditionality	O↑
		Status	New - Active
Description	The fifth information item, upper lip print characterization list/ ULCL, is optional. It is text that may be used to describe the print. The characterizations are those developed by Suzuki and Tsuchihashi. It is highly recommended that any distinctive patterns be outlined using Field 10.033: Feature contours / FEC. This field's XML reference is not in the NIEM Biometrics domain table. Coded as biom domain by NIST Appendix G.		
Field Min	1	Occur Min	0
Field Max	2	Occur Max	1
Char Types	AS	Special Chars	n/a
Format	n/a	Constraints	list may have up to 5 values
Code List	CHEILIOSCOPIC CHARACTERIZATION CODES		
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1..1
XML Level 2	biom:CheilosopicImageInformation	Cardinality	0..1
XML Level 3	biom:UpperLipCharacterizationCodeList/biom:LipCharacterizationCode	Cardinality	0..5
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

10.049_6

Cheiloscopic Image Description

Lower Lip Characterization List

Mnemonic	LLCL	Conditionality	O↑
		Status	New - Active
Description	The fifth information item, lower lip print characterization list/ LLCL, is optional. It is text that may be used to describe the print. The characterizations are those developed by Suzuki and Tsuchihashi. It is highly recommended that any distinctive patterns be outlined using Field 10.033: Feature contours / FEC. This field's XML reference is not in the NIEM Biometrics domain table. Coded as biom domain by NIST Appendix G.		
Field Min	1	Occur Min	0
Field Max	2	Occur Max	1
Char Types	AS	Special Chars	For traditional encoding, the special character “ ” is allowed as a separator character
Format	n/a	Constraints	list may have up to 5 values
Code List	CHEILIOSCOPIC CHARACTERIZATION CODES		
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1..1
XML Level 2	biom:CheilosopicImageInformation	Cardinality	0..1
XML Level 3	biom:LowerLipCharacterizationCodeList/biom:LipCharacterizationCode	Cardinality	0..5
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

10.049_7

Cheiloscopic Image Description

Lip Contact Line Descriptor

Mnemonic	LCLD			Conditionality	O↑		
				Status	New - Active		
Description	Contains the LIP CONTACT LINE DESCRIPTOR CODES.						
Field Min	1	Occur Min	0				
Field Max	1	Occur Max	1				
Char Types	A	Special Chars	n/a				
Format	n/a	Constraints	LCLD = L, C or M				
Code List	LIP CONTACT LINE DESCRIPTOR CODES						
Source	ANSI/NIST ITL 2011: (Update 2013)						
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1..1				
XML Level 2	biom:CheilosopicImageInformation	Cardinality	0..1				
XML Level 3	biom:LipContactLineDescriptorCode	Cardinality	0..1				
XML Level 4		Cardinality					
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

10.049_8

Cheiloscopic Image Description

Lip Print Characterization Text

Mnemonic	LPCT			Conditionality	O↑		
				Status	New - Active		
Description	Description of the lip print characterization. This field is mandatory if LPCL contains the value O. It is UNICODE free text.						
Field Min	1	Occur Min	0				
Field Max	Unlimited	Occur Max	1				
Char Types	U	Special Chars	n/a				
Format	n/a	Constraints					
Code List							
Source	ANSI/NIST ITL 2011: (Update 2013)						
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1..1				
XML Level 2	biom:CheilosopicImageInformation	Cardinality	0..1				
XML Level 3	biom:LipPrintCharacterizationText	Cardinality	0..1				
XML Level 4		Cardinality					
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

10.049_9

Cheiloscopic Image Description

Lip Print Pathologies and Peculiarities List

Mnemonic	LPPL	Conditionality	O↑
		Status	New - Active
Description	If Type-code 99 is selected, then LPPT shall be used to describe the condition. Only one of the values 8, 9, 10, 11 or 12 may appear in the list. List may have up to 13 values. Only one of the values 8, 9, 10 11, or 12 may appear in the list. List may have up to 13 values. This field's XML reference is not in the NIEM Biometrics domain table. Coded as biom domain by NIST Appendix G.		
Field Min	1	Occur Min	0
Field Max	Unlimited	Occur Max	1
Char Types	NS	Special Chars	For traditional encoding, the special character “ ” is allowed as a separator character
Format	n/a	Constraints	8, 9, 10 11, or 12
Code List	LIP PATHOLOGIES AND PECULIARITIES CODE		
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1..1
XML Level 2	biom:CheiloscopicalImageInformation	Cardinality	0..1
XML Level 3	biom:LipPrintPathologiesPeculiaritiesCodeList/biom:LipPrintPathologiesPeculiaritiesCode	Cardinality	0..13
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

10.049_10

Cheiloscopic Image Description

Lip Print Pathologies and Peculiarities Descriptive Text

Mnemonic	LPPT	Conditionality	O↑
		Status	New - Active
Description	This field contains descriptive text regarding the lip print pathologies and peculiarities. This field shall appear if LPPL has a value of 99. This field's XML reference is not in the NIEM Biometrics domain table. Coded as biom domain by NIST Appendix G.		
Field Min	1	Occur Min	0
Field Max	Unlimited	Occur Max	1
Char Types	U	Special Chars	n/a
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1..1
XML Level 2	biom:CheiloscopicalImageInformation	Cardinality	0..1
XML Level 3	biom:LipPrintPathologiesPeculiaritiesText	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

10.049_11

Cheiloscopic Image Description

Lip Print Surface List

Mnemonic	LPSL			Conditionality	O↑
				Status	New - Active
Description	Multiple codes may be selected from Lip Print Surface codes, since a lip print may be on multiple surfaces. An exemplar of a lip print may be made on a standard surface, such as a glass photographic slide mount. If a Type-code other than 1 is selected, then lip print surface descriptive text / LPST shall be entered. If Type-code 1 is chosen, then no other values shall be entered in the list. List may have up to 3 values. If Typecode 1 is chosen, no other values are allowed. This field's XML reference is not in the NIEM Biometrics domain table. Coded as biom domain by NIST Appendix G.				
Field Min	1	Occur Min	0		
Field Max	Unlimited	Occur Max	1		
Char Types	NS	Special Chars	For traditional encoding, the special character " " is allowed as a separator character		
Format	n/a	Constraints			
Code List	LIP PRINT SURFACE CODE				
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1..1		
XML Level 2	biom:CheiloscopiImageInformation	Cardinality	0..1		
XML Level 3	biom:LipPrintSurfaceCodeList/biom:LipPrintSurfaceCode	Cardinality	0..3		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

10.049_12

Cheiloscopic Image Description

Lip Print Surface Descriptive Text

Mnemonic	LPST			Conditionality	O↑
				Status	New - Active
Description	This field describes the surface on which the lip print occurs. This field contains descriptive text for the lip print surface. It should be entered if LPSL has a value other than 1.				
Field Min	1	Occur Min	0		
Field Max	Unlimited	Occur Max	1		
Char Types	U	Special Chars	n/a		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1..1		
XML Level 2	biom:CheiloscopiImageInformation	Cardinality	0..1		
XML Level 3	biom:LipPrintSurfaceText	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-10: Photographic Body Part Imagery (including Face and S

Page 553 of 1037

10.049_13

Cheiloscopic Image Description

Lip Print Medium Code

Mnemonic	LPMC			Conditionality	O↑
				Status	New - Active
Description	This field shall be selected from Lip Print Medium Codes. If Type-code 9 is selected, then lip print medium descriptive text / LPMT shall be entered.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	N	Special Chars	n/a		
Format	n/a	Constraints			
Code List	LIP PRINT MEDIUM CODE				
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1..1		
XML Level 2	biom:CheilosopicImageInformation	Cardinality	0..1		
XML Level 3	biom:LipPrintMediumCode	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

10.049_14

Cheiloscopic Image Description

Lip Print Medium Descriptive Text

Mnemonic	LPMT			Conditionality	O↑
				Status	New - Active
Description	This field describes the lip print medium. If LPMC has a value of 9, then it shall be entered.				
Field Min	1	Occur Min	0		
Field Max	Unlimited	Occur Max	1		
Char Types	U	Special Chars	n/a		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1..1		
XML Level 2	biom:CheilosopicImageInformation	Cardinality	0..1		
XML Level 3	biom:LipPrintMediumText	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.049_15

Cheiloscopic Image Description

Facial Hair Descriptive Text

Mnemonic	FHDT			Conditionality	O↑
				Status	New - Active
Description	This field is used to describe the presence, pattern, distribution and density of the follicles if they are visible in the image.				
Field Min	1	Occur Min	0		
Field Max	Unlimited	Occur Max	1		
Char Types	U	Special Chars	n/a		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1...1		
XML Level 2	biom:CheiloscopicalImageInformation	Cardinality	0..1		
XML Level 3	biom:PersonFacialHairText	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

10.049_16

Cheiloscopic Image Description

Lip Print Position and Tension Text

Mnemonic	LPDT			Conditionality	O↑
				Status	New - Active
Description	This information item should describe in general terms the probable, possible or verified relative position of the lips to each other and the muscle tension and shape of the lip print. There may be considerable variation in lip prints if the lips were pursed or open or if a print is taken post-mortem.				
Field Min	1	Occur Min	0		
Field Max	Unlimited	Occur Max	1		
Char Types	U	Special Chars	n/a		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1...1		
XML Level 2	biom:CheiloscopicalImageInformation	Cardinality	0..1		
XML Level 3	biom:LipPositionTensionDescriptiveText	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.049_17

Cheiloscopical Image Description

Lip Print Additional Descriptive Text

Mnemonic	LPAT			Conditionality	O↑
				Status	New - Active
Description	This field should be used to describe any relevant information that may assist in the analysis of the cheiloscopical image.				
Field Min	1	Occur Min	0		
Field Max	Unlimited	Occur Max	1		
Char Types	U	Special Chars	n/a		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1...1		
XML Level 2	biom:CheiloscopicalImageInformation	Cardinality	0..1		
XML Level 3	biom:LipPrintDescriptiveText	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

10.049_18

Cheiloscopical Image Description

Lip Print Comparison Descriptive Text

Mnemonic	LPCD			Conditionality	O↑
				Status	New - Active
Description	This field may be used by an analyst to note the results of a comparison against another image. If this information item is present, then Field 10.039: Type-10 reference number / T10 shall be present in the record to indicate the image against which the image in this instance of the Record Type-10 is compared.				
Field Min	1	Occur Min	0		
Field Max	Unlimited	Occur Max	1		
Char Types	U	Special Chars	n/a		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1...1		
XML Level 2	biom:CheiloscopicalImageInformation	Cardinality	0..1		
XML Level 3	biom:LipPrintComparisonDescriptiveText	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.05

Dental Visual Image Data Information

Mnemonic	VID			Conditionality	0
				Status	New - Active
Description	This field is used to highlight distinctive features in an image. This field shall only be used if Field 10.003: Image type / IMT has a value of EXTRAORAL or INTRAORAL. When distinct features are outlined for comparison on an exemplar and a latent image, then Field 10.039: Type-10 reference number / T10 should be used to link the two Type-10 records.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:PhysicalFeatureImage			Cardinality	1..1
XML Level 2	biom:DentalVisualImageDataInformation			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

10.050_1

Dental Visual Image Data Information

Visual Image View Code

Mnemonic	VIVC			Conditionality	M↑
				Status	New - Active
Description	It is an entry selected from the "View Code" column of Dental Image codes.				
Field Min	3		Occur Min	1	
Field Max	4		Occur Max	1	
Char Types	A		Special Chars	n/a	
Format	n/a		Constraints		
Code List	DENTAL IMAGE CODE				
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:PhysicalFeatureImage			Cardinality	1..1
XML Level 2	biom:DentalVisualImageDataInformation			Cardinality	0..1
XML Level 3	biom:DentalVisualImageCode			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

10.050_2

Dental Visual Image Data Information

Visual Image Additional Descriptive Text

Mnemonic	VIDT			Conditionality	D
				Status	New - Active
Description	This field contains descriptive text on the Dental Visual Image.				
Field Min	1	Occur Min	0		
Field Max	Unlimited	Occur Max	1		
Char Types	U	Special Chars	n/a		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1...1		
XML Level 2	biom:DentalVisualImageDataInformation	Cardinality	0..1		
XML Level 3	biom:DentalVisualImageDescriptiveText	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

10.050_3

Dental Visual Image Data Information

Visual Image Comparison Descriptive Text

Mnemonic	VICD			Conditionality	D
				Status	New - Active
Description	This field is normally used by an analyst to note the results of a comparison against another image. If this information item is present, then Field 10.039: Type-10 reference number / T10 shall be present in the record to indicate the image against which the image in this instance of the Record Type-10 is compared.				
Field Min	1	Occur Min	0		
Field Max	Unlimited	Occur Max	1		
Char Types	U	Special Chars	n/a		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1...1		
XML Level 2	biom:DentalVisualImageDataInformation	Cardinality	0..1		
XML Level 3	biom:DentalVisualImageComparisonDescriptiveText	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.051

Ruler or Scale Presence

Mnemonic	RSP		Conditionality	0
			Status	New - Active
Description	This set of fields allows the user to state whether a ruler or other known scale is present in the image.			
Field Min	n/a	Occur Min	0	
Field Max	n/a	Occur Max	1	
Char Types	n/a	Special Chars	n/a	
Format	n/a	Constraints	n/a	
Code List				
Source	ANSI/NIST ITL 2011: (Update 2013)			
XML Level 1	(ITL)biom:FacelImage or (ITL)biom:PhysicalFeatureImage	Cardinality	1..1	
XML Level 2	dod-ebts:RulerScalePresenceInformation	Cardinality	0..1	
XML Level 3		Cardinality		
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0 No DoD EBTS 4.0 Yes

10.051_1

Ruler or Scale Presence

Ruler or Scale Units

Mnemonic	RSU		Conditionality	D
			Status	New - Active
Description	This field indicates the units of measurement visible on the ruler or measurement scale. Valid entries are: IN = inches; MM = millimeters; BOTH = both inches and millimeters			
Field Min	2	Occur Min	0	
Field Max	4	Occur Max	1	
Char Types	A	Special Chars	n/a	
Format	n/a	Constraints	RSU = IN, MM, or BOTH	
Code List				
Source	ANSI/NIST ITL 2011: (Update 2013)			
XML Level 1	(ITL)biom:FacelImage or (ITL)biom:PhysicalFeatureImage	Cardinality	1..1	
XML Level 2	dod-ebts:RulerScalePresenceInformation	Cardinality	0..1	
XML Level 3	dod-ebts:RulerScaleUnitCode	Cardinality	0..1	
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0 No DoD EBTS 4.0 Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.051_2

Ruler or Scale Presence

Ruler or Scale Make

Mnemonic	RSM	Conditionality	D
		Status	New - Active
Description	This field lists the maker of the ruler or scale (if known).		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	n/a
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	(ITL)biom:FacelImage or (ITL)biom:PhysicalFeatureImage	Cardinality	1..1
XML Level 2	dod-ebts:RulerScalePresenceInformation	Cardinality	0..1
XML Level 3	dod-ebts:RulerScaleMakeText	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

10.051_3

Ruler or Scale Presence

Ruler or Scale Model

Mnemonic	RSO	Conditionality	O
		Status	New - Active
Description	This field lists the model of the ruler or scale (if known). For patterned injuries, the ABFO # 2 Reference Scale (commonly called the ABFO # 2 ruler) shall be used.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	n/a
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	(ITL)biom:FacelImage or (ITL)biom:PhysicalFeatureImage	Cardinality	1..1
XML Level 2	dod-ebts:RulerScalePresenceInformation	Cardinality	0..1
XML Level 3	dod-ebts:RulerScaleModelText	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.902

Annotated Information

Mnemonic	ANN			Conditionality	0
				Status	Active
Description	This is an optional field, listing the operations performed on the original source in order to prepare it for inclusion in a biometric record type.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	biom:ProcessAnnotation			Cardinality	0...*
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

10.902_0

Annotated Information

Subfields: Repeating sets of information items

Mnemonic	ANN			Conditionality	M↑
				Status	Active
Description	This is an optional field, listing the operations performed on the original source in order to prepare it for inclusion in a biometric record type.				
Field Min	n/a		Occur Min	1	
Field Max	n/a		Occur Max	Unlimited	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	biom:ProcessAnnotation			Cardinality	0...*
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

10.902_1

Annotated Information

Greenwich Mean Time

Mnemonic	GMT			Conditionality	M↑
				Status	Active
Description	This information item is the Greenwich Mean Time (GMT) when the processing occurred. The data is formatted as YYYYMMDDhhmmssZ, where the Z indicates the zone description of 0 hours. This time is independent of the actual time zone where the time and date is recorded.				
Field Min	Dependent on encoding		Occur Min	1	
Field Max	Dependent on encoding		Occur Max	1	
Char Types	AN		Special Chars	None	
Format	YYYYMMDDHHMMSSZ - for Traditional Encoding		Constraints		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	biom:ProcessAnnotation			Cardinality	0..*
XML Level 2	biom:ProcessUTCDate/nc:DateTime			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

10.902_2

Annotated Information

Processing Algorithm Name / Version

Mnemonic	NAV			Conditionality	M↑
				Status	Active
Description	This information item shall contain text identifying the name and version of the processing algorithm, application, procedure, or workstation				
Field Min	1		Occur Min	1	
Field Max	Unlimited		Occur Max	1	
Char Types	U		Special Chars	None	
Format	n/a		Constraints		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	biom:ProcessAnnotation			Cardinality	0..*
XML Level 2	biom:ProcessName			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.902_3

Annotated Information

Algorithm Owner

Mnemonic	OWN	Conditionality	M↑
		Status	Active
Description	This information item shall contain an unformatted text string of up to 64 characters with the contact information for the organization that owns the processing algorithm or latent workstation. Where there is no 'algorithm owner,' enter N/A.		
Field Min	1	Occur Min	1
Field Max	64	Occur Max	1
Char Types	U	Special Chars	None
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	biom:ProcessAnnotation	Cardinality	0..*
XML Level 2	biom:ProcessOwnerText	Cardinality	1..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

10.902_4

Annotated Information

Process Description

Mnemonic	PRO	Conditionality	M↑
		Status	Active
Description	This information item field shall contain text describing a process or procedure applied to the sample in this Type-9 record.		
Field Min	1	Occur Min	1
Field Max	Unlimited	Occur Max	1
Char Types	U	Special Chars	None
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	biom:ProcessAnnotation	Cardinality	0..*
XML Level 2	biom:ProcessDescriptionText	Cardinality	1..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.903

Device Unique Identifier

Mnemonic	DUI			Conditionality	O		
				Status	Active		
Description	The DUI shall contain a string uniquely identifying the device or source of the data. This field shall be one of the following: a Host PC MAC address (identified by the first character "M"), a Host PC processor ID (identified by the first character "P"). since it is available in the Make / Model / Serial Number field.						
Field Min	13			Occur Min	0		
Field Max	16			Occur Max	1		
Char Types	ANS			Special Chars	Any		
Format	n/a			Constraints	first character = M or P		
Code List							
Source	ANSI/NIST ITL 2011: (Update 2013)						
XML Level 1	biom:BiometricCapture			Cardinality	1..1		
XML Level 2	(ITL)biom:CaptureDeviceIdentification/nc:IdentificationID			Cardinality	0..1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

10.904

Make/Model/Serial Number

Mnemonic	MMS			Conditionality	O		
				Status	Active		
Description	The MMS contains the make, model and serial number for the capture device. It shall consist of three information items. Each information item shall be 1 to 50 characters. Unknown information may be indicated with the value "0." Any or all information items may indicate that information is unknown with the value "0".						
Field Min	n/a			Occur Min	0		
Field Max	n/a			Occur Max	1		
Char Types	n/a			Special Chars	n/a		
Format	n/a			Constraints	n/a		
Code List							
Source	ANSI/NIST ITL 2011: (Update 2013)						
XML Level 1	biom:BiometricCapture			Cardinality	1..1		
XML Level 2				Cardinality			
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-10: Photographic Body Part Imagery (including Face and S

Page 564 of 1037

10.904_1

Make/Model/Serial Number

Make

Mnemonic	MAK			Conditionality	M↑
				Status	Active
Description	The name of the manufacturer for the capture device.				
Field Min	1	Occur Min	1		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	biom:BiometricCapture	Cardinality	1...1		
XML Level 2	biom:CaptureDeviceMakeText	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

10.904_2

Make/Model/Serial Number

Model

Mnemonic	MOD			Conditionality	M↑
				Status	Active
Description	The model number for the capture device.				
Field Min	1	Occur Min	1		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	biom:BiometricCapture	Cardinality	1...1		
XML Level 2	biom:CaptureDeviceModelText	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-10: Photographic Body Part Imagery (including Face and S

Page 565 of 1037

10.904_3

Make/Model/Serial Number

Serial Number

Mnemonic	SER	Conditionality	M↑
		Status	Active
Description	The serial number for the capture device.		
Field Min	1	Occur Min	1
Field Max	50	Occur Max	1
Char Types	U	Special Chars	Any
Format	n/a	Constraints	n/a
Code List			
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	biom:BiometricCapture	Cardinality	1...1
XML Level 2	biom:CaptureDeviceSerialNumberText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

10.992

Biometric Cross Reference Identification

Mnemonic	T2C	Conditionality	0
		Status	New - Active
Description	When used, it contains the IDC value of the Type-2 record that contains relevant biographic information and other data concerning the subject of this instance of the record, who may be different from the subject of the transaction.		
Field Min	1	Occur Min	0
Field Max	2	Occur Max	1
Char Types	N	Special Chars	n/a
Format	n/a	Constraints	0 < T2C < 99, non-negative integer
Code List			
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	(ITL)biom:Type2CrossReferenceIdentification/nc:IdentificationID	Cardinality	0..1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.993

Source Agency Name

Mnemonic	SAN		Conditionality	0	
			Status	Active	
Description	This is an optional field. It may contain up to 125 Unicode characters. It is the name of the agency referenced in Field xx.004: Source agency / SRC for record types 9-99.				
Field Min	1		Occur Min	0	
Field Max	125		Occur Max	1	
Char Types	U		Special Chars	Any	
Format	n/a		Constraints		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	biom:BiometricCapture		Cardinality	1..1	
XML Level 2	(ITL)biom:CaptureOrganization		Cardinality	1..1	
XML Level 3	nc:OrganizationName		Cardinality	0..1	
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

10.995

Associated Context

Mnemonic	ASC		Conditionality	0	
			Status	Active	
Description	This optional field refers to one or more Type 21 Records with the same ACN. Type 21 Records contain images that are NOT used to derive the biometric data in Field 13.999: Latent friction ridge image (DATA) but that may be relevant to the collection of that data, such as general scenes of the area where a latent print was found.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	biom:AssociatedContext		Cardinality	0..1	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.995_0

Associated Context

Subfields: Repeating sets of information items

Mnemonic	ASC_0			Conditionality	M↑
				Status	New - Active
Description	This optional field refers to one or more Type 21 Records with the same ACN. Type 21 Records contain images that are NOT used to derive the biometric data in Field 13.999: Latent friction ridge image (DATA) but that may be relevant to the collection of that data, such as general scenes of the area where a latent print was found.				
Field Min	n/a	Occur Min	1		
Field Max	n/a	Occur Max	255		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	biom:AssociatedContext			Cardinality	0..255
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

10.995_1

Associated Context

Associated Context Number

Mnemonic	ACN			Conditionality	M↑
				Status	Active
Description	The first information item for the Associated Context field for a particular Record Type-21. This is mandatory for each Field xx.995, when the field is used. It contains an index to a particular instance of a Type-21 record in the transaction. This same index value appears in the appropriate instance of Record Type-21 as Field 21.021: Associated context number (CAN). The value of the CAN shall be a sequentially assigned a positive integer starting from one and incremented by one, not to exceed 255.				
Field Min	1	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	AN	Special Chars	None		
Format	n/a	Constraints	1 <= ACN <= 255; positive integer		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	biom:AssociatedContext			Cardinality	0..255
XML Level 2	biom:ContextIdentification/nc:IdentificationID			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.995_2

Associated Context

Associated Segment Position

Mnemonic	ASP		Conditionality	0↑	
			Status	Active	
Description	The first information item is the associated segment position (ASP). This provides a unique index to a segmentation.				
Field Min	1		Occur Min	0	
Field Max	2		Occur Max	1	
Char Types	N		Special Chars	n/a	
Format	n/a		Constraints	1 <= ASP <= 99; positive integer	
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	biom:AssociatedContext		Cardinality	0..255	
XML Level 2	biom:ImageSegmentIdentification/nc:IdentificationID		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

10.996

Hash

Mnemonic	HAS		Conditionality	0	
			Status	Active	
Description	Optional field xx.996, is designed for use in Record types 10 and above with a Field xx.999 storing the biometric data. It is comprised of 64 characters representing hexadecimal values. Thus, each character may be a digit from "0" to "9" or a letter "A" through "F". See the latest version of the Federal Information Processing Standard 180, Secure Hash Standard for information on computing SHA-256 hashes. At the time of this standard's publication, FIPS 180-37 had been published. It is also possible to use Field xx.996 to contain the hash for data stored externally, which is referenced in Field 20.994: External file reference (EFR) and/or Field 21.994: External file reference (EFR). The ability to store files externally is new to this version of the standard, and is only implemented for the two new record types referred to here. Use of the hash enables the receiver of the data to perform quick searches of large databases to determine if the data already exist in the database. It is not intended as an information assurance check. That is handled by Record Type-98: Information assurance record.				
Field Min	64		Occur Min	0	
Field Max	64		Occur Max	1	
Char Types	H		Special Chars	None	
Format	n/a		Constraints		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	(ITL)biom:ImageHashValue		Cardinality	0..1	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.997

Source Representation

Mnemonic	SOR			Conditionality	0
				Status	Active
Description	This optional field refers to a representation in Record Type-20 with the same SRN from which the data in Field 13.999: Latent friction ridge image (DATA) was derived.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	biom:SourceRepresentation			Cardinality	0...1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

10.997_0

Source Representation

Mnemonic	SOR_0			Conditionality	M↑
				Status	New - Active
Description	This optional field refers to a representation in Record Type-20 with the same SRN from which the data in Field 13.999: Latent friction ridge image (DATA) was derived.				
Field Min	n/a	Occur Min	1		
Field Max	n/a	Occur Max	255		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	biom:SourceRepresentation			Cardinality	0...255
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.997_1

Source Representation

Source Representation Number

Mnemonic	SRN	Conditionality	M↑
		Status	Active
Description	This is the first information item and is mandatory for each Field xx.997. It contains an index to a particular instance of a Type-20 record in the transaction. This same index value appears in the appropriate instance of Record Type-20 as Field 20.021: Source representation number (SRN). The value of the SRN shall be a sequentially assigned a positive integer starting from one and incremented by one, not to exceed 255.		
Field Min	1	Occur Min	1
Field Max	3	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	1 <= SRN <= 255; positive integer
Code List			
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	biom:SourceRepresentation	Cardinality	0...255
XML Level 2	biom:SourceIdentification/nc:IdentificationID	Cardinality	1..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

10.997_2

Source Representation

Reference Segment Position

Mnemonic	RSP	Conditionality	O↑
		Status	Active
Description	The first information item is the reference segment position (RSP). This provides a unique index to a segmentation.		
Field Min	1	Occur Min	0
Field Max	2	Occur Max	1
Char Types	AN	Special Chars	n/a
Format	n/a	Constraints	1 <= RSP <= 99; positive integer
Code List			
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	biom:SourceRepresentation	Cardinality	0...255
XML Level 2	biom:ImageSegmentIdentification/nc:IdentificationID	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

10.998

Geographic Sample Acquisition Location

Mnemonic	GEO			Conditionality	0
				Status	Active
Description	This optional field contains the location where the iris sample/original source/context information was acquired – not where it is stored.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	biom:BiometricCapture			Cardinality	1..1
XML Level 2	biom:CaptureLocation			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

10.998_01

Geographic Sample Acquisition Location

Universal Time Entry

Mnemonic	UTE			Conditionality	0↑
				Status	Active
Description	The coordinated universal time (UTC) where the biometric sample was collected. This time is independent of the actual time zone where the time and date is recorded. The date is YYYYMMDDhhmmssZ, where the Z indicates the zone description of 0 hours. If sample collection time is unknown, set it to "00000000000000Z."				
Field Min	Dependent on encoding		Occur Min	0	
Field Max	Dependent on encoding		Occur Max	1	
Char Types	AN		Special Chars	None	
Format	n/a		Constraints		
Code List					
Source	ANSI/NIST ITL 2011: (Update 2013)				
XML Level 1	biom:BiometricCapture			Cardinality	1..1
XML Level 2	biom:CaptureLocation			Cardinality	0..1
XML Level 3	biom:CaptureUTCDateTime/nc:DateTime			Cardinality	0..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.998_02

Geographic Sample Acquisition Location

Latitude Degree Value

Mnemonic	LTD	Conditionality	D
		Status	Active
Description	The second information item is latitude degree value (LTD). This is a value that specifies the degree of latitude. The value shall be between -90 (inclusive) and +90 (inclusive). The degrees may be expressed as an integer (without a decimal) or a real number including decimals. If decimals are present, then minutes and seconds shall be empty. Examples: Buenos Aires, Argentina: -34 (with minutes LTM = 36) NIST, Gaithersburg, Maryland: 39.137627 (no LTM or LTS) However, latitude degree value / LTD and longitude degree value / LGD are co-conditional, so they shall both be present if either is present.		
Field Min	1	Occur Min	0
Field Max	9	Occur Max	1
Char Types	NS	Special Chars	Decimal,Minus Sign,Plus Sign
Format	n/a	Constraints	-90 < LTD < 90
Code List			
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	biom:BiometricCapture	Cardinality	1..1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate (0..1)/nc:GeographicCoordinateLatitude (0..1)	Cardinality	0..1
XML Level 4	nc:LatitudeDegreeValue	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

10.998_03

Geographic Sample Acquisition Location

Latitude Minute Value

Mnemonic	LTM	Conditionality	D
		Status	Active
Description	This information item is latitude minute value (LTM). This is a value that specifies a minute of a degree. The value shall be between 0 (inclusive) to 60 (exclusive). The minute value may be expressed as an integer (without a decimal) or as a real number including decimals. If decimals are present then seconds shall be empty. Thus, the allowed special character is a period. The minute value can be empty, even if the degree value is an integer. LTM and LGM are co-conditional, so they shall both be present if either is present. Further, "minutes" values LTM and LGM can only be present if their corresponding "degrees" values are present.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	NS	Special Chars	Decimal,Minus Sign,Plus Sign
Format	n/a	Constraints	0 <= LTM < 60
Code List			
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	biom:BiometricCapture	Cardinality	1..1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate (0..1)/nc:GeographicCoordinateLatitude (0..1)	Cardinality	0..1
XML Level 4	nc:LatitudeMinuteValue	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

10.998_04

Geographic Sample Acquisition Location

Latitude Second Value

Mnemonic	LTS	Conditionality	D
		Status	Active
Description	The fourth information item is the latitude second value (LTS). This is a value that specifies a second of a minute. The integer shall be 0 (inclusive) to 60 (exclusive). The second value is empty, even if the minute value is an integer. Also, "seconds" values LTS and LGS can only be present if their corresponding "minutes" value is present.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	0 <= LTS < 60
Code List			
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	biom:BiometricCapture	Cardinality	1..1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate (0..1)/nc:GeographicCoordinateLatitude (0..1)	Cardinality	0..1
XML Level 4	nc:LatitudeSecondValue	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

10.998_05

Geographic Sample Acquisition Location

Longitude Degree Value

Mnemonic	LGD	Conditionality	D
		Status	Active
Description	The fifth information item is the longitude degree value (LGD). It is a value that specifies the degree of a longitude. The value shall be between -180 (inclusive) and +180 (inclusive). If LTD is present, then LGD shall be present. The degrees may be expressed as whole numbers (without a decimal) or real numbers including decimals. If decimals are present, then minutes and seconds are empty. Examples: Buenos Aires, Argentina: -58 (with minutes LGM = 22), NIST, Gaithersburg, Maryland: -77.216032 (no LGM or LGS) However, latitude degree value / LTD and longitude degree value / LGD are co-conditional, so they shall both be present if either is present.		
Field Min	1	Occur Min	0
Field Max	10	Occur Max	1
Char Types	NS	Special Chars	Decimal, Minus Sign, Plus Sign
Format	n/a	Constraints	-180 =< LGD =< 180
Code List			
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	biom:BiometricCapture	Cardinality	1..1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate (0..1)/nc:GeographicCoordinateLatitude (0..1)	Cardinality	0..1
XML Level 4	nc:LongitudeDegreeValue	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

10.998_06

Geographic Sample Acquisition Location

Longitude Minute Value

Mnemonic	LGM	Conditionality	D
		Status	Active
Description	The sixth information item is the longitude minute value (LGM). It is a value that specifies a minute of a degree. The value shall be from 0 (inclusive) to 60 (exclusive). The minute value may be expressed as an integer (without a decimal) or as a real number including decimals. If decimals are present then seconds shall not appear. The minute value is empty, even if the degree value is an integer. If LTM is present, then LGM shall be present. Further, "minutes" values LTM and LGM can only be present if their corresponding "degrees" values are present.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	NS	Special Chars	Decimal
Format	n/a	Constraints	1 <= LGM < 60
Code List			
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	biom:BiometricCapture	Cardinality	1..1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate (0..1)/nc:GeographicCoordinateLatitude (0..1)	Cardinality	0..1
XML Level 4	nc:LongitudeMinuteValue	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

10.998_07

Geographic Sample Acquisition Location

Longitude Second Value

Mnemonic	LGS	Conditionality	D
		Status	Active
Description	The seventh information item is the longitude second value (LGS). This is a value that specifies a second of a minute. The integer shall be 0 (inclusive) to 60 (exclusive). The second value is empty, even if the minute value is an integer. If LTS is present, then LGS shall be present. Also, "seconds" values LTS and LGS can only be present if their corresponding "minutes" value is present.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	0 <= LGS < 60
Code List			
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	biom:BiometricCapture	Cardinality	1..1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate (0..1)/nc:GeographicCoordinateLatitude (0..1)	Cardinality	0..1
XML Level 4	nc:LongitudeSecondValue	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.998_08

Geographic Sample Acquisition Location

Elevation

Mnemonic	ELE	Conditionality	D
		Status	Active
Description	The eighth information item is elevation (ELE). It is expressed in meters. It is a numeric value. It is between -422 meters (Dead Sea) and 8848 meters (Mount Everest). Allowed special characters are the negative sign and the period.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	NS	Special Chars	Minus Sign,Period
Format	n/a	Constraints	-422.000 < ELE < 8848.000; real number
Code List			
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	biom:BiometricCapture	Cardinality	1..1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	nc:LocationGeographicElevation	Cardinality	0..1
XML Level 4	nc:MeasurePoint	Cardinality	1..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

10.998_09

Geographic Sample Acquisition Location

Geodetic Datum Code

Mnemonic	GDC	Conditionality	D
		Status	Active
Description	The ninth information item is the geodetic datum code (GDC11). It is an alphanumeric value of 3 to 6 characters in length. This information item is used to indicate which coordinate system was used to represent the values in information items 2 through 7. If no entry is made in this information item, then the basis for the values entered in the first eight information items shall be WGS84, the code for the World Geodetic Survey 1984 version - WGS 84 (G873). See look up codes for values. If no entry is made in this information item, then the basis for the values entered in the first eight information items shall be WGS84, the code for the World Geodetic Survey 1984 version - WGS 84 (G873). See look up codes for values.		
Field Min	3	Occur Min	0
Field Max	6	Occur Max	1
Char Types	AN	Special Chars	None
Format	n/a	Constraints	see Look Up Codes
Code List	GEOGRAPHIC COORDINATE DATUM CODE		
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	biom:BiometricCapture	Cardinality	1..1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate (0..1)/nc:GeographicCoordinateLatitude (0..1)	Cardinality	0..1
XML Level 4	biom:GeodeticDatumCoordinateSystemCode or biom:GeodeticDatumCoordinateSystemName	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-10: Photographic Body Part Imagery (including Face and S

Page 576 of 1037

10.998_10

Geographic Sample Acquisition Location

Geographic Coordinate Universal Transverse Mercator Zone

Mnemonic	GCM	Conditionality	D
		Status	Active
Description	It is an alphanumeric value of 2 to 3 characters. This is a one or two digit UTM zone number followed by the 8 degree latitudinal band designator (which is a single letter).		
Field Min	2	Occur Min	0
Field Max	3	Occur Max	1
Char Types	AN	Special Chars	None
Format	n/a	Constraints	One or two integers followed by a single letter
Code List			
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	biom:BiometricCapture	Cardinality	1..1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	nc:LocationUTMCoordinate	Cardinality	0..1
XML Level 4	nc:UTMGridZoneID	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

10.998_11

Geographic Sample Acquisition Location

Geographic Coordinate Universal Transverse Mercator Easting

Mnemonic	GCE	Conditionality	D
		Status	Active
Description	The eleventh information item is the geographic coordinate universal transverse Mercator easting (GCE). It is an integer of 1 to 6 digits.		
Field Min	1	Occur Min	0
Field Max	6	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	n/a
Code List			
Source	ANSI/NIST ITL 2011: (Update 2013)		
XML Level 1	biom:BiometricCapture	Cardinality	1..1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	nc:LocationUTMCoordinate	Cardinality	0..1
XML Level 4	nc:UTMEastingValue	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-10: Photographic Body Part Imagery (including Face and S

Page 577 of 1037

10.998_12

Geographic Sample Acquisition Location

Geographic Coordinate Universal Transverse Mercator Northing

Mnemonic	GCN		Conditionality	D
			Status	Active
Description	The twelfth information item is the geographic coordinate universal transverse Mercator northing (GCN). It is an integer of 1 to 8 digits.			
Field Min	1	Occur Min	0	
Field Max	8	Occur Max	1	
Char Types	N	Special Chars	None	
Format	n/a	Constraints	n/a	
Code List				
Source	ANSI/NIST ITL 2011: (Update 2013)			
XML Level 1	biom:BiometricCapture	Cardinality	1...1	
XML Level 2	biom:CaptureLocation	Cardinality	0..1	
XML Level 3	nc:LocationUTMCoordinate	Cardinality	0..1	
XML Level 4	nc:UTMNorthingValue	Cardinality	0..1	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0
				Yes
				DoD EBTS 4.0
				Yes

10.998_13

Geographic Sample Acquisition Location

Geographic Reference Text

Mnemonic	GRT		Conditionality	O
			Status	Active
Description	It is a free form text describing a street address or other physical location (such as 'Corner of Washington and Madison, Geneva, NY').			
Field Min	1	Occur Min	0	
Field Max	150	Occur Max	1	
Char Types	U	Special Chars	Any	
Format	n/a	Constraints	n/a	
Code List				
Source	ANSI/NIST ITL 2011: (Update 2013)			
XML Level 1	biom:BiometricCapture	Cardinality	1...1	
XML Level 2	biom:CaptureLocation	Cardinality	0..1	
XML Level 3	biom:GeographicLocationText	Cardinality	0..1	
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0
				Yes
				DoD EBTS 4.0
				Yes

10.998_14

Geographic Sample Acquisition Location

Geographic Coordinate Other System Identifier

Mnemonic	OSI		Conditionality	O			
			Status	Active			
Description	A fourteenth optional information item geographic coordinate other system identifier (OSI) allows for other coordinate systems. This information items specifies the system identifier. It is up to 10 characters in length. Examples are: • MGRS (Militar Grid Reference System), • USNG (United States National Grid), • GARS (Global Area Reference System), • GEOREF (World Geographic Reference), • LANDMARK landmark (e.g. hydant) and position relative to the landmark.						
Field Min	1	Occur Min	0				
Field Max	10	Occur Max	1				
Char Types	U	Special Chars	n/a				
Format	n/a	Constraints	n/a				
Code List							
Source	ANSI/NIST ITL 2011: (Update 2013)						
XML Level 1	biom:BiometricCapture	Cardinality	1..1				
XML Level 2	biom:CaptureLocation	Cardinality	0..1				
XML Level 3	biom:LocationAlternateGeographicSystemValue	Cardinality	0..1				
XML Level 4	biom:GeographicLocationSystemName	Cardinality	1..1				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

10.998_15

Geographic Sample Acquisition Location

Geographic Coordinate Other System Value

Mnemonic	OCV		Conditionality	D			
			Status	Active			
Description	A fifteenth optional information item, is the geographic coordinate other system value (OCV). It shall only be present if OSI is present in the record. It can be up to 126 characters in length. If OSI is LANDMARK, OCV is free text and may be up to 126 characters. For details on the formatting of OCV for the other coordinate systems shown in OSI as examples, see http://earth-info.nga.mil/GandG/coordsys/grids/referencesys.html .						
Field Min	1	Occur Min	0				
Field Max	126	Occur Max	1				
Char Types	U	Special Chars	Any				
Format	n/a	Constraints	n/a				
Code List							
Source	ANSI/NIST ITL 2011: (Update 2013)						
XML Level 1	biom:BiometricCapture	Cardinality	1..1				
XML Level 2	biom:CaptureLocation	Cardinality	0..1				
XML Level 3	biom:LocationAlternateGeographicSystemValue	Cardinality	0..1				
XML Level 4	biom:GeographicLocationText	Cardinality	0..1				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

10.999

Body Part Image

Mnemonic	DATA		Conditionality	M
			Status	Active
Description	This mandatory field contains the image. See Section 7.2 of ANSI/NIST ITL 1-2011 for details.			
Field Min	1	Occur Min	1	
Field Max	Unlimited	Occur Max	1	
Char Types	B	Special Chars	None, niem-xs:base64Binary	
Format	n/a	Constraints	n/a	
Code List				
Source	ANSI/NIST ITL 2011: (Update 2013)			
XML Level 1	(ITL)biom:PhysicalFeatureImage	Cardinality	1..1	
XML Level 2	nc:BinaryBase64Object	Cardinality	1..1	
XML Level 3		Cardinality		
XML Level 4		Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0 Yes DoD EBTS 4.0 Yes

11.001

Record Header

Mnemonic	LEN		Conditionality	M
			Status	New Active
Description	The record header appears as the first field (xx.001) in each Record Type. It contains information particular to the encoding format chosen, in order to enable proper reading of the record. In Traditional encoding, this field contains the record length in bytes (including all information separators). In NIEM-conformant XML encoding, this field contains the RecordCategoryCode, which is the numeric representation of the Record Type.			
Field Min	T = 4; X = 1	Occur Min	1	
Field Max	T = 8; X = 2	Occur Max	1	
Char Types	N	Special Chars	None	
Format	n/a	Constraints	positive integer	
Code List				
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)			
XML Level 1	nist-itl:RecordCategoryCode	Cardinality	1..1	
XML Level 2		Cardinality		
XML Level 3		Cardinality		
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0 No DoD EBTS 4.0 Yes

11.002

Information Designation Character

Mnemonic	IDC		Conditionality	M
			Status	New Active
Description	Contains the IDC assigned to this Type-11 record as listed in the information item IDC for this record.			
Field Min	1	Occur Min	1	
Field Max	2	Occur Max	1	
Char Types	integer	Special Chars	None	
Format	n/a	Constraints	0 <= IDC <= 99	
Code List				
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)			
XML Level 1	nist-itl:ImageReferenceIdentification/nc:IdentificationID		Cardinality	1..1
XML Level 2			Cardinality	
XML Level 3			Cardinality	
XML Level 4			Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0 No DoD EBTS 4.0 Yes

11.003

Audio Object Descriptor Code

Mnemonic	AOD		Conditionality	M
			Status	New Active
Description	Indicates the type of audio object containing the voice recording which is the focus of this Type-11 record.			
Field Min	1	Occur Min	1	
Field Max	1	Occur Max	1	
Char Types	T = integer, X = AudioObjectDescriptorCodeType	Special Chars	None	
Format	n/a	Constraints	0 <= AOD <= 5	
Code List				
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)			
XML Level 1	biom:AudioObjectDescriptorCode		Cardinality	1..1
XML Level 2			Cardinality	
XML Level 3			Cardinality	
XML Level 4			Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0 No DoD EBTS 4.0 Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.004

Source Agency

Mnemonic	SRC			Conditionality	M
				Status	New Active
Description	The SRC is a code for a particular agency that is assigned by the implementation domain (such as NORAM, which is maintained by the FBI). It is often not the common name of the organization. This field denotes the agency that prepared this record. It is not necessarily the agency that is transmitting this transaction.				
Field Min	1	Occur Min	1		
Field Max	Unlimited	Occur Max	1		
Char Types	none	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:CaptureOrganization	Cardinality	1..1		
XML Level 2	nc:OrganizationIdentification/nc:IdentificationID	Cardinality	1..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.005

Voice Recording Source Organization

Mnemonic	VRSO			Conditionality	O
				Status	New Active
Description	Contains information about the person, group, site or agency that created the voice recording pointed to or included in this record. In the case of files created from previous recordings, this is not necessarily the source of the original transduction of the acoustic vocalizations from the person to whom the Type- 11 record pertains.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:RecordingSettingDetail	Cardinality	0..1		
XML Level 2		Cardinality			
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.005_1

Voice Recording Source Organization

Source Organization Type Code

Mnemonic	STC			Conditionality	M↑
				Status	New Active
Description	A single character describing the site or agency that created the voice recording.				
Field Min	1	Occur Min	1		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars	None		
Format	n/a	Constraints	U, P, I, G or O		
Code List	SOURCE ORGANIZATION TYPE CODE				
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:RecordingSettingDetail			Cardinality	0..1
XML Level 2	biom:RecordingSourceCategoryCode			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.005_2

Voice Recording Source Organization

Source Organization Name

Mnemonic	SON			Conditionality	O↑
				Status	New Active
Description	The name of the group, organization or agency that created the voice recording.				
Field Min	1	Occur Min	0		
Field Max	400	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:RecordingSettingDetail			Cardinality	0..1
XML Level 2	biom:SourceOrganizationName			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.005_3

Voice Recording Source Organization

Point Of Contact

Mnemonic	POC			Conditionality	O↑
				Status	New Active
Description	Point of contact / POC - states who composed the voice recording.				
Field Min	1	Occur Min	0		
Field Max	200	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:RecordingSettingDetail			Cardinality	0..1
XML Level 2	nc:OrganizationPrimaryContactInformation/nc>ContactEntityDescriptionText			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.005_4

Voice Recording Source Organization

Record Setting Detail Country Code

Mnemonic	CSC			Conditionality	O↑
				Status	New Active
Description	Code of where the voice recording was created – not necessarily the nation of the agency entered in Field 11.993: Source agency name / SAN. Field 1.018: Geographic name set / GNS is set to GENC, and the default for this field is GENC alpha 3.				
Field Min	2	Occur Min	0		
Field Max	3	Occur Max	1		
Char Types	AN	Special Chars	None		
Format	n/a	Constraints	EBTS 4.0 Mandates GENC		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:RecordingSettingDetail			Cardinality	0..1
XML Level 2	biom:RecordingSourceCountryGENCAlpha3Code			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.006

Voice Recording Content Descriptor

Mnemonic	VRC	Conditionality	0
		Status	New Active
Description	Describes the contents of the voice recording.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	n/a
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:RecordingContentDescriptor	Cardinality	0..1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

11.006_1

Voice Recording Content Descriptor

Assigned Voice Indicator

Mnemonic	AVI	Conditionality	M↑
		Status	New Active
Description	Assigned voice indicator / AVI - Indicates if the voice recording sample was obtained from a known subject.		
Field Min	1	Occur Min	1
Field Max	1	Occur Max	1
Char Types	A	Special Chars	None
Format	n/a	Constraints	AVI = A, N or Q
Code List	VOICE RECORDING CONTENT INDICATOR CODE		
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:RecordingContentDescriptor	Cardinality	0..1
XML Level 2	biom:RecordingAssignedVoiceCategoryCode	Cardinality	1..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.006_2

Voice Recording Content Descriptor

Speaker Plurality Code

Mnemonic	SPC			Conditionality	O↑
				Status	New Active
Description	Speaker plurality code / SPC - indicates plurality of speakers represented on voice recording.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars	None		
Format	n/a	Constraints	SPC = M or S		
Code List	SPEAKER PLURALITY CODE				
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:RecordingContentDescriptor			Cardinality	0..1
XML Level 2	biom:SpeakerPluralityCode			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.006_3

Voice Recording Content Descriptor

Comment

Mnemonic	COM			Conditionality	O↑
				Status	New Active
Description	Describes methods by which the plurality and nationality of the speakers was determined, along with any supporting text.				
Field Min	1	Occur Min	0		
Field Max	Unlimited	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:RecordingContentDescriptor			Cardinality	0..1
XML Level 2	biom:RecordingContentComment			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.007

Audio Recording Device

Mnemonic	AREC		Conditionality	0			
			Status	New Active			
Description	Indicates information about the recording equipment that created the voice recording contained in or pointed to by this record. As recordings or data files may be transcoded from previously recorded or broadcast content, this equipment may or may not be the equipment used to record the original acoustic vocalization of the person to whom the Type-11 record pertains.						
Field Min	n/a	Occur Min	0				
Field Max	n/a	Occur Max	1				
Char Types	n/a	Special Chars	n/a				
Format	n/a	Constraints					
Code List							
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)						
XML Level 1	biom:AudioSourceRecorder		Cardinality	0..1			
XML Level 2			Cardinality				
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

11.007_1

Audio Recording Device

Recording Device Descriptive Text

Mnemonic	RDD		Conditionality	0↑			
			Status	New Active			
Description	Text field describing the recording device that created the voice recording.						
Field Min	1	Occur Min	0				
Field Max	Unlimited	Occur Max	1				
Char Types	U	Special Chars	None				
Format	n/a	Constraints					
Code List							
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)						
XML Level 1	biom:AudioSourceRecorder		Cardinality	0..1			
XML Level 2	biom:CaptureDeviceDescriptionText		Cardinality	0..1			
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.007_2

Audio Recording Device

Recording Device Make

Mnemonic	MAK			Conditionality	O↑		
				Status	New Active		
Description	Describes make of the recording device that created the voice recording.						
Field Min	1		Occur Min	0			
Field Max	50		Occur Max	1			
Char Types	U		Special Chars	None			
Format	n/a		Constraints				
Code List							
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)						
XML Level 1	biom:AudioSourceRecorder			Cardinality	0..1		
XML Level 2	biom:CaptureDeviceMakeText			Cardinality	0..1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

11.007_3

Audio Recording Device

Recording Device Model

Mnemonic	MOD			Conditionality	O↑		
				Status	New Active		
Description	Contains the make, model and serial number, respectively, for the recording device.						
Field Min	1		Occur Min	0			
Field Max	50		Occur Max	1			
Char Types	U		Special Chars	None			
Format	n/a		Constraints				
Code List							
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)						
XML Level 1	biom:AudioSourceRecorder			Cardinality	0..1		
XML Level 2	biom:CaptureDeviceModelText			Cardinality	0..1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

11.007_4

Audio Recording Device

Recording Device Serial Number

Mnemonic	SER	Conditionality	O↑
		Status	New Active
Description	Recording device serial number.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	None
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:AudioSourceRecorder	Cardinality	0..1
XML Level 2	biom:CaptureDeviceSerialNumberText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

11.008

Acquisition Source

Mnemonic	AQS	Conditionality	D
		Status	New Active
Description	Specifies and describes the acquisition source. Mandatory field if AOD does not equal 5. It shall not appear if AOD = 5.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	n/a
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:SourceAcquisition	Cardinality	0..1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.008_1

Acquisition Source

Acquisition Source Code

Mnemonic	AQC			Conditionality	M↑
				Status	New Active
Description	It is an optional integer that specifies the source from which the voice in the identified segments was received.				
Field Min	1	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints			
Code List	ACQUISITION SOURCE CODE				
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:SourceAcquisition			Cardinality	0..1
XML Level 2	biom:AcquisitionSourceCode			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.008_2

Acquisition Source

Analog To Digital Conversion Description

Mnemonic	A2D			Conditionality	D
				Status	New Active
Description	Used to enter the make, model and serial number of the analog to digital conversion equipment used, if known. This field should also address parameters used, such as the sampling rate, if known. This field should address parameters used, such as sample rate, if known.				
Field Min	1	Occur Min	0		
Field Max	Unlimited	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:SourceAcquisition			Cardinality	0..1
XML Level 2	biom:AcquisitionDigitalConversionDescriptionText			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.008_3

Acquisition Source

Contains Radio Transmission Format Description.

Mnemonic	FDN			Conditionality	D
				Status	New Active
Description	Radio transmission format description / FDN - Mandatory if the AQT is 23 or 24.				
Field Min	1	Occur Min	0		
Field Max	Unlimited	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:SourceAcquisition	Cardinality	0..1		
XML Level 2	biom:AcquisitionRadioTransmissionFormatDescriptionText	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.008_4

Acquisition Source

Contains Acquisition Special Characteristics.

Mnemonic	AQSC			Conditionality	O↑
				Status	New Active
Description	Describes any specific conditions not mentioned in the table.				
Field Min	1	Occur Min	0		
Field Max	Unlimited	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:SourceAcquisition	Cardinality	0..1		
XML Level 2	biom:AcquisitionSpecialCharacteristicsText	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.009

Record Creation Date

Record Creation Date

Mnemonic	RCD	Conditionality	M
		Status	New Active
Description	Contains the date and time of creation of this Type-11 record. This date will generally be different from the voice recording creation date and may be different from the date at which the acoustic vocalization originally occurred.		
Field Min	Dependent on Encoding	Occur Min	1
Field Max	Dependent on Encoding	Occur Max	1
Char Types	AN	Special Chars	None
Format	Dependent on Encoding	Constraints	YYYYMMDDhhmm
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:RecordCreationDate/nc:DateTime	Cardinality	1..1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

11.01

Total Recording Duration

Voice Recording Creation Date

Mnemonic	VRD	Conditionality	O
		Status	New Active
Description	Total length of the voice recording time for this Type-11 record.		
Field Min	Dependent on Encoding	Occur Min	0
Field Max	Dependent on Encoding	Occur Max	1
Char Types	AN	Special Chars	None
Format	Dependent on Encoding	Constraints	YYYYMMDDhhmm
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom_2:CaptureDate/nc:DateTime	Cardinality	0..1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.011

Voice Recording Date

Total Recording Duration

Mnemonic	TRD	Conditionality	0
		Status	New Active
Description	Gives the total length of the voice recording time for this Type-11 record. The second and third items of this field only apply to digital audio objects, as indicated by a value of 0, 1 or 2 in AOD. At least one of the three information items must be entered if this field is used.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	n/a
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:RecordingDuration	Cardinality	0..1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

11.011_1

Voice Recording Date

Voice Recording Time

Mnemonic	TIM	Conditionality	0↑
		Status	New Active
Description	The total time of the voice recording in microseconds. The size of this item is limited to 11 digits, limiting the total time duration of the signal to 99,999 seconds, which is approximately 28 hours.		
Field Min	1	Occur Min	0
Field Max	11	Occur Max	1
Char Types	N	Special Chars	Contains integers with no commas or periods
Format	n/a	Constraints	1 <= TIM <= 99999999999
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:RecordingDuration	Cardinality	0..1
XML Level 2	biom:RecordingDurationTime	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.011_2

Voice Recording Date

Compressed Bytes

Mnemonic	CBY			Conditionality	O↑
				Status	New Active
Description	The total number of compressed bytes in the digital voice data file. This information item applies only to digital voice recordings stored as voice data files. The size of this item is limited to 14 digits, limiting the total size of the voice data file to 99 terabytes.				
Field Min	1	Occur Min	0		
Field Max	14	Occur Max	1		
Char Types	N	Special Chars	integers no commas or periods		
Format	n/a	Constraints	1 <= CBY <= 99999999999999		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:RecordingDuration	Cardinality	0..1		
XML Level 2	biom:RecordingCompressedBytesQuantity	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.011_3

Voice Recording Date

Total Digital Samples

Mnemonic	TSM			Conditionality	O↑
				Status	New Active
Description	The number of digital samples in the voice data file after any decompression of the compressed signal. This information item applies only to digital voice recordings stored as voice data files. The size of this item is limited to 14 digits.				
Field Min	1	Occur Min	0		
Field Max	14	Occur Max	1		
Char Types	N	Special Chars	integers, no commas or periods		
Format	n/a	Constraints	1 <= TSM <= 99999999999999		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:RecordingDuration	Cardinality	0..1		
XML Level 2	biom:RecordingSampleQuantity	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.012

Physical Media Object

Mnemonic	PMO			Conditionality	D
				Status	New Active
Description	Identifies the characteristics of the physical media containing the voice recording. There can be only one physical media object per Type-11 record, but multiple Type physical media object. This field only applies if AOD has an attribute code of AOD. The location of the physical media object is given in EFR.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:PhysicalMediaObject			Cardinality	0..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.012_1

Physical Media Object

Media Type Description

Mnemonic	MTD			Conditionality	M↑
				Status	New Active
Description	It is mandatory if this field is used and contains text describing the general type of media (e.g., analog cassette tape, reel-to-reel tape, CD, DVD, phonograph record) upon which the voice recording is stored.				
Field Min	1	Occur Min	1		
Field Max	300	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:PhysicalMediaObject			Cardinality	0..1
XML Level 2	biom:MediaCategoryText			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.012_2

Physical Media Object

Recording Speed

Mnemonic	RSP	Conditionality	O↑
		Status	New Active
Description	Gives a numerical value to the speed at which the physical media object must be played to reproduce the voice signal content.		
Field Min	1	Occur Min	0
Field Max	9	Occur Max	1
Char Types	NS	Special Chars	numbers, with decimals allowed
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:PhysicalMediaObject	Cardinality	0..1
XML Level 2	biom:RecordingSpeedRate	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

11.012_3

Physical Media Object

Recording Speed Measurement Units Description Text

Mnemonic	RSU	Conditionality	D
		Status	New Active
Description	Recording speed measurement units description text Mandatory if the second information item, RSP, is entered and contains text to indicate the units of measure to which RSP refers (such as Rotations per minute).		
Field Min	1	Occur Min	0
Field Max	Unlimited	Occur Max	1
Char Types	U	Special Chars	None
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:PhysicalMediaObject	Cardinality	0..1
XML Level 2	biom:RecordingSpeedUnitText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.012_4

Physical Media Object

Equalization Description

Mnemonic	EQD	Conditionality	O↑
		Status	New Active
Description	Indicates the equalization that should be applied for faithful rendering of the voice recording on the physical media object.		
Field Min	1	Occur Min	0
Field Max	Unlimited	Occur Max	1
Char Types	U	Special Chars	None
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:PhysicalMediaObject	Cardinality	0..1
XML Level 2	biom:AudioEqualizationText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

11.012_5

Physical Media Object

Track Count

Mnemonic	TRC	Conditionality	O↑
		Status	New Active
Description	Gives the number of tracks on the physical media object.		
Field Min	1	Occur Min	0
Field Max	4	Occur Max	1
Char Types	N	Special Chars	Integers - Contains optional integer between 1 and 9999, inclusive.
Format	n/a	Constraints	1 <= TRC <= 99999999999999
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:PhysicalMediaObject	Cardinality	0..1
XML Level 2	biom:AudioTrackQuantity	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.012_6

Physical Media Object

Speaker Track Number

Mnemonic	STK			Conditionality	O↑
				Status	New Active
Description	Indicate which tracks carry the voices of the speaker(s). A value of 0 or no entry for this information item indicates that all tracks contain voice data for the speaker(s). (list may have less than or equal to TRC elements)				
Field Min	1	Occur Min	0		
Field Max	4	Occur Max	9999		
Char Types	NS		Special Chars	List of non-negative integers For Traditional encoding, the separator character “ ” is used between elements. This is not applicable to XML encoding.	
Format	n/a		Constraints		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:PhysicalMediaObject			Cardinality	0..1
XML Level 2	biom:SpeakerTrackList/biom:TrackID			Cardinality	0..9999
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.012_7

Physical Media Object

Comment

Mnemonic	COM			Conditionality	O↑
				Status	New Active
Description	Allows for additional comments describing the physical media object.				
Field Min	1	Occur Min	0		
Field Max	Unlimited	Occur Max	1		
Char Types	U		Special Chars	None	
Format	n/a		Constraints		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:PhysicalMediaObject			Cardinality	0..1
XML Level 2	biom:MediaCommentText			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.013

Container

Mnemonic	CONT		Conditionality	0	
			Status	New Active	
Description	Contains information about the container format that encapsulates the audio data of the electronic file used to carry the voice data in the digital recording. This field is not used if the voice recording is stored on a physical media object as an analog signal – so it can only appear if Audio object descriptor code /AOD is set to 0, 1 or 2.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:DigitalMediaContainer		Cardinality	0..1	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.013_1

Container

Container Code

Mnemonic	CONC		Conditionality	M↑	
			Status	New Active	
Description	Information about the container format that encapsulates the audio data of the electronic file used to carry the voice data in the digital recording. This field is not used if the voice recording is stored on a physical media object as an analog signal – so it can only appear if Audio object descriptor code /AOD is set to 0, 1 or 2. A container code of Other (CONC = 2) indicates that the container is given neither in Table 78 Audio Visual Container Codes nor in the external container table and must be specified. If CONC = 2, the Field 11.051: Comment / COM shall be used to describe the container.				
Field Min	1		Occur Min	0	
Field Max	2		Occur Max	1	
Char Types	N		Special Chars	None	
Format	n/a		Constraints		
Code List	CONTAINER CODE				
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:DigitalMediaContainer		Cardinality	0..1	
XML Level 2	biom:DigitalMediaContainerFormatCode		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.013_2

Container

External Container Reference Code

Mnemonic	ECON	Conditionality	D
		Status	New Active
Description	Contains the external container reference code. Required if CONC = 1.		
Field Min	1	Occur Min	0
Field Max	80	Occur Max	1
Char Types	U	Special Chars	None
Format	n/a	Constraints	
Code List	Code List Here - http://biometrics.nist.gov/cs_links/standard/ansi_2012/Codec.xlsx - Includes the fields		
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:DigitalMediaContainer	Cardinality	0..1
XML Level 2	biom:DigitalMediaContainerExternalReferenceCodeText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

11.013_3

Container

Comment

Mnemonic	COM	Conditionality	D
		Status	New Active
Description	Information about the container or additional instructions for reconstruction of audio output from the stored digital data. Container parameters shall be specified in this information item when required for unambiguous decoding. This item should include a description of any noise reduction processing or equalization that must be applied to faithfully render the voice recording. Required if CONC = 2		
Field Min	1	Occur Min	0
Field Max	Unlimited	Occur Max	1
Char Types	U	Special Chars	None
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:DigitalMediaContainer	Cardinality	0..1
XML Level 2	biom:AudioCommentText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.014

Codec

Mnemonic	CDC			Conditionality	D
				Status	New Active
Description	Gives information about the codec used to encode the voice and audio data in the digital recording. Appears when AOD is set to 0, 1 or 2.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:CodecDetails			Cardinality	0..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.014_1

Codec

Codec Code

Mnemonic	CODC			Conditionality	O↑
				Status	New Active
Description	Indicates the single codec type used for all audio segments in the record. If the codec code is identified as Other (CODC = 2), the final information item (comments / COM) shall be used to describe the codec. If other Codecs are used (reference here - http://www.nist.gov/itl/iad/ig/ansi_standard.cfm) then use codec 1.				
Field Min	1	Occur Min	0		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints			
Code List	CODEC TYPE CODE				
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:CodecDetails			Cardinality	0..1
XML Level 2	biom:CodecCategoryCode			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.014_2

Codec

Sampling Rate Number

Mnemonic	SRTN			Conditionality	O↑
				Status	New Active
Description	Indicates the number of digital samples per second that represent a second of analog voice data upon conversion to an acoustic signal. The value of 0 shall only be used to indicate unknown or variable sampling rate. The sampling rate is expressed in Hz				
Field Min	1	Occur Min	0		
Field Max	9	Occur Max	1		
Char Types	N	Special Chars	positive integer, no commas		
Format	n/a	Constraints	0 < SRTN < 100000000		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:CodecDetails	Cardinality	0..1		
XML Level 2	biom:SamplingRate	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.014_3

Codec

Bit Depth Count

Mnemonic	BITD			Conditionality	O↑
				Status	New Active
Description	Indicates the number of bits that are used to represent a single digital sample of voice data. Encoders of unknown or variable bit depth shall be given the value of 0.				
Field Min	1	Occur Min	0		
Field Max	4	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 < BITD < 1024, positive integer		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:CodecDetails	Cardinality	0..1		
XML Level 2	biom:RecordingBitDepthValue	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.014_4

Codec

Endian Code

Mnemonic	ENDC			Conditionality	O↑		
				Status	New Active		
Description	Indicates which byte goes first for digital samples containing two or more bytes. ENDC is optional and ignored for digital samples that do not contain two or more integer multiples of bytes).						
Field Min	1		Occur Min	0			
Field Max	1		Occur Max	1			
Char Types	N		Special Chars	None			
Format	n/a		Constraints	ENDC = 0 or 1			
Code List	ENDIAN CODE						
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)						
XML Level 1	biom:CodecDetails			Cardinality	0..1		
XML Level 2	biom:RecordingEndianCode			Cardinality	0..1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

11.014_5

Codec

Numeric Format

Mnemonic	NFMT			Conditionality	O↑		
				Status	New Active		
Description	Integer and floating point representations.						
Field Min	1		Occur Min	0			
Field Max	5		Occur Max	1			
Char Types	AN		Special Chars	NFMT = nonnegative integer with an optional letters s, b, or d following it			
Format	n/a		Constraints				
Code List	NUMERIC FORMAT CODE						
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)						
XML Level 1	biom:CodecDetails			Cardinality	0..1		
XML Level 2	biom:NumericFormatText			Cardinality	0..1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.014_6

Codec

Channel Count

Mnemonic	CHC			Conditionality	O↑
				Status	New Active
Description	Integer of number of channels of data represented in the digital voice data file. The number of channels must be between 1 and 9999, inclusive.				
Field Min	1	Occur Min	0		
Field Max	4	Occur Max	1		
Char Types	N	Special Chars	Contains positive integer		
Format	n/a	Constraints	1 <= CHC <= 9999		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:CodecDetails	Cardinality	0..1		
XML Level 2	biom:RecordingChannelsQuantity	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.014_7

Codec

External Codec Reference Code

Mnemonic	ECOD			Conditionality	D
				Status	New Active
Description	It contains the 'reference code' from the table of codecs available at http://www.nist.gov/itl/iad/ig/ansi_standard.cfm . If the codec is not listed in the external table, enter the name and description of the codec in COM. It can only appear if CODC = 1.				
Field Min	1	Occur Min	0		
Field Max	80	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints			
Code List	Table of codecs available at http://www.nist.gov/itl/iad/ig/ansi_standard.cfm .				
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:CodecDetails	Cardinality	0..1		
XML Level 2	biom:CodecExternalReferenceCodeText	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.014_8

Codec

Comment

Mnemonic	COM	Conditionality	D
		Status	New Active
Description	Contains additional information about the codec or additional instructions for reconstruction of audio output from the stored digital data. Codec parameters shall be specified in this information item when required for unambiguous decoding. This item should include a description of any noise reduction processing or equalization that must be applied to faithfully render the voice recording.		
Field Min	1	Occur Min	0
Field Max	Unlimited	Occur Max	1
Char Types	U	Special Chars	None
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:CodecDetails	Cardinality	0..1
XML Level 2	biom:CodecCommentText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

11.021

Redaction

Mnemonic	RED	Conditionality	O
		Status	New Active
Description	It indicates whether the voice recording contains overwritten or erased sections intended to remove, without altering the length of the segment, semantic content deemed not suitable for transmission or storage.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	n/a
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:RedactionInformation	Cardinality	0..1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-11: Forensic and Investigatory Voice Data

Page 605 of 1037

11.021_1

Redaction

Redaction Indicator

Mnemonic	RDI	Conditionality	M↑
		Status	New Active
Description	Single character redaction indicator code.		
Field Min	0	Occur Min	1
Field Max	1	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	RDI = 0, 1 or 2
Code List	REDACTION INDICATOR CODE		
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:RedactionInformation	Cardinality	0..1
XML Level 2	dod-ebts:ProcessingIndicatorCode	Cardinality	1..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

11.021_2

Redaction

Redaction Authority Organization Name

Mnemonic	RDA	Conditionality	D
		Status	New Active
Description	Contains information about the agency that directed, authorized or performed the redaction. Can only be present if RDI = 1		
Field Min	1	Occur Min	0
Field Max	300	Occur Max	1
Char Types	U	Special Chars	None
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:RedactionInformation	Cardinality	0..1
XML Level 2	biom:ProcessingAuthorityText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.021_3

Redaction

Comment

Mnemonic	COM	Conditionality	O↑
		Status	New Active
Description	It is an optional unrestricted text string that may contain text information about the redactions affecting the stored voice recording.		
Field Min	1	Occur Min	0
Field Max	Unlimited	Occur Max	1
Char Types	U	Special Chars	None
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:RedactionInformation	Cardinality	0..1
XML Level 2	biom:ProcessingCommentText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

11.022

Redaction

Mnemonic	RDD	Conditionality	O
		Status	New Active
Description	This field contains subfields that locate the segments within the recording of this Type- 11 record that may be of interest for investigatory purposes but are not focused upon speech. If Field 11.027 is included in the record, then this field shall be present only if DII = 1.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	n/a
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:RedactionDiaryInformation	Cardinality	0..1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.022_0

Redaction

Subfields: Repeating Sets Of Information Items

Mnemonic	RDD_0	Conditionality	M↑
		Status	New Active
Description	This field contains subfields that locate the segments within the recording of this Type- 11 record that may be of interest for investigatory purposes but are not focused upon speech. If Field 11.027 is included in the record, then this field shall be present only if DII = 1.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	600000
Char Types	n/a	Special Chars	n/a
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:RedactionDiaryInformation	Cardinality	0..600000
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

11.022_1

Redaction Diary

Segment Identifier

Mnemonic	SID	Conditionality	M
		Status	New Active
Description	Present in each subfield and uniquely numbers the segment to which the following items in the subfield apply. M↑ Repeating Subfields 1 to 600000		
Field Min	1	Occur Min	1
Field Max	6	Occur Max	1
Char Types	N	Special Chars	Contains positive integer, no commas
Format	n/a	Constraints	1 <= SID <= 600000
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:RedactionDiaryInformation	Cardinality	0..600000
XML Level 2	biom:SegmentIdentifier	Cardinality	1..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.022_2

Redaction Diary

Track And Channel Number List

Mnemonic	TRK			Conditionality	D
				Status	New Active
Description	A track and channel number list. It is mandatory if TRC in Field 11.012: Physical media object / PMO or CHC of Field 11.014: Codec / CDC is greater than one and lists all tracks or channels on the recording to which the segment identifier applies. No value in this list should be greater than the value of TRC or CHC, whichever applies.				
Field Min	1	Occur Min	0		
Field Max	4	Occur Max	9999		
Char Types	NS	Special Chars	For Traditional encoding, the separator character " " is used between elements. This is not applicable to XML encoding.		
Format	n/a	Constraints	List of non-negative integers		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:RedactionDiaryInformation	Cardinality	0..600000		
XML Level 2	biom:TrackChannelList/biom:TrackID	Cardinality	0..9999		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.022_3

Redaction Diary

Relative Start Time

Mnemonic	RST			Conditionality	M↑
				Status	New Active
Description	It indicates in microseconds the time of the start of the segment relative to the absolute beginning of the recording. Segments from the same track of the audio object identified in Field 11.003: Audio object descriptor code /AOD should not overlap.				
Field Min	1	Occur Min	1		
Field Max	Unlimited	Occur Max	1		
Char Types	N	Special Chars	Must be a positive integer.		
Format	n/a	Constraints	1 <= RST		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:RedactionDiaryInformation	Cardinality	0..600000		
XML Level 2	biom:RelativeStartTime	Cardinality	1..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.022_4

Redaction Diary

Relative End Time

Mnemonic	RET			Conditionality	M↑
				Status	New Active
Description	It indicates in microseconds the time of the end of the segment relative to the absolute beginning of the recording. It is a mandatory integer for the redaction identified by SID within each subfield.				
Field Min	1	Occur Min	1		
Field Max	Unlimited	Occur Max	1		
Char Types	N	Special Chars	Must be a positive integer.		
Format	n/a	Constraints	RET > RST		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:RedactionDiaryInformation			Cardinality	0..600000
XML Level 2	biom:RelativeEndTime			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.022_5

Redaction Diary

Comment

Mnemonic	COM			Conditionality	O↑
				Status	New Active
Description	Contains an unrestricted text string that allows for comments of any type to be made on a segment.				
Field Min	1	Occur Min	0		
Field Max	Unlimited	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:RedactionDiaryInformation			Cardinality	0..600000
XML Level 2	biom:DiaryCommentText			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.023

Redaction Diary

Mnemonic	DIS				Conditionality	0			
					Status	New Active			
Description	Indicates by its presence that the voice recording referenced in this Type-11 record has had segments removed or that signals are not present for another reason.								
Field Min	n/a				Occur Min	0			
Field Max	n/a				Occur Max	1			
Char Types	n/a				Special Chars	n/a			
Format	n/a				Constraints				
Code List									
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)								
XML Level 1	biom:DiscontinuityInformation				Cardinality	0..1			
XML Level 2					Cardinality				
XML Level 3					Cardinality				
XML Level 4					Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes		

11.023_1

Discontinuities

Discontinuity Indicator

Mnemonic	DCI				Conditionality	M↑			
					Status	New Active			
Description	Code that indicates whether the voice recording contains temporal discontinuities.								
Field Min	1				Occur Min	1			
Field Max	1				Occur Max	1			
Char Types	N				Special Chars	SGI = 0 , 1 or 2			
Format	n/a				Constraints	non-negative integer			
Code List	DISCONTINUITY INDICATOR CODE								
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)								
XML Level 1	biom:DiscontinuityInformation				Cardinality	0..1			
XML Level 2	dod-ebts:ProcessingIndicatorCode				Cardinality	1..1			
XML Level 3					Cardinality				
XML Level 4					Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.023_2

Discontinuities

Cutting Authority Organization Name

Mnemonic	CTA			Conditionality	D
				Status	New Active
Description	Contains information about the agency that performed a post-processing cutting upon the original recording (removing signal content). Agencies undertaking postprocessing cutting activities should log their actions in Field 98.900: Audit log / ALF and/or Field 11.902: Annotation information / ANN of this record. Item shall only appear if DCI = 1.				
Field Min	1	Occur Min	0		
Field Max	300	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:DiscontinuityInformation			Cardinality	0..1
XML Level 2	biom:ProcessingAuthorityText			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.023_3

Discontinuities

Comments

Mnemonic	COM			Conditionality	O↑
				Status	New Active
Description	Unrestricted text string that may contain text information about the snip activities affecting the voice recording.				
Field Min	1	Occur Min	0		
Field Max	Unlimited	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:DiscontinuityInformation			Cardinality	0..1
XML Level 2	biom:ProcessingCommentText			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.024

Discontinuities

Discontinuities Diary

Mnemonic	DCD			Conditionality	O
				Status	New Active
Description	This optional field allows the documentation of discontinuities in the signal. This field need not be present if Field 11.023: Discontinuities / DIS is present in the record and DCI = 1, but it is highly recommended in such a case that this field be present.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:DiscontinuityDiaryInformation			Cardinality	0..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.024_0

Discontinuities

Subfields: Repeating Sets Of Information Items

Mnemonic	DCD_0			Conditionality	M↑
				Status	New Active
Description	This optional field allows the documentation of discontinuities in the signal. This field need not be present if Field 11.023: Discontinuities / DIS is present in the record and DCI = 1, but it is highly recommended in such a case that this field be present.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	600000		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:DiscontinuityDiaryInformation			Cardinality	0..600000
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.024_1

Discontinuities Diary

Segment Identifier

Mnemonic	SID			Conditionality	M↑
				Status	New Active
Description	Uniquely numbers the discontinuity to which the following items in the subfield apply. It is mandatory if TRC in Field 11.012: Physical media object / PMO or CHC of Field 11.014: Codec / CDC is greater than one and lists all tracks or channels on the recording to which SID applies. Must be a positive integer, no commas. 1 < SID < 600000 Repeating M↑ subsets 1 to 600000				
Field Min	1	Occur Min	1		
Field Max	6	Occur Max	1		
Char Types	N	Special Chars	positive integer, no commas		
Format	n/a	Constraints	1 < SID < 600000		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:DiscontinuityDiaryInformation			Cardinality	0..600000
XML Level 2	biom:SegmentIdentifier			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.024_2

Discontinuities Diary

Track And Channel Number List

Mnemonic	TRK			Conditionality	M↑
				Status	New Active
Description	Contains the Track and Channel Number List. It is mandatory if TRC in Field 11.012: Physical media object / PMO or CHC of Field 11.014: Codec / CDC is greater than one and lists all tracks or channels on the recording to which SID applies.				
Field Min	1	Occur Min	0		
Field Max	4	Occur Max	9999		
Char Types	NS	Special Chars	For Traditional encoding, the separator character “ ” is used between elements. This is not applicable to XML encoding.		
Format	n/a	Constraints	List of non-negative integers		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:DiscontinuityDiaryInformation			Cardinality	0..600000
XML Level 2	biom:TrackChannelList/biom:TrackID			Cardinality	0..9999
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.024_3

Discontinuities Diary

Relative Start Time

Mnemonic	RST	Conditionality	M
		Status	New Active
Description	It indicates in microseconds the time of the start of the discontinuity relative to the beginning of the voice recording contained in this Type-11 record.		
Field Min	1	Occur Min	1
Field Max	Unlimited	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	1 <= RST, integer
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:DiscontinuityDiaryInformation	Cardinality	0..600000
XML Level 2	biom:RelativeStartTime	Cardinality	1..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

11.024_4

Discontinuities Diary

Relative End Time

Mnemonic	RET	Conditionality	M↑
		Status	New Active
Description	An integer for every discontinuity identified by an SID and indicates in microseconds the time of the end of the discontinuity relative to the beginning of the voice recording contained in this Type-11 record. If RET > RST, that indicates that the content has been removed or is not present183, but not redacted (masked).		
Field Min	1	Occur Min	1
Field Max	Unlimited	Occur Max	1
Char Types	N	Special Chars	integer
Format	n/a	Constraints	RET > RST
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:DiscontinuityDiaryInformation	Cardinality	0..600000
XML Level 2	biom:RelativeEndTime	Cardinality	1..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.024_5

Discontinuities Diary

Comment

Mnemonic	COM			Conditionality	O↑
				Status	New Active
Description	An unrestricted text string that allows for comments of any type to be made about a discontinuity.				
Field Min	1	Occur Min	0		
Field Max	Unlimited	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:DiscontinuityDiaryInformation			Cardinality	0..600000
XML Level 2	biom:DiaryCommentText			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.025

Vocal Content

Mnemonic	VOC			Conditionality	O
				Status	New Active
Description	Indicates whether the voice recording content has been diarized, meaning that time markings are included in Field 11.026: Vocal content diary / VCD to indicate the speech segments of interest pertaining to the subject of this Type-11 record.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:VocalContentInformation			Cardinality	0..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-11: Forensic and Investigatory Voice Data

Page 616 of 1037

11.025_1

Vocal Content

Diarization Indicator

Mnemonic	DII			Conditionality	M↑
				Status	New Active
Description	Code that indicates whether the voice recording is accompanied by a segment diary in Field 11.026 indicating speech segments from the voice signal subject of the Type-11 record.				
Field Min	1	Occur Min	1		
Field Max	1	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	DII = 0 or 1, DiarizationIndicatorCodeType		
Code List	DISCONTINUITY INDICATOR CODE				
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:VocalContentInformation	Cardinality	0..1		
XML Level 2	biom:DiarizationIndicatorCode	Cardinality	1..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.025_2

Vocal Content

Diarization Authority Organization Name

Mnemonic	DAU			Conditionality	O↑
				Status	New Active
Description	An optional text field of up to 300 characters containing information about the agency that performed the diarization. Agencies undertaking diarization activities on the original speech should log their actions by appending to this item and noting the change of field contents in the Type-98 record and/or Field 11.902: Annotation information / ANN of this record. This information item shall only appear if DII = 1.				
Field Min	1	Occur Min	0		
Field Max	300	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:VocalContentInformation	Cardinality	0..1		
XML Level 2	biom:ProcessingAuthorityText	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.025_3

Vocal Content

Comments

Mnemonic	COM	Conditionality	O↑
		Status	New Active
Description	Contains text information about the diarization activities undertaken on the voice data.		
Field Min	1	Occur Min	0
Field Max	Unlimited	Occur Max	1
Char Types	U	Special Chars	None
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:VocalContentInformation	Cardinality	0..1
XML Level 2	biom:ProcessingCommentText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

11.026

Vocal Content

Mnemonic	VCD	Conditionality	O
		Status	New Active
Description	This field contains subfields that locate the segments within the voice recording of this Type-11 record that are associated with a single speaker – the subject of the record (not necessarily the subject of the transaction). Contains text information about the diarization activities undertaken on the voice data. If Field 11.025 is included in the record, then this field shall be present only if DII = 1. This field may be used for individual snips, as well as concatenated snips.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	n/a
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:VocalContentDiaryInformation	Cardinality	0..1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.026_0

Vocal Content

Subfields: Repeating Sets Of Information Items

Mnemonic	VCD_0	Conditionality	M↑
		Status	New Active
Description	This field contains subfields that locate the segments within the voice recording of this Type-11 record that are associated with a single speaker – the subject of the record (not necessarily the subject of the transaction). Contains text information about the diarization activities undertaken on the voice data. If Field 11.025 is included in the record, then this field shall be present only if DII = 1. This field may be used for individual snips, as well as concatenated snips.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	600000
Char Types	n/a	Special Chars	n/a
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:VocalContentDiaryInformation	Cardinality	0..600000
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

11.026_1

Vocal Content Diary

Segment Identifier

Mnemonic	SID	Conditionality	M↑
		Status	New Active
Description	Uniquely numbers the segment to which the following items in the subfield apply. Repeating M↑ subsets 1 to 600000		
Field Min	1	Occur Min	1
Field Max	6	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	1 <= SID <= 600000, Contains integer, no commas
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:VocalContentDiaryInformation	Cardinality	0..600000
XML Level 2	biom:SegmentIdentifier	Cardinality	1..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.026_2

Vocal Content Diary

Track And Channel Number List

Mnemonic	TRK	Conditionality	D
		Status	New Active
Description	Lists all tracks or channels on the recording to which the segment identifier applies. Mandatory if TRC in Field 11.012: Physical media object / PMO or CHC of Field 11.014: Codec / CDC is greater than one and lists all tracks or channels on the recording to which the segment identifier applies. A single value of 0 indicates that all tracks or channels are to be used. Note: tracks and channel counts are <= 9999.		
Field Min	1	Occur Min	0
Field Max	4	Occur Max	9999
Char Types	NS	Special Chars	For Traditional encoding, the separator character " " is used between elements. This is not applicable to XML encoding.
Format	n/a	Constraints	Contains list of non-negative integers
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:VocalContentDiaryInformation	Cardinality	0..600000
XML Level 2	biom:TrackChannelList	Cardinality	0..9999
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

11.026_3

Vocal Content Diary

Relative Start Time

Mnemonic	RST	Conditionality	M↑
		Status	New Active
Description	Indicates in microseconds the time of the start of the segment relative to the absolute beginning of the voice recording contained in this Type-11 record. A single value of 0 indicates that all tracks or channels are to be used.		
Field Min	1	Occur Min	1
Field Max	11	Occur Max	1
Char Types	N	Special Chars	Contains an integer
Format	n/a	Constraints	1 <= RST
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:VocalContentDiaryInformation	Cardinality	0..600000
XML Level 2	biom:RelativeStartTime	Cardinality	1..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.026_4

Vocal Content Diary

Relative End Time

Mnemonic	RET			Conditionality	M↑
				Status	New Active
Description	Indicates in microseconds the time of the end of the segment relative to the absolute beginning of the voice recording contained in this Type-11 record. Indicates in microseconds the time of the end of the segment relative to the absolute beginning of the voice recording contained in this Type-11 record.				
Field Min	1	Occur Min	1		
Field Max	Unlimited	Occur Max	1		
Char Types	N	Special Chars	Contains integer		
Format	n/a	Constraints	RET > RST		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:VocalContentDiaryInformation			Cardinality	0..600000
XML Level 2	biom:RelativeEndTime			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.026_5

Vocal Content Diary

Comment

Mnemonic	COM			Conditionality	O↑
				Status	New Active
Description	Allows for comments of any type to be made on a segment.				
Field Min	1	Occur Min	0		
Field Max	Unlimited	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:VocalContentDiaryInformation			Cardinality	0..600000
XML Level 2	biom:DiaryCommentText			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.026_6

Vocal Content Diary

Tagged Data

Mnemonic	TDT			Conditionality	O↑
				Status	New Active
Description	Gives the date indicated on the original, contemporaneous capture of the voice recording in the segment identified in this Type-11 record.				
Field Min	Dependent on Encoding		Occur Min	0	
Field Max	Dependent on Encoding		Occur Max	1	
Char Types	Dependent on Encoding		Special Chars		
Format	Dependent on Encoding		Constraints	YYYYMMDD	
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:VocalContentDiaryInformation			Cardinality	0..600000
XML Level 2	biom:DiaryTaggedDate/nc:Date			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.026_7

Vocal Content Diary

Tagged Start Time

Mnemonic	TST			Conditionality	O↑
				Status	New Active
Description	Time tagged on the original, contemporaneous capture of the recording in the segment identified.				
Field Min	Dependent on Encoding		Occur Min	0	
Field Max	Dependent on Encoding		Occur Max	1	
Char Types	Dependent on Encoding		Special Chars		
Format	Dependent on Encoding		Constraints	YYYYMMDDhhmm	
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:VocalContentDiaryInformation			Cardinality	0..600000
XML Level 2	biom:TagStartDateTime/nc:DateTime			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-11: Forensic and Investigatory Voice Data

Page 622 of 1037

11.026_8

Vocal Content Diary

Tagged End Time

Mnemonic	TET			Conditionality	O↑
				Status	New Active
Description	Time tagged on original, contemporaneous capture of the data at the end of the segment identified.				
Field Min	Dependent on Encoding		Occur Min	0	
Field Max	Dependent on Encoding		Occur Max	1	
Char Types	Dependent on Encoding		Special Chars		
Format	Dependent on Encoding		Constraints	YYYYMMDDhhmm	
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:VocalContentDiaryInformation			Cardinality	0..600000
XML Level 2	biom:TagEndDateTime/nc:DateTime			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.026_9

Vocal Content Diary

Original Recording Date

Mnemonic	ORD			Conditionality	O↑
				Status	New Active
Description	Date of the original, contemporaneous capture of the recording in the segment identified.				
Field Min	Dependent on Encoding		Occur Min	0	
Field Max	Dependent on Encoding		Occur Max	1	
Char Types	Dependent on Encoding		Special Chars		
Format	Dependent on Encoding		Constraints	YYYYMMDDhhmm	
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:VocalContentDiaryInformation			Cardinality	0..600000
XML Level 2	biom:OriginalRecordingDateTime/nc:Date			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-11: Forensic and Investigatory Voice Data

Page 623 of 1037

11.026_10

Vocal Content Diary

Segment Recording Start Time

Mnemonic	SRT			Conditionality	O↑
				Status	New Active
Description	Local end time of the original, contemporaneous capture of the recording in the segment identified. This information item may also be used in the case of DIA = 0, with the entire record treated as a single segment.				
Field Min	Dependent on Encoding		Occur Min	0	
Field Max	Dependent on Encoding		Occur Max	1	
Char Types	Dependent on Encoding		Special Chars		
Format	Dependent on Encoding		Constraints	YYYYMMDDhhmm	
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:VocalContentDiaryInformation			Cardinality	0..600000
XML Level 2	biom:SegmentRecordingStartDate/nc:DateTime			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.026_11

Vocal Content Diary

Segment Recording End Time

Mnemonic	END			Conditionality	O↑
				Status	New Active
Description	Local end time of the original, contemporaneous capture of the recording in the segment identified. This information item may also be used in the case of DIA = 0, with the entire record treated as a single segment.				
Field Min	Dependent on Encoding		Occur Min	0	
Field Max	Dependent on Encoding		Occur Max	1	
Char Types	Dependent on Encoding		Special Chars		
Format	Dependent on Encoding		Constraints	YYYYMMDDhhmm	
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:VocalContentDiaryInformation			Cardinality	0..600000
XML Level 2	biom:SegmentRecordingEndDate/nc:DateTime			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.026_12

Vocal Content Diary

Time Source Description Text

Mnemonic	TMD			Conditionality	O↑
				Status	New Active
Description	Reference for the values used in ORD, SRT and END.				
Field Min	1	Occur Min	0		
Field Max	300	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:VocalContentDiaryInformation	Cardinality	0..600000		
XML Level 2	biom:TimeSourceDescriptionText	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.026_13

Vocal Content Diary

Timing Comments

Mnemonic	TCOM			Conditionality	O↑
				Status	New Active
Description	Comments of any type to be made on the timings of the segment recording including the perceived accuracy of the values of ORD, SRT and END.				
Field Min	1	Occur Min	0		
Field Max	Unlimited	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:VocalContentDiaryInformation	Cardinality	0..600000		
XML Level 2	biom:TimeCommentText	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.027

Vocal Content Diary

Other Content

Mnemonic	OCON			Conditionality	O↑
				Status	New Active
Description	Indicates whether the recording content has been diarized, meaning that time markings are included, in Field 11.028: Other content diary / OCD in order to indicate the segments of the recording that may contain sounds other than the voice of the subject of the record that could assist in the investigation (such as the sound of an automobile accident in a recording). Indicates whether the recording content has been diarized, meaning that time markings are included, in Field 11.028: Other content diary / OCD in order to indicate the segments of the recording that may contain sounds other than the voice of the subject of the record that could assist in the investigation.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints			
Code List	DISCONTINUITY INDICATOR CODE				
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:OtherContentInformation			Cardinality	0..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.027_1

Other Content

Diarization Indicator

Mnemonic	DII			Conditionality	M↑
				Status	New Active
Description	This information item is mandatory if this field is used. It indicates whether the recording is accompanied by a segment diary in Field 11.028 indicating segments from the signal contained in or referred to by the Type-11 record. A value of 0 indicates that there is no accompanying diary and a value of 1 indicates the presence of Field 11.028: Other content diary / OCD. Value of 0 indicates that there is no accompanying diary and a value of 1 indicates the presence of Field 11.028: Other content diary / OCD.				
Field Min	1	Occur Min	1		
Field Max	1	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	DII = 0 or 1		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:OtherContentInformation			Cardinality	0..1
XML Level 2	biom:DiarizationIndicatorCode			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.027_2

Other Content

Diarization Authority

Mnemonic	DAU			Conditionality	D
				Status	New Active
Description	This information item is an optional text field containing information about the agency that performed the diarization. Agencies undertaking diarization activities should log their actions by appending to this item and noting the change of field contents in the Type-98 record and/or Field 11.902: Annotation information / ANN of this record. This information item shall only appear if DII = 1.				
Field Min	1	Occur Min	0		
Field Max	300	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:OtherContentInformation			Cardinality	0..1
XML Level 2	biom:ProcessingAuthorityText			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.027_3

Other Content

Comments

Mnemonic	COM			Conditionality	O↑
				Status	New Active
Description	The third information item is comments / COM. It is an optional unrestricted text string that may contain text information about the diarization activities undertaken on the recording.				
Field Min	1	Occur Min	0		
Field Max	Unlimited	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:OtherContentInformation			Cardinality	0..1
XML Level 2	biom:ProcessingCommentText			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.028

Other Content

Mnemonic	OCD		Conditionality	0	
			Status	New Active	
Description	This field contains subfields that locate the segments within the recording of this Type-11 record that may be of interest for investigatory purposes but are not focused upon speech. Although Field 11.027: Other content / OCON need not be present in the record if this field is included in the record, it is highly recommended that it be present. If Field 11.027 is included in the record, then this field shall be present only if DII = 1. This record type accommodates up to 600,000 segments.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:OtherContentDiaryInformation		Cardinality	0..1	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.028_0

Other Content

Subfields: Repeating Sets Of Information Items

Mnemonic	OCD_0		Conditionality		
			Status	New Active	
Description	This field contains subfields that locate the segments within the recording of this Type-11 record that may be of interest for investigatory purposes but are not focused upon speech. Although Field 11.027: Other content / OCON need not be present in the record if this field is included in the record, it is highly recommended that it be present. If Field 11.027 is included in the record, then this field shall be present only if DII = 1. This record type accommodates up to 600,000 segments.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	600000	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:OtherContentDiaryInformation		Cardinality	0..600000	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.028_1

Other Content

Segment Identifier

Mnemonic	SID			Conditionality	M
				Status	New Active
Description	Uniquely numbers the segment to which the following items in the subfield apply. Repeating M↑ subsets 1 to 600000				
Field Min	1	Occur Min	1		
Field Max	6	Occur Max	1		
Char Types	N	Special Chars	Contains integer, no commas		
Format	n/a	Constraints	1 <= SID <= 600000		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:OtherContentDiaryInformation	Cardinality	0..600000		
XML Level 2	biom:SegmentIdentifier	Cardinality	1..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.028_2

Other Content

Track And Channel Number List

Mnemonic	TRK			Conditionality	D
				Status	New Active
Description	Lists all tracks or channels on the recording to which the segment identifier applies. Mandatory if TRC in Field 11.012: Physical media object / PMO or CHC of Field 11.014: Codec / CDC is greater than one and lists all tracks or channels on the recording to which the segment identifier applies. A single value of 0 indicates that all tracks or channels are to be used. Note: tracks and channel counts are <= 9999.				
Field Min	1	Occur Min	0		
Field Max	4	Occur Max	9999		
Char Types	NS	Special Chars	For Traditional encoding, the separator character “ ” is used between elements. This is not applicable to XML encoding.		
Format	n/a	Constraints	Contains list of non-negative integers		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:OtherContentDiaryInformation	Cardinality	0..600000		
XML Level 2	biom:TrackChannelList/biom:TrackID	Cardinality	0..9999		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.028_3

Other Content

Relative Start Time

Mnemonic	RST	Conditionality	M↑
		Status	New Active
Description	Indicates in microseconds the time of the start of the segment relative to the absolute beginning of the voice recording contained in this Type-11 record.		
Field Min	1	Occur Min	1
Field Max	11	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	1 <= RST, Contains an integer
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:OtherContentDiaryInformation	Cardinality	0..600000
XML Level 2	biom:RelativeStartTime	Cardinality	1..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

11.028_4

Other Content

Relative End Time

Mnemonic	RET	Conditionality	M↑
		Status	New Active
Description	Indicates in microseconds the time of the end of the segment relative to the absolute beginning of the voice recording contained in this Type-11 record.		
Field Min	1	Occur Min	1
Field Max	Unlimited	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	RET > RST ; tracks and channel counts are < 9999, Contains integer
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:OtherContentDiaryInformation	Cardinality	0..600000
XML Level 2	biom:RelativeEndTime	Cardinality	1..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.028_5

Other Content

Comment

Mnemonic	COM	Conditionality	O↑
		Status	New Active
Description	Allows for comments of any type to be made on a segment.		
Field Min	1	Occur Min	0
Field Max	Unlimited	Occur Max	1
Char Types	U	Special Chars	None
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:OtherContentDiaryInformation	Cardinality	0..600000
XML Level 2	biom:DiaryCommentText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes

11.028_6

Other Content

Tagged Data

Mnemonic	TDT	Conditionality	O↑
		Status	New Active
Description	Gives the date indicated on the original, contemporaneous capture of the voice recording in the segment identified in this Type-11 record.		
Field Min	Dependent on Encoding	Occur Min	0
Field Max	Dependent on Encoding	Occur Max	1
Char Types	Dependent on Encoding	Special Chars	
Format	Dependent on Encoding	Constraints	Dependent on Encoding
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:OtherContentDiaryInformation	Cardinality	0..600000
XML Level 2	biom:DiaryTaggedDate/nc:Date	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-11: Forensic and Investigatory Voice Data

Page 631 of 1037

11.028_7

Other Content

Tagged Start Time

Mnemonic	TST			Conditionality	O↑
				Status	New Active
Description	Time tagged on the original, contemporaneous capture of the recording in the segment identified.				
Field Min	Dependent on Encoding		Occur Min	0	
Field Max	Dependent on Encoding		Occur Max	1	
Char Types	Dependent on Encoding		Special Chars		
Format	Dependent on Encoding		Constraints	Dependent on Encoding	
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:OtherContentDiaryInformation			Cardinality	0..600000
XML Level 2	biom:TagStartDateTime/nc:DateTime			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.028_8

Other Content

Tagged End Time

Mnemonic	TET			Conditionality	O↑
				Status	New Active
Description	Time tagged on original, contemporaneous capture of the data at the end of the segment identified.				
Field Min	Dependent on Encoding		Occur Min	0	
Field Max	Dependent on Encoding		Occur Max	1	
Char Types	Dependent on Encoding		Special Chars		
Format	Dependent on Encoding		Constraints	Dependent on Encoding	
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:OtherContentDiaryInformation			Cardinality	0..600000
XML Level 2	biom:TagEndDateTime/nc:DateTime			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.028_9

Other Content

Original Recording Date

Mnemonic	ORD			Conditionality	O↑
				Status	New Active
Description	Date of the original, contemporaneous capture of the recording in the segment identified.				
Field Min	Dependent on Encoding		Occur Min	0	
Field Max	Dependent on Encoding		Occur Max	1	
Char Types	Dependent on Encoding		Special Chars		
Format	Dependent on Encoding		Constraints	Dependent on Encoding	
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:OtherContentDiaryInformation			Cardinality	0..600000
XML Level 2	biom:OriginalRecordingDateTime/nc:Date			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.028_10

Other Content

Segment Recording Start Time

Mnemonic	SRT			Conditionality	O↑
				Status	New Active
Description	Local end time of the original, contemporaneous capture of the recording in the segment identified. This information item may also be used in the case of DIA = 0, with the entire record treated as a single segment.				
Field Min	Dependent on Encoding		Occur Min	0	
Field Max	Dependent on Encoding		Occur Max	1	
Char Types	Dependent on Encoding		Special Chars		
Format	Dependent on Encoding		Constraints	Dependent on Encoding	
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:OtherContentDiaryInformation			Cardinality	0..600000
XML Level 2	biom:SegmentRecordingStartDateTime/nc:DateTime			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.028_11

Other Content

Segment Recording End Time

Mnemonic	END	Conditionality	O↑
		Status	New Active
Description	Local end time of the original, contemporaneous capture of the recording in the segment identified. This information item may also be used in the case of DIA = 0, with the entire record treated as a single segment.		
Field Min	Dependent on Encoding	Occur Min	0
Field Max	Dependent on Encoding	Occur Max	1
Char Types	Dependent on Encoding	Special Chars	
Format	Dependent on Encoding	Constraints	Dependent on Encoding
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:OtherContentDiaryInformation	Cardinality	0..600000
XML Level 2	biom:SegmentRecordingEndDateTime/nc:DateTime	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

11.028_12

Other Content

Time Source Description Text

Mnemonic	TMD	Conditionality	O↑
		Status	New Active
Description	Reference for the values used in ORD, SRT and END.		
Field Min	1	Occur Min	0
Field Max	300	Occur Max	1
Char Types	U	Special Chars	None
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:OtherContentDiaryInformation	Cardinality	0..600000
XML Level 2	biom:TimeSourceDescriptionText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.028_13

Other Content

Timing Comments

Mnemonic	TCOM			Conditionality	O↑
				Status	New Active
Description	Comments of any type to be made on the timings of the segment recording including the perceived accuracy of the values of ORD, SRT and END.				
Field Min	1	Occur Min	0		
Field Max	Unlimited	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:OtherContentDiaryInformation	Cardinality	0..600000		
XML Level 2	biom:TimeCommentText	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.032

Vocal Segment Geographical Information

Mnemonic	SGEO			Conditionality	D
				Status	New Active
Description	Gives the geographical location of the primary subject of the Type-11 record at the beginning of that segment. If Field 11.025: Vocal content / VOC is present, then this field shall only be present if DII = 1. This field shall only be present if Field 11.026: Vocal content diary / VCD is present.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints			
Code List					
Source	n/a				
XML Level 1	biom:SegmentGeographicalLocation	Cardinality	0..1		
XML Level 2		Cardinality			
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	n/a	DoD EBTS 2.0	n/a	DoD EBTS 3.0	n/a
				DoD EBTS 4.0	n/a

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.032_0

Vocal Segment Geographical Information

Subfield: Repeating Sets of Information Items

Mnemonic	SGEO_0			Conditionality	M↑
				Status	New Active
Description	Gives the geographical location of the primary subject of the Type-11 record at the beginning of that segment. If Field 11.025: Vocal content / VOC is present, then this field shall only be present if DII = 1. This field shall only be present if Field 11.026: Vocal content diary / VCD is present.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints		
Code List					
Source	n/a				
XML Level 1	biom:SegmentGeographicalLocation			Cardinality	0..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	n/a	DoD EBTS 2.0	n/a	DoD EBTS 3.0	n/a
				DoD EBTS 4.0	n/a

11.032_01

Vocal Segment Geographical Information

Segment Identifier List

Mnemonic	SIL			Conditionality	M↑
				Status	New Active
Description	Segment identifiers to which the values in this subfield pertain. A value of 0 in this subfield indicates the segment geographical information in this subfield shall be considered the default value for all segments not specifically identified in other occurrences of this subfield. Repeating M↑ subsets 1 to 600000.				
Field Min	1		Occur Min	1	
Field Max	6		Occur Max	600000	
Char Types	NS		Special Chars	list of non-negative integers For Traditional encoding, the separator character “ ” is used between elements.This is not applicable to XML encoding.	
Format	n/a		Constraints	None	
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:SegmentGeographicalLocation			Cardinality	0..1
XML Level 2	biom:SegmentIdentifierList/biom:SegmentIdentifier			Cardinality	1..600000
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.032_02

Vocal Segment Geographical Information

Segment Cell Phone Tower Code

Mnemonic	SCT			Conditionality	O↑
				Status	New Active
Description	Identifies the cell phone tower, if any, that relayed the audio data at the start of the segment or segments referred to in this subfield.				
Field Min	1	Occur Min	0		
Field Max	100	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:SegmentGeographicalLocation			Cardinality	0..1
XML Level 2	biom:CellPhoneTowerCodeText			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.032_03

Vocal Segment Geographical Information

Latitude Degree Value

Mnemonic	LTD			Conditionality	D
				Status	New Active
Description	The second information item is latitude degree value / LTD. This is a value that specifies the degree of latitude. The value shall be between -90 (inclusive) and +90 (inclusive). The degrees may be expressed as an integer (without a decimal) or a real number including decimals. If decimals are present, then minutes and seconds shall be empty.				
Field Min	1	Occur Min	1		
Field Max	9	Occur Max	1		
Char Types	NS	Special Chars	Decimal,Minus Sign,Plus Sign		
Format	n/a	Constraints	-90 < LTD < 90		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:SegmentGeographicalLocation			Cardinality	0..1
XML Level 2	biom:TwoDimensionalGeographicCoordinate (0...1)/nc:GeographicCoordinateLatitude (0...1)			Cardinality	0..1
XML Level 3	nc:LatitudeDegreeValue			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

11.032_04

Vocal Segment Geographical Information

Latitude Minute Value

Mnemonic	LTM	Conditionality	D
		Status	New Active
Description	The third information item is latitude minute value / LTM. This is a value that specifies a minute of a degree. The value shall be between 0 (inclusive) to 60 (exclusive). The minute value may be expressed as an integer (without a decimal) or as a real number including decimals. If decimals are present then seconds shall be empty. The minute value is empty, even if the degree value is an integer.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	NS	Special Chars	Decimal,Minus Sign,Plus Sign
Format	n/a	Constraints	0 <= LTM < 60
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:SegmentGeographicalLocation	Cardinality	0..1
XML Level 2	biom:TwoDimensionalGeographicCoordinate (0..1)/nc:GeographicCoordinateLatitude (0..1)	Cardinality	0..1
XML Level 3	nc:LatitudeMinuteValue	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

11.032_05

Vocal Segment Geographical Information

Latitude Second Value

Mnemonic	LTS	Conditionality	D
		Status	New Active
Description	The fourth information item is the latitude second value / LTS. This is a value that specifies a second of a minute. The integer shall be 0 (inclusive) to 60 (exclusive). The second value is empty, even if the minute value is an integer.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	NS	Special Chars	None
Format	n/a	Constraints	0 <= LTS < 60
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:SegmentGeographicalLocation	Cardinality	0..1
XML Level 2	biom:TwoDimensionalGeographicCoordinate (0..1)/nc:GeographicCoordinateLatitude (0..1)	Cardinality	0..1
XML Level 3	nc:LatitudeSecondValue	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.032_06

Vocal Segment Geographical Information

Longitude Degree Value

Mnemonic	LGD	Conditionality	D
		Status	New Active
Description	The fifth information item is the longitude degree value / LGD. It is a value that specifies the degree of a longitude. The value shall be between -180 (inclusive) and +180 (inclusive). If LTD is present, then LGD shall be present. The degrees may be expressed as whole numbers (without a decimal) or real numbers including decimals. If decimals are present, then minutes and seconds are empty.		
Field Min	1	Occur Min	0
Field Max	10	Occur Max	1
Char Types	NS	Special Chars	Decimal,Minus Sign,Plus Sign
Format	n/a	Constraints	-180 =< LGD =< 180
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:SegmentGeographicalLocation	Cardinality	0..1
XML Level 2	biom:TwoDimensionalGeographicCoordinate (0...1)/nc:GeographicCoordinateLongitude (0...1)	Cardinality	0..1
XML Level 3	nc:LongitudeDegreeValue	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

11.032_07

Vocal Segment Geographical Information

Longitude Minute Value

Mnemonic	LGM	Conditionality	D
		Status	New Active
Description	The sixth information item is the longitude minute value / LGM. It is a value that specifies a minute of a degree. The value shall be from 1 (inclusive) to 60 (exclusive). The minute value may be expressed as an integer (without a decimal) or as a real number including decimals. If decimals are present then seconds shall not appear. The minute value is empty, even if the degree value is an integer. If LTM is present, then L		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	NS	Special Chars	Decimal
Format	n/a	Constraints	1 <= LGM < 60
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:SegmentGeographicalLocation	Cardinality	0..1
XML Level 2	biom:TwoDimensionalGeographicCoordinate (0...1)/nc:GeographicCoordinateLongitude (0...1)	Cardinality	0..1
XML Level 3	nc:LongitudeMinuteValue	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

11.032_08

Vocal Segment Geographical Information

Longitude Second Value

Mnemonic	LGS	Conditionality	D
		Status	New Active
Description	The seventh information item is the longitude second value / LGS. This is a value that specifies a second of a minute. The integer shall be 0 (inclusive) to 60 (exclusive). The second value is empty, even if the minute value is an integer. If LTS is present, then LGS shall be present.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	NS	Special Chars	None
Format	n/a	Constraints	0 <= LGS < 60
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:SegmentGeographicalLocation	Cardinality	0..1
XML Level 2	biom:TwoDimensionalGeographicCoordinate (0..1)/nc:GeographicCoordinateLongitude (0..1)	Cardinality	0..1
XML Level 3	nc:LongitudeSecondValue	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

11.032_09

Vocal Segment Geographical Information

Elevation

Mnemonic	ELE	Conditionality	D
		Status	New Active
Description	Elevation is expressed in meters as a numeric value. It is between -422 meters (Dead Sea) and 8848 meters (Mount Everest).		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	NS	Special Chars	Minus Sign,Period
Format	n/a	Constraints	-422.000 < ELE < 8848.000; real number
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:SegmentGeographicalLocation	Cardinality	0..1
XML Level 2	nc:LocationElevation	Cardinality	0..1
XML Level 3	nc:MeasurePointValue	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.032_10

Vocal Segment Geographical Information

Geodetic Datum Code

Mnemonic	GDC			Conditionality	D
				Status	New Active
Description	The ninth information item is the geodetic datum code / GDC11. This information item is used to indicate which coordinate system was used to represent the values in information items 2 through 7. If no entry is made in this information item, then the basis for the values entered in the first eight information items shall be WGS84, the code for the World Geodetic Survey 1984 version - WGS 84 (G873). See look up codes for values.				
Field Min	3	Occur Min	0		
Field Max	6	Occur Max	1		
Char Types	AN	Special Chars	None		
Format	n/a	Constraints	see Look Up Codes		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:SegmentGeographicalLocation	Cardinality	0..1		
XML Level 2	nc:GeographicDatum	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.032_11

Vocal Segment Geographical Information

Geographic Coordinate Universal Transverse Mercator Zone

Mnemonic	GCM			Conditionality	D
				Status	New Active
Description	It is an alphanumeric value of 2 to 3 characters. This is a one or two digit UTM zone number followed by the 8 degree latitudinal band designator (which is a single letter).				
Field Min	2	Occur Min	0		
Field Max	3	Occur Max	1		
Char Types	AN	Special Chars	None		
Format	n/a	Constraints	One or two integers followed by a single letter. Valid latitudinal band designators include C through X, omitting I and O.		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:SegmentGeographicalLocation	Cardinality	0..1		
XML Level 2	nc:LocationUTMCoordinate	Cardinality	0..1		
XML Level 3	nc:UTMGridZoneID	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-11: Forensic and Investigatory Voice Data

Page 641 of 1037

11.032_12

Vocal Segment Geographical Information

Geographic Coordinate Universal Transverse Mercator Easting

Mnemonic	GCE			Conditionality	D
				Status	New Active
Description	The eleventh information item is the geographic coordinate universal transverse Mercator easting / GCE. It is an integer of 1 to 6 digits.				
Field Min	1	Occur Min	0		
Field Max	6	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:SegmentGeographicalLocation	Cardinality	0..1		
XML Level 2	nc:LocationUTMCoordinate	Cardinality	0..1		
XML Level 3	nc:UTMEastingValue	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.032_13

Vocal Segment Geographical Information

Geographic Coordinate Universal Transverse Mercator Northing

Mnemonic	GCN			Conditionality	D
				Status	New Active
Description	The twelfth information item is the geographic coordinate universal transverse Mercator northing / GCN. It is an integer of 1 to 8 digits.				
Field Min	1	Occur Min	0		
Field Max	8	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:SegmentGeographicalLocation	Cardinality	0..1		
XML Level 2	nc:LocationUTMCoordinate	Cardinality	0..1		
XML Level 3	nc:UTMNorthingValue	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.032_14

Vocal Segment Geographical Information

Geographic Reference Text

Mnemonic	GRT	Conditionality	O
		Status	New Active
Description	A fourteenth optional information item geographic coordinate other system identifier / OSI allows for other coordinate systems. This information items specifies the system identifier. It is up to 10 characters in length. Examples are: MGRS (Military Grid Reference System), USNG (United States National Grid), GARS (Global Area Reference System), GEOREF (World Geographic Reference), and LANDMARK landmark (e.g. hydant) and position relative to the landmark.		
Field Min	1	Occur Min	1
Field Max	150	Occur Max	1
Char Types	U	Special Chars	Any
Format	n/a	Constraints	
Code List	GEOGRAPHIC COORDINATE DATUM CODE		
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:SegmentGeographicalLocation	Cardinality	0..1
XML Level 2	biom_2:GeographicLocationText	Cardinality	1..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

11.032_15

Vocal Segment Geographical Information

Geographic Coordinate Other System Identifier (or Landmark)

Mnemonic	OSI	Conditionality	O
		Status	New Active
Description	A fifteenth optional information item, is the geographic coordinate other system value / OCV. It shall only be present if OSI is present in the record. It can be up to 126 characters in length. If OSI is LANDMARK, OCV is free text and may be up to 126 characters. For details on the formatting of OCV for the other coordinate systems shown in OSI as examples, see http://earth-info.nga.mil/GandG/coordsys/grids/referencesys.html .		
Field Min	1	Occur Min	1
Field Max	10	Occur Max	1
Char Types	U	Special Chars	None
Format	n/a	Constraints	
Code List	GEOGRAPHIC COORDINATE DATUM CODE		
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:SegmentGeographicalLocation	Cardinality	0..1
XML Level 2	biom_2:LocationAlternateGeographicSystemValue	Cardinality	0..1
XML Level 3	biom_2:GeographicLocationSystemName	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.032_16

Vocal Segment Geographical Information

Geographic Coordinate Other System Value

Mnemonic	OCV			Conditionality	D
				Status	New Active
Description	A sixteenth information item is the geographic coordinate other system value / OCV. It is optional and may only be present if OSI is present in the record (which is the dependency listed in the record layout table).				
Field Min	1	Occur Min	0		
Field Max	126	Occur Max	1		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:SegmentGeographicalLocation	Cardinality	0..1		
XML Level 2	biom_2:LocationAlternateGeographicSystemValue	Cardinality	0..1		
XML Level 3	biom_2:GeographicLocationText	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.033

Vocal Segment Quality Values

Mnemonic	SQV			Conditionality	D
				Status	New Active
Description	Quality values based on different types of quality assessments, Present if DII = 1.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:VocalSegmentQualityValue	Cardinality	0..1		
XML Level 2		Cardinality			
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.033_0

Vocal Segment Quality Values

Subfield: Repeating Sets of Information Items

Mnemonic	SQV_0	Conditionality	M↑
		Status	New Active
Description	Quality values based on different types of quality assessments, Present if DII = 1.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	9
Char Types	n/a	Special Chars	n/a
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:VocalSegmentQualityValue	Cardinality	0..9
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

11.033_1

Vocal Segment

Segment Identifier List

Mnemonic	SIL	Conditionality	M↑
		Status	New Active
Description	Each subfield and gives the segment identifiers to which the values in this subfield pertain. A value of 0 in this subfield indicates the segment geographical information in this subfield shall be considered the default value for all segments not specifically identified in other occurrences of this subfield. Repeating M↑ subsets 1 to 9.		
Field Min	1	Occur Min	0
Field Max	6	Occur Max	600000
Char Types	NS	Special Chars	For Traditional encoding, the separator character “ ” is used between elements. This is not applicable to XML encoding.
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:VocalSegmentQualityValue	Cardinality	0..9
XML Level 2	biom:SegmentIdentifierList/biom:SegmentIdentifier	Cardinality	0..600000
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.033_2

Vocal Segment Quality Values

Quality Value

Mnemonic	QVU			Conditionality	M↑
				Status	New Active
Description	Indicate the segment quality value between 0 (low quality) and 100 (high quality). A value of 255 indicates that quality was not assessed.				
Field Min	1	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	integer		
Format	n/a	Constraints	0 <= QVU <+ 100 or = 255		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:VocalSegmentQualityValue			Cardinality	0..9
XML Level 2	biom:QualityValue			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.033_3

Vocal Segment Quality Values

Algorithm Vendor Identification

Mnemonic	QAV			Conditionality	M↑
				Status	New Active
Description	Specifies the ID of the vendor of the quality assessment algorithm used to calculate the quality score. This 4-digit hex value is assigned by IBIA and expressed as four characters. A value of 0000 indicates a vendor without a designation by IBIA.				
Field Min	4	Occur Min	1		
Field Max	4	Occur Max	1		
Char Types	H	Special Chars	None		
Format	n/a	Constraints	0000 <= QAV <= FFFF		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:VocalSegmentQualityValue			Cardinality	0..9
XML Level 2	biom:QualityAlgorithmVendorIdentification/nc:IdentificationType			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.033_4

Vocal Segment Quality Values

Algorithm Product Identification

Mnemonic	QAP			Conditionality	M↑
				Status	New Active
Description	Specifies a numeric product code assigned by the vendor of the quality assessment algorithm. Indicates which of the vendor's algorithms was used in the calculation of the quality score. A value of 0 indicates a vendor without a designation by IBIA.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	integer		
Format	n/a	Constraints	0 <= QAP <= 65534		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:VocalSegmentQualityValue	Cardinality	0..9		
XML Level 2	biom:QualityAlgorithmProductIdentification/nc:IdentificationType	Cardinality	1..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.033_5

Vocal Segment Quality Values

Comments

Mnemonic	COM			Conditionality	D
				Status	New Active
Description	Provides information about the quality assessment process, including a description of any unregistered quality assessment algorithms used.				
Field Min	0	Occur Min	0		
Field Max	Unlimited	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:VocalSegmentQualityValue	Cardinality	0..9		
XML Level 2	biom:VocalSegmentQualityCommentText	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.034

Vocal Collision Identifier

Mnemonic	VCI	Conditionality	D
		Status	New Active
Description	Field indicating that a vocal collision (two or more persons talking at once) occurs within the segment. If Field 11.025: Vocal content / VOC is present, then this field shall only be present if DII = 1. This field shall only be present if Field 11.026: Vocal content diary / VCD is present.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1
Char Types	N	Special Chars	non-negative integer
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:VocalCollisionIdentifierList	Cardinality	0..1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

11.034_0

Vocal Collision Identifier

Subfield: Repeating Sets Of Information Items

Mnemonic	VCI_0	Conditionality	M↑
		Status	New Active
Description	Gives the segment identifiers to which the values in this subfield pertain. A value of 0 indicates the segment geographical information in this subfield shall be considered the default value. Repeating M↑ subsets 1 to 600000.		
Field Min	1	Occur Min	0
Field Max	6	Occur Max	600000
Char Types	N	Special Chars	list of non-negative integers For Traditional encoding, the separator character “ ” is used between elements. This is not applicable to XML encoding.
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:VocalCollisionIdentifierList/biom:SegmentIdentifier	Cardinality	0..600000
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

11.035

Vocal Segment Processing Priority

Mnemonic	PPY		Conditionality	M			
			Status	New Active			
Description	Only appears if Field 11.025: Vocal content / VOC exists in this record. Segments not identified should be given the lowest priority.						
Field Min	n/a	Occur Min	0				
Field Max	n/a	Occur Max	1				
Char Types	n/a	Special Chars	n/a				
Format	n/a	Constraints					
Code List							
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)						
XML Level 1	biom:SegmentProcessingPriorityInformation		Cardinality	0..1			
XML Level 2			Cardinality				
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

11.035_0

Vocal Segment Processing Priority

Subfield: Repeating Sets Of Information Items

Mnemonic	PPY_0		Conditionality	M↑			
			Status	New Active			
Description	Only appears if Field 11.025: Vocal content / VOC exists in this record. Segments not identified should be given the lowest priority.						
Field Min	n/a	Occur Min	0				
Field Max	n/a	Occur Max	9				
Char Types	n/a	Special Chars	n/a				
Format	n/a	Constraints					
Code List							
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)						
XML Level 1	biom:SegmentProcessingPriorityInformation		Cardinality	0..9			
XML Level 2			Cardinality				
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.035_1

Vocal Segment Processing Priority

Segment Identifier List

Mnemonic	SIL			Conditionality	M↑
				Status	New Active
Description	Gives the segment identifiers to which the values in this subfield pertain. A value of 0 indicates the segment geographical information in this subfield shall be considered the default value. Repeating M↑ subsets 1 to 600000.				
Field Min	1	Occur Min	0		
Field Max	6	Occur Max	600000		
Char Types	NS		Special Chars	For Traditional encoding, the separator character “ ” is used between elements. This is not applicable to XML encoding.	
Format	n/a		Constraints		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:SegmentProcessingPriorityInformation			Cardinality	0..9
XML Level 2	biom:SegmentIdentifierList/biom:SegmentIdentifier			Cardinality	0..600000
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.035_2

Vocal Segment Processing Priority

Priority

Mnemonic	PTY			Conditionality	M↑
				Status	New Active
Description	Indicates the priority with which the segments identified in this subfield should be processed. A value of 1 will indicate the highest priority and 9 the lowest.				
Field Min	1	Occur Min	1		
Field Max	1	Occur Max	1		
Char Types	N		Special Chars	positive integer	
Format	n/a		Constraints	1 <= PTY <= 9	
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:SegmentProcessingPriorityInformation			Cardinality	0..9
XML Level 2	biom:ProcessingPriorityValue			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.036

Vocal Segment Processing Priority

Mnemonic	VSCT			Conditionality	D
				Status	New Active
Description	Gives an assessment of the content of the voice data within the identified segment and includes provision for semantic transcripts, phonetic transcripts and translations of the segment.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:SegmentContentInformation			Cardinality	0..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.036_0

Vocal Segment Processing Priority

Subfield: Repeating Sets Of Information Items

Mnemonic	VSCT_0			Conditionality	M↑
				Status	New Active
Description	Gives an assessment of the content of the voice data within the identified segment and includes provision for semantic transcripts, phonetic transcripts and translations of the segment.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	600000		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:SegmentContentInformation			Cardinality	0..600000
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.036_1

Vocal Segment Processing Priority

Segment Identifier List

Mnemonic	SIL			Conditionality	M↑
				Status	New Active
Description	A value of 0 indicates the segment geographical information in this subfield shall be considered the default value. Repeating M↑ subsets 1 to 600000.				
Field Min	1	Occur Min	0		
Field Max	6	Occur Max	600000		
Char Types	NS	Special Chars	For Traditional encoding, the separator character “ ” is used between elements. This is not applicable to XML encoding.		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:SegmentContentInformation	Cardinality	0..600000		
XML Level 2	biom:SegmentIdentifierList/biom:SegmentIdentifier	Cardinality	0..600000		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.036_2

Vocal Segment Processing Priority

Transcript Text

Mnemonic	TRN			Conditionality	O↑
				Status	New Active
Description	Contains a semantic transcription of the segment.				
Field Min	1	Occur Min	0		
Field Max	Unlimited	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:SegmentContentInformation	Cardinality	0..600000		
XML Level 2	biom:SegmentTranscriptText	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.036_3

Vocal Segment Processing Priority

Transcript Language

Mnemonic	LNG	Conditionality	O↑
		Status	New Active
Description	Code for the language of the translation.		
Field Min	3	Occur Min	0
Field Max	3	Occur Max	1
Char Types	A	Special Chars	None
Format	n/a	Constraints	
Code List	3 character ISO 639-3 code for the language of the translation included in this subfield.		
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:SegmentContentInformation	Cardinality	0..600000
XML Level 2	biom:SegmentTranscriptLanguageCode	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

11.036_4

Vocal Segment Processing Priority

Phonetic Transcript Text

Mnemonic	PTT	Conditionality	O↑
		Status	New Active
Description	Contains a phonetic transcription of the segment.		
Field Min	1	Occur Min	0
Field Max	Unlimited	Occur Max	1
Char Types	U	Special Chars	None
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:SegmentContentInformation	Cardinality	0..600000
XML Level 2	biom:SegmentPhoneticTranscriptText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-11: Forensic and Investigatory Voice Data

Page 653 of 1037

11.036_5

Vocal Segment Processing Priority

Phonetic Transcript Convention

Mnemonic	PTC			Conditionality	O↑
				Status	New Active
Description	States the phonetic transcript convention. Present only if PTT is present in the subfield.				
Field Min	1	Occur Min	0		
Field Max	100	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:SegmentContentInformation			Cardinality	0..600000
XML Level 2	biom:PhoneticTranscriptConvention			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.036_6

Vocal Segment Processing Priority

Translation Text

Mnemonic	TLT			Conditionality	O↑
				Status	New Active
Description	Contains a translation of the segment into a language other than the one in which the original segment was spoken.				
Field Min	1	Occur Min	0		
Field Max	Unlimited	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:SegmentContentInformation			Cardinality	0..600000
XML Level 2	biom:SegmentTranslationText			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-11: Forensic and Investigatory Voice Data

Page 654 of 1037

11.036_7

Vocal Segment Processing Priority

Translation Language

Mnemonic	TLG			Conditionality	O↑		
				Status	New Active		
Description	Language of the translation. Present only if TLT is present.						
Field Min	3			Occur Min	0		
Field Max	3			Occur Max	1		
Char Types	A			Special Chars	None		
Format	n/a			Constraints			
Code List	3 character ISO 639-3 code for the language of the translation included in this subfield.						
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)						
XML Level 1	biom:SegmentContentInformation			Cardinality	0..600000		
XML Level 2	biom:TranslationLanguageCode			Cardinality	0..1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

11.036_8

Vocal Segment Processing Priority

Segment Content Comment

Mnemonic	COM			Conditionality	O↑		
				Status	New Active		
Description	Contains comments on the content of the segment.						
Field Min	1			Occur Min	0		
Field Max	Unlimited			Occur Max	1		
Char Types	U			Special Chars	None		
Format	n/a			Constraints			
Code List							
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)						
XML Level 1	biom:SegmentContentInformation			Cardinality	0..600000		
XML Level 2	biom:SegmentContentCommentText			Cardinality	0..1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.036_9

Vocal Segment Processing Priority

Transcript Authority Comment Text

Mnemonic	TAC	Conditionality	O↑
		Status	New Active
Description	States the authority providing the transcription, translation or comments in TRN, PTT, TLT or COM. If an automated process was used to develop the transcript, information about the process (i.e., the automated algorithm used) should be stated.		
Field Min	1	Occur Min	0
Field Max	Unlimited	Occur Max	1
Char Types	U	Special Chars	None
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:SegmentContentInformation	Cardinality	0..600000
XML Level 2	biom:TranscriptAuthorityCommentText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

11.037

Vocal Segment Speaker Characteristics

Mnemonic	SCC	Conditionality	D
		Status	New Active
Description	Gives an assessment of the characteristics of the voice within the segment, including intelligibility, emotional state and impairment. This field shall only appear if Field 11.025: Vocal content / VOC exists in the record.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	n/a
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:SegmentSpeakerCharacteristicsInformation	Cardinality	0..1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.037_0

Vocal Segment Speaker Characteristics

Subfield: Repeating Sets Of Information Items

Mnemonic	SCC_0			Conditionality	M↑
				Status	New Active
Description	Gives an assessment of the characteristics of the voice within the segment, including intelligibility, emotional state and impairment. This field shall only appear if Field 11.025: Vocal content / VOC exists in the record.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	600000		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:SegmentSpeakerCharacteristicsInformation			Cardinality	0..600000
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.037_1

Vocal Segment Speaker Characteristics

Segment Identifier List

Mnemonic	SIL			Conditionality	M↑
				Status	New Active
Description	Gives the segment identifiers to which the values in this subfield pertain. 0 in this subfield indicates the segment geographical information in this subfield shall be considered the default value for all segments not specifically identified in other occurrences of this subfield. Repeating M↑ subsets 1 to 600000.				
Field Min	1	Occur Min	0		
Field Max	6	Occur Max	600000		
Char Types	NS	Special Chars	For Traditional encoding, the separator character “ ” is used between elements.		
Format	n/a	Constraints	List of non-negative integers		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:SegmentSpeakerCharacteristicsInformation			Cardinality	0..600000
XML Level 2	biom:SegmentIdentifierList/biom:SegmentIdentifier			Cardinality	0..600000
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.037_2

Vocal Segment Speaker Characteristics

Speaker List

Mnemonic	SPL			Conditionality	O↑
				Status	New Active
Description	List of unique identifiers for the speakers in the segments identified in SIL. List may have up to 9999 speakers per segment grouping.				
Field Min	1	Occur Min	0		
Field Max	4	Occur Max	9999		
Char Types	U	Special Chars	For Traditional encoding, the separator character “ ” is used between elements. This is not applicable to XML encoding.		
Format	n/a	Constraints	List of non-negative integers		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:SegmentSpeakerCharacteristicsInformation			Cardinality	0..600000
XML Level 2	biom:SpeakerList/biom:SpeakerIdentifier			Cardinality	0..9999
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.037_3

Vocal Segment Speaker Characteristics

Type-2 Record Cross Reference

Mnemonic	T2C			Conditionality	O↑
				Status	New Active
Description	Contains the IDC value of the Type-2 record that contains relevant biographic information and other data concerning the subject of this instance of the record. This list may have up to 98 references (there is a maximum of 100 records in a transaction; Type-1 is required and this record has an IDC value, leaving a maximum of 98 other possible records.				
Field Min	1	Occur Min	0		
Field Max	2	Occur Max	98		
Char Types	NS	Special Chars	For Traditional encoding, the separator character “ ” is used between elements. This is not applicable to XML encoding.		
Format	n/a	Constraints	List of non-negative integers, 1 < T2C value < 99		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:SegmentSpeakerCharacteristicsInformation			Cardinality	0..600000
XML Level 2	biom:Type2CrossReferenceIdentificationList/biom:Type2CrossReferenceIdentification/nc:IdentificationID			Cardinality	0..98
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.037_4

Vocal Segment Speaker Characteristics

Impairment Level Number

Mnemonic	IMP			Conditionality	O↑
				Status	New Active
Description	Indicates a subjective, observed level of neurological diminishment, whether from fatigue, disease, trauma, or the influence of medication/substances, across the speech segments identified. An integer between 0 (no noticed impairment) and 5 (significant), inclusive.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= IMP <= 5, integer		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:SegmentSpeakerCharacteristicsInformation			Cardinality	0..600000
XML Level 2	biom:ImpairmentValue			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.037_5

Vocal Segment Speaker Characteristics

Dominant Spoken

Mnemonic	DSL			Conditionality	O↑
				Status	New Active
Description	3 character ISO 639-3 code for the dominant language in the segments identified in this subfield.				
Field Min	3	Occur Min	0		
Field Max	3	Occur Max	1		
Char Types	A	Special Chars	None		
Format	n/a	Constraints			
Code List	3 character ISO 639-3 code for the language of the translation included in this subfield.				
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:SegmentSpeakerCharacteristicsInformation			Cardinality	0..600000
XML Level 2	biom:SpokenLanguageCode			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.037_6

Vocal Segment Speaker Characteristics

Language Code

Mnemonic	LPS	Conditionality	O↑
		Status	New Active
Description	Rates the subjective estimation of the fluency of the language being spoken Scale of 0 (no proficiency) to 9 (high proficiency)		
Field Min	1	Occur Min	0
Field Max	1	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	0 < =LPS <= 9
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:SegmentSpeakerCharacteristicsInformation	Cardinality	0..600000
XML Level 2	biom:LanguageProficiencyValue	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

11.037_7

Vocal Segment Speaker Characteristics

Speech Style Code

Mnemonic	STY	Conditionality	O↑
		Status	New Active
Description	Code indicating the dominant style of speech within the segments.		
Field Min	1	Occur Min	0
Field Max	2	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	
Code List	SPEECH STYLE CODE		
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:SegmentSpeakerCharacteristicsInformation	Cardinality	0..600000
XML Level 2	biom:SpeechStyleCode	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.037_8

Vocal Segment Speaker Characteristics

Intelligibility Scale Code

Mnemonic	INT	Conditionality	O↑
		Status	New Active
Description	Integer describing the subjective evaluation of the speech. 0 (unintelligible) to 9 (clear and fully intelligible)		
Field Min	0	Occur Min	0
Field Max	1	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	0 <= INT <= 9, integer
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:SegmentSpeakerCharacteristicsInformation	Cardinality	0..600000
XML Level 2	biom:IntelligibilityValue	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

11.037_9

Vocal Segment Speaker Characteristics

Familiarity Degree Code

Mnemonic	FDC	Conditionality	O↑
		Status	New Active
Description	Indicates the perceived degree of familiarity between the data subject and the interlocutor. Ranges from 0 indicating no familiarity to 5 indicating high familiarity/intimacy.		
Field Min	0	Occur Min	0
Field Max	1	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	0 <= FDC <= 5,integer
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:SegmentSpeakerCharacteristicsInformation	Cardinality	0..600000
XML Level 2	biom:FamiliarityValue	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-11: Forensic and Investigatory Voice Data

Page 661 of 1037

11.037_10

Vocal Segment Speaker Characteristics

Health Comment

Mnemonic	HCM			Conditionality	O↑		
				Status	New Active		
Description	Notes any observable health issues impacting the data subject during the speech segment.						
Field Min	0		Occur Min	0			
Field Max	Unlimited		Occur Max	1			
Char Types	U		Special Chars	None			
Format	n/a		Constraints				
Code List							
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)						
XML Level 1	biom:SegmentSpeakerCharacteristicsInformation			Cardinality	0..600000		
XML Level 2	biom:HealthCommentText			Cardinality	0..1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

11.037_11

Vocal Segment Speaker Characteristics

Emotional State Code

Mnemonic	EMC			Conditionality	O↑		
				Status	New Active		
Description	An integer giving a subjective estimation of the emotional state of the data subject for the data subject across the segments identified.						
Field Min	1		Occur Min	0			
Field Max	2		Occur Max	1			
Char Types	N		Special Chars	None			
Format	n/a		Constraints				
Code List	EMOTIONAL STATE CODE						
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)						
XML Level 1	biom:SegmentSpeakerCharacteristicsInformation			Cardinality	0..600000		
XML Level 2	biom:EmotionalStateCode			Cardinality	0..1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.037_12

Vocal Segment Speaker Characteristics

Vocal Effort Scale Number

Mnemonic	VES			Conditionality	O↑
				Status	New Active
Description	Reports the subjective, perceived vocal effort of the subject across the identified segments (very low vocal effort) and 5 (screaming/crying) Integer between 0				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 < =VES <= 5, integer		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:SegmentSpeakerCharacteristicsInformation			Cardinality	0..600000
XML Level 2	biom:VocalEffortValue			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.037_13

Vocal Segment Speaker Characteristics

Vocal Style Code

Mnemonic	VSC			Conditionality	O↑
				Status	New Active
Description	Assesses the subjective predominant vocal style of the data subject across the identified segments.				
Field Min	1	Occur Min	0		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints			
Code List	VOCAL STYLE CODE				
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:SegmentSpeakerCharacteristicsInformation			Cardinality	0..600000
XML Level 2	biom:VocalStyleCode			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.037_14

Vocal Segment Speaker Characteristics

Recording Awareness Indicator

Mnemonic	RAI			Conditionality	O↑
				Status	New Active
Description	Indicates whether the data subject is aware that a recording is being made.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	RAI = 0, 1 or 2		
Code List	RECORDING AWARENESS INDICATOR				
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:SegmentSpeakerCharacteristicsInformation			Cardinality	0..600000
XML Level 2	biom:RecordingAwarenessCode			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.037_15

Vocal Segment Speaker Characteristics

Script Text

Mnemonic	SCR			Conditionality	O↑
				Status	New Active
Description	Used to give the script used for read, prompted or repeated speech.				
Field Min	1	Occur Min	0		
Field Max	Unlimited	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:SegmentSpeakerCharacteristicsInformation			Cardinality	0..600000
XML Level 2	biom:ScriptText			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.037_16

Vocal Segment Speaker Characteristics

Comments

Mnemonic	COM	Conditionality	O↑
		Status	New Active
Description	Used to give additional information about the characteristic assessment process, including a description of any characteristic assessment algorithms used, Notes on any known external stresses applicable to the data subject, and a description of how the values in the items of this subfield were assigned.		
Field Min	1	Occur Min	0
Field Max	Unlimited	Occur Max	1
Char Types	U	Special Chars	None
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:SegmentSpeakerCharacteristicsInformation	Cardinality	0..600000
XML Level 2	biom:SpeechCharacteristicsCommentText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

11.038

Vocal Segment Channel

Mnemonic	SCH	Conditionality	D
		Status	New Active
Description	Describes the transducer and transmission channel within the identified segments. Only be present if Field 11.025: Vocal content / VOC appears in this record. A value of 0 in this subfield indicates the segment geographical information in this subfield is the default value for all segments not specifically identified in other occurrences of this subfield.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	n/a
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:SegmentChannelInformation	Cardinality	0..1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.038_0

Vocal Segment Channel

Subfield: Repeating Sets Of Information Items

Mnemonic	SCH_0			Conditionality	M↑
				Status	New Active
Description	Describes the transducer and transmission channel within the identified segments. Only be present if Field 11.025: Vocal content / VOC appears in this record. A value of 0 in this subfield indicates the segment geographical information in this subfield is the default value for all segments not specifically identified in other occurrences of this subfield.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	600000		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:SegmentChannelInformation			Cardinality	0..600000
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.038_1

Vocal Segment Channel

Segment Identifier List

Mnemonic	SIL			Conditionality	M↑
				Status	New Active
Description	Gives the segment identifiers to which the values in this subfield pertain. Repeating M↑ subsets 1 to 600000.				
Field Min	1	Occur Min	1		
Field Max	6	Occur Max	600000		
Char Types	NS	Special Chars	For Traditional encoding, the separator character “ ” is used between elements. This is not applicable to XML encoding.		
Format	n/a	Constraints	List of non-negative integers		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:SegmentChannelInformation			Cardinality	0..600000
XML Level 2	biom:SegmentIdentifierList/biom:SegmentIdentifier			Cardinality	1..600000
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.038_2

Vocal Segment Channel

Audio Capture Device Code

Mnemonic	ACD			Conditionality	O↑
				Status	New Active
Description	A code indicating the audio capture device type. A value of "2" indicates that more than one type of microphone is being used simultaneously to collect the audio signal.				
Field Min	1	Occur Min	0		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	AudioCaptureDeviceCodeType		
Code List	AUDIO CAPTURE DEVICE CODE				
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:SegmentChannelInformation	Cardinality	0..600000		
XML Level 2	biom:AudioCaptureDeviceCode	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.038_3

Vocal Segment Channel

Microphone Type Code

Mnemonic	MTC			Conditionality	O↑
				Status	New Active
Description	A code specifying the transducer type. Transducer arrays using mixed transducer types shall be designated "other".				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	MTC = 0 , 1, 2, 3 or 4		
Code List	TRANSDUCER PRINCIPLE CODE				
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:SegmentChannelInformation	Cardinality	0..600000		
XML Level 2	biom:TransducerPrincipleCode	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.038_4

Vocal Segment Channel

Capture Environment Description Text

Mnemonic	ENV			Conditionality	O↑	
				Status	New Active	
Description	Describes the acoustic environment of the recording.					
Field Min	1	Occur Min	0			
Field Max	Unlimited	Occur Max	1			
Char Types	U	Special Chars	None			
Format	n/a	Constraints				
Code List						
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)					
XML Level 1	biom:SegmentChannelInformation			Cardinality	0..600000	
XML Level 2	biom:AudioCaptureEnvironmentText			Cardinality	0..1	
XML Level 3				Cardinality		
XML Level 4				Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0 Yes

11.038_5

Vocal Segment Channel

Transducer Distance

Mnemonic	DST			Conditionality	O↑	
				Status	New Active	
Description	Specifies the approximate distance in centimeters, rounded to the nearest integer number of centimeters, between the speaker in the identified segments and the transducer. A value of 0 will be used if the distance is less than one-centimeter.					
Field Min	1	Occur Min	0			
Field Max	5	Occur Max	1			
Char Types	N	Special Chars	integer			
Format	n/a	Constraints	0 <= DST <= 99999			
Code List						
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)					
XML Level 1	biom:SegmentChannelInformation			Cardinality	0..600000	
XML Level 2	biom:TransducerDistanceValue			Cardinality	0..1	
XML Level 3				Cardinality		
XML Level 4				Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0 Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-11: Forensic and Investigatory Voice Data

Page 668 of 1037

11.038_6

Vocal Segment Channel

Acquisition Source Code

Mnemonic	AQC			Conditionality	0↑		
				Status	New Active		
Description	Specifies the source from which the voice in the identified segments was received.						
Field Min	1		Occur Min	0			
Field Max	2		Occur Max	1			
Char Types	N		Special Chars	None			
Format	n/a		Constraints				
Code List	ACQUISITION SOURCE CODE						
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)						
XML Level 1	biom:SegmentChannelInformation			Cardinality	0..600000		
XML Level 2	biom:AcquisitionSourceCode			Cardinality	0..1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

11.038_7

Vocal Segment Channel

Voice Modification Description Text

Mnemonic	VMT			Conditionality	0↑		
				Status	New Active		
Description	Unrestricted string for a description of any digital masking between transducer and recording, disguisers or other attempts to change the voice quality.						
Field Min	1		Occur Min	0			
Field Max	Unlimited		Occur Max	1			
Char Types	U		Special Chars	None			
Format	n/a		Constraints				
Code List							
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)						
XML Level 1	biom:SegmentChannelInformation			Cardinality	0..600000		
XML Level 2	biom:TransductionAlterationDescriptionText			Cardinality	0..1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.038_8

Vocal Segment Channel

Comments

Mnemonic	COM			Conditionality	O↑
				Status	New Active
Description	Unrestricted string for additional information to identify or describe the transduction and transmission channels of the identified segments.				
Field Min	1	Occur Min	0		
Field Max	Unlimited	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:SegmentChannelInformation	Cardinality	0..600000		
XML Level 2	biom:ChannelCommentText	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.051

Comments

Mnemonic	COM			Conditionality	O↑
				Status	New Active
Description	Unrestricted text string that may contain comments of any type on the Type 11 record as a whole.				
Field Min	1	Occur Min	0		
Field Max	Unlimited	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:AudioCommentText	Cardinality	0..1		
XML Level 2		Cardinality			
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.902

Annotation Information

Mnemonic	ANN			Conditionality	O
				Status	New Active
Description	Listing the operations performed on the original source in order to prepare it for inclusion in a biometric record type. Repeating sets of information items M↑				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:ProcessAnnotation			Cardinality	0..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.902_0

Annotated Information

Subfields: Repeating Sets Of Information Items

Mnemonic	ANN_0			Conditionality	D
				Status	New Active
Description	Listing the operations performed on the original source in order to prepare it for inclusion in a biometric record type. Repeating sets of information items M↑				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	*	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013				
XML Level 1	biom:ProcessAnnotation			Cardinality	0..*
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-11: Forensic and Investigatory Voice Data

Page 671 of 1037

11.902_1

Annotation Information

Greenwich Mean Time

Mnemonic	GMT			Conditionality	M↑
				Status	New Active
Description	The Greenwich Mean Time (coordinated universal time – UTC) / GMT of when the processing occurred.				
Field Min	dependent on encoding	Occur Min	1		
Field Max	dependent on encoding	Occur Max	1		
Char Types	encoding specific	Special Chars	None		
Format	encoding specific	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013				
XML Level 1	biom:ProcessAnnotation	Cardinality	0..*		
XML Level 2	biom:ProcessUTCDate/nc:DateTime	Cardinality	1..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.902_2

Annotation Information

Processing Algorithm Name / Version

Mnemonic	NAV			Conditionality	M↑
				Status	New Active
Description	Field that contains the identifying the name and version of the processing algorithm / application / process or workstation.				
Field Min	1	Occur Min	1		
Field Max	Unlimited	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013				
XML Level 1	biom:ProcessAnnotation	Cardinality	0..*		
XML Level 2	biom:ProcessName	Cardinality	1..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.902_3

Annotation Information

Algorithm Owner

Mnemonic	OWN			Conditionality	M↑
				Status	New Active
Description	The organization that developed / maintains the processing algorithm / application or latent workstation.				
Field Min	1	Occur Min	1		
Field Max	64	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013				
XML Level 1	biom:ProcessAnnotation			Cardinality	0..*
XML Level 2	biom:ProcessOwnerText			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.902_4

Annotation Information

Process Description

Mnemonic	PRO			Conditionality	M↑
				Status	New Active
Description	Describes the process or procedure applied.				
Field Min	1	Occur Min	1		
Field Max	Unlimited	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013				
XML Level 1	biom:ProcessAnnotation			Cardinality	0..*
XML Level 2	biom:ProcessDescriptionText			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-11: Forensic and Investigatory Voice Data

Page 673 of 1037

11.993

Source Agency Name

Mnemonic	SAN		Conditionality	0	
			Status	New Active	
Description	The name of the agency referred to in Field 11.004: Source agency / SRC.				
Field Min	1		Occur Min	0	
Field Max	125		Occur Max	1	
Char Types	U		Special Chars	None	
Format	n/a		Constraints		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:CaptureOrganization		Cardinality	1..1	
XML Level 2	nc:OrganizationName		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.994

External Reference File

Mnemonic	EFR		Conditionality	D	
			Status	New Active	
Description	Lists the organization that developed / maintains the processing algorithm / application or latent workstation.				
Field Min	1		Occur Min	0	
Field Max	200		Occur Max	1	
Char Types	U		Special Chars	None	
Format	n/a		Constraints		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:SourceExternalAnalogFileReferenceText or biom:SourceExternalDigitalAudioReferenceText o rbiom:SourceExternalDigitalVideoReferenceText or biom:SourceExternalFileReferenceText		Cardinality	0..1	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.995

Associated Context

Mnemonic	ASC		Conditionality	O	
			Status	New Active	
Description	Describes a process or procedure applied to the sample. Refers to one or more Records Type-21 instances with the same ACN. Repeating M↑ subsets 1 to 255.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	255	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:AssociatedContext		Cardinality	0..255	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.995_0

Associated Context

Subfields: Repeating Sets Of Information Items

Mnemonic	ASC_0		Conditionality	M↑	
			Status	New Active	
Description	Describes a process or procedure applied to the sample. Refers to one or more Records Type-21 instances with the same ACN. Repeating M↑ subsets 1 to 255.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	255	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:AssociatedContext		Cardinality	0..255	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.995_1

Associated Context

Associated Context Number

Mnemonic	ACN			Conditionality	M↑
				Status	New Active
Description	Contains the associated context number / ACN for a particular Record Type-21. Mandatory for each Field xx.995, when the field is used.				
Field Min	1	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	1 <= ACN <= 255; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:AssociatedContext			Cardinality	0..255
XML Level 2	biom:ContextIdentification/nc:IdentificationID			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.995_2

Associated Context

Associated Segment Position

Mnemonic	ASP			Conditionality	O↑
				Status	New Active
Description	Contains the index to a particular set of segmentation coordinates of the associated context data. This same segmentation index value appears in Record Type-21 as the associated segment position / ASP in Field 21.016: Segments / SEG.				
Field Min	1	Occur Min	0		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	n/a		
Format	n/a	Constraints	1 <= ASP <= 99; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:AssociatedContext			Cardinality	0..255
XML Level 2	biom:ImageSegmentIdentification/nc:IdentificationID			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.996

Hash

Mnemonic	HAS			Conditionality	0
				Status	New Active
Description	Applies to all digital audio records, whether stored in Field 11.999: Voice record data / DATA or reference to an external storage location in Field 11.994: External file reference / EFR and shall contain the hash value of the data, calculated using SHA-256. Enables the receiver of the digital data to check that the data has been transmitted correctly, and may also be used for quick searches of large databases to determine if the data already exists in the database.				
Field Min	64	Occur Min	0		
Field Max	64	Occur Max	1		
Char Types	H	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:DigitalAudioRecordHashValue			Cardinality	0..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

11.997

Source Representation

Mnemonic	SOR			Conditionality	0
				Status	New Active
Description	This optional field refers to a representation in Record Type-20 with the same SRN from which the data in Field 13.999: Latent friction ridge image / DATA was derived.				
Field Min	64	Occur Min	0		
Field Max	64	Occur Max	255		
Char Types	H	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)				
XML Level 1	biom:SourceRepresentation			Cardinality	0..255
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

11.997_1

Source Representation

Source Representation Number

Mnemonic	SRN	Conditionality	M↑
		Status	New Active
Description	Contains a reference number for the source representation stored in this record. Repeating M↑ subsets 1 to 255.		
Field Min	1	Occur Min	1
Field Max	3	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	1 <= SRN <= 255, positive integer
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	biom:SourceRepresentation	Cardinality	0..255
XML Level 2	biom:SourceIdentification/nc:IdentificationID	Cardinality	1..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

11.999

Data

Voice Data

Mnemonic	DATA	Conditionality	D
		Status	New Active
Description	If this field is used, Field 11.994: External file reference / EFR shall not be set. One of the two fields shall be present in this record unless Field 11.003: Audio object descriptor code /AOD has a value of 5. Field xx.999 is reserved in Record Types 10 and above for data associated with the record that is described in the other fields of the record. It does not appear in Type-18 or Type-98.		
Field Min	1	Occur Min	0
Field Max	Unlimited	Occur Max	1
Char Types	Base64	Special Chars	
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 1-2011: Update 2013 (Type-11)		
XML Level 1	nc:Base64BinaryObject	Cardinality	0..1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

13.001

Record Header

Mnemonic	LEN	Conditionality	M
		Status	Active
Description	The record header appears as the first field (xx.001) in each Record Type. It contains information particular to the encoding format chosen, in order to enable proper reading of the record. In Traditional encoding, this field contains the record length in bytes (including all information separators). In NIEM-conformant XML encoding, this field contains the RecordCategoryCode, which is the numeric representation of the Record Type.		
Field Min	T = 4; X = 1	Occur Min	1
Field Max	T = 8; X = 2	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	positive integer
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-13)		
XML Level 1	nist-itl:RecordCategoryCode	Cardinality	1...1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

13.002

Information Designation Character

Mnemonic	IDC	Conditionality	M
		Status	Active
Description	Each of the records present in a transaction, with the exception of the Type-1 record, shall include a field (xx.002) containing the information designation character / IDC. The value of the IDC shall be a sequentially assigned positive integer starting from zero and incremented by one up to a maximum of 99. IDC references are stated in Type-1 Field 1.003 Transaction content (CNT) and shall be used to relate information items in the CNT field of the Type-1 record to the other records in the transaction. Two or more records may share a single IDC solely to identify and link together records that pertain to different representations of the same biometric trait.		
Field Min	1	Occur Min	1
Field Max	2	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	0 <= IDC <= 99; integer
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-13)		
XML Level 1	nist-itl:ImageReferenceIdentification/nc:IdentificationID	Cardinality	1...1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-13: Variable-Resolution Latent Friction Ridge Image

Page 679 of 1037

13.003

Impression Type

Mnemonic	IMP		Conditionality	M
			Status	Active
Description	This mandatory field shall indicate the manner by which the friction ridge print was obtained.			
Field Min	1	Occur Min	1	
Field Max	2	Occur Max	1	
Char Types	N	Special Chars	None	
Format	n/a	Constraints	see Look Up Codes	
Code List	FRICTION RIDGE IMPRESSION CODES			
Source	ANSI/NIST ITL 1-2013 (Type-13)			
XML Level 1	biom:FingerImpressionImage or biom:PalmpPrintImage or biom:PlantarImage or biom:FrictionRidgeImage		Cardinality	1..1
XML Level 2	biom_2:MinutiaeImpressionCaptureCategoryCode		Cardinality	1..1
XML Level 3			Cardinality	
XML Level 4			Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0
			Yes	DoD EBTS 4.0
				Yes

13.004

Source Agency

Mnemonic	SRC		Conditionality	M
			Status	Active
Description	This is the identifier of the agency that actually created the record and supplied the information contained in it.			
Field Min	1	Occur Min	1	
Field Max	*	Occur Max	1	
Char Types	U	Special Chars	None	
Format	n/a	Constraints	None	
Code List				
Source	ANSI/NIST ITL 1-2013 (Type-13)			
XML Level 1	biom:FingerImpressionImage or biom:PalmpPrintImage or biom:PlantarImage or biom:FrictionRidgeImage		Cardinality	1..1
XML Level 2	biom_2:CaptureOrganization		Cardinality	1..1
XML Level 3	nc:OrganizationIdentification/nc:IdentificationID		Cardinality	1..1
XML Level 4			Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0
			Yes	DoD EBTS 4.0
				Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

13.005

Latent Capture Date

Mnemonic	LCD			Conditionality	M
				Status	Active
Description	This mandatory field shall contain the date that the latent biometric data contained in the record was captured.				
Field Min	Dependent upon encoding		Occur Min	1	
Field Max	Dependent upon encoding		Occur Max	1	
Char Types	N		Special Chars	None	
Format	T = YYYYMMDD; X = <CaptureDate>		Constraints	Dependent upon encoding.	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom:FingerImpressionImage or biom:PalmprintImage or biom:PlantarImage or biom:FrictionRidgeImage			Cardinality	1..1
XML Level 2	biom_2:CaptureDate/nc:Date			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

13.006

Horizontal Line Length

Mnemonic	HLL			Conditionality	M
				Status	Active
Description	HLL defines the number of pixels contained on a single horizontal line of the image. The maximum horizontal size is limited to 65,535 pixels in Record Types-4 and 8, and to 99,999 for other record types. The minimum value is 10 pixels.				
Field Min	2		Occur Min	1	
Field Max	5		Occur Max	1	
Char Types	N		Special Chars	None	
Format	n/a		Constraints	10 <= HLL <= 99999; positive integer	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom:FingerImpressionImage or biom:PalmprintImage or biom:PlantarImage or biom:FrictionRidgeImage			Cardinality	1..1
XML Level 2	biom_2:ImageHorizontalLineLengthPixelQuantity			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

13.007

Vertical Line Length

Mnemonic	VLL	Conditionality	M
		Status	Active
Description	VLL defines the number of horizontal lines contained in the image. The maximum vertical size is limited to 65,535 pixels in Record Types-4 and 8, and to 99,999 for other record types. The minimum value is 10 pixels.		
Field Min	2	Occur Min	1
Field Max	5	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	10 <= VLL <= 99999; positive integer
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-13)		
XML Level 1	biom:FingerImpressionImage or biom:PalmpPrintImage or biom:PlantarImage or biom:FrictionRidgeImage	Cardinality	1..1
XML Level 2	biom_2:ImageVerticalLineLengthPixelQuantity	Cardinality	1..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

13.008

Scale Units

Mnemonic	SLC	Conditionality	M
		Status	Active
Description	The image sampling frequency (pixel density). A value of "1" shall indicate pixels per inch. A value of "2" shall indicate pixels per centimeter. A value of "0" in this field indicates that no scale is provided, and the quotient of THPS/TVPS shall provide the pixel aspect ratio.		
Field Min	1	Occur Min	1
Field Max	1	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	SLC = 0, 1 or 2
Code List	SCALE UNIT CODES		
Source	ANSI/NIST ITL 1-2013 (Type-13)		
XML Level 1	biom:FingerImpressionImage or biom:PalmpPrintImage or biom:PlantarImage or biom:FrictionRidgeImage	Cardinality	1..1
XML Level 2	biom_2:ImageScaleUnitsCode	Cardinality	1..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

13.009

Transmitted Horizontal Pixel Scale

Mnemonic	THPS			Conditionality	M
				Status	Active
Description	This is the integer pixel density used in the horizontal direction of the image if SLC has a value of "1" or "2". If SLC has a value of "0", this information item shall contain the horizontal component of the pixel aspect ratio, up to 5 integer digits. For example, if the SLC value = 1, then the value of THPS could be '1000' for a 1000 ppi sensor.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom:FingerImpressionImage or biom:PalmpPrintImage or biom:PlantarImage or biom:FrictionRidgeImage			Cardinality	1..1
XML Level 2	biom_2:ImageHorizontalPixelDensityValue			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

13.01

Transmitted Vertical Pixel Scale

Mnemonic	TVPS			Conditionality	M
				Status	Active
Description	This is the integer pixel density used in the vertical direction of the image if SLC has a value of "1" or "2". If SLC has a value of "0", this information item shall contain the vertical component of the pixel aspect ratio, up to 5 integer digits. If SLC is 1 or 2, then TVPS shall equal THPS.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom:FingerImpressionImage or biom:PalmpPrintImage or biom:PlantarImage or biom:FrictionRidgeImage			Cardinality	1..1
XML Level 2	biom_2:ImageVerticalPixelDensityValue			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

13.011

Compression Algorithm

Mnemonic	CGA		Conditionality	M
			Status	Active
Description	This is a mandatory field. It shall specify the algorithm used to compress the transmitted color or grayscale images.			
Field Min	3	Occur Min	1	
Field Max	5	Occur Max	1	
Char Types	AN	Special Chars	None	
Format	n/a	Constraints	see Look Up Codes	
Code List	COMPRESSION CODES			
Source	ANSI/NIST ITL 1-2013 (Type-13)			
XML Level 1	biom:FingerImpressionImage or biom:PalmprintImage or biom:PlantarImage or biom:FrictionRidgeImage		Cardinality	1..1
XML Level 2	biom_2:ImageCompressionAlgorithmText		Cardinality	1..1
XML Level 3			Cardinality	
XML Level 4			Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0
			Yes	DoD EBTS 4.0
				Yes

13.012

Bits Per Pixel

Mnemonic	BPX		Conditionality	M
			Status	Active
Description	This ASCII field shall contain the number of bits used to represent a pixel. This field shall contain an entry of "8" for normal grayscale values of "0" to "255" or each RGB color component. Any entry in this field greater than "8" shall represent a grayscale or color pixel component with increased precision.			
Field Min	1	Occur Min	1	
Field Max	2	Occur Max	1	
Char Types	N	Special Chars	None	
Format	n/a	Constraints	positive integer	
Code List				
Source	ANSI/NIST ITL 1-2013 (Type-13)			
XML Level 1	biom:FingerImpressionImage or biom:PalmprintImage or biom:PlantarImage or biom:FrictionRidgeImage		Cardinality	1..1
XML Level 2	biom_2:ImageBitsPerPixelQuantity		Cardinality	1..1
XML Level 3			Cardinality	
XML Level 4			Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0
			Yes	DoD EBTS 4.0
				Yes

13.013

Friction Ridge Generalized Position

Mnemonic	FGP		Conditionality	M
			Status	Active
Description	This field is mandatory. Each subfield shall contain one possible finger, palm or plantar position that may match the latent image, up to a maximum of 6 possibilities. The code "0" shall be used to reference every finger position from 1 to 10, 16 and 17. The code "20" for "Unknown palm" shall be used to reference every listed palm print position. The code "60" for "Unknown sole" shall be used for every listed plantar position. Code "18" shall be used if it is unknown whether the print is from a hand or foot. Code "19" shall be used for a latent image that includes substantive portion of the medial or proximal segments of a finger, or the extreme tip of a fingerprint. If code 19 is used, fields 13.014 and 13.015 shall be used. See Look Up Codes for valid entries.			
Field Min	n/a	Occur Min	0	
Field Max	n/a	Occur Max	1	
Char Types	N	Special Chars	None	
Format	n/a	Constraints	see Look Up Codes	
Code List	FRICTION RIDGE GENERALIZED POSITION CODES			
Source	ANSI/NIST ITL 1-2013 (Type-13)			
XML Level 1	biom:FingerImpressionImage or biom:PalmprintImage or biom:PlantarImage or biom:FrictionRidgeImage		Cardinality	1..1
XML Level 2	biom_2:FingerPositionCode or biom_2:PalmPositionCode or biom_2:PlantarPositionCode or biom_2:FrictionRidgePositionCode		Cardinality	0..1
XML Level 3			Cardinality	
XML Level 4			Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0
			Yes	DoD EBTS 4.0
				Yes

13.013_0

Friction Ridge Generalized Position

Subfield: Repeating Sets Of Information Items

Mnemonic	FGP_0		Conditionality	M↑
			Status	New Active
Description	This field is mandatory. Each subfield shall contain one possible finger, palm or plantar position that may match the latent image, up to a maximum of 6 possibilities. The code "0" shall be used to reference every finger position from 1 to 10, 16 and 17. The code "20" for "Unknown palm" shall be used to reference every listed palm print position. The code "60" for "Unknown sole" shall be used for every listed plantar position. Code "18" shall be used if it is unknown whether the print is from a hand or foot. Code "19" shall be used for a latent image that includes substantive portion of the medial or proximal segments of a finger, or the extreme tip of a fingerprint. If code 19 is used, fields 13.014 and 13.015 shall be used. See Look Up Codes for valid entries.			
Field Min	1	Occur Min	1	
Field Max	2	Occur Max	6	
Char Types	N	Special Chars	None	
Format	n/a	Constraints	see Look Up Codes	
Code List	FRICTION RIDGE GENERALIZED POSITION CODES			
Source	ANSI/NIST ITL 1-2013 (Type-13)			
XML Level 1	biom:FingerImpressionImage or biom:PalmprintImage or biom:PlantarImage or biom:FrictionRidgeImage		Cardinality	1..1
XML Level 2	biom_2:FingerPositionCode or biom_2:PalmPositionCode or biom_2:PlantarPositionCode or biom_2:FrictionRidgePositionCode		Cardinality	1..6
XML Level 3			Cardinality	
XML Level 4			Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0
			Yes	DoD EBTS 4.0
				Yes

13.014

Search Position Descriptors

Mnemonic	SPD		Conditionality	D
			Status	Active
Description	Shall be present if and only if the finger position code "19" appears in Field 13.013. It is used to narrow the search of the latent image in this record against a database. The lack of an XML element is a structural anomaly. There is no element to represent the Field 13.014, and instead each information item repeats. This anomaly is retained for backward compatibility purposes.			
Field Min	n/a	Occur Min	0	
Field Max	n/a	Occur Max	1	
Char Types	n/a	Special Chars	n/a	
Format	n/a	Constraints	n/a	
Code List				
Source	ANSI/NIST ITL 1-2013 (Type-13)			
XML Level 1	biom:FingerImpressionImage or biom:FrictionRidgeImage		Cardinality	1..1
XML Level 2	biom:FingerprintImageMajorCasePrint		Cardinality	0..1
XML Level 3			Cardinality	
XML Level 4			Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0 Yes DoD EBTS 4.0 Yes

13.014_0

Search Position Descriptors

Subfield: Repeating Sets Of Information Items

Mnemonic	SPD_0		Conditionality	M↑
			Status	New Active
Description	Shall be present if and only if the finger position code "19" appears in Field 13.013. It is used to narrow the search of the latent image in this record against a database. The lack of an XML element is a structural anomaly. There is no element to represent the Field 13.014, and instead each information item repeats. This anomaly is retained for backward compatibility purposes.			
Field Min	n/a	Occur Min	1	
Field Max	n/a	Occur Max	1	
Char Types	n/a	Special Chars	n/a	
Format	n/a	Constraints	n/a	
Code List				
Source	ANSI/NIST ITL 1-2013 (Type-13)			
XML Level 1	biom:FingerImpressionImage/biom_2:FingerprintImageMajorCasePrint		Cardinality	1..1
XML Level 2			Cardinality	
XML Level 3			Cardinality	
XML Level 4			Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0 Yes DoD EBTS 4.0 Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-13: Variable-Resolution Latent Friction Ridge Image

Page 686 of 1037

13.014_1

Search Position Descriptors

Probable Decimal Finger Position Code

Mnemonic	PDF	Conditionality	M↑
		Status	Active
Description	The first information item is the probable decimal finger position code (PDF) taken from the Look Up Codes, with integers 0 through 10, 16 or 17 allowed.		
Field Min	1	Occur Min	0
Field Max	2	Occur Max	9
Char Types	N	Special Chars	None
Format	n/a	Constraints	0 <= PDF <= 10, or PDF = 16 or 17
Code List	FRICTION RIDGE GENERALIZED POSITION CODES		
Source	ANSI/NIST ITL 1-2013 (Type-13)		
XML Level 1	biom:FingerImpressionImage/biom_2:FingerprintImageMajorCasePrint	Cardinality	1..1
XML Level 2	biom_2:FingerPositionCode	Cardinality	0..9
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

13.014_2

Search Position Descriptors

Finger Image Code

Mnemonic	FIC	Conditionality	M↑
		Status	Active
Description	The second information item is finger image code(FIC). Latent images of full length fingers use codes FV1 through FV4. Other allowable codes are EJI, TIP, PRX, DST and MED. See Look Up Codes for valid entries.		
Field Min	3	Occur Min	0
Field Max	3	Occur Max	9
Char Types	AN	Special Chars	None
Format	n/a	Constraints	FIC = EJI, TIP, FV1, FV2, FV3, FV4, PRX, DST or MED
Code List	PRINT POSITION DESCRIPTORS		
Source	ANSI/NIST ITL 1-2013 (Type-13)		
XML Level 1	biom:FingerImpressionImage/biom_2:FingerprintImageMajorCasePrint	Cardinality	1..1
XML Level 2	biom_2:MajorCasePrintCode	Cardinality	0..9
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

13.015

Print Position Coordinates

Mnemonic	PPC		Conditionality	D			
			Status	Active			
Description	This field may be present if and only if the finger position code "19" appears in Field 13.013: Friction ridge generalized position (FGP). It is an optional field. Individual full finger or segment definitions may be entered as separate subfields. For the case of a fingertip, the first information item shall be "TIP", and the second information item shall be "NA". When used, this field shall consist of six (6) mandatory information items describing the type or portion of the image contained in this record and its location within an EJI. This information will describe either the location of the entire joint image, one full finger view, or segment. Individual full finger or segment definitions may be repeated as repeating sets of information items.						
Field Min	n/a	Occur Min	0				
Field Max	n/a	Occur Max	1				
Char Types	n/a	Special Chars	n/a				
Format	n/a	Constraints	n/a				
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-13)						
XML Level 1	biom:FingerImpressionImage/biom_2:FingerprintImageMajorCasePrint	Cardinality	1..1				
XML Level 2	biom_2:MajorCasePrintSegmentOffset	Cardinality	0..1				
XML Level 3		Cardinality					
XML Level 4		Cardinality					
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

13.015_0

Subfield: Repeating Sets Of Information Items

Mnemonic	PPC_0		Conditionality	M↑			
			Status	New Active			
Description	This field may be present if and only if the finger position code "19" appears in Field 13.013: Friction ridge generalized position (FGP). It is an optional field. Individual full finger or segment definitions may be entered as separate subfields. For the case of a fingertip, the first information item shall be "TIP", and the second information item shall be "NA". When used, this field shall consist of six (6) mandatory information items describing the type or portion of the image contained in this record and its location within an EJI. This information will describe either the location of the entire joint image, one full finger view, or segment. Individual full finger or segment definitions may be repeated as repeating sets of information items.						
Field Min	n/a	Occur Min	0				
Field Max	n/a	Occur Max	12				
Char Types	n/a	Special Chars	n/a				
Format	n/a	Constraints	n/a				
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-13)						
XML Level 1	biom:FingerImpressionImage/biom_2:FingerprintImageMajorCasePrint	Cardinality	1..1				
XML Level 2	biom_2:MajorCasePrintSegmentOffset	Cardinality	0..12				
XML Level 3		Cardinality					
XML Level 4		Cardinality					
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

13.015_1

Print Position Coordinates

Full Finger View

Mnemonic	FVC	Conditionality	M↑
		Status	Active
Description	The first information item is the full finger view / FVC with values of "FV1" through "FV4". Values of "FV1" to "FV4" specify the perspective for each full finger view. For a fingertip, the first information item shall be "TIP". FVC will contain the code "NA" if only a proximal, distal, or medial segment is available.		
Field Min	2	Occur Min	1
Field Max	3	Occur Max	1
Char Types	AN	Special Chars	None
Format	n/a	Constraints	FVC = NA, TIP, FV1, FV2, FV3 or FV4; see Look Up Codes
Code List	PRINT POSITION DESCRIPTORS		
Source	ANSI/NIST ITL 1-2013 (Type-13)		
XML Level 1	biom:FingerImpressionImage/biom_2:FingerprintImageMajorCasePrint	Cardinality	1..1
XML Level 2	biom_2:MajorCasePrintSegmentOffset	Cardinality	0..12
XML Level 3	biom_2:SegmentFingerViewCode	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

13.015_2

Print Position Coordinates

Location of Segment

Mnemonic	LOS	Conditionality	M↑
		Status	Active
Description	The second information item is used to identify the location of a segment (LOS) within a full finger view. LOS will contain the not applicable code "NA" if the image portion refers to a full finger view, tip or to the entire joint image locations. Otherwise, it shall contain "PRX", "DST", "MED" for a proximal, distal, or medial segment, respectively		
Field Min	2	Occur Min	1
Field Max	3	Occur Max	1
Char Types	AN	Special Chars	None
Format	n/a	Constraints	LOS = NA, PRX, DST or MED; see Look Up Codes
Code List	PRINT POSITION DESCRIPTORS		
Source	ANSI/NIST ITL 1-2013 (Type-13)		
XML Level 1	biom:FingerImpressionImage/biom_2:FingerprintImageMajorCasePrint	Cardinality	1..1
XML Level 2	biom_2:MajorCasePrintSegmentOffset	Cardinality	0..12
XML Level 3	biom_2:SegmentLocationCode	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

13.015_3

Print Position Coordinates

Left Horizontal Coordinate

Mnemonic	LHC			Conditionality	M↑
				Status	Active
Description	This information item is the horizontal offset in pixels to the left edge of the bounding box relative to the origin positioned in the upper left corner of the image.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	1 <= LHC <= HLL; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom:FingerImpressionImage/biom_2:FingerprintImageMajorCasePrint	Cardinality	1..1		
XML Level 2	biom_2:MajorCasePrintSegmentOffset	Cardinality	0..12		
XML Level 3	biom_2:SegmentLeftHorizontalCoordinateValue	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

13.015_4

Print Position Coordinates

Right Horizontal Coordinate

Mnemonic	RHC			Conditionality	M↑
				Status	Active
Description	This information item is the horizontal offset in pixels to the right edge of the bounding box relative to the origin positioned in the upper left corner of the image.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	1 <= RHC <= HLL; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom:FingerImpressionImage/biom_2:FingerprintImageMajorCasePrint	Cardinality	1..1		
XML Level 2	biom_2:MajorCasePrintSegmentOffset	Cardinality	0..12		
XML Level 3	biom_2:SegmentRightHorizontalCoordinateValue	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-13: Variable-Resolution Latent Friction Ridge Image

Page 690 of 1037

13.015_5

Print Position Coordinates

Top Vertical Coordinate

Mnemonic	TVC			Conditionality	M↑
				Status	Active
Description	This information item is vertical offset (pixel counts down) to the top of the bounding box.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	1 <= TVC <= VLL; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom:FingerImpressionImage/biom_2:FingerprintImageMajorCasePrint	Cardinality	1..1		
XML Level 2	biom_2:MajorCasePrintSegmentOffset	Cardinality	0..12		
XML Level 3	biom_2:SegmentTopVerticalCoordinateValue	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

13.015_6

Print Position Coordinates

Bottom Vertical Coordinate

Mnemonic	BVC			Conditionality	M↑
				Status	Active
Description	This information item is the vertical offset from the upper left corner of the image down to the bottom of the bounding box. It is counted in pixels.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	1 <= BVC <= VLL; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom:FingerImpressionImage/biom_2:FingerprintImageMajorCasePrint	Cardinality	1..1		
XML Level 2	biom_2:MajorCasePrintSegmentOffset	Cardinality	0..12		
XML Level 3	biom_2:SegmentBottomVerticalCoordinateValue	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

13.016

Scanned Horizontal Pixel Scale

Mnemonic	SHPS		Conditionality	0	
			Status	Active	
Description	This ASCII field shall specify the horizontal pixel density used for scanning providing the SLC field contains a "1" or a "2". Otherwise, it indicates the horizontal component of the pixel aspect ratio.				
Field Min	1	Occur Min	0		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom:FingerImpressionImage/biom_1:ImageCaptureDetail or biom:PalmpointImage/biom_1:ImageCaptureDetail or biom:PlantarImage/biom_1:ImageCaptureDetail or biom:FrictionRidgeImage/biom_1:ImageCaptureDetail		Cardinality	1..1	
XML Level 2	biom_2:CaptureHorizontalPixelDensityValue		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

13.017

Scanned Vertical Pixel Scale

Mnemonic	SVPS		Conditionality	0	
			Status	Active	
Description	This ASCII field shall specify the vertical pixel density used for scanning providing the SLC field contains a "1" or a "2". Otherwise, it indicates the vertical component of the pixel aspect ratio.				
Field Min	1	Occur Min	0		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom:FingerImpressionImage/biom_1:ImageCaptureDetail or biom:PalmpointImage/biom_1:ImageCaptureDetail or biom:PlantarImage/biom_1:ImageCaptureDetail or biom:FrictionRidgeImage/biom_1:ImageCaptureDetail		Cardinality	1..1	
XML Level 2	biom_2:CaptureVerticalPixelDensityValue		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

13.018

Ruler or Scale Presence

Mnemonic	RSP			Conditionality	0
				Status	Active
Description	This optional field allows the user to state whether a ruler or other known scale is present in the image.				
Field Min	n/a			Occur Min	0
Field Max	n/a			Occur Max	1
Char Types	n/a			Special Chars	None
Format	n/a			Constraints	n/a
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom:FingerImpressionImage			Cardinality	1..1
XML Level 2	biom_2:RulerScalePresenceInformation or biom_2:StandardFingerprintFormNumberText			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

13.018_1

Ruler or Scale Presence

Ruler or Scale Units

Mnemonic	RSU			Conditionality	D
				Status	Active
Description	The first information item, ruler or scale units (RSU), indicates the units of measurement visible on the ruler or measurement scale				
Field Min	2			Occur Min	0
Field Max	4			Occur Max	1
Char Types	A			Special Chars	None
Format	n/a			Constraints	RSP = IN, MM, BOTH; See Look Up Codes
Code List	RULER OR SCALE UNIT CODES				
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom:FingerImpressionImage			Cardinality	1..1
XML Level 2	biom_2:RulerScalePresenceInformation or biom_2:StandardFingerprintFormNumberText			Cardinality	0..1
XML Level 3	biom_2:RulerScaleUnitCode			Cardinality	0..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

13.018_2

Ruler or Scale Presence

Ruler or Scale Make

Mnemonic	RSM	Conditionality	D
		Status	Active
Description	The second information item, ruler or scale make (RSM), lists the maker of the ruler or scale (if known).		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	None
Format	n/a	Constraints	None
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-13)		
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1
XML Level 2	biom_2:RulerScalePresenceInformation or biom_2:StandardFingerprintFormNumberText	Cardinality	0..1
XML Level 3	biom_2:RulerScaleMakeText	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

13.018_3

Ruler or Scale Presence

Ruler or Scale Model

Mnemonic	RSO	Conditionality	D
		Status	Active
Description	The third information item, ruler or scale model (RSO), lists the model of the ruler or scale (if known).		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	None
Format	n/a	Constraints	None
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-13)		
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1
XML Level 2	biom_2:RulerScalePresenceInformation or biom_2:StandardFingerprintFormNumberText	Cardinality	0..1
XML Level 3	biom_2:RulerScaleModelText	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

13.018_4

Ruler or Scale Presence

Standard Fingerprint Form Number

Mnemonic	RSF	Conditionality	D
		Status	Active
Description	The fourth information item, standard fingerprint form number (RSF) permits entry of a standard fingerprint form number such as FD-249, FD-258 or C-216C. If RSF is specified, none of the other three information items (RSU, RSM or RSO) shall be specified. Conversely, if any of those three information items is present, RSF shall not appear in this field.		
Field Min	1	Occur Min	0
Field Max	99	Occur Max	1
Char Types	U	Special Chars	None
Format	n/a	Constraints	None
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-13)		
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1
XML Level 2	biom_2:RulerScalePresenceInformation or biom_2:StandardFingerprintFormNumberText	Cardinality	0..1
XML Level 3	biom_2:StandardFingerprintFormNumber	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

13.019

Resolution Method

Mnemonic	REM	Conditionality	O
		Status	Active
Description	This optional field states the method used for determining the pixel density of the image. The second through the seventh information items are mandatory if MDR = RULER and are optional if MDR = FORM. They shall not be used for other values of MDR. When the known scale coordinates are used, the resolution can be calculated as the distance in pixels between points A and B divided by KSL. The pixel counts used in SXA, SYA, SXB, SYB are zero-based. The top left pixel has coordinates (0,0). If the transmitted pixel density of an image in Field 13.009: Transmitted horizontal pixel scale (THPS) and Field 13.010: Transmitted vertical pixel scale (TVPS) differs from the scanned (original) pixel density stated in Field 13.016: Scanned horizontal pixel scale (SHPS) and Field 13.017: Scanned vertical pixel scale (SVPS), then the values in this field are with respect to the scanned pixel density and shall not be recalculated to correspond to the transmitted pixel density.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	n/a
Format	n/a	Constraints	n/a
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-13)		
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1
XML Level 2	biom_2:ResolutionMethodInformation	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

13.019_1

Resolution Method

Means of Determining Resolution

Mnemonic	MDR			Conditionality	M↑
				Status	Active
Description	The first information item, means of determining resolution (MDR), specifies whether the resolution is calculated (from a ruler or known scale), estimated (by a human or computer), or is from a known source (such as a flatbed scanner or standard form).				
Field Min	1	Occur Min	0		
Field Max	9	Occur Max	1		
Char Types	AS	Special Chars	None		
Format	n/a	Constraints	MDR = FLATBED, FIXED, RULER, FORM, EST-HUMAN, EST-AUTO		
Code List	MEANS OF DETERMINING RESOLUTION CODES				
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1		
XML Level 2	biom_2:ResolutionMethodInformation	Cardinality	0..1		
XML Level 3	biom_2:ResolutionMeansCode	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

13.019_2

Resolution Method

Known Scale Length

Mnemonic	KSL			Conditionality	D
				Status	Active
Description	The second information item, known scale units (KSL), specifies the length of the known scale from point A to point B. It may contain a period.				
Field Min	1	Occur Min	0		
Field Max	6	Occur Max	1		
Char Types	NS	Special Chars	Period		
Format	n/a	Constraints	0.01 <= KSL <= 999.00; maximum of two digits to right of decimal		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1		
XML Level 2	biom_2:ResolutionMethodInformation	Cardinality	0..1		
XML Level 3	biom_2:ResolutionScaleLength	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

13.019_3

Resolution Method

Known Scale Units

Mnemonic	KSU			Conditionality	D
				Status	Active
Description	The third information item, known scale units (KSU) indicates whether the known scales units are in inches or millimeters.				
Field Min	2	Occur Min	0		
Field Max	2	Occur Max	1		
Char Types	A	Special Chars	None		
Format	n/a	Constraints	KSU = IN or MM		
Code List	RULER OR SCALE UNIT CODES				
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1		
XML Level 2	biom_2:ResolutionMethodInformation	Cardinality	0..1		
XML Level 3	biom_2:ResolutionScaleUnitCode	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

13.019_4

Resolution Method

Known Scale X Coordinate for Point A

Mnemonic	SXA			Conditionality	D
				Status	Active
Description	The fourth information item, known scale x coordinate for point A (SXA) is expressed in number of pixels from the left of the image.				
Field Min	1	Occur Min	0		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	Integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1		
XML Level 2	biom_2:ResolutionMethodInformation	Cardinality	0..1		
XML Level 3	biom_2:ResolutionScaleXCoordinateA	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-13: Variable-Resolution Latent Friction Ridge Image

Page 697 of 1037

13.019_5

Resolution Method

Known Scale Y Coordinate for Point A

Mnemonic	SYA			Conditionality	D
				Status	Active
Description	The fifth information item, known scale y coordinate for point A (SYA) is expressed in number of pixels from the top of the image.				
Field Min	1	Occur Min	0		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	Integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1		
XML Level 2	biom_2:ResolutionMethodInformation	Cardinality	0..1		
XML Level 3	biom_2:ResolutionScaleYCoordinateA	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

13.019_6

Resolution Method

Known Scale X Coordinate for Point B

Mnemonic	SXB			Conditionality	D
				Status	Active
Description	The sixth information item, known scale x coordinate for point B (SXB) is expressed in number of pixels from the left of the image.				
Field Min	1	Occur Min	0		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	Integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1		
XML Level 2	biom_2:ResolutionMethodInformation	Cardinality	0..1		
XML Level 3	biom_2:ResolutionScaleXCoordinateB	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-13: Variable-Resolution Latent Friction Ridge Image

Page 698 of 1037

13.019_7

Resolution Method

Known Scale Y Coordinate for Point B

Mnemonic	SYB			Conditionality	D
				Status	Active
Description	The seventh information item, known scale y coordinate for point B (SYB) is expressed in number of pixels from the top of the image.				
Field Min	1	Occur Min	0		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	Integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1		
XML Level 2	biom_2:ResolutionMethodInformation	Cardinality	0..1		
XML Level 3	biom_2:ResolutionScaleYCoordinateB	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

13.019_8

Resolution Method

Comment

Mnemonic	COM			Conditionality	O↑
				Status	Active
Description	The eighth information item, comment (COM), is a UNICODE text comment or description provided by the examiner about the resolution method.				
Field Min	1	Occur Min	0		
Field Max	99	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints	Integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1		
XML Level 2	biom_2:ResolutionMethodInformation	Cardinality	0..1		
XML Level 3	biom_2:ResolutionCommentText	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

13.02

Comment

Mnemonic	COM	Conditionality	0
		Status	Active
Description	The optional Comment field appears in many record types and may be used to insert free text information. It is not reserved exclusively for log-related information but has historically often been used for this purpose. It is limited to a maximum of 126 characters. This maximum size was established in order to maintain consistency across encodings. The maximum size differed in the 2007 and 2008 versions of the standard.		
Field Min	1	Occur Min	0
Field Max	126	Occur Max	1
Char Types	U	Special Chars	Any
Format	n/a	Constraints	None
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-13)		
XML Level 1	biom:FingerImpressionImage or biom:PalmpPrintImage or biom:PlantarImage or biom:FrictionRidgeImage	Cardinality	1..1
XML Level 2	biom_2:ImageCommentText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

13.024

Latent Quality Metric

Mnemonic	LQM	Conditionality	0
		Status	Active
Description	This optional field is used to specify one or more different metrics of latent image quality score data for the image stored in this record.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	n/a
Format	n/a	Constraints	n/a
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-13)		
XML Level 1	biom:FingerImpressionImage or biom:PalmpPrintImage or biom:PlantarImage or biom:FrictionRidgeImage	Cardinality	1..1
XML Level 2	biom_2:FingerprintImageQuality or biom_2:PalmpPrintImageQuality or biom_2:PlantarImageQuality or biom_2:FrictionRidgeImageQuality	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

13.024_0

Latent Quality Metric

Mnemonic	LQM_0		Conditionality	M↑	
			Status	New Active	
Description	This optional field is used to specify one or more different metrics of latent image quality score data for the image stored in this record.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	9	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom:FingerImpressionImage or biom:PalmpPrintImage or biom:PlantarImage or biom:FrictionRidgeImage		Cardinality	1..1	
XML Level 2	biom_2:FingerprintImageQuality or biom_2:PalmpPrintImageQuality or biom_2:PlantarImageQuality or biom_2:FrictionRidgeImageQuality		Cardinality	0..9	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

13.024_1

Latent Quality Metric

Friction Ridge Metric Position

Mnemonic	FRMP		Conditionality	M↑	
			Status	Active	
Description	The first information item is the entry in Field 13.013: Friction ridge generalized position (FGP). This information item is called the friction ridge metric position (FRMP) to differentiate it from FGP.				
Field Min	1		Occur Min	1	
Field Max	2		Occur Max	1	
Char Types	N		Special Chars	None	
Format	n/a		Constraints	see Look Up Codes	
Code List	FRICTION RIDGE GENERALIZED POSITION CODES				
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom:FingerImpressionImage or biom:PalmpPrintImage or biom:PlantarImage or biom:FrictionRidgeImage		Cardinality	1..1	
XML Level 2	biom_2:FingerprintImageQuality or biom_2:PalmpPrintImageQuality or biom_2:PlantarImageQuality or biom_2:FrictionRidgeImageQuality		Cardinality	0..9	
XML Level 3	biom_2:FingerPositionCode or biom_2:PalmPositionCode or biom_2:PlantarPositionCode or biom_2:FrictionRidgePositionCode		Cardinality	0..9	
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

13.024_2

Latent Quality Metric

Quality Value

Mnemonic	QVU		Conditionality	M↑
			Status	Active
Description	The first information item shall be a quantitative expression of the predicted matching performance of the biometric sample, which is a quality value (QVU). This information item shall contain the integer image quality score between 0 and 100 (inclusive) assigned to the image data by a quality algorithm. Higher values indicate better quality. An entry of "255" shall indicate a failed attempt to calculate a quality score. An entry of "254" shall indicate that no attempt to calculate a quality score was made.			
Field Min	1	Occur Min	1	
Field Max	3	Occur Max	1	
Char Types	N	Special Chars	None	
Format	n/a	Constraints	0 <= QVU <= 100 or QVU = 254 or 255; integer	
Code List				
Source	ANSI/NIST ITL 1-2013 (Type-13)			
XML Level 1	biom:FingerImpressionImage or biom:PalmpPrintImage or biom:PlantarImage or biom:FrictionRidgeImage		Cardinality	1..1
XML Level 2	biom_2:FingerprintImageQuality or biom_2:PalmpPrintImageQuality or biom_2:PlantarImageQuality or biom_2:FrictionRidgeImageQuality		Cardinality	0..9
XML Level 3	biom_2:QualityValue		Cardinality	1..1
XML Level 4			Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0 Yes DoD EBTS 4.0 Yes

13.024_3

Latent Quality Metric

Algorithm Vendor Identification

Mnemonic	QAV		Conditionality	M↑
			Status	Active
Description	The second information item shall specify the ID of the vendor of the quality algorithm used to calculate the quality score, which is an algorithm vendor identification (QAV). This 4-digit hex value is assigned by IBIA and expressed as four characters. The IBIA maintains the Vendor Registry of CBEFF Biometric Organizations that map the value in this field to a registered organization			
Field Min	4	Occur Min	1	
Field Max	4	Occur Max	1	
Char Types	H	Special Chars	None	
Format	n/a	Constraints	0000 <= QAV <= FFFF	
Code List				
Source	ANSI/NIST ITL 1-2013 (Type-13)			
XML Level 1	biom:FingerImpressionImage or biom:PalmpPrintImage or biom:PlantarImage or biom:FrictionRidgeImage		Cardinality	1..1
XML Level 2	biom_2:FingerprintImageQuality or biom_2:PalmpPrintImageQuality or biom_2:PlantarImageQuality or biom_2:FrictionRidgeImageQuality		Cardinality	0..9
XML Level 3	biom_2:QualityAlgorithmVendorIdentification/nc:IdentificationID		Cardinality	1..1
XML Level 4			Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0 Yes DoD EBTS 4.0 Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

13.024_4

Latent Quality Metric

Algorithm Product Identification

Mnemonic	QAP			Conditionality	M↑
				Status	Active
Description	The third information item shall specify a numeric product code assigned by the vendor of the quality algorithm, which may be registered with the IBIA, but registration is not required. This is the algorithm product identification (QAP) that indicates which of the vendor's algorithms was used in the calculation of the quality score. This information item contains the integer product code and should be within the range 1 to 65,535.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	1 <= QAP <= 65535; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom:FingerImpressionImage or biom:PalmpImage or biom:PlantarImage or biom:FrictionRidgeImage			Cardinality	1..1
XML Level 2	biom_2:FingerprintImageQuality or biom_2:PalmpImageQuality or biom_2:PlantarImageQuality or biom_2:FrictionRidgeImageQuality			Cardinality	0..9
XML Level 3	biom_2:QualityAlgorithmProductIdentification/nc:IdentificationID			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

13.046

Image Subject Condition

Mnemonic	SUB			Conditionality	O
				Status	Active
Description	This field is optional. This field is particularly useful if the image is obtained from a deceased person. However, its use is not limited to such circumstances. Some implementation domains support the submission of fingerprints taken from deceased individuals as latent prints, due to the quality of the friction ridges and the resulting images. In such cases, SSC is specified as D. For latent images taken from a surface, the value is typically X.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom:FingerImpressionImage or biom:PalmpImage or biom:PlantarImage or biom:FrictionRidgeImage			Cardinality	1..1
XML Level 2	biom_2:SubjectExistentialDetails			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-13: Variable-Resolution Latent Friction Ridge Image

Page 703 of 1037

13.046_1

Image Subject Condition

Subject Status Code

Mnemonic	SSC			Conditionality	M↑
				Status	Active
Description	The first information item is mandatory if this field is present. It is subject status code (SSC).				
Field Min	1	Occur Min	1		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars	None		
Format	n/a	Constraints	SSC = X, A, or D		
Code List	SUBJECT STATUS CODES				
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom:FingerImpressionImage or biom:PalmpPrintImage or biom:PlantarImage or biom:FrictionRidgeImage			Cardinality	1..1
XML Level 2	biom_2:SubjectExistentialDetails			Cardinality	0..1
XML Level 3	biom_2:SubjectExistentialStatusCode			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

13.046_2

Image Subject Condition

Subject Body Status Code

Mnemonic	SBSC			Conditionality	D
				Status	Active
Description	The second information item shall be entered if and only if SSC is D. It is subject body status code (SBSC). Its purpose is to indicate whether the information relates to an entire corpse or a separate body part.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	SBSC = 1 or 2		
Code List	SUBJECT BODY STATUS CODES				
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom:FingerImpressionImage or biom:PalmpPrintImage or biom:PlantarImage or biom:FrictionRidgeImage			Cardinality	1..1
XML Level 2	biom_2:SubjectExistentialDetails			Cardinality	0..1
XML Level 3	biom_2:SubjectBodyStatusCode			Cardinality	0..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

13.046_3

Image Subject Condition

Subject Body Class Code

Mnemonic	SBCC		Conditionality	D			
			Status	Active			
Description	The third information item shall be entered if and only if SSC is D. It is subject body class code (SBCC).						
Field Min	1	Occur Min	0				
Field Max	1	Occur Max	1				
Char Types	N	Special Chars	None				
Format	n/a	Constraints	SBCC = 1 or 2				
Code List	SUBJECT BODY CLASS CODES						
Source	ANSI/NIST ITL 1-2013 (Type-13)						
XML Level 1	biom:FingerImpressionImage or biom:PalmpPrintImage or biom:PlantarImage or biom:FrictionRidgeImage		Cardinality	1..1			
XML Level 2	biom_2:SubjectExistentialDetails		Cardinality	0..1			
XML Level 3	biom_2:SubjectBodyClassCode		Cardinality	0..1			
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

13.047

Capture Organization Name

Mnemonic	CON		Conditionality	O			
			Status	Active			
Description	This field is optional. Note that this can be different from the agency entered in Field 13.004: Source agency (SRC) and Field 13.993: Source agency name (SAN). SRC and SAN describe the agency that created the record. Since the record may have been forwarded by another agency to the final destination, Field 1.008: Originating agency identifier (ORI) is used to indicate the transmitting organization. In many implementation domains, there are a limited number of transmission organizations that can send data. Therefore, the agency listed in SRC may send the transaction to another location that has access rights to the final destination. This intermediary may add information to the transaction, as well. The final transmitting organization code is listed in Field 1.008: Originating agency identifier (ORI). Its name may be entered in Originating agency name (OAN) in Field 1.017: Agency names (ANM).						
Field Min	1	Occur Min	0				
Field Max	1000	Occur Max	1				
Char Types	U	Special Chars	None				
Format	n/a	Constraints	n/a				
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-13)						
XML Level 1	biom:FingerImpressionImage/biom1:ImageCaptureDetail or biom:PalmpPrintImage/biom1:ImageCaptureDetail or biom:PlantarImage/biom1:ImageCaptureDetail or biom:FrictionRidgeImage/biom1:ImageCaptureDetail		Cardinality	1..1			
XML Level 2	biom_2:CaptureOrganization		Cardinality	1..1			
XML Level 3	nc:OrganizationUnitName		Cardinality	0..1			
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

13.902

Annotated Information

Mnemonic	ANN		Conditionality	0	
			Status	Active	
Description	This is an optional field, listing the operations performed on the original source in order to prepare it for inclusion in a biometric record type.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom_2:ProcessAnnotation		Cardinality	0..1	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

13.902_0

Annotated Information

Subfield: Repeating Sets Of Information Items

Mnemonic	ANN_0		Conditionality	M↑	
			Status	New Active	
Description	This is an optional field, listing the operations performed on the original source in order to prepare it for inclusion in a biometric record type.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	*	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom_2:ProcessAnnotation		Cardinality	0..*	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-13: Variable-Resolution Latent Friction Ridge Image

Page 706 of 1037

13.902_1

Annotated Information

Greenwich Mean Time

Mnemonic	GMT			Conditionality	M↑
				Status	Active
Description	This information item is the Greenwich Mean Time (GMT) when the processing occurred. The data is formatted as YYYYMMDDhhmmssZ, where the Z indicates the zone description of 0 hours. This time is independent of the actual time zone where the time and date is recorded.				
Field Min	15	Occur Min	1		
Field Max	15	Occur Max	1		
Char Types	AN	Special Chars	None		
Format	YYYYMMDDHHMMSSZ - for Traditional Encoding	Constraints	Dependent upon encoding		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom_2:ProcessAnnotation	Cardinality	0..*		
XML Level 2	biom_2:ProcessUTCDate/nc:DateTime	Cardinality	1..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

13.902_2

Annotated Information

Processing Algorithm Name / Version

Mnemonic	NAV			Conditionality	M↑
				Status	Active
Description	This information item shall contain text identifying the name and version of the processing algorithm, application, procedure, or workstation				
Field Min	1	Occur Min	1		
Field Max	*	Occur Max	1		
Char Types	U	Special Chars	n/a		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom_2:ProcessAnnotation	Cardinality	0..*		
XML Level 2	biom_2:ProcessName	Cardinality	1..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

13.902_3

Annotated Information

Algorithm Owner

Mnemonic	OWN			Conditionality	M↑
				Status	Active
Description	This information item shall contain an unformatted text string of up to 64 characters with the contact information for the organization that owns the processing algorithm or latent workstation. Where there is no 'algorithm owner,' enter N/A.				
Field Min	1	Occur Min	1		
Field Max	64	Occur Max	1		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom_2:ProcessAnnotation			Cardinality	0..*
XML Level 2	biom_2:ProcessOwnerText			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

13.902_4

Annotated Information

Process Description

Mnemonic	PRO			Conditionality	M↑
				Status	Active
Description	This information item field shall contain text describing a process or procedure applied to the sample in this Type-9 record.				
Field Min	1	Occur Min	1		
Field Max	255	Occur Max	1		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom_2:ProcessAnnotation			Cardinality	0..*
XML Level 2	biom_2:ProcessDescriptionText			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

13.903

Device Unique Identifier

Mnemonic	DUI	Conditionality	0		
		Status	Active		
Description	The DUI shall contain a string uniquely identifying the device or source of the data. This field shall be one of the following: a Host PC MAC address (identified by the first character "M"), a Host PC processor ID (identified by the first character "P"). since it is available in the Make / Model / Serial Number field.				
Field Min	13	Occur Min	0		
Field Max	16	Occur Max	1		
Char Types	ANS	Special Chars	Any		
Format	n/a	Constraints	First character = M or P		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom_2:ProcessAnnotation	Cardinality	0..*		
XML Level 2	biom_2:CaptureDeviceIdentification/nc:IdentificationID	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

13.904

Make/Model/Serial Number

Mnemonic	MMS	Conditionality	0		
		Status	Active		
Description	The MMS contains the make, model and serial number for the capture device. It shall consist of three information items. Each information item shall be 1 to 50 characters. Unknown information may be indicated with the value "0." Any or all information items may indicate that information is unknown with the value "0".				
Field Min	n/a	Occur Min	1		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom:FingerImpressionImage/biom1:ImageCaptureDetail or biom:PalmpPrintImage/biom1:ImageCaptureDetail or biom:PlantarImag/biom1:ImageCaptureDetail e or biom:FrictionRidgeImage/biom1:ImageCaptureDetail	Cardinality	1..1		
XML Level 2		Cardinality			
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

13.904_1

Make/Model/Serial Number

Make

Mnemonic	MAK	Conditionality	M↑
		Status	Active
Description	The name of the manufacturer for the capture device.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	Any
Format	n/a	Constraints	"0" = Unknown
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-13)		
XML Level 1	biom:FingerImpressionImage/biom1:ImageCaptureDetail or biom:PalmpointImage/biom1:ImageCaptureDetail or biom:PlantarImag/biom1:ImageCaptureDetail e or biom:FrictionRidgeImage/biom1:ImageCaptureDetail	Cardinality	1..1
XML Level 2	biom_2:CaptureDeviceMakeText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

13.904_2

Make/Model/Serial Number

Model

Mnemonic	MOD	Conditionality	M↑
		Status	Active
Description	The model number for the capture device.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	Any
Format	n/a	Constraints	"0" = Unknown
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-13)		
XML Level 1	biom:FingerImpressionImage/biom1:ImageCaptureDetail or biom:PalmpointImage/biom1:ImageCaptureDetail or biom:PlantarImag/biom1:ImageCaptureDetail e or biom:FrictionRidgeImage/biom1:ImageCaptureDetail	Cardinality	1..1
XML Level 2	biom_2:CaptureDeviceModelText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

13.904_3

Make/Model/Serial Number

Serial Number

Mnemonic	SER	Conditionality	M↑
		Status	Active
Description	The serial number for the capture device.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	Any
Format	n/a	Constraints	"0" = Unknown
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-13)		
XML Level 1	biom:FingerImpressionImage/biom1:ImageCaptureDetail or biom:PalmpointImage/biom1:ImageCaptureDetail or biom:PlantarImag/biom1:ImageCaptureDetail e or biom:FrictionRidgeImage/biom1:ImageCaptureDetail	Cardinality	1..1
XML Level 2	biom_2:CaptureDeviceSerialNumberText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

13.993

Source Agency Name

Mnemonic	SAN	Conditionality	O
		Status	Active
Description	This is an optional field. It may contain up to 125 Unicode characters. It is the name of the agency referenced in Field xx.004: Source agency / SRC for record types 9-99.		
Field Min	1	Occur Min	0
Field Max	125	Occur Max	1
Char Types	U	Special Chars	Any
Format	n/a	Constraints	None
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-13)		
XML Level 1	biom:FingerImpressionImage/biom1:ImageCaptureDetail or biom:PalmpointImage/biom1:ImageCaptureDetail or biom:PlantarImag/biom1:ImageCaptureDetail e or biom:FrictionRidgeImage/biom1:ImageCaptureDetail	Cardinality	1..1
XML Level 2	biom_2:CaptureOrganization	Cardinality	1..1
XML Level 3	nc:OrganizationName	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

13.995

Associated Context

Mnemonic	ASC			Conditionality	0
				Status	Active
Description	This optional field refers to one or more Type 21 Records with the same ACN. Type 21 Records contain images that are NOT used to derive the biometric data in Field 13.999: Latent friction ridge image (DATA) but that may be relevant to the collection of that data, such as general scenes of the area where a latent print was found.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom_2:AssociatedContext			Cardinality	0..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

13.995_0

Associated Context

Mnemonic	ASC_0			Conditionality	M↑
				Status	New Active
Description	This optional field refers to one or more Type 21 Records with the same ACN. Type 21 Records contain images that are NOT used to derive the biometric data in Field 13.999: Latent friction ridge image (DATA) but that may be relevant to the collection of that data, such as general scenes of the area where a latent print was found.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	255		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom_2:AssociatedContext			Cardinality	0..255
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

13.995_1

Associated Context

Associated Context Number

Mnemonic	ACN			Conditionality	M↑
				Status	Active
Description	The first information item for the Associated Context field for a particular Record Type-21. This is mandatory for each Field xx.995, when the field is used. It contains an index to a particular instance of a Type-21 record in the transaction. This same index value appears in the appropriate instance of Record Type-21 as Field 21.021: Associated context number (CAN). The value of the CAN shall be a sequentially assigned a positive integer starting from one and incremented by one, not to exceed 255.				
Field Min	1	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	n/a	Special Chars	None		
Format	n/a	Constraints	1 <= ACN <= 255; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom_2:AssociatedContext	Cardinality	0..255		
XML Level 2	biom_2:ContextIdentification/nc:IdentificationID	Cardinality	1..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

13.995_2

Associated Context

Associated Segment Position

Mnemonic	ASP			Conditionality	O↑
				Status	Active
Description	The first information item is the associated segment position (ASP). This provides a unique index to a segmentation.				
Field Min	1	Occur Min	0		
Field Max	2	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	1 <= ASP <= 99; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom_2:AssociatedContext	Cardinality	0..255		
XML Level 2	biom_2:ImageSegmentIdentification/nc:IdentificationID	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

13.996

Hash

Mnemonic	HAS			Conditionality	0
				Status	Active
Description	Optional field xx.996, is designed for use in Record types 10 and above with a Field xx.999 storing the biometric data. It is comprised of 64 characters representing hexadecimal values. Thus, each character may be a digit from "0" to "9" or a letter "A" through "F". See the latest version of the Federal Information Processing Standard 180, Secure Hash Standard for information on computing SHA-256 hashes. At the time of this standard's publication, FIPS 180-37 had been published. It is also possible to use Field xx.996 to contain the hash for data stored externally, which is referenced in Field 20.994: External file reference (EFR) and/or Field 21.994: External file reference (EFR). The ability to store files externally is new to this version of the standard, and is only implemented for the two new record types referred to here. Use of the hash enables the receiver of the data to perform quick searches of large databases to determine if the data already exist in the database. It is not intended as an information assurance check. That is handled by Record Type-98: Information assurance record.				
Field Min	64	Occur Min	0		
Field Max	64	Occur Max	1		
Char Types	H	Special Chars	None		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom_2:ImageHashValue			Cardinality	0..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

13.997

Source Representation

Mnemonic	SOR			Conditionality	0
				Status	Active
Description	This optional field refers to a representation in Record Type-20 with the same SRN from which the data in Field 13.999: Latent friction ridge image (DATA) was derived.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom_2:SourceRepresentation			Cardinality	0..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

13.997_0

Source Representation

Mnemonic	SOR_0			Conditionality	M↑
				Status	New Active
Description	This optional field refers to a representation in Record Type-20 with the same SRN from which the data in Field 13.999: Latent friction ridge image (DATA) was derived.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	255		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom_2:SourceRepresentation			Cardinality	0..255
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

13.997_1

Source Representation

Source Representation Number

Mnemonic	SRN			Conditionality	M↑
				Status	Active
Description	This is the first information item and is mandatory for each Field xx.997. It contains an index to a particular instance of a Type-20 record in the transaction. This same index value appears in the appropriate instance of Record Type-20 as Field 20.021: Source representation number (SRN). The value of the SRN shall be a sequentially assigned a positive integer starting from one and incremented by one, not to exceed 255.				
Field Min	1	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	1 <= SRN <= 255; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom_2:SourceRepresentation			Cardinality	0..255
XML Level 2	biom_2:SourceIdentification/nc:IdentificationID			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

13.997_2

Source Representation

Reference Segment Position

Mnemonic	RSP		Conditionality	O↑	
			Status	Active	
Description	The first information item is the reference segment position (RSP). This provides a unique index to a segmentation.				
Field Min	1		Occur Min	0	
Field Max	2		Occur Max	1	
Char Types	N		Special Chars	None	
Format	n/a		Constraints	1 <= RSP <= 99; positive integer	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom_2:SourceRepresentation		Cardinality	0..255	
XML Level 2	biom_2:ImageSegmentIdentification/nc:IdentificationID		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

13.998

Geographic Sample Acquisition Location

Mnemonic	GEO		Conditionality	O	
			Status	Active	
Description	This optional field contains the location where the iris sample/original source/context information was acquired – not where it is stored.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom:FingerImpressionImage/biom1:ImageCaptureDetail or biom:PalmpointImage/biom1:ImageCaptureDetail or biom:PlantarImage/biom1:ImageCaptureDetail or biom:FrictionRidgeImage/biom1:ImageCaptureDetail		Cardinality	1..1	
XML Level 2	biom_2:CaptureLocation		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

13.998_01

Geographic Sample Acquisition Location

Universal Time Entry

Mnemonic	UTE			Conditionality	O↑
				Status	Active
Description	The coordinated universal time (UTC) where the biometric sample was collected. This time is independent of the actual time zone where the time and date is recorded. The date is YYYYMMDDhhmmssZ, where the Z indicates the zone description of 0 hours. If sample collection time is unknown, set it to "00000000000000Z."				
Field Min	15	Occur Min	0		
Field Max	15	Occur Max	1		
Char Types	AN	Special Chars	None		
Format	YYYYMMDDHHMMSSZ - for Traditional Encoding	Constraints	Dependent upon encoding		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom:FingerImpressionImage/biom1:ImageCaptureDetail or biom:PalmpointImage/biom1:ImageCaptureDetail or biom:PlantarImag/biom1:ImageCaptureDetail e or biom:FrictionRidgeImage/biom1:ImageCaptureDetail			Cardinality	1..1
XML Level 2	biom_2:CaptureLocation			Cardinality	0..1
XML Level 3	biom:CaptureUTCDateTime/nc:DateTime			Cardinality	0..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

13.998_02

Geographic Sample Acquisition Location

Latitude Degree Value

Mnemonic	LTD			Conditionality	D
				Status	Active
Description	The second information item is latitude degree value (LTD). This is a value that specifies the degree of latitude. The value shall be between -90 (inclusive) and +90 (inclusive). The degrees may be expressed as an integer (without a decimal) or a real number including decimals. If decimals are present, then minutes and seconds shall be empty. Examples: Buenos Aires, Argentina: -34 (with minutes LTM = 36) NIST, Gaithersburg, Maryland: 39.137627 (no LTM or LTS)				
Field Min	1	Occur Min	0		
Field Max	9	Occur Max	1		
Char Types	NS	Special Chars	Decimal, Minus Sign, Plus Sign		
Format	n/a	Constraints	=-90 <= LTD <= 90		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom:FingerImpressionImage/biom1:ImageCaptureDetail or biom:PalmpointImage/biom1:ImageCaptureDetail or biom:PlantarImag/biom1:ImageCaptureDetail e or biom:FrictionRidgeImage/biom1:ImageCaptureDetail			Cardinality	1..1
XML Level 2	biom_2:CaptureLocation			Cardinality	0..1
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate (0..1)/nc:GeographicCoordinateLatitude (0..1)			Cardinality	0..1
XML Level 4	nc:LatitudeDegreeValue			Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-13: Variable-Resolution Latent Friction Ridge Image

Page 717 of 1037

13.998_03

Geographic Sample Acquisition Location

Latitude Minute Value

Mnemonic	LTM	Conditionality	D
		Status	Active
Description	This information item is latitude minute value (LTM). This is a value that specifies a minute of a degree. The value shall be between 0 (inclusive) to 60 (exclusive). The minute value may be expressed as an integer (without a decimal) or as a real number including decimals. If decimals are present then seconds shall be empty. Thus, the allowed special character is a period. The minute value can be empty, even if the degree value is an integer. LTM and LGM are co-conditional, so they shall both be present if either is present.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	NS	Special Chars	Decimal
Format	n/a	Constraints	0 <= LTM < 60
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-13)		
XML Level 1	biom:FingerImpressionImage/biom1:ImageCaptureDetail or biom:PalmpPrintImage/biom1:ImageCaptureDetail or biom:PlantarImag/biom1:ImageCaptureDetail e or biom:FrictionRidgeImage/biom1:ImageCaptureDetail	Cardinality	1..1
XML Level 2	biom_2:CaptureLocation	Cardinality	0..1
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate (0...1)/nc:GeographicCoordinateLatitude (0...1)	Cardinality	0...1
XML Level 4	nc:LatitudeMinuteValue	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

13.998_04

Geographic Sample Acquisition Location

Latitude Second Value

Mnemonic	LTS	Conditionality	D
		Status	Active
Description	The fourth information item is the latitude second value (LTS). This is a value that specifies a second of a minute. The integer shall be 0 (inclusive) to 60 (exclusive). The second value is empty, even if the minute value is an integer.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	0 <= LTS < 60
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-13)		
XML Level 1	biom:FingerImpressionImage/biom1:ImageCaptureDetail or biom:PalmpPrintImage/biom1:ImageCaptureDetail or biom:PlantarImag/biom1:ImageCaptureDetail e or biom:FrictionRidgeImage/biom1:ImageCaptureDetail	Cardinality	1..1
XML Level 2	biom_2:CaptureLocation	Cardinality	0..1
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate (0...1)/nc:GeographicCoordinateLatitude (0...1)	Cardinality	0...1
XML Level 4	nc:LatitudeSecondValue	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

13.998_05

Geographic Sample Acquisition Location

Longitude Degree Value

Mnemonic	LGD		Conditionality	D			
			Status	Active			
Description	The fifth information item is the longitude degree value (LGD). It is a value that specifies the degree of a longitude. The value shall be between -180 (inclusive) and +180 (inclusive). If LTD is present, then LGD shall be present. The degrees may be expressed as whole numbers (without a decimal) or real numbers including decimals. If decimals are present, then minutes and seconds are empty. Examples: Buenos Aires, Argentina: -58 (with minutes LGM = 22), NIST, Gaithersburg, Maryland: -77.216032 (no LGM or LGS)						
Field Min	1	Occur Min	0				
Field Max	10	Occur Max	1				
Char Types	NS	Special Chars	Decimal, Minus Sign, Plus Sign				
Format	n/a	Constraints	-180 <= LGD <= 180				
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-13)						
XML Level 1	biom:FingerImpressionImage/biom1:ImageCaptureDetail or biom:PalmpPrintImage/biom1:ImageCaptureDetail or biom:PlantarImag/biom1:ImageCaptureDetail e or biom:FrictionRidgeImage/biom1:ImageCaptureDetail		Cardinality	1..1			
XML Level 2	biom_2:CaptureLocation		Cardinality	0..1			
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate (0...1)/nc:GeographicCoordinateLatitude (0...1)		Cardinality	0...1			
XML Level 4	nc:LongitudeDegreeValue		Cardinality	0..1			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

13.998_06

Geographic Sample Acquisition Location

Longitude Minute Value

Mnemonic	LGM		Conditionality	D			
			Status	Active			
Description	The sixth information item is the longitude minute value (LGM). It is a value that specifies a minute of a degree. The value shall be from 0 (inclusive) to 60 (exclusive). The minute value may be expressed as an integer (without a decimal) or as a real number including decimals. If decimals are present then seconds shall not appear. The minute value is empty, even if the degree value is an integer. If LTM is present, then LGM shall be present.						
Field Min	1	Occur Min	0				
Field Max	8	Occur Max	1				
Char Types	NS	Special Chars	Decimal				
Format	n/a	Constraints	0 <= LGM < 60				
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-13)						
XML Level 1	biom:FingerImpressionImage/biom1:ImageCaptureDetail or biom:PalmpPrintImage/biom1:ImageCaptureDetail or biom:PlantarImag/biom1:ImageCaptureDetail e or biom:FrictionRidgeImage/biom1:ImageCaptureDetail		Cardinality	1..1			
XML Level 2	biom_2:CaptureLocation		Cardinality	0..1			
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate (0...1)/nc:GeographicCoordinateLatitude (0...1)		Cardinality	0...1			
XML Level 4	nc:LongitudeMinuteValue		Cardinality	0..1			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

13.998_07

Geographic Sample Acquisition Location

Longitude Second Value

Mnemonic	LGS	Conditionality	D
		Status	Active
Description	The seventh information item is the longitude second value (LGS). This is a value that specifies a second of a minute. The integer shall be 0 (inclusive) to 60 (exclusive). The second value is empty, even if the minute value is an integer. If LTS is present, then LGS shall be present.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	0 <= LGS < 60
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-13)		
XML Level 1	biom:FingerImpressionImage/biom1:ImageCaptureDetail or biom:PalmpointImage/biom1:ImageCaptureDetail or biom:PlantarImag/biom1:ImageCaptureDetail e or biom:FrictionRidgeImage/biom1:ImageCaptureDetail	Cardinality	1..1
XML Level 2	biom_2:CaptureLocation	Cardinality	0..1
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate (0...1)/nc:GeographicCoordinateLatitude (0...1)	Cardinality	0...1
XML Level 4	nc:LongitudeSecondValue	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

13.998_08

Geographic Sample Acquisition Location

Elevation

Mnemonic	ELE	Conditionality	O
		Status	Active
Description	The eighth information item is elevation (ELE). It is expressed in meters. It is a numeric value. It is between -422 meters (Dead Sea) and 8848 meters (Mount Everest). Allowed special characters are the negative sign and the period.		
Field Min	3	Occur Min	1
Field Max	8	Occur Max	1
Char Types	NS	Special Chars	Minus Sign,Period
Format	n/a	Constraints	-422.000 < ELE < 8848.000; real number
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-13)		
XML Level 1	biom:FingerImpressionImage/biom1:ImageCaptureDetail or biom:PalmpointImage/biom1:ImageCaptureDetail or biom:PlantarImag/biom1:ImageCaptureDetail e or biom:FrictionRidgeImage/biom1:ImageCaptureDetail	Cardinality	1..1
XML Level 2	biom_2:CaptureLocation	Cardinality	0..1
XML Level 3	nc:LocationGeographicElevation	Cardinality	0..1
XML Level 4	nc:MeasurePoint	Cardinality	1..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

13.998_09

Geographic Sample Acquisition Location

Geodetic Datum Code

Mnemonic	GDC	Conditionality	O
		Status	Active
Description	The ninth information item is the geodetic datum code (GDC11). It is an alphanumeric value of 3 to 6 characters in length. This information item is used to indicate which coordinate system was used to represent the values in information items 2 through 7. If no entry is made in this information item, then the basis for the values entered in the first eight information items shall be WGS84, the code for the World Geodetic Survey 1984 version - WGS 84 (G873). See look up codes for values. If no entry is made in this information item, then the basis for the values entered in the first eight information items shall be WGS84, the code for the World Geodetic Survey 1984 version - WGS 84 (G873). See look up codes for values.		
Field Min	2	Occur Min	0
Field Max	6	Occur Max	1
Char Types	AN	Special Chars	None
Format	n/a	Constraints	see Look Up Codes
Code List	GEOGRAPHIC COORDINATE DATUM CODE		
Source	ANSI/NIST ITL 1-2013 (Type-13)		
XML Level 1	biom:FingerImpressionImage/biom1:ImageCaptureDetail or biom:PalmpPrintImage/biom1:ImageCaptureDetail or biom:PlantarImag/biom1:ImageCaptureDetail e or biom:FrictionRidgeImage/biom1:ImageCaptureDetail	Cardinality	1..1
XML Level 2	biom_2:CaptureLocation	Cardinality	0..1
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate (0...1)/nc:GeographicCoordinateLatitude (0...1)	Cardinality	0...1
XML Level 4	biom:GeodeticDatumCoordinateSystemCode or biom:GeodeticDatumCoordinateSystemName	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

13.998_10

Geographic Sample Acquisition Location

Geographic Coordinate Universal Transverse Mercator Zone

Mnemonic	GCM	Conditionality	D
		Status	Active
Description	It is an alphanumeric value of 2 to 3 characters. This is a one or two digit UTM zone number followed by the 8 degree latitudinal band designator (which is a single letter).		
Field Min	1	Occur Min	0
Field Max	3	Occur Max	1
Char Types	AN	Special Chars	None
Format	n/a	Constraints	One or two digit UTM zone
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-13)		
XML Level 1	biom:FingerImpressionImage/biom1:ImageCaptureDetail or biom:PalmpPrintImage/biom1:ImageCaptureDetail or biom:PlantarImag/biom1:ImageCaptureDetail e or biom:FrictionRidgeImage/biom1:ImageCaptureDetail	Cardinality	1..1
XML Level 2	biom_2:CaptureLocation	Cardinality	0..1
XML Level 3	nc:LocationUTMCoordinate	Cardinality	0..1
XML Level 4	nc:UTMGridZoneID	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-13: Variable-Resolution Latent Friction Ridge Image

Page 721 of 1037

13.998_11

Geographic Sample Acquisition Location

Geographic Coordinate Universal Transverse Mercator Easting

Mnemonic	GCE			Conditionality	D
				Status	Active
Description	The eleventh information item is the geographic coordinate universal transverse Mercator easting (GCE). It is an integer of 1 to 6 digits.				
Field Min	1	Occur Min	0		
Field Max	6	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= GCE; integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom:FingerImpressionImage/biom1:ImageCaptureDetail or biom:PalmpointImage/biom1:ImageCaptureDetail or biom:PlantarImag/biom1:ImageCaptureDetail e or biom:FrictionRidgeImage/biom1:ImageCaptureDetail			Cardinality	1..1
XML Level 2	biom_2:CaptureLocation			Cardinality	0..1
XML Level 3	nc:LocationUTMCoordinate			Cardinality	0..1
XML Level 4	nc:UTMEastingValue			Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

13.998_12

Geographic Sample Acquisition Location

Geographic Coordinate Universal Transverse Mercator Northing

Mnemonic	GCN			Conditionality	D
				Status	Active
Description	The twelfth information item is the geographic coordinate universal transverse Mercator northing (GCN). It is an integer of 1 to 8 digits.				
Field Min	1	Occur Min	0		
Field Max	8	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= GCN; integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-13)				
XML Level 1	biom:FingerImpressionImage/biom1:ImageCaptureDetail or biom:PalmpointImage/biom1:ImageCaptureDetail or biom:PlantarImag/biom1:ImageCaptureDetail e or biom:FrictionRidgeImage/biom1:ImageCaptureDetail			Cardinality	1..1
XML Level 2	biom_2:CaptureLocation			Cardinality	0..1
XML Level 3	nc:LocationUTMCoordinate			Cardinality	0..1
XML Level 4	nc:UTMNorthingValue			Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-13: Variable-Resolution Latent Friction Ridge Image

Page 722 of 1037

13.998_13

Geographic Sample Acquisition Location

Geographic Reference Text

Mnemonic	GRT	Conditionality	O
		Status	Active
Description	It is a free form text describing a street address or other physical location (such as 'Corner of Washington and Madison, Geneva, NY').		
Field Min	1	Occur Min	0
Field Max	150	Occur Max	1
Char Types	U	Special Chars	Any
Format	n/a	Constraints	None
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-13)		
XML Level 1	biom:FingerImpressionImage/biom1:ImageCaptureDetail or biom:PalmpointImage/biom1:ImageCaptureDetail or biom:PlantarImag/biom1:ImageCaptureDetail e or biom:FrictionRidgelImage/biom1:ImageCaptureDetail	Cardinality	1..1
XML Level 2	biom_2:CaptureLocation	Cardinality	0..1
XML Level 3	biom:GeographicLocationText	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

13.998_14

Geographic Sample Acquisition Location

Geographic Coordinate Other System Identifier

Mnemonic	OSI	Conditionality	O
		Status	Active
Description	A fourteenth optional information item geographic coordinate other system identifier (OSI) allows for other coordinate systems. This information items specifies the system identifier. It is up to 10 characters in length. Examples are: • MGRS (Military Grid Reference System), • USNG (United States National Grid), • GARS (Global Area Reference System), • GEOREF (World Geographic Reference), • LANDMARK landmark (e.g. hydant) and position relative to the landmark.		
Field Min	1	Occur Min	0
Field Max	10	Occur Max	1
Char Types	U	Special Chars	Any
Format	n/a	Constraints	None
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-13)		
XML Level 1	biom:FingerImpressionImage/biom1:ImageCaptureDetail or biom:PalmpointImage/biom1:ImageCaptureDetail or biom:PlantarImag/biom1:ImageCaptureDetail e or biom:FrictionRidgelImage/biom1:ImageCaptureDetail	Cardinality	1..1
XML Level 2	biom_2:CaptureLocation	Cardinality	0..1
XML Level 3	biom:LocationAlternateGeographicSystemValue	Cardinality	0..1
XML Level 4	biom:GeographicLocationSystemName	Cardinality	1..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

13.998_15

Geographic Sample Acquisition Location

Geographic Coordinate Other System Value

Mnemonic	OCV		Conditionality	D			
			Status	Active			
Description	A fifteenth optional information item, is the geographic coordinate other system value (OCV). It shall only be present if OSI is present in the record. It can be up to 126 characters in length. If OSI is LANDMARK, OCV is free text and may be up to 126 characters. For details on the formatting of OCV for the other coordinate systems shown in OSI as examples, see http://earth-info.nga.mil/GandG/coordsys/grids/referencesys.html .						
Field Min	1	Occur Min	1				
Field Max	126	Occur Max	1				
Char Types	U	Special Chars	Any				
Format	n/a	Constraints	None				
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-13)						
XML Level 1	biom:FingerImpressionImage/biom1:ImageCaptureDetail or biom:PalmpPrintImage/biom1:ImageCaptureDetail or biom:PlantarImag/biom1:ImageCaptureDetail e or biom:FrictionRidgeImage/biom1:ImageCaptureDetail		Cardinality	1..1			
XML Level 2	biom_2:CaptureLocation		Cardinality	0..1			
XML Level 3	biom:LocationAlternateGeographicSystemValue		Cardinality	0..1			
XML Level 4	biom:GeographicLocationText		Cardinality	0...1			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

13.999

Latent Friction Ridge Image

Mnemonic	DATA		Conditionality	D			
			Status	Active			
Description	This mandatory field contains the fingerprint image. See Section 7.2 of ANSI/NIST ITL 1-2013 for details.						
Field Min	1	Occur Min	0				
Field Max	*	Occur Max	1				
Char Types	B	Special Chars	None				
Format	n/a	Constraints	None				
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-13)						
XML Level 1	nc:BinaryBase64Object		Cardinality	0..1			
XML Level 2			Cardinality				
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

14.001

Record Header

Mnemonic	LEN		Conditionality	M			
			Status	Active			
Description	The record header appears as the first field (xx.001) in each Record Type. It contains information particular to the encoding format chosen, in order to enable proper reading of the record. In Traditional encoding, this field contains the record length in bytes (including all information separators). In NIEM-conformant XML encoding, this field contains the RecordCategoryCode, which is the numeric representation of the Record Type.						
Field Min	T = 4; X = 1		Occur Min	1			
Field Max	T = 8; X = 2		Occur Max	1			
Char Types	N		Special Chars	None			
Format	n/a		Constraints	positive integer			
Code List							
Source	ANSI/NIST ITL 1-2013						
XML Level 1	nist-itl:RecordCategoryCode		Cardinality	1...1			
XML Level 2			Cardinality				
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

14.002

Information Designation Character

Mnemonic	IDC		Conditionality	M			
			Status	Active			
Description	Each of the records present in a transaction, with the exception of the Type-1 record, shall include a field (xx.002) containing the information designation character / IDC. The value of the IDC shall be a sequentially assigned positive integer starting from zero and incremented by one up to a maximum of 99. IDC references are stated in Type-1 Field 1.003 Transaction content (CNT) and shall be used to relate information items in the CNT field of the Type-1 record to the other records in the transaction. Two or more records may share a single IDC solely to identify and link together records that pertain to different representations of the same biometric trait.						
Field Min	1		Occur Min	1			
Field Max	2		Occur Max	1			
Char Types	N		Special Chars	None			
Format	n/a		Constraints	0 <= IDC <= 99; integer			
Code List							
Source	ANSI/NIST ITL 1-2013						
XML Level 1	nist-itl:ImageReferenceIdentification/nc:IdentificationID		Cardinality	1...1			
XML Level 2			Cardinality				
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-14: Variable-Resolution Fingerprint Image

Page 725 of 1037

14.003

Impression Type

Mnemonic	IMP			Conditionality	M
				Status	Active
Description	This mandatory field shall indicate the manner by which the friction ridge print was obtained.				
Field Min	1	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= IMP <= 3, IMP = 8, 20 <= IMP <= 29, 40 <= IMP <= 41; integer		
Code List	FRICTION RIDGE IMPRESSION CODES				
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage			Cardinality	1..1
XML Level 2	biom:FingerprintImageImpressionCaptureCategoryCode			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

14.004

Source Agency

Mnemonic	SRC			Conditionality	M
				Status	Active
Description	This is the identifier of the agency that actually created the record and supplied the information contained in it.				
Field Min	1	Occur Min	1		
Field Max	Unlimited	Occur Max	1		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage/biom:ImageCaptureDetail			Cardinality	1..1
XML Level 2	biom:CaptureOrganization			Cardinality	1..1
XML Level 3	nc:OrganizationIdentification/nc:IdentificationID			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

14.005

Fingerprint Capture Date

Mnemonic	FCD	Conditionality	M
		Status	Active
Description	This mandatory field shall contain the local date that the fingerprint data contained in the record was captured.		
Field Min	Dependent upon encoding	Occur Min	1
Field Max	Dependent upon encoding	Occur Max	1
Char Types	N	Special Chars	None
Format	T = YYYYMMDD; X = <CaptureDate>	Constraints	Dependent upon encoding.
Code List			
Source	ANSI/NIST ITL 1-2013		
XML Level 1	biom:FingerImpressionImage/biom:ImageCaptureDetail	Cardinality	1..1
XML Level 2	biom_2:CaptureDate/nc:Date	Cardinality	1..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

14.006

Horizontal Line Length

Mnemonic	HLL	Conditionality	D
		Status	Active
Description	HLL defines the number of pixels contained on a single horizontal line of the image. The maximum horizontal size is limited to 65,535 pixels in Record Types-4 and 8, and to 99,999 for other record types. The minimum value is 10 pixels. The total image size (HLL times VLL) must be able to be accommodated in Field xx.001 for Traditional encoding.		
Field Min	2	Occur Min	0
Field Max	5	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	10 <= HLL <= 99999; positive integer
Code List			
Source	ANSI/NIST ITL 1-2013		
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1
XML Level 2	biom_2:ImageHorizontalLineLengthPixelQuantity	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

14.007

Vertical Line Length

Mnemonic	VLL			Conditionality	D
				Status	Active
Description	VLL defines the number of pixels contained in a single vertical line in the image. The maximum vertical size is limited to 65,535 pixels in Record Types-4 and 8, and to 99,999 for other record types. The minimum value is 10 pixels. The total image size (HLL times VLL) must be able to be accommodated in Field xx.001 for Traditional encoding.				
Field Min	2	Occur Min	0		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	10 <= VLL <= 99999; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1		
XML Level 2	biom_2:ImageVerticalLineLengthPixelQuantity	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

14.008

Scale Units

Mnemonic	SLC			Conditionality	D
				Status	Active
Description	The image sampling frequency (pixel density). A value of "1" shall indicate pixels per inch. A value of "2" shall indicate pixels per centimeter. A value of "0" in this field indicates that no scale is provided, and the quotient of THPS/TVPS shall provide the pixel aspect ratio.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= SLC <= 2, See Look Up Codes		
Code List	SCALE UNIT CODES				
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1		
XML Level 2	biom_2:ImageScaleUnitsCode	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

14.009

Transmitted Horizontal Pixel Scale

Mnemonic	THPS			Conditionality	D
				Status	Active
Description	This is the integer pixel density used in the horizontal direction of the image if SLC has a value of "1" or "2". If SLC has a value of "0", this information item shall contain the horizontal component of the pixel aspect ratio, up to 5 integer digits. For example, if the SLC value = 1, then the value of THPS could be '1000' for a 1000 ppi sensor.				
Field Min	1	Occur Min	0		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1		
XML Level 2	biom_2:ImageHorizontalPixelDensityValue	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

14.01

Transmitted Vertical Pixel Scale

Mnemonic	TVPS			Conditionality	D
				Status	Active
Description	This is the integer pixel density used in the vertical direction of the image if SLC has a value of "1" or "2". If SLC has a value of "0", this information item shall contain the vertical component of the pixel aspect ratio, up to 5 integer digits. If SLC is 1 or 2, then TVPS shall equal THPS.				
Field Min	1	Occur Min	0		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1		
XML Level 2	biom_2:ImageVerticalPixelDensityValue	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-14: Variable-Resolution Fingerprint Image

Page 729 of 1037

14.011

Compression Algorithm

Mnemonic	CGA			Conditionality	D
				Status	Active
Description	This field is mandatory if an image is present in Field 14.999: Fingerprint image / DATA. Otherwise it is absent. It shall specify the algorithm used to compress the transmitted grayscale images.				
Field Min	3	Occur Min	0		
Field Max	5	Occur Max	1		
Char Types	AN	Special Chars	None		
Format	n/a	Constraints	see Look Up Codes		
Code List	COMPRESSION CODES				
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1		
XML Level 2	biom_2:ImageCompressionAlgorithmText	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

14.012

Bits Per Pixel

Mnemonic	BPX			Conditionality	D
				Status	Active
Description	This ASCII field shall contain the number of bits used to represent a pixel. This field shall contain an entry of "8" for normal grayscale values of "0" to "255" or each RGB color component. Any entry in this field greater than "8" shall represent a grayscale or color pixel component with increased precision.				
Field Min	1	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	8 <= BPX <= 99		
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom_2:ImageBitsPerPixelQuantity	Cardinality	0..1		
XML Level 2	biom_2:ImageCaptureDetail	Cardinality	1..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

14.013

Friction Ridge Generalized Position

Mnemonic	FGP		Conditionality	M
			Status	Active
Description	This field is used in Record types dealing with friction ridges. It specifies which friction ridge biometric sample was collected.			
Field Min	n/a	Occur Min	1	
Field Max	n/a	Occur Max	1	
Char Types	N	Special Chars	None	
Format	n/a	Constraints	0 <= FGP <= 19, or FGP = 33, or FGP = 36 or 40 <= FGP <= 54; integer; see Look Up Codes	
Code List	FRICTION RIDGE POSITION CODES			
Source	ANSI/NIST ITL 1-2013			
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1	
XML Level 2	biom_2:FingerPositionCode	Cardinality	1..1	
XML Level 3		Cardinality		
XML Level 4		Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0 Yes DoD EBTS 4.0 Yes

14.014

Print Position Descriptors

Mnemonic	PPD		Conditionality	D
			Status	Active
Description	This ASCII field shall be present if and only if the finger position code "19" appears in [Type-14 Finger Position field]. This field shall consist of two information items. The first is the probable decimal finger position code (0-10). The second information item is the code to indicate the portion of the EJI or tip image that is stored as a single image in the database. There may be up to 17 such images for a single finger. Images of full-length fingers use codes FV1 through FV4.			
Field Min	n/a	Occur Min	0	
Field Max	n/a	Occur Max	1	
Char Types	n/a	Special Chars	n/a	
Format	n/a	Constraints	n/a	
Code List				
Source	ANSI/NIST ITL 1-2013			
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1	
XML Level 2	biom_2:FingerprintImageMajorCasePrint	Cardinality	0..1	
XML Level 3		Cardinality		
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0 Yes DoD EBTS 4.0 Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-14: Variable-Resolution Fingerprint Image

Page 731 of 1037

14.014_1

Print Position Descriptors

Decimal Finger Position Code

Mnemonic	DFP			Conditionality	M↑
				Status	Active
Description	The first information item of 14.014 Print Position Descriptors with value of 1 to 10, inclusive or 16 or 17.				
Field Min	1	Occur Min	0		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	1 <= DFP <= 10 or DFP = 16 or 17; see Look Up Codes		
Code List	FRICTION RIDGE POSITION CODES				
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage	Cardinality	1...1		
XML Level 2	biom_2:FingerprintImageMajorCasePrint	Cardinality	0..1		
XML Level 3	biom_2:FingerPositionCode	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

14.014_2

Print Position Descriptors

Finger Image Code

Mnemonic	FIC			Conditionality	M↑
				Status	Active
Description	The second information item of the Search Position Descriptors (SPD) field to indicate the portion of the database to search. Full-length finger joint images use codes FV1 through FV4. Figure 2 is an illustration of the Entire Joint Image for a middle finger with each of the full finger views and constituent parts identified. Multiple portions of the EJI may be listed in a separate subfield.				
Field Min	3	Occur Min	0		
Field Max	3	Occur Max	1		
Char Types	AN	Special Chars	D		
Format	n/a	Constraints	EJI, TIP, FV1, FV2, FV3, FV4, PRX, DST or MED		
Code List	PRINT POSITION DESCRIPTORS				
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage	Cardinality	1...1		
XML Level 2	biom_2:FingerprintImageMajorCasePrint	Cardinality	0..1		
XML Level 3	biom_2:MajorCasePrintCode	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

14.015

Print Position Coordinates

Mnemonic	PPC		Conditionality	D	
			Status	Active	
Description	This field describes the type or portion of the latent image contained in this record and its location within an entire joint image. If finger position code "19" appears in Finger Position field, this setmay optionally contain offsets to the locations for the bounding box of the EJI, each of the full finger views, or segments within the EJI. When used, this field shall consist of six (6) mandatory information items describing the type or portion of the image contained in this record and its location within an EJI. This information will describe either the location of the entire joint image, one full finger view, or segment. Individual full finger or segment definitions may be repeated as repeating sets of information items.				
Field Min	n/a		Occur Min	0	
Field Max	b		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage		Cardinality	1..1	
XML Level 2	biom_2:FingerprintImageMajorCasePrint		Cardinality	0..1	
XML Level 3	biom_2:MajorCasePrintSegmentOffset		Cardinality	0..1	
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

14.015_0

Print Position Coordinates

Mnemonic	PPC_0		Conditionality	M↑	
			Status	New Active	
Description	This field describes the type or portion of the latent image contained in this record and its location within an entire joint image. If finger position code "19" appears in Finger Position field, this setmay optionally contain offsets to the locations for the bounding box of the EJI, each of the full finger views, or segments within the EJI. When used, this field shall consist of six (6) mandatory information items describing the type or portion of the image contained in this record and its location within an EJI. This information will describe either the location of the entire joint image, one full finger view, or segment. Individual full finger or segment definitions may be repeated as repeating sets of information items.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	12	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage		Cardinality	1..1	
XML Level 2	biom_2:FingerprintImageMajorCasePrint		Cardinality	0..1	
XML Level 3	biom_2:MajorCasePrintSegmentOffset		Cardinality	0..12	
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes		

14.015_1

Print Position Coordinates

Full Finger View

Mnemonic	FVC	Conditionality	M↑
		Status	Active
Description	This information item is the number of the full finger view with values of "FV1" through "FV4". Values of "FV1" to "FV4" specify the bounding coordinates for each full finger view. For the case of a fingertip, this information item shall be "TIP". FVC will contain the code "NA" if only a proximal, distal or medial segment is available.		
Field Min	2	Occur Min	1
Field Max	3	Occur Max	1
Char Types	AN	Special Chars	None
Format	n/a	Constraints	FVC = NA, FV1, FV2, FV3, FV4 or TIP; see Look Up Codes
Code List	PRINT POSITION DESCRIPTORS		
Source	ANSI/NIST ITL 1-2013		
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1
XML Level 2	biom_2:FingerprintImageMajorCasePrint	Cardinality	0..1
XML Level 3	biom_2:MajorCasePrintSegmentOffset	Cardinality	0..12
XML Level 4	biom_2:SegmentFingerViewCode	Cardinality	1..1
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

14.015_2

Print Position Coordinates

Location of Segment

Mnemonic	LOS	Conditionality	M↑
		Status	Active
Description	This information item is used to identify the location of a segment within a full finger view. It will contain the not applicable code "NA" if the image portion refers to a full finger view or to the entire joint image locations. It shall contain "PRX", "DST", "MED" for a proximal, distal, or medial segment.		
Field Min	2	Occur Min	1
Field Max	3	Occur Max	1
Char Types	A	Special Chars	None
Format	n/a	Constraints	LOS = NA, PRX, DST or MED; see Look Up Codes
Code List	PRINT POSITION DESCRIPTORS		
Source	ANSI/NIST ITL 1-2013		
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1
XML Level 2	biom_2:FingerprintImageMajorCasePrint	Cardinality	0..1
XML Level 3	biom_2:MajorCasePrintSegmentOffset	Cardinality	0..12
XML Level 4	biom_2:SegmentLocationCode	Cardinality	1..1
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-14: Variable-Resolution Fingerprint Image

Page 734 of 1037

14.015_3

Print Position Coordinates

Left Horizontal Coordinate

Mnemonic	LHC			Conditionality	M↑
				Status	Active
Description	It is the horizontal offset in pixels to the left edge of the bounding box relative to the origin positioned in the upper left corner of the image.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= LHC < HLL; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1		
XML Level 2	biom_2:FingerprintImageMajorCasePrint	Cardinality	0..1		
XML Level 3	biom_2:MajorCasePrintSegmentOffset	Cardinality	0..12		
XML Level 4	biom_2:SegmentLeftHorizontalCoordinateValue	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

14.015_4

Print Position Coordinates

Right Horizontal Coordinate

Mnemonic	RHC			Conditionality	M↑
				Status	Active
Description	It is the horizontal offset in pixels to the right edge of the bounding box relative to the origin positioned in the upper left corner of the image.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	LHC < RHC < HLL; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1		
XML Level 2	biom_2:FingerprintImageMajorCasePrint	Cardinality	0..1		
XML Level 3	biom_2:MajorCasePrintSegmentOffset	Cardinality	0..12		
XML Level 4	biom_2:SegmentRightHorizontalCoordinateValue	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-14: Variable-Resolution Fingerprint Image

Page 735 of 1037

14.015_5

Print Position Coordinates

Top Vertical Coordinate

Mnemonic	TVC			Conditionality	M↑
				Status	Active
Description	The vertical offset (pixel counts down) to the top of the bounding box.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= TVC < VLL; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1		
XML Level 2	biom_2:FingerprintImageMajorCasePrint	Cardinality	0..1		
XML Level 3	biom_2:MajorCasePrintSegmentOffset	Cardinality	0..12		
XML Level 4	biom_2:SegmentTopVerticalCoordinateValue	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

14.015_6

Print Position Coordinates

Bottom Vertical Coordinate

Mnemonic	BVC			Conditionality	M↑
				Status	Active
Description	It is the vertical offset from the upper left corner of the image down to the bottom of the bounding box. It is counted in pixels.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	TVC < BVC < VLL; non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1		
XML Level 2	biom_2:FingerprintImageMajorCasePrint	Cardinality	0..1		
XML Level 3	biom_2:MajorCasePrintSegmentOffset	Cardinality	0..12		
XML Level 4	biom_2:SegmentBottomVerticalCoordinateValue	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

14.016

Scanned Horizontal Pixel Scale

Mnemonic	SHPS			Conditionality	0		
				Status	Active		
Description	This ASCII field shall specify the horizontal pixel density used for scanning providing the SLC field contains a "1" or a "2". Otherwise, it indicates the horizontal component of the pixel aspect ratio.						
Field Min	1			Occur Min	0		
Field Max	5			Occur Max	1		
Char Types	N			Special Chars	None		
Format	n/a			Constraints	positive integer		
Code List							
Source	ANSI/NIST ITL 1-2013						
XML Level 1	biom:FingerImpressionImage/biom:ImageCaptureDetail				Cardinality	1...1	
XML Level 2	biom_2:CaptureHorizontalPixelDensityValue				Cardinality	0..1	
XML Level 3					Cardinality		
XML Level 4					Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

14.017

Scanned Vertical Pixel Scale

Mnemonic	SVPS			Conditionality	0		
				Status	Active		
Description	This ASCII field shall specify the vertical pixel density used for scanning providing the SLC field contains a "1" or a "2". Otherwise, it indicates the vertical component of the pixel aspect ratio.						
Field Min	1			Occur Min	0		
Field Max	5			Occur Max	1		
Char Types	N			Special Chars	None		
Format	n/a			Constraints	positive integer		
Code List							
Source	ANSI/NIST ITL 1-2013						
XML Level 1	biom:FingerImpressionImage/biom:ImageCaptureDetail				Cardinality	1...1	
XML Level 2	biom_2:CaptureVerticalPixelDensityValue				Cardinality	0..1	
XML Level 3					Cardinality		
XML Level 4					Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

14.018

Amputated or Bandaged

Mnemonic	AMP		Conditionality	0	
			Status	Active	
Description	This optional field shall specify if one or more fingers are amputated or bandaged. This field shall consist of one subfield for each amputated or missing finger. Multiple amputated or unprintable finger positions may each be entered as a separate repeating subfield. This field is to be used anytime there are fewer than expected printable fingers in a submission (e.g., less than four in a left or right slap or less than two in a two-thumb slap). A partially scarred finger should be printed. XX shall be used only when a partial print exists due to amputation; therefore it contains some friction ridge detail. UP shall be used with the complete block where an image was to be transmitted, but there is no image due to amputation or total lack of friction ridge detail (such as with a bandage). An image with a scar should not be marked XX or UP.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage		Cardinality	1...1	
XML Level 2	biom_2:FingerprintImageFingerMissing		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

14.018_0

Amputated or Bandaged

Mnemonic	AMP_0		Conditionality	M↑	
			Status	New Active	
Description	This optional field shall specify if one or more fingers are amputated or bandaged. This field shall consist of one subfield for each amputated or missing finger. Multiple amputated or unprintable finger positions may each be entered as a separate repeating subfield. This field is to be used anytime there are fewer than expected printable fingers in a submission (e.g., less than four in a left or right slap or less than two in a two-thumb slap). A partially scarred finger should be printed. XX shall be used only when a partial print exists due to amputation; therefore it contains some friction ridge detail. UP shall be used with the complete block where an image was to be transmitted, but there is no image due to amputation or total lack of friction ridge detail (such as with a bandage). An image with a scar should not be marked XX or UP.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	5	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage		Cardinality	1...1	
XML Level 2	biom_2:FingerprintImageFingerMissing		Cardinality	0..5	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-14: Variable-Resolution Fingerprint Image

Page 738 of 1037

14.018_1

Amputated or Bandaged

Friction Ridge Amputation or Bandage Position

Mnemonic	FRAP			Conditionality	M↑
				Status	Active
Description	The first information item of the amputated and bandaged field indicating the friction ridge position.				
Field Min	1	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	1 <= FRAP <= 10 or FRAP = 16 or 17; see Look Up Codes		
Code List	FRICTION RIDGE POSITION CODES				
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1		
XML Level 2	biom_2:FingerprintImageFingerMissing	Cardinality	0..5		
XML Level 3	biom_2:FingerPositionCode	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

14.018_2

Amputated or Bandaged

Amputated or Bandaged Code

Mnemonic	ABC			Conditionality	M↑
				Status	Active
Description	This information item provides the code that describes the reason the finger's image is missing.				
Field Min	2	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	A	Special Chars	None		
Format	n/a	Constraints	ABC = XX or UP; See Look Up Codes		
Code List	AMPUTATED OR BANDAGED CODE				
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1		
XML Level 2	biom_2:FingerprintImageFingerMissing	Cardinality	0..5		
XML Level 3	biom_2:FingerMissingCode	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

14.02

Comment

Mnemonic	COM	Conditionality	0
		Status	Active
Description	The optional Comment field appears in many record types and may be used to insert free text information. It is not reserved exclusively for log-related information but has historically often been used for this purpose. It is limited to a maximum of 126 characters. This maximum size was established in order to maintain consistency across encodings. The maximum size differed in the 2007 and 2008 versions of the standard.		
Field Min	1	Occur Min	0
Field Max	126	Occur Max	1
Char Types	U	Special Chars	Any
Format	n/a	Constraints	None
Code List			
Source	ANSI/NIST ITL 1-2013		
XML Level 1	biom:FingerImpressionImage	Cardinality	1...1
XML Level 2	biom_2:ImageCommentText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

14.021

Finger Segment Position(s)

Mnemonic	SEG	Conditionality	D
		Status	Active
Description	This ASCII field shall contain offsets to the locations of image segments containing the individual fingers within the flat images of the four simultaneous fingers from each hand or the two simultaneous thumbs. The offsets are relative to the origin positioned in the upper left corner of the image. The horizontal offsets (X) are the pixel counts to the right, and the vertical offsets (Y) are the pixel counts down. A finger segment is defined by the FINGER NUMBER The five information items within a finger segment definition are separated by the "US" separator. Individual finger segment definitions are separated. If more than one algorithm is used to segment the image, successive sets finger segmentation positions		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	n/a
Format	n/a	Constraints	n/a
Code List			
Source	ANSI/NIST ITL 1-2013		
XML Level 1	biom:FingerImpressionImage	Cardinality	1...1
XML Level 2	biom_2:FingerprintImageSegmentPositionSquare	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

14.021_0

Finger Segment Position(s)

Mnemonic	SEG_0		Conditionality	M↑	
			Status	New Active	
Description	This ASCII field shall contain offsets to the locations of image segments containing the individual fingers within the flat images of the four simultaneous fingers from each hand or the two simultaneous thumbs. The offsets are relative to the origin positioned in the upper left corner of the image. The horizontal offsets (X) are the pixel counts to the right, and the vertical offsets (Y) are the pixel counts down. A finger segment is defined by the FINGER NUMBER The five information items within a finger segment definition are separated by the "US" separator. Individual finger segment definitions are separated. If more than one algorithm is used to segment the image, successive sets finger segmentation positions				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	5	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage		Cardinality	1..1	
XML Level 2	biom_2:FingerprintImageSegmentPositionSquare		Cardinality	0..5	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

14.021_1

Finger Segment Position(s)

Friction Ridge Segment Position

Mnemonic	FRSP		Conditionality	M↑	
			Status	Active	
Description	The first information item of the segment position field indicating the friction ridge position.				
Field Min	1		Occur Min	1	
Field Max	2		Occur Max	1	
Char Types	N		Special Chars	None	
Format	n/a		Constraints	see Look Up Codes	
Code List	FRICTION RIDGE POSITION CODES				
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage		Cardinality	1..1	
XML Level 2	biom_2:FingerprintImageSegmentPositionSquare		Cardinality	0..5	
XML Level 3	biom_2:FingerPositionCode		Cardinality	1..1	
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-14: Variable-Resolution Fingerprint Image

Page 741 of 1037

14.021_2

Finger Segment Position(s)

Left Horizontal Coordinate

Mnemonic	LHC			Conditionality	M↑
				Status	Active
Description	It is the horizontal offset in pixels to the left edge of the bounding box relative to the origin positioned in the upper left corner of the image.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= LHC <= HLL; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1		
XML Level 2	biom_2:FingerprintImageSegmentPositionSquare	Cardinality	0..5		
XML Level 3	biom_2:SegmentLeftHorizontalCoordinateValue	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

14.021_3

Finger Segment Position(s)

Right Horizontal Coordinate

Mnemonic	RHC			Conditionality	M↑
				Status	Active
Description	It is the horizontal offset in pixels to the right edge of the bounding box relative to the origin positioned in the upper left corner of the image.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	LHC < RHC < HLL; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1		
XML Level 2	biom_2:FingerprintImageSegmentPositionSquare	Cardinality	0..5		
XML Level 3	biom_2:SegmentRightHorizontalCoordinateValue	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

14.021_4

Finger Segment Position(s)

Top Vertical Coordinate

Mnemonic	TVC			Conditionality	M↑
				Status	Active
Description	The vertical offset (pixel counts down) to the top of the bounding box.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= TVC < VLL; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1		
XML Level 2	biom_2:FingerprintImageSegmentPositionSquare	Cardinality	0..5		
XML Level 3	biom_2:SegmentTopVerticalCoordinateValue	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

14.021_5

Finger Segment Position(s)

Bottom Vertical Coordinate

Mnemonic	BVC			Conditionality	M↑
				Status	Active
Description	It is the vertical offset from the upper left corner of the image down to the bottom of the bounding box. It is counted in pixels.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	TVC < BVC < VLL; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1		
XML Level 2	biom_2:FingerprintImageSegmentPositionSquare	Cardinality	0..5		
XML Level 3	biom_2:SegmentBottomVerticalCoordinateValue	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

14.022

NIST Quality Metric

Mnemonic	NQM		Conditionality	0	
			Status	Active	
Description	This ASCII field shall contain the NIST Fingerprint Image Quality (NFIQ) scores for the individual finger(s) derived from the slap impressions or individual rolled fingerprints. It consists of two information items. The first item is the finger number between one and ten. The second item is the quality score which is a quantitative expression of the predicted AFIS matcher accuracy performance of the fingerprint image. The scores range from "1" for the best quality im image. A "254" indicates that no score was ever computed while an entry of "255" shall indicate a failed attempt to calculate the image quality metric. These two information items are separated. Individual finger quality definitions are separated.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage		Cardinality	1..1	
XML Level 2	biom_2:FingerprintImageNISTQuality		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

14.022_0

NIST Quality Metric

Mnemonic	NQM_0		Conditionality	M↑	
			Status	New Active	
Description	This ASCII field shall contain the NIST Fingerprint Image Quality (NFIQ) scores for the individual finger(s) derived from the slap impressions or individual rolled fingerprints. It consists of two information items. The first item is the finger number between one and ten. The second item is the quality score which is a quantitative expression of the predicted AFIS matcher accuracy performance of the fingerprint image. The scores range from "1" for the best quality im image. A "254" indicates that no score was ever computed while an entry of "255" shall indicate a failed attempt to calculate the image quality metric. These two information items are separated. Individual finger quality definitions are separated.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	5	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage		Cardinality	1..1	
XML Level 2	biom_2:FingerprintImageNISTQuality		Cardinality	0..5	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-14: Variable-Resolution Fingerprint Image

Page 744 of 1037

14.022_1

NIST Quality Metric

Friction Ridge NIST Quality Position

Mnemonic	FRNP			Conditionality	M↑
				Status	Active
Description	The first information item of a NIST quality metric field indicating the friction ridge position.				
Field Min	1	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	1 <= FRNP <= 10 or FGP = 16 or 17; see Look Up Codes		
Code List	FRICTION RIDGE POSITION CODES				
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1		
XML Level 2	biom_2:FingerprintImageNISTQuality	Cardinality	0..5		
XML Level 3	biom_2:FingerPositionCode	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

14.022_2

NIST Quality Metric

NIST Image Quality Score

Mnemonic	IQS			Conditionality	M↑
				Status	Active
Description	This information item is the quality score which is a quantitative expression of the predicted AFIS matcher accuracy performance of the fingerprint image. The scores range from "1" for the best quality image, to "5" for the worst quality image. A "254" indicates that no score was ever computed while an entry of "255" shall indicate a failed attempt to calculate the image quality metric.				
Field Min	1	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	1 <= IQS <= 5 or IQS = 254 or 255; integer		
Code List	NIST IMAGE QUALITY SCORE CODES				
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1		
XML Level 2	biom_2:FingerprintImageNISTQuality	Cardinality	0..5		
XML Level 3	biom_2:NISTQualityMeasure	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

14.023

Segmentation Quality Metric

Mnemonic	SQM		Conditionality	0	
			Status	Active	
Description	This ASCII field provides a measure of estimated correctness regarding the accuracy of the location of the segmented finger within the right or left four finger or two thumbs slap image. For each segmented finger, this field shall contain four information items separated. The first information item is the finger number between one and ten. The other three items identify a quality score and the algorithm used to create the quality score. T recipient of the quality score to differentiate between quality scores generated by different algorithms and adjust for any differences in processing or analysis as necessary.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage		Cardinality	1..1	
XML Level 2	biom_2:FingerprintImageSegmentationQuality		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

14.023_0

Segmentation Quality Metric

Mnemonic	SQM_0		Conditionality	M↑	
			Status	New Active	
Description	This ASCII field provides a measure of estimated correctness regarding the accuracy of the location of the segmented finger within the right or left four finger or two thumbs slap image. For each segmented finger, this field shall contain four information items separated. The first information item is the finger number between one and ten. The other three items identify a quality score and the algorithm used to create the quality score. T recipient of the quality score to differentiate between quality scores generated by different algorithms and adjust for any differences in processing or analysis as necessary.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	5	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage		Cardinality	1..1	
XML Level 2	biom_2:FingerprintImageSegmentationQuality		Cardinality	0..5	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-14: Variable-Resolution Fingerprint Image

Page 746 of 1037

14.023_1

Segmentation Quality Metric

Friction Ridge Segment Quality Position

Mnemonic	FRQP			Conditionality	M↑
				Status	Active
Description	The first information item of a segmentation quality metric field indicating the friction ridge position.				
Field Min	1	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	1 <= FRQP <= 10 or FGP = 16 or 17; see Look Up Codes		
Code List	FRICTION RIDGE POSITION CODES				
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1		
XML Level 2	biom_2:FingerprintImageSegmentationQuality	Cardinality	0..5		
XML Level 3	biom_2:FingerPositionCode	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

14.023_2

Segmentation Quality Metric

Quality Value

Mnemonic	QVU			Conditionality	M↑
				Status	Active
Description	This information item shall contain the integer image quality score between 0 and 100 (inclusive) assigned to the image data by a quality algorithm. Higher values indicate better quality. An entry of "255" shall indicate a failed attempt to calculate a quality score. An entry of "254" shall indicate that no attempt to calculate a quality score was made.				
Field Min	1	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= QVU <= 100 or QVU = 254 or 255; integer		
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1		
XML Level 2	biom_2:FingerprintImageSegmentationQuality	Cardinality	0..5		
XML Level 3	biom_2:QualityValue	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

14.023_3

Segmentation Quality Metric

Algorithm Vendor Identification

Mnemonic	QAV			Conditionality	M↑
				Status	Active
Description	This information item shall specify the ID of the vendor of the quality algorithm used to calculate the quality score. This 4-digit hex value is assigned by IBIA and expressed as four ASCII characters. The IBIA shall maintain the Vendor Registry of CBEFF Biometric Organizations that will map the value in this field to a registered organization.				
Field Min	4	Occur Min	1		
Field Max	4	Occur Max	1		
Char Types	H	Special Chars	None		
Format	n/a	Constraints	0000 <= QAV <= FFFF		
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage			Cardinality	1..1
XML Level 2	biom_2:FingerprintImageSegmentationQuality			Cardinality	0..5
XML Level 3	biom_2:QualityAlgorithmVendorIdentification/nc:IdentificationID			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

14.023_4

Segmentation Quality Metric

Algorithm Product Identification

Mnemonic	QAP			Conditionality	M↑
				Status	Active
Description	This information item shall specify a numeric product code assigned by the vendor of the quality algorithm, which may be registered with the IBIA, but it is not required to be registered. It indicates which of the vendor's algorithms was used in the calculation of the quality score. This field contains the ASCII representation of the integer product code and should be within the range 1 to 65535.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	1 <= QAP <= 65535; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage			Cardinality	1..1
XML Level 2	biom_2:FingerprintImageSegmentationQuality			Cardinality	0..5
XML Level 3	biom_2:QualityAlgorithmProductIdentification/nc:IdentificationID			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

14.024

Fingerprint Quality Metric

Mnemonic	FQM		Conditionality	0	
			Status	Active	
Description	This ASCII field is used to specify one or more different metrics of fingerprint image quality score data for the image stored in this record. The meaning attributed to this metric must be defined and interpreted by the producer of the scoring algorithm or by the person or system used to assign the metric to the fingerprint image. The metric may be a predictor of AFIS matcher accuracy performance indicate a value associated with the quality of the fingerprint image for a particular function. This field may contain one or more subfields, each consisting of four information items separated. The first information item is the finger number. The other algorithm used to create the quality score. This information is useful to enable the recipient of the quality score to differentiate between quality scores generated by different algorithms and adjust for any differences in processing or analysis as needed				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage		Cardinality	1...1	
XML Level 2	biom_2:FingerprintImageQuality		Cardinality	0...1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

14.024_0

Fingerprint Quality Metric

Mnemonic	FQM_0		Conditionality	M↑	
			Status	Active	
Description	This ASCII field is used to specify one or more different metrics of fingerprint image quality score data for the image stored in this record. The meaning attributed to this metric must be defined and interpreted by the producer of the scoring algorithm or by the person or system used to assign the metric to the fingerprint image. The metric may be a predictor of AFIS matcher accuracy performance indicate a value associated with the quality of the fingerprint image for a particular function. This field may contain one or more subfields, each consisting of four information items separated. The first information item is the finger number. The other algorithm used to create the quality score. This information is useful to enable the recipient of the quality score to differentiate between quality scores generated by different algorithms and adjust for any differences in processing or analysis as needed				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	5	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage		Cardinality	1...1	
XML Level 2	biom_2:FingerprintImageQuality		Cardinality	0..5	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

14.024_1

Fingerprint Quality Metric

Friction Ridge Metric Position

Mnemonic	FRMP			Conditionality	M↑
				Status	Active
Description	The first information item of a quality metric field indicating the friction ridge position.				
Field Min	1	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	1 <= FRMP <= 10 or FGP = 16 or 17; see Look Up Codes		
Code List	FRICTION RIDGE POSITION CODES				
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1		
XML Level 2	biom_2:FingerprintImageQuality	Cardinality	0..5		
XML Level 3	biom_2:FingerPositionCode	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

14.024_2

Fingerprint Quality Metric

Quality Value

Mnemonic	QVU			Conditionality	M↑
				Status	Active
Description	This information item shall contain the integer image quality score between 0 and 100 (inclusive) assigned to the image data by a quality algorithm. Higher values indicate better quality. An entry of "255" shall indicate a failed attempt to calculate a quality score. An entry of "254" shall indicate that no attempt to calculate a quality score was made.				
Field Min	1	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= QUV <= 100 or QVU = 254 or 255; integer		
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1		
XML Level 2	biom_2:FingerprintImageQuality	Cardinality	0..5		
XML Level 3	biom_2:QualityValue	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

14.024_3

Fingerprint Quality Metric

Algorithm Vendor Identification

Mnemonic	QAV			Conditionality	M↑
				Status	Active
Description	This information item shall specify the ID of the vendor of the quality algorithm used to calculate the quality score. This 4-digit hex value is assigned by IBIA and expressed as four ASCII characters. The IBIA shall maintain the Vendor Registry of CBEFF Biometric Organizations that will map the value in this field to a registered organization.				
Field Min	4	Occur Min	1		
Field Max	4	Occur Max	1		
Char Types	H	Special Chars	None		
Format	n/a	Constraints	0000 <= QAV <= FFFF		
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1		
XML Level 2	biom_2:FingerprintImageQuality	Cardinality	0..5		
XML Level 3	biom_2:QualityAlgorithmVendorIdentification/nc:IdentificationID	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

14.024_4

Fingerprint Quality Metric

Algorithm Product Identification

Mnemonic	QAP			Conditionality	M↑
				Status	Active
Description	This information item shall specify a numeric product code assigned by the vendor of the quality algorithm, which may be registered with the IBIA, but it is not required to be registered. It indicates which of the vendor's algorithms was used in the calculation of the quality score. This field contains the ASCII representation of the integer product code and should be within the range 1 to 65535.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	1 <= QAP <= 65535; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1		
XML Level 2	biom_2:FingerprintImageQuality	Cardinality	0..5		
XML Level 3	biom_2:QualityAlgorithmProductIdentification/nc:IdentificationID	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

14.025

Alternate Finger Segment Position

Mnemonic	ASEG		Conditionality	0
			Status	Active
Description	<p>This ASCII field is an alternate approach to describing the locations for each of the image segments of the individual fingers within a flat image containing the capture of four simultaneous fingers or two simultaneous thumbs. This field uses an n-vertex polygon to encompass each finger image segment, where “n” is between 3 and 99. The order of the vertices must be in their consecutive order around the perimeter of the polygon, either clockwise or counterclockwise. No two verti location. The polygon side defined by the last subfield and the first subfield shall complete the polygon. The polygon must be a simple, plane figure with no sides crossing and no interior holes. This field shall consist of one to four subfields. Each sub between 1 and 10, the total number of vertices of the polygon encompassing the finger, and the set of consecutive vertices. Each vertex shall be represented as horizontal and vertical pixel offsets relative to the origin positioned in the upper left corne are the pixel counts to the right, and the vertical offsets (Y) are the pixel counts down from the origin.A minimum of three points is required to describe a finger location. The finger number, the number of vertices, each X coordinate, and each Y coordin Subfields representing each finger are separated.</p>			
Field Min	n/a	Occur Min	0	
Field Max	n/a	Occur Max	1	
Char Types	n/a	Special Chars	n/a	
Format	n/a	Constraints	n/a	
Code List				
Source	ANSI/NIST ITL 1-2013			
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1	
XML Level 2	biom_2:FingerprintImageSegmentPositionPolygon	Cardinality	0..1	
XML Level 3		Cardinality		
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0 Yes DoD EBTS 4.0 Yes

14.025_0

Alternate Finger Segment Position

Mnemonic	ASEG_0			Conditionality	M↑
				Status	New Active
Description	This ASCII field is an alternate approach to describing the locations for each of the image segments of the individual fingers within a flat image containing the capture of four simultaneous fingers or two simultaneous thumbs. This field uses an n-vertex polygon to encompass each finger image segment, where “n” is between 3 and 99. The order of the vertices must be in their consecutive order around the perimeter of the polygon, either clockwise or counterclockwise. No two verti location. The polygon side defined by the last subfield and the first subfield shall complete the polygon. The polygon must be a simple, plane figure with no sides crossing and no interior holes. This field shall consist of one to four subfields. Each sub between 1 and 10, the total number of vertices of the polygon encompassing the finger, and the set of consecutive vertices. Each vertex shall be represented as horizontal and vertical pixel offsets relative to the origin positioned in the upper left corne are the pixel counts to the right, and the vertical offsets (Y) are the pixel counts down from the origin.A minimum of three points is required to describe a finger location. The finger number, the number of vertices, each X coordinate, and each Y coordin Subfields representing each finger are separated.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	5		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1		
XML Level 2	biom_2:FingerprintImageSegmentPositionPolygon	Cardinality	0..5		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

14.025_1

Alternate Finger Segment Position

Friction Ridge Alternate Segment Position

Mnemonic	FRAS			Conditionality	M↑
				Status	Active
Description	The first information item of an alternate segment position field indicating the friction ridge position.				
Field Min	1	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	1 <= FRAS <= 10 or FGP = 16 or 17; see Look Up Codes		
Code List	FRICTION RIDGE POSITION CODES				
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1		
XML Level 2	biom_2:FingerprintImageSegmentPositionPolygon	Cardinality	0..5		
XML Level 3	biom_2:FingerPositionCode	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

14.025_2

Alternate Finger Segment Position

Number of Points

Mnemonic	NOP			Conditionality	M↑
				Status	Active
Description	Specifies the number of vertices.				
Field Min	1	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	3 <= NOP <= 99; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1		
XML Level 2	biom_2:FingerprintImageSegmentPositionPolygon	Cardinality	0..5		
XML Level 3	biom_2:PositionPolygonVertex	Cardinality	3..99		
XML Level 4	biom_2:PositionHorizontalCoordinateValue	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

14.025_3

Alternate Finger Segment Position

Horizontal Point Offset

Mnemonic	HPO			Conditionality	M↑
				Status	Active
Description	The pixel counts to the right.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= HPO <= HLL; integer		
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1		
XML Level 2	biom_2:FingerprintImageSegmentPositionPolygon	Cardinality	0..5		
XML Level 3	biom_2:PositionPolygonVertex	Cardinality	3..99		
XML Level 4	biom_2:PositionVerticalCoordinateValue	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

14.025_4

Alternate Finger Segment Position

Vertical Point Offset

Mnemonic	VPO	Conditionality	M↑
		Status	Active
Description	The pixel counts down from the origin.		
Field Min	1	Occur Min	1
Field Max	5	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	0 <= VPO <= VLL; integer
Code List			
Source	ANSI/NIST ITL 1-2013		
XML Level 1	biom:FingerImpressionImage	Cardinality	1...1
XML Level 2	biom_2:FingerprintImageSegmentPositionPolygon	Cardinality	0..5
XML Level 3	biom_2:PositionVerticalCoordinateValue	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

14.026

Simultaneous Capture

Mnemonic	SCF	Conditionality	O
		Status	Active
Description	This optional field allows the user to link together fingerprint images that were captured simultaneously. Note that this is different from the IDC. This is used, for instance, when individual flat print are captured on different platens simultaneously. Such images should not be stitched together for transmission as a single multiple-finger print image, but they should be coded with the same SCF value to indicate that they were captured simultaneously, and that there is little possibility of a mistaken f 1-based numeric index that is incremented for each simultaneously captured set of images, and shall be omitted otherwise.		
Field Min	1	Occur Min	0
Field Max	3	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	1 <= SCF <= 255; positive integer
Code List			
Source	ANSI/NIST ITL 1-2013		
XML Level 1	biom:FingerImpressionImage/biom:ImageCaptureDetail	Cardinality	1...1
XML Level 2	biom_2:CaptureIdentification/nc:IdentificationID	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

14.027

Stitched Image Flag

Mnemonic	SIF			Conditionality	D
				Status	Active
Description	This field signifies that images captured separately were stitched together to form a single image. This field is mandatory if an image has been stitched, and the value shall be set to 'Y'. Otherwise, this field shall not appear in the record.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars	None		
Format	n/a	Constraints	SIF = Y		
Code List	STITCHED IMAGE CODES				
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage			Cardinality	1..1
XML Level 2	biom_2:FingerprintImageStitchedIndicator			Cardinality	0..1
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

14.03

Device Monitoring Mode

Mnemonic	DMM			Conditionality	O
				Status	Active
Description	This field provides information describing the human monitoring operation of the image capture device. This field will contain an entry from [possible codes below] to indicate the monitoring mode of the biometric sample capture device.				
Field Min	7	Occur Min	0		
Field Max	10	Occur Max	1		
Char Types	A	Special Chars	None		
Format	n/a	Constraints	see Look Up Codes		
Code List	CAPTURE DEVICE MONITORING MODE CODES				
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage/biom:ImageCaptureDetail			Cardinality	1..1
XML Level 2	biom_2:CaptureDeviceMonitoringModeCode			Cardinality	0..1
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

14.031

Subject Acquisition Profile - Fingerprint

Mnemonic	FAP		Conditionality	0	
			Status	Active	
Description	The profile levels for fingerprint acquisition are optional and are based upon those listed in the Mobile ID Best Practice Recommendation.				
Field Min	2		Occur Min	0	
Field Max	2		Occur Max	1	
Char Types	N		Special Chars	None	
Format	n/a		Constraints	FAP = 10, 20, 30, 40, 50 or 60; integer	
Code List	FINGERPRINT ACQUISITION PROFILE CODES				
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage		Cardinality	1..1	
XML Level 2	biom_2:FingerprintImageAcquisitionProfileCode		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

14.046

Image Subject Condition

Mnemonic	SUB		Conditionality	0	
			Status	Active	
Description	This field is optional. There may be different values for SUB in different instances of Type-14 records. For example, some images may have been acquired antemortem, while others were acquired post-mortem. This field describes the condition of the subject				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	None	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom_2:SubjectExistentialDetails		Cardinality	0..1	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-14: Variable-Resolution Fingerprint Image

Page 757 of 1037

14.046_1

Image Subject Condition

Subject Status Code

Mnemonic	SSC			Conditionality	M↑
				Status	Active
Description	This information item is mandatory if this field is present. It is subject status code / SSC.				
Field Min	1	Occur Min	1		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars	None		
Format	n/a	Constraints	SSC = X, A, or D		
Code List	SUBJECT STATUS CODES				
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom_2:SubjectExistentialDetails			Cardinality	0..1
XML Level 2	biom_2:SubjectExistentialStatusCode			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

14.046_2

Image Subject Condition

Subject Body Status Code

Mnemonic	SBSC			Conditionality	D
				Status	Active
Description	This information item shall be entered if and only if SSC is D. It is subject body status code / SBSC. Its purpose is to indicate whether the information relates to an entire corpse or a separate body part.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	SBSC = 1 or 2		
Code List	SUBJECT BODY STATUS CODES				
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom_2:SubjectExistentialDetails			Cardinality	0..1
XML Level 2	biom_2:SubjectBodyStatusCode			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-14: Variable-Resolution Fingerprint Image

Page 758 of 1037

14.046_3

Image Subject Condition

Subject Body Class Code

Mnemonic	SBCC			Conditionality	D
				Status	Active
Description	This information item shall be entered if and only if SSC is D. It is subject body class code/ SBCC.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	SBCC = 1 or 2		
Code List	SUBJECT BODY CLASS CODES				
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom_2:SubjectExistentialDetails			Cardinality	0..1
XML Level 2	biom_2:SubjectBodyClassCode			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

14.047

Capture Organization Name

Mnemonic	CON			Conditionality	O
				Status	Active
Description	This field is optional. Note that this can be different from the agency entered in Field 14.004: Source agency / SRC and Field 14.993: Source agency name / SAN. SRC and SAN describe the agency that created the record. Since the record may have been forwarded the final destination, Field 1.008: Originating agency identifier / ORI is used to indicate the transmitting organization. See Section 7.6 for details about SRC, SAN, and ORI. For example, • The friction ridge prints are taken from a decedent's body in a examiner's office would be CON. • The local police department that would create the actual ANSI/NIST-ITL 1-2011 conformant record. Such an organization's code would be entered in Field 14.004: Source agency / SRC (for example NA54-X) and its name in Field name / SAN (for example New Artichoke Police). In many implementation domains, there are a limited number of transmission organizations that can send data. Therefore, the agency listed in SRC may send the transaction to another location that has access to This intermediary may add information to the transaction, as well. The final transmitting organization code is listed in Field 1.008: Originating agency identifier / ORI. Its name may be entered in Originating agency name /OAN in Field 1.017: Agency names				
Field Min	1	Occur Min	0		
Field Max	1000	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints	none		
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage/biom:ImageCaptureDetail			Cardinality	1..1
XML Level 2	biom:CaptureOrganization			Cardinality	1..1
XML Level 3	nc:OrganizationUnitName			Cardinality	0..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

14.2

Image Source Code

Mnemonic	ISC		Conditionality	0	
			Status	Active	
Description	This optional numeric field indicates to which source the included image belongs. This field allows images from multiple biometric sets that use the same Record Type to be distinguishable. Two different values are used for the Palmprint card to distinguish between the index finger image on the front of the card and the index finger that is part of the set of five finger images on the back of the card. Livescan palm capture should use value 2 and is not expected to contain any finger images.				
Field Min	1		Occur Min	0	
Field Max	1		Occur Max	1	
Char Types	N		Special Chars	None	
Format	n/a		Constraints	ISC = 1, 2, 3, or 4	
Code List	IMAGE SOURCE CODES				
Source	ANSI/NIST ITL 1-2013				
XML Level 1	nist-itl:UserDefinedFields		Cardinality	0..*	
XML Level 2	dod-ebts:ImageSourceCode		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

14.902

Annotated Information

Mnemonic	ANN		Conditionality	0	
			Status	Active	
Description	This optional field is used to store annotation, logging, or processing information associated with one or more processing algorithms or latent workstations (other than the FBI developed ULW).				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom_2:ProcessAnnotation		Cardinality	0...1	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-14: Variable-Resolution Fingerprint Image

Page 760 of 1037

14.902_0

Annotated Information

Mnemonic	ANN_0		Conditionality	M↑	
			Status	New Active	
Description	This optional field is used to store annotation, logging, or processing information associated with one or more processing algorithms or latent workstations (other than the FBI developed ULW).				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	*	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom_2:ProcessAnnotation		Cardinality	0..*	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

14.902_1

Annotated Information

Greenwich Mean Time

Mnemonic	GMT		Conditionality	M↑	
			Status	Active	
Description	This information item is the Greenwich Mean Time (GMT) when the annotation occurred. The data is formatted as YYYYMMDDhhmmssZ, where the Z is indicates the zone description of 0 hours. Time (GMT) units. This time is independent of the actual time zone where the time and date is recorded.				
Field Min	15		Occur Min	1	
Field Max	15		Occur Max	1	
Char Types	AN		Special Chars	None	
Format	YYYYMMDDHHMMSSZ - for Traditional Encoding		Constraints	Dependent upon encoding	
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom_2:ProcessAnnotation		Cardinality	0..*	
XML Level 2	biom_2:ProcessUTCDate/nc:DateTime		Cardinality	1..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-14: Variable-Resolution Fingerprint Image

Page 761 of 1037

14.902_2

Annotated Information

Processing Algorithm Name / Version

Mnemonic	NAV			Conditionality	M↑
				Status	Active
Description	The second information item of the Type-14 Annotated Information field shall contain an unformatted text string of up to 64 characters identifying the name and version of the processing algorithm or workstation.				
Field Min	1	Occur Min	1		
Field Max	Unlimited	Occur Max	1		
Char Types	U	Special Chars	n/a		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom_2:ProcessAnnotation			Cardinality	0..*
XML Level 2	biom_2:ProcessName			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

14.902_3

Annotated Information

Algorithm Owner

Mnemonic	OWN			Conditionality	M↑
				Status	Active
Description	The third information item Type-14 Annotated Information field shall contain an unformatted text string of up to 64 characters with the contact information for the organization that owns the processing algorithm or latent workstation.				
Field Min	1	Occur Min	1		
Field Max	64	Occur Max	1		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom_2:ProcessAnnotation			Cardinality	0..*
XML Level 2	biom_2:ProcessOwnerText			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-14: Variable-Resolution Fingerprint Image

Page 762 of 1037

14.902_4

Annotated Information

Process Description

Mnemonic	PRO			Conditionality	M↑
				Status	Active
Description	The fourth and final information item of the Type-14 Annotated Information field shall contain an unformatted text string of up to 255 characters describing a process or procedure applied to the sample in this Type-XX record.				
Field Min	1	Occur Min	1		
Field Max	255	Occur Max	1		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom_2:ProcessAnnotation			Cardinality	0..*
XML Level 2	biom_2:ProcessDescriptionText			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

14.903

Device Unique Identifier

Mnemonic	DUI			Conditionality	0
				Status	Active
Description	The DUI shall contain a string uniquely identifying the device or source of the data. This field shall be one of: Host PC MAC address, identified by the first character "M", or Host PC processor ID, identified by the first character "P". Note: ANSI/NIST ITL 1-2011 has deleted the options for "Serial number or No serial number" from Field 17.017, since it is available in the Make / Model / Serial Number field.				
Field Min	13	Occur Min	0		
Field Max	16	Occur Max	1		
Char Types	ANS	Special Chars	Any		
Format	n/a	Constraints	first character = M or P		
Code List	DEVICE UNIQUE IDENTIFIER CODES				
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage/biom:ImageCaptureDetail			Cardinality	1...1
XML Level 2	biom_2:CaptureDeviceIdentification/nc:IdentificationID			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-14: Variable-Resolution Fingerprint Image

Page 763 of 1037

14.904

Make/Model/Serial Number

Mnemonic	MMS	Conditionality	0
		Status	Active
Description	The MMS contains the make, model and serial number for the capture device. It shall consist of three information items. Each information item shall be 1 to 50 characters. Any or all information items may indicate that information is unknown with the value "0".		
Field Min	n/a	Occur Min	1
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	n/a
Format	n/a	Constraints	n/a
Code List			
Source	ANSI/NIST ITL 1-2013		
XML Level 1	biom:FingerImpressionImage/biom:ImageCaptureDetail	Cardinality	1...1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

14.904_1

Make/Model/Serial Number

Make

Mnemonic	MAK	Conditionality	M↑
		Status	Active
Description	The name of the manufacturer for the capture device.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	Any
Format	n/a	Constraints	None
Code List			
Source	ANSI/NIST ITL 1-2013		
XML Level 1	biom:FingerImpressionImage/biom:ImageCaptureDetail	Cardinality	1...1
XML Level 2	biom_2:CaptureDeviceMakeText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-14: Variable-Resolution Fingerprint Image

Page 764 of 1037

14.904_2

Make/Model/Serial Number

Model

Mnemonic	MOD	Conditionality	M↑
		Status	Active
Description	The model number for the capture device.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	Any
Format	n/a	Constraints	None
Code List			
Source	ANSI/NIST ITL 1-2013		
XML Level 1	biom:FingerImpressionImage/biom:ImageCaptureDetail	Cardinality	1...1
XML Level 2	biom_2:CaptureDeviceModelText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

14.904_3

Make/Model/Serial Number

Serial Number

Mnemonic	SER	Conditionality	M↑
		Status	Active
Description	The serial number for the capture device.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	Any
Format	n/a	Constraints	None
Code List			
Source	ANSI/NIST ITL 1-2013		
XML Level 1	biom:FingerImpressionImage/biom:ImageCaptureDetail	Cardinality	1...1
XML Level 2	biom_2:CaptureDeviceSerialNumberText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-14: Variable-Resolution Fingerprint Image

Page 765 of 1037

14.993

Source Agency Name

Mnemonic	SAN			Conditionality	0
				Status	Active
Description	This is an optional field. It may contain up to 125 Unicode characters. It is the name of the agency referenced in Field 14.004: Source agency / SRC for record types 9-99.				
Field Min	1	Occur Min	1		
Field Max	125	Occur Max	1		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage/biom:ImageCaptureDetail	Cardinality	1..1		
XML Level 2	biom:CaptureOrganization	Cardinality	1..1		
XML Level 3	nc:OrganizationName	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

14.995

Associated Context

Mnemonic	ASC			Conditionality	0
				Status	Active
Description	Optional field 14.995 is contained in biometric data sample Record Types 10 and above that may have instances of Record Type-21 linked to it. Record Type-21 stores images and/or recordings that are not the actual source of the biometric data contained in another Record Type, but do show the context of the biometric data. An example would be a photograph of a glass that had latent prints on it. This is because there may be multiple instances of associated context records associated with a single biometric sample.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom_2:AssociatedContext	Cardinality	0..1		
XML Level 2		Cardinality			
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

14.995_0

Associated Context

Mnemonic	ASC_0			Conditionality	M↑
				Status	New Active
Description	Optional field 14.995 is contained in biometric data sample Record Types 10 and above that may have instances of Record Type-21 linked to it. Record Type-21 stores images and/or recordings that are not the actual source of the biometric data contained in another Record Type, but do show the context of the biometric data. An example would be a photograph of a glass that had latent prints on it. This is because there may be multiple instances of associated context records associated with a single biometric sample.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	255		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom_2:AssociatedContext			Cardinality	0..255
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

14.995_1

Associated Context Number

Mnemonic	ACN			Conditionality	M↑
				Status	Active
Description	The first information item for the Associated Context field for a particular Record Type-21. This is mandatory for each Field 14.995, when the field is used. It contains an index to a particular instance of a Type-21 record in the transaction. This same index value appears in the appropriate instance of Record Type-21 as Field 21.021: Associated context number / CAN. The value of the CAN shall be a sequentially assigned a positive integer starting from one and incremented by one, not to exceed				
Field Min	1	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	1 <= ACN <= 255; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom_2:AssociatedContext			Cardinality	0..255
XML Level 2	biom_2:ContextIdentification/nc:IdentificationID			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

14.995_2

Associated Context Number

Associated Segment Position

Mnemonic	ASP			Conditionality	O↑
				Status	Active
Description	The first information item is the associated segment position / ASP. This provides a unique index to a segmentation.				
Field Min	1	Occur Min	0		
Field Max	2	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	1 <= ASP <= 99; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom_2:AssociatedContext			Cardinality	0..255
XML Level 2	biom_2:ImageSegmentIdentification/nc:IdentificationID			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

14.996

Hash

Mnemonic	HAS			Conditionality	O
				Status	Active
Description	Optional field 14.996, is designed for use in Record types 10 and above with a Field xx.999 storing the biometric data. It is comprised of 64 characters representing hexadecimal values. This field shall contain the hash value of the data in Field 14.999: Thus, each character may be a digit from "0" to "9" or a letter "A" through "F". See the latest version of the Federal Information Processing Standard 180, Secure Hash Standard for information on computing SHA-256 hashes. At the time of this standard's publication, FIPS 180-37 had been published. It is also possible to use Field xx.996 to contain the hash for data stored externally, which is referenced in Field 20.994: External file reference / EFR and /or Field 21.994: Ex The ability to store files externally is new to this version of the standard, and is only implemented for the two new record types referred to here. Use of the hash enables the receiver of the data to perform quick searches of large databases to determine database. It is not intended as an information assurance check. That is handled by Record Type-98: Information assurance record.				
Field Min	64	Occur Min	0		
Field Max	64	Occur Max	1		
Char Types	H	Special Chars	None		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom_2:ImageHashValue			Cardinality	0..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-14: Variable-Resolution Fingerprint Image

Page 768 of 1037

14.997

Source Representation

Mnemonic	SOR			Conditionality	0
				Status	Active
Description	This optional field 14.997 is allowed in biometric data sample Record Types 10 and above that could have the biometric sample derived from a source representation in Record Type-20. The biometric data is stored in Field 14.999.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom_2:SourceRepresentation			Cardinality	0..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

14.997_0

Source Representation

Mnemonic	SOR_0			Conditionality	M↑
				Status	New Active
Description	This optional field 14.997 is allowed in biometric data sample Record Types 10 and above that could have the biometric sample derived from a source representation in Record Type-20. The biometric data is stored in Field 14.999.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	255		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom_2:SourceRepresentation			Cardinality	0..255
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

14.997_1

Source Representation

Source Representation Number

Mnemonic	SRN	Conditionality	M↑
		Status	Active
Description	This is the first information item and is mandatory for each Field xx.997. It contains an index to a particular instance of a Type-20 record in the transaction. This same index value appears in the appropriate instance of Record Type-20 as Field 20.021: Source representation number / SRN. The value of the SRN shall be a sequentially assigned a positive integer starting from one and incremented by one, not to exce		
Field Min	1	Occur Min	1
Field Max	3	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	1 <= SRN <= 255; positive integer
Code List			
Source	ANSI/NIST ITL 1-2013		
XML Level 1	biom_2:SourceRepresentation	Cardinality	0..255
XML Level 2	biom_2:SourceIdentification/nc:IdentificationID	Cardinality	1..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

14.997_2

Source Representation

Reference Segment Position

Mnemonic	RSP	Conditionality	O↑
		Status	Active
Description	The first information item is the reference segment position / RSP. This provides a unique index to a segmentation.		
Field Min	1	Occur Min	0
Field Max	2	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	1 <= RSP <= 99; positive integer
Code List			
Source	ANSI/NIST ITL 1-2013		
XML Level 1	biom_2:SourceRepresentation	Cardinality	0..255
XML Level 2	biom_2:ImageSegmentIdentification/nc:IdentificationID	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

14.998

Geographic Sample Acquisition Location

Mnemonic	GEO			Conditionality	O		
				Status	Active		
Description	This optional field contains the location where the iris sample/original source/context information was acquired – not where it is stored.						
Field Min	n/a			Occur Min	1		
Field Max	n/a			Occur Max	1		
Char Types	n/a			Special Chars	n/a		
Format	n/a			Constraints	n/a		
Code List							
Source	ANSI/NIST ITL 1-2013						
XML Level 1	biom:FingerImpressionImage/biom:ImageCaptureDetail			Cardinality	1...1		
XML Level 2				Cardinality			
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

14.998_1

Geographic Sample Acquisition Location

Universal Time Entry

Mnemonic	UTE			Conditionality	O↑		
				Status	Active		
Description	The coordinated universal time (UTC) where the biometric sample was collected. This time is independent of the actual time zone where the time and date is recorded. The date is YYYYMMDDhhmmssZ, where the Z indicates the zone description of 0 hours. If sample collection time is unknown, set it to "00000000000000Z."						
Field Min	15			Occur Min	0		
Field Max	15			Occur Max	1		
Char Types	AN			Special Chars	None		
Format	YYYYMMDDHHMMSSZ - for Traditional Encoding			Constraints	Dependent upon encoding		
Code List							
Source	ANSI/NIST ITL 1-2013						
XML Level 1	biom:FingerImpressionImage/biom:ImageCaptureDetail			Cardinality	1...1		
XML Level 2	biom:CaptureLocation			Cardinality	0..1		
XML Level 3	biom:CaptureUTCDateTime/nc:DateTime			Cardinality	0...1		
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

14.998_2

Geographic Sample Acquisition Location

Latitude Degree Value

Mnemonic	LTD	Conditionality	D
		Status	Active
Description	The second information item is latitude degree value / LTD. This is a value that specifies the degree of latitude. The value shall be between -90 (inclusive) and +90 (inclusive). The degrees may be expressed as an integer (without a decimal) or a real number including decimals. If decimals are present, then minutes and seconds shall be empty. Examples: Buenos Aires, Argentina: -34 (with minutes LTM = 36) NIST, Gaithersburg, Maryland: 39.137627 (no LTM or LTS)		
Field Min	1	Occur Min	0
Field Max	9	Occur Max	1
Char Types	NS	Special Chars	Decimal,Minus Sign,Plus Sign
Format	n/a	Constraints	=-90 <= LTD <= 90
Code List			
Source	ANSI/NIST ITL 1-2013		
XML Level 1	biom:FingerImpressionImage/biom:ImageCaptureDetail	Cardinality	1...1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate (0...1)/nc:GeographicCoordinateLatitude (0...1)	Cardinality	0...1
XML Level 4	nc:LatitudeDegreeValue	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

14.998_3

Geographic Sample Acquisition Location

Latitude Minute Value

Mnemonic	LTM	Conditionality	D
		Status	Active
Description	This information item is latitude minute value / LTM. This is a value that specifies a minute of a degree. The value shall be between 0 (inclusive) to 60 (exclusive). The minute value may be expressed as an integer (without a decimal) or as a real number. If decimals are present then seconds shall be empty. Thus, the allowed special character is a period. The minute value can be empty, even if the degree value is an integer. LTM and LGM are co-conditional, so they shall both be present if either is present		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	NS	Special Chars	Decimal
Format	n/a	Constraints	0 <= LTM < 60
Code List			
Source	ANSI/NIST ITL 1-2013		
XML Level 1	biom:FingerImpressionImage/biom:ImageCaptureDetail	Cardinality	1...1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate (0...1)/nc:GeographicCoordinateLatitude (0...1)	Cardinality	0...1
XML Level 4	nc:LatitudeMinuteValue	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

14.998_4

Geographic Sample Acquisition Location

Latitude Second Value

Mnemonic	LTS	Conditionality	D
		Status	Active
Description	The fourth information item is the latitude second value / LTS. This is a value that specifies a second of a minute. The integer shall be 0 (inclusive) to 60 (exclusive). The second value is empty, even if the minute value is an integer.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	0 <= LTS < 60
Code List			
Source	ANSI/NIST ITL 1-2013		
XML Level 1	biom:FingerImpressionImage/biom:ImageCaptureDetail	Cardinality	1...1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate (0...1)/nc:GeographicCoordinateLatitude (0...1)	Cardinality	0...1
XML Level 4	nc:LatitudeSecondValue	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

14.998_5

Geographic Sample Acquisition Location

Longitude Degree Value

Mnemonic	LGD	Conditionality	D
		Status	Active
Description	The fifth information item is the longitude degree value / LGD. It is a value that specifies the degree of a longitude. The value shall be between -180 (inclusive) and +180 (inclusive). If LTD is present, then LGD shall be present. The degrees may be expressed as whole numbers (without a decimal) or real numbers including decimals. If decimals are present, then minutes and seconds are empty. Examples: Buenos Aires, Argentina: -58 (with minutes LGM = 22), NIST, Gaithersburg, Maryland: -77.216032 (no LGM or LGS)		
Field Min	1	Occur Min	0
Field Max	10	Occur Max	1
Char Types	NS	Special Chars	Decimal,Minus Sign,Plus Sign
Format	n/a	Constraints	-180 <= LGD <= 180
Code List			
Source	ANSI/NIST ITL 1-2013		
XML Level 1	biom:FingerImpressionImage/biom:ImageCaptureDetail	Cardinality	1...1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate (0...1)/nc:GeographicCoordinateLatitude (0...1)	Cardinality	0...1
XML Level 4	nc:LongitudeDegreeValue	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

14.998_6

Geographic Sample Acquisition Location

Longitude Minute Value

Mnemonic	LGM	Conditionality	D
		Status	Active
Description	The sixth information item is the longitude minute value / LGM. It is a value that specifies a minute of a degree. The value shall be from 0 (inclusive) to 60 (exclusive). The minute value may be expressed as an integer (without a decimal) or as a real number including decimals. If decimals are present then seconds shall not appear. The minute value is empty, even if the degree value is an integer. If LTM is present, then L		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	NS	Special Chars	Decimal
Format	n/a	Constraints	0 <= LGM < 60
Code List			
Source	ANSI/NIST ITL 1-2013		
XML Level 1	biom:FingerImpressionImage/biom:ImageCaptureDetail	Cardinality	1...1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate (0...1)/nc:GeographicCoordinateLatitude (0...1)	Cardinality	0...1
XML Level 4	nc:LongitudeMinuteValue	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

14.998_7

Geographic Sample Acquisition Location

Longitude Second Value

Mnemonic	LGS	Conditionality	D
		Status	Active
Description	The seventh information item is the longitude second value / LGS. This is a value that specifies a second of a minute. The integer shall be 0 (inclusive) to 60 (exclusive). The second value is empty, even if the minute value is an integer. If LTS is present, then LGS shall be present.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	0 <= LGS < 60
Code List			
Source	ANSI/NIST ITL 1-2013		
XML Level 1	biom:FingerImpressionImage/biom:ImageCaptureDetail	Cardinality	1...1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate (0...1)/nc:GeographicCoordinateLatitude (0...1)	Cardinality	0...1
XML Level 4	nc:LongitudeSecondValue	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-14: Variable-Resolution Fingerprint Image

Page 774 of 1037

14.998_8

Geographic Sample Acquisition Location

Elevation

Mnemonic	ELE	Conditionality	O
		Status	Active
Description	The eighth information item is elevation / ELE. It is expressed in meters. It is a numeric value. It is between -422 meters (Dead Sea) and 8848 meters (Mount Everest). Allowed special characters are the negative sign and the period.		
Field Min	3	Occur Min	1
Field Max	8	Occur Max	1
Char Types	NS	Special Chars	Minus Sign,Period
Format	n/a	Constraints	-422.000 < ELE < 8848.000; real number
Code List			
Source	ANSI/NIST ITL 1-2013		
XML Level 1	biom:FingerImpressionImage/biom:ImageCaptureDetail	Cardinality	1..1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	nc:LocationGeographicElevation	Cardinality	0..1
XML Level 4	nc:MeasurePoint	Cardinality	1..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

14.998_9

Geographic Sample Acquisition Location

Geodetic Datum Code

Mnemonic	GDC	Conditionality	O
		Status	Active
Description	The ninth information item is the geodetic datum code / GDC11. It is an alphanumeric value of 3 to 6 characters in length. This information item is used to indicate which coordinate system was used to represent the values in information items 2 through 7. information item, then the basis for the values entered in the first eight information items shall be WGS84, the code for the World Geodetic Survey 1984 version - WGS 84 (G873). See look up codes for values. If no entry is made in this information item, in the first eight information items shall be WGS84, the code for the World Geodetic Survey 1984 version - WGS 84 (G873). See look up codes for values.		
Field Min	2	Occur Min	0
Field Max	6	Occur Max	1
Char Types	AN	Special Chars	None
Format	n/a	Constraints	see Look Up Codes
Code List	GEOGRAPHIC COORDINATE DATUM CODES		
Source	ANSI/NIST ITL 1-2013		
XML Level 1	biom:FingerImpressionImage/biom:ImageCaptureDetail	Cardinality	1..1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate (0..1)/nc:GeographicCoordinateLatitude (0..1)	Cardinality	0..1
XML Level 4	biom:GeodeticDatumCoordinateSystemCode or biom:GeodeticDatumCoordinateSystemName	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-14: Variable-Resolution Fingerprint Image

Page 775 of 1037

14.998_10

Geographic Sample Acquisition Location

Geographic Coordinate Universal Transverse Mercator Zone

Mnemonic	GCM			Conditionality	D
				Status	Active
Description	It is an alphanumeric value of 2 to 3 characters. This is a one or two digit UTM zone number followed by the 8 degree latitudinal band designator (which is a single letter).				
Field Min	1	Occur Min	0		
Field Max	3	Occur Max	1		
Char Types	AN	Special Chars	None		
Format	n/a	Constraints	One or two digit UTM zone		
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage/biom:ImageCaptureDetail	Cardinality	1...1		
XML Level 2	biom:CaptureLocation	Cardinality	0..1		
XML Level 3	nc:LocationUTMCoordinate	Cardinality	0..1		
XML Level 4	nc:UTMGridZoneID	Cardinality	0..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

14.998_11

Geographic Sample Acquisition Location

Geographic Coordinate Universal Transverse Mercator Easting

Mnemonic	GCE			Conditionality	D
				Status	Active
Description	The eleventh information item is the geographic coordinate universal transverse Mercator easting / GCE. It is an integer of 1 to 6 digits.				
Field Min	1	Occur Min	0		
Field Max	6	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= GCE; integer		
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage/biom:ImageCaptureDetail	Cardinality	1...1		
XML Level 2	biom:CaptureLocation	Cardinality	0..1		
XML Level 3	nc:LocationUTMCoordinate	Cardinality	0..1		
XML Level 4	nc:UTMEastingValue	Cardinality	0..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-14: Variable-Resolution Fingerprint Image

Page 776 of 1037

14.998_12

Geographic Sample Acquisition Location

Geographic Coordinate Universal Transverse Mercator Northing

Mnemonic	GCN			Conditionality	D
				Status	Active
Description	The twelfth information item is the geographic coordinate universal transverse Mercator northing / GCN. It is an integer of 1 to 8 digits.				
Field Min	1	Occur Min	0		
Field Max	8	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= GCN; integer		
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage/biom:ImageCaptureDetail	Cardinality	1...1		
XML Level 2	biom:CaptureLocation	Cardinality	0..1		
XML Level 3	nc:LocationUTMCoordinate	Cardinality	0..1		
XML Level 4	nc:UTMNorthingValue	Cardinality	0..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

14.998_13

Geographic Sample Acquisition Location

Geographic Reference Text

Mnemonic	GRT			Conditionality	O
				Status	Active
Description	It is a free form text describing a street address or other physical location (such as 'Corner of Washington and Madison, Geneva, NY').				
Field Min	1	Occur Min	0		
Field Max	150	Occur Max	1		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2013				
XML Level 1	biom:FingerImpressionImage/biom:ImageCaptureDetail	Cardinality	1...1		
XML Level 2	biom:CaptureLocation	Cardinality	0..1		
XML Level 3	biom:GeographicLocationText	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

14.998_14

Geographic Sample Acquisition Location

Geographic Coordinate Other System Identifier

Mnemonic	OSI		Conditionality	O
			Status	Active
Description	A fourteenth optional information item geographic coordinate other system identifier / OSI allows for other coordinate systems. This information items specifies the system identifier. It is up to 10 characters in length. I Examples are: • MGRS (Militar Grid Reference System), • USNG (United States National Grid), • GARS (Global Area Reference System), • GEOREF (World Geographic Reference), • LANDMARK landmark (e.g. hydant) and position relative to the landmark.			
Field Min	1	Occur Min	1	
Field Max	10	Occur Max	1	
Char Types	U	Special Chars	Any	
Format	n/a	Constraints	None	
Code List				
Source	ANSI/NIST ITL 1-2013			
XML Level 1	biom:FingerImpressionImage/biom:ImageCaptureDetail	Cardinality	1..1	
XML Level 2	biom:CaptureLocation	Cardinality	0..1	
XML Level 3	biom:LocationAlternateGeographicSystemValue	Cardinality	0..1	
XML Level 4	biom:GeographicLocationSystemName	Cardinality	1..1	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0
				Yes
				DoD EBTS 4.0
				Yes

14.998_15

Geographic Sample Acquisition Location

Geographic Coordinate Other System Value

Mnemonic	OCV		Conditionality	D
			Status	Active
Description	A fifteenth optional information item, is the geographic coordinate other system value / OCV. It shall only be present if OSI is present in the record. It can be up to 126 characters in length. If OSI is LANDMARK, OCV is free text and may be up to 126 characters. For details on the formatting of OCV for the other coordinate systems shown in OSI as examples, see http://earth-info.nga.mil/GandG/coordsys/grids/referencesys.html .			
Field Min	1	Occur Min	0	
Field Max	126	Occur Max	1	
Char Types	U	Special Chars	Any	
Format	n/a	Constraints	None	
Code List				
Source	ANSI/NIST ITL 1-2013			
XML Level 1	biom:FingerImpressionImage/biom:ImageCaptureDetail	Cardinality	1..1	
XML Level 2	biom:CaptureLocation	Cardinality	0..1	
XML Level 3	biom:LocationAlternateGeographicSystemValue	Cardinality	0..1	
XML Level 4	biom:GeographicLocationText	Cardinality	0..1	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0
				Yes
				DoD EBTS 4.0
				Yes

14.999

Fingerprint Image

Mnemonic	DATA	Conditionality	D
		Status	Active
Description	This mandatory field contains the fingerprint image. See Section 7.2 of ANSI/NIST ITL 1-2011 for details.		
Field Min	1	Occur Min	0
Field Max	Unlimited	Occur Max	1
Char Types	B	Special Chars	None
Format	n/a	Constraints	None
Code List			
Source	ANSI/NIST ITL 1-2013		
XML Level 1	biom:FingerImpressionImage	Cardinality	1..1
XML Level 2	nc:BinaryBase64Object	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

15.001

Record Header

Mnemonic	LEN	Conditionality	M
		Status	Active
Description	The record header appears as the first field (xx.001) in each Record Type. It contains information particular to the encoding format chosen, in order to enable proper reading of the record. In Traditional encoding, this field contains the record length in bytes (including all information separators). In NIEM-conformant XML encoding, this field contains the RecordCategoryCode, which is the numeric representation of the Record Type.		
Field Min	T = 4; X = 1	Occur Min	1
Field Max	T = 8; X = 2	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	positive integer
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-15)		
XML Level 1	nist-itl:RecordCategoryCode	Cardinality	1..1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

15.002

Information Designation Character

Mnemonic	IDC		Conditionality	M
			Status	Active
Description	Each of the records present in a transaction, with the exception of the Type-1 record, shall include a field (xx.002) containing the information designation character (IDC). The value of the IDC shall be a sequentially assigned positive integer starting from zero and incremented by one up to a maximum of 99. IDC references are stated in Type-1 Field 1.003 Transaction content (CNT) and shall be used to relate information items in the CNT field of the Type-1 record to the other records in the transaction. Two or more records may share a single IDC solely to identify and link together records that pertain to different representations of the same biometric trait.			
Field Min	1	Occur Min	1	
Field Max	2	Occur Max	1	
Char Types	N	Special Chars	None	
Format	n/a	Constraints	0 <= IDC <= 99; positive integer	
Code List				
Source	ANSI/NIST ITL 1-2013 (Type-15)			
XML Level 1	nist-itl:ImageReferenceIdentification/nc:IdentificationID	Cardinality	1...1	
XML Level 2		Cardinality		
XML Level 3		Cardinality		
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0 Yes DoD EBTS 4.0 Yes

15.003

Impression Type

Mnemonic	IMP		Conditionality	M
			Status	Active
Description	This mandatory field shall indicate the manner by which the friction ridge print was obtained.			
Field Min	2	Occur Min	1	
Field Max	2	Occur Max	1	
Char Types	N	Special Chars	None	
Format	n/a	Constraints	IMP = 10 or 11 or 28 or 29	
Code List	FRICTION RIDGE IMPRESSION CODES			
Source	ANSI/NIST ITL 1-2013 (Type-15)			
XML Level 1	biom:PalmpImage_1(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1	
XML Level 2	dod-ebts:FrictionRidgeImageImpressionCaptureCategoryCode	Cardinality	1..1	
XML Level 3		Cardinality		
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0 Yes DoD EBTS 4.0 Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

15.004

Source Agency

Mnemonic	SRC		Conditionality	M
			Status	Active
Description	This is the identifier of the agency that actually created the record and supplied the information contained in it.			
Field Min	1	Occur Min	1	
Field Max	Unlimited	Occur Max	1	
Char Types	U	Special Chars	Any	
Format	n/a	Constraints	None	
Code List				
Source	ANSI/NIST ITL 1-2013 (Type-15)			
XML Level 1	biom:PalmprintImage_1(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1..1	
XML Level 2	biom_2:CaptureOrganization	Cardinality	1..1	
XML Level 3	nc:OrganizationIdentification/nc:IdentificationID	Cardinality	1..1	
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0 Yes DoD EBTS 4.0 Yes

15.005

Palmprint Capture Date

Mnemonic	PCD		Conditionality	M
			Status	Active
Description	This ASCII field shall contain the date that the palmprint image contained in the record was captured. The date shall appear as eight digits in the format YYYYMMDD.			
Field Min	Dependent on encoding	Occur Min	1	
Field Max	Dependent on encoding	Occur Max	1	
Char Types	N	Special Chars	None	
Format	YYYYMMDD	Constraints	Dependent upon encoding	
Code List				
Source	ANSI/NIST ITL 1-2013 (Type-15)			
XML Level 1	biom:PalmprintImage_1(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1..1	
XML Level 2	biom_2:CaptureDate/nc:Date	Cardinality	1..1	
XML Level 3		Cardinality		
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0 Yes DoD EBTS 4.0 Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

15.006

Horizontal Line Length

Mnemonic	HLL			Conditionality	D
				Status	Active
Description	HLL defines the number of pixels contained on a single horizontal line of the image. The maximum horizontal size is limited to 65,535 pixels in Record Types-4 and 8, and to 99,999 for other record types. The minimum value is 10 pixels. The total image size (HLL times VLL) must be able to be accommodated in Field xx.001 for Traditional encoding. This field is mandatory if an image is present in Field 17.999: Iris image data (DATA). Otherwise it is absent.				
Field Min	2	Occur Min	0		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	10 <= HLL <= 99999; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom:PalmprintImage_1	Cardinality	1...1		
XML Level 2	biom_2:ImageHorizontalLineLengthPixelQuantity	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

15.007

Vertical Line Length

Mnemonic	VLL			Conditionality	D
				Status	Active
Description	VLL defines the number of horizontal lines contained in the image. The maximum vertical size is limited to 65,535 pixels in Record Types-4 and 8, and to 99,999 for other record types. The minimum value is 10 pixels. This field is mandatory if an image is present in Field 17.999: Iris image data (DATA). Otherwise it is absent.				
Field Min	2	Occur Min	0		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	10 <= VLL <= 99999; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom:PalmprintImage_1	Cardinality	1...1		
XML Level 2	biom_2:ImageVerticalLineLengthPixelQuantity	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

15.008

Scale Units

Mnemonic	SLC		Conditionality	D			
			Status	Active			
Description	This field is the image sampling frequency (pixel density). A value of "1" shall indicate pixels per inch. A value of "2" shall indicate pixels per centimeter. A value of "0" in this field indicates that no scale is provided, and the quotient of THPS/TVPS shall provide the pixel aspect ratio. For contact exemplar friction ridge images, a value of 1 or 2 shall be specified. For a value of 1 or 2, the transmitted horizontal and vertical scales shall be the same. A value of 1 or 2 shall also be specified for latent friction ridge prints if the lifted latent print is transmitted directly from a scanner. If the latent print is contained in a photograph, a value of 1 or 2 shall be entered only if the image of the latent was captured with a scale measurement visible in the image and the pixels across an inch or centimeter can be calculated – given the known characteristics of the camera and its distance from the latent print. A value of 0 for a latent print indicates that the true ppi value of the image is not known. For non-contact images of body parts, SLC shall be set to 0 unless the object being imaged is a fixed distance from the capture device and the ppi or ppm values for the capture device are accurately known at that fixed distance. (An example might be an iris capture device with a very small effective capture zone). NGI-DOC-01078-10.0 - For A value of "0" in this field indicates that no scale is provided, and NGI will reject transactions containing this value.						
Field Min	1	Occur Min	0				
Field Max	1	Occur Max	1				
Char Types	N	Special Chars	None				
Format	n/a	Constraints	0 <= SLC <= 2; integer				
Code List	SCALE UNIT CODE						
Source	ANSI/NIST ITL 1-2013 (Type-15)						
XML Level 1	biom:PalmprintImage_1	Cardinality	1...1				
XML Level 2	biom_2:ImageScaleUnitsCode	Cardinality	0..1				
XML Level 3		Cardinality					
XML Level 4		Cardinality					
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

15.009

Transmitted Horizontal Pixel Scale

Mnemonic	THPS		Conditionality	D			
			Status	Active			
Description	This is the integer pixel density used in the horizontal direction of the image if SLC has a value of "1" or "2". If SLC has a value of "0", this information item shall contain the horizontal component of the pixel aspect ratio, up to 5 integer digits. For example, if the SLC value = 1, then the value of THPS could be '1000' for a 1000 ppi sensor. When using certain formats, such as PNG, conversion from ppm (or other scales) may result in a decimal value. Since these fields require integer values, rounding should be used. Any value greater than x.0 and less than x.5 would be rounded down to x, regardless of the number of significant digits to the right of the decimal.						
Field Min	1	Occur Min	0				
Field Max	5	Occur Max	1				
Char Types	N	Special Chars	None				
Format	n/a	Constraints	positive integer				
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-15)						
XML Level 1	biom:PalmprintImage_1	Cardinality	1...1				
XML Level 2	biom_2:ImageHorizontalPixelDensityValue	Cardinality	0..1				
XML Level 3		Cardinality					
XML Level 4		Cardinality					
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

15.01

Transmitted Vertical Pixel Scale

Mnemonic	TVPS	Conditionality	D
		Status	Active
Description	This is the integer pixel density used in the vertical direction of the image if SLC has a value of "1" or "2". If SLC has a value of "0", this information item shall contain the vertical component of the pixel aspect ratio, up to 5 integer digits. If SLC is 1 or 2, then TVPS shall equal THPS. When using certain formats, such as PNG, conversion from ppm (or other scales) may result in a decimal value. Since these fields require integer values, rounding up at .5 should be used. For example with the values 1.3, 1.5 and 1.8 the resulting TVPS values would be 1, 2, and 2.		
Field Min	1	Occur Min	0
Field Max	5	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	integer
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-15)		
XML Level 1	biom:PalmprintImage_1	Cardinality	1...1
XML Level 2	biom_2:ImageVerticalPixelDensityValue	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

15.011

Compression Algorithm

Mnemonic	CGA	Conditionality	D
		Status	Active
Description	This is a mandatory field. It shall specify the algorithm used to compress the transmitted color or grayscale images.		
Field Min	3	Occur Min	0
Field Max	5	Occur Max	1
Char Types	AN	Special Chars	None
Format	n/a	Constraints	see Lookup Codes
Code List	COMPRESSION CODES		
Source	ANSI/NIST ITL 1-2013 (Type-15)		
XML Level 1	biom:PalmprintImage_1	Cardinality	1...1
XML Level 2	biom_2:ImageCompressionAlgorithmText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

15.012

Bits Per Pixel

Mnemonic	BPX		Conditionality	D
			Status	Active
Description	This ASCII field shall contain the number of bits used to represent a pixel. This field shall contain an entry of "8" for normal grayscale values of "0" to "255" or each RGB color component. Any entry in this field greater than "8" shall represent a grayscale or color pixel component with increased precision. For color, BPX represents the total number of bits per pixel (not per color).			
Field Min	1	Occur Min	0	
Field Max	2	Occur Max	1	
Char Types	N	Special Chars	None	
Format	n/a	Constraints	positive integer	
Code List				
Source	ANSI/NIST ITL 1-2013 (Type-15)			
XML Level 1	biom:PalmprintImage_1	Cardinality	1..1	
XML Level 2	biom_2:ImageBitsPerPixelQuantity	Cardinality	0..1	
XML Level 3		Cardinality		
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0 Yes DoD EBTS 4.0 Yes

15.013

Friction Ridge Generalized Position

Mnemonic	FGP		Conditionality	M
			Status	Active
Description	This field is used in Record types dealing with friction ridges. It specifies which friction ridge biometric sample was collected. This field shall contain the palm print position that matches the palm print image. Valid codes range from 20 to 38, or 81 to 86228.			
Field Min	2	Occur Min	1	
Field Max	2	Occur Max	1	
Char Types	N	Special Chars	20 <= FGP <= 38 or 81 <= FGP <= 84; see Look Up Codes	
Format	n/a	Constraints	n/a	
Code List	FRICTION RIDGE POSITION CODES			
Source	ANSI/NIST ITL 1-2013 (Type-15)			
XML Level 1	biom:PalmprintImage_1	Cardinality	1..1	
XML Level 2	biom:PalmPositionCode	Cardinality	1..1	
XML Level 3		Cardinality		
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0 Yes DoD EBTS 4.0 Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

15.016

Scanned Horizontal Pixel Scale

Mnemonic	SHPS			Conditionality	0
				Status	Active
Description	This ASCII field shall specify the horizontal pixel density used for scanning providing the SLC field contains a "1" or a "2". Otherwise, it indicates the horizontal component of the pixel aspect ratio. This field is used if the transmission pixel scale differs from the original image scale, as listed in Transmitted horizontal pixel scale (THPS).				
Field Min	1	Occur Min	0		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom:PalmprintImage_1(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1		
XML Level 2	biom:CaptureHorizontalPixelDensityValue	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

15.017

Scanned Vertical Pixel Scale

Mnemonic	SVPS			Conditionality	0
				Status	Active
Description	This ASCII field shall specify the vertical pixel density used for scanning providing the SLC field contains a "1" or a "2". Otherwise, it indicates the vertical component of the pixel aspect ratio.				
Field Min	1	Occur Min	0		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom:PalmprintImage_1(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1		
XML Level 2	biom_2:CaptureVerticalPixelDensityValue	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

15.018

Amputated or Bandaged

Mnemonic	AMP		Conditionality	0	
			Status	Active	
Description	This optional field shall specify if one or more fingers are amputated or bandaged. This field shall consist of one subfield for each amputated or missing finger. Each subfield shall contain two information items.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom:PalmprintImage_1		Cardinality	1..1	
XML Level 2	biom:PalmprintImageMissingArea		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

15.018_0

Amputated or Bandaged

Subfields: Repeating sets of information items

Mnemonic	AMP_0		Conditionality	M↑	
			Status	New-Active	
Description	This optional field shall specify if one or more fingers are amputated or bandaged. This field shall consist of one subfield for each amputated or missing finger. Each subfield shall contain two information items.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	9	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom:PalmprintImage_1		Cardinality	1..1	
XML Level 2	biom:PalmprintImageMissingArea		Cardinality	0..9	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes		

15.018_1

Amputated or Bandaged

Friction Ridge Amputation or Bandage Position

Mnemonic	FRAP			Conditionality	M↑
				Status	Active
Description	The first information item of the amputated and bandaged field indicating the friction ridge position between 21 and 38 or 81 through 86. This information item is called the friction ridge amputated or bandaged position / FRAP to differentiate it from FGP.				
Field Min	1	Occur Min	1		
Field Max	1	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	21 <= FRAP <= 38 or 81 <= FRAP <= 84; see Look Up Codes		
Code List	PALM POSITION (NIST)				
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom:PalmprintImage_1	Cardinality	1..1		
XML Level 2	biom:PalmprintImageMissingArea	Cardinality	0..9		
XML Level 3	biom:PalmPositionCode	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

15.018_2

Amputated or Bandaged

Amputated or Bandaged Code

Mnemonic	ABC			Conditionality	M↑
				Status	Active
Description	This information item provides the code that describes the reason the finger's image is missing.				
Field Min	2	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	A	Special Chars	None		
Format	n/a	Constraints	ABC = XX or UP		
Code List	AMPUTATED OR BANDAGED CODE				
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom:PalmprintImage_1	Cardinality	1..1		
XML Level 2	biom:PalmprintImageMissingArea	Cardinality	0..9		
XML Level 3	biom:PalmMissingAreaReasonCode	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

15.02

Comment

Mnemonic	COM	Conditionality	0
		Status	Active
Description	The optional Comment field appears in many record types and may be used to insert free text information. It is not reserved exclusively for log-related information but has historically often been used for this purpose. It is limited to a maximum of 126 characters. This maximum size was established in order to maintain consistency across encodings. The maximum size differed in the 2007 and 2008 versions of the standard.		
Field Min	1	Occur Min	0
Field Max	126	Occur Max	1
Char Types	U	Special Chars	None
Format	n/a	Constraints	None
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-15)		
XML Level 1	biom:PalmprintImage_1	Cardinality	1..1
XML Level 2	biom_2:ImageCommentText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

15.021

Finger Segment Position

Mnemonic	SEG	Conditionality	D
		Status	New-Active
Description	Contains offsets to the locations of image segments containing the individual fingers within the flat images of simultaneous fingers from each hand or the two simultaneous thumbs. This field shall only be present if FGP = 20, 21, 23, 37, 38, 83 or 84 from as entered in Field 15.013: Friction ridge generalized position (FGP). The subfield occurs at least once, and may be repeated if more than one algorithm is used to segment the image.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	n/a
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-15)		
XML Level 1	biom_2:FingerprintImageSegmentPositionSquare	Cardinality	0..1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

15.021_0

Finger Segment Position

Subfields: Repeating sets of information items

Mnemonic	SEG_0			Conditionality	M↑
				Status	New-Active
Description	Contains offsets to the locations of image segments containing the individual fingers within the flat images of simultaneous fingers from each hand or the two simultaneous thumbs. This field shall only be present if FGP = 20, 21, 23, 37, 38, 83 or 84 from as entered in Field 15.013: Friction ridge generalized position (FGP). The subfield occurs at least once, and may be repeated if more than one algorithm is used to segment the image.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	17		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom_2:FingerprintImageSegmentPositionSquare			Cardinality	0..17
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

15.021_1

Finger Segment Position

Friction Ridge Segment Position

Mnemonic	FRSP			Conditionality	M↑
				Status	New-Active
Description	The first information item is the friction ridge segment position / FRSP with values of 22, 24 – 36, 81, 82, 85 or 86 selected. This information item is called the friction ridge segment position / FRSP to differentiate it from FGP.				
Field Min	1	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	FSRP = 22, 24-36, 81, 82, 85 or 86; integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom_2:FingerprintImageSegmentPositionSquare			Cardinality	0..17
XML Level 2	biom:PalmPositionCode			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-15: Variable-Resolution Palmprint Image

Page 790 of 1037

15.021_2

Finger Segment Position

Bottom Vertical Coordinate Value

Mnemonic	BVC			Conditionality	M↑
				Status	New-Active
Description	This field contained the vertical offset from the upper left corner of the image down to the bottom of the bounding box.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	TVC < BVC < VLL; integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom_2:FingerprintImageSegmentPositionSquare			Cardinality	0..17
XML Level 2	biom_2:SegmentBottomVerticalCoordinateValue			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

15.021_3

Finger Segment Position

Left Horizontal Coordinate Value

Mnemonic	LHC			Conditionality	M↑
				Status	New-Active
Description	This field described the horizontal offset in pixels to the left edge of the bounding box relative to the origin positioned in the upper left corner of the image.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 < LHC < HLL; integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom_2:FingerprintImageSegmentPositionSquare			Cardinality	0..17
XML Level 2	biom_2:SegmentLeftHorizontalCoordinateValue			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-15: Variable-Resolution Palmprint Image

Page 791 of 1037

15.021_4

Finger Segment Position

Right Horizontal Coordinate Value

Mnemonic	RHC			Conditionality	M↑
				Status	New-Active
Description	This field describes the horizontal offset in pixels to the right edge of the bounding box relative to the origin positioned in the upper left corner of the image.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	LHC < RHC < HLL; integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom_2:FingerprintImageSegmentPositionSquare			Cardinality	0..17
XML Level 2	biom_2:SegmentRightHorizontalCoordinateValue			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

15.021_5

Finger Segment Position

Top Vertical Coordinate Value

Mnemonic	TVC			Conditionality	M↑
				Status	New-Active
Description	This field contains the vertical offset (pixel counts down) to the top of the bounding box.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 < TVC < VLL; integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom_2:FingerprintImageSegmentPositionSquare			Cardinality	0..17
XML Level 2	biom_2:SegmentTopVerticalCoordinateValue			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

15.023

Scanned Vertical Pixel Scale

Mnemonic	SVPS			Conditionality	0
				Status	Active
Description	This ASCII field shall specify the vertical pixel density used for scanning providing the SLC field contains a "1" or a "2". Otherwise, it indicates the vertical component of the pixel aspect ratio. This field is used if the transmission pixel scale differs from the original image scale, as listed in Transmitted Vertical Pixel Scale (TVPS).				
Field Min	1	Occur Min	0		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom_2:CaptureVerticalPixelDensityValue			Cardinality	0..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

15.024

Palmprint Quality Metric

Mnemonic	PQM			Conditionality	M↑
				Status	Active
Description	This ASCII set is used to specify one or more different metrics of palm image quality score data for the image stored in this record. The meaning attributed to this metric must be defined and interpreted by the producer of the scoring algorithm or by the person or system used to assign the metric to the palm print image. This field may contain one or more subfields, each consisting of four information items. The first information item is the palm code. The other three items identify a quality score and the algorithm used to create the quality score. This information is useful to enable the recipient of the quality score to differentiate between quality scores generated by different algorithms and adjust for any differences in processing or analysis as necessary. Valid codes range from 20 to 38, and 81 to 86.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom:PalmpintImage_1			Cardinality	0..1
XML Level 2	biom:PalmpintImageQuality			Cardinality	0..9
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

15.024_0

Palmprint Quality Metric

Mnemonic	PQM_0	Conditionality	M↑
		Status	New-Active
Description	This ASCII set is used to specify one or more different metrics of palm image quality score data for the image stored in this record. The meaning attributed to this metric must be defined and interpreted by the producer of the scoring algorithm or by the person or system used to assign the metric to the palm print image. This field may contain one or more subfields, each consisting of four information items. The first information item is the palm code. The other three items identify a quality score and the algorithm used to create the quality score. This information is useful to enable the recipient of the quality score to differentiate between quality scores generated by different algorithms and adjust for any differences in processing or analysis as necessary. Valid codes range from 20 to 38, and 81 to 86.		
Field Min	n/a	Occur Min	0
Field Max	n/a	Occur Max	9
Char Types	N	Special Chars	n/a
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-15)		
XML Level 1	biom:PalmprintImage_1	Cardinality	1..1
XML Level 2	biom:PalmprintImageQuality	Cardinality	0..9
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes

15.024_1

Palmprint Quality Metric

Friction Ridge Metric Position

Mnemonic	FRMP	Conditionality	M↑
		Status	New-Active
Description	The first information item of a quality metric field indicating the friction ridge position. Valid codes range from 20 to 38, and 81 to 86		
Field Min	1	Occur Min	1
Field Max	2	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	20 <= FRMP <= 38 or 81 <= FRMP <= 86; positive integer
Code List	FRICTION RIDGE POSITION CODES		
Source	ANSI/NIST ITL 1-2013 (Type-15)		
XML Level 1	biom:PalmprintImage_1	Cardinality	1..1
XML Level 2	biom:PalmprintImageQuality	Cardinality	0..9
XML Level 3	biom:PalmPositionCode	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

15.024_2

Palmprint Quality Metric

Quality Value

Mnemonic	QVU			Conditionality	M↑
				Status	New-Active
Description	This information item shall contain the integer image quality score between 0 and 100 (inclusive) assigned to the image data by a quality algorithm. Higher values indicate better quality. An entry of "255" shall indicate a failed attempt to calculate a quality score. An entry of "254" shall indicate that no attempt to calculate a quality score was made.				
Field Min	1	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= QVU <= 100 or QVU = 254 or 255; integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom:PalmprintImage_1	Cardinality	1..1		
XML Level 2	biom:PalmprintImageQuality	Cardinality	0..9		
XML Level 3	biom_2: ImageQualityType	Cardinality	1..1		
XML Level 4	biom:QualityAlgorithmProductIdentification\nc:identificationType	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

15.024_3

Palmprint Quality Metric

Algorithm Vendor Identification

Mnemonic	QAV			Conditionality	M↑
				Status	New-Active
Description	This information item shall specify the ID of the vendor of the quality algorithm used to calculate the quality score. This 4-digit hex value is assigned by IBIA and expressed as four ASCII characters. The IBIA shall maintain the Vendor Registry of CBEFF Biometric Organizations that will map the value in this field to a registered organization.				
Field Min	4	Occur Min	1		
Field Max	4	Occur Max	1		
Char Types	H	Special Chars	None		
Format	n/a	Constraints	0000 <= QAV <= FFFF		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom:PalmprintImage_1	Cardinality	1..1		
XML Level 2	biom:PalmprintImageQuality	Cardinality	0..9		
XML Level 3	biom_2: ImageQualityType	Cardinality	1..1		
XML Level 4	biom_2:QualityValue	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

15.024_4

Palmprint Quality Metric

Algorithm Product Identification

Mnemonic	QAP		Conditionality	M↑
			Status	New-Active
Description	This information item shall specify a numeric product code assigned by the vendor of the quality algorithm, which may be registered with the IBIA, but it is not required to be registered. It indicates which of the vendor's algorithms was used in the calculation of the quality score. This field contains the ASCII representation of the integer product code and should be within the range 1 to 65535.			
Field Min	1	Occur Min	1	
Field Max	5	Occur Max	1	
Char Types	N	Special Chars	None	
Format	n/a	Constraints	1 <= QAP <= 65535; positive integer	
Code List				
Source	ANSI/NIST ITL 1-2013 (Type-15)			
XML Level 1	biom:PalmprintImage_1	Cardinality	1..1	
XML Level 2	biom:PalmprintImageQuality	Cardinality	0..9	
XML Level 3	biom_2: ImageQualityType	Cardinality	1..1	
XML Level 4	biom_2:QualityAlgorithmVendorIdentification\nc:IdentificationType	Cardinality	1..1	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0 Yes DoD EBTS 4.0 Yes

15.03

Device Monitoring Mode

Mnemonic	DMM		Conditionality	O
			Status	Active
Description	This field provides information describing the human monitoring operation of the image capture device. This field will contain an entry from to indicate the monitoring mode of the biometric sample capture device.			
Field Min	7	Occur Min	0	
Field Max	10	Occur Max	1	
Char Types	A	Special Chars	None	
Format	n/a	Constraints	see Lookup Values	
Code List	CAPTURE DEVICE MONITORING MODE CODE			
Source	ANSI/NIST ITL 1-2013 (Type-15)			
XML Level 1	biom:PalmprintImage_1(1..1)/biom_2:ImageCaptureDetail(1..1)	Cardinality	1..1	
XML Level 2	biom:CaptureDeviceMonitoringModeCode	Cardinality	0..1	
XML Level 3		Cardinality		
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0 Yes DoD EBTS 4.0 Yes

15.046

Image Subject Condition

Mnemonic	SUB		Conditionality	0			
			Status	New-Active			
Description	This field is optional. This field is particularly useful if the image is obtained from a deceased person. However, its use is not limited to such circumstances. Some implementation domains support the submission of fingerprints taken from deceased individuals as latent prints, due to the quality of the friction ridges and the resulting images. In such cases, SSC is specified as D. For latent images taken from a surface, the value is typically X. There may be different values for SUB in different instances of Type-15 records.						
Field Min	n/a	Occur Min	0				
Field Max	n/a	Occur Max	1				
Char Types	n/a	Special Chars	n/a				
Format		Constraints					
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-15)						
XML Level 1	biom:PalmprintImage_1	Cardinality					
XML Level 2	biom:SubjectExistentialDetails	Cardinality	0..1				
XML Level 3		Cardinality					
XML Level 4		Cardinality					
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

15.046_1

Image Subject Condition

Subject Status Code

Mnemonic	SSC		Conditionality	M↑			
			Status	New-Active			
Description	The first information item is mandatory if this field is present. It is subject status code (SSC).						
Field Min	1	Occur Min	1				
Field Max	1	Occur Max	1				
Char Types	A	Special Chars	None				
Format	n/a	Constraints	SSC = X, A or D				
Code List	SUBJECT STATUS CODE						
Source	ANSI/NIST ITL 1-2013 (Type-15)						
XML Level 1	biom:PalmprintImage_2	Cardinality					
XML Level 2	biom:SubjectExistentialDetails	Cardinality	0..1				
XML Level 3	biom:SubjectExistentialStatusCode	Cardinality	1..1				
XML Level 4		Cardinality					
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-15: Variable-Resolution Palmprint Image

Page 797 of 1037

15.046_2

Image Subject Condition

Subject Body Status Code

Mnemonic	SBSC			Conditionality	D
				Status	New-Active
Description	The second information item shall be entered if and only if SSC is D. It is subject body status code (SBSC). Its purpose is to indicate whether the information relates to an entire corpse or a separate body part.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	SBSC = 1 or 2		
Code List	SUBJECT BODY STATUS CODE				
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom:PalmprintImage_3	Cardinality			
XML Level 2	biom:SubjectExistentialDetails	Cardinality	0..1		
XML Level 3	biom:SubjectBodyStatusCode	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

15.046_3

Image Subject Condition

Subject Body Class Code

Mnemonic	SBCC			Conditionality	D
				Status	New-Active
Description	The third information item shall be entered if and only if SSC is D. It is subject body class code (SBCC).				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	SBCC = 1 or 2		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom:PalmprintImage_4	Cardinality			
XML Level 2	biom:SubjectExistentialDetails	Cardinality	0..1		
XML Level 3	biom:SubjectBodyClassCode	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

15.047

Capture Organization Name

Mnemonic	CON			Conditionality	0		
				Status	New-Active		
Description	This field is optional. Note that this can be different from the agency entered in Field 13.004: Source agency (SRC) and Field 13.993: Source agency name (SAN). SRC and SAN describe the agency that created the record. Since the record may have been forwarded by another agency to the final destination, Field 1.008: Originating agency identifier (ORI) is used to indicate the transmitting organization. In many implementation domains, there are a limited number of transmission organizations that can send data. Therefore, the agency listed in SRC may send the transaction to another location that has access rights to the final destination. This intermediary may add information to the transaction, as well. The final transmitting organization code is listed in Field 1.008: Originating agency identifier (ORI). Its name may be entered in Originating agency name (OAN) in Field 1.017: Agency names (ANM). The final transmitting organization code is listed in Field 1.008: Originating agency identifier / ORI. Its name may be entered in Originating agency name /OAN in Field 1.017: Agency names / ANM.						
Field Min	1			Occur Min	0		
Field Max	1000			Occur Max	1		
Char Types	U			Special Chars	None		
Format	n/a			Constraints	n/a		
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-15)						
XML Level 1	biom:PalmprintImage_1(1...1)/biom_2:ImageCaptureDetail(1...1)				Cardinality	1...1	
XML Level 2	nc:OrganizationUnitName				Cardinality	0..1	
XML Level 3					Cardinality		
XML Level 4					Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

15.2

Image Source Code

Mnemonic	ISC			Conditionality	0		
				Status	Active		
Description	This optional numeric field indicates to which source the included image belongs. This field allows images from multiple biometric sets that use the same record type to be distinguishable. Two different values are used for the Palmprint card to distinguish between the index finger image on the front of the card and the index finger that is part of the set of five finger images on the back of the card. Livescan palm capture should use value						
Field Min	0			Occur Min	0		
Field Max	2			Occur Max	*		
Char Types	N			Special Chars	None		
Format	n/a			Constraints	ISC = 1, 2, 3, or 4		
Code List	ISC CODE						
Source	NGI-DOC-01078-10.0 (Type-15)						
XML Level 1	fbi-ebts:ImageSourceCode				Cardinality	0...*	
XML Level 2					Cardinality		
XML Level 3					Cardinality		
XML Level 4					Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

15.902

Annotated Information

Mnemonic	ANN			Conditionality	M↑
				Status	Active
Description	This is an optional field, listing the operations performed on the original source in order to prepare it for inclusion in a biometric record type.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom:ProcessAnnotation			Cardinality	0..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

15.902_0

Annotated Information

Subfields: Repeating sets of information items

Mnemonic	ANN_0			Conditionality	D
				Status	New-Active
Description	This is an optional field, listing the operations performed on the original source in order to prepare it for inclusion in a biometric record type.				
Field Min	n/a		Occur Min	1	
Field Max	n/a		Occur Max	*	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom:ProcessAnnotation			Cardinality	0..*
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

15.902_1

Annotated Information

Greenwich Mean Time

Mnemonic	GMT			Conditionality	M↑
				Status	Active
Description	This information item is the Greenwich Mean Time (GMT) when the processing occurred. The data is formatted as YYYYMMDDhhmmssZ, where the Z is indicates the zone description of 0 hours. This time is independent of the actual time zone where the time and date is recorded.				
Field Min	dependent on encoding		Occur Min	1	
Field Max	dependent on encoding		Occur Max	1	
Char Types	AN		Special Chars	None	
Format	YYYYMMDDHHMMSSZ - for Traditional Encoding		Constraints		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom:ProcessAnnotation			Cardinality	0..*
XML Level 2	biom:ProcessUTCDate/nc:DateTime			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

15.902_2

Annotated Information

Processing Algorithm Name / Version

Mnemonic	NAV			Conditionality	M↑
				Status	Active
Description	This information item shall contain text identifying the name and version of the processing algorithm, application, procedure, or workstation				
Field Min	1		Occur Min	1	
Field Max	Unlimited		Occur Max	1	
Char Types	U		Special Chars	None	
Format	n/a		Constraints	None	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom:ProcessAnnotation			Cardinality	0..*
XML Level 2	biom:ProcessName			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

15.902_3

Annotated Information

Algorithm Owner

Mnemonic	OWN			Conditionality	M↑
				Status	Active
Description	This information item shall contain an unformatted text string of up to 64 characters with the contact information for the organization that owns the processing algorithm or latent workstation. Where there is no 'algorithm owner,' enter N/A.				
Field Min	1	Occur Min	1		
Field Max	64	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom:ProcessAnnotation	Cardinality	0..*		
XML Level 2	biom:ProcessOwnerText	Cardinality	1..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

15.902_4

Annotated Information

Process Description

Mnemonic	PRO			Conditionality	M↑
				Status	Active
Description	This information item field shall contain text describing a process or procedure applied to the sample in this Type-9 record.				
Field Min	1	Occur Min	0		
Field Max	255	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom:ProcessAnnotation	Cardinality	0..*		
XML Level 2	biom:ProcessDescriptionText	Cardinality	1..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

15.903

Device Unique Identifier

Mnemonic	DUI			Conditionality	O
				Status	Active
Description	The DUI shall contain a string uniquely identifying the device or source of the data. This field shall be one of the following: a Host PC MAC address (identified by the first character "M"), a Host PC processor ID (identified by the first character "P"). since it is available in the Make / Model / Serial Number field.				
Field Min	13	Occur Min	0		
Field Max	16	Occur Max	1		
Char Types	ANS	Special Chars	Any		
Format	n/a	Constraints	first character = M or P		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom:PalmprintImage_1(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1		
XML Level 2	biom_2:CaptureDeviceIdentification/nc:IdentificationID	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

15.904

Make/Model/Serial Number

Mnemonic	MMS			Conditionality	O
				Status	Active
Description	The MMS contains the make, model and serial number for the capture device. It shall consist of three information items. Each information item shall be 1 to 50 characters. Unknown information may be indicated with the value "0." Any or all information items may indicate that information is unknown with the value "0".				
Field Min	1	Occur Min	1		
Field Max	Unlimited	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom:PalmprintImage_1(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1		
XML Level 2		Cardinality			
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-15: Variable-Resolution Palmprint Image

Page 803 of 1037

15.904_1

Make/Model/Serial Number

Make

Mnemonic	MAK	Conditionality	M↑
		Status	Active
Description	The name of the manufacturer for the capture device.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	Any
Format	n/a	Constraints	None
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-15)		
XML Level 1	biom:PalmprintImage_1(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1
XML Level 2	biom_2:CaptureDeviceMakeText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

15.904_2

Make/Model/Serial Number

Model

Mnemonic	MOD	Conditionality	M↑
		Status	Active
Description	The model number for the capture device.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	Any
Format	n/a	Constraints	None
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-15)		
XML Level 1	biom:PalmprintImage_1(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1
XML Level 2	biom_2:CaptureDeviceModelText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-15: Variable-Resolution Palmprint Image

Page 804 of 1037

15.904_3

Make/Model/Serial Number

Serial Number

Mnemonic	SER	Conditionality	M↑
		Status	Active
Description	The serial number for the capture device.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	Any
Format	n/a	Constraints	None
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-15)		
XML Level 1	biom:PalmprintImage_1(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1
XML Level 2	biom_2:CaptureDeviceSerialNumberText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

15.993

Source Agency Name

Mnemonic	SAN	Conditionality	0
		Status	Active
Description	This is an optional field. It may contain up to 125 Unicode characters. It is the name of the agency referenced in Field xx.004: Source agency / SRC for record types 9-99.		
Field Min	1	Occur Min	0
Field Max	125	Occur Max	1
Char Types	U	Special Chars	Any
Format	n/a	Constraints	None
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-15)		
XML Level 1	biom:PalmprintImage_1(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1
XML Level 2	biom:CaptureOrganization	Cardinality	1..1
XML Level 3	nc:OrganizationName	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

15.995

Associated Context

Mnemonic	ASC			Conditionality	0
				Status	Active
Description	This optional field refers to one or more Type 21 Records with the same ACN. Type 21 Records contain images that are NOT used to derive the biometric data in Field 13.999: Latent friction ridge image (DATA) but that may be relevant to the collection of that data, such as general scenes of the area where a latent print was found.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom:AssociatedContext			Cardinality	0..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

15.995_0

Associated Context

Mnemonic	ASC_0			Conditionality	M↑
				Status	New-Active
Description	This optional field refers to one or more Type 21 Records with the same ACN. Type 21 Records contain images that are NOT used to derive the biometric data in Field 13.999: Latent friction ridge image (DATA) but that may be relevant to the collection of that data, such as general scenes of the area where a latent print was found.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	255		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom:AssociatedContext			Cardinality	0..255
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

15.995_1

Associated Context

Associated Context Number

Mnemonic	ACN			Conditionality	M↑
				Status	Active
Description	The first information item for the Associated Context field for a particular Record Type-21. This is mandatory for each Field xx.995, when the field is used. It contains an index to a particular instance of a Type-21 record in the transaction. This same index value appears in the appropriate instance of Record Type-21 as Field 21.021: Associated context number (CAN). The value of the CAN shall be a sequentially assigned a positive integer starting from one and incremented by one, not to exceed 255.				
Field Min	1	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	1 <= ACN <= 255; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom:AssociatedContext	Cardinality	0..255		
XML Level 2	biom_2:ContextIdentification/nc:IdentificationID	Cardinality	1..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

15.995_2

Associated Context

Associated Segment Position

Mnemonic	ASP			Conditionality	O↑
				Status	Active
Description	The first information item is the associated segment position (ASP). This provides a unique index to a segmentation.				
Field Min	1	Occur Min	0		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	n/a		
Format	n/a	Constraints	1 <= ASP <= 99		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom:AssociatedContext	Cardinality	0..255		
XML Level 2	biom_2:ImageSegmentIdentification/nc:IdentificationID	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

15.996

Hash

Mnemonic	HAS		Conditionality	0	
			Status	Active	
Description	Optional field xx.996, is designed for use in Record types 10 and above with a Field xx.999 storing the biometric data. It is comprised of 64 characters representing hexadecimal values. Thus, each character may be a digit from "0" to "9" or a letter "A" through "F". See the latest version of the Federal Information Processing Standard 180, Secure Hash Standard for information on computing SHA-256 hashes. At the time of this standard's publication, FIPS 180-37 had been published. It is also possible to use Field xx.996 to contain the hash for data stored externally, which is referenced in Field 20.994: External file reference (EFR) and/or Field 21.994: External file reference (EFR). The ability to store files externally is new to this version of the standard, and is only implemented for the two new record types referred to here. Use of the hash enables the receiver of the data to perform quick searches of large databases to determine if the data already exist in the database. It is not intended as an information assurance check. That is handled by Record Type-98: Information assurance record.				
Field Min	64		Occur Min	0	
Field Max	64		Occur Max	1	
Char Types	H		Special Chars	None	
Format	n/a		Constraints	None	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom_2:ImageHashValue		Cardinality	0..1	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

15.997

Source Representation

Source Representation Number

Mnemonic	SOR		Conditionality	0	
			Status	Active	
Description	This optional field refers to a representation in Record Type-20 with the same SRN from which the data in Field 13.999: Latent friction ridge image (DATA) was derived.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom:SourceRepresentation		Cardinality	0..1	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-15: Variable-Resolution Palmprint Image

Page 808 of 1037

15.997_0

Source Representation

Source Representation Number

Mnemonic	SOR_0			Conditionality	M↑
				Status	New-Active
Description	This optional field refers to a representation in Record Type-20 with the same SRN from which the data in Field 13.999: Latent friction ridge image (DATA) was derived.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	255		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom:SourceRepresentation			Cardinality	0..255
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

15.997_1

Source Representation

Source Representation Number

Mnemonic	SRN			Conditionality	M↑
				Status	Active
Description	This is the first information item and is mandatory for each Field xx.997. It contains an index to a particular instance of a Type-20 record in the transaction. This same index value appears in the appropriate instance of Record Type-20 as Field 20.021: Source representation number (SRN). The value of the SRN shall be a sequentially assigned a positive integer starting from one and incremented by one, not to exceed 255.				
Field Min	1	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	1 <= SRN <= 255; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom:SourceRepresentation			Cardinality	0..255
XML Level 2	biom:SourceIdentification/nc:IdentificationID			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

15.997_2

Source Representation

Reference Segment Position

Mnemonic	RSP			Conditionality	0↑		
				Status	Active		
Description	The first information item is the reference segment position (RSP). This provides a unique index to a segmentation.						
Field Min	1		Occur Min	0			
Field Max	2		Occur Max	1			
Char Types	N		Special Chars	None			
Format	n/a		Constraints	1 <= RSP <= 99; positive integer			
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-15)						
XML Level 1	biom:SourceRepresentation			Cardinality	0..255		
XML Level 2	biom:ImageSegmentIdentification/nc:IdentificationID			Cardinality	0..1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

15.998

Geographic Sample Acquisition Location

Mnemonic	GEO			Conditionality	0		
				Status	Active		
Description	This optional field contains the location where the iris sample/original source/context information was acquired – not where it is stored.						
Field Min	n/a		Occur Min	0			
Field Max	n/a		Occur Max	1			
Char Types	n/a		Special Chars	n/a			
Format	n/a		Constraints	n/a			
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-15)						
XML Level 1	biom:PalmprintImage_1(1...1)/biom_2:ImageCaptureDetail(1...1)			Cardinality	1...1		
XML Level 2	dod-ebts:CaptureLocation			Cardinality	0..1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-15: Variable-Resolution Palmprint Image

Page 810 of 1037

15.998_01

Geographic Sample Acquisition Location

Universal Time Entry

Mnemonic	UTE			Conditionality	O↑
				Status	Active
Description	The coordinated universal time (UTC) where the biometric sample was collected. This time is independent of the actual time zone where the time and date is recorded. The date is YYYYMMDDhhmmssZ, where the Z indicates the zone description of 0 hours. If sample collection time is unknown, set it to "00000000000000Z."				
Field Min	dependent on encoding	Occur Min	0		
Field Max	dependent on encoding	Occur Max	1		
Char Types	AN	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom:PalmpintImage_1(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1		
XML Level 2	biom:CaptureUTCDateTime/nc:DateTime	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

15.998_02

Geographic Sample Acquisition Location

Latitude Degree Value

Mnemonic	LTD			Conditionality	D
				Status	Active
Description	The second information item is latitude degree value (LTD). This is a value that specifies the degree of latitude. The value shall be between -90 (inclusive) and +90 (inclusive). The degrees may be expressed as an integer (without a decimal) or a real number including decimals. If decimals are present, then minutes and seconds shall be empty. Examples: Buenos Aires, Argentina: -34 (with minutes LTM = 36) NIST, Gaithersburg, Maryland: 39.137627 (no LTM or LTS)				
Field Min	1	Occur Min	1		
Field Max	9	Occur Max	1		
Char Types	NS	Special Chars	Decimal, Minus Sign, Plus Sign		
Format	n/a	Constraints	-90 < LTD < 90		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom:PalmpintImage_1(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1		
XML Level 2	biom:CaptureLocation	Cardinality	0..1		
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate (0...1)/nc:GeographicCoordinateLatitude	Cardinality	0..1		
XML Level 4	nc:LatitudeDegreeValue	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

15.998_03

Geographic Sample Acquisition Location

Latitude Minute Value

Mnemonic	LTM	Conditionality	D
		Status	Active
Description	This information item is latitude minute value (LTM). This is a value that specifies a minute of a degree. The value shall be between 0 (inclusive) to 60 (exclusive). The minute value may be expressed as an integer (without a decimal) or as a real number including decimals. If decimals are present then seconds shall be empty. Thus, the allowed special character is a period. The minute value can be empty, even if the degree value is an integer. LTM and LGM are co-conditional, so they shall both be present if either is present.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	NS	Special Chars	Decimal,Minus Sign,Plus Sign
Format	n/a	Constraints	0 <= LTM < 60
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-15)		
XML Level 1	biom:PalmprintImage_1(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate (0...1)/nc:GeographicCoordinateLatitude	Cardinality	0..1
XML Level 4	nc:LatitudeMinuteValue	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

15.998_04

Geographic Sample Acquisition Location

Latitude Second Value

Mnemonic	LTS	Conditionality	D
		Status	Active
Description	The fourth information item is the latitude second value (LTS). This is a value that specifies a second of a minute. The integer shall be 0 (inclusive) to 60 (exclusive). The second value is empty, even if the minute value is an integer.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	0 <= LTS < 60
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-15)		
XML Level 1	biom:PalmprintImage_1(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate (0...1)/nc:GeographicCoordinateLatitude	Cardinality	0..1
XML Level 4	nc:LatitudeSecondValue	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

15.998_05

Geographic Sample Acquisition Location

Longitude Degree Value

Mnemonic	LGD	Conditionality	D
		Status	Active
Description	The fifth information item is the longitude degree value (LGD). It is a value that specifies the degree of a longitude. The value shall be between -180 (inclusive) and +180 (inclusive). If LTD is present, then LGD shall be present. The degrees may be expressed as whole numbers (without a decimal) or real numbers including decimals. If decimals are present, then minutes and seconds are empty. Examples: Buenos Aires, Argentina: -58 (with minutes LGM = 22), NIST, Gaithersburg, Maryland: -77.216032 (no LGM or LGS)		
Field Min	1	Occur Min	0
Field Max	10	Occur Max	1
Char Types	NS	Special Chars	Decimal, Minus Sign, Plus Sign
Format	n/a	Constraints	-180 =< LGD =< 180
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-15)		
XML Level 1	biom:PalmprintImage_1(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1..1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate (0...1)/nc:GeographicCoordinateLatitude	Cardinality	0..1
XML Level 4	nc:LongitudeDegreeValue	Cardinality	1..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

15.998_06

Geographic Sample Acquisition Location

Longitude Minute Value

Mnemonic	LGM	Conditionality	D
		Status	Active
Description	The sixth information item is the longitude minute value (LGM). It is a value that specifies a minute of a degree. The value shall be from 0 (inclusive) to 60 (exclusive). The minute value may be expressed as an integer (without a decimal) or as a real number including decimals. If decimals are present then seconds shall not appear. The minute value is empty, even if the degree value is an integer. If LTM is present, then LGM shall be present.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	NS	Special Chars	Decimal
Format	n/a	Constraints	1 <= LGM < 60
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-15)		
XML Level 1	biom:PalmprintImage_1(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1..1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate (0...1)/nc:GeographicCoordinateLatitude	Cardinality	0..1
XML Level 4	nc:LongitudeMinuteValue	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-15: Variable-Resolution Palmprint Image

Page 813 of 1037

15.998_07

Geographic Sample Acquisition Location

Longitude Second Value

Mnemonic	LGS	Conditionality	D
		Status	Active
Description	The seventh information item is the longitude second value (LGS). This is a value that specifies a second of a minute. The integer shall be 0 (inclusive) to 60 (exclusive). The second value is empty, even if the minute value is an integer. If LTS is present, then LGS shall be present.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	0 <= LGS < 60
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-15)		
XML Level 1	biom:PalmpImage_1(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate(0...1)/nc:GeographicCoordinateLatitude	Cardinality	0..1
XML Level 4	nc:LongitudeSecondValue	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

15.998_08

Geographic Sample Acquisition Location

Elevation

Mnemonic	ELE	Conditionality	D
		Status	Active
Description	The eighth information item is elevation (ELE). It is expressed in meters. It is a numeric value. It is between -422 meters (Dead Sea) and 8848 meters (Mount Everest). Allowed special characters are the negative sign and the period.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	NS	Special Chars	Minus Sign,Period
Format	n/a	Constraints	-422.000 < ELE < 8848.000; real number
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-15)		
XML Level 1	biom:PalmpImage_1(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	nc:LocationGeographicElevation	Cardinality	0..1
XML Level 4	nc:MeasurePointValue	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-15: Variable-Resolution Palmprint Image

Page 814 of 1037

15.998_09

Geographic Sample Acquisition Location

Geodetic Datum Code

Mnemonic	GDC	Conditionality	D
		Status	Active
Description	The ninth information item is the geodetic datum code (GDC11). It is an alphanumeric value of 3 to 6 characters in length. This information item is used to indicate which coordinate system was used to represent the values in information items 2 through 7. If no entry is made in this information item, then the basis for the values entered in the first eight information items shall be WGS84, the code for the World Geodetic Survey 1984 version - WGS 84 (G873). See look up codes for values. If no entry is made in this information item, then the basis for the values entered in the first eight information items shall be WGS84, the code for the World Geodetic Survey 1984 version - WGS 84 (G873). See look up codes for values.		
Field Min	3	Occur Min	0
Field Max	6	Occur Max	1
Char Types	AN	Special Chars	None
Format	n/a	Constraints	see Look Up Codes
Code List	GEOGRAPHIC COORDINATE DATUM CODE		
Source	ANSI/NIST ITL 1-2013 (Type-15)		
XML Level 1	biom:PalmpImage_1(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate	Cardinality	0..1
XML Level 4	biom:GeodeticDatumCoordinateSystemCode or biom:GeodeticDatumCoordinateSystemName	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

15.998_10

Geographic Sample Acquisition Location

Geographic Coordinate Universal Transverse Mercator Zone

Mnemonic	GCM	Conditionality	D
		Status	Active
Description	It is an alphanumeric value of 2 to 3 characters. This is a one or two digit UTM zone number followed by the 8 degree latitudinal band designator (which is a single letter).		
Field Min	2	Occur Min	0
Field Max	3	Occur Max	1
Char Types	AN	Special Chars	None
Format	n/a	Constraints	One or two integers followed by a single letter. Valid latitudinal band designators include C through X, omitting I and O.
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-15)		
XML Level 1	biom:PalmpImage_1(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	nc:LocationUTMCoordinate	Cardinality	0..1
XML Level 4	nc:UTMGridZoneID	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-15: Variable-Resolution Palmprint Image

Page 815 of 1037

15.998_11

Geographic Sample Acquisition Location

Geographic Coordinate Universal Transverse Mercator Easting

Mnemonic	GCE			Conditionality	D
				Status	Active
Description	The eleventh information item is the geographic coordinate universal transverse Mercator easting (GCE). It is an integer of 1 to 6 digits.				
Field Min	1	Occur Min	0		
Field Max	6	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom:PalmprintImage_1(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1		
XML Level 2	biom:CaptureLocation	Cardinality	0..1		
XML Level 3	nc:LocationUTMCoordinate	Cardinality	0..1		
XML Level 4	nc:UTMEastingValue	Cardinality	0..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

15.998_12

Geographic Sample Acquisition Location

Geographic Coordinate Universal Transverse Mercator Northing

Mnemonic	GCN			Conditionality	D
				Status	Active
Description	The twelfth information item is the geographic coordinate universal transverse Mercator northing (GCN). It is an integer of 1 to 8 digits.				
Field Min	1	Occur Min	0		
Field Max	8	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom:PalmprintImage_1(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1		
XML Level 2	biom:CaptureLocation	Cardinality	0..1		
XML Level 3	nc:LocationUTMCoordinate	Cardinality	0..1		
XML Level 4	nc:UTMNorthingValue	Cardinality	0..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-15: Variable-Resolution Palmprint Image

Page 816 of 1037

15.998_13

Geographic Sample Acquisition Location

Geographic Reference Text

Mnemonic	GRT			Conditionality	O
				Status	Active
Description	It is a free form text describing a street address or other physical location (such as 'Corner of Washington and Madison, Geneva, NY').				
Field Min	1	Occur Min	1		
Field Max	150	Occur Max	1		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom:PalmprintImage_1(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1		
XML Level 2	biom:CaptureLocation	Cardinality	0..1		
XML Level 3	biom_2:LocationAlternateGeographicSystemValue	Cardinality	0..1		
XML Level 4	biom_2:GeographicLocationText	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

15.998_14

Geographic Sample Acquisition Location

Geographic Coordinate Other System Identifier

Mnemonic	OSI			Conditionality	O
				Status	Active
Description	A fourteenth optional information item geographic coordinate other system identifier (OSI) allows for other coordinate systems. This information items specifies the system identifier. It is up to 10 characters in length. Examples are: • MGRS (Military Grid Reference System), • USNG (United States National Grid), • GARS (Global Area Reference System), • GEOREF (World Geographic Reference), • LANDMARK landmark (e.g. hydant) and position relative to the landmark.				
Field Min	1	Occur Min	1		
Field Max	10	Occur Max	1		
Char Types	U	Special Chars	n/a		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-15)				
XML Level 1	biom:PalmprintImage_1(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1		
XML Level 2	biom:CaptureLocation	Cardinality	0..1		
XML Level 3	biom_2:LocationAlternateGeographicSystemValue	Cardinality	0..1		
XML Level 4	biom_2:GeographicLocationSystemName	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-15: Variable-Resolution Palmprint Image

Page 817 of 1037

15.998_15

Geographic Sample Acquisition Location

Geographic Coordinate Other System Value

Mnemonic	OCV	Conditionality	D
		Status	Active
Description	A fifteenth optional information item, is the geographic coordinate other system value (OCV). It shall only be present if OSI is present in the record. It can be up to 126 characters in length. If OSI is LANDMARK, OCV is free text and may be up to 126 characters. For details on the formatting of OCV for the other coordinate systems shown in OSI as examples, see http://earth-info.nga.mil/GandG/coordsys/grids/referencesys.html .		
Field Min	1	Occur Min	0
Field Max	126	Occur Max	1
Char Types	U	Special Chars	Any
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-15)		
XML Level 1	biom:PalmprintImage_1(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	biom_2:LocationAlternateGeographicSystemValue	Cardinality	0..1
XML Level 4	biom_2:GeographicLocationText	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

15.999

Palmprint Image

Mnemonic	DATA	Conditionality	D
		Status	Active
Description	This field contains the palm print image. It shall contain an image, unless Field 15.018: Amputated or bandaged / AMP has a value of "UP". In the latter case, the field is optional.		
Field Min	1	Occur Min	0
Field Max	Unlimited	Occur Max	1
Char Types	B	Special Chars	None
Format	n/a	Constraints	None
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-15)		
XML Level 1	biom:PalmprintImage_1	Cardinality	1...1
XML Level 2	nc:BinaryBase64Object	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

n/a

Capture Device Firmware Version Number (Sunset)

Mnemonic			Conditionality	n/a	
			Status	Retired	
Description	The firmware version number for the biometric capture device that was used to collect the associated biometric sample.				
Field Min	n/a		Occur Min	n/a	
Field Max	n/a		Occur Max	n/a	
Char Types	ANS		Special Chars	Any	
Format	n/a		Constraints	None	
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-15)				
XML Level 1			Cardinality		
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
		DoD EBTS 4.0	No		

n/a

Capture Time (Sunset)

Mnemonic			Conditionality	n/a	
			Status	Retired	
Description	This ASCII field shall contain the time in UTC that the biometric sample or contextual information contained in the record was captured. The time shall appear as 6 digits format HHMMSS with 'Z' being the zone designator for the zero UTC offset. The complete time must be a legitimate time.				
Field Min	n/a		Occur Min	n/a	
Field Max	n/a		Occur Max	n/a	
Char Types	AN		Special Chars	None	
Format	n/a		Constraints	None	
Code List					
Source	n/a				
XML Level 1			Cardinality		
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
		DoD EBTS 4.0	No		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

n/a

Digitization Time (Sunset)

Mnemonic			Conditionality	n/a	
			Status	Retired	
Description	The Greenwich Mean Time (GMT) when the image was digitized if different then the capture date in order for submission.				
Field Min	n/a		Occur Min	n/a	
Field Max	n/a		Occur Max	n/a	
Char Types	AN		Special Chars	None	
Format	n/a		Constraints	n/a	
Code List					
Source	n/a				
XML Level 1				Cardinality	
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
		DoD EBTS 4.0	No		

15.201

Capture Device Global Identifier (Sunset)

Mnemonic	DEV_GI		Conditionality	0	
			Status	Retired	
Description	This field shall contain a 16-byte string to indicate a global unique identifier for an image capture device.				
Field Min	16		Occur Min	0	
Field Max	16		Occur Max	1	
Char Types	ANS		Special Chars	Any	
Format	n/a		Constraints	None	
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-15)				
XML Level 1	n/a			Cardinality	
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Sunset
		DoD EBTS 4.0	No		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

17.001

Record Header

Mnemonic	LEN		Conditionality	M			
			Status	Active			
Description	The record header appears as the first field (xx.001) in each Record Type. It contains information particular to the encoding format chosen, in order to enable proper reading of the record. In Traditional encoding, this field contains the record length in bytes (including all information separators). In NIEM-conformant XML encoding, this field contains the RecordCategoryCode, which is the numeric representation of the Record Type.						
Field Min	Encoding Specific		Occur Min	1			
Field Max	Encoding Specific		Occur Max	1			
Char Types	Encoding Specific		Special Chars	None			
Format	n/a		Constraints	Dependent on encoding			
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-17)						
XML Level 1	nist-itl:RecordCategoryCode		Cardinality	1...1			
XML Level 2			Cardinality				
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

17.002

Information Designation Character

Mnemonic	IDC		Conditionality	M			
			Status	Active			
Description	Each of the records present in a transaction, with the exception of the Type-1 record, shall include a field (xx.002) containing the information designation character / IDC. The value of the IDC shall be a sequentially assigned positive integer starting from zero and incremented by one up to a maximum of 99. IDC references are stated in Type-1 Field 1.003 Transaction content (CNT) and shall be used to relate information items in the CNT field of the Type-1 record to the other records in the transaction. Two or more records may share a single IDC solely to identify and link together records that pertain to different representations of the same biometric trait.						
Field Min	1		Occur Min	1			
Field Max	2		Occur Max	1			
Char Types	N		Special Chars	None			
Format	n/a		Constraints	0 <= IDC <= 99; integer			
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-17)						
XML Level 1	nist-itl:ImageReferenceIdentification/nc:IdentificationID		Cardinality	1...1			
XML Level 2			Cardinality				
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-17: Iris Image Data

Page 821 of 1037

17.003

Eye Label

Mnemonic	ELR			Conditionality	M
				Status	Active
Description	This field shall contain an identifier for the eye represented by the image in the record. An entry of "0" in this field indicates that the image in this record is undefined. An entry of "1" in this field indicates that the image in this record is the subject's right eye. An entry of "2" in this field indicates that the image in this record is the subject's left eye.				
Field Min	1	Occur Min	1		
Field Max	1	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	ELR = 0,1 or 2		
Code List	FEATURE IDENTIFIER CODE				
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage(1...1)	Cardinality	1..1		
XML Level 2	biom_2:IrisEyePosition/biom:IrisEyePositionCode	Cardinality	1..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

17.004

Source Agency

Mnemonic	SRC			Conditionality	M
				Status	Active
Description	This is the identifier of the agency that actually created the record and supplied the information contained in it.				
Field Min	1	Occur Min	1		
Field Max	1	Occur Max	1		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1..1		
XML Level 2	biom_2:CaptureOrganization	Cardinality	1..1		
XML Level 3	nc:OrganizationIdentification/nc:IdentificationID	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

17.005

Iris Capture Date

Mnemonic	ICD			Conditionality	M
				Status	Active
Description	This mandatory field shall contain the date that the iris biometric data contained in the record was captured.				
Field Min	Encoding Specific		Occur Min	1	
Field Max	Encoding Specific		Occur Max	1	
Char Types	Encoding Specific		Special Chars	None	
Format	YYYYMMDD		Constraints		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage(1...1)/biom_2:ImageCaptureDetail(1...1)			Cardinality	1...1
XML Level 2	biom_2:CaptureDate/nc:Date			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

17.006

Horizontal Line Length

Mnemonic	HLL			Conditionality	D
				Status	Active
Description	HLL defines the number of pixels contained on a single horizontal line of the image. The maximum horizontal size is limited to 65,535 pixels in Record Types-4 and 8, and to 99,999 for other record types. The minimum value is 10 pixels. The total image size (HLL times VLL) must be able to be accommodated in Field xx.001 for Traditional encoding. This field is mandatory if an image is present in Field 17.999: Iris image data / DATA. Otherwise it is absent.				
Field Min	2		Occur Min	0	
Field Max	5		Occur Max	1	
Char Types	N		Special Chars	None	
Format	n/a		Constraints	10 <= HLL <= 99999; positive integer	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage			Cardinality	1...1
XML Level 2	biom_2:ImageHorizontalLineLengthPixelQuantity			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

17.007

Vertical Line Length

Mnemonic	VLL		Conditionality	D	
			Status	Active	
Description	VLL defines the number of horizontal lines contained in the image. The maximum vertical size is limited to 65,535 pixels in Record Types-4 and 8, and to 99,999 for other record types. The minimum value is 10 pixels. This field is mandatory if an image is present in Field 17.999: Iris image data / DATA. Otherwise it is absent.				
Field Min	2		Occur Min	0	
Field Max	5		Occur Max	1	
Char Types	N		Special Chars	None	
Format	n/a		Constraints	10 <= VLL <= 99999, positive integer	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage		Cardinality	1..1	
XML Level 2	biom_2:ImageVerticalLineLengthPixelQuantity		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

17.008

Scale Units

Mnemonic	SLC		Conditionality	D	
			Status	Active	
Description	The image sampling frequency (pixel density). A value of "1" shall indicate pixels per inch. A value of "2" shall indicate pixels per centimeter. A value of "0" in this field indicates that no scale is provided, and the quotient of THPS/TVPS shall provide the pixel aspect ratio.				
Field Min	1		Occur Min	0	
Field Max	1		Occur Max	1	
Char Types	N		Special Chars	None	
Format	n/a		Constraints	0 <= SLC <= 2, integer	
Code List	SCALE UNIT CODE				
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage		Cardinality	1..1	
XML Level 2	biom_2:ImageScaleUnitsCode		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

17.009

Transmitted Horizontal Pixel Scale

Mnemonic	THPS			Conditionality	D
				Status	Active
Description	This is the integer pixel density used in the horizontal direction of the image if SLC has a value of "1" or "2". If SLC has a value of "0", this information item shall contain the horizontal component of the pixel aspect ratio, up to 5 integer digits. For example, if the SLC value = 1, then the value of THPS could be '1000' for a 1000 ppi sensor.				
Field Min	1	Occur Min	0		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage	Cardinality	1..1		
XML Level 2	biom_2:ImageHorizontalPixelDensityValue	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

17.01

Transmitted Vertical Pixel Scale

Mnemonic	TVPS			Conditionality	D
				Status	Active
Description	This is the integer pixel density used in the vertical direction of the image if SLC has a value of "1" or "2". If SLC has a value of "0", this information item shall contain the vertical component of the pixel aspect ratio, up to 5 integer digits. If SLC is 1 or 2, then TVPS shall equal THPS.				
Field Min	1	Occur Min	0		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage	Cardinality	1..1		
XML Level 2	biom_2:ImageVerticalPixelDensityValue	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

17.011

Compression Algorithm

Mnemonic	CGA		Conditionality	D
			Status	Active
Description	This is a mandatory field. It shall specify the algorithm used to compress the transmitted color or grayscale images. While JPEG was allowed in prior versions of this standard, it shall not be allowed for new images. Implementers may want to support JPEG decoding for handling legacy images. The baseline JPEG algorithm (ISO/IEC 10918) shall not be used for Type-17 iris images. It has been shown that both false non-match and false match rates increase due to the presence of tiling artifacts introduced by JPEG's discrete cosine transform.			
Field Min	3	Occur Min	0	
Field Max	4	Occur Max	1	
Char Types	AN	Special Chars	None	
Format	n/a	Constraints	CGA = NONE, PNG, JP2 or JP2L	
Code List	COMPRESSION CODES			
Source	ANSI/NIST ITL 1-2013 (Type-17)			
XML Level 1	biom_2:IrisImage	Cardinality	1...1	
XML Level 2	biom_2:ImageCompressionAlgorithmText	Cardinality	0..1	
XML Level 3		Cardinality		
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0 Yes DoD EBTS 4.0 Yes

17.012

Bits Per Pixel

Mnemonic	BPX		Conditionality	D
			Status	Active
Description	This ASCII field shall contain the number of bits used to represent a pixel. This field shall contain an entry of "8" for normal grayscale values of "0" to "255" or each RGB color component. Any entry in this field greater than "8" shall represent a grayscale or color pixel component with increased precision.			
Field Min	1	Occur Min	0	
Field Max	2	Occur Max	1	
Char Types	N	Special Chars	None	
Format	n/a	Constraints	8 <= BPX <= 99, integer	
Code List				
Source	ANSI/NIST ITL 1-2013 (Type-17)			
XML Level 1	biom_2:IrisImage	Cardinality	1...1	
XML Level 2	biom_2:ImageBitsPerPixelQuantity	Cardinality	0..1	
XML Level 3		Cardinality		
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0 Yes DoD EBTS 4.0 Yes

17.013

Color Space

Mnemonic	CSP			Conditionality	D
				Status	Active
Description	It shall contain an entry from the lookup codes. If Field 17.025: Effective acquisition spectrum / EAS is set to "NIR" this field shall be set to "GRAY".				
Field Min	3	Occur Min	0		
Field Max	4	Occur Max	1		
Char Types	A	Special Chars	None		
Format	n/a	Constraints	see Lookup Values		
Code List	COLOR SPACE CODE				
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage	Cardinality	1..1		
XML Level 2	biom_2:ImageColorSpaceCode	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

17.014

Rotation Angle of Eye

Mnemonic	RAE			Conditionality	O
				Status	Active
Description	Indicates the in-plane rotation angle of the iris. Such rotation can be caused by head tilt, camera tilt, and also by the common natural rotation of the eye itself. The rotation angle of the eye encoded in this field is defined here in terms of roll of the subject's head. The angle is defined, and measured in degrees, as the angle between a line joining the pupil or iris centers of the left and right eyes, and the horizontal axis of the imaging system. The value "FFFF" indicates rotation angle of eye is undefined. The in-plane eye rotation angle shall be recorded as angle = round (65535 * angle / 360) modulo 65535. This is encoded as a hexadecimal value. For encoding angular orientation of an eye not directed toward the camera, see Field 17.041: Frontal gaze (GAZ). It may be difficult to estimate rotation using a monocular camera. In such cases, the rotation uncertainty encoded in Field 17.015: Rotation uncertainty (RAU) will be appropriately larger.				
Field Min	1	Occur Min	0		
Field Max	4	Occur Max	1		
Char Types	H	Special Chars	None		
Format	n/a	Constraints	0000 <= RAE <= FFFF		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage	Cardinality	1..1		
XML Level 2	biom:IrisEyeRotationAngleText	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

17.015

Rotation Uncertainty

Mnemonic	RAU			Conditionality	D
				Status	Active
Description	Indicates the uncertainty in the in-plane eye rotation given in Field 17.014: Rotation angle of eye (RAE). The rotation uncertainty is non-negative and equal to [round (65535 * uncertainty / 180)]. The uncertainty is measured in degrees and is the absolute value of maximum error. The value "FFFF" indicates that uncertainty is undefined. Note that this is encoded as a hexadecimal value. This field is mandatory if Field 17.014: Rotation angle of eye (RAE) is present.				
Field Min	1	Occur Min	0		
Field Max	4	Occur Max	1		
Char Types	H	Special Chars	None		
Format	n/a	Constraints	0000 <= RAE <= FFFF		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage	Cardinality	1..1		
XML Level 2	biom:IrisEyeRotationUncertaintyValueText	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

17.016

Image Property Code

Mnemonic	IPC			Conditionality	O
				Status	Active
Description	This set shall contain the image property code. It shall contain three information items. The first information item shall indicate the specific horizontal orientation. The second information item shall indicate the specific vertical orientation. The third information item shall indicate the specific scan type. Each information item shall be one character.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage(1..1)/biom:biom:IrisImageCapture(1..1)	Cardinality	0..1		
XML Level 2		Cardinality			
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

17.016_1

Image Property Code

Horizontal Orientation

Mnemonic	IHO	Conditionality	M↑
		Status	Active
Description	This field shall be one of: "0" for Undefined, "1" for Base, or "2" for Flipped. "Base" orientation refers to images corresponding to the view facing the subject, where the nasal side of subject's left eye or outer edge of the subject's right eye is on the left side the of image. "Flipped" orientation refers to images where the orientation is opposite from that described for "Base".		
Field Min	1	Occur Min	1
Field Max	1	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	0 <= IHO <= 2, integer
Code List	IMAGE ORIENTATION CODE		
Source	ANSI/NIST ITL 1-2013 (Type-17)		
XML Level 1	biom_2:IrisImage(1...1)/biom:biom:IrisImageCapture(1...1)	Cardinality	0..1
XML Level 2	biom:IrisImageHorizontalOrientationCode	Cardinality	1..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

17.016_2

Image Property Code

Vertical Orientation

Mnemonic	IVO	Conditionality	M↑
		Status	Active
Description	This shall be one of: "0" for Undefined, "1" for Base, or "2" for Flipped. "Base" orientation refers to images where the superior (top) edge of the eye is at the top of the image. "Flipped" orientation refers to images where the orientation is opposite from that described for "Base".		
Field Min	1	Occur Min	1
Field Max	1	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	0 <= IVO <= 2, integer
Code List	IMAGE ORIENTATION CODE		
Source	ANSI/NIST ITL 1-2013 (Type-17)		
XML Level 1	biom_2:IrisImage(1...1)/biom:biom:IrisImageCapture(1...1)	Cardinality	0..1
XML Level 2	biom:IrisImageVerticalOrientationCode	Cardinality	1..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

17.016_3

Image Property Code

Specific Scan Type

Mnemonic	IST			Conditionality	M↑		
				Status	Active		
Description	This shall be one of: "0" for Undefined and "1" for Progressive. "Progressive" indicates that the image was captured using progressive scanning, in which case all image lines are generated sequentially. "2" for Interlace Frame, or "3" for Interlace fields are deprecated and shall not be used in records claiming conformance to this version of the standard.						
Field Min	1		Occur Min	1			
Field Max	1		Occur Max	1			
Char Types	N		Special Chars	None			
Format	n/a		Constraints	IST = 0 or 1; X = biom:ImageScanCategoryCodeType			
Code List	SCAN TYPE CODE						
Source	ANSI/NIST ITL 1-2013 (Type-17)						
XML Level 1	biom_2:IrisImage(1...1)/biom:biom:IrisImageCapture(1...1)			Cardinality	0..1		
XML Level 2	biom:IrisImageScanCategoryCode			Cardinality	1..1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

17.017

Device Unique Identifier

Mnemonic	DUI			Conditionality	O		
				Status	Active		
Description	The DUI shall contain a string uniquely identifying the device or source of the data. This field shall be one of: Host PC MAC address, identified by the first character "M", or Host PC processor ID, identified by the first character "P". Note: ANSI/NIST ITL 1-2011 has deleted the options for "Serial number or No serial number" from Field 17.017, since it is available in the Make / Model / Serial Number field.						
Field Min	13		Occur Min	0			
Field Max	16		Occur Max	1			
Char Types	ANS		Special Chars	Any			
Format	n/a		Constraints	first character = M or P			
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-17)						
XML Level 1	biom_2:IrisImage(1...1)/biom_2:ImageCaptureDetail(1...1)			Cardinality	1...1		
XML Level 2	biom:CaptureDeviceIdentification/nc:IdentificationID			Cardinality	0..1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-17: Iris Image Data

Page 830 of 1037

17.019

Make/Model/Serial Number

Mnemonic	MMS	Conditionality	O
		Status	Active
Description	The MMS contains the make, model and serial number for the capture device. It shall consist of three information items. Each information item shall be 1 to 50 characters. Unknown information may be indicated with the value "0." Any or all information items may indicate that information is unknown with the value "0".		
Field Min	n/a	Occur Min	1
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	n/a
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-17)		
XML Level 1	biom_2:IrisImage(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

17.019_1

Make/Model/Serial Number

Make

Mnemonic	MAK	Conditionality	M↑
		Status	Active
Description	The name of the manufacturer for the capture device.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	Any
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-17)		
XML Level 1	biom_2:IrisImage(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1
XML Level 2	biom_2:CaptureDeviceMakeText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

17.019_2

Make/Model/Serial Number

Model

Mnemonic	MOD	Conditionality	M↑
		Status	Active
Description	The model number for the capture device.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	Any
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-17)		
XML Level 1	biom_2:IrisImage(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1
XML Level 2	biom_2:CaptureDeviceModelText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

17.019_3

Make/Model/Serial Number

Serial Number

Mnemonic	SER	Conditionality	M↑
		Status	Active
Description	The serial number for the capture device.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	Any
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-17)		
XML Level 1	biom_2:IrisImage(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1
XML Level 2	biom_2:CaptureDeviceSerialNumberText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

17.02

Eye Color

Mnemonic	ECL	Conditionality	0
		Status	Active
Description	This field shall specify the subject's eye color or 'XXX' if it is unknown from the image (as is the case with infra-red images).		
Field Min	3	Occur Min	0
Field Max	3	Occur Max	1
Char Types	A	Special Chars	None
Format	n/a	Constraints	see Lookup Values
Code List	ALPHA EYE COLOR CODE		
Source	ANSI/NIST ITL 1-2013 (Type-17)		
XML Level 1	biom_2:IrisImage	Cardinality	1..1
XML Level 2	biom:IrisEyeColorAttributeCode	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

17.021

Comment

Mnemonic	COM	Conditionality	0
		Status	Active
Description	The optional Comment field appears in many record types and may be used to insert free text information. It is not reserved exclusively for log-related information but has historically often been used for this purpose. It is limited to a maximum of 126 characters. This maximum size was established in order to maintain consistency across encodings. The maximum size differed in the 2007 and 2008 versions of the standard.		
Field Min	1	Occur Min	0
Field Max	126	Occur Max	1
Char Types	U	Special Chars	Any
Format	n/a	Constraints	
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-17)		
XML Level 1	biom_2:IrisImage	Cardinality	1..1
XML Level 2	biom_2:ImageCommentText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

17.022

Scanned Horizontal Pixel Scale

Mnemonic	SHPS			Conditionality	0		
				Status	Active		
Description	This ASCII field shall specify the horizontal pixel density used for scanning providing the SLC field contains a "1" or a "2". Otherwise, it indicates the horizontal component of the pixel aspect ratio. This field is used if the transmission pixel scale differs from the original image scale, as listed in Transmitted horizontal pixel scale (THPS).						
Field Min	1			Occur Min	0		
Field Max	5			Occur Max	1		
Char Types	N			Special Chars	None		
Format	n/a			Constraints	positive integer		
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-17)						
XML Level 1	biom_2:IrisImage(1...1)/biom_2:ImageCaptureDetail(1...1)				Cardinality	1..1	
XML Level 2	biom:CaptureHorizontalPixelDensityValue				Cardinality	0..1	
XML Level 3					Cardinality		
XML Level 4					Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

17.023

Scanned Vertical Pixel Scale

Mnemonic	SVPS			Conditionality	0		
				Status	Active		
Description	This ASCII field shall specify the vertical pixel density used for scanning providing the SLC field contains a "1" or a "2". Otherwise, it indicates the vertical component of the pixel aspect ratio. This field is used if the transmission pixel scale differs from the original image scale, as listed in Transmitted vertical pixel scale (TVPS).						
Field Min	1			Occur Min	0		
Field Max	5			Occur Max	1		
Char Types	N			Special Chars	None		
Format	n/a			Constraints	positive integer		
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-17)						
XML Level 1	biom_2:IrisImage(1...1)/biom_2:ImageCaptureDetail(1...1)				Cardinality	1..1	
XML Level 2	biom:CaptureVerticalPixelDensityValue				Cardinality	0..1	
XML Level 3					Cardinality		
XML Level 4					Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

17.024

Image Quality Score

Mnemonic	IQS		Conditionality	0	
			Status	Active	
Description	This ASCII field shall specify a quality score data for the iris image stored in this record. Each subfield shall contain three information items. They identify a quality score and the algorithm used to create the quality score. This information is useful to enable the recipient of the quality score to differentiate between quality scores generated by different algorithms and adjust for any differences in processing or analysis as necessary.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage		Cardinality	1...1	
XML Level 2	biom_2:ImageQuality		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

17.024

Image Quality Score

Mnemonic	IQS_0		Conditionality	M↑	
			Status	New-Active	
Description	This ASCII field shall specify a quality score data for the iris image stored in this record. Each subfield shall contain three information items. They identify a quality score and the algorithm used to create the quality score. This information is useful to enable the recipient of the quality score to differentiate between quality scores generated by different algorithms and adjust for any differences in processing or analysis as necessary.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	9	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage		Cardinality	1...1	
XML Level 2	biom_2:ImageQuality		Cardinality	0..9	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes		

17.024_1

Image Quality Score

Quality Value

Mnemonic	QVU	Conditionality	M↑
		Status	Active
Description	This information item shall contain the integer image quality score between 0 and 100 (inclusive) assigned to the image data by a quality algorithm. Higher values indicate better quality. An entry of "255" shall indicate a failed attempt to calculate a quality score. An entry of "254" shall indicate that no attempt to calculate a quality score was made.		
Field Min	1	Occur Min	1
Field Max	3	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	0 <= QVU <= 100 or QVU = 254 or 255, integer
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-17)		
XML Level 1	biom_2:IrisImage	Cardinality	1..1
XML Level 2	biom_2:ImageQuality	Cardinality	0..9
XML Level 3	biom_2:QualityAlgorithmProductIdentification/nc:IdentificationID	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

17.024_2

Image Quality Score

Algorithm Vendor Identification

Mnemonic	QAV	Conditionality	M↑
		Status	Active
Description	This information item shall specify the ID of the vendor of the quality algorithm used to calculate the quality score. This 4-digit hex value is assigned by IBIA and expressed as four ASCII characters. The IBIA shall maintain the Vendor Registry of CBEFF Biometric Organizations that will map the value in this field to a registered organization.		
Field Min	4	Occur Min	1
Field Max	4	Occur Max	1
Char Types	H	Special Chars	None
Format	n/a	Constraints	0000 <= QAV <= FFFF
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-17)		
XML Level 1	biom_2:IrisImage	Cardinality	1..1
XML Level 2	biom_2:ImageQuality	Cardinality	0..9
XML Level 3	biom_2:QualityValue	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

17.024_3

Image Quality Score

Algorithm Product Identification

Mnemonic	QAP			Conditionality	M↑
				Status	Active
Description	This information item shall specify a numeric product code assigned by the vendor of the quality algorithm, which may be registered with the IBIA, but it is not required to be registered. It indicates which of the vendor's algorithms was used in the calculation of the quality score. This field contains the ASCII representation of the integer product code and should be within the range 1 to 65535.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	<= QAP <= 65535, positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage	Cardinality	1..1		
XML Level 2	biom_2:ImageQuality	Cardinality	0..9		
XML Level 3	biom_2:QualityAlgorithmVendorIdentification/nc:IdentificationID	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

17.025

Effective Acquisition Spectrum

Mnemonic	EAS			Conditionality	0
				Status	Active
Description	This field indicates the acquisition spectrum used in capturing the iris image. The acquisition spectrum is the effective acquisition spectrum, which is limited by both the lighting spectrum and the spectrum limitations of the acquisition device: it is defined by the overlap of the two spectra. This field contains an alphabetic entry selected from the column "Value" in Look Up Code list.				
Field Min	3	Occur Min	0		
Field Max	9	Occur Max	1		
Char Types	A	Special Chars	None		
Format	n/a	Constraints	see Lookup Values		
Code List	LIGHTING SPECTRUM ACQUISITION CODE				
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage	Cardinality	1..1		
XML Level 2	biom:IrisImageAcquisitionLightingSpectrum	Cardinality	0..1		
XML Level 3	biom:AcquisitionLightingSpectrumCode	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

17.026

Iris Diameter

Mnemonic	IRD		Conditionality	0	
			Status	Active	
Description	This field shall specify the expected iris diameter in pixels.				
Field Min	2		Occur Min	0	
Field Max	4		Occur Max	1	
Char Types	N		Special Chars	None	
Format	n/a		Constraints	10 < IRD < 9999; positive integer	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage		Cardinality	1..1	
XML Level 2	biom:IrisDiameterPixelQuantity		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

17.027

Specified Spectrum Value

Mnemonic	SSV		Conditionality	D	
			Status	Active	
Description	This field shall only be present if Field 17.025: Effective acquisition spectrum (EAS) has a value of 'DEFINED'. It is comprised of two information items:				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage		Cardinality	1..1	
XML Level 2	biom:IrisImageAcquisitionLightingSpectrum		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-17: Iris Image Data

Page 838 of 1037

17.027_1

Specified Spectrum Value

Spectrum Lower Bound

Mnemonic	LOW	Conditionality	M↑
		Status	Active
Description	It is a three digit entry indicating the lower frequency bound in nm.		
Field Min	3	Occur Min	1
Field Max	4	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	500 <= LOW, positive integer evenly divisible by 10
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-17)		
XML Level 1	biom_2:IrisImage	Cardinality	1..1
XML Level 2	biom:IrisImageAcquisitionLightingSpectrum	Cardinality	0..1
XML Level 3	biom:AcquisitionLightingSpectrumLowerMeasure	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

17.027_2

Specified Spectrum Value

Spectrum Upper Bound

Mnemonic	HIG	Conditionality	M↑
		Status	Active
Description	It is a three digit entry indicating the upper frequency bound in nm.		
Field Min	3	Occur Min	1
Field Max	4	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	510 <= HIG, positive integer evenly divisible by 10
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-17)		
XML Level 1	biom_2:IrisImage	Cardinality	1..1
XML Level 2	biom:IrisImageAcquisitionLightingSpectrum	Cardinality	0..1
XML Level 3	biom:AcquisitionLightingSpectrumUpperMeasure	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

17.028

Damaged or Missing Eye

Mnemonic	DME			Conditionality	O
				Status	Active
Description	This optional field shall specify if one or both eyes are unable to provide usable iris images. The eye position is specified in Field 17.003: Eye Label / ELR . This field shall contain a code from Look Up Codes. "UC" should be entered if the eye is physically present, but a usable iris image cannot be captured. An example is when the eye is swollen shut due to injury.				
Field Min	2	Occur Min	0		
Field Max	2	Occur Max	1		
Char Types	A	Special Chars	None		
Format	n/a	Constraints	DME = MA or UC		
Code List	MISSING AND DAMAGED EYE CODE				
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage	Cardinality	1..1		
XML Level 2	biom:IrisImageMissingReasonCode	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

17.03

Device Monitoring Mode

Mnemonic	DMM			Conditionality	O
				Status	Active
Description	This field provides information describing the human monitoring operation of the image capture device. This field will contain an entry from [possible codes below] to indicate the monitoring mode of the biometric sample capture device.				
Field Min	7	Occur Min	0		
Field Max	10	Occur Max	1		
Char Types	A	Special Chars	None		
Format	n/a	Constraints	see Lookup Values		
Code List	CAPTURE DEVICE MONITORING MODE CODE				
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage(1..1)/biom_2:ImageCaptureDetail(1..1)	Cardinality	1..1		
XML Level 2	biom:CaptureDeviceMonitoringModeCode	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

17.031

Subject Acquisition Profile - IRIS

Mnemonic	IAP		Conditionality	0	
			Status	Active	
Description	This optional field lists the IAP level associated with the iris acquisition device. The BPR was developed prior to the 2011 version of the standard. This version of the ANSI/NIST-ITL standard reflects research associated with the IREX study which was performed after the release of the BPR. The storage format specified in the BPR for all profile levels is 'Raw' as specified in ISO/IEC 19794-6 and Record Type-17 of the ANSI/NIST-ITL standard. 'Raw' corresponds to ISF code level 2 and has dimensions 640 x 480. This is the size output by most deployed iris acquisition systems. It is the display resolution for the Video Graphics Array (VGA). The iris diameter requirements of the BPR shall be adhered to if the IAP level is specified in the Type-17 record.				
Field Min	2		Occur Min	0	
Field Max	2		Occur Max	1	
Char Types	N		Special Chars	None	
Format	n/a		Constraints	IAP = 20, 30 or 40	
Code List	IRIS SUBJECT ACQUISITION PROFILE CODE				
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage		Cardinality	1..1	
XML Level 2	biom:IrisImageAcquisitionProfileCode		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

17.032

Iris Storage Format

Mnemonic	ISF		Conditionality	0	
			Status	Active	
Description	This mandatory field shall indicate the storage format of the iris image. ISF format code 1 is designated for high resolution outputs. ISF level 2 is the format output in most commercial iris acquisition systems and corresponds to the dimensions of the Video Graphics Array (VGA).				
Field Min	1		Occur Min	0	
Field Max	1		Occur Max	1	
Char Types	N		Special Chars	None	
Format	n/a		Constraints	ISF = 1, 2, 3 or 7	
Code List	IRIS STORAGE FORM CODE				
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage		Cardinality	1..1	
XML Level 2	biom:IrisImageStorageFormatCode		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-17: Iris Image Data

Page 841 of 1037

17.033

Iris Pupil Boundary

Mnemonic	IPB			Conditionality	0
				Status	Active
Description	This optional field defines the pupillary boundary, between the iris and pupil. Some paths in Record Type-17: Iris image record can be a circle or ellipse. A circle only requires 2 points to define it. An ellipse requires 3 points to define it.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage			Cardinality	1..1
XML Level 2	biom:IrisImageIrisPupilBoundary			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

17.033_1

Boundary Code

Mnemonic	BYC			Conditionality	M↑
				Status	Active
Description	Defines the shape of a boundary of a feature within an image.				
Field Min	1		Occur Min	1	
Field Max	1		Occur Max	1	
Char Types	A		Special Chars	None	
Format	n/a		Constraints	BYC = C, E or P; see Look Up Codes	
Code List	BOUNDARY DEFINITION CODE				
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage			Cardinality	1..1
XML Level 2	biom:IrisImageIrisPupilBoundary			Cardinality	0..1
XML Level 3	biom:IrisBoundaryShapeCode			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

17.033_2

Iris Pupil Boundary

Number of Points

Mnemonic	NOP			Conditionality	M↑
				Status	Active
Description	Specifies the number of vertices.				
Field Min	1	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	2 <= NOP <= 99; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage	Cardinality	1..1		
XML Level 2	biom:IrisImageIrisPupilBoundary	Cardinality	0..1		
XML Level 3	biom:ImageFeatureVertexQuantity	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

17.033_3

Iris Pupil Boundary

Horizontal Point Offset

Mnemonic	HPO			Conditionality	M↑
				Status	Active
Description	The pixel counts to the right. HPO and VPO information items are repeated as pairs, in order by point following the path – for a total of NOP pairs.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= HPO < HLL; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage	Cardinality	1..1		
XML Level 2	biom:IrisImageIrisPupilBoundary	Cardinality	0..1		
XML Level 3	biom:ImageFeatureVertex	Cardinality	2..99		
XML Level 4	biom:PositionHorizontalCoordinateValue	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-17: Iris Image Data

Page 843 of 1037

17.033_4

Iris Pupil Boundary

Vertical Point Offset

Mnemonic	VPO			Conditionality	M↑
				Status	Active
Description	The pixel counts down from the origin. HPO and VPO information items are repeated as pairs, in order by point following the path – for a total of NOP pairs.				
Field Min	1	Occur Min	0		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= VPO < VLL, positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage	Cardinality	1..1		
XML Level 2	biom:IrisImageIrisPupilBoundary	Cardinality	0..1		
XML Level 3	biom:ImageFeatureVertex	Cardinality	2..99		
XML Level 4	biom:PositionVerticalCoordinateValue	Cardinality	0..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

17.034

Iris Sclera Boundary

Mnemonic	ISB			Conditionality	O
				Status	Active
Description	This optional field defines the limbic boundary, between the iris and sclera.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage	Cardinality	1..1		
XML Level 2	biom:IrisImageIrisScleraBoundary	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

17.034_1

Iris Sclera Boundary

Boundary Code

Mnemonic	BYC			Conditionality	M↑
				Status	Active
Description	Defines the shape of a boundary of a feature within an image.				
Field Min	1	Occur Min	1		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars	None		
Format	n/a	Constraints	BYC = C, E or P, see Look Up Codes		
Code List	BOUNDARY DEFINITION CODE				
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage	Cardinality	1..1		
XML Level 2	biom:IrisImageIrisScleraBoundary	Cardinality	0..1		
XML Level 3	biom:IrisBoundaryShapeCode	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

17.034_2

Iris Sclera Boundary

Number of Points

Mnemonic	NOP			Conditionality	M↑
				Status	Active
Description	Specifies the number of vertices.				
Field Min	1	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	2 <= NOP <= 99, positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage	Cardinality	1..1		
XML Level 2	biom:IrisImageIrisScleraBoundary	Cardinality	0..1		
XML Level 3	biom:ImageFeatureVertexQuantity	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-17: Iris Image Data

Page 845 of 1037

17.034_3

Iris Sclera Boundary

Horizontal Point Offset

Mnemonic	HPO			Conditionality	M↑
				Status	Active
Description	The pixel counts to the right. HPO and VPO information items are repeated as pairs, in order by point following the path – for a total of NOP pairs.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= HPO < HLL, positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage	Cardinality	1..1		
XML Level 2	biom:IrisImageIrisScleraBoundary	Cardinality	0..1		
XML Level 3	biom:ImageFeatureVertex	Cardinality	2..99		
XML Level 4	biom:PositionHorizontalCoordinateValue	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

17.034_4

Iris Sclera Boundary

Vertical Point Offset

Mnemonic	VPO			Conditionality	M↑
				Status	Active
Description	The pixel counts down from the origin. HPO and VPO information items are repeated as pairs, in order by point following the path – for a total of NOP pairs.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= VPO < VLL, positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage	Cardinality	1..1		
XML Level 2	biom:IrisImageIrisScleraBoundary	Cardinality	0..1		
XML Level 3	biom:ImageFeatureVertex	Cardinality	2..99		
XML Level 4	biom:PositionVerticalCoordinateValu	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

17.035

Upper Eyelid Boundary

Mnemonic	UEB			Conditionality	0
				Status	Active
Description	This optional field defines the boundary between the upper eyelid and the eye.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage			Cardinality	1..1
XML Level 2	biom:IrisImageIrisUpperEyelidBoundary			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

17.035_1

Upper Eyelid Boundary

Boundary Code

Mnemonic	BYC			Conditionality	M↑
				Status	Active
Description	Defines the shape of a boundary of a feature within an image.				
Field Min	1		Occur Min	1	
Field Max	1		Occur Max	1	
Char Types	A		Special Chars	None	
Format	n/a		Constraints	BYC = P, see Look Up Codes	
Code List	BOUNDARY DEFINITION CODE				
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage			Cardinality	1..1
XML Level 2	biom:IrisImageIrisUpperEyelidBoundary			Cardinality	0..1
XML Level 3	biom:IrisBoundaryShapeCode			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

17.035_2

Upper Eyelid Boundary

Number of Points

Mnemonic	NOP			Conditionality	M↑
				Status	Active
Description	Specifies the number of vertices.				
Field Min	1	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	3 <= NOP <= 99, positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage	Cardinality	1..1		
XML Level 2	biom:IrisImageIrisUpperEyelidBoundary	Cardinality	0..1		
XML Level 3	biom:ImageFeatureVertexQuantity	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

17.035_3

Upper Eyelid Boundary

Horizontal Point Offset

Mnemonic	HPO			Conditionality	M↑
				Status	Active
Description	The pixel counts to the right. HPO and VPO information items are repeated as pairs, in order by point following the path – for a total of NOP pairs.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= HPO < HLL, positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage	Cardinality	1..1		
XML Level 2	biom:IrisImageIrisUpperEyelidBoundary	Cardinality	0..1		
XML Level 3	biom:ImageFeatureVertex	Cardinality	3..99		
XML Level 4	biom:PositionHorizontalCoordinateValue	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-17: Iris Image Data

Page 848 of 1037

17.035_4

Upper Eyelid Boundary

Vertical Point Offset

Mnemonic	VPO			Conditionality	M↑
				Status	Active
Description	The pixel counts down from the origin. HPO and VPO information items are repeated as pairs, in order by point following the path – for a total of NOP pairs.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= VPO < VLL, positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage	Cardinality	1..1		
XML Level 2	biom:IrisImageIrisUpperEyelidBoundary	Cardinality	0..1		
XML Level 3	biom:ImageFeatureVertex	Cardinality	3..99		
XML Level 4	biom:PositionVerticalCoordinateValu	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

17.036

Lower Eyelid Boundary

Mnemonic	LEB			Conditionality	O
				Status	Active
Description	This optional field defines the boundary between the lower eyelid and the eye.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage	Cardinality	1..1		
XML Level 2	biom:IrisImageIrisLowerEyelidBoundary	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

17.036_1

Lower Eyelid Boundary

Boundary Code

Mnemonic	BYC			Conditionality	M↑
				Status	Active
Description	Defines the shape of a boundary of a feature within an image.				
Field Min	1	Occur Min	1		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars	None		
Format	n/a	Constraints	BYC = P, see Look Up Codes		
Code List	BOUNDARY DEFINITION CODE				
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage	Cardinality	1..1		
XML Level 2	biom:IrisImageIrisLowerEyelidBoundary	Cardinality	0..1		
XML Level 3	biom:IrisBoundaryShapeCode	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

17.036_2

Lower Eyelid Boundary

Number of Points

Mnemonic	NOP			Conditionality	M↑
				Status	Active
Description	Specifies the number of vertices				
Field Min	1	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	3 <= NOP <= 99, positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage	Cardinality	1..1		
XML Level 2	biom:IrisImageIrisLowerEyelidBoundary	Cardinality	0..1		
XML Level 3	biom:ImageFeatureVertexQuantity	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

17.036_3

Lower Eyelid Boundary

Horizontal Point Offset

Mnemonic	HPO			Conditionality	M↑
				Status	Active
Description	The pixel counts to the right. HPO and VPO information items are repeated as pairs, in order by point following the path – for a total of NOP pairs.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= HPO < HLL, positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage	Cardinality	1..1		
XML Level 2	biom:IrisImageIrisLowerEyelidBoundary	Cardinality	0..1		
XML Level 3	biom:ImageFeatureVertex	Cardinality	3..99		
XML Level 4	biom:PositionHorizontalCoordinateValue	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

17.036_4

Lower Eyelid Boundary

Vertical Point Offset

Mnemonic	VPO			Conditionality	M↑
				Status	Active
Description	The pixel counts down from the origin. HPO and VPO information items are repeated as pairs, in order by point following the path – for a total of NOP pairs.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= VPO < VLL, positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage	Cardinality	1..1		
XML Level 2	biom:IrisImageIrisLowerEyelidBoundary	Cardinality	0..1		
XML Level 3	biom:ImageFeatureVertex	Cardinality	3..99		
XML Level 4	biom:PositionVerticalCoordinateValue	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-17: Iris Image Data

Page 851 of 1037

17.037

Make/Model/Serial Number

Non-eyelid Occlusions

Mnemonic	NEO			Conditionality	O
				Status	Active
Description	This optional field defines the outline and contents of any non-eyelid occlusions that partially or totally blocks the image of the iris. It is a contour or a polygon.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage	Cardinality	1...1		
XML Level 2	biom:IrisImageOcclusion	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

17.037_0

Make/Model/Serial Number

Subfields: Repeating sets of information items information items

Mnemonic	NEO_0			Conditionality	M↑
				Status	New-Active
Description	This optional field defines the outline and contents of any non-eyelid occlusions that partially or totally blocks the image of the iris. It is a contour or a polygon.				
Field Min	n/a	Occur Min	1		
Field Max	n/a	Occur Max	*		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage	Cardinality	1...1		
XML Level 2	biom:IrisImageOcclusion	Cardinality	0..*		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes		

17.037_1

Non-eyelid Occlusions

Occlusion Opacity

Mnemonic	OCY			Conditionality	M↑
				Status	Active
Description	The first information item of the Occlusions (OCC) field.				
Field Min	1	Occur Min	1		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars	None		
Format	n/a	Constraints	OCY = T, I, L or S, see Look Up Codes		
Code List	OCCLUSION OPACITY CODE				
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage	Cardinality	1..1		
XML Level 2	biom:IrisImageOcclusion	Cardinality	0..*		
XML Level 3	biom:IrisImageOcclusionOpacityCode	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

17.037_2

Non-eyelid Occlusions

Occlusion Type

Mnemonic	OCT			Conditionality	M↑
				Status	Active
Description	The second information item of the OCCLUSIONS (OCC) field.				
Field Min	1	Occur Min	1		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars	None		
Format	n/a	Constraints	OCT = L, S, C, R or O, see Look Up Codes		
Code List	OCCLUSIONS CODE				
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage	Cardinality	1..1		
XML Level 2	biom:IrisImageOcclusion	Cardinality	0..*		
XML Level 3	biom:IrisImageOcclusionCategoryCode	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

17.037_3

Non-eyelid Occlusions

Number of Points

Mnemonic	NOP			Conditionality	M↑
				Status	Active
Description	Specifies the number of vertices.				
Field Min	1	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	3 <= NOP <= 99, positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage	Cardinality	1..1		
XML Level 2	biom:IrisImageOcclusion	Cardinality	0..*		
XML Level 3	biom:ImageFeatureVertexQuantity	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

17.037_4

Non-eyelid Occlusions

Horizontal Point Offset

Mnemonic	HPO			Conditionality	M↑
				Status	Active
Description	The pixel counts to the right. HPO and VPO information items are repeated as pairs, in order by point following the path – for a total of NOP pairs.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= HPO < HLL, positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage	Cardinality	1..1		
XML Level 2	biom:IrisImageOcclusion	Cardinality	0..*		
XML Level 3	biom:ImageFeatureVertex	Cardinality	3..99		
XML Level 4	biom:PositionHorizontalCoordinateValue	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

17.037_5

Non-eyelid Occlusions

Vertical Point Offset

Mnemonic	VPO			Conditionality	M↑
				Status	Active
Description	The pixel counts down from the origin. HPO and VPO information items are repeated as pairs, in order by point following the path – for a total of NOP pairs.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= VPO < VLL, positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage	Cardinality	1...1		
XML Level 2	biom:IrisImageOcclusion	Cardinality	0..*		
XML Level 3	biom:ImageFeatureVertex	Cardinality	3..99		
XML Level 4	biom:PositionVerticalCoordinateValue	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

17.04

Range

Mnemonic	RAN			Conditionality	O
				Status	Active
Description	This optional field contains the estimated distance from the lens of the camera to the iris. It shall be measured in centimeters.				
Field Min	1	Occur Min	0		
Field Max	7	Occur Max	1		
Char Types	N	Special Chars	n/a		
Format	n/a	Constraints	positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage	Cardinality	1...1		
XML Level 2	biom:IrisImageRangeMeasure	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

17.041

Frontal Gaze

Mnemonic	GAZ		Conditionality	0	
			Status	Active	
Description	This optional field describes the metric that estimates the degree of eye(s) sight-angle relative to the camera. The angle shall be reported in degrees and defined as between: The optical axis of the eye, and a line connecting the optical center of the eye and the optical center of the camera. This measure is inclusive of both head angular orientation and eye-gaze angle relative to the head. The inclusive approach for gaze direction is not intended to be representative of the possible difficulty with iris segmentation due to non-frontal head orientation. Hence, two images with the same frontal gaze, but significantly different frontal head orientation may perform differently with different segmentation and matching algorithms. Note that iris image recognition systems typically rely upon having a small gaze angle in the image. While not prohibited in this standard, it is strongly discouraged that gaze angles greater than 15 degrees be used for enrollment or matching. While not prohibited in this standard, it is strongly discouraged that gaze angles greater than 15 degrees be used for enrollment or matching.				
Field Min	1		Occur Min	0	
Field Max	2		Occur Max	1	
Char Types	N		Special Chars	n/a	
Format	n/a		Constraints	0 <= GAZ <= 90, positive integer	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage		Cardinality	1...1	
XML Level 2	biom:IrisImageGazeAngleMeasure		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

17.902

Annotated Information

Mnemonic	ANN		Conditionality	0	
			Status	Active	
Description	This is an optional field, listing the operations performed on the original source in order to prepare it for inclusion in a biometric record type.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom:ProcessAnnotation		Cardinality	0..1	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-17: Iris Image Data

Page 856 of 1037

17.902_0

Annotated Information

Subfields: Repeating sets of information items

Mnemonic	ANN_0			Conditionality	M↑
				Status	New-Active
Description	This is an optional field, listing the operations performed on the original source in order to prepare it for inclusion in a biometric record type.				
Field Min	n/a	Occur Min	1		
Field Max	n/a	Occur Max	*		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom:ProcessAnnotation			Cardinality	0..*
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

17.902_1

Annotated Information

Greenwich Mean Time

Mnemonic	GMT			Conditionality	M↑
				Status	Active
Description	This information item is the Greenwich Mean Time (GMT) when the processing occurred. The data is formatted as YYYYMMDDhhmmssZ, where the Z is indicates the zone description of 0 hours. This time is independent of the actual time zone where the time and date is recorded.				
Field Min	dependent on encoding	Occur Min	1		
Field Max	dependent on encoding	Occur Max	1		
Char Types	AN	Special Chars	None		
Format	YYYYMMDDHHMMSSZ - for Traditional Encoding	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom:ProcessAnnotation			Cardinality	0..*
XML Level 2	biom:ProcessUTCDate/nc:DateTime			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-17: Iris Image Data

Page 857 of 1037

17.902_2

Annotated Information

Processing Algorithm Name / Version

Mnemonic	NAV			Conditionality	M↑
				Status	Active
Description	This information item shall contain text identifying the name and version of the processing algorithm, application, procedure, or workstation				
Field Min	1	Occur Min	1		
Field Max	Unlimited	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom:ProcessAnnotation	Cardinality	0..*		
XML Level 2	biom:ProcessName	Cardinality	1..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

17.902_3

Annotated Information

Algorithm Owner

Mnemonic	OWN			Conditionality	M↑
				Status	Active
Description	This information item shall contain an unformatted text string of up to 64 characters with the contact information for the organization that owns the processing algorithm or latent workstation. Where there is no 'algorithm owner,' enter N/A.				
Field Min	1	Occur Min	1		
Field Max	64	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom:ProcessAnnotation	Cardinality	0..*		
XML Level 2	biom:ProcessOwnerText	Cardinality	1..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-17: Iris Image Data

Page 858 of 1037

17.902_4

Annotated Information

Process Description

Mnemonic	PRO			Conditionality	M↑
				Status	Active
Description	This information item field shall contain text describing a process or procedure applied to the sample in this Type-9 record.				
Field Min	1	Occur Min	1		
Field Max	255	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom:ProcessAnnotation	Cardinality	0..*		
XML Level 2	biom:ProcessDescriptionText	Cardinality	1..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

17.993

Source Agency Name

Mnemonic	SAN			Conditionality	O
				Status	Active
Description	This is an optional field. It may contain up to 125 Unicode characters. It is the name of the agency referenced in Field xx.004: Source agency / SRC for record types 9-99.				
Field Min	1	Occur Min	0		
Field Max	125	Occur Max	1		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage(1..1)/biom_2:ImageCaptureDetail(1..1)	Cardinality	1..1		
XML Level 2	biom:CaptureOrganization	Cardinality	1..1		
XML Level 3	nc:OrganizationName	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-17: Iris Image Data

Page 859 of 1037

17.995

Associated Context

Mnemonic	ASC			Conditionality	0
				Status	Active
Description	This optional field refers to one or more Type 21 Records with the same ACN. Type 21 Records contain images that are NOT used to derive the biometric data in Field 13.999: Latent friction ridge image (DATA) but that may be relevant to the collection of that data, such as general scenes of the area where a latent print was found.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom:AssociatedContext			Cardinality	0..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

17.995_0

Associated Context

Subfields: Repeating sets of information items

Mnemonic	ASC_0			Conditionality	M↑
				Status	New-Active
Description	This optional field refers to one or more Type 21 Records with the same ACN. Type 21 Records contain images that are NOT used to derive the biometric data in Field 13.999: Latent friction ridge image (DATA) but that may be relevant to the collection of that data, such as general scenes of the area where a latent print was found.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	255		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom:AssociatedContext			Cardinality	0..255
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

17.995_1

Associated Context

Associated Context Number

Mnemonic	ACN			Conditionality	M↑
				Status	Active
Description	The first information item for the Associated Context field for a particular Record Type-21. This is mandatory for each Field xx.995, when the field is used. It contains an index to a particular instance of a Type-21 record in the transaction. This same index value appears in the appropriate instance of Record Type-21 as Field 21.021: Associated context number (CAN). The value of the CAN shall be a sequentially assigned a positive integer starting from one and incremented by one, not to exceed 255.				
Field Min	1	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	1 <= ACN <= 255, positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom:AssociatedContext			Cardinality	0..255
XML Level 2	biom:ContextIdentification/nc:IdentificationID			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

17.995_2

Associated Context

Associated Segment Position

Mnemonic	ASP			Conditionality	O↑
				Status	Active
Description	The first information item is the associated segment position (ASP). This provides a unique index to a segmentation.				
Field Min	1	Occur Min	0		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	n/a		
Format	n/a	Constraints	1 <= ASP <= 99, positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom:AssociatedContext			Cardinality	0..255
XML Level 2	biom:ImageSegmentIdentification/nc:IdentificationID			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

17.996

Hash

Mnemonic	HAS		Conditionality	0	
			Status	Active	
Description	Optional field xx.996, is designed for use in Record types 10 and above with a Field xx.999 storing the biometric data. It is comprised of 64 characters representing hexadecimal values. Thus, each character may be a digit from "0" to "9" or a letter "A" through "F". See the latest version of the Federal Information Processing Standard 180, Secure Hash Standard for information on computing SHA-256 hashes. At the time of this standard's publication, FIPS 180-37 had been published. It is also possible to use Field xx.996 to contain the hash for data stored externally, which is referenced in Field 20.994: External file reference (EFR) and/or Field 21.994: External file reference (EFR). The ability to store files externally is new to this version of the standard, and is only implemented for the two new record types referred to here. Use of the hash enables the receiver of the data to perform quick searches of large databases to determine if the data already exist in the database. It is not intended as an information assurance check. That is handled by Record Type-98: Information assurance record.				
Field Min	64		Occur Min	0	
Field Max	64		Occur Max	1	
Char Types	H		Special Chars	None	
Format	n/a		Constraints		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:ImageHashValue		Cardinality	0..1	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

17.997

Source Representation

Mnemonic	SOR		Conditionality	0	
			Status	Active	
Description	This optional field refers to a representation in Record Type-20 with the same SRN from which the data in Field 13.999: Latent friction ridge image (DATA) was derived.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom:SourceRepresentation		Cardinality	0..1	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

17.997_0

Source Representation

Subfields: Repeating sets of information items

Mnemonic	SOR_0			Conditionality	M↑
				Status	New-Active
Description	This optional field refers to a representation in Record Type-20 with the same SRN from which the data in Field 13.999: Latent friction ridge image (DATA) was derived.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	255		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom:SourceRepresentation			Cardinality	0...255
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

17.997_1

Source Representation

Source Representation Number

Mnemonic	SRN			Conditionality	M↑
				Status	Active
Description	This is the first information item and is mandatory for each Field xx.997. It contains an index to a particular instance of a Type-20 record in the transaction. This same index value appears in the appropriate instance of Record Type-20 as Field 20.021: Source representation number (SRN). The value of the SRN shall be a sequentially assigned a positive integer starting from one and incremented by one, not to exceed 255.				
Field Min	1	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	1 <= SRN <= 255, positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom:SourceRepresentation			Cardinality	0...255
XML Level 2	biom:SourceIdentification/nc:IdentificationID			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

17.997_2

Source Representation

Reference Segment Position

Mnemonic	RSP			Conditionality	O↑
				Status	Active
Description	The first information item is the reference segment position (RSP). This provides a unique index to a segmentation.				
Field Min	1	Occur Min	0		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	1 <= RSP <= 99, positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom:SourceRepresentation			Cardinality	0...255
XML Level 2	biom:ImageSegmentIdentification/nc:IdentificationID			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

17.998

Geographic Sample Acquisition Location

Mnemonic	GEO			Conditionality	O
				Status	Active
Description	This optional field contains the location where the iris sample/original source/context information was acquired – not where it is stored.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a, BiometricCaptureType		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage(1...1)/biom_2:ImageCaptureDetail(1...1)			Cardinality	1...1
XML Level 2	biom:CaptureLocation			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

17.998_01

Geographic Sample Acquisition Location

Universal Time Entry

Mnemonic	UTE		Conditionality	O↑			
			Status	Active			
Description	The coordinated universal time (UTC) where the biometric sample was collected. This time is independent of the actual time zone where the time and date is recorded. The date is YYYYMMDDhhmmssZ, where the Z indicates the zone description of 0 hours. If sample collection time is unknown, set it to "00000000000000Z."						
Field Min	dependent on encoding	Occur Min	0				
Field Max	dependent on encoding	Occur Max	1				
Char Types	AN	Special Chars	None				
Format	n/a	Constraints					
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-17)						
XML Level 1	biom_2:IrisImage(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1				
XML Level 2	biom:CaptureUTCDateTime/nc:DateTime	Cardinality	0..1				
XML Level 3		Cardinality					
XML Level 4		Cardinality					
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

17.998_02

Geographic Sample Acquisition Location

Latitude Degree Value

Mnemonic	LTD		Conditionality	D			
			Status	Active			
Description	The second information item is latitude degree value (LTD). This is a value that specifies the degree of latitude. The value shall be between -90 (inclusive) and +90 (inclusive). The degrees may be expressed as an integer (without a decimal) or a real number including decimals. If decimals are present, then minutes and seconds shall be empty. Examples: Buenos Aires, Argentina: -34 (with minutes LTM = 36) NIST, Gaithersburg, Maryland: 39.137627 (no LTM or LTS)						
Field Min	1	Occur Min	1				
Field Max	9	Occur Max	1				
Char Types	NS	Special Chars	Decimal, Minus Sign, Plus Sign				
Format	n/a	Constraints	-90 < LTD < 90				
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-17)						
XML Level 1	biom_2:IrisImage(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1				
XML Level 2	biom:CaptureLocation(0...1)/biom:LocationTwoDimensionalGeographicCoordinate(0...1)/nc:GeographicCoordinateLatitude(0...1)	Cardinality	0..1				
XML Level 3	nc:LatitudeDegreeValue	Cardinality	1..1				
XML Level 4		Cardinality					
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

17.998_03

Geographic Sample Acquisition Location

Latitude Minute Value

Mnemonic	LTM	Conditionality	D
		Status	Active
Description	This information item is latitude minute value (LTM). This is a value that specifies a minute of a degree. The value shall be between 0 (inclusive) to 60 (exclusive). The minute value may be expressed as an integer (without a decimal) or as a real number including decimals. If decimals are present then seconds shall be empty. Thus, the allowed special character is a period. The minute value can be empty, even if the degree value is an integer. LTM and LGM are co-conditional, so they shall both be present if either is present.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	NS	Special Chars	Decimal,Minus Sign,Plus Sign
Format	n/a	Constraints	0 <= LTM < 60
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-17)		
XML Level 1	biom_2:IrisImage(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1
XML Level 2	biom:CaptureLocation(0...1)/biom:LocationTwoDimensionalGeographicCoordinate(0...1)/nc:GeographicCoordinateLatitude (0...1)	Cardinality	0..1
XML Level 3	nc:LatitudeMinuteValue	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

17.998_04

Geographic Sample Acquisition Location

Latitude Second Value

Mnemonic	LTS	Conditionality	D
		Status	Active
Description	The fourth information item is the latitude second value (LTS). This is a value that specifies a second of a minute. The integer shall be 0 (inclusive) to 60 (exclusive). The second value is empty, even if the minute value is an integer.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	0 <= LTS < 60
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-17)		
XML Level 1	biom_2:IrisImage(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1
XML Level 2	biom:CaptureLocation(0...1)/biom:LocationTwoDimensionalGeographicCoordinate(0...1)/nc:GeographicCoordinateLatitude (0...1)	Cardinality	0..1
XML Level 3	nc:LatitudeSecondValue	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

17.998_05

Geographic Sample Acquisition Location

Longitude Degree Value

Mnemonic	LGD			Conditionality	D
				Status	Active
Description	The fifth information item is the longitude degree value (LGD). It is a value that specifies the degree of a longitude. The value shall be between -180 (inclusive) and +180 (inclusive). If LTD is present, then LGD shall be present. The degrees may be expressed as whole numbers (without a decimal) or real numbers including decimals. If decimals are present, then minutes and seconds are empty. Examples: Buenos Aires, Argentina: -58 (with minutes LGM = 22), NIST, Gaithersburg, Maryland: -77.216032 (no LGM or LGS)				
Field Min	1	Occur Min	1		
Field Max	10	Occur Max	1		
Char Types	NS	Special Chars	Decimal,Minus Sign,Plus Sign		
Format	n/a	Constraints	-180 =< LGD =< 180		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage(1...1)/biom_2:ImageCaptureDetail(1...1)			Cardinality	1...1
XML Level 2	biom:CaptureLocation(0...1)/biom:LocationTwoDimensionalGeographicCoordinate(0...1)/nc:GeographicCoordinateLongitude (0...1)			Cardinality	0..1
XML Level 3	nc:LongitudeDegreeValue			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

17.998_06

Geographic Sample Acquisition Location

Longitude Minute Value

Mnemonic	LGM			Conditionality	D
				Status	Active
Description	The sixth information item is the longitude minute value (LGM). It is a value that specifies a minute of a degree. The value shall be from 0 (inclusive) to 60 (exclusive). The minute value may be expressed as an integer (without a decimal) or as a real number including decimals. If decimals are present then seconds shall not appear. The minute value is empty, even if the degree value is an integer. If LTM is present, then LGM shall be present.				
Field Min	1	Occur Min	0		
Field Max	8	Occur Max	1		
Char Types	NS	Special Chars	Decimal		
Format	n/a	Constraints	1 <= LGM < 60		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage(1...1)/biom_2:ImageCaptureDetail(1...1)			Cardinality	1...1
XML Level 2	biom:CaptureLocation(0...1)/biom:LocationTwoDimensionalGeographicCoordinate(0...1)/nc:GeographicCoordinateLongitude (0...1)			Cardinality	0..1
XML Level 3	nc:LongitudeMinuteValue			Cardinality	0..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

17.998_07

Geographic Sample Acquisition Location

Longitude Second Value

Mnemonic	LGS	Conditionality	D
		Status	Active
Description	The seventh information item is the longitude second value (LGS). This is a value that specifies a second of a minute. The integer shall be 0 (inclusive) to 60 (exclusive). The second value is empty, even if the minute value is an integer. If LTS is present, then LGS shall be present.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	0 <= LGS < 60
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-17)		
XML Level 1	biom_2:IrisImage(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1
XML Level 2	biom:CaptureLocation(0...1)/biom:LocationTwoDimensionalGeographicCoordinate(0...1)/nc:GeographicCoordinateLongitude (0...1)	Cardinality	0..1
XML Level 3	nc:LongitudeSecondValue	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

17.998_08

Geographic Sample Acquisition Location

Elevation

Mnemonic	ELE	Conditionality	D
		Status	Active
Description	The eighth information item is elevation (ELE). It is expressed in meters. It is a numeric value. It is between -422 meters (Dead Sea) and 8848 meters (Mount Everest). Allowed special characters are the negative sign and the period.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	NS	Special Chars	Minus Sign,Period
Format	n/a	Constraints	-422.000 < ELE < 8848.000, real number
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-17)		
XML Level 1	biom_2:IrisImage(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1
XML Level 2	biom:CaptureLocation(0...1)/nc:LocationGeographicElevation (0...1)	Cardinality	0..1
XML Level 3	nc:MeasurePointValue	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

17.998_09

Geographic Sample Acquisition Location

Geodetic Datum Code

Mnemonic	GDC			Conditionality	D
				Status	Active
Description	The ninth information item is the geodetic datum code (GDC11). It is an alphanumeric value of 3 to 6 characters in length. This information item is used to indicate which coordinate system was used to represent the values in information items 2 through 7. If no entry is made in this information item, then the basis for the values entered in the first eight information items shall be WGS84, the code for the World Geodetic Survey 1984 version - WGS 84 (G873). See look up codes for values. If no entry is made in this information item, then the basis for the values entered in the first eight information items shall be WGS84, the code for the World Geodetic Survey 1984 version - WGS 84 (G873). See look up codes for values.				
Field Min	3	Occur Min	0		
Field Max	6	Occur Max	1		
Char Types	AN	Special Chars	None		
Format	n/a	Constraints	see Look Up Codes		
Code List	GEOGRAPHIC COORDINATE DATUM CODE				
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1		
XML Level 2	biom:CaptureLocation(0...1)/biom:LocationTwoDimensionalGeographicCoordinate(0...1)	Cardinality	0..1		
XML Level 3	biom:GeodeticDatumCoordinateSystemName or biom:GeodeticDatumCoordinateSystemCode	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

17.998_10

Geographic Sample Acquisition Location

Geographic Coordinate Universal Transverse Mercator Zone

Mnemonic	GCM			Conditionality	D
				Status	Active
Description	It is an alphanumeric value of 2 to 3 characters. This is a one or two digit UTM zone number followed by the 8 degree latitudinal band designator (which is a single letter).				
Field Min	2	Occur Min	0		
Field Max	3	Occur Max	1		
Char Types	AN	Special Chars	None		
Format	n/a	Constraints	One or two integers followed by a single letter. Valid latitudinal band designators include C through X, omitting I and O		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1		
XML Level 2	biom:CaptureLocation(0...1)/nc:LocationUTMCoordinate(0...1)	Cardinality	0..1		
XML Level 3	nc:UTMGridZoneID	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-17: Iris Image Data

Page 869 of 1037

17.998_11

Geographic Sample Acquisition Location

Geographic Coordinate Universal Transverse Mercator Easting

Mnemonic	GCE			Conditionality	D
				Status	Active
Description	The eleventh information item is the geographic coordinate universal transverse Mercator easting (GCE). It is an integer of 1 to 6 digits.				
Field Min	1	Occur Min	1		
Field Max	6	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1		
XML Level 2	biom:CaptureLocation(0...1)/nc:LocationUTMCoordinate (0...1)	Cardinality	0..1		
XML Level 3	nc:UTMEastingValue	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

17.998_12

Geographic Sample Acquisition Location

Geographic Coordinate Universal Transverse Mercator Northing

Mnemonic	GCN			Conditionality	D
				Status	Active
Description	The twelfth information item is the geographic coordinate universal transverse Mercator northing (GCN). It is an integer of 1 to 8 digits.				
Field Min	1	Occur Min	1		
Field Max	8	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1		
XML Level 2	biom:CaptureLocation(0...1)/nc:LocationUTMCoordinate (0...1)	Cardinality	0..1		
XML Level 3	nc:UTMNorthingValue	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-17: Iris Image Data

Page 870 of 1037

17.998_13

Geographic Sample Acquisition Location

Geographic Reference Text

Mnemonic	GRT		Conditionality	O
			Status	Active
Description	It is a free form text describing a street address or other physical location (such as 'Corner of Washington and Madison, Geneva, NY').			
Field Min	1	Occur Min	0	
Field Max	150	Occur Max	1	
Char Types	U	Special Chars	Any	
Format	n/a	Constraints		
Code List				
Source	ANSI/NIST ITL 1-2013 (Type-17)			
XML Level 1	biom_2:IrisImage(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1	
XML Level 2	biom:CaptureLocation(0...1)	Cardinality	0..1	
XML Level 3	nc:LocationDescriptionText	Cardinality	0..1	
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0
				Yes
				DoD EBTS 4.0
				Yes

17.998_14

Geographic Sample Acquisition Location

Geographic Coordinate Other System Identifier

Mnemonic	OSI		Conditionality	O
			Status	Active
Description	A fourteenth optional information item geographic coordinate other system identifier (OSI) allows for other coordinate systems. This information items specifies the system identifier. It is up to 10 characters in length. Examples are: • MGRS (Military Grid Reference System), • USNG (United States National Grid), • GARS (Global Area Reference System), • GEOREF (World Geographic Reference), • LANDMARK landmark (e.g. hydant) and position relative to the landmark.			
Field Min	1	Occur Min	1	
Field Max	10	Occur Max	1	
Char Types	U	Special Chars	n/a	
Format	n/a	Constraints		
Code List				
Source	ANSI/NIST ITL 1-2013 (Type-17)			
XML Level 1	biom_2:IrisImage(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1	
XML Level 2	biom:CaptureLocation(0...1)/biom:LocationAlternateGeographicSystemValue (0...1)	Cardinality	0..1	
XML Level 3	biom:GeographicLocationSystemName	Cardinality	1..1	
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0
				Yes
				DoD EBTS 4.0
				Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-17: Iris Image Data

Page 871 of 1037

17.998_15

Geographic Sample Acquisition Location

Geographic Coordinate Other System Value

Mnemonic	OCV			Conditionality	D
				Status	Active
Description	A fifteenth optional information item, is the geographic coordinate other system value (OCV). It shall only be present if OSI is present in the record. It can be up to 126 characters in length. If OSI is LANDMARK, OCV is free text and may be up to 126 characters. For details on the formatting of OCV for the other coordinate systems shown in OSI as examples, see http://earth-info.nga.mil/GandG/coordsys/grids/referencesys.html .				
Field Min	1	Occur Min	1		
Field Max	126	Occur Max	1		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage(1..1)/biom_2:ImageCaptureDetail(1..1)	Cardinality	1..1		
XML Level 2	biom:CaptureLocation(0..1)/biom:LocationAlternateGeographicSystem Value (0..1)	Cardinality	0..1		
XML Level 3	biom:GeographicLocationText	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

17.999

Iris Image Data

Mnemonic	DATA			Conditionality	D
				Status	Active
Description	This mandatory field contains the iris image. See Section 7.2 of ANSI/NIST ITL 1-2011 for details.				
Field Min	1	Occur Min	0		
Field Max	Unlimited	Occur Max	1		
Char Types	B	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-17)				
XML Level 1	biom_2:IrisImage	Cardinality	1..1		
XML Level 2	nc:Base64BinaryObject	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-17: Iris Image Data

Page 872 of 1037

n/a

Capture Time

Mnemonic			Conditionality	n/a
			Status	Retired
Description	This ASCII field shall contain the time in UTC that the biometric sample or contextual information contained in the record was captured. The time shall appear as 6 digits format HHMMSS with 'Z' being the zone designator for the zero UTC offset. The complete time must be a legitimate time.			
Field Min	n/a	Occur Min	n/a	
Field Max	n/a	Occur Max	n/a	
Char Types	AN	Special Chars	None	
Format	n/a	Constraints	n/a	
Code List				
Source	ANSI/NIST ITL 1-2013 (Type-17)			
XML Level 1			Cardinality	
XML Level 2			Cardinality	
XML Level 3			Cardinality	
XML Level 4			Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0 No DoD EBTS 4.0 No

n/a

Digitization Time

Mnemonic			Conditionality	n/a
			Status	Retired
Description				
Field Min	n/a	Occur Min	n/a	
Field Max	n/a	Occur Max	n/a	
Char Types	AN	Special Chars	None	
Format	n/a	Constraints	n/a	
Code List				
Source	ANSI/NIST ITL 1-2013 (Type-17)			
XML Level 1			Cardinality	
XML Level 2			Cardinality	
XML Level 3			Cardinality	
XML Level 4			Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0 No DoD EBTS 4.0 No

17.018

Global Unique Identifier

Mnemonic	GUI	Conditionality	n/a
		Status	Retired
Description	This optional field shall contain a 16-byte string to indicate a GUID – a globally unique identifier.		
Field Min	n/a	Occur Min	n/a
Field Max	n/a	Occur Max	n/a
Char Types	AN	Special Chars	None
Format	n/a	Constraints	n/a
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-17)		
XML Level 1		Cardinality	
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	DoD EBTS 2.0	Yes	DoD EBTS 3.0
			No
			DoD EBTS 4.0
			No

18.001

Record Header

Mnemonic	LEN	Conditionality	M
		Status	Active
Description	The record header appears as the first field (xx.001) in each Record Type. It contains information particular to the encoding format chosen, in order to enable proper reading of the record. In Traditional encoding, this field contains the record length in bytes (including all information separators). In NIEM-conformant XML encoding, this field contains the RecordCategoryCode, which is the numeric representation of the Record Type.		
Field Min	T = 4; X = 1	Occur Min	1
Field Max	T = 8; X = 2	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	positive integer
Code List			
Source	ANSI/NIST ITL 1-2011 (Type-18)		
XML Level 1	nist-itl:RecordCategoryCode	Cardinality	1...1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

18.002

Information Designation Character

Mnemonic	IDC	Conditionality	M
		Status	Active
Description	Each of the records present in a transaction, with the exception of the Type-1 record, shall include a field (xx.002) containing the information designation character / IDC. The value of the IDC shall be a sequentially assigned positive integer starting from zero and incremented by one up to a maximum of 99. IDC references are stated in Type-1 Field 1.003 Transaction content (CNT) and shall be used to relate information items in the CNT field of the Type-1 record to the other records in the transaction. Two or more records may share a single IDC solely to identify and link together records that pertain to different representations of the same biometric trait.		
Field Min	1	Occur Min	1
Field Max	2	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	0 <= IDC <= 99; integer
Code List			
Source	ANSI/NIST ITL 1-2011 (Type-18)		
XML Level 1	nist-itl:ImageReferenceIdentification/nc:IdentificationID	Cardinality	1..1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

18.003

DNA Laboratory Setting

Mnemonic	DLS	Conditionality	M
		Status	Active
Description	This field is mandatory. The first information item is mandatory. The remaining information items are optional for all unit types.		
Field Min	n/a	Occur Min	1
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	n/a
Format	n/a	Constraints	n/a
Code List			
Source	ANSI/NIST ITL 1-2011 (Type-18)		
XML Level 1	biom:DNASample (1..1)/biom:DNALaboratory (1..1)	Cardinality	1..1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

18.003_1

DNA Laboratory Setting

Unit Type

Mnemonic	UTY			Conditionality	M
				Status	Active
Description	The first information item unit type / UTY is mandatory and contains a numeric value.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	1 <= UTY <= 4; integer		
Code List	DNA LABORATORY SETTING UNIT TYPE CODE				
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample (1..1)/biom:DNALaboratory (1..1)			Cardinality	1..1
XML Level 2	biom:DNALaboratoryUnitCategoryCode			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.003_2

DNA Laboratory Setting

Lab Type

Mnemonic	LTY			Conditionality	D
				Status	Active
Description	The second information item is the lab type / LTY. It is mandatory if the value for UTY is 1 or 2. It is not entered otherwise. When present, this information item contains a single character describing the laboratory that processed the DNA.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars	None		
Format	n/a	Constraints	LTY = G, I, O or U		
Code List	DNA LABORATORY SETTING LAB TYPE CODE				
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample (1..1)/biom:DNALaboratory (1..1)			Cardinality	1..1
XML Level 2	biom:DNALaboratoryCategoryCode			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.003_3

DNA Laboratory Setting

Accreditation Information

Mnemonic	ACC	Conditionality	D
		Status	Active
Description	The third information item is the accreditation information / ACC. It is mandatory if the value for UTY is 1 or 2. It shall not be entered otherwise. When present, this information item shall contain a minimum of one numeric character if the value is 0 or a minimum of two characters (one numeric followed immediately by one alpha character if the lab is accredited). If the laboratory has an unknown accreditation status, three numeric characters '255' are entered. The values in this information item shall be separated individually by commas between accreditation and scope pairings. More than one accreditation and scope of accreditation is permitted.		
Field Min	1	Occur Min	0
Field Max	35	Occur Max	4
Char Types	ANS	Special Chars	Comma
Format	n/a	Constraints	Numeric (0,1,2,3,4,5,6 or 255). It may be followed by an alpha string (N, M, D and/or O). That may be followed by up to 5 more such strings, each separated by a comma. The entire string is treated as a single information item.
Code List	DNA LABORATORY SETTING ACCREDITATION STATUS CODE and DNA LABORATORY ACCREDITATION SCOPE CODES		
Source	ANSI/NIST ITL 1-2011 (Type-18)		
XML Level 1	biom:DNASample (1...1)/biom:DNALaboratory (1...1)	Cardinality	1..1
XML Level 2	biom:DNALaboratoryAccreditation	Cardinality	0..6
XML Level 3	biom:DNALaboratoryAccreditationLevelCode	Cardinality	1..1
XML Level 4	biom:DNALaboratoryAccreditationLevelCode (1...1)/biom:DNALaboratoryAccreditationScopeCode (0...4)	Cardinality	0..4
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

18.003_4

DNA Laboratory Setting

Name of the Organization

Mnemonic	NOO	Conditionality	O
		Status	Active
Description	The fourth information item is the name of the organization / NOO that originally processed the DNA data. This may be different from the entry in Field 18.004: Source Agency / SRC. This is an optional information item. It is entered in Unicode characters This is an optional information item that may be up to 100 alphanumeric characters in length.		
Field Min	1	Occur Min	0
Field Max	Unlimited	Occur Max	1
Char Types	U	Special Chars	n/a
Format	n/a	Constraints	None
Code List			
Source	ANSI/NIST ITL 1-2011 (Type-18)		
XML Level 1	biom:DNASample (1...1)/biom:DNALaboratory (1...1)	Cardinality	1..1
XML Level 2	nc:OrganizationName	Cardinality	0..1
XML Level 3	nc:OrganizationPrimaryContactInformation	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-18: DNA Data

Page 877 of 1037

18.003_5

DNA Laboratory Setting

Point of Contact

Mnemonic	POC			Conditionality	O
				Status	Active
Description	This information item is the point of contact / POC who composed the DNA record metadata. This is an optional information item that could include the name, telephone number and e-mail address of the person responsible for this record submission. This information item may be up to 200 Unicode characters.				
Field Min	1	Occur Min	0		
Field Max	200	Occur Max	1		
Char Types	U	Special Chars	n/a		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample (1...1)/biom:DNALaboratory (1...1)			Cardinality	1..1
XML Level 2	nc:OrganizationPrimaryContactInformation			Cardinality	0..1
XML Level 3	nc:ContactInformationDescriptionText			Cardinality	0..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.003_6

DNA Laboratory Setting

Code of Sending Country

Mnemonic	CSC			Conditionality	O
				Status	Active
Description	The sixth information item is optional. It is the ISO-3166-1 code of the sending country / CSC. This is the code of where the DNA was processed, not necessarily the nation of the agency entered in Field 18.004: Source agency / SRC. All three formats specified in ISO-3166-1 are allowed (Alpha2, Alpha3 and Numeric). A country code is either 2 or 3 characters long. CSC defaults to ISO-3166-1 coding. If GENC used, then the version of that alternate code is entered in Field 1.018. which applies to ALL country codes in all records within the transaction. The DoD EBTS 4.0 default for this field is the GENC three character alpha codelist (genc:CountryAlpha3CodeType).				
Field Min	2	Occur Min	0		
Field Max	4	Occur Max	1		
Char Types	AN	Special Chars	None		
Format	n/a	Constraints	Value from GENC Country Codes, genc:CountryAlpha3CodeType		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample (1...1)/biom:DNALaboratory (1...1)			Cardinality	1..1
XML Level 2	biom:DNALaboratoryProcessingCountryGENCAAlpha3Code			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.003_7

DNA Laboratory Setting

International Organization Name

Mnemonic	ION			Conditionality	O
				Status	Active
Description	The seventh information item is optional. It is the international organization name / ION of the submitting organization. This is completed if the DNA was processed by an organization that is not affiliated with a country (such as a multinational organization). This optional information item is the name/acronym of an organization, and may be up to 100 Unicode characters.				
Field Min	1	Occur Min	0		
Field Max	100	Occur Max	1		
Char Types	U	Special Chars	n/a		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample (1...1)/biom:DNALaboratory (1...1)			Cardinality	1..1
XML Level 2	biom:DNALaboratoryInternationalOrganizationName			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.004

Source Agency

Mnemonic	SRC			Conditionality	M
				Status	Active
Description	This is the identifier of the agency that actually created the record and supplied the information contained in it.				
Field Min	1	Occur Min	1		
Field Max	Unlimited	Occur Max	1		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample (1...1)/biom:BiometricCaptureDetail (1...1)/biom:CaptureOrganization (1...1)			Cardinality	1..1
XML Level 2	nc:OrganizationIdentification/nc:IdentificationID			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.005

Number of Analysis Flag

Mnemonic	NAL		Conditionality	M
			Status	Active
Description	This mandatory field indicates whether the DNA record contains multiple or single data analyses.			
Field Min	1	Occur Min	1	
Field Max	1	Occur Max	1	
Char Types	N	Special Chars	None	
Format	n/a	Constraints	NAL = 0 or 1	
Code List	DNA LABORATORY NUMBER OF ANALYSES CODES			
Source	ANSI/NIST ITL 1-2011 (Type-18)			
XML Level 1	biom:DNASample	Cardinality	1..1	
XML Level 2	biom:DNAAnalysisQuantityCode	Cardinality	1..1	
XML Level 3		Cardinality		
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0 Yes
				DoD EBTS 4.0 Yes

18.006

Sample Donor Information

Mnemonic	SDI		Conditionality	M
			Status	Active
Description	This field is mandatory. It indicates if the DNA information contained in the record is from the subject of the transaction or from another person (the subject of the record), that is being sent to assist in establishing or verifying the identity of the subject of the transaction. Each subject of a record may have a distinct Type-2 record contained in the transaction. If that is the case, it is highly recommended that Field 18.992: Type-2 Record cross reference / T2C be used to link the Type-18 record to the appropriate Type-2 record. Note that multiple Type-18 records may be included in a single transaction; only one record may have a value of 0 for the first information item.			
Field Min	n/a	Occur Min	1	
Field Max	n/a	Occur Max	1	
Char Types	n/a	Special Chars	n/a	
Format	n/a	Constraints	n/a	
Code List				
Source	ANSI/NIST ITL 1-2011 (Type-18)			
XML Level 1	biom:DNASample	Cardinality	1..1	
XML Level 2	biom:DNADonor	Cardinality	1..1	
XML Level 3		Cardinality		
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0 Yes
				DoD EBTS 4.0 Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-18: DNA Data

Page 880 of 1037

18.006_1

Sample Donor Information

DNA Sample Donor

Mnemonic	DSD			Conditionality	M
				Status	Active
Description	The allowed numeric values for the first mandatory information item DNA sample donor / DSD.				
Field Min	1	Occur Min	1		
Field Max	1	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	DSD = 0, 1 or 2		
Code List	DNA SAMPLE DONOR CODES				
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample	Cardinality	1..1		
XML Level 2	biom:DNADonor	Cardinality	1..1		
XML Level 3	biom:DNADonorCategoryCode	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.006_2

Sample Donor Information

Gender ID

Mnemonic	GID			Conditionality	O
				Status	Active
Description	The second information item is the gender ID / GID. This is an optional single character identifier of "M" or "F" or "U". "U" indicates unknown. GID may be set based on self-assignment by the specimen donor. The GID may not match the results from the Amelogenin or for other valid cases.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars	None		
Format	n/a	Constraints	GID = M, F or U		
Code List	DNA SAMPLE DONOR GENDER				
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample	Cardinality	1..1		
XML Level 2	biom:DNADonor	Cardinality	1..1		
XML Level 3	nc:PersonSexCode	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-18: DNA Data

Page 881 of 1037

18.006_3

Sample Donor Information

Date of Last Contact

Mnemonic	DLC			Conditionality	O
				Status	Active
Description	The third information item, date of last contact / DLC is an optional date field. The local date is recorded as YYYYMMDD. Note that this may be a different date than the corresponding GMT, due to time zone differences.				
Field Min	8	Occur Min	0		
Field Max	8	Occur Max	1		
Char Types	N	Special Chars	None		
Format	YYYYMMDD	Constraints	YYYYMMDD format		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample	Cardinality	1..1		
XML Level 2	biom:DNADonor	Cardinality	1..1		
XML Level 3	biom:DNADonorLastContactDate/nc:Date	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.006_4

Sample Donor Information

Donor Date of Birth

Mnemonic	DOB			Conditionality	O
				Status	Active
Description	The fourth information item, date of birth / DOB, is an optional date field. The local date is recorded as YYYYMMDD. Note that this may be a different date than the corresponding GMT, due to time zone differences.				
Field Min	8	Occur Min	0		
Field Max	8	Occur Max	1		
Char Types	N	Special Chars	None		
Format	YYYYMMDD	Constraints	YYYYMMDD format		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample	Cardinality	1..1		
XML Level 2	biom:DNADonor	Cardinality	1..1		
XML Level 3	nc:PersonBirthDate/nc:Date	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-18: DNA Data

Page 882 of 1037

18.006_5

Sample Donor Information

Ethnic Group

Mnemonic	EGP			Conditionality	O
				Status	Active
Description	The fifth information item is the ethnic group / EGP. It is an optional string of 50 Unicode characters used to describe the ethnic group to which the subject belongs.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars	n/a		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample	Cardinality	1..1		
XML Level 2	biom:DNADonor	Cardinality	1..1		
XML Level 3	nc:PersonEthnicityText	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.006_6

Sample Donor Information

Dental Records Available

Mnemonic	DRA			Conditionality	D
				Status	Active
Description	The sixth information item is optional and indicates if dental records are available for the subject (dental records available / DRA). This information item shall be entered only if DSD = 0.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	DRA = 0, 1 or 2 integer		
Code List	DENTAL RECORD AVAILABLE INDICATION CODES				
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample	Cardinality	1..1		
XML Level 2	biom:DNADonor	Cardinality	1..1		
XML Level 3	biom:DNADonorDentalRecordsAvailableCode	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.006_7

Sample Donor Information

Sample Collection Location Description

Mnemonic	LLC			Conditionality	O
				Status	Active
Description	The seventh optional information item is the sample collection location description / LLC. It is an optional string of up to 4000 Unicode characters.				
Field Min	1	Occur Min	0		
Field Max	4000	Occur Max	1		
Char Types	U	Special Chars	n/a		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample	Cardinality	1..1		
XML Level 2	biom:DNADonor	Cardinality	1..1		
XML Level 3	biom:DNADonorCollectionLocationDescriptionText	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.006_8

Sample Donor Information

Sample Donor Status

Mnemonic	SDS			Conditionality	O
				Status	Active
Description	The eighth optional information item is the sample donor status / SDS. This information item will include whether or not the sample donor is deceased, missing or unknown. Normally, this item would only be used for the sample associated with the subject of the transaction (SDI = 0), but it could be possible to use it in other cases, such as a hair sample from a deceased relative. It could also be 'unknown' for the purported relative's status, but DNA samples were available for that individual (such as blood sample previously collected).				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	SDS = 0, 1 or 2 integer		
Code List	DNA SAMPLE DONOR STATUS CODES				
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample	Cardinality	1..1		
XML Level 2	biom:DNADonor	Cardinality	1..1		
XML Level 3	biom:DNADonorStatusCode	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.007

Claimed Or Purported Relationship

Mnemonic	COPR			Conditionality	D
				Status	Active
Description	This field is mandatory if the value for [DNA Sample Donor / DSD] is equal to 1 [Claimed, purported or validated relative].				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	U	Special Chars	n/a		
Format	n/a	Constraints	1 <= COPR <= 7; positive integer		
Code List	RELATIONSHIP CODES				
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample	Cardinality	1..1		
XML Level 2	biom:DNAClaimedRelationshipCode	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.008

Validated Relationship

Mnemonic	VRS			Conditionality	D
				Status	Active
Description	This field is optional and is a numeric value. This information item is completed based upon a comparison of the subject's DNA with the DNA of the person with whom the relationship is claimed or purported. It is only filled in if DSD = 1. This information item is completed based upon a comparison of the subject's DNA with the DNA of the person with whom the relationship is claimed or purported. It is only filled in if [Donor Status Description] DSD = 1 [Claimed or Purported Relationship].				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	1 <= VRS <= 7; positive integer		
Code List	RELATIONSHIP CODES				
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample	Cardinality	1..1		
XML Level 2	biom:DNAValidatedRelationshipCode	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.009

Pedigree Information

Mnemonic	PED			Conditionality	0
				Status	Active
Description	This optional field contains information and structure associated with the pedigree.				
Field Min	n/a			Occur Min	0
Field Max	n/a			Occur Max	1
Char Types	n/a			Special Chars	n/a
Format	n/a			Constraints	n/a
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample			Cardinality	1..1
XML Level 2	biom:DNAPedigree			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.009_1

Pedigree Information

Pedigree ID

Mnemonic	PID			Conditionality	M↑
				Status	Active
Description	The first information item is the pedigree ID / PID. It is a character string of up to 24 Unicode characters. It is mandatory if this field is used and it indicates the identity of the pedigree determined and held at the laboratory that originates the pedigree.				
Field Min	1			Occur Min	1
Field Max	24			Occur Max	1
Char Types	U			Special Chars	n/a
Format	n/a			Constraints	None
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample			Cardinality	1..1
XML Level 2	biom:DNAPedigree			Cardinality	0..1
XML Level 3	biom:DNAPedigreeidentification/nc:identificationID			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-18: DNA Data

Page 886 of 1037

18.009_2

Pedigree Information

Pedigree Member ID

Mnemonic	PMI	Conditionality	M↑
		Status	Active
Description	The second information item is the pedigree member ID / PMI. It is a unique reference within the pedigree. It is mandatory if this field is used. This information item refers to the subject of the transaction. It is a character string of up to 6 Unicode characters. This information item shall also provide the ability to link pedigree information.		
Field Min	1	Occur Min	1
Field Max	6	Occur Max	1
Char Types	U	Special Chars	None
Format	n/a	Constraints	None
Code List			
Source	ANSI/NIST ITL 1-2011 (Type-18)		
XML Level 1	biom:DNASample	Cardinality	1..1
XML Level 2	biom:DNAPedigree	Cardinality	0..1
XML Level 3	biom:DNAPedigreeMemberIdentification/nc:IdentificationID	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

18.009_3

Pedigree Information

Pedigree Member Status

Mnemonic	PMS	Conditionality	M↑
		Status	Active
Description	The third information item is the pedigree member status / PMS. It is mandatory if this field is used. It is a single character.		
Field Min	1	Occur Min	1
Field Max	1	Occur Max	1
Char Types	A	Special Chars	None
Format	n/a	Constraints	PMS = K or U
Code List	PEDIGREE MEMBER STATUS CODES		
Source	ANSI/NIST ITL 1-2011 (Type-18)		
XML Level 1	biom:DNASample	Cardinality	1..1
XML Level 2	biom:DNAPedigree	Cardinality	0..1
XML Level 3	biom:DNAPedigreeMemberStatusCode	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-18: DNA Data

Page 887 of 1037

18.009_4

Pedigree Information

Sample Identifier

Mnemonic	SID			Conditionality	M↑
				Status	Active
Description	The fourth information item is the DNA sample identifier / SID for the transaction. It is not an identifier within the pedigree chain, unlike the following two identifiers or the PID. It is a character string of 24 characters or less. This information item relates the sample in this record to the pedigree.				
Field Min	1	Occur Min	1		
Field Max	24	Occur Max	1		
Char Types	AN	Special Chars	None		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample	Cardinality	1..1		
XML Level 2	biom:DNAPedigree	Cardinality	0..1		
XML Level 3	biom:DNAPedigreeSampleIdentification/nc:IdentificationID	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.009_5

Pedigree Information

Father Identifier

Mnemonic	FID			Conditionality	O↑
				Status	Active
Description	The fifth information item is the father identifier / FID. It is optional and is a numeric value of 3 digits or less that is unique within the pedigree. This information item is the father identified as related to the sample indicated in the PMI item.				
Field Min	1	Occur Min	0		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample	Cardinality	1..1		
XML Level 2	biom:DNAPedigree	Cardinality	0..1		
XML Level 3	biom:DNAPedigreeFatherIdentification/nc:IdentificationID	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-18: DNA Data

Page 888 of 1037

18.009_6

Pedigree Information

Mother Identifier

Mnemonic	MID	Conditionality	O↑
		Status	Active
Description	The sixth information item is the mother identifier / MID. It is optional and is a numeric value of 3 digits or less that is unique within the pedigree. This information item is the mother identified as related to the sample indicated in the PMI item.		
Field Min	1	Occur Min	0
Field Max	3	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	None
Code List			
Source	ANSI/NIST ITL 1-2011 (Type-18)		
XML Level 1	biom:DNASample	Cardinality	1..1
XML Level 2	biom:DNAPedigree	Cardinality	0..1
XML Level 3	biom:DNAPedigreeMotherIdentification/nc:IdentificationID	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

18.009_7

Pedigree Information

Pedigree Comment

Mnemonic	PCM	Conditionality	O↑
		Status	Active
Description	The seventh optional information item is the pedigree comment / PCM. It is up to 2000 Unicode characters.		
Field Min	1	Occur Min	0
Field Max	2000	Occur Max	1
Char Types	U	Special Chars	n/a
Format	n/a	Constraints	None
Code List			
Source	ANSI/NIST ITL 1-2011 (Type-18)		
XML Level 1	biom:DNASample	Cardinality	1..1
XML Level 2	biom:DNAPedigree	Cardinality	0..1
XML Level 3	biom:DNAPedigreeCommentText	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

18.01

Sample Type

Mnemonic	STY			Conditionality	M
				Status	Active
Description	This mandatory field contains two information items. The first represents the origination cell type from where the sample was collected (sample cellular type / SCT). The second information item is the sample origin / SMO. It is an optional item of a string of 2 characters describing where the sample was obtained.				
Field Min	n/a	Occur Min	1		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample			Cardinality	1..1
XML Level 2	biom:DNASampleOrigin			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.010_1

Sample Type

Sample Cellular Type

Mnemonic	SCT			Conditionality	M
				Status	Active
Description	This information item represents the origination cell type from where the sample was collected (sample cellular type / SCT). It is mandatory.				
Field Min	1	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= STY <= 11; positive integer		
Code List	DNA SAMPLE CELLULAR CODES				
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample			Cardinality	1..1
XML Level 2	biom:DNASampleOrigin			Cardinality	1..1
XML Level 3	biom:DNACellularCategoryCode			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-18: DNA Data

Page 890 of 1037

18.010_2

Sample Type

Sample Origin

Mnemonic	SMO			Conditionality	O
				Status	Active
Description	The second information item is the sample origin / SMO. It is an optional item of a string of 2 characters describing where the sample was obtained.				
Field Min	2	Occur Min	0		
Field Max	2	Occur Max	1		
Char Types	A	Special Chars	None		
Format	n/a	Constraints	SMO = NS, WB or BP		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample	Cardinality	1..1		
XML Level 2	biom:DNASampleOrigin	Cardinality	1..1		
XML Level 3	biom:DNASampleOriginCode	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.011

Sample Typing Information

Mnemonic	STI			Conditionality	M
				Status	Active
Description	This mandatory field represents the technology utilized to type the DNA sample. A repeating subfield with the following information item shall comprise this field.				
Field Min	n/a	Occur Min	1		
Field Max	n/a	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	n/a		
Code List	DNA SAMPLE TYPING AVAILABILITY CODES				
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample	Cardinality	1..1		
XML Level 2	biom:DNATypingTechnologyCategoryCode	Cardinality	0..		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.011_0

Sample Typing Information

Mnemonic	STI_0		Conditionality	M
			Status	Active
Description	This mandatory field represents the technology utilized to type the DNA sample. A repeating subfield with the following information item shall comprise this field.			
Field Min	1	Occur Min	1	
Field Max	1	Occur Max	5	
Char Types	N	Special Chars	None	
Format	n/a	Constraints	0 <= STI <= 4; non-negative integer	
Code List	DNA SAMPLE TYPING AVAILABILITY CODES			
Source	ANSI/NIST ITL 1-2011 (Type-18)			
XML Level 1	biom:DNASample	Cardinality	1..1	
XML Level 2	biom:DNATypingTechnologyCategoryCode	Cardinality	0..	
XML Level 3	biom:DNATypingTechnologyCategoryCode	Cardinality	1..5	
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0 Yes
				DoD EBTS 4.0 Yes

18.012

Sample Collection Method

Mnemonic	SCM		Conditionality	O
			Status	Active
Description	This field contains a description of the method used to collect the DNA sample. It is a character string up to 255 characters.			
Field Min	1	Occur Min	0	
Field Max	255	Occur Max	1	
Char Types	U	Special Chars	n/a	
Format	n/a	Constraints	None	
Code List				
Source	ANSI/NIST ITL 1-2011 (Type-18)			
XML Level 1	biom:DNASample	Cardinality	1..1	
XML Level 2	biom:DNATypingTechnologyCategoryCode	Cardinality	0..	
XML Level 3	biom:DNASampleCollectionMethodText	Cardinality	0..1	
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0 Yes
				DoD EBTS 4.0 Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-18: DNA Data

Page 892 of 1037

18.013

Sample Collection Date

Mnemonic	SCD			Conditionality	M
				Status	Active
Description	This mandatory field contains the date and time that the sample was collected.				
Field Min	15	Occur Min	1		
Field Max	15	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	Description points to 7.7.2.2 YYYYMMDDhhmmssZ, where the Z is indicates the zone description of 0 hours format. Consider naming as "Sample Collection DateTime"		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample (1...1)/BiometricCaptureDetail			Cardinality	1..1
XML Level 2	biom_2:CaptureDate/nc:Date			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.014

Profile Storage Date

Mnemonic	PSD			Conditionality	M
				Status	Active
Description	This mandatory field contains date and time the sample was collected.				
Field Min	15	Occur Min	1		
Field Max	15	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	Description points to 7.7.2.2 YYYYMMDDhhmmssZ, where the Z is indicates the zone description of 0 hours format. Consider naming as "PROFILE STORAGE DATETIME".		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample			Cardinality	1..1
XML Level 2	biom:DNAProfileStorageDate/nc:Date			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.015

DNA Profile Data

Mnemonic	DPD			Conditionality	M
				Status	Active
Description	This is a mandatory field. It contains information and structure associated with the DNA profile data.				
Field Min	n/a	Occur Min	1		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample (1...1)/biom:DNAProfile (1...1)			Cardinality	1..1
XML Level 2	biom:DNAProfile			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.015_1

DNA Profile Data

Profile Type

Mnemonic	PTP			Conditionality	M
				Status	Active
Description	The first information item is mandatory. It is the profile type / PTP. It is a numerical value. Allowable values are 0 = Person or 1 = Stain.				
Field Min	1	Occur Min	1		
Field Max	1	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	PTP = 0 or 1 integer		
Code List	DNA PROFILE TYPE				
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample (1...1)/biom:DNAProfile (1...1)			Cardinality	1..1
XML Level 2	biom:DNAProfile			Cardinality	1..1
XML Level 3	biom:DNAProfileCategoryCode			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-18: DNA Data

Page 894 of 1037

18.015_2

DNA Profile Data

Result

Mnemonic	RES			Conditionality	O
				Status	Active
Description	The second information item is optional and is the result / RES. It is entered with a numeric value selected from Table 78 [DNA Result Codes].				
Field Min	1	Occur Min	0		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= RES <= 10 integer		
Code List	DNA PROFILE RESULT CODES				
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample (1...1)/biom:DNAProfile (1...1)			Cardinality	1..1
XML Level 2	biom:DNAProfile			Cardinality	1..1
XML Level 3	biom:DNAProfileResultCode			Cardinality	0..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.015_3

DNA Profile Data

Profile ID

Mnemonic	PRF			Conditionality	M
				Status	Active
Description	The third information item is mandatory and is the profile ID / PRF. It is a character string with a unique party identification. This information item is used to uniquely identify the profile or sample for which the transaction is based. It is a maximum of 64 alphanumeric characters.				
Field Min	1	Occur Min	1		
Field Max	64	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample (1...1)/biom:DNAProfile (1...1)			Cardinality	1..1
XML Level 2	biom:DNAProfile			Cardinality	1..1
XML Level 3	biom:DNAProfileIdentification/nc:IdentificationID			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.015_4

DNA Profile Data

Supplemental Message

Mnemonic	SUP			Conditionality	O
				Status	Active
Description	The optional fourth information item is a supplemental message / SUP. This information item states if this transaction is a supplemental message to a previous transmission. It is an alphanumeric string containing up to 100 characters.				
Field Min	1	Occur Min	0		
Field Max	100	Occur Max	1		
Char Types	U	Special Chars	n/a		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample (1..1)/biom:DNAProfile (1..1)			Cardinality	1..1
XML Level 2	biom:DNAProfile			Cardinality	1..1
XML Level 3	biom:DNAProfileSupplementalText			Cardinality	0..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.015_5

DNA Profile Data

DNA Profile Comment

Mnemonic	DPC			Conditionality	O
				Status	Active
Description	The optional fifth information item is a DNA profile comment / DPC. It is up to 100 Unicode characters.				
Field Min	1	Occur Min	0		
Field Max	100	Occur Max	1		
Char Types	U	Special Chars	n/a		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample (1..1)/biom:DNAProfile (1..1)			Cardinality	1..1
XML Level 2	biom:DNAProfile			Cardinality	1..1
XML Level 3	biom:DNAProfileCommentText			Cardinality	0..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.016

Autosomal STR, X-STR and Y-STR Profile

Mnemonic	STR			Conditionality	D
				Status	Active
Description	This optional field may be comprised of as many subfields as there are combinations of data type and locus type reported. This field is only present if Field 18.011: Sample typing Information / STI has a subfield with the value 0.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample (1...1)/biom:DNAProfile (1...1)			Cardinality	1..1
XML Level 2	biom:DNASTRProfile			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.016_0

Autosomal STR, X-STR and Y-STR Profile

Mnemonic	STR_0			Conditionality	M↑
				Status	Active
Description	This field may be comprised of as many subfields as there are combinations of data type and locus type reported. This field is only present if Field 18.011: Sample typing Information / STI has a subfield with the value 0.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	*		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample (1...1)/biom:DNAProfile (1...1)			Cardinality	1..1
XML Level 2	biom:DNASTRProfile			Cardinality	0..*
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-18: DNA Data

Page 897 of 1037

18.016_1

Autosomal STR, X-STR and Y-STR Profile

DNA STR Type

Mnemonic	DST			Conditionality	M↑
				Status	Active
Description	The first information item is mandatory. It is the DNA STR type / DST.				
Field Min	1	Occur Min	1		
Field Max	1	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	DST = 0, 1 or 2 integer		
Code List	DNA STR TYPE CODES				
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample (1...1)/biom:DNAProfile (1...1)			Cardinality	1..1
XML Level 2	biom:DNASTRProfile			Cardinality	0..*
XML Level 3	biom:DNASTRProfileCategoryCode			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.016_2

Autosomal STR, X-STR and Y-STR Profile

DNA Locus Reference

Mnemonic	DLR			Conditionality	M↑
				Status	Active
Description	The second information item is mandatory. It is the DNA locus reference / DLR. The current valid loci for Autosomal, Y and X-STRs are maintained by NIST and are available at http://www.nist.gov/itl/iad/ig/ansi_standard.cfm . This information item is an integer entry with up to 3 characters per locus.				
Field Min	1	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	1 <= DLR <= 200; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample (1...1)/biom:DNAProfile (1...1)			Cardinality	1..1
XML Level 2	biom:DNASTRProfile			Cardinality	0..*
XML Level 3	biom:DNALocusIdentification/nc:IdentificationID			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-18: DNA Data

Page 898 of 1037

18.016_3

Autosomal STR, X-STR and Y-STR Profile

Allele Indicator

Mnemonic	ALL	Conditionality	M↑
		Status	Active
Description	The third information item, allele indicator / ALL, is mandatory. It is a numeric entry containing a zero if no allele is found. Otherwise it is filled with a 1.		
Field Min	1	Occur Min	1
Field Max	1	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	ALL = 0 or 1 integer
Code List			
Source	ANSI/NIST ITL 1-2011 (Type-18)		
XML Level 1	biom:DNASample (1...1)/biom:DNAProfile (1...1)	Cardinality	1..1
XML Level 2	biom:DNASTRProfile	Cardinality	0..*
XML Level 3	biom:DNAAlleleIndicator	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

18.016_4

Autosomal STR, X-STR and Y-STR Profile

Locus Analysis Indicator

Mnemonic	LAI	Conditionality	M↑
		Status	Active
Description	The fourth information item is mandatory. It is the locus analysis indicator / LAI. It is a numeric entry, containing a zero if not analyzed. Otherwise it contains a 1.		
Field Min	1	Occur Min	1
Field Max	1	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	LAI = 0 or 1 integer
Code List			
Source	ANSI/NIST ITL 1-2011 (Type-18)		
XML Level 1	biom:DNASample (1...1)/biom:DNAProfile (1...1)	Cardinality	1..1
XML Level 2	biom:DNASTRProfile	Cardinality	0..*
XML Level 3	biom:DNALocusAnalysisIndicator	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-18: DNA Data

Page 899 of 1037

18.016_5

Autosomal STR, X-STR and Y-STR Profile

Precise Call Determination

Mnemonic	PCDT			Conditionality	M↑
				Status	Active
Description	The fifth information item is mandatory. It is the precise call determination / PCDT. It is a numeric entry containing a zero if the precise call cannot be determined, due to an uncertainty in the call. Otherwise it contains a 1.				
Field Min	1	Occur Min	1		
Field Max	1	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	PCDT = 0 or 1 integer		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample (1...1)/biom:DNAProfile (1...1)			Cardinality	1..1
XML Level 2	biom:DNASTRProfile			Cardinality	0..*
XML Level 3	biom:DNAPreciseCallIndicator			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.016_6

Autosomal STR, X-STR and Y-STR Profile

Allele Call 1

Mnemonic	AL1			Conditionality	D
				Status	Active
Description	The sixth information item is conditional upon the value of ALL being 1. It is the allele call 1 / AL1. This is the allele call for the locus reference DLR.				
Field Min	1	Occur Min	0		
Field Max	4	Occur Max	1		
Char Types	NS	Special Chars	Period		
Format	n/a	Constraints	integer > 0; or real number with one digit to right of decimal		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample (1...1)/biom:DNAProfile (1...1)			Cardinality	1..1
XML Level 2	biom:DNASTRProfile			Cardinality	0..*
XML Level 3	biom:DNAAlleleCall1Text			Cardinality	0..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.016_7

Autosomal STR, X-STR and Y-STR Profile

Allele Call 2

Mnemonic	AL2	Conditionality	D
		Status	Active
Description	The eighth information item is optional but shall not appear unless ALL = 1. It is the allele call 2 / AL2. This is the allele call for the locus reference DLR. This is not used for mixtures, but is for the rare case of a tri-allele. The information item allele call 3 / AL3 shall only appear if information items AL1 and AL2 are present.		
Field Min	1	Occur Min	0
Field Max	4	Occur Max	1
Char Types	NS	Special Chars	Period
Format	n/a	Constraints	integer > 0; or real number with one digit to right of decimal
Code List			
Source	ANSI/NIST ITL 1-2011 (Type-18)		
XML Level 1	biom:DNASample (1...1)/biom:DNAProfile (1...1)	Cardinality	1..1
XML Level 2	biom:DNASTRProfile	Cardinality	0..*
XML Level 3	biom:DNAAlleleCall2Text	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

18.016_8

Autosomal STR, X-STR and Y-STR Profile

Allele Call 3

Mnemonic	AL3	Conditionality	D
		Status	Active
Description	The eighth information item is optional but shall not appear unless ALL = 1. It is the allele call 3 / AL3. This is the allele call for the locus reference DLR. This is not used for mixtures, but is for the rare case of a tri-allele. The information item allele call 3 / AL3 shall only appear if information items AL1 and AL2 are present.		
Field Min	1	Occur Min	0
Field Max	4	Occur Max	1
Char Types	NS	Special Chars	Period
Format	n/a	Constraints	integer > 0; or real number with one digit to right of decimal
Code List			
Source	ANSI/NIST ITL 1-2011 (Type-18)		
XML Level 1	biom:DNASample (1...1)/biom:DNAProfile (1...1)	Cardinality	1..1
XML Level 2	biom:DNASTRProfile	Cardinality	0..*
XML Level 3	biom:DNAAlleleCall3Text	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

18.016_9

Autosomal STR, X-STR and Y-STR Profile

Batch ID

Mnemonic	BID			Conditionality	O↑
				Status	Active
Description	The ninth information item is the batch ID / BID. This optional information item shall contain an identifier for the batch to which a locus belongs. This may be referred to as the gel or plate identifier. A specimen may have loci from multiple batches. The BID shall be up to 32 Unicode characters.				
Field Min	1	Occur Min	0		
Field Max	32	Occur Max	1		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample (1...1)/biom:DNAProfile (1...1)			Cardinality	1..1
XML Level 2	biom:DNASTRProfile			Cardinality	0..*
XML Level 3	biom:DNABatchIdentification/nc:IdentificationID			Cardinality	0..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.016_10

Autosomal STR, X-STR and Y-STR Profile

Electropherogram Cross Reference

Mnemonic	ECR			Conditionality	O↑
				Status	Active
Description	The tenth information item is optional. It is called the electropherogram cross reference / ECR and has the same value as the electropherogram image reference / EIR from the appropriate subfield of Field 18.019: Electropherogram description / EPD that is associated with the information in this field and particular subfield instance (if there is such an electropherogram present in this instance of the record).				
Field Min	1	Occur Min	0		
Field Max	8	Occur Max	1		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample (1...1)/biom:DNAProfile (1...1)			Cardinality	1..1
XML Level 2	biom:DNASTRProfile			Cardinality	0..*
XML Level 3	biom:DNAElectropherogramIdentification/nc:IdentificationID			Cardinality	0..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-18: DNA Data

Page 902 of 1037

18.016_11

Autosomal STR, X-STR and Y-STR Profile

Ladder Cross Reference

Mnemonic	LCR			Conditionality	O↑
				Status	Active
Description	The eleventh information item is optional. It is called the ladder cross reference / LCR and has the same value as the ladder image reference / LIR from the appropriate subfield of Field 18.023: Electropherogram ladder / EPL that is associated with the in and particular subfield instance (if there is such a ladder present in this instance of the record).				
Field Min	1	Occur Min	0		
Field Max	8	Occur Max	1		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample (1...1)/biom:DNAProfile (1...1)			Cardinality	1..1
XML Level 2	biom:DNASTRProfile			Cardinality	0..*
XML Level 3	biom:DNAElectropherogramLadderIdentification/nc:IdentificationID			Cardinality	0..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.016_12

Autosomal STR, X-STR and Y-STR Profile

Kit ID

Mnemonic	KID			Conditionality	M↑
				Status	Active
Description	The twelfth information item is the kit ID / KID. This mandatory information item contains a number that references the kit used to process the DNA described in this record. The numeric values for specific kits are contained in the table of kits maintained by NIST at: http://www.nist.gov/itl/iad/ig/ansi_standard.cfm . The values to be entered are those in the "Reference Number" column. The KID value shall be represented as 0 for a non-listed kit. If a non-listed kit is used (KID = 0), then the following three information items are mandatory.				
Field Min	1	Occur Min	0		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= KID <= 999; integer		
Code List	DNA KIT ID CODES				
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample (1...1)/biom:DNAProfile (1...1)			Cardinality	1..1
XML Level 2	biom:DNASTRProfile (0..*)/biom:DNAKit (1...1)			Cardinality	1..1
XML Level 3	biom:DNAKitIdentification/nc:IdentificationID			Cardinality	0..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-18: DNA Data

Page 903 of 1037

18.016_13

Autosomal STR, X-STR and Y-STR Profile

Kit Name

Mnemonic	KNM	Conditionality	D
		Status	Active
Description	The thirteenth information item is the kit name / KNM. This is an alphanumeric value of up to 32 Unicode characters. KNM shall be entered if KID = 0.		
Field Min	1	Occur Min	0
Field Max	32	Occur Max	1
Char Types	U	Special Chars	n/a
Format	n/a	Constraints	None
Code List			
Source	ANSI/NIST ITL 1-2011 (Type-18)		
XML Level 1	biom:DNASample (1...1)/biom:DNAProfile (1...1)	Cardinality	1..1
XML Level 2	biom:DNASTRProfile (0...*)/biom:DNAKit (1...1)	Cardinality	1..1
XML Level 3	biom:DNAKitName	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

18.016_14

Autosomal STR, X-STR and Y-STR Profile

Manufacturer

Mnemonic	KMF	Conditionality	D
		Status	Active
Description	The fourteenth information item is the manufacturer / KMF. It is an alphanumeric value of up to 32 Unicode characters. KMF shall be entered if KID = 0.		
Field Min	1	Occur Min	0
Field Max	32	Occur Max	1
Char Types	U	Special Chars	n/a
Format	n/a	Constraints	None
Code List			
Source	ANSI/NIST ITL 1-2011 (Type-18)		
XML Level 1	biom:DNASample (1...1)/biom:DNAProfile (1...1)	Cardinality	1..1
XML Level 2	biom:DNASTRProfile (0...*)/biom:DNAKit (1...1)	Cardinality	1..1
XML Level 3	biom:DNAKitManufacturerName	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-18: DNA Data

Page 904 of 1037

18.016_15

Autosomal STR, X-STR and Y-STR Profile

Description of the Kit (with part or catalog number)

Mnemonic	KDS		Conditionality	D			
			Status	Active			
Description	The fifteenth information item is the description of the kit (with part or catalog number) / KDS. This is up to 128 Unicode characters. KDS shall be entered if KID = 0.						
Field Min	1	Occur Min	0				
Field Max	128	Occur Max	1				
Char Types	U	Special Chars	n/a				
Format	n/a	Constraints	None				
Code List							
Source	ANSI/NIST ITL 1-2011 (Type-18)						
XML Level 1	biom:DNASample (1...1)/biom:DNAProfile (1...1)		Cardinality	1..1			
XML Level 2	biom:DNASTRProfile (0...*)/biom:DNAKit (1...1)		Cardinality	1..1			
XML Level 3	biom:DNAKitDescriptionText		Cardinality	0..1			
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

18.017

Mitochondrial DNA Data

Mnemonic	DMD		Conditionality	D			
			Status	Active			
Description	To accommodate the differences in how mtDNA types are derived (differences from reference), the interpretation issue is avoided in this standard by dividing the control region into 2 regions (even though HV3 exists) to ensure any insertions /deletions/stretchches are included. This method enables any receiver of the data to use it in a way to which they are accustomed (either using the full sequence or interpreting the full sequence according to their own methodology). The resultant data use would then be fully consistent with the receiver's database and enable processing. This is an optional field, but if it is entered, all information items are mandatory. This field is only present if Field 18.011: Sample typing information / STI has a subfield with the value 1.						
Field Min	n/a	Occur Min	0				
Field Max	n/a	Occur Max	1				
Char Types	n/a	Special Chars	n/a				
Format	n/a	Constraints	n/a				
Code List							
Source	ANSI/NIST ITL 1-2011 (Type-18)						
XML Level 1	biom:DNASample		Cardinality	1..1			
XML Level 2	biom:DNAMitochondrialData		Cardinality	0..1			
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

18.017_1

Mitochondrial DNA Data

Mito Control Region 1

Mnemonic	MT1			Conditionality	M↑
				Status	Active
Description	This information item is the mito control region 1 / MT1. It is defined as inclusive of HV1, starting at 16024 and ending at 16569. The string may have up to 400 insertions. This string length allows for insertions in HV1. Each character is an IUPAC value.				
Field Min	1	Occur Min	1		
Field Max	946	Occur Max	1		
Char Types	AS	Special Chars	Comma		
Format	n/a	Constraints	character string from Lookup Codes or a sequence value: A, G, C or T		
Code List	IUPAC DNA CODES				
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample	Cardinality	1..1		
XML Level 2	biom:DNAMitochondrialData	Cardinality	0..1		
XML Level 3	biom:DNAMitoControlRegion1Text	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.017_2

Mitochondrial DNA Data

Mito Control Region 2

Mnemonic	MT2			Conditionality	M↑
				Status	Active
Description	The second information item is the mito control region 2 / MT2 is defined as inclusive of HV2 and HV3, starting at 1 and ending at 576. Up to 400 insertions may be specified . Each character is an IUPAC or a sequence value: A, G, C or T.				
Field Min	1	Occur Min	1		
Field Max	977	Occur Max	1		
Char Types	AS	Special Chars	Comma		
Format	n/a	Constraints	character string from Lookup Codes or a sequence value: A, G, C or T		
Code List	IUPAC DNA CODES				
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample	Cardinality	1..1		
XML Level 2	biom:DNAMitochondrialData	Cardinality	0..1		
XML Level 3	biom:DNAMitoControlRegion2Text	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-18: DNA Data

Page 906 of 1037

18.017_3

Mitochondrial DNA Data

Base Composition Starting Point

Mnemonic	BSP			Conditionality	M↑
				Status	Active
Description	The third information item is the base composition starting point / BSP. This entry is numeric, up to 5 digits. Starting point is the base position (rCRS) where the primer pair starts interrogating the mitochondrial DNA.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	positive integer		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample	Cardinality	1..1		
XML Level 2	biom:DNAMitochondrialData	Cardinality	0..1		
XML Level 3	biom:DNAMitoBaseStartNumeric	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.017_4

Mitochondrial DNA Data

Base Composition Ending Point

Mnemonic	BEP			Conditionality	M↑
				Status	Active
Description	The fourth information item is the base composition ending point / BEP. This entry is numeric, up to 5 digits. Ending point is the base position (rCRS) where the primer pair stops interrogating the mitochondrial DNA.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	positive integer; BEP > BSP		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample	Cardinality	1..1		
XML Level 2	biom:DNAMitochondrialData	Cardinality	0..1		
XML Level 3	biom:DNAMitoBaseEndNumeric	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-18: DNA Data

Page 907 of 1037

18.017_5

Mitochondrial DNA Data

Base Composition A Length

Mnemonic	BCA			Conditionality	M↑
				Status	Active
Description	The fifth information item is the base composition A length / BCA. It is a numerical value of up to two digits. A represents the number of adenines in the region being amplified.				
Field Min	1	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	positive integer		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample	Cardinality	1..1		
XML Level 2	biom:DNAMitochondrialData	Cardinality	0..1		
XML Level 3	biom:DNAMitoBaseAdenineQuantity	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.017_6

Mitochondrial DNA Data

Base Composition G Length

Mnemonic	BCG			Conditionality	M↑
				Status	Active
Description	The sixth information item is the base composition G length / BCG. It is a numerical value of up to two digits. G represents the number of guanines in the region being amplified				
Field Min	1	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	positive integer		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample	Cardinality	1..1		
XML Level 2	biom:DNAMitochondrialData	Cardinality	0..1		
XML Level 3	biom:DNAMitoBaseGuanineQuantity	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-18: DNA Data

Page 908 of 1037

18.017_7

Mitochondrial DNA Data

Base Composition C Length

Mnemonic	BCC			Conditionality	M↑
				Status	Active
Description	The seventh information item is the base composition C length / BCC. It is a numerical value of up to two digits. C represents the number of cytosines in the region being amplified.				
Field Min	1	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	positive integer		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample	Cardinality	1..1		
XML Level 2	biom:DNAMitochondrialData	Cardinality	0..1		
XML Level 3	biom:DNAMitoBaseCytosineQuantity	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.017_8

Mitochondrial DNA Data

Base Composition T Length

Mnemonic	BCT			Conditionality	M↑
				Status	Active
Description	The eighth information item is the base composition T length / BCT. It is a numerical value of up to two digits. T represents the number of thymines in the region being amplified.				
Field Min	1	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	positive integer		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample	Cardinality	1..1		
XML Level 2	biom:DNAMitochondrialData	Cardinality	0..1		
XML Level 3	biom:DNAMitoBaseThymineQuantity	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.018

DNA User-Defined Profile

Mnemonic	UDP			Conditionality	D
				Status	Active
Description	This optional field is user-defined, when data other than Autosomal STR, X-STR, Y-STR, mtDNA or an electropherogram is included as part of the transaction. The sender shall provide the receiver with a description of the field contents. This field is only present if Field 18.011: Sample typing Information / STI has a subfield with the value 4.				
Field Min	n/a	Occur Min	1		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample			Cardinality	1..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.018_0

DNA User-Defined Profile

Mnemonic	UDP_0			Conditionality	M↑
				Status	Active
Description	This field is user-defined, when data other than Autosomal STR, X-STR, Y-STR, mtDNA or an electropherogram is included as part of the transaction. The sender shall provide the receiver with a description of the field contents. This field is only present if Field 18.011: Sample typing Information / STI has a subfield with the value 4.				
Field Min	n/a	Occur Min	1		
Field Max	n/a	Occur Max	*		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample			Cardinality	1..1
XML Level 2	biom:DNAUserDefinedProfile			Cardinality	0..*
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.019

Electropherogram Description

Mnemonic	EPD			Conditionality	D
				Status	Active
Description	This optional field contains a subfield for each electropherogram. This field is only present if Field 18.011: Sample typing Information / STI has a subfield with value 2.				
Field Min	n/a	Occur Min	1		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample			Cardinality	1..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.019_0

Electropherogram Description

Mnemonic	EPD_0			Conditionality	M↑
				Status	Active
Description	This field contains a subfield for each electropherogram. This field is only present if Field 18.011: Sample typing Information / STI has a subfield with value 2.				
Field Min	n/a	Occur Min	1		
Field Max	n/a	Occur Max	*		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample			Cardinality	1..1
XML Level 2	biom:DNAElectropherogram			Cardinality	0..*
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.019_1

Electropherogram Description

Electropherogram Image Reference

Mnemonic	EIR	Conditionality	M↑
		Status	Active
Description	The first information item is the electropherogram image reference / EIR. It shall contain an alphanumeric reference up to 8 characters, which is unique for each image. If none has been assigned, enter 999.		
Field Min	1	Occur Min	1
Field Max	8	Occur Max	1
Char Types	U	Special Chars	Any
Format	n/a	Constraints	If none assigned enter 999
Code List			
Source	ANSI/NIST ITL 1-2011 (Type-18)		
XML Level 1	biom:DNASample	Cardinality	1..1
XML Level 2	biom:DNAElectropherogram	Cardinality	0..*
XML Level 3	biom:DNAElectropherogramIdentification/nc:IdentificationID	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

18.019_2

Electropherogram Description

Electropherogram Storage Type

Mnemonic	EST	Conditionality	M↑
		Status	Active
Description	The second information item is the electropherogram storage type / EST. This is a character string of up to 4 characters, representing the file type suffix for the electropherogram. The data is stored in "fsa", "hid" or "----". The dashes may be substituted with character strings for other format types as they become available.		
Field Min	1	Occur Min	1
Field Max	4	Occur Max	1
Char Types	U	Special Chars	n/a
Format	n/a	Constraints	"fsa", "hid" or "----", dashes may be substituted with character strings for other format types as they become available.
Code List			
Source	ANSI/NIST ITL 1-2011 (Type-18)		
XML Level 1	biom:DNASample	Cardinality	1..1
XML Level 2	biom:DNAElectropherogram	Cardinality	0..*
XML Level 3	biom:DNAElectropherogramFileStorageText	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-18: DNA Data

Page 912 of 1037

18.019_3

Electropherogram Description

Image Data Descriptor

Mnemonic	IDD			Conditionality	M↑
				Status	Active
Description	The third information item is the image data descriptor / IDD of the electropherogram contained in this subfield. If the data is stored externally, enter the filename. This is a Unicode string of up to 200 characters.				
Field Min	1	Occur Min	1		
Field Max	200	Occur Max	1		
Char Types	U	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample	Cardinality	1..1		
XML Level 2	biom:DNAElectropherogram	Cardinality	0..*		
XML Level 3	biom:DNAElectropherogramDataDescriptionText	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.019_4

Electropherogram Description

Electropherogram Data

Mnemonic	ELPD			Conditionality	M↑
				Status	Active
Description	The fourth information item is the electropherogram data/ ELPD. This shall be stored in base-64 format.				
Field Min	2	Occur Min	1		
Field Max	Unlimited	Occur Max	1		
Char Types	Base64	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample	Cardinality	1..1		
XML Level 2	biom:DNAElectropherogram	Cardinality	0..*		
XML Level 3	biom:DNAElectropherogramBinaryObject	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.019_5

Electropherogram Description

Electropherogram Screenshot

Mnemonic	EPS			Conditionality	0↑		
				Status	Active		
Description	The fifth information item is optional. It is the electropherogram screenshot / EPS. This may be an image captured during the analysis. This shall be stored in base-64 format.						
Field Min	2		Occur Min	1			
Field Max	Unlimited		Occur Max	1			
Char Types	Base64		Special Chars	n/a			
Format	n/a		Constraints	n/a			
Code List							
Source	ANSI/NIST ITL 1-2011 (Type-18)						
XML Level 1	biom:DNASample			Cardinality	1..1		
XML Level 2	biom:DNAElectropherogram			Cardinality	0..*		
XML Level 3	biom:DNAElectropherogramScreenshotImage			Cardinality	0..1		
XML Level 4	nc:BinaryBase64Object			Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

18.02

DNA Genotype Distribution

Mnemonic	DGD			Conditionality	0		
				Status	Active		
Description	This field contains informative genotype representation type of DNA information. It is an optional field. The entry is numeric: 0 = Likelihood 1 = Probability.						
Field Min	1		Occur Min	0			
Field Max	1		Occur Max	1			
Char Types	N		Special Chars	None			
Format	n/a		Constraints	DGD = 0 or 1; integer			
Code List	DNA GENOTYPE DISTROBUTION CODES						
Source	ANSI/NIST ITL 1-2011 (Type-18)						
XML Level 1	biom:DNASample			Cardinality	1..1		
XML Level 2	biom:DNAGenotypeDistributionCode			Cardinality	0..1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-18: DNA Data

Page 914 of 1037

18.021

DNA Genotype Allele Pair

Mnemonic	GAP			Conditionality	D
				Status	Active
Description	This field is only present if Field 18.020: DNA Genotype Distribution / DGD has a value. It is used for low-template, mixture or stain scenarios only. It is comprised of a repeating subfield that occurs once for each allele pair. Allele calls are captured in Field 18.016: Autosomal STR, X-STR and Y-STR profile / STR.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample	Cardinality	1..1		
XML Level 2	biom:DNAGenotypeAllelePair	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.021_0

DNA Genotype Allele Pair

Mnemonic	GAP_0			Conditionality	M↑
				Status	Active
Description	This field is only present if Field 18.020: DNA Genotype Distribution / DGD has a value. It is used for low-template, mixture or stain scenarios only. It is comprised of a repeating subfield that occurs once for each allele pair. Allele calls are captured in Field 18.016: Autosomal STR, X-STR and Y-STR profile / STR.				
Field Min	n/a	Occur Min	1		
Field Max	n/a	Occur Max	*		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample	Cardinality	1..1		
XML Level 2	biom:DNAGenotypeAllelePair	Cardinality	0..*		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.021_1

DNA Genotype Allele Pair

Genotype Locus Reference

Mnemonic	GLR		Conditionality	M↑
			Status	Active
Description	The first information item is the genotype locus reference / GLR. The current valid loci for Autosomal, Y and X-STRs are maintained by NIST and are available at http://www.nist.gov/itl/iad/ig/ansi_standard.cfm . The GLR is a numeric entry with up to 3 characters per locus. The maximum value of 200 listed in Table 100 is to allow for potential additions to the loci reference table.			
Field Min	1	Occur Min	1	
Field Max	3	Occur Max	1	
Char Types	N	Special Chars	None	
Format	n/a	Constraints	1 <= GLR <= 200; positive integer	
Code List	DNA LOCI CODES			
Source	ANSI/NIST ITL 1-2011 (Type-18)			
XML Level 1	biom:DNASample	Cardinality	1..1	
XML Level 2	biom:DNAGenotypeAllelePair	Cardinality	0..*	
XML Level 3	biom:DNALocusIdentification/nd:IdentificationID	Cardinality	1..1	
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0 Yes
				DoD EBTS 4.0 Yes

18.021_2

DNA Genotype Allele Pair

Allele Pair

Mnemonic	ALP		Conditionality	M↑
			Status	Active
Description	The second information item is the allele pair / ALP. This is a numeric information item containing the allele pair data of up to 9 numeric characters separated by a comma between values. An example is "14,23.3" or "22.1,23.3"			
Field Min	3	Occur Min	1	
Field Max	9	Occur Max	1	
Char Types	NS	Special Chars	n/a	
Format	n/a	Constraints	n/a	
Code List				
Source	ANSI/NIST ITL 1-2011 (Type-18)			
XML Level 1	biom:DNASample	Cardinality	1..1	
XML Level 2	biom:DNAGenotypeAllelePair	Cardinality	0..*	
XML Level 3	biom:DNAGenotypeAllelePairText	Cardinality	1..1	
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0 Yes
				DoD EBTS 4.0 Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-18: DNA Data

Page 916 of 1037

18.021_3

DNA Genotype Allele Pair

Genotype Numerical Weight

Mnemonic	GNW			Conditionality	M↑
				Status	Active
Description	The third information item is the genotype numerical weight / GNW. It is a non-negative real number up to 5 characters ranging from 0 to 1. An example is "0.114".				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	NS	Special Chars	Period		
Format	n/a	Constraints	0 <= GNW <=1; non-negative real number up to 5 characters, which may have a period		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample	Cardinality	1..1		
XML Level 2	biom:DNAGenotypeAllelePair	Cardinality	0..*		
XML Level 3	biom:DNAGenotypeWeightNumeric	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.022

Comment

Mnemonic	COM			Conditionality	0
				Status	Active
Description	The optional Comment field appears in many record types and may be used to insert free text information. It is not reserved exclusively for log-related information but has historically often been used for this purpose. It is limited to a maximum of 126 characters. This maximum size was established in order to maintain consistency across encodings. The maximum size differed in the 2007 and 2008 versions of the standard.				
Field Min	1	Occur Min	0		
Field Max	126	Occur Max	1		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample	Cardinality	1..1		
XML Level 2	biom.DNACommentText	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.023

Electropherogram Ladder

Mnemonic	EPL			Conditionality	D
				Status	Active
Description	This optional field contains a repeating subfield for a ladder / control sample. This field is only present if Field 18.011: Sample typing Information / STI has a subfield with the value 3.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample	Cardinality	1..1		
XML Level 2	biom:DNAElectropherogramLadder	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.023_0

Electropherogram Ladder

Mnemonic	EPL_0			Conditionality	M↑
				Status	Active
Description	This field contains a repeating subfield for a ladder / control sample. This field is only present if Field 18.011: Sample typing Information / STI has a subfield with the value 3.				
Field Min	n/a	Occur Min	1		
Field Max	n/a	Occur Max	*		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample	Cardinality	1..1		
XML Level 2	biom:DNAElectropherogramLadder	Cardinality	0..*		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-18: DNA Data

Page 918 of 1037

18.023_1

Electropherogram Ladder

Ladder Image Reference

Mnemonic	LIR			Conditionality	M↑
				Status	Active
Description	The first information item is the ladder image reference / LIR. It shall contain an alphanumeric reference up to 8 characters, which is unique for each image. If none has been assigned, enter 999. This is a unique identifier.				
Field Min	1	Occur Min	1		
Field Max	8	Occur Max	1		
Char Types	U	Special Chars	n/a		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample	Cardinality	1..1		
XML Level 2	biom:DNAElectropherogramLadder	Cardinality	0..*		
XML Level 3	biom:DNAElectropherogramIdentification/nc:IdentificationID	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.023_2

Electropherogram Ladder

Ladder Storage Type

Mnemonic	LST			Conditionality	M↑
				Status	Active
Description	The second information item is the ladder storage type / LST. This is a string of up to 4 characters, representing the file type suffix for the electropherogram. The data is stored in "fsa", "hid" or "----" The dashes may be substituted with character strings for other format types as they become available.				
Field Min	1	Occur Min	1		
Field Max	4	Occur Max	1		
Char Types	U	Special Chars	n/a		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample	Cardinality	1..1		
XML Level 2	biom:DNAElectropherogramLadder	Cardinality	0..*		
XML Level 3	biom:DNAElectropherogramFileStorageText	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-18: DNA Data

Page 919 of 1037

18.023_3

Electropherogram Ladder

Ladder Image Data Descriptor

Mnemonic	LDD	Conditionality	M↑
		Status	Active
Description	The third information item is the ladder image data descriptor / LDD of the electropherogram contained in this subfield. If the data is stored externally, enter the filename. This is an alphanumeric string with special characters allowed. An example is "NIST Run 5 Well A07 12 Jan 11"		
Field Min	1	Occur Min	1
Field Max	200	Occur Max	1
Char Types	U	Special Chars	Any
Format	n/a	Constraints	None
Code List			
Source	ANSI/NIST ITL 1-2011 (Type-18)		
XML Level 1	biom:DNASample	Cardinality	1..1
XML Level 2	biom:DNAElectropherogramLadder	Cardinality	0..*
XML Level 3	biom:DNAElectropherogramDataDescriptionText	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

18.023_4

Electropherogram Ladder

Ladder Electropherogram Data

Mnemonic	LEPD	Conditionality	M↑
		Status	Active
Description	The fourth information item is the ladder electropherogram data/ LEPD. This shall be stored in base-64 format.		
Field Min	2	Occur Min	1
Field Max	Unlimited	Occur Max	1
Char Types	Base64	Special Chars	n/a
Format	n/a	Constraints	None
Code List			
Source	ANSI/NIST ITL 1-2011 (Type-18)		
XML Level 1	biom:DNASample	Cardinality	1..1
XML Level 2	biom:DNAElectropherogramLadder	Cardinality	0..*
XML Level 3	biom:DNAElectropherogramBinaryObject	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

18.023_5

Electropherogram Ladder

Ladder Electropherogram Screenshot

Mnemonic	LES			Conditionality	0↑
				Status	Active
Description	The fifth information item is optional. It is the ladder electropherogram screenshot / LES. This may be an image captured during the analysis. This shall be stored in base-64 format.				
Field Min	2	Occur Min	1		
Field Max	Unlimited	Occur Max	1		
Char Types	Base64	Special Chars	n/a		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample	Cardinality	1..1		
XML Level 2	biom:DNAElectropherogramLadder	Cardinality	0..*		
XML Level 3	biom:DNAElectropherogramScreenshotImage	Cardinality	0..1		
XML Level 4	nc:BinaryBase64Object	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.902

Annotation Information

Mnemonic	ANN			Conditionality	0
				Status	Active
Description	This is an optional field, listing the operations performed on the original source in order to prepare it for inclusion in a biometric record type.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	None		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:ProcessAnnotation	Cardinality	0..1		
XML Level 2		Cardinality			
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-18: DNA Data

Page 921 of 1037

18.902_0

Annotation Information

Subfields: Repeating sets of information items

Mnemonic	ANN_0			Conditionality	M↑
				Status	Active
Description	This is an optional field, listing the operations performed on the original source in order to prepare it for inclusion in a biometric record type.				
Field Min	n/a		Occur Min	1	
Field Max	n/a		Occur Max	*	
Char Types	n/a		Special Chars	None	
Format	n/a		Constraints	None	
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:ProcessAnnotation			Cardinality	0..*
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

18.902_1

Annotation Information

Greenwich Mean Time

Mnemonic	GMT			Conditionality	M↑
				Status	Active
Description	This information item is the Greenwich Mean Time (GMT) when the processing occurred. The data is formatted as YYYYMMDDhhmmssZ, where the Z is indicates the zone description of 0 hours. This time is independent of the actual time zone where the time and date is recorded.				
Field Min	15		Occur Min	1	
Field Max	15		Occur Max	1	
Char Types	AN		Special Chars	None	
Format	YYYYMMDDHHMMSSZ - for Traditional Encoding		Constraints	Dependent upon encoding	
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:ProcessAnnotation			Cardinality	0..*
XML Level 2	biom:ProcessUTCDate/nc:DateTime			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-18: DNA Data

Page 922 of 1037

18.902_2

Annotation Information

Processing Algorithm Name / Version

Mnemonic	NAV			Conditionality	M↑
				Status	Active
Description	This information item shall contain text identifying the name and version of the processing algorithm, application, procedure, or workstation				
Field Min	1	Occur Min	1		
Field Max	*	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:ProcessAnnotation			Cardinality	0..*
XML Level 2	biom:ProcessName			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

18.902_3

Annotation Information

Algorithm Owner

Mnemonic	OWN			Conditionality	M↑
				Status	Active
Description	This information item shall contain an unformatted text string of up to 64 characters with the contact information for the organization that owns the processing algorithm or latent workstation. Where there is no 'algorithm owner,' enter N/A.				
Field Min	1	Occur Min	1		
Field Max	64	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:ProcessAnnotation			Cardinality	0..*
XML Level 2	biom:ProcessOwnerText			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-18: DNA Data

Page 923 of 1037

18.902_4

Annotation Information

Process Description

Mnemonic	PRO			Conditionality	M↑
				Status	Active
Description	This information item field shall contain text describing a process or procedure applied to the sample in this Type-9 record.				
Field Min	1	Occur Min	1		
Field Max	255	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:ProcessAnnotation			Cardinality	0..*
XML Level 2	biom:ProcessDescriptionText			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

18.992

Type-2 Record Cross Reference

Mnemonic	T2C			Conditionality	M
				Status	Active
Description	This is an optional field. When used, it contains the IDC value of the Type-2 record that contains relevant biographic information and other data concerning the subject of this instance of the record, who may be different from the subject of the transacti				
Field Min	1	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= T2C <=99; integer		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:Type2CrossReferenceIdentification/nc:IdentificationID			Cardinality	1..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-18: DNA Data

Page 924 of 1037

18.993

Source Agency Name

Mnemonic	SAN			Conditionality	0
				Status	Active
Description	This is an optional field. It may contain up to 125 Unicode characters. It is the name of the agency referenced in Field xx.004: Source agency / SRC for record types 9-99.				
Field Min	1	Occur Min	0		
Field Max	125	Occur Max	1		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:DNASample	Cardinality	1..1		
XML Level 2	biom:BiometricCaptureDetail	Cardinality	0..1		
XML Level 3	biom:CaptureOrganization	Cardinality	0..1		
XML Level 4	nc:OrganizationName	Cardinality	0..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.995

Annotated Information

Mnemonic	ASC			Conditionality	0
				Status	Active
Description	This optional field refers to one or more Type 21 Records with the same ACN. Type 21 Records contain images that are NOT used to derive the biometric data in Field 13.999: Latent friction ridge image (DATA) but that may be relevant to the collection of that data, such as general scenes of the area where a latent print was found.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:AssociatedContext	Cardinality	0..1		
XML Level 2		Cardinality			
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-18: DNA Data

Page 925 of 1037

18.995_0

Annotated Information

Mnemonic	ASC_0			Conditionality	M↑
				Status	Active
Description	This optional field refers to one or more Type 21 Records with the same ACN. Type 21 Records contain images that are NOT used to derive the biometric data in Field 13.999: Latent friction ridge image (DATA) but that may be relevant to the collection of that data, such as general scenes of the area where a latent print was found.				
Field Min	n/a	Occur Min	1		
Field Max	n/a	Occur Max	255		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:AssociatedContext/nc:IdentificationID			Cardinality	0..255
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

18.995_1

Associated Context Number

Mnemonic	ACN			Conditionality	M↑
				Status	Active
Description	The first information item for the Associated Context field for a particular Record Type-21. This is mandatory for each Field xx.995, when the field is used. It contains an index to a particular instance of a Type-21 record in the transaction. This same index value appears in the appropriate instance of Record Type-21 as Field 21.021: Associated context number (CAN). The value of the CAN shall be a sequentially assigned a positive integer starting from one and incremented by one, not to exceed 255.				
Field Min	1	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	n/a	Special Chars	None		
Format	n/a	Constraints	1 <= ACN <= 255; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-18)				
XML Level 1	biom:AssociatedContext/nc:IdentificationID			Cardinality	0..255
XML Level 2	biom:ContextIdentification/nc:IdentificationID			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-18: DNA Data

Page 926 of 1037

18.995_2

Associated Context

Associated Segment Position

Mnemonic	ASP			Conditionality	0↑		
				Status	Active		
Description	The first information item is the associated segment position (ASP). This provides a unique index to a segmentation.						
Field Min	1		Occur Min	0			
Field Max	2		Occur Max	1			
Char Types	n/a		Special Chars	n/a			
Format	n/a		Constraints	1 <= ASP <= 99; positive integer			
Code List							
Source	ANSI/NIST ITL 1-2011 (Type-18)						
XML Level 1	biom:AssociatedContext/nc:IdentificationID			Cardinality	0..255		
XML Level 2	biom_2:ImageSegmentIdentification/nc:IdentificationID			Cardinality	0..1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

18.998

Geographic Sample Acquisition Location

Mnemonic	GEO			Conditionality	0		
				Status	Active		
Description	This optional field contains the location where the iris sample/original source/context information was acquired – not where it is stored.						
Field Min	n/a		Occur Min	0			
Field Max	n/a		Occur Max	1			
Char Types	n/a		Special Chars	n/a			
Format	n/a		Constraints	n/a			
Code List							
Source	ANSI/NIST ITL 1-2011 (Type-14)						
XML Level 1	biom:DNASample			Cardinality	1..1		
XML Level 2	biom:BiometricCaptureDetail			Cardinality	0..1		
XML Level 3	biom:CaptureLocation			Cardinality	0..1		
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-18: DNA Data

Page 927 of 1037

18.998_01

Geographic Sample Acquisition Location

Universal Time Entry

Mnemonic	UTE		Conditionality	O↑
			Status	Active
Description	The coordinated universal time (UTC) where the biometric sample was collected. This time is independent of the actual time zone where the time and date is recorded. The date is YYYYMMDDhhmmssZ, where the Z indicates the zone description of 0 hours. If sample collection time is unknown, set it to "00000000000000Z."			
Field Min	15	Occur Min	0	
Field Max	15	Occur Max	1	
Char Types	AN	Special Chars	None	
Format	YYYYMMDDHHMMSSZ - for Traditional Encoding	Constraints	Dependent upon encoding	
Code List				
Source	ANSI/NIST ITL 1-2011 (Type-14)			
XML Level 1	biom:DNASample	Cardinality	1..1	
XML Level 2	biom:BiometricCaptureDetail	Cardinality	0..1	
XML Level 3	biom:CaptureUTCDateTime/nc:DateTime	Cardinality	0..1	
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0 Yes
				DoD EBTS 4.0 Yes

18.998_02

Geographic Sample Acquisition Location

Latitude Degree Value

Mnemonic	LTD		Conditionality	D
			Status	Active
Description	The second information item is latitude degree value (LTD). This is a value that specifies the degree of latitude. The value shall be between -90 (inclusive) and +90 (inclusive). The degrees may be expressed as an integer (without a decimal) or a real number including decimals. If decimals are present, then minutes and seconds shall be empty. Examples: Buenos Aires, Argentina: -34 (with minutes LTM = 36) NIST, Gaithersburg, Maryland: 39.137627 (no LTM or LTS)			
Field Min	1	Occur Min	0	
Field Max	9	Occur Max	1	
Char Types	NS	Special Chars	Decimal, Minus Sign, Plus Sign	
Format	n/a	Constraints	=-90 <= LTD <= 90	
Code List				
Source	ANSI/NIST ITL 1-2011 (Type-14)			
XML Level 1	biom:DNASample	Cardinality	1..1	
XML Level 2	biom:BiometricCaptureDetail	Cardinality	0..1	
XML Level 3	biom:CaptureLocation(0..1)/biom:LocationTwoDimensionalGeographicCoordinate(0..1)/nc:GeographicCoordinateLatitude (0..1)	Cardinality		
XML Level 4	nc:LatitudeDegreeValue	Cardinality	0..1	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0 Yes
				DoD EBTS 4.0 Yes

18.998_03

Geographic Sample Acquisition Location

Latitude Minute Value

Mnemonic	LTM	Conditionality	D
		Status	Active
Description	This information item is latitude minute value (LTM). This is a value that specifies a minute of a degree. The value shall be between 0 (inclusive) to 60 (exclusive). The minute value may be expressed as an integer (without a decimal) or as a real number including decimals. If decimals are present then seconds shall be empty. Thus, the allowed special character is a period. The minute value can be empty, even if the degree value is an integer. LTM and LGM are co-conditional, so they shall both be present if either is present.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	NS	Special Chars	Decimal
Format	n/a	Constraints	0 <= LTM < 60
Code List			
Source	ANSI/NIST ITL 1-2011 (Type-14)		
XML Level 1	biom:DNASample	Cardinality	1..1
XML Level 2	biom:BiometricCaptureDetail	Cardinality	0..1
XML Level 3	biom:CaptureLocation(0..1)/biom:LocationTwoDimensionalGeographicCoordinate(0..1)/nc:GeographicCoordinateLatitude (0..1)	Cardinality	0..1
XML Level 4	nc:LatitudeMinuteValue	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

18.998_04

Geographic Sample Acquisition Location

Latitude Second Value

Mnemonic	LTS	Conditionality	D
		Status	Active
Description	The fourth information item is the latitude second value (LTS). This is a value that specifies a second of a minute. The integer shall be 0 (inclusive) to 60 (exclusive). The second value is empty, even if the minute value is an integer.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	0 <= LTS < 60
Code List			
Source	ANSI/NIST ITL 1-2011 (Type-14)		
XML Level 1	biom:DNASample	Cardinality	1..1
XML Level 2	biom:BiometricCaptureDetail	Cardinality	0..1
XML Level 3	biom:CaptureLocation(0..1)/biom:LocationTwoDimensionalGeographicCoordinate(0..1)/nc:GeographicCoordinateLatitude (0..1)	Cardinality	0..1
XML Level 4	nc:LatitudeSecondValue	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-18: DNA Data

Page 929 of 1037

18.998_05

Geographic Sample Acquisition Location

Longitude Degree Value

Mnemonic	LGD		Conditionality	D
			Status	Active
Description	The fifth information item is the longitude degree value (LGD). It is a value that specifies the degree of a longitude. The value shall be between -180 (inclusive) and +180 (inclusive). If LTD is present, then LGD shall be present. The degrees may be expressed as whole numbers (without a decimal) or real numbers including decimals. If decimals are present, then minutes and seconds are empty. Examples: Buenos Aires, Argentina: -58 (with minutes LGM = 22), NIST, Gaithersburg, Maryland: -77.216032 (no LGM or LGS)			
Field Min	1	Occur Min	0	
Field Max	10	Occur Max	1	
Char Types	NS	Special Chars	Decimal, Minus Sign, Plus Sign	
Format	n/a	Constraints	-180 <= LGD <= 180	
Code List				
Source	ANSI/NIST ITL 1-2011 (Type-14)			
XML Level 1	biom:DNASample	Cardinality	1..1	
XML Level 2	biom:BiometricCaptureDetail	Cardinality	0..1	
XML Level 3	biom:CaptureLocation(0..1)/biom:LocationTwoDimensionalGeographicCoordinate(0..1)/nc:GeographicCoordinateLongitude (0..1)	Cardinality	0..1	
XML Level 4	nc:LongitudeDegreeValue	Cardinality	0..1	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0
				Yes
				DoD EBTS 4.0
				Yes

18.998_06

Geographic Sample Acquisition Location

Longitude Minute Value

Mnemonic	LGM		Conditionality	D
			Status	Active
Description	The sixth information item is the longitude minute value (LGM). It is a value that specifies a minute of a degree. The value shall be from 0 (inclusive) to 60 (exclusive). The minute value may be expressed as an integer (without a decimal) or as a real number including decimals. If decimals are present then seconds shall not appear. The minute value is empty, even if the degree value is an integer. If LTM is present, then LGM shall be present.			
Field Min	1	Occur Min	0	
Field Max	8	Occur Max	1	
Char Types	NS	Special Chars	Decimal	
Format	n/a	Constraints	0 <= LGM < 60	
Code List				
Source	ANSI/NIST ITL 1-2011 (Type-14)			
XML Level 1	biom:DNASample	Cardinality	1..1	
XML Level 2	biom:BiometricCaptureDetail	Cardinality	0..1	
XML Level 3	biom:CaptureLocation(0..1)/biom:LocationTwoDimensionalGeographicCoordinate(0..1)/nc:GeographicCoordinateLongitude (0..1)	Cardinality	0..1	
XML Level 4	nc:LongitudeMinuteValue	Cardinality	0..1	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0
				Yes
				DoD EBTS 4.0
				Yes

18.998_07

Geographic Sample Acquisition Location

Longitude Second Value

Mnemonic	LGS	Conditionality	D
		Status	Active
Description	The seventh information item is the longitude second value (LGS). This is a value that specifies a second of a minute. The integer shall be 0 (inclusive) to 60 (exclusive). The second value is empty, even if the minute value is an integer. If LTS is present, then LGS shall be present.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	0 <= LGS < 60
Code List			
Source	ANSI/NIST ITL 1-2011 (Type-14)		
XML Level 1	biom:DNASample	Cardinality	1..1
XML Level 2	biom:BiometricCaptureDetail	Cardinality	0..1
XML Level 3	biom:CaptureLocation(0...1)/biom:LocationTwoDimensionalGeographicCoordinate(0...1)/nc:GeographicCoordinateLongitude (0...1)	Cardinality	0..1
XML Level 4	nc:LongitudeSecondValue	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

18.998_08

Geographic Sample Acquisition Location

Elevation

Mnemonic	ELE	Conditionality	O
		Status	Active
Description	The eighth information item is elevation (ELE). It is expressed in meters. It is a numeric value. It is between -422 meters (Dead Sea) and 8848 meters (Mount Everest). Allowed special characters are the negative sign and the period.		
Field Min	3	Occur Min	0
Field Max	8	Occur Max	1
Char Types	NS	Special Chars	Minus Sign,Period
Format	n/a	Constraints	-422.000 < ELE < 8848.000; real number
Code List			
Source	ANSI/NIST ITL 1-2011 (Type-14)		
XML Level 1	biom:DNASample	Cardinality	1..1
XML Level 2	biom:BiometricCaptureDetail	Cardinality	0..1
XML Level 3	biom:CaptureLocation(0...1)/nc:LocationGeographicElevation (0...1)	Cardinality	0..1
XML Level 4	nc:MeasurePointValue	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

18.998_09

Geographic Sample Acquisition Location

Geodetic Datum Code

Mnemonic	GDC	Conditionality	O
		Status	Active
Description	The ninth information item is the geodetic datum code (GDC11). It is an alphanumeric value of 3 to 6 characters in length. This information item is used to indicate which coordinate system was used to represent the values in information items 2 through 7. If no entry is made in this information item, then the basis for the values entered in the first eight information items shall be WGS84, the code for the World Geodetic Survey 1984 version - WGS 84 (G873). See look up codes for values. If no entry is made in this information item, then the basis for the values entered in the first eight information items shall be WGS84, the code for the World Geodetic Survey 1984 version - WGS 84 (G873). See look up codes for values.		
Field Min	2	Occur Min	0
Field Max	6	Occur Max	1
Char Types	AN	Special Chars	None
Format	n/a	Constraints	see Look Up Codes
Code List	GEOGRAPHIC COORDINATE DATUM CODE		
Source	ANSI/NIST ITL 1-2011 (Type-14)		
XML Level 1	biom:DNASample	Cardinality	1..1
XML Level 2	biom:BiometricCaptureDetail	Cardinality	0..1
XML Level 3	biom:CaptureLocation(0...1)/biom:LocationTwoDimensionalGeographicCoordinate (0...1)	Cardinality	0..1
XML Level 4	biom:GeodeticDatumCoordinateSystemName or biom:GeodeticDatumCoordinateSystemCode	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

18.998_10

Geographic Sample Acquisition Location

Geographic Coordinate Universal Transverse Mercator Zone

Mnemonic	GCM	Conditionality	D
		Status	Active
Description	It is an alphanumeric value of 2 to 3 characters. This is a one or two digit UTM zone number followed by the 8 degree latitudinal band designator (which is a single letter).		
Field Min	1	Occur Min	0
Field Max	3	Occur Max	1
Char Types	AN	Special Chars	None
Format	n/a	Constraints	One or two digit UTM zone
Code List			
Source	ANSI/NIST ITL 1-2011 (Type-14)		
XML Level 1	biom:DNASample	Cardinality	1..1
XML Level 2	biom:BiometricCaptureDetail	Cardinality	0..1
XML Level 3	biom:CaptureLocation(0...1)/nc:LocationUTMCoordinate (0...1)	Cardinality	0..1
XML Level 4	nc:UTMGridZoneID	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-18: DNA Data

Page 932 of 1037

18.998_11

Geographic Sample Acquisition Location

Geographic Coordinate Universal Transverse Mercator Easting

Mnemonic	GCE			Conditionality	D
				Status	Active
Description	The eleventh information item is the geographic coordinate universal transverse Mercator easting (GCE). It is an integer of 1 to 6 digits.				
Field Min	1	Occur Min	0		
Field Max	6	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= GCE; integer		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-14)				
XML Level 1	biom:DNASample	Cardinality	1..1		
XML Level 2	biom:BiometricCaptureDetail	Cardinality	0..1		
XML Level 3	biom:CaptureLocation(0..1)/nc:LocationUTMCoordinate (0..1)	Cardinality	0..1		
XML Level 4	nc:UTMEastingValue	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.998_12

Geographic Sample Acquisition Location

Geographic Coordinate Universal Transverse Mercator Northing

Mnemonic	GCN			Conditionality	D
				Status	Active
Description	The twelfth information item is the geographic coordinate universal transverse Mercator northing (GCN). It is an integer of 1 to 8 digits.				
Field Min	1	Occur Min	0		
Field Max	8	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= GCN; integer		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-14)				
XML Level 1	biom:DNASample	Cardinality	1..1		
XML Level 2	biom:BiometricCaptureDetail	Cardinality	0..1		
XML Level 3	biom:CaptureLocation(0..1)/nc:LocationUTMCoordinate (0..1)	Cardinality	0..1		
XML Level 4	nc:UTMNorthingValue	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-18: DNA Data

Page 933 of 1037

18.998_13

Geographic Sample Acquisition Location

Geographic Reference Text

Mnemonic	GRT			Conditionality	O
				Status	Active
Description	It is a free form text describing a street address or other physical location (such as 'Corner of Washington and Madison, Geneva, NY').				
Field Min	1	Occur Min	0		
Field Max	150	Occur Max	1		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-14)				
XML Level 1	biom:DNASample	Cardinality	1..1		
XML Level 2	biom:BiometricCaptureDetail	Cardinality	0..1		
XML Level 3	biom:CaptureLocation(0..1)	Cardinality	0..1		
XML Level 4	nc:LocationDescriptionText	Cardinality	0..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

18.998_14

Geographic Sample Acquisition Location

Geographic Coordinate Other System Identifier

Mnemonic	OSI			Conditionality	O
				Status	Active
Description	A fourteenth optional information item geographic coordinate other system identifier (OSI) allows for other coordinate systems. This information items specifies the system identifier. It is up to 10 characters in length. Examples are: • MGRS (Military Grid Reference System), • USNG (United States National Grid), • GARS (Global Area Reference System), • GEOREF (World Geographic Reference), • LANDMARK landmark (e.g. hydant) and position relative to the landmark.				
Field Min	1	Occur Min	0		
Field Max	10	Occur Max	1		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-14)				
XML Level 1	biom:DNASample	Cardinality	1..1		
XML Level 2	biom:BiometricCaptureDetail	Cardinality	0..1		
XML Level 3	biom:CaptureLocation(0..1)/biom:LocationAlternateGeographicSystemValue (0..1)	Cardinality	0..1		
XML Level 4	biom:GeographicLocationSystemName	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-18: DNA Data

Page 934 of 1037

18.998_15

Geographic Sample Acquisition Location

Geographic Coordinate Other System Value

Mnemonic	OCV		Conditionality	D
			Status	Active
Description	A fifteenth optional information item, is the geographic coordinate other system value (OCV). It shall only be present if OSI is present in the record. It can be up to 126 characters in length. If OSI is LANDMARK, OCV is free text and may be up to 126 characters. For details on the formatting of OCV for the other coordinate systems shown in OSI as examples, see http://earth-info.nga.mil/GandG/coordsys/grids/referencesys.html .			
Field Min	1	Occur Min	0	
Field Max	126	Occur Max	1	
Char Types	U	Special Chars	Any	
Format	n/a	Constraints	None	
Code List				
Source	ANSI/NIST ITL 1-2011 (Type-14)			
XML Level 1	biom:DNASample	Cardinality	1..1	
XML Level 2	biom:BiometricCaptureDetail	Cardinality	0..1	
XML Level 3	biom:CaptureLocation(0...1)/biom:LocationAlternateGeographicSystem Value (0...1)	Cardinality	0..1	
XML Level 4	biom:GeographicLocationText	Cardinality	1..1	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0
			Yes	DoD EBTS 4.0
				Yes

20.001

Record Header

Mnemonic	LEN		Conditionality	M
			Status	Active
Description	The record header appears as the first field (xx.001) in each Record Type. It contains information particular to the encoding format chosen, in order to enable proper reading of the record. In Traditional encoding, this field contains the record length in bytes (including all information separators). In NIEM-conformant XML encoding, this field contains the RecordCategoryCode, which is the numeric representation of the Record Type. n/a			
Field Min	T = 4; X = 1	Occur Min	1	
Field Max	T = 8; X = 2	Occur Max	1	
Char Types	N	Special Chars	None	
Format	n/a	Constraints	positive integer	
Code List				
Source	ANSI/NIST ITL 1-2013 (Type-20)			
XML Level 1	nist-itl:RecordCategoryCode	Cardinality	1..1	
XML Level 2		Cardinality		
XML Level 3		Cardinality		
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0
			Yes	DoD EBTS 4.0
				Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

20.002

Information Designation Character

Mnemonic	IDC		Conditionality	M			
			Status	Active			
Description	Each of the records present in a transaction, with the exception of the Type-1 record, shall include a field (xx.002) containing the information designation character (IDC). The value of the IDC shall be a sequentially assigned positive integer starting from zero and incremented by one up to a maximum of 99. IDC references are stated in Type-1 Field 1.003 Transaction content (CNT) and shall be used to relate information items in the CNT field of the Type-1 record to the other records in the transaction. Two or more records may share a single IDC solely to identify and link together records that pertain to different representations of the same biometric trait. n/a						
Field Min	1	Occur Min	1				
Field Max	2	Occur Max	1				
Char Types	N	Special Chars	None				
Format	n/a	Constraints	0 <= IDC <= 99 integer				
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-20)						
XML Level 1	nist-itl:ImageReferenceIdentification/nc:IdentificationID		Cardinality	1..1			
XML Level 2			Cardinality				
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

20.003

SRN Cardinality

Mnemonic	CAR		Conditionality	M			
			Status	Active			
Description	This mandatory field indicates how this record is being used. It describes the cardinality: one to one (S), one to many (D), or many-to-one (M) of how the source representation record relates to other record(s) within the transaction. n/a						
Field Min	1	Occur Min	1				
Field Max	1	Occur Max	1				
Char Types	A	Special Chars	None				
Format	n/a	Constraints	CAR = S, D, or M				
Code List	CARDINALITY CODE						
Source	ANSI/NIST ITL 1-2013 (Type-20)						
XML Level 1	biom_2:SourceRecordCardinalityCode		Cardinality	1..1			
XML Level 2			Cardinality				
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

20.004

Source Agency

Mnemonic	SRC		Conditionality	M			
			Status	Active			
Description	This is the identifier of the agency that actually created the record and supplied the information contained in it. n/a						
Field Min	1	Occur Min	1				
Field Max	Unlimited	Occur Max	1				
Char Types	U	Special Chars	Any				
Format	n/a	Constraints	None				
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-20)						
XML Level 1	biom:SourceImage or biom:SourceVideo or biom:SourceAudio		Cardinality	1..1			
XML Level 2	biom:ImageCaptureDetail or biom:BiometricCaptureDetail		Cardinality	1..1			
XML Level 3	biom:CaptureOrganization		Cardinality	1..1			
XML Level 4	nc:OrganizationIdentification/nc:IdentificationType		Cardinality	1..1			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

20.005

Source Representation Date

Mnemonic	SRD		Conditionality	O			
			Status	Active			
Description	This optional field shall contain the local date and time that the source representation contained in the record was captured. n/a						
Field Min	Dependent upon encoding		Occur Min	0			
Field Max	Dependent upon encoding		Occur Max	1			
Char Types	N		Special Chars	None			
Format	n/a		Constraints	YYYYMMDDhhmm			
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-20)						
XML Level 1	biom:SourceImage or biom:SourceVideo or biom:SourceAudio		Cardinality	1..1			
XML Level 2	biom:ImageCaptureDetail or biom:BiometricCaptureDetail		Cardinality	1..1			
XML Level 3	biom:CaptureDate		Cardinality	0..1			
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

20.006

Hash

Horizontal Line Length

Mnemonic	HLL			Conditionality	D
				Status	Active
Description	HLL defines the number of pixels contained on a single horizontal line of the image. The maximum horizontal size is limited to 65,535 pixels in Record Types-4 and 8, and to 99,999 for other record types. The minimum value is 10 pixels. The total image size (HLL times VLL) must be able to be accommodated in Field xx.001 for Traditional encoding. n/a				
Field Min	2	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	T = 10 <= HLL <= 99999; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom:SourceImage	Cardinality	1..1		
XML Level 2	biom_2:ImageHorizontalLineLengthPixelQuantity	Cardinality	1..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

20.007

Vertical Line Length

Mnemonic	VLL			Conditionality	D
				Status	Active
Description	VLL defines the number of horizontal lines contained in the image. The maximum vertical size is limited to 65,535 pixels in Record Types-4 and 8, and to 99,999 for other record types. The minimum value is 10 pixels. n/a				
Field Min	2	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	T = 10 <= VLL <= 99999, positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom:SourceImage	Cardinality	1..1		
XML Level 2	biom_2:ImageVerticalLineLengthPixelQuantity	Cardinality	1..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

20.008

Scale Units

Mnemonic	SLC		Conditionality	D
			Status	Active
Description	The image sampling frequency (pixel density). A value of "1" shall indicate pixels per inch. A value of "2" shall indicate pixels per centimeter. A value of "0" in this field indicates that no scale is provided, and the quotient of THPS/TVPS shall provide the pixel aspect ratio. For non-contact images of body parts, SLC shall be set to 0 unless the object being imaged is a fixed distance from the capture device and the ppi or ppm values for the capture device are accurately known at that fixed distance. n/a			
Field Min	1	Occur Min	0	
Field Max	1	Occur Max	1	
Char Types	N	Special Chars	None	
Format	n/a	Constraints	SLC = 0, 1 or 2 integer	
Code List				
Source	ANSI/NIST ITL 1-2013 (Type-20)			
XML Level 1	biom:SourceImage	Cardinality	1..1	
XML Level 2	biom:ImageScaleUnitsCode	Cardinality	0..1	
XML Level 3		Cardinality		
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0
				Yes
				DoD EBTS 4.0
				Yes

20.009

Transmitted Horizontal Pixel Scale

Mnemonic	THPS		Conditionality	D
			Status	Active
Description	This is the integer pixel density used in the horizontal direction of the image if SLC has a value of "1" or "2". If SLC has a value of "0", this information item shall contain the horizontal component of the pixel aspect ratio, up to 5 integer digits. For example, if the SLC value = 1, then the value of THPS could be '1000' for a 1000 ppi sensor. n/a			
Field Min	1	Occur Min	0	
Field Max	5	Occur Max	1	
Char Types	N	Special Chars	None	
Format	n/a	Constraints	positive integer	
Code List				
Source	ANSI/NIST ITL 1-2013 (Type-20)			
XML Level 1	biom:SourceImage	Cardinality	1..1	
XML Level 2	biom:ImageHorizontalPixelDensityValue	Cardinality	0..1	
XML Level 3		Cardinality		
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0
				Yes
				DoD EBTS 4.0
				Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

20.01

Transmitted Vertical Pixel Scale

Mnemonic	TVPS	Conditionality	D
		Status	Active
Description	This is the integer pixel density used in the vertical direction of the image if SLC has a value of "1" or "2". If SLC has a value of "0", this information item shall contain the vertical component of the pixel aspect ratio, up to 5 integer digits. If SLC is 1 or 2, then TVPS shall equal THPS. n/a		
Field Min	1	Occur Min	0
Field Max	5	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	positive integer
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-20)		
XML Level 1	biom:SourceImage	Cardinality	1..1
XML Level 2	biom:ImageVerticalPixelDensityValue	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

20.011

Compression Algorithm

Mnemonic	CGA	Conditionality	D
		Status	Active
Description	This is a mandatory field. It shall specify the algorithm used to compress the transmitted color or grayscale images. n/a		
Field Min	3	Occur Min	0
Field Max	5	Occur Max	1
Char Types	AN	Special Chars	None
Format	n/a	Constraints	value from Image Compression Algorithm Type
Code List	COMPRESSION CODES		
Source	ANSI/NIST ITL 1-2013 (Type-20)		
XML Level 1	biom:SourceImage	Cardinality	1..1
XML Level 2	biom:ImageCompressionAlgorithmText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

20.012

Bits Per Pixel

Mnemonic	BPX			Conditionality	D
				Status	Active
Description	This ASCII field shall contain the number of bits used to represent a pixel. This field shall contain an entry of "8" for normal grayscale values of "0" to "255" or each RGB color component. Any entry in this field greater than "8" shall represent a grayscale or color pixel component with increased precision. n/a				
Field Min	1	Occur Min	0		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	8<= BPX <= 99 positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom:SourceImage	Cardinality	1..1		
XML Level 2	biom:ImageBitsPerPixelQuantity	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

20.013

Color Space

Mnemonic	CSP			Conditionality	D
				Status	Active
Description	It shall contain an entry from the lookup codes below. This field is mandatory if a 2D still image is contained in this instance of the record. Otherwise it shall be omitted. n/a				
Field Min	3	Occur Min	0		
Field Max	4	Occur Max	1		
Char Types	A	Special Chars	None		
Format	n/a	Constraints	Value from Color Space Type		
Code List	COLOR SPACES CODE				
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom:SourceImage	Cardinality	1..1		
XML Level 2	biom:ImageColorSpaceCode	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

20.014

Acquisition Source

Mnemonic	AQS			Conditionality	M
				Status	Active
Description	This mandatory field shall specify and describe the acquisition source. The information items may be repeated for up to 9 sources. n/a				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom_2:SourceAcquisition			Cardinality	0..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

20.014_0

Acquisition Source

Subfields: Repeating sets of information items

Mnemonic	AQS_0			Conditionality	M
				Status	New - Active
Description	This mandatory field shall specify and describe the acquisition source. The information items may be repeated for up to 9 sources. n/a				
Field Min	n/a		Occur Min	1	
Field Max	n/a		Occur Max	9	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom_2:SourceAcquisition			Cardinality	1..9
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

20.014_1

Acquisition Source

Acquisition Source Type

Mnemonic	AQT			Conditionality	M
				Status	Active
Description	The first information item, Acquisition source type (AQT), is mandatory and it shall be a numeric entry selected from the "attribute code" column of the Acquisition Source codelist. n/a				
Field Min	1	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	see Look Up Codes		
Code List	ACQUISITION SOURCE CODE				
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom_2:SourceAcquisition			Cardinality	1..9
XML Level 2	dod-ebts:AcquisitionSourceCode			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

20.014_2

Acquisition Source

Analog to Digital Conversion

Mnemonic	A2D			Conditionality	D
				Status	Active
Description	The second information item is mandatory if the acquisition source is analog, and the data is stored in digital format. It is a text field, analog to digital conversion (A2D), that describes the analog to digital equipment used to store a representation of the source. This field should address parameters used, such as sample rate, if known. n/a				
Field Min	1	Occur Min	0		
Field Max	200	Occur Max	1		
Char Types	U	Special Chars	n/a		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom_2:SourceAcquisition			Cardinality	1..9
XML Level 2	dod-ebts:AcquisitionDigitalConversionDescriptionText			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

20.014_3

Acquisition Source

Radio Transmission Format Description

Mnemonic	FDN			Conditionality	D
				Status	Active
Description	The third information item is mandatory if the AQT is 23 or 24. It is a text field, radio transmission format description (FDN). It is optional for other radio transmission codes. n/a				
Field Min	1	Occur Min	0		
Field Max	200	Occur Max	1		
Char Types	U	Special Chars	n/a		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom_2:SourceAcquisition			Cardinality	1..9
XML Level 2	dod-ebts:AcquisitionFormatDescriptionText			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

20.014_4

Acquisition Source

Acquisition Special Characteristics

Mnemonic	AQSC			Conditionality	D
				Status	Active
Description	The fourth information item is optional. It is a free text field, acquisition special characteristics (AQSC) that is used to describe any specific conditions not mentioned in the [Acquisition Source] table. An example would be a nearinfrared camera outputting images in visible wavelengths. n/a				
Field Min	1	Occur Min	0		
Field Max	200	Occur Max	1		
Char Types	U	Special Chars	n/a		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom_2:SourceAcquisition			Cardinality	1..9
XML Level 2	dod-ebts:AcquisitionSpecialCharacteristicsText			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

20.015

Source Representation Format

Mnemonic	SFT			Conditionality	M
				Status	Active
Description	This is a mandatory field comprised of two information items. n/a				
Field Min	n/a		Occur Min	1	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom_2:SourceFileFormat			Cardinality	1..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

20.015_1

Source Representation Format

File Type

Mnemonic	FTY			Conditionality	M
				Status	Active
Description	The first information item is mandatory. It is file type (FTY). If the source representation is a digital file, this shall contain the suffix indicating the file type (such as JPG). If it is an analog file, enter 'ANALOG'. For digital data stored in other formats (such as digital tape), enter 'OTHER'. n/a				
Field Min	3		Occur Min	1	
Field Max	6		Occur Max	1	
Char Types	U		Special Chars	n/a	
Format	n/a		Constraints	None	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom_2:SourceFileFormat			Cardinality	1..1
XML Level 2	dod-ebts:SourceFileCategoryText			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

20.015_2

Source Representation Format

Decoding Instructions

Mnemonic	DEI			Conditionality	0		
				Status	Active		
Description	The second information item is decoding instructions (DEI). It is optional and contains free text up to 1000 characters. n/a						
Field Min	1			Occur Min	0		
Field Max	1000			Occur Max	1		
Char Types	U			Special Chars	n/a		
Format	n/a			Constraints	None		
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-20)						
XML Level 1	biom_2:SourceFileFormat			Cardinality	1..1		
XML Level 2	dod-ebts:SourceFileDecodingInstructionsText			Cardinality	0..1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

20.016

Segments

Mnemonic	SEG			Conditionality	0		
				Status	New-Active		
Description	This optional field shall consist of a subfield for each segment of a 2D image to be defined. Each subfield consists of a series of information items. n/a						
Field Min	n/a			Occur Min	0		
Field Max	n/a			Occur Max	1		
Char Types	n/a			Special Chars	n/a		
Format	n/a			Constraints	n/a		
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-20)						
XML Level 1	biom:SourceVideo			Cardinality	1..1		
XML Level 2	biom:ImageSegment			Cardinality	0..1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

20.016_0

Segments

Subfields: Repeating sets of information items

Mnemonic	SEG_0			Conditionality	M↑
				Status	Active
Description	This optional field shall consist of a subfield for each segment of a 2D image to be defined. Each subfield consists of a series of information items.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	99	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom:SourceVideo			Cardinality	1..1
XML Level 2	biom:ImageSegment			Cardinality	0..99
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

20.016_1

Segments

Reference Segment Position

Mnemonic	RSP			Conditionality	M↑
				Status	Active
Description	The first information item is the reference segment position / RSP. This provides a unique index to a segmentation.				
Field Min	1		Occur Min	1	
Field Max	2		Occur Max	1	
Char Types	N		Special Chars	None	
Format	n/a		Constraints	1 <= RSP <= 99, positive integer	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom:SourceVideo			Cardinality	1..1
XML Level 2	biom:ImageSegment			Cardinality	0..99
XML Level 3	biom:ImageSegmentIdentification/nc:IdentificationID			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

20.016_2

Segments

Internal File Reference Pointer

Mnemonic	IPT			Conditionality	M↑
				Status	Active
Description	This information item is the internal file reference pointer (IPT). It is set to 0 if the source representation is a single file. If the external file referenced in Field 20.994: External file reference (EFR) or Field 21.994: External file reference (EFR) is a PDF, video, or presentation file, or has multiple locations where a sample may be located, this information item is the reference to the particular instance, such as page, video frame, or slide number used to derive the image transmitted in other record types. If a particular frame is chosen and there is no further image segmentation needed, the following information items shall not be used.				
Field Min	1	Occur Min	1		
Field Max	15	Occur Max	1		
Char Types	ANS	Special Chars	n/a		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom:SourceVideo			Cardinality	1..1
XML Level 2	biom:ImageSegment			Cardinality	0..99
XML Level 3	biom:ImageSegmentInternalIdentification/nc:IdentificationID			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

20.016_3

Segments

Number of Points

Mnemonic	NOP			Conditionality	D
				Status	Active
Description	Specifies the number of vertices. HPO and VPO are repeated as pairs, in order by point following the path, up to the final point – for a total of NOP pairs.				
Field Min	1	Occur Min	0		
Field Max	2	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	3 <= NOP <= 99, positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom:SourceVideo			Cardinality	1..1
XML Level 2	biom:ImageSegment			Cardinality	0..99
XML Level 3	biom:PositionPolygonVertexQuantity			Cardinality	0..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-20: Source Representation

Page 948 of 1037

20.016_4

Segments

Horizontal Point Offset

Mnemonic	HPO			Conditionality	D
				Status	Active
Description	The pixel counts to the right. HPO and VPO are repeated as pairs, in order by point following the path, up to the final point – for a total of NOP pairs.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= HPO <= HLL, positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom:SourceVideo	Cardinality	1..1		
XML Level 2	biom:ImageSegment	Cardinality	0..99		
XML Level 3	biom:PositionPolygonVertexQuantity	Cardinality	0..99		
XML Level 4	biom:PositionHorizontalCoordinateValue	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

20.016_5

Segments

Vertical Point Offset

Mnemonic	VPO			Conditionality	D
				Status	Active
Description	The pixel counts down from the origin.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= VPO <= VLL, positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom:SourceVideo	Cardinality	1..1		
XML Level 2	biom:ImageSegment	Cardinality	0..99		
XML Level 3	biom:PositionPolygonVertexQuantity	Cardinality	0..99		
XML Level 4	biom:PositionVerticalCoordinateValue	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

20.017

Scanned Horizontal Pixel Scale

Mnemonic	SHPS			Conditionality	D
				Status	Active
Description	This ASCII field shall specify the horizontal pixel density used for scanning providing the SLC field contains a "1" or a "2". Otherwise, it indicates the horizontal component of the pixel aspect ratio.				
Field Min	1	Occur Min	0		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom:SourceImage/biom:ImageCaptureDetail			Cardinality	1..1
XML Level 2	biom:CaptureHorizontalPixelDensityValue			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

20.018

Scanned Vertical Pixel Scale

Mnemonic	SVPS			Conditionality	D
				Status	Active
Description	This ASCII field shall specify the vertical pixel density used for scanning providing the SLC field contains a "1" or a "2". Otherwise, it indicates the vertical component of the pixel aspect ratio. Note that density is directly related to resolution. If SLC is 1 or 2 and SHPS is entered, then SVPS shall equal SHPS. This field is used if the transmission pixel scale differs from the original image scale, as listed in Transmitted vertical pixel scale / TVPS.				
Field Min	1	Occur Min	0		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom:SourceImage/biom:ImageCaptureDetail			Cardinality	0..1
XML Level 2	biom_2:CaptureVerticalPixelDensityValue			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

20.019

Time Index

Mnemonic	TIX			Conditionality	D
				Status	Active
Description	This is a conditional field. If the record contains video or audio, it shall contain the start and end times of segments within the file. For Type-20 or Type-21 records containing video or audio, this field shall contain two information items, time index start /TIS and time index end / TIE for the start and end times of segments within a video or audio file, measured in hh:mm:ss.sss. This field is comprised of one or more subfields. Each repeating subfield corresponds to a single segment, with a starting and end time as separate information items. This data is handled differently for each encoding. The zero time index shall be clearly indicated on the source, unless it is the absolute beginning of the file.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom:SourceImage or biom:SourceVideo			Cardinality	1..1
XML Level 2	biom:TimeSegment			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

20.019_0

Time Index

Subfields: Repeating sets of information items

Mnemonic	TIX_0			Conditionality	M↑
				Status	New-Active
Description	Subfields: Repeating sets of information items				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	99		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom:SourceImage or biom:SourceVideo			Cardinality	1..1
XML Level 2	biom:TimeSegment			Cardinality	0..99
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

20.019_1

Time Index

Time Index Start

Mnemonic	TIS			Conditionality	M↑
				Status	Active
Description	For Type-20 or Type-21 records containing video or audio, this information item of the Time Index field shall contain the start times of segments within a video or audio file, measured in hh:mm:ss.sss where ss.sss refers to the seconds and milliseconds.				
Field Min	12	Occur Min	1		
Field Max	12	Occur Max	1		
Char Types	NS	Special Chars	n/a		
Format	n/a	Constraints	T = TIS > zero time index (00:00:00.000)		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom:SourceImage or biom:SourceVideo			Cardinality	1..1
XML Level 2	biom:TimeSegment			Cardinality	0..99
XML Level 3	biom:TimeSegmentStartTimeValue			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

20.019_2

Time Index

Time Index End

Mnemonic	TIE			Conditionality	M↑
				Status	Active
Description	For Type-20 or Type-21 records containing video or audio, this information item of the Time Index field shall contain the end times of segments within a video or audio file, measured in hh:mm:ss.sss where ss.sss refers to the seconds and milliseconds.				
Field Min	12	Occur Min	1		
Field Max	12	Occur Max	1		
Char Types	NS	Special Chars	n/a		
Format	n/a	Constraints	T = TIE > TIS		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom:SourceImage or biom:SourceVideo			Cardinality	1..1
XML Level 2	biom:TimeSegment			Cardinality	0..99
XML Level 3	biom:TimeSegmentEndTimeValue			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

20.02

Comment

Mnemonic	COM	Conditionality	0
		Status	Active
Description	The optional Comment field appears in many record types and may be used to insert free text information. It is not reserved exclusively for log-related information but has historically often been used for this purpose. It is limited to a maximum of 126 characters. This maximum size was established in order to maintain consistency across encodings. The maximum size differed in the 2007 and 2008 versions of the standard.		
Field Min	1	Occur Min	0
Field Max	126	Occur Max	1
Char Types	U	Special Chars	Any
Format	n/a	Constraints	None
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-20)		
XML Level 1	biom_2:SourceCommentText	Cardinality	0..1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

20.021

Source Representation Number

Mnemonic	SRN	Conditionality	M
		Status	Active
Description	This mandatory field contains a reference number for the source representation stored in this record. Note that the segment references are contained in Field 20.016: Segments (SEG) if they exist. The value for SRN in Field 20.021 corresponds to the SRN that may be referenced as the first information item in the SOR field of other Record Types. The SRN is a positive integer that uniquely refers to a particular instance of Record Type-20. It is an integer, numbered sequentially beginning at one and incremented for each instance of Record Type-20.		
Field Min	1	Occur Min	1
Field Max	3	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	T = 1 <= SRN <= 255; positive integer
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-20)		
XML Level 1	biom:SourceIdentification/nc:IdentificationID	Cardinality	1..1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

20.022

Imagery Capture Date Range Estimate

Mnemonic	ICDR			Conditionality	D
				Status	Active
Description	The amount of time (plus and minus) of which SRD is the center point during which the image data could have been originally collected. A time measure indicator followed by 1 or 2 digits. May be concatenated, with larger time units first. Units: Y year, M month, D day				
Field Min	3	Occur Min	0		
Field Max	9	Occur Max	1		
Char Types	AN	Special Chars			
Format		Constraints	YyyMmmDdd		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom:SourceImage or biom:SourceVideo or biom:SourceAudio			Cardinality	0..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

20.101

Voice Engine Mode Export

Mnemonic	MODEL_EXPORT			Conditionality	0
				Status	New - Emerging
Description	Information set returned with the Speaker Candidate Results (SCR) response TOT as a result of the SID - Speaker Identification request TOT. The information set contains results information regarding matches against the stored voice engine model compariso				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	U	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	Addition for Voice Type 11				
XML Level 1	dod-ebts:VoiceEngineModelExport			Cardinality	0..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

20.101_1

Voice Engine Mode Export

Model Identifier

Mnemonic	MODEL_EXPORT_1	Conditionality	O
		Status	New - Emerging
Description	Identifier for the Exported Model File		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	n/a
Format	n/a	Constraints	n/a
Code List			
Source	Addition for Voice Type 11		
XML Level 1	dod-ebts:VoiceEngineModelExport	Cardinality	0...*
XML Level 2	dod-ebts:ModelID/nc:IdentificationID	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes

20.101_2

Voice Engine Mode Export

Model Export Software Version

Mnemonic	MODEL_EXPORT_2	Conditionality	O
		Status	New - Emerging
Description	Software version of the voice model engine generating the model and running the voice match comparison algorithm.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	n/a
Format	n/a	Constraints	n/a
Code List			
Source	Addition for Voice Type 11		
XML Level 1	dod-ebts:VoiceEngineModelExport	Cardinality	0...*
XML Level 2	dod-ebts:softwareVersionText	Cardinality	0...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-20: Source Representation

Page 955 of 1037

20.101_3

Voice Engine Mode Export

Model Export Software Name

Mnemonic	MODEL_EXPORT_3			Conditionality	0		
				Status	New - Emerging		
Description	Name of the software voice model engine generating the model and running the voice match comparison algorithm.						
Field Min	1		Occur Min	0			
Field Max	50		Occur Max	1			
Char Types	U		Special Chars	n/a			
Format	n/a		Constraints	n/a			
Code List							
Source	Addition for Voice Type 11						
XML Level 1	dod-ebts:VoiceEngineModelExport			Cardinality	0...*		
XML Level 2	dod-ebts:SoftwareName			Cardinality	0...1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

20.101_4

Voice Engine Mode Export

Model Export Associated Type 2 Reference

Mnemonic	MODEL_EXPORT_4			Conditionality	0		
				Status	New - Emerging		
Description	Transaction Identification Character (IDC) for the Type 2 record associated with the exported model.						
Field Min	1		Occur Min	0			
Field Max	6		Occur Max	1			
Char Types	U		Special Chars	n/a			
Format	n/a		Constraints	n/a			
Code List							
Source	Addition for Voice Type 11						
XML Level 1	dod-ebts:VoiceEngineModelExport			Cardinality	0...*		
XML Level 2	ansi-nist:Type2CrossReferenceIdentification			Cardinality	0...1		
XML Level 3				Cardinality			
XML Level 4				Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

20.101_5

Voice Engine Mode Export

Model Export Comment

Mnemonic	MODEL_EXPORT_5	Conditionality	0		
		Status	New - Emerging		
Description	Comment Text Regarding Model Export				
Field Min	1	Occur Min	0		
Field Max	255	Occur Max	1		
Char Types	U	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	Addition for Voice Type 11				
XML Level 1	dod-ebts:VoiceEngineModelExport	Cardinality	0...*		
XML Level 2	nc:CommentText	Cardinality	0...1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes		

20.101_6

Voice Engine Mode Export

Model Export Software Vendor

Mnemonic	MODEL_EXPORT_6	Conditionality	0		
		Status	New - Emerging		
Description	Text that specifies the software code vendor name				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	Addition for Voice Type 11				
XML Level 1	dod-ebts:VoiceEngineModelExport	Cardinality	0...*		
XML Level 2	dod-ebts:SoftwareVendorNameText	Cardinality	0...1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
		DoD EBTS 4.0	Yes		

20.902

Annotated Information

Mnemonic	ANN			Conditionality	M↑
				Status	Active
Description	This is an optional field, listing the operations performed on the original source in order to prepare it for inclusion in a biometric record type.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom:ProcessAnnotation			Cardinality	0..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

20.902_0

Annotated Information

Subfields: Repeating sets of information items

Mnemonic	ANN_0			Conditionality	D
				Status	New-Active
Description	This is an optional field, listing the operations performed on the original source in order to prepare it for inclusion in a biometric record type.				
Field Min	n/a		Occur Min	1	
Field Max	n/a		Occur Max	*	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom:ProcessAnnotation			Cardinality	1..*
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-20: Source Representation

Page 958 of 1037

20.902_1

Annotated Information

Greenwich Mean Time

Mnemonic	GMT			Conditionality	M↑
				Status	Active
Description	This information item is the Greenwich Mean Time (GMT) when the processing occurred. The data is formatted as YYYYMMDDhhmmssZ, where the Z indicates the zone description of 0 hours. This time is independent of the actual time zone where the time and date is recorded.				
Field Min	dependent on encoding		Occur Min	1	
Field Max	dependent on encoding		Occur Max	1	
Char Types	AN		Special Chars	None	
Format	YYYYMMDDHHMMSSZ - for Traditional Encoding		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom:ProcessAnnotation			Cardinality	1..*
XML Level 2	biom:ProcessUTCDate/nc:DateTime			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

20.902_2

Annotated Information

Processing Algorithm Name / Version

Mnemonic	NAV			Conditionality	M↑
				Status	Active
Description	This information item shall contain text identifying the name and version of the processing algorithm, application, procedure, or workstation				
Field Min	1		Occur Min	1	
Field Max	Unlimited		Occur Max	1	
Char Types	U		Special Chars	None	
Format	n/a		Constraints	None	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom:ProcessAnnotation			Cardinality	1..*
XML Level 2	biom:ProcessName			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

20.902_3

Annotated Information

Algorithm Owner

Mnemonic	OWN			Conditionality	M↑
				Status	Active
Description	This information item shall contain an unformatted text string of up to 64 characters with the contact information for the organization that owns the processing algorithm or latent workstation. Where there is no 'algorithm owner,' enter N/A.				
Field Min	1	Occur Min	1		
Field Max	64	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom:ProcessAnnotation			Cardinality	1..*
XML Level 2	biom:ProcessOwnerText			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

20.902_4

Annotated Information

Process Description

Mnemonic	PRO			Conditionality	M↑
				Status	Active
Description	This information item field shall contain text describing a process or procedure applied to the sample in this Type-9 record.				
Field Min	1	Occur Min	1		
Field Max	Unlimited	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints			
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom:ProcessAnnotation			Cardinality	1..*
XML Level 2	biom:ProcessDescriptionText			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

20.903

Device Unique Identifier

Mnemonic	DUI	Conditionality	0		
		Status	Active		
Description	The DUI shall contain a string uniquely identifying the device or source of the data. This field shall be one of the following: a Host PC MAC address (identified by the first character "M"), a Host PC processor ID (identified by the first character "P"). since it is available in the Make / Model / Serial Number field.				
Field Min	13	Occur Min	0		
Field Max	16	Occur Max	1		
Char Types	ANS	Special Chars	Any		
Format	n/a	Constraints	First character = M or P		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom:SourceImage/biom:ImageCaptureDetail or biom:SourceVideo/biom:BiometricCaptureDetail or biom_:SourceAudio/biom:BiometricCaptureDetail		Cardinality	1...1	
XML Level 2	biom:CaptureDeviceIdentification/nc:IdentificationID		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

20.904

Make/Model/Serial Number

Mnemonic	MMS	Conditionality	0		
		Status	Active		
Description	The MMS contains the make, model and serial number for the capture device. It shall consist of three information items. Each information item shall be 1 to 50 characters. Unknown information may be indicated with the value "0." Any or all information items may indicate that information is unknown with the value "0".				
Field Min	n/a	Occur Min	1		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom:SourceImage/biom:ImageCaptureDetail or biom:SourceVideo/biom:BiometricCaptureDetail or biom_:SourceAudio/biom:BiometricCaptureDetail		Cardinality	1...1	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

20.904_1

Make/Model/Serial Number

Make

Mnemonic	MAK	Conditionality	M↑
		Status	Active
Description	The name of the manufacturer for the capture device.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	Any
Format	n/a	Constraints	n/a
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-20)		
XML Level 1	biom:SourceImage/biom:ImageCaptureDetail or biom:SourceVideo/biom:BiometricCaptureDetail or biom_:SourceAudio/biom:BiometricCaptureDetail	Cardinality	1...1
XML Level 2	biom:CaptureDeviceMakeText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

20.904_2

Make/Model/Serial Number

Model

Mnemonic	MOD	Conditionality	M↑
		Status	Active
Description	The model number for the capture device.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	Any
Format	n/a	Constraints	n/a
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-20)		
XML Level 1	biom:SourceImage/biom:ImageCaptureDetail or biom:SourceVideo/biom:BiometricCaptureDetail or biom_:SourceAudio/biom:BiometricCaptureDetail	Cardinality	1...1
XML Level 2	biom:CaptureDeviceModelText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-20: Source Representation

Page 962 of 1037

20.904_3

Make/Model/Serial Number

Serial Number

Mnemonic	SER	Conditionality	M↑
		Status	Active
Description	The serial number for the capture device.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	Any
Format	n/a	Constraints	n/a
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-20)		
XML Level 1	biom:SourceImage/biom:ImageCaptureDetail or biom:SourceVideo/biom:BiometricCaptureDetail or biom_:SourceAudio/biom:BiometricCaptureDetail	Cardinality	1...1
XML Level 2	biom:CaptureDeviceSerialNumberText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

20.993

Source Agency Name

Mnemonic	SAN	Conditionality	O
		Status	Active
Description	This is an optional field. It may contain up to 125 Unicode characters. It is the name of the agency referenced in Field xx.004: Source agency / SRC for record types 9-99.		
Field Min	1	Occur Min	0
Field Max	125	Occur Max	1
Char Types	U	Special Chars	Any
Format	n/a	Constraints	None
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-20)		
XML Level 1	biom:SourceImage/biom:ImageCaptureDetail or biom:SourceVideo/biom:BiometricCaptureDetail or biom_:SourceAudio/biom:BiometricCaptureDetail	Cardinality	1...1
XML Level 2	nc:OrganizationName	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

20.994

External File Reference

Mnemonic	EFR			Conditionality	D
				Status	Active
Description	This conditional field shall be used to enter the URL / URI or other unique reference to a storage location for all associated context files EXCEPT 2D still images. If this field is used, Field 21.999: Associated context data (DATA) shall not be set. If this field is used, Field 20.999 shall not be set. However, one of the two fields shall be present in all instances of this record type. A non-URL reference might be similar to: "Case 2009:1468 AV Tape 5". It is highly recommended that the user state the format of the external file in Field 20.020: Comment / COM.				
Field Min	1	Occur Min	0		
Field Max	200	Occur Max	1		
Char Types	U	Special Chars	n/a		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom:SourceExternalAnalogFileReferenceText or biom:SourceExternalFileReferenceText or biom:SourceExternalDigitalImageReferenceText or biom:SourceExternalDigitalAudioReferenceText or biom:SourceExternalDigitalVideoReferenceText			Cardinality	0..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

20.995

Associated Context

Mnemonic	ASC			Conditionality	O
				Status	Active
Description	This optional field refers to one or more Type 21 Records with the same ACN. Type 21 Records contain images that are NOT used to derive the biometric data in Field 13.999: Latent friction ridge image (DATA) but that may be relevant to the collection of that data, such as general scenes of the area where a latent print was found.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom:AssociatedContext			Cardinality	0..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

20.995_0

Associated Context

Subfields: Repeating sets of information items

Mnemonic	ASC_0			Conditionality	M↑
				Status	New-Active
Description	This optional field refers to one or more Type 21 Records with the same ACN. Type 21 Records contain images that are NOT used to derive the biometric data in Field 13.999: Latent friction ridge image (DATA) but that may be relevant to the collection of that data, such as general scenes of the area where a latent print was found.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	255		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom:AssociatedContext			Cardinality	0..255
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

20.995_1

Associated Context

Associated Context Number

Mnemonic	ACN			Conditionality	M↑
				Status	Active
Description	The first information item for the Associated Context field for a particular Record Type-21. This is mandatory for each Field xx.995, when the field is used. It contains an index to a particular instance of a Type-21 record in the transaction. This same index value appears in the appropriate instance of Record Type-21 as Field 21.021: Associated context number (CAN). The value of the CAN shall be a sequentially assigned a positive integer starting from one and incremented by one, not to exceed 255.				
Field Min	1	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	1 <= ACN <= 255; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom:AssociatedContext			Cardinality	0..255
XML Level 2	biom:ContextIdentification			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

20.995_2

Associated Context

Associated Segment Position

Mnemonic	ASP		Conditionality	0↑	
			Status	Active	
Description	The first information item is the associated segment position (ASP). This provides a unique index to a segmentation.				
Field Min	1		Occur Min	0	
Field Max	2		Occur Max	1	
Char Types	N		Special Chars	n/a	
Format	n/a		Constraints	1 <= ASP <= 99; positive integer	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom:AssociatedContext		Cardinality	0..255	
XML Level 2	biom:ImageSegmentIdentification		Cardinality	0..1	
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

20.996

Hash

Mnemonic	HAS		Conditionality	0	
			Status	Active	
Description	Optional field xx.996, is designed for use in Record types 10 and above with a Field xx.999 storing the biometric data. It is comprised of 64 characters representing hexadecimal values. Thus, each character may be a digit from "0" to "9" or a letter "A" through "F". See the latest version of the Federal Information Processing Standard 180, Secure Hash Standard for information on computing SHA-256 hashes. At the time of this standard's publication, FIPS 180-37 had been published. It is also possible to use Field xx.996 to contain the hash for data stored externally, which is referenced in Field 20.994: External file reference (EFR) and/or Field 21.994: External file reference (EFR). The ability to store files externally is new to this version of the standard, and is only implemented for the two new record types referred to here. Use of the hash enables the receiver of the data to perform quick searches of large databases to determine if the data already exist in the database. It is not intended as an information assurance check. That is handled by Record Type-98: Information assurance record.				
Field Min	64		Occur Min	0	
Field Max	64		Occur Max	1	
Char Types	H		Special Chars	None	
Format	n/a		Constraints	None	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom_2:ImageHashValue		Cardinality	0..1	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

20.998

Geographic Sample Acquisition Location

Mnemonic	GEO		Conditionality	0	
			Status	Active	
Description	This optional field contains the location where the iris sample/original source/context information was acquired – not where it is stored.				
Field Min	n/a		Occur Min	1	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom:SourceImage/biom:ImageCaptureDetail or biom:SourceVideo/biom:BiometricCaptureDetail or biom_:SourceAudio/biom:BiometricCaptureDetail			Cardinality	1...1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

20.998_01

Geographic Sample Acquisition Location

Universal Time Entry

Mnemonic	UTE		Conditionality	0↑	
			Status	Active	
Description	The coordinated universal time (UTC) where the biometric sample was collected. This time is independent of the actual time zone where the time and date is recorded. The date is YYYYMMDDhhmmssZ, where the Z is indicates the zone description of 0 hours.				
Field Min	dependent upon encoding		Occur Min	0	
Field Max	dependent upon encoding		Occur Max	1	
Char Types	AN		Special Chars	None	
Format	n/a		Constraints		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-20)				
XML Level 1	biom:SourceImage/biom:ImageCaptureDetail or biom:SourceVideo/biom:BiometricCaptureDetail or biom_:SourceAudio/biom:BiometricCaptureDetail			Cardinality	1...1
XML Level 2	biom:CaptureLocation			Cardinality	0..1
XML Level 3	biom:CaptureUTCDateTime/nc:DateTime			Cardinality	0...1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

20.998_02

Geographic Sample Acquisition Location

Latitude Degree Value

Mnemonic	LTD	Conditionality	D
		Status	Active
Description	The second information item is latitude degree value (LTD). This is a value that specifies the degree of latitude. The value shall be between -90 (inclusive) and +90 (inclusive). The degrees may be expressed as an integer (without a decimal) or a real number including decimals. If decimals are present, then minutes and seconds shall be empty. Examples: Buenos Aires, Argentina: -34 (with minutes LTM = 36) NIST, Gaithersburg, Maryland: 39.137627 (no LTM or LTS) If sample collection time is unknown, set it to "00000000000000Z."		
Field Min	1	Occur Min	0
Field Max	9	Occur Max	1
Char Types	NS	Special Chars	Decimal, Minus Sign, Plus Sign
Format	n/a	Constraints	-90 <= LTD <= 90
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-20)		
XML Level 1	biom:SourceImage/biom:ImageCaptureDetail or biom:SourceVideo/biom:BiometricCaptureDetail or biom_:SourceAudio/biom:BiometricCaptureDetail	Cardinality	1...1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate (0...1)/nc:GeographicCoordinateLatitude (0...1)	Cardinality	0...1
XML Level 4	nc:LatitudeDegreeValue	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

20.998_03

Geographic Sample Acquisition Location

Latitude Minute Value

Mnemonic	LTM	Conditionality	D
		Status	Active
Description	This information item is latitude minute value (LTM). This is a value that specifies a minute of a degree. The value shall be between 0 (inclusive) to 60 (exclusive). The minute value may be expressed as an integer (without a decimal) or as a real number including decimals. If decimals are present then seconds shall be empty. Thus, the allowed special character is a period. The minute value can be empty, even if the degree value is an integer. LTM and LGM are co-conditional, so they shall both be present if either is present. However, latitude degree value / LTD and longitude degree value / LGD are co-conditional, so they shall both be present if either is present.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	NS	Special Chars	Decimal
Format	n/a	Constraints	0 <= LTM < 60
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-20)		
XML Level 1	biom:SourceImage/biom:ImageCaptureDetail or biom:SourceVideo/biom:BiometricCaptureDetail or biom_:SourceAudio/biom:BiometricCaptureDetail	Cardinality	1...1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate (0...1)/nc:GeographicCoordinateLatitude (0...1)	Cardinality	0...1
XML Level 4	nc:LatitudeMinuteValue	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

20.998_04

Geographic Sample Acquisition Location

Latitude Second Value

Mnemonic	LTS	Conditionality	D
		Status	Active
Description	The fourth information item is the latitude second value (LTS). This is a value that specifies a second of a minute. The integer shall be 0 (inclusive) to 60 (exclusive). The second value is empty, even if the minute value is an integer. Further, "minutes" values LTM and LGM can only be present if their corresponding "degrees" values are present.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	NS	Special Chars	None
Format	n/a	Constraints	0 <= LTS < 60
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-20)		
XML Level 1	biom:SourceImage/biom:ImageCaptureDetail or biom:SourceVideo/biom:BiometricCaptureDetail or biom_:SourceAudio/biom:BiometricCaptureDetail	Cardinality	1...1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate (0...1)/nc:GeographicCoordinateLatitude (0...1)	Cardinality	0...1
XML Level 4	nc:LatitudeSecondValue	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

20.998_05

Geographic Sample Acquisition Location

Longitude Degree Value

Mnemonic	LGD	Conditionality	D
		Status	Active
Description	The fifth information item is the longitude degree value (LGD). It is a value that specifies the degree of a longitude. The value shall be between -180 (inclusive) and +180 (inclusive). If LTD is present, then LGD shall be present. The degrees may be expressed as whole numbers (without a decimal) or real numbers including decimals. If decimals are present, then minutes and seconds are empty. Examples: Buenos Aires, Argentina: -58 (with minutes LGM = 22), NIST, Gaithersburg, Maryland: -77.216032 (no LGM or LGS) Also, "seconds" values LTS and LGS can only be present if their corresponding "minutes" value is present.		
Field Min	1	Occur Min	0
Field Max	10	Occur Max	1
Char Types	NS	Special Chars	Decimal,Minus Sign,Plus Sign
Format	n/a	Constraints	-180 <= LGD <= 180
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-20)		
XML Level 1	biom:SourceImage/biom:ImageCaptureDetail or biom:SourceVideo/biom:BiometricCaptureDetail or biom_:SourceAudio/biom:BiometricCaptureDetail	Cardinality	1...1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate (0...1)/nc:GeographicCoordinateLatitude (0...1)	Cardinality	0...1
XML Level 4	nc:LongitudeDegreeValue	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

20.998_06

Geographic Sample Acquisition Location

Longitude Minute Value

Mnemonic	LGM	Conditionality	D
		Status	Active
Description	The sixth information item is the longitude minute value (LGM). It is a value that specifies a minute of a degree. The value shall be from 0 (inclusive) to 60 (exclusive). The minute value may be expressed as an integer (without a decimal) or as a real number including decimals. If decimals are present then seconds shall not appear. The minute value is empty, even if the degree value is an integer. If LTM is present, then LGM shall be present. However, latitude degree value / LTD and longitude degree value / LGD are co-conditional, so they shall both be present if either is present.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	NS	Special Chars	Decimal
Format	n/a	Constraints	0 <= LGM < 60
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-20)		
XML Level 1	biom:SourceImage/biom:ImageCaptureDetail or biom:SourceVideo/biom:BiometricCaptureDetail or biom_:SourceAudio/biom:BiometricCaptureDetail	Cardinality	1..1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate (0...1)/nc:GeographicCoordinateLatitude (0...1)	Cardinality	0..1
XML Level 4	nc:LongitudeMinuteValue	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

20.998_07

Geographic Sample Acquisition Location

Longitude Second Value

Mnemonic	LGS	Conditionality	D
		Status	Active
Description	The seventh information item is the longitude second value (LGS). This is a value that specifies a second of a minute. The integer shall be 0 (inclusive) to 60 (exclusive). The second value is empty, even if the minute value is an integer. If LTS is present, then LGS shall be present. Further, "minutes" values LTM and LGM can only be present if their corresponding "degrees" values are present.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	NS	Special Chars	None
Format	n/a	Constraints	0 <= LGS < 60
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-20)		
XML Level 1	biom:SourceImage/biom:ImageCaptureDetail or biom:SourceVideo/biom:BiometricCaptureDetail or biom_:SourceAudio/biom:BiometricCaptureDetail	Cardinality	1..1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate (0...1)/nc:GeographicCoordinateLatitude (0...1)	Cardinality	0..1
XML Level 4	nc:LongitudeSecondValue	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

20.998_08

Geographic Sample Acquisition Location

Elevation

Mnemonic	ELE	Conditionality	O
		Status	Active
Description	The eighth information item is elevation (ELE). It is expressed in meters. It is a numeric value. It is between -422 meters (Dead Sea) and 8848 meters (Mount Everest). Allowed special characters are the negative sign and the period. Also, "seconds" values LTS and LGS can only be present if their corresponding "minutes" value is present.		
Field Min	1	Occur Min	1
Field Max	8	Occur Max	1
Char Types	NS	Special Chars	Minus Sign,Period
Format	n/a	Constraints	422.000 <= ELE <= 8848.000; real number
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-20)		
XML Level 1	biom:SourceImage/biom:ImageCaptureDetail or biom:SourceVideo/biom:BiometricCaptureDetail or biom_:SourceAudio/biom:BiometricCaptureDetail	Cardinality	1..1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	nc:LocationGeographicElevation	Cardinality	0..1
XML Level 4	nc:MeasurePoint	Cardinality	1..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

20.998_09

Geographic Sample Acquisition Location

Geodetic Datum Code

Mnemonic	GDC	Conditionality	O
		Status	Active
Description	The ninth information item is the geodetic datum code (GDC11). It is an alphanumeric value of 3 to 6 characters in length. This information item is used to indicate which coordinate system was used to represent the values in information items 2 through 7. If no entry is made in this information item, then the basis for the values entered in the first eight information items shall be WGS84, the code for the World Geodetic Survey 1984 version - WGS 84 (G873). See look up codes for values. If no entry is made in this information item, then the basis for the values entered in the first eight information items shall be WGS84, the code for the World Geodetic Survey 1984 version - WGS 84 (G873). See look up codes for values.		
Field Min	3	Occur Min	0
Field Max	6	Occur Max	1
Char Types	AN	Special Chars	None
Format	n/a	Constraints	see Look Up Codes
Code List	GEOGRAPHIC COORDINATE DATUM CODE		
Source	ANSI/NIST ITL 1-2013 (Type-20)		
XML Level 1	biom:SourceImage/biom:ImageCaptureDetail or biom:SourceVideo/biom:BiometricCaptureDetail or biom_:SourceAudio/biom:BiometricCaptureDetail	Cardinality	1..1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate (0..1)/nc:GeographicCoordinateLatitude (0..1)	Cardinality	0..1
XML Level 4	biom:GeodeticDatumCoordinateSystemCode or biom:GeodeticDatumCoordinateSystemName	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-20: Source Representation

Page 971 of 1037

20.998_10

Geographic Sample Acquisition Location

Geographic Coordinate Universal Transverse Mercator Zone

Mnemonic	GCM	Conditionality	D
		Status	Active
Description	It is an alphanumeric value of 2 to 3 characters. This is a one or two digit UTM zone number followed by the 8 degree latitudinal band designator (which is a single letter).		
Field Min	2	Occur Min	0
Field Max	3	Occur Max	1
Char Types	AN	Special Chars	None
Format	n/a	Constraints	One or two digits followed by a single letter
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-20)		
XML Level 1	biom:SourceImage/biom:ImageCaptureDetail or biom:SourceVideo/biom:BiometricCaptureDetail or biom_:SourceAudio/biom:BiometricCaptureDetail	Cardinality	1...1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	nc:LocationUTMCoordinate	Cardinality	0..1
XML Level 4	nc:UTMGridZoneID	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

20.998_11

Geographic Sample Acquisition Location

Geographic Coordinate Universal Transverse Mercator Easting

Mnemonic	GCE	Conditionality	D
		Status	Active
Description	The eleventh information item is the geographic coordinate universal transverse Mercator easting (GCE). It is an integer of 1 to 6 digits.		
Field Min	1	Occur Min	0
Field Max	6	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	integer
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-20)		
XML Level 1	biom:SourceImage/biom:ImageCaptureDetail or biom:SourceVideo/biom:BiometricCaptureDetail or biom_:SourceAudio/biom:BiometricCaptureDetail	Cardinality	1...1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	nc:LocationUTMCoordinate	Cardinality	0..1
XML Level 4	nc:UTMEastingValue	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-20: Source Representation

Page 972 of 1037

20.998_12

Geographic Sample Acquisition Location

Geographic Coordinate Universal Transverse Mercator Northing

Mnemonic	GCN		Conditionality	D			
			Status	Active			
Description	The twelfth information item is the geographic coordinate universal transverse Mercator northing (GCN). It is an integer of 1 to 8 digits.						
Field Min	1	Occur Min	0				
Field Max	8	Occur Max	1				
Char Types	N	Special Chars	None				
Format	n/a	Constraints	integer				
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-20)						
XML Level 1	biom:SourceImage/biom:ImageCaptureDetail or biom:SourceVideo/biom:BiometricCaptureDetail or biom_:SourceAudio/biom:BiometricCaptureDetail		Cardinality	1...1			
XML Level 2	biom:CaptureLocation		Cardinality	0..1			
XML Level 3	nc:LocationUTMCoordinate		Cardinality	0..1			
XML Level 4	nc:UTMNorthingValue		Cardinality	0..1			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

20.998_13

Geographic Sample Acquisition Location

Geographic Reference Text

Mnemonic	GRT		Conditionality	O			
			Status	Active			
Description	It is a free form text describing a street address or other physical location (such as 'Corner of Washington and Madison, Geneva, NY').						
Field Min	1	Occur Min	0				
Field Max	150	Occur Max	1				
Char Types	U	Special Chars	Any				
Format	n/a	Constraints	None				
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-20)						
XML Level 1	biom:SourceImage/biom:ImageCaptureDetail or biom:SourceVideo/biom:BiometricCaptureDetail or biom_:SourceAudio/biom:BiometricCaptureDetail		Cardinality	1...1			
XML Level 2	biom:CaptureLocation		Cardinality	0..1			
XML Level 3	biom:GeographicLocationText		Cardinality	0..1			
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

20.998_14

Geographic Sample Acquisition Location

Geographic Coordinate Other System Identifier

Mnemonic	OSI		Conditionality	O			
			Status	Active			
Description	A fourteenth optional information item geographic coordinate other system identifier (OSI) allows for other coordinate systems. This information items specifies the system identifier. It is up to 10 characters in length. Examples are: • MGRS (Military Grid Reference System), • USNG (United States National Grid), • GARS (Global Area Reference System), • GEOREF (World Geographic Reference), • LANDMARK landmark (e.g. hydant) and position relative to the landmark.						
Field Min	1	Occur Min	0				
Field Max	10	Occur Max	1				
Char Types	U	Special Chars	n/a				
Format	n/a	Constraints	None				
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-20)						
XML Level 1	biom:SourceImage/biom:ImageCaptureDetail or biom:SourceVideo/biom:BiometricCaptureDetail or biom_:SourceAudio/biom:BiometricCaptureDetail		Cardinality	1...1			
XML Level 2	biom:CaptureLocation		Cardinality	0..1			
XML Level 3	biom:LocationAlternateGeographicSystemValue		Cardinality	0..1			
XML Level 4	biom:GeographicLocationSystemName		Cardinality	1..1			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

20.998_15

Geographic Sample Acquisition Location

Geographic Coordinate Other System Value

Mnemonic	OCV		Conditionality	D			
			Status	Active			
Description	A fifteenth optional information item, is the geographic coordinate other system value (OCV). It shall only be present if OSI is present in the record. It can be up to 126 characters in length. If OSI is LANDMARK, OCV is free text and may be up to 126 characters. For details on the formatting of OCV for the other coordinate systems shown in OSI as examples, see http://earth-info.nga.mil/GandG/coordsys/grids/referencesys.html .						
Field Min	1	Occur Min	1				
Field Max	126	Occur Max	1				
Char Types	U	Special Chars	Any				
Format	n/a	Constraints	None				
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-20)						
XML Level 1	biom:SourceImage/biom:ImageCaptureDetail or biom:SourceVideo/biom:BiometricCaptureDetail or biom_:SourceAudio/biom:BiometricCaptureDetail		Cardinality	1...1			
XML Level 2	biom:CaptureLocation		Cardinality	0..1			
XML Level 3	biom:LocationAlternateGeographicSystemValue		Cardinality	0..1			
XML Level 4	biom:GeographicLocationText		Cardinality	0...1			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

20.999

Source Representation Data

Mnemonic	DATA		Conditionality	D			
			Status	Active			
Description	A fifteenth optional information item, is the geographic coordinate other system value / OCV. It shall only be present if OSI is present in the record. It can be up to 126 characters in length. It shall only be present if OSI is present in the record and OSI is set to LANDMARK. OCV is free text and may be up to 126 characters.						
Field Min	1	Occur Min	0				
Field Max	Unlimited	Occur Max	1				
Char Types	B	Special Chars	None				
Format	n/a	Constraints					
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-20)						
XML Level 1	nc:Base64BinaryObject	Cardinality	0..1				
XML Level 2		Cardinality					
XML Level 3		Cardinality					
XML Level 4		Cardinality					
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

21.001

Record Header

Mnemonic	LEN		Conditionality	M			
			Status	Active			
Description	The record header appears as the first field (xx.001) in each Record Type. It contains information particular to the encoding format chosen, in order to enable proper reading of the record. In Traditional encoding, this field contains the record length in bytes (including all information separators). In NIEM-conformant XML encoding, this field contains the RecordCategoryCode, which is the numeric representation of the Record Type.						
Field Min	T = 4; X = 1	Occur Min	1				
Field Max	T = 8; X = 2	Occur Max	1				
Char Types	N	Special Chars	None				
Format	n/a	Constraints	positive integer				
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-21)						
XML Level 1	nist-itl:RecordCategoryCode	Cardinality	1...1				
XML Level 2		Cardinality					
XML Level 3		Cardinality					
XML Level 4		Cardinality					
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

21.002

Information Designation Character

Mnemonic	IDC	Conditionality	M
		Status	Active
Description	Each of the records present in a transaction, with the exception of the Type-1 record, shall include a field (xx.002) containing the information designation character / IDC. The value of the IDC shall be a sequentially assigned positive integer starting from zero and incremented by one up to a maximum of 99. IDC references are stated in Type-1 Field 1.003 Transaction content (CNT) and shall be used to relate information items in the CNT field of the Type-1 record to the other records in the transaction. Two or more records may share a single IDC solely to identify and link together records that pertain to different representations of the same biometric trait.		
Field Min	1	Occur Min	1
Field Max	2	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	0 <= IDC <= 99; integer
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-21)		
XML Level 1	nist-itl:ImageReferenceIdentification/nc:IdentificationID	Cardinality	1...1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

21.004

Source Agency

Mnemonic	SRC	Conditionality	M
		Status	Active
Description	This is the identifier of the agency that actually created the record and supplied the information contained in it.		
Field Min	1	Occur Min	1
Field Max	Unlimited	Occur Max	1
Char Types	U	Special Chars	Any
Format	n/a	Constraints	None
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-21)		
XML Level 1	biom_2:ContextImage or biom_2:ContextAudio or biom_2:ContextVideo	Cardinality	1...1
XML Level 2	biom_2:ImageCaptureDetail or biom_2:BiometricCaptureDetail	Cardinality	0...1
XML Level 3	nc:OrganizationIdentification/nc:IdentificationID	Cardinality	1...1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

21.005

Associated Context Date

Mnemonic	ACD		Conditionality	0	
			Status	Active	
Description	This optional field shall contain the date and time that the context representation contained in the record was captured. It may not be possible to know the exact date of imagery capture. In such a case, specify the date to the level known and fill the rest of the date with zeros. Field 21.022: Imagery capture date range estimate/ ICDR should be used in conjunction with this field.				
Field Min	12		Occur Min	0	
Field Max	12		Occur Max	1	
Char Types	N		Special Chars	None	
Format	YYYYMMDDhhmm		Constraints	YYYYMMDDhhmm	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-21)				
XML Level 1	biom_2:ContextImage or biom_2:ContextAudio or biom_2:ContextVideo		Cardinality	1...1	
XML Level 2	biom_2:ImageCaptureDetail or biom_2:BiometricCaptureDetail		Cardinality	0...1	
XML Level 3	biom_2:CaptureDate/nc:DateTime		Cardinality	0..1	
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

21.006

Medical Device Information

Mnemonic	MDI		Conditionality	0	
			Status	Active	
Description	This field is designed to allow the transmission of information concerning medically implanted devices or devices used by an individual externally that may be discovered in or on unknown deceased and may assist in the person's identification. Each subfield is comprised of six information items, any combination of which may be entered. Each subfield describes a single device (such as a pacemaker or an artificial knee).				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-21)				
XML Level 1	biom_2:MedicalDeviceInformation		Cardinality	0..1	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

21.006_0

Medical Device Information

Repeating Subfields

Mnemonic	MDI_0			Conditionality	M↑
				Status	Active
Description	This field is designed to allow the transmission of information concerning medically implanted devices or devices used by an individual externally that may be discovered in or on unknown deceased and may assist in the person's identification. Each subfield is comprised of six information items, any combination of which may be entered. Each subfield describes a single device (such as a pacemaker or an artificial knee).				
Field Min	n/a		Occur Min	1	
Field Max	n/a		Occur Max	*	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-21)				
XML Level 1	biom_2:MedicalDeviceInformation			Cardinality	0..*
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

21.006_1

Medical Device Information

Type of Device

Mnemonic	TYP			Conditionality	O↑
				Status	Active
Description	The first information item is the type of device / TYP. It is optional. A typical entry may be 'metal plate in right arm' or 'external leg brace for left leg'.				
Field Min	1		Occur Min	0	
Field Max	500		Occur Max	1	
Char Types	U		Special Chars	None	
Format	n/a		Constraints	None	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-21)				
XML Level 1	biom_2:MedicalDeviceInformation			Cardinality	0..*
XML Level 2	biom_2:DeviceTypeText			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

21.006_2

Medical Device Information

Device Manufacturer

Mnemonic	MFG	Conditionality	O↑
		Status	Active
Description	The second information item is the device manufacturer / MFG. It is optional.		
Field Min	1	Occur Min	0
Field Max	500	Occur Max	1
Char Types	U	Special Chars	None
Format	n/a	Constraints	None
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-21)		
XML Level 1	biom_2:MedicalDeviceInformation	Cardinality	0..*
XML Level 2	biom_2:DeviceManufacturerText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

21.006_3

Medical Device Information

Device Make

Mnemonic	MAK	Conditionality	O↑
		Status	Active
Description	The third information item is the device make / MAK. It is optional.		
Field Min	1	Occur Min	0
Field Max	500	Occur Max	1
Char Types	U	Special Chars	None
Format	n/a	Constraints	None
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-21)		
XML Level 1	biom_2:MedicalDeviceInformation	Cardinality	0..*
XML Level 2	biom_2:CaptureDeviceMakeText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

21.006_4

Medical Device Information

Device Model

Mnemonic	MOD	Conditionality	O↑
		Status	Active
Description	The fourth information item is the device model / MOD. It is optional.		
Field Min	1	Occur Min	0
Field Max	500	Occur Max	1
Char Types	U	Special Chars	None
Format	n/a	Constraints	None
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-21)		
XML Level 1	biom_2:MedicalDeviceInformation	Cardinality	0..*
XML Level 2	biom_2:CaptureDeviceModelText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

21.006_5

Medical Device Information

Device Serial Number

Mnemonic	SER	Conditionality	O↑
		Status	Active
Description	The fifth information item is the device serial number / SER. It is optional.		
Field Min	1	Occur Min	0
Field Max	500	Occur Max	1
Char Types	U	Special Chars	None
Format	n/a	Constraints	None
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-21)		
XML Level 1	biom_2:MedicalDeviceInformation	Cardinality	0..*
XML Level 2	biom_2:CaptureDeviceSerialNumberText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

21.006_6

Medical Device Information

Comments

Mnemonic	COM	Conditionality	O↑
		Status	Active
Description	The sixth information item is optional. It is any comment / COM concerning the device.		
Field Min	1	Occur Min	0
Field Max	Unlimited	Occur Max	1
Char Types	U	Special Chars	None
Format	n/a	Constraints	None
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-21)		
XML Level 1	biom_2:MedicalDeviceInformation	Cardinality	0..*
XML Level 2	nc:CommentText	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

21.015

Associated Context Format

Mnemonic	AFT	Conditionality	M
		Status	Active
Description	This is a mandatory field comprised of two information items. The first information item is mandatory. It is file type / FTY. If the associated context file is a digital file, this shall contain the suffix indicating the file type. If it is an analog file, enter 'ANALOG'. For digital data stored in other formats (such as digital tape), enter 'OTHER'. The second information item is decoding instructions / DEI. It is optional and contains free text up to 1000 characters.		
Field Min	n/a	Occur Min	1
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	n/a
Format	n/a	Constraints	n/a
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-21)		
XML Level 1	biom_2:ContextFileFormat	Cardinality	1..1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

21.015_1

Associated Context Format

File Type

Mnemonic	FTY			Conditionality	M
				Status	Active
Description	The first information item is mandatory. It is file type / FTY. If the source representation is a digital file, this shall contain the suffix indicating the file type (such as JPG). If it is an analog file, enter 'ANALOG'. For digital data stored in other formats (such as digital tape), enter 'OTHER'.				
Field Min	3	Occur Min	1		
Field Max	6	Occur Max	1		
Char Types	U	Special Chars	n/a		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-21)				
XML Level 1	biom_2:ContextFileFormat	Cardinality	1..1		
XML Level 2	biom_2:ContextFileCategoryText	Cardinality	1..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

21.015_2

Associated Context Format

Decoding Instructions

Mnemonic	DEI			Conditionality	O
				Status	Active
Description	The second information item is decoding instructions / DEI. It is optional and contains free text up to 1000 characters.				
Field Min	1	Occur Min	0		
Field Max	1000	Occur Max	1		
Char Types	U	Special Chars	n/a		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-21)				
XML Level 1	biom_2:ContextFileFormat	Cardinality	1..1		
XML Level 2	biom_2:ContextFileDecodingInstructionsText	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-21: Associated Context

Page 982 of 1037

21.016

Segments

Mnemonic	SEG			Conditionality	0
				Status	Active
Description	This optional field shall consist of a subfield for each segment to be defined. Each subfield consists of a series of information items.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-21)				
XML Level 1	biom_2:ContextImage			Cardinality	1..1
XML Level 2	biom_2:ImageSegment			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

21.016_0

Segments

Repeating Subfields

Mnemonic	SEG_0			Conditionality	M↑
				Status	Active
Description	This optional field shall consist of a subfield for each segment to be defined. Each subfield consists of a series of information items.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	99		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-21)				
XML Level 1	biom_2:ContextImage			Cardinality	1..1
XML Level 2	biom_2:ImageSegment			Cardinality	0..99
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

21.016_1

Segments

Associated Segment Position

Mnemonic	ASP			Conditionality	M↑
				Status	Active
Description	The first information item is the associated segment position / ASP. This provides a unique index to a segmentation.				
Field Min	1	Occur Min	1		
Field Max	2	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	1 <= ASP <= 99; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-21)				
XML Level 1	biom_2:ContextImage	Cardinality	1..1		
XML Level 2	biom_2:ImageSegment	Cardinality	0..99		
XML Level 3	biom_2:ImageSegmentIdentification/nc:IdentificationID	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

21.016_2

Segments

Internal File Reference Pointer

Mnemonic	IPT			Conditionality	M↑
				Status	Active
Description	The second information item is the internal file reference pointer/ IPT. It is set to 0 if the source representation is a single file. If the external file referenced in Field 20.994: External file reference / EFR or Field 21.994: External file reference / EFR is a PDF, video, or presentation file, or has multiple locations where a sample may be located, this information item is the reference to the particular instance, such as page, video frame, or slide number used to derive the image transmitted in other record types. If a particular frame is chosen and there is no further image segmentation needed, the following information items shall not be used. This entry is free text with any special characters are allowed.				
Field Min	1	Occur Min	1		
Field Max	15	Occur Max	1		
Char Types	ANS	Special Chars	n/a		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-21)				
XML Level 1	biom_2:ContextImage	Cardinality	1..1		
XML Level 2	biom_2:ImageSegment	Cardinality	0..99		
XML Level 3	biom_2:ImageSegmentInternalIdentification/nc:IdentificationID	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

21.016_3

Segments

Number of Points

Mnemonic	NOP			Conditionality	O↑
				Status	Active
Description	Specifies the number of vertices.				
Field Min	1	Occur Min	0		
Field Max	2	Occur Max	99		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	3 <= NOP <= 99; positive integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-21)				
XML Level 1	biom_2:ContextImage	Cardinality	1..1		
XML Level 2	biom_2:ImageSegment	Cardinality	0..99		
XML Level 3	biom_2:PositionPolygonVertex	Cardinality	0..99		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

21.016_4

Segments

Horizontal Point Offset

Mnemonic	HPO			Conditionality	D
				Status	Active
Description	The pixel counts to the right.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-21)				
XML Level 1	biom_2:ContextImage	Cardinality	1..1		
XML Level 2	biom_2:ImageSegment	Cardinality	0..99		
XML Level 3	biom_2:PositionPolygonVertex	Cardinality	0..99		
XML Level 4	biom_2:PositionHorizontalCoordinateValue	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

21.016_5

Segments

Vertical Point Offset

Mnemonic	VPO			Conditionality	D
				Status	Active
Description	The pixel counts down from the origin.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	non-negative integer		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-21)				
XML Level 1	biom_2:ContextImage	Cardinality	1..1		
XML Level 2	biom_2:ImageSegment	Cardinality	0..99		
XML Level 3	biom_2:PositionPolygonVertex	Cardinality	0..99		
XML Level 4	biom_2:PositionVerticalCoordinateValue	Cardinality	1..1		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

21.019

Time Index

Mnemonic	TIX			Conditionality	D
				Status	Active
Description	This is a conditional field. If the record contains video or audio, it shall contain the start and end times of segments within the file. For records containing video or audio, this field shall contain two information items, time index start /TIS and time index end / TIE for the start and end times of segments within a video or audio file. This field is comprised of one or more subfields. Each repeating subfield corresponds to a single segment, with a starting and end time as separate information items.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-21)				
XML Level 1	biom_2:TimeSegment	Cardinality	0..1		
XML Level 2		Cardinality			
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

21.019_0

Time Index

Repeating Subfields

Mnemonic	TIX_0			Conditionality	M↑
				Status	Active
Description	This is a conditional field. If the record contains video or audio, it shall contain the start and end times of segments within the file. For records containing video or audio, this field shall contain two information items, time index start /TIS and time index end / TIE for the start and end times of segments within a video or audio file. This field is comprised of one or more subfields. Each repeating subfield corresponds to a single segment, with a starting and end time as separate information items.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	99		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-21)				
XML Level 1	biom_2:TimeSegment			Cardinality	0..99
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

21.019_1

Time Index

Time Index Start

Mnemonic	TIS			Conditionality	M↑
				Status	Active
Description	For records containing video or audio, this information item of the Time Index field shall contain the start times of segments within a video or audio file, measured in hh:mm:ss.sss where ss.sss refers to the seconds and milliseconds.				
Field Min	12	Occur Min	1		
Field Max	12	Occur Max	1		
Char Types	NS	Special Chars	n/a		
Format	n/a	Constraints	TIS >= 0 time index (00:00:00.000)		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-21)				
XML Level 1	biom_2:TimeSegment			Cardinality	0..99
XML Level 2	biom_2:TimeSegmentStartTimeValue			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

21.019_2

Time Index

Time Index End

Mnemonic	TIE			Conditionality	M↑
				Status	Active
Description	For records containing video or audio, this information item of the Time Index field shall contain the end times of segments within a video or audio file, measured in hh:mm:ss.sss where ss.sss refers to the seconds and milliseconds.				
Field Min	12	Occur Min	1		
Field Max	12	Occur Max	1		
Char Types	NS	Special Chars	n/a		
Format	n/a	Constraints	TIE > TIS		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-21)				
XML Level 1	biom_2:TimeSegment			Cardinality	0..99
XML Level 2	biom_2:TimeSegmentEndTimeValue			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

21.02

Comment

Mnemonic	COM			Conditionality	0
				Status	Active
Description	The optional Comment field appears in many record types and may be used to insert free text information. It is not reserved exclusively for log-related information but has historically often been used for this purpose. It is limited to a maximum of 126 characters. This maximum size was established in order to maintain consistency across encodings. The maximum size differed in the 2007 and 2008 versions of the standard.				
Field Min	1	Occur Min	0		
Field Max	126	Occur Max	1		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-21)				
XML Level 1	biom_2:ContextCommentText			Cardinality	0..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

21.021

Associated Context Number

Mnemonic	ACN	Conditionality	M
		Status	Active
Description	This mandatory field contains a reference number for the context representation stored in this record. Note that the segment references are contained in Field 21.016: Segments / SEG, if they exist. This number corresponds to the ACN that may be referenced as the first information item in the ASC field of other Record Types. The ACN is a positive integer that uniquely refers to a particular instance of Record Type-21. It is a positive integer, numbered sequentially beginning at one and incremented for each instance of Record Type-21.		
Field Min	1	Occur Min	1
Field Max	3	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	1 <= ACN <= 255; positive integer
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-21)		
XML Level 1	biom_2:ContextIdentification/nc:IdentificationID	Cardinality	1..1
XML Level 2		Cardinality	
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

21.022

Image Capture Date Range Estimate

Mnemonic	ICDR	Conditionality	D
		Status	Active
Description	This is the amount of time (plus and minus) of which ACD is the center point during which the image data could have been originally collected. It is entered in the format as YyyMmmDdd. It is possible to enter only a year, month and/or day range, such as D meaning that the actual date of collection is estimated to be 5 days plus or minus from that specified in ACD. Leading zeros need not be entered.		
Field Min	3	Occur Min	0
Field Max	9	Occur Max	1
Char Types	AN	Special Chars	None
Format	n/a	Constraints	Time measure indicator followed by 1 or 2 digits. May be concatenated, with larger time units first. Units: Y year, M Month, D Day
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-21)		
XML Level 1	biom_2:ContextImage/biom:ImageCaptureDetail or biom_2:ContextAudio/biom_2:BiometricCaptureDetail or biom_2:ContextVideo/biom_2:BiometricCaptureDetail	Cardinality	1..1
XML Level 2	biom:ImageCaptureDateEstimateRange	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	No	DoD EBTS 4.0	Yes

21.046

Image Subject Condition

Mnemonic	SUB			Conditionality	O
				Status	Active
Description	This field is optional. There may be different values for SUB in different instances of Type-14 records. For example, some images may have been acquired antemortem, while others were acquired post-mortem. This field describes the condition of the subject				
Field Min	n/a	Occur Min	1		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-21)				
XML Level 1	biom_2:SubjectExistentialDetails			Cardinality	1..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

21.046_1

Image Subject Condition

Subject Status Code

Mnemonic	SSC			Conditionality	M↑
				Status	Active
Description	This information item is mandatory if this field is present. It is subject status code / SSC.				
Field Min	1	Occur Min	1		
Field Max	1	Occur Max	1		
Char Types	A	Special Chars	None		
Format	n/a	Constraints	SSC = X, A, or D		
Code List	SUBJECT STATUS CODES				
Source	ANSI/NIST ITL 1-2013 (Type-21)				
XML Level 1	biom_2:SubjectExistentialDetails			Cardinality	1..1
XML Level 2	biom_2:SubjectExistentialStatusCode			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

21.046_2

Image Subject Condition

Subject Body Status Code

Mnemonic	SBSC			Conditionality	D
				Status	Active
Description	This information item shall be entered if and only if SSC is D. It is subject body status code / SBSC. Its purpose is to indicate whether the information relates to an entire corpse or a separate body part.				
Field Min	1	Occur Min	1		
Field Max	1	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	SBSC = 1 or 2		
Code List	SUBJECT BODY STATUS CODES				
Source	ANSI/NIST ITL 1-2013 (Type-21)				
XML Level 1	biom_2:SubjectExistentialDetails			Cardinality	1..1
XML Level 2	biom_2:SubjectBodyStatusCode			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

21.046_3

Image Subject Condition

Subject Body Class Code

Mnemonic	SBCC			Conditionality	D
				Status	Active
Description	This information item shall be entered if and only if SSC is D. It is subject body class code/ SBCC.				
Field Min	1	Occur Min	0		
Field Max	1	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	SBCC = 1 or 2		
Code List	SUBJECT BODY CLASS CODES				
Source	ANSI/NIST ITL 1-2013 (Type-21)				
XML Level 1	biom_2:SubjectExistentialDetails			Cardinality	1..1
XML Level 2	biom_2:SubjectBodyClassCode			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

21.047

Capture Organization Name

Mnemonic	CON			Conditionality	O
				Status	Active
Description	This field is optional. Note that this can be different from the agency entered in Field 21.004: Source agency / SRC and Field 21.993: Source agency name / SAN. SRC and SAN describe the agency that created the record. Since the record may have been forward another agency to the final destination, Field 1.008: Originating agency identifier / ORI is used to indicate the transmitting organization. In many implementation domains, there are a limited number of transmission organizations that can send data. Therefore, the agency listed in SRC may send the transaction to another location that has access rights to the final destination. This intermediary may add information to the transaction, as well. The final transmitting organization code is listed in Field 1.008: Originating agency identifier / ORI. Its name may be entered in Originating agency name / OAN in Field 1.017: Agency names / ANM.				
Field Min	1	Occur Min	0		
Field Max	1000	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-21)				
XML Level 1	biom_2:ContextImage or biom_2:ContextAudio or biom_2:ContextVideo			Cardinality	1..1
XML Level 2	nc:OrganizationUnitName			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

21.902

Annotated Information

Mnemonic	ANN			Conditionality	O
				Status	Active
Description	This is an optional field, listing the operations performed on the original source in order to prepare it for inclusion in a biometric record type.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-21)				
XML Level 1	biom_2:ProcessAnnotation			Cardinality	0..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

21.902_0

Annotated Information

Repeating Subfields

Mnemonic	ANN_0			Conditionality	M↑
				Status	Active
Description	This is an optional field, listing the operations performed on the original source in order to prepare it for inclusion in a biometric record type.				
Field Min	n/a		Occur Min	1	
Field Max	n/a		Occur Max	*	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-21)				
XML Level 1	biom_2:ProcessAnnotation			Cardinality	0..*
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

21.902_1

Annotated Information

Greenwich Mean Time

Mnemonic	GMT			Conditionality	M↑
				Status	Active
Description	This information item is the Greenwich Mean Time (GMT) when the processing occurred. The data is formatted as YYYYMMDDhhmmssZ, where the Z indicates the zone description of 0 hours. This time is independent of the actual time zone where the time and date is recorded.				
Field Min	15		Occur Min	1	
Field Max	15		Occur Max	1	
Char Types	AN		Special Chars	None	
Format	YYYYMMDDHHMMSSZ - for Traditional Encoding		Constraints	Dependent upon encoding	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-21)				
XML Level 1	biom_2:ProcessUTCDate/nc:DateTime			Cardinality	1..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-21: Associated Context

Page 993 of 1037

21.902_2

Annotated Information

Processing Algorithm Name / Version

Mnemonic	NAV			Conditionality	M↑
				Status	Active
Description	This information item shall contain text identifying the name and version of the processing algorithm, application, procedure, or workstation				
Field Min	1	Occur Min	1		
Field Max	Unlimited	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-21)				
XML Level 1	biom_2:ProcessName			Cardinality	1..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

21.902_3

Annotated Information

Algorithm Owner

Mnemonic	OWN			Conditionality	M↑
				Status	Active
Description	This information item shall contain an unformatted text string of up to 64 characters with the contact information for the organization that owns the processing algorithm or latent workstation. Where there is no 'algorithm owner,' enter N/A.				
Field Min	1	Occur Min	1		
Field Max	64	Occur Max	1		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-21)				
XML Level 1	biom_2:ProcessOwnerText			Cardinality	1..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-21: Associated Context

Page 994 of 1037

21.902_4

Annotated Information

Process Description

Mnemonic	PRO			Conditionality	M↑
				Status	Active
Description	This information item field shall contain text describing a process or procedure applied to the sample in this Type-9 record.				
Field Min	1	Occur Min	1		
Field Max	255	Occur Max	1		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-21)				
XML Level 1	biom_2:ProcessDescriptionText			Cardinality	1..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

21.993

Source Agency Name

Mnemonic	SAN			Conditionality	0
				Status	Active
Description	This is an optional field. It may contain up to 125 Unicode characters. It is the name of the agency referenced in Field xx.004: Source agency / SRC for record types 9-99.				
Field Min	1	Occur Min	0		
Field Max	125	Occur Max	1		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-21)				
XML Level 1	biom_2:ContextImage/biom:ImageCaptureDetail or biom_2:ContextAudio/biom_2:BiometricCaptureDetail or biom_2:ContextVideo/biom_2:BiometricCaptureDetail			Cardinality	1..1
XML Level 2	nc:OrganizationName			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

21.994

External File Reference

Mnemonic	EFR		Conditionality	D	
			Status	Active	
Description	This conditional field shall be used to enter the URL / URI or other unique reference to a storage location for all associated context files EXCEPT 2D still images. If this field is used, Field 21.999: Associated context data / DATA shall not be set. However, one of the two fields shall be present in all instances of this record type. It is an alphanumeric entry, with special characters allowed. A non-URL reference might be similar to: "Case 2009:1468 AV Tape 5".				
Field Min	1	Occur Min	0		
Field Max	200	Occur Max	1		
Char Types	U	Special Chars	n/a		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-21)				
XML Level 1	biom:ContextExternalFileReferenceText or biom:SourceExternalAnalogFileReferenceText or biom:SourceExternalDigitalImageReferenceText or biom:SourceExternalDigitalAudioReferenceText or biom:SourceExternalDigitalVideoReferenceText		Cardinality	0..1	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

21.996

Hash

Mnemonic	HAS		Conditionality	O	
			Status	Active	
Description	Optional field xx.996, is designed for use in Record types 10 and above with a Field xx.999 storing the biometric data. It is comprised of 64 characters representing hexadecimal values. Thus, each character may be a digit from "0" to "9" or a letter "A" through "F". See the latest version of the Federal Information Processing Standard 180, Secure Hash Standard for information on computing SHA-256 hashes. At the time of this standard's publication, FIPS 180-37 had been published. It is also possible to use Field xx.996 to contain the hash for data stored externally, which is referenced in Field 20.994: External file reference (EFR) and/or Field 21.994: External file reference (EFR). The ability to store files externally is new to this version of the standard, and is only implemented for the two new record types referred to here. Use of the hash enables the receiver of the data to perform quick searches of large databases to determine if the data already exist in the database. It is not intended as an information assurance check. That is handled by Record Type-98: Information assurance record.				
Field Min	64	Occur Min	0		
Field Max	64	Occur Max	1		
Char Types	H	Special Chars	None		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-21)				
XML Level 1	biom_2:ImageHashValue		Cardinality	0..1	
XML Level 2			Cardinality		
XML Level 3			Cardinality		
XML Level 4			Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

21.998

Geographic Sample Acquisition Location

Mnemonic	GEO			Conditionality	0
				Status	Active
Description	This optional field contains the location where the iris sample/original source/context information was acquired – not where it is stored.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-21)				
XML Level 1	biom_2:ContextImage/biom:ImageCaptureDetail or biom_2:ContextAudio/biom_2:BiometricCaptureDetail or biom_2:ContextVideo/biom_2:BiometricCaptureDetail			Cardinality	0...1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

21.998_01

Geographic Sample Acquisition Location

Universal Time Entry

Mnemonic	UTE			Conditionality	0↑
				Status	Active
Description	The coordinated universal time (UTC) where the biometric sample was collected. This time is independent of the actual time zone where the time and date is recorded. The date is YYYYMMDDhhmmssZ, where the Z is indicates the zone description of 0 hours. If sample collection time is unknown, set it to "00000000000000Z."				
Field Min	15		Occur Min	0	
Field Max	15		Occur Max	1	
Char Types	AN		Special Chars	None	
Format	YYYYMMDDHHMMSSZ - for Traditional Encoding		Constraints	Dependent upon encoding	
Code List					
Source	ANSI/NIST ITL 1-2013 (Type-21)				
XML Level 1	biom_2:ContextImage/biom:ImageCaptureDetail or biom_2:ContextAudio/biom_2:BiometricCaptureDetail or biom_2:ContextVideo/biom_2:BiometricCaptureDetail			Cardinality	1...1
XML Level 2	biom:CaptureLocation			Cardinality	0..1
XML Level 3	biom:CaptureUTCDateTime/nc:DateTime			Cardinality	0...1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

21.998_02

Geographic Sample Acquisition Location

Latitude Degree Value

Mnemonic	LTD	Conditionality	D
		Status	Active
Description	The second information item is latitude degree value (LTD). This is a value that specifies the degree of latitude. The value shall be between -90 (inclusive) and +90 (inclusive). The degrees may be expressed as an integer (without a decimal) or a real number including decimals. If decimals are present, then minutes and seconds shall be empty. Examples: Buenos Aires, Argentina: -34 (with minutes LTM = 36) NIST, Gaithersburg, Maryland: 39.137627 (no LTM or LTS)		
Field Min	1	Occur Min	0
Field Max	9	Occur Max	1
Char Types	NS	Special Chars	Decimal, Minus Sign, Plus Sign
Format	n/a	Constraints	-90 <= LTD <= 90
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-21)		
XML Level 1	biom_2:ContextImage/biom:ImageCaptureDetail or biom_2:ContextAudio/biom_2:BiometricCaptureDetail or biom_2:ContextVideo/biom_2:BiometricCaptureDetail	Cardinality	1...1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate (0...1)/nc:GeographicCoordinateLatitude (0...1)	Cardinality	0...1
XML Level 4	nc:LatitudeDegreeValue	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

21.998_03

Geographic Sample Acquisition Location

Latitude Minute Value

Mnemonic	LTM	Conditionality	D
		Status	Active
Description	This information item is latitude minute value (LTM). This is a value that specifies a minute of a degree. The value shall be between 0 (inclusive) to 60 (exclusive). The minute value may be expressed as an integer (without a decimal) or as a real number including decimals. If decimals are present then seconds shall be empty. Thus, the allowed special character is a period. The minute value can be empty, even if the degree value is an integer. LTM and LGM are co-conditional, so they shall both be present if either is present.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	NS	Special Chars	Decimal
Format	n/a	Constraints	0 <= LTM < 60
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-21)		
XML Level 1	biom_2:ContextImage/biom:ImageCaptureDetail or biom_2:ContextAudio/biom_2:BiometricCaptureDetail or biom_2:ContextVideo/biom_2:BiometricCaptureDetail	Cardinality	1...1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate (0...1)/nc:GeographicCoordinateLatitude (0...1)	Cardinality	0...1
XML Level 4	nc:LatitudeMinuteValue	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

21.998_04

Geographic Sample Acquisition Location

Latitude Second Value

Mnemonic	LTS	Conditionality	D
		Status	Active
Description	The fourth information item is the latitude second value (LTS). This is a value that specifies a second of a minute. The integer shall be 0 (inclusive) to 60 (exclusive). The second value is empty, even if the minute value is an integer.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	0 <= LTS < 60
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-21)		
XML Level 1	biom_2:ContextImage/biom:ImageCaptureDetail or biom_2:ContextAudio/biom_2:BiometricCaptureDetail or biom_2:ContextVideo/biom_2:BiometricCaptureDetail	Cardinality	1...1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate (0...1)/nc:GeographicCoordinateLatitude (0...1)	Cardinality	0...1
XML Level 4	nc:LatitudeSecondValue	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

21.998_05

Geographic Sample Acquisition Location

Longitude Degree Value

Mnemonic	LGD	Conditionality	D
		Status	Active
Description	The fifth information item is the longitude degree value (LGD). It is a value that specifies the degree of a longitude. The value shall be between -180 (inclusive) and +180 (inclusive). If LTD is present, then LGD shall be present. The degrees may be expressed as whole numbers (without a decimal) or real numbers including decimals. If decimals are present, then minutes and seconds are empty. Examples: Buenos Aires, Argentina: -58 (with minutes LGM = 22), NIST, Gaithersburg, Maryland: -77.216032 (no LGM or LGS)		
Field Min	1	Occur Min	0
Field Max	10	Occur Max	1
Char Types	NS	Special Chars	Decimal,Minus Sign,Plus Sign
Format	n/a	Constraints	-180 <= LGD <= 180
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-21)		
XML Level 1	biom_2:ContextImage/biom:ImageCaptureDetail or biom_2:ContextAudio/biom_2:BiometricCaptureDetail or biom_2:ContextVideo/biom_2:BiometricCaptureDetail	Cardinality	1...1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate (0...1)/nc:GeographicCoordinateLatitude (0...1)	Cardinality	0...1
XML Level 4	nc:LongitudeDegreeValue	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

21.998_06

Geographic Sample Acquisition Location

Longitude Minute Value

Mnemonic	LGM	Conditionality	D
		Status	Active
Description	The sixth information item is the longitude minute value (LGM). It is a value that specifies a minute of a degree. The value shall be from 0 (inclusive) to 60 (exclusive). The minute value may be expressed as an integer (without a decimal) or as a real number including decimals. If decimals are present then seconds shall not appear. The minute value is empty, even if the degree value is an integer. If LTM is present, then LGM shall be present.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	NS	Special Chars	Decimal
Format	n/a	Constraints	0 <= LGM < 60
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-21)		
XML Level 1	biom_2:ContextImage/biom:ImageCaptureDetail or biom_2:ContextAudio/biom_2:BiometricCaptureDetail or biom_2:ContextVideo/biom_2:BiometricCaptureDetail	Cardinality	1..1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate (0..1)/nc:GeographicCoordinateLatitude (0..1)	Cardinality	0..1
XML Level 4	nc:LongitudeMinuteValue	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

21.998_07

Geographic Sample Acquisition Location

Longitude Second Value

Mnemonic	LGS	Conditionality	D
		Status	Active
Description	The seventh information item is the longitude second value (LGS). This is a value that specifies a second of a minute. The integer shall be 0 (inclusive) to 60 (exclusive). The second value is empty, even if the minute value is an integer. If LTS is present, then LGS shall be present.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	0 <= LGS < 60
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-21)		
XML Level 1	biom_2:ContextImage/biom:ImageCaptureDetail or biom_2:ContextAudio/biom_2:BiometricCaptureDetail or biom_2:ContextVideo/biom_2:BiometricCaptureDetail	Cardinality	1..1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate (0..1)/nc:GeographicCoordinateLatitude (0..1)	Cardinality	0..1
XML Level 4	nc:LongitudeSecondValue	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-21: Associated Context

Page 1000 of 1037

21.998_08

Geographic Sample Acquisition Location

Elevation

Mnemonic	ELE	Conditionality	0
		Status	Active
Description	The eighth information item is elevation (ELE). It is expressed in meters. It is a numeric value. It is between -422 meters (Dead Sea) and 8848 meters (Mount Everest). Allowed special characters are the negative sign and the period.		
Field Min	3	Occur Min	0
Field Max	8	Occur Max	1
Char Types	NS	Special Chars	Minus Sign,Period
Format	n/a	Constraints	-422.000 < ELE < 8848.000; real number
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-21)		
XML Level 1	biom_2:ContextImage/biom:ImageCaptureDetail or biom_2:ContextAudio/biom_2:BiometricCaptureDetail or biom_2:ContextVideo/biom_2:BiometricCaptureDetail	Cardinality	1...1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	nc:LocationGeographicElevation	Cardinality	0..1
XML Level 4	nc:MeasurePoint	Cardinality	1..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

21.998_09

Geographic Sample Acquisition Location

Geodetic Datum Code

Mnemonic	GDC	Conditionality	0
		Status	Active
Description	The ninth information item is the geodetic datum code (GDC11). It is an alphanumeric value of 3 to 6 characters in length. This information item is used to indicate which coordinate system was used to represent the values in information items 2 through 7. If no entry is made in this information item, then the basis for the values entered in the first eight information items shall be WGS84, the code for the World Geodetic Survey 1984 version - WGS 84 (G873). See look up codes for values. If no entry is made in this information item, then the basis for the values entered in the first eight information items shall be WGS84, the code for the World Geodetic Survey 1984 version - WGS 84 (G873). See look up codes for values.		
Field Min	2	Occur Min	0
Field Max	6	Occur Max	1
Char Types	AN	Special Chars	None
Format	n/a	Constraints	see Look Up Codes
Code List	GEOGRAPHIC COORDINATE DATUM CODE		
Source	ANSI/NIST ITL 1-2013 (Type-21)		
XML Level 1	biom_2:ContextImage/biom:ImageCaptureDetail or biom_2:ContextAudio/biom_2:BiometricCaptureDetail or biom_2:ContextVideo/biom_2:BiometricCaptureDetail	Cardinality	1...1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	biom:LocationTwoDimensionalGeographicCoordinate (0...1)/nc:GeographicCoordinateLatitude (0...1)	Cardinality	0...1
XML Level 4	biom:GeodeticDatumCoordinateSystemCode or biom:GeodeticDatumCoordinateSystemName	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

21.998_10

Geographic Sample Acquisition Location

Geographic Coordinate Universal Transverse Mercator Zone

Mnemonic	GCM	Conditionality	D
		Status	Active
Description	It is an alphanumeric value of 2 to 3 characters. This is a one or two digit UTM zone number followed by the 8 degree latitudinal band designator (which is a single letter).		
Field Min	1	Occur Min	0
Field Max	3	Occur Max	1
Char Types	AN	Special Chars	None
Format	n/a	Constraints	One or two digit UTM zone
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-21)		
XML Level 1	biom_2:ContextImage/biom:ImageCaptureDetail or biom_2:ContextAudio/biom_2:BiometricCaptureDetail or biom_2:ContextVideo/biom_2:BiometricCaptureDetail	Cardinality	1...1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	nc:LocationUTMCoordinate	Cardinality	0..1
XML Level 4	nc:UTMGridZoneID	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

21.998_11

Geographic Sample Acquisition Location

Geographic Coordinate Universal Transverse Mercator Easting

Mnemonic	GCE	Conditionality	D
		Status	Active
Description	The eleventh information item is the geographic coordinate universal transverse Mercator easting (GCE). It is an integer of 1 to 6 digits.		
Field Min	1	Occur Min	0
Field Max	6	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	0 <= GCE; integer
Code List			
Source	ANSI/NIST ITL 1-2013 (Type-21)		
XML Level 1	biom_2:ContextImage/biom:ImageCaptureDetail or biom_2:ContextAudio/biom_2:BiometricCaptureDetail or biom_2:ContextVideo/biom_2:BiometricCaptureDetail	Cardinality	1...1
XML Level 2	biom:CaptureLocation	Cardinality	0..1
XML Level 3	nc:LocationUTMCoordinate	Cardinality	0..1
XML Level 4	nc:UTMEastingValue	Cardinality	0..1
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

21.998_12

Geographic Sample Acquisition Location

Geographic Coordinate Universal Transverse Mercator Northing

Mnemonic	GCN		Conditionality	D			
			Status	Active			
Description	The twelfth information item is the geographic coordinate universal transverse Mercator northing (GCN). It is an integer of 1 to 8 digits.						
Field Min	1	Occur Min	0				
Field Max	8	Occur Max	1				
Char Types	N	Special Chars	None				
Format	n/a	Constraints	0 <= GCN; integer				
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-21)						
XML Level 1	biom_2:ContextImage/biom:ImageCaptureDetail or biom_2:ContextAudio/biom_2:BiometricCaptureDetail or biom_2:ContextVideo/biom_2:BiometricCaptureDetail		Cardinality	1...1			
XML Level 2	biom:CaptureLocation		Cardinality	0..1			
XML Level 3	nc:LocationUTMCoordinate		Cardinality	0..1			
XML Level 4	nc:UTMNorthingValue		Cardinality	0..1			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

21.998_13

Geographic Sample Acquisition Location

Geographic Reference Text

Mnemonic	GRT		Conditionality	O			
			Status	Active			
Description	It is a free form text describing a street address or other physical location (such as 'Corner of Washington and Madison, Geneva, NY').						
Field Min	1	Occur Min	0				
Field Max	150	Occur Max	1				
Char Types	U	Special Chars	Any				
Format	n/a	Constraints	None				
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-21)						
XML Level 1	biom_2:ContextImage/biom:ImageCaptureDetail or biom_2:ContextAudio/biom_2:BiometricCaptureDetail or biom_2:ContextVideo/biom_2:BiometricCaptureDetail		Cardinality	1...1			
XML Level 2	biom:CaptureLocation		Cardinality	0..1			
XML Level 3	biom:GeographicLocationText		Cardinality	0..1			
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

21.998_14

Geographic Sample Acquisition Location

Geographic Coordinate Other System Identifier

Mnemonic	OSI		Conditionality	O			
			Status	Active			
Description	A fourteenth optional information item geographic coordinate other system identifier (OSI) allows for other coordinate systems. This information items specifies the system identifier. It is up to 10 characters in length. Examples are: • MGRS (Military Grid Reference System), • USNG (United States National Grid), • GARS (Global Area Reference System), • GEOREF (World Geographic Reference), • LANDMARK landmark (e.g. hydant) and position relative to the landmark.						
Field Min	1	Occur Min	0				
Field Max	10	Occur Max	1				
Char Types	U	Special Chars	Any				
Format	n/a	Constraints	None				
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-21)						
XML Level 1	biom_2:ContextImage/biom:ImageCaptureDetail or biom_2:ContextAudio/biom_2:BiometricCaptureDetail or biom_2:ContextVideo/biom_2:BiometricCaptureDetail		Cardinality	1..1			
XML Level 2	biom:CaptureLocation		Cardinality	0..1			
XML Level 3	biom:LocationAlternateGeographicSystemValue		Cardinality	0..1			
XML Level 4	biom:GeographicLocationSystemName		Cardinality	1..1			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

21.998_15

Geographic Sample Acquisition Location

Geographic Coordinate Other System Value

Mnemonic	OCV		Conditionality	D			
			Status	Active			
Description	A fifteenth optional information item, is the geographic coordinate other system value (OCV). It shall only be present if OSI is present in the record. It can be up to 126 characters in length. If OSI is LANDMARK, OCV is free text and may be up to 126 characters. For details on the formatting of OCV for the other coordinate systems shown in OSI as examples, see http://earth-info.nga.mil/GandG/coordsys/grids/referencesys.html .						
Field Min	1	Occur Min	1				
Field Max	126	Occur Max	1				
Char Types	U	Special Chars	Any				
Format	n/a	Constraints	None				
Code List							
Source	ANSI/NIST ITL 1-2013 (Type-21)						
XML Level 1	biom_2:ContextImage/biom:ImageCaptureDetail or biom_2:ContextAudio/biom_2:BiometricCaptureDetail or biom_2:ContextVideo/biom_2:BiometricCaptureDetail		Cardinality	1..1			
XML Level 2	biom:CaptureLocation		Cardinality	0..1			
XML Level 3	biom:LocationAlternateGeographicSystemValue		Cardinality	0..1			
XML Level 4	biom:GeographicLocationText		Cardinality	0..1			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

21.999

Associated Context Data

Mnemonic	DATA		Conditionality	D
			Status	Active
Description	If this field is used, Field 21.994: External file reference / EFR shall not be set. However, one of the two fields shall be present in all instances of this record type. It is mandatory for a 2D still image. See Section 7.2 of ANSI/NIST ITL 1-2011 for details.			
Field Min	1	Occur Min	0	
Field Max	Unlimited	Occur Max	1	
Char Types	B	Special Chars	None	
Format	n/a	Constraints	None	
Code List				
Source	ANSI/NIST ITL 1-2013 (Type-21)			
XML Level 1	nc:BinaryBase64Object	Cardinality	0..1	
XML Level 2		Cardinality		
XML Level 3		Cardinality		
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0
			Yes	DoD EBTS 4.0
				Yes

98.001

Record Header

Mnemonic	LEN		Conditionality	M
			Status	Active
Description	The record header appears as the first field (xx.001) in each Record Type. It contains information particular to the encoding format chosen, in order to enable proper reading of the record. In Traditional encoding, this field contains the record length in bytes (including all information separators). In NIEM-conformant XML encoding, this field contains the RecordCategoryCode, which is the numeric representation of the Record Type.			
Field Min	T = 4; X = 1	Occur Min	1	
Field Max	T = 8; X = 2	Occur Max	1	
Char Types	N	Special Chars	None	
Format	n/a	Constraints	positive integer	
Code List				
Source	ANSI/NIST ITL 1-2011 (Type-98)			
XML Level 1	itl:PackageInformationAssuranceRecordType	Cardinality		
XML Level 2	nist-itl:RecordCategoryCode	Cardinality	1..1	
XML Level 3		Cardinality		
XML Level 4		Cardinality		
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0
			Yes	DoD EBTS 4.0
				Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

98.002

Information Designation Character

Mnemonic	IDC	Conditionality	M
		Status	Active
Description	Each of the records present in a transaction, with the exception of the Type-1 record, shall include a field (xx.002) containing the information designation character / IDC. The value of the IDC shall be a sequentially assigned positive integer starting from zero and incremented by one up to a maximum of 99. IDC references are stated in Type-1 Field 1.003 Transaction content (CNT) and shall be used to relate information items in the CNT field of the Type-1 record to the other records in the transaction. Two or more records may share a single IDC solely to identify and link together records that pertain to different representations of the same biometric trait.		
Field Min	1	Occur Min	1
Field Max	2	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	Constraints 0 <= IDC <= 99; integer
Code List			
Source	ANSI/NIST ITL 1-2011 (Type-98)		
XML Level 1	itl:PackageInformationAssuranceRecordType	Cardinality	
XML Level 2	nist-itl:ImageReferenceIdentification/nc:IdentificationID	Cardinality	1...1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

98.003

IA Data Format Owner

Mnemonic	DFO	Conditionality	M
		Status	Active
Description	This mandatory field shall contain a four digit hex value assigned by an authoritative body which denotes the vendor, standards body, working group, or industry consortium that has defined the format of the information assurance data. The IA data format owner and Field 98.005: IA data format type / DFT , when used in combination with one another uniquely identify the specific format of the IA content. This IA data format definition may be published (public) or unpublished (non-public).		
Field Min	4	Occur Min	1
Field Max	4	Occur Max	1
Char Types	H	Special Chars	None
Format	n/a	Constraints	None
Code List			
Source	ANSI/NIST ITL 1-2011 (Type-98)		
XML Level 1	itl:PackageInformationAssuranceRecordType	Cardinality	
XML Level 2	(ITL)biom:AssuranceFormatOwnerIdentification/nc:IdentificationID	Cardinality	1..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

98.004

Source Agency

Mnemonic	SRC		Conditionality	M			
			Status	Active			
Description	This is the identifier of the agency that actually created the record and supplied the information contained in it.						
Field Min	1	Occur Min	1				
Field Max	Unlimited	Occur Max	1				
Char Types	U	Special Chars	Any				
Format	n/a	Constraints	None				
Code List							
Source	ANSI/NIST ITL 1-2011 (Type-98)						
XML Level 1	itl:PackageInformationAssuranceRecordType		Cardinality				
XML Level 2	(ITL)biom:AssuranceOrganization		Cardinality	1..1			
XML Level 3	nc:OrganizationIdentification/nc:IdentificationID		Cardinality	1..1			
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

98.005

IA Data Format Type

Mnemonic	DFT		Conditionality	M			
			Status	Active			
Description	This mandatory field shall be used to identify the value assigned by the format owner (DFO) to represent the specific IA data format as specified by the format owner. This may be a nonstandard, unpublished data format or a data format that has been standardized by an industry group, consortium, or standards body.						
Field Min	1	Occur Min	1				
Field Max	20	Occur Max	1				
Char Types	U	Special Chars	None				
Format	n/a	Constraints	None				
Code List							
Source	ANSI/NIST ITL 1-2011 (Type-98)						
XML Level 1	itl:PackageInformationAssuranceRecordType		Cardinality				
XML Level 2	(ITL)biom:AssuranceFormatIdentification/nc:IdentificationID		Cardinality	1..1			
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

98.006

IA Data Creation Date

Mnemonic	DCD			Conditionality	M
				Status	Active
Description	This mandatory field shall contain the date and time that IA data was created. The date and time shall appear as GMT format.				
Field Min	Dependent on Encoding		Occur Min	1	
Field Max	Dependent on Encoding		Occur Max	1	
Char Types	N		Special Chars	None	
Format	n/a		Constraints	Dependent upon encoding, nc:DateTime	
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-98)				
XML Level 1	itl:PackageInformationAssuranceRecordType			Cardinality	
XML Level 2	(ITL)biom:AssuranceDateTime/nc:DateTime			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

98.9

Audit Log

Mnemonic	ALF			Conditionality	O
				Status	Active
Description	One complete audit statement (subfield of ALF) shall be completed for each modified datum. If this field appears, then Field 98.901 Audit revision number / ARN shall also be in the record.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-98)				
XML Level 1	itl:PackageInformationAssuranceRecordType			Cardinality	
XML Level 2	(ITL)biom:AssuranceLogEntry			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

98.900_0

Audit Log

Subfields: Repeating sets of information items

Mnemonic	ALF_0			Conditionality	M↑
				Status	Active
Description	This optional field contains a series of repeating subfields. One complete audit statement (subfield of ALF) shall be completed for each modified datum. If this field appears, then Field 98.901 Audit revision number / ARN shall also be in the record.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	*		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-98)				
XML Level 1	itl:PackageInformationAssuranceRecordType			Cardinality	
XML Level 2	(ITL)biom:AssuranceLogEntry			Cardinality	0..*
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

98.900_1

Audit Log

Event

Mnemonic	EVT			Conditionality	M↑
				Status	Yes
Description	It is mandatory and shall contain textual information describing the event that occurred to the ANSI/NIST-ITL record field, and shall be chosen from the following controlled vocabulary: Added, Modified, Deleted, Corrupted				
Field Min	5	Occur Min	1		
Field Max	9	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	EVT = Added, Modified, Deleted or Corrupted		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-98)				
XML Level 1	itl:PackageInformationAssuranceRecordType			Cardinality	
XML Level 2	(ITL)biom:AssuranceLogEntry			Cardinality	0..*
XML Level 3	(ITL)biom:AssuranceLogEventCode			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

98.900_2

Audit Log

Event Reason

Mnemonic	EVR	Conditionality	O↑
		Status	Active
Description	It states the rationale behind the Event that occurred. This information item is optional and should be populated with alphanumeric text with special characters up to 200 characters.		
Field Min	1	Occur Min	0
Field Max	200	Occur Max	1
Char Types	U	Special Chars	integer
Format	n/a	Constraints	n/a
Code List			
Source	ANSI/NIST ITL 1-2011 (Type-98)		
XML Level 1	itl:PackageInformationAssuranceRecordType	Cardinality	
XML Level 2	(ITL)biom:AssuranceLogEntry	Cardinality	0..*
XML Level 3	(ITL)biom:AssuranceLogEventReasonText	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

98.900_3

Audit Log

Information Identifier

Mnemonic	IID	Conditionality	M↑
		Status	Active
Description	Information identifier / IID is the third information item. It is mandatory and identifies the field/subfield/information item that has been affected by the Event. It is defined as the concatenation of the IDC, a comma, the Field Number in the standard, a comma, the repeat count of the subfield (default = NA), a comma, and the information item mnemonic (if it exists). If a repeating subfield or information item does not exist, enter a "NA". For the case when a repeated subfield is removed, the entry for the repeat field number is the original repeat set count, preceded by a negative; the information item mnemonic is entered as "NA". When an information item is removed, the mnemonic is preceded by a negative. When an optional field is removed, the field number is preceded by a minus. Even though subfields and information items may have been in the field, the field number is followed by "NA,NA" so that the subfields and information items do not have to be individually listed.		
Field Min	15	Occur Min	1
Field Max	30	Occur Max	1
Char Types	H	Special Chars	None
Format	n/a	Constraints	Field number exists, Repeat count valid for the field number, Mnemonic exists
Code List			
Source	ANSI/NIST ITL 1-2011 (Type-98)		
XML Level 1	itl:PackageInformationAssuranceRecordType	Cardinality	
XML Level 2	(ITL)biom:AssuranceLogEntry	Cardinality	0..*
XML Level 3	(ITL)biom:AssuranceLogEventLocationText	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

98.900_4

Audit Log

Agent

Mnemonic	AGT			Conditionality	M↑
				Status	Active
Description	It is mandatory and shall contain information describing the entity (Agent) responsible for the EVT that affected the object identified by the IID. It is an alphanumeric entry of up to 200 characters with special characters allowed.				
Field Min	1	Occur Min	1		
Field Max	200	Occur Max	1		
Char Types	U	Special Chars	None		
Format	n/a	Constraints	None		
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-98)				
XML Level 1	itl:PackageInformationAssuranceRecordType			Cardinality	
XML Level 2	(ITL)biom:AssuranceLogEntry			Cardinality	0..*
XML Level 3	(ITL)biom:AssuranceLogAgentText			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

98.900_5

Audit Log

Old Reference

Mnemonic	OLD			Conditionality	O↑
				Status	Active
Description	It is optional. When used, it shall contain the original value of the location in the transaction referenced in IID before it was affected by the event (EVT).				
Field Min	Dependent upon the format of the location referenced by 98.900_3 Information Identifier (IID)		Occur Min	0	
Field Max	Dependent upon the format of the location referenced by 98.900_3 Information Identifier (IID)		Occur Max	1	
Char Types	U		Special Chars	None	
Format	n/a		Constraints	Value of datum prior to the EVT in the location referenced by 98.900_3 Information Identifier (IID)	
Code List					
Source	ANSI/NIST ITL 1-2011 (Type-98)				
XML Level 1	itl:PackageInformationAssuranceRecordType			Cardinality	
XML Level 2	(ITL)biom:AssuranceLogEntry			Cardinality	0..*
XML Level 3	(ITL)biom:AssuranceLogEventOriginalValueText			Cardinality	0..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

98.901

Audit Log

Audit Revision Number

Mnemonic	ARN	Conditionality	D
		Status	Active
Description	This field is mandatory if Field 98.900: Audit log / ALF appears in the record. It contains a unique reference to the revision within the revision history. It is numeric, with up to 3 digits. Revision "x" may contain multiple events, each of which is recorded as a discrete modification (requiring a separate subfield in ARN). Thus, a different revision, with its corresponding log of modifications (recorded in ARN) requires a separate instance of Record Type-98.		
Field Min	1	Occur Min	0
Field Max	3	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	1 <= ARN <= 999; positive integer
Code List			
Source	ANSI/NIST ITL 1-2011 (Type-98)		
XML Level 1	itl:PackageInformationAssuranceRecordType	Cardinality	
XML Level 2	(ITL)biom:AssuranceAuditRevisionIdentification/nc:IdentificationID	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

98.993

Source Agency Name

Mnemonic	SAN	Conditionality	O
		Status	Active
Description	This is an optional field. It may contain up to 125 Unicode characters. It is the name of the agency referenced in Field xx.004: Source agency / SRC for record types 9-99.		
Field Min	1	Occur Min	0
Field Max	125	Occur Max	1
Char Types	U	Special Chars	Any
Format	n/a	Constraints	None
Code List			
Source	ANSI/NIST ITL 1-2011 (Type-98)		
XML Level 1	itl:PackageInformationAssuranceRecordType	Cardinality	
XML Level 2	(ITL)biom:AssuranceOrganization	Cardinality	1..1
XML Level 3	nc:OrganizationName	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

99.001

Record Header

Mnemonic	LEN		Conditionality	M			
			Status	Active			
Description	The record header appears as the first field (xx.001) in each Record Type. It contains information particular to the encoding format chosen, in order to enable proper reading of the record. In Traditional encoding, this field contains the record length in bytes (including all information separators). In NIEM-conformant XML encoding, this field contains the RecordCategoryCode, which is the numeric representation of the Record Type.						
Field Min	T = 4; X = 1		Occur Min	1			
Field Max	T = 8; X = 2		Occur Max	1			
Char Types	N		Special Chars	None			
Format	n/a		Constraints	positive integer			
Code List							
Source	ANSI/NIST ITL 1-2013						
XML Level 1	nist-itl:RecordCategoryCode		Cardinality	1...1			
XML Level 2			Cardinality				
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

99.002

Information Designation Character

Mnemonic	IDC		Conditionality	M			
			Status	Active			
Description	Each of the records present in a transaction, with the exception of the Type-1 record, shall include a field (xx.002) containing the information designation character / IDC. The value of the IDC shall be a sequentially assigned positive integer starting from zero and incremented by one up to a maximum of 99. IDC references are stated in Type-1 Field 1.003 Transaction content (CNT) and shall be used to relate information items in the CNT field of the Type-1 record to the other records in the transaction. Two or more records may share a single IDC solely to identify and link together records that pertain to different representations of the same biometric trait.						
Field Min	1		Occur Min	1			
Field Max	2		Occur Max	1			
Char Types	N		Special Chars	None			
Format	n/a		Constraints	0 <= IDC <= 99; integer			
Code List							
Source	"ANSI/NIST ITL 1-2013"						
XML Level 1	nist-itl:ImageReferenceIdentification/nc:IdentificationID		Cardinality	1...1			
XML Level 2			Cardinality				
XML Level 3			Cardinality				
XML Level 4			Cardinality				
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

99.004

Source Agency

Mnemonic	SRC			Conditionality	M
				Status	Active
Description	This is the identifier of the agency that actually created the record and supplied the information contained in it.				
Field Min	1	Occur Min	1		
Field Max	Unlimited	Occur Max	1		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints	None		
Code List					
Source	"ANSI/NIST ITL 1-2013"				
XML Level 1	biom_1:CBEFFImage	Cardinality	1..1		
XML Level 2	biom_1:ImageCaptureDetail	Cardinality	1..1		
XML Level 3	biom_1:CaptureOrganization	Cardinality	0..1		
XML Level 4	nc:OrganizationIdentification/nc:IdentificationID	Cardinality	1..1		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

99.005

Biometric Capture Date

Mnemonic	BCD			Conditionality	M
				Status	Active
Description	This ASCII field shall contain the date and time that the biometric sample was captured. The date and time shall appear as fifteen digits in the format YYYYMMDDhhmmssZ. The YYYY characters shall represent the year the image was captured; the MM characters shall be the tens and units values of the month; the DD characters shall be the tens and units values of the day in the month; the hh characters shall be the tens and units values of the hour of the day in 24-hour format; the mm characters shall be the tens and units values of the the DD characters shall be the tens and units values of the day in the month; the hh characters shall be the tens and units values of the hour of the day in 24-hour format; the mm characters shall be the tens and units values of the minute within the hour; the ss characters shall be the tens and units values of the second of the minute; and "Z" denotes Coordinated Universal Time, which is abbreviated UTC. For example, December 15, 2000 at 5 AM, 35 minutes and 30 seconds is expressed as 20001215053530Z. The complete date must be a legitimate date.				
Field Min	1	Occur Min	1		
Field Max	Unlimited	Occur Max	1		
Char Types	N	Special Chars	None		
Format	YYYYMMDDhhmmssZ	Constraints	Dependent upon encoding		
Code List					
Source	"ANSI/NIST ITL 1-2013"				
XML Level 1	biom_1:CBEFFImage	Cardinality	1..1		
XML Level 2	biom_1:ImageCaptureDetail	Cardinality	1..1		
XML Level 3	biom_2:CaptureDate/nc:Date	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

99.1

CBEFF Header Version

Mnemonic	HDV			Conditionality	M
				Status	Active
Description	This ASCII field shall be used to identify the version of CBEFF specification that this record conforms to. The format is two characters for major version number followed by two characters for minor version. The current version of CBEFF is INCITS 398-2005 represented by the string '0101' (major version '01' and minor version '01').				
Field Min	T = 4, X = 3		Occur Min	1	
Field Max	4		Occur Max	1	
Char Types	N		Special Chars	None	
Format	n/a		Constraints	HDV = 0101	
Code List					
Source	"ANSI/NIST ITL 1-2013"				
XML Level 1	biom_1:CBEFFImage			Cardinality	1..1
XML Level 2	biom_2:CBEFFVersionIdentification/nc:IdentificationID			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

99.101

Biometric Type

Mnemonic	BTY			Conditionality	M
				Status	Active
Description	This ASCII field shall be used to identify the type of biometric technology. This specification adopts the values presented in CBEFF with the addition of two leading zeros for future expansion.				
Field Min	T = 4, X = 3		Occur Min	1	
Field Max	8		Occur Max	1	
Char Types	H		Special Chars	None	
Format	n/a		Constraints	see Look Up Codes	
Code List	BIOMETRIC MODALITY CODES				
Source	"ANSI/NIST ITL 1-2013"				
XML Level 1	biom_1:CBEFFImage			Cardinality	1..1
XML Level 2	biom_1:CBEFFCategoryCode			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

99.102

Biometric Data Quality

Mnemonic	BDQ			Conditionality	0
				Status	Active
Description	This set shall specify a quality score data for the biometric data stored in the BDB in this record. The three information items identify a quality score and the algorithm used to create the quality score. This information is useful to enable the recipient of the quality score to differentiate between quality scores generated by different algorithms and adjust for any differences in processing or analysis as necessary.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	"ANSI/NIST ITL 1-2013"				
XML Level 1	biom_1:CBEFFImage	Cardinality	1..1		
XML Level 2	biom_2:ImageQuality	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

99.102_0

Biometric Data Quality

Mnemonic	BDQ_0			Conditionality	M↑
				Status	Active
Description	This set shall specify a quality score data for the biometric data stored in the BDB in this record. The three information items identify a quality score and the algorithm used to create the quality score. This information is useful to enable the recipient of the quality score to differentiate between quality scores generated by different algorithms and adjust for any differences in processing or analysis as necessary.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	9		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	"ANSI/NIST ITL 1-2013"				
XML Level 1	biom_1:CBEFFImage	Cardinality	1..1		
XML Level 2	biom_2:ImageQuality	Cardinality	0..9		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

99.102_1

Biometric Data Quality

Quality Value

Mnemonic	QVU			Conditionality	M↑
				Status	Active
Description	This information item shall contain the integer image quality score between 0 and 100 (inclusive) assigned to the image data by a quality algorithm. Higher values indicate better quality. An entry of "255" shall indicate a failed attempt to calculate a quality score. An entry of "254" shall indicate that no attempt to calculate a quality score was made.				
Field Min	1	Occur Min	1		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= QUV <= 100 or QVU = 254 or 255; integer		
Code List					
Source	"ANSI/NIST ITL 1-2013"				
XML Level 1	biom_1:CBEFFImage	Cardinality	1..1		
XML Level 2	biom_2:ImageQuality	Cardinality	0..9		
XML Level 3	biom_2:QualityValue	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

99.102_2

Biometric Data Quality

Algorithm Vendor Identification

Mnemonic	QAV			Conditionality	M↑
				Status	Active
Description	This information item shall specify the ID of the vendor of the quality algorithm used to calculate the quality score. This 4-digit hex value is assigned by IBIA and expressed as four ASCII characters. The IBIA shall maintain the Vendor Registry of CBEFF Biometric Organizations that will map the value in this field to a registered organization.				
Field Min	4	Occur Min	1		
Field Max	4	Occur Max	1		
Char Types	H	Special Chars	None		
Format	n/a	Constraints	0000 <= QAV <= FFFF		
Code List					
Source	"ANSI/NIST ITL 1-2013"				
XML Level 1	biom_1:CBEFFImage	Cardinality	1..1		
XML Level 2	biom_2:ImageQuality	Cardinality	0..9		
XML Level 3	biom_2:QualityAlgorithmVendorIdentification/nc:IdentificationID	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

99.102_3

Biometric Data Quality

Algorithm Product Identification

Mnemonic	QAP			Conditionality	M↑
				Status	Active
Description	This information item shall specify a numeric product code assigned by the vendor of the quality algorithm, which may be registered with the IBIA, but it is not required to be registered. It indicates which of the vendor's algorithms was used in the calculation of the quality score. This field contains the ASCII representation of the integer product code and should be within the range 1 to 65535.				
Field Min	1	Occur Min	1		
Field Max	5	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	1 <= QAP <= 65535; positive integer		
Code List					
Source	"ANSI/NIST ITL 1-2013"				
XML Level 1	biom_1:CBEFFImage	Cardinality	1..1		
XML Level 2	biom_2:ImageQuality	Cardinality	0..9		
XML Level 3	biom_2:QualityAlgorithmProductIdentification/nc:IdentificationID	Cardinality	1..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

99.103

BDB Format Owner

Mnemonic	BFO			Conditionality	M
				Status	Active
Description	This ASCII field shall be used to denote the vendor, standards body, working group, or industry consortium that has defined the format of the biometric data (in the BDB). In a CBEFF structure the BDB Format Owner and Format Type, when used in combination, uniquely identify the specific format of the BDB content. The format and content of the BDB is "owned" by the CBEFF Client (see Clause 6.1 of the CBEFF standard). This BDB format definition may be published (public) or unpublished (non-public). A CBEFF requirement is that format owners register with IBIA for an assigned identifier of the format owner. The number is guaranteed to be unique. Refer to the CBEFF standard, Clause 6, "CBEFF Patrons and Clients," for registration information. The four hex digits assigned by IBIA shall be represented by a string of four ASCII characters.				
Field Min	4	Occur Min	1		
Field Max	4	Occur Max	1		
Char Types	H	Special Chars	None		
Format	n/a	Constraints	None		
Code List					
Source	"ANSI/NIST ITL 1-2013"				
XML Level 1	biom_1:CBEFFImage	Cardinality	1..1		
XML Level 2	biom_2:CBEFFFormatOwnerIdentification/nc:IdentificationID	Cardinality	1..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes		

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

99.104

BDB Format Type

Mnemonic	BFT			Conditionality	M
				Status	Active
Description	This ASCII field shall be used to identify the value assigned by the format owner to represent the specific BDB Format as specified by the format owner. This may be a nonstandard, unpublished data format or a data format that has been standardized by an industry group, consortium, or standards body. The registration of the Format Type value is recommended but not required. Refer to the CBEFF standard, Clause 6, "CBEFF Patrons and Clients," for registration information. The four hex digits assigned by the format owner shall be represented by a string of four ASCII characters.				
Field Min	4	Occur Min	1		
Field Max	4	Occur Max	1		
Char Types	H	Special Chars	None		
Format	n/a	Constraints	None		
Code List					
Source	"ANSI/NIST ITL 1-2013"				
XML Level 1	biom_1:CBEFFImage	Cardinality	1..1		
XML Level 2	biom_2:CBEFFFormatCategoryIdentification/nc:IdentificationID	Cardinality	1..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

99.902

Annotated Information

Mnemonic	ANN			Conditionality	O
				Status	Active
Description	This is an optional field, listing the operations performed on the original source in order to prepare it for inclusion in a biometric record type.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	"ANSI/NIST ITL 1-2013"				
XML Level 1	biom_2:ProcessAnnotation	Cardinality	0..1		
XML Level 2		Cardinality			
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

99.902_0

Annotated Information

Repeating subsets

Mnemonic	ANN_0			Conditionality	M↑
				Status	Active
Description	This is an optional field, listing the operations performed on the original source in order to prepare it for inclusion in a biometric record type.				
Field Min	n/a		Occur Min	1	
Field Max	n/a		Occur Max	*	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	"ANSI/NIST ITL 1-2013"				
XML Level 1	biom_2:ProcessAnnotation			Cardinality	0..*
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

99.902_1

Annotated Information

Greenwich Mean Time

Mnemonic	GMT			Conditionality	M↑
				Status	Active
Description	This information item is the Greenwich Mean Time (GMT) when the processing occurred. The data is formatted as YYYYMMDDhhmmssZ, where the Z is indicates the zone description of 0 hours. This time is independent of the actual time zone where the time and date is recorded.				
Field Min	15		Occur Min	1	
Field Max	15		Occur Max	1	
Char Types	AN		Special Chars	None	
Format	YYYYMMDDHHMMSSZ - for Traditional Encoding		Constraints	Dependent upon encoding	
Code List					
Source	"ANSI/NIST ITL 1-2013"				
XML Level 1	biom_2:ProcessAnnotation			Cardinality	0..*
XML Level 2	biom_2:ProcessUTCDate/nc:DateTime			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

99.902_2

Annotated Information

Processing Algorithm Name / Version

Mnemonic	NAV			Conditionality	M↑
				Status	Active
Description	This information item shall contain text identifying the name and version of the processing algorithm, application, procedure, or workstation				
Field Min	1	Occur Min	1		
Field Max	Unlimited	Occur Max	1		
Char Types	U	Special Chars	n/a		
Format	n/a	Constraints	None		
Code List					
Source	"ANSI/NIST ITL 1-2013"				
XML Level 1	biom_2:ProcessAnnotation	Cardinality	0..*		
XML Level 2	biom_2:ProcessName	Cardinality	1..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

99.902_3

Annotated Information

Algorithm Owner

Mnemonic	OWN			Conditionality	M↑
				Status	Active
Description	This information item shall contain an unformatted text string of up to 64 characters with the contact information for the organization that owns the processing algorithm or latent workstation. Where there is no 'algorithm owner,' enter N/A.				
Field Min	1	Occur Min	1		
Field Max	64	Occur Max	1		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints	None		
Code List					
Source	"ANSI/NIST ITL 1-2013"				
XML Level 1	biom_2:ProcessAnnotation	Cardinality	0..*		
XML Level 2	biom_2:ProcessOwnerText	Cardinality	1..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

99.902_4

Annotated Information

Process Description

Mnemonic	PRO			Conditionality	M↑
				Status	Active
Description	This information item field shall contain text describing a process or procedure applied to the sample in this Type-9 record.				
Field Min	1	Occur Min	1		
Field Max	255	Occur Max	1		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints	None		
Code List					
Source	"ANSI/NIST ITL 1-2013"				
XML Level 1	biom_2:ProcessAnnotation	Cardinality	0..*		
XML Level 2	biom_2:ProcessDescriptionText	Cardinality	1..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

99.903

Device Unique Identifier

Mnemonic	DUI			Conditionality	0
				Status	Active
Description	The DUI shall contain a string uniquely identifying the device or source of the data. This field shall be one of the following: a Host PC MAC address (identified by the first character "M"), a Host PC processor ID (identified by the first character "P"). since it is available in the Make / Model / Serial Number field.				
Field Min	13	Occur Min	0		
Field Max	16	Occur Max	1		
Char Types	ANS	Special Chars	Any		
Format	n/a	Constraints	first character = M or P		
Code List	DEVICE UNIQUE IDENTIFIER CODES				
Source	"ANSI/NIST ITL 1-2013"				
XML Level 1	biom_1:CBEFFImage	Cardinality	1..1		
XML Level 2	biom_2:ImageCaptureDetail	Cardinality	1..1		
XML Level 3	biom_2:CaptureDeviceIdentification/nc:IdentificationID	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

99.904

Make/Model/Serial Number

Mnemonic	MMS	Conditionality	O
		Status	Active
Description	The MMS contains the make, model and serial number for the capture device. It shall consist of three information items. Each information item shall be 1 to 50 characters. Unknown information may be indicated with the value "0." Any or all information items may indicate that information is unknown with the value "0".		
Field Min	n/a	Occur Min	1
Field Max	n/a	Occur Max	1
Char Types	n/a	Special Chars	n/a
Format	n/a	Constraints	n/a
Code List			
Source	"ANSI/NIST ITL 1-2013"		
XML Level 1	biom_1:CBEFFImage	Cardinality	1..1
XML Level 2	biom_2:ImageCaptureDetail	Cardinality	1..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

99.904_1

Make/Model/Serial Number

Make

Mnemonic	MAK	Conditionality	M↑
		Status	Active
Description	The name of the manufacturer for the capture device.		
Field Min	1	Occur Min	0
Field Max	50	Occur Max	1
Char Types	U	Special Chars	Any
Format	n/a	Constraints	None
Code List			
Source	"ANSI/NIST ITL 1-2013"		
XML Level 1	biom_1:CBEFFImage	Cardinality	1..1
XML Level 2	biom_2:ImageCaptureDetail	Cardinality	1..1
XML Level 3	biom_2:CaptureDeviceMakeText	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-99: CBEFF Biometric Data

Page 1023 of 1037

99.904_2

Make/Model/Serial Number

Model

Mnemonic	MOD			Conditionality	M↑
				Status	Active
Description	The model number for the capture device.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints	None		
Code List					
Source	"ANSI/NIST ITL 1-2013"				
XML Level 1	biom_1:CBEFFImage	Cardinality	1..1		
XML Level 2	biom_2:ImageCaptureDetail	Cardinality	1..1		
XML Level 3	biom_2:CaptureDeviceModelText	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

99.904_3

Make/Model/Serial Number

Serial Number

Mnemonic	SER			Conditionality	M↑
				Status	Active
Description	The serial number for the capture device.				
Field Min	1	Occur Min	0		
Field Max	50	Occur Max	1		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints	None		
Code List					
Source	"ANSI/NIST ITL 1-2013"				
XML Level 1	biom_1:CBEFFImage	Cardinality	1..1		
XML Level 2	biom_2:ImageCaptureDetail	Cardinality	1..1		
XML Level 3	biom_2:CaptureDeviceSerialNumberText	Cardinality	0..1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-99: CBEFF Biometric Data

Page 1024 of 1037

99.993

Source Agency Name

Mnemonic	SAN			Conditionality	0
				Status	Active
Description	This is an optional field. It may contain up to 125 Unicode characters. It is the name of the agency referenced in Field xx.004: Source agency / SRC for record types 9-99.				
Field Min	1	Occur Min	0		
Field Max	125	Occur Max	1		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints	None		
Code List					
Source	"ANSI/NIST ITL 1-2013"				
XML Level 1	biom_1:CBEFFImage	Cardinality	1..1		
XML Level 2	biom_2:ImageCaptureDetail	Cardinality	1..1		
XML Level 3	biom_1:CaptureOrganization	Cardinality	0..1		
XML Level 4	nc:OrganizationName	Cardinality	0..1		
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

99.995

Associated Context

Mnemonic	ASC			Conditionality	0
				Status	Active
Description	This optional field refers to one or more Type 21 Records with the same ACN. Type 21 Records contain images that are NOT used to derive the biometric data in Field 13.999: Latent friction ridge image (DATA) but that may be relevant to the collection of that data, such as general scenes of the area where a latent print was found.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	"ANSI/NIST ITL 1-2013"				
XML Level 1	biom_2:AssociatedContext	Cardinality	0..1		
XML Level 2		Cardinality			
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-99: CBEFF Biometric Data

Page 1025 of 1037

99.995_0

Associated Context

Repeating subsets

Mnemonic	ASC_0			Conditionality	M↑
				Status	Active
Description	This optional field refers to one or more Type 21 Records with the same ACN. Type 21 Records contain images that are NOT used to derive the biometric data in Field 13.999: Latent friction ridge image (DATA) but that may be relevant to the collection of that data, such as general scenes of the area where a latent print was found.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	255		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	"ANSI/NIST ITL 1-2013"				
XML Level 1	biom_2:AssociatedContext			Cardinality	0..255
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

99.995_1

Associated Context Number

Mnemonic	ACN			Conditionality	M↑
				Status	Active
Description	The first information item for the Associated Context field for a particular Record Type-21. This is mandatory for each Field xx.995, when the field is used. It contains an index to a particular instance of a Type-21 record in the transaction. This same index value appears in the appropriate instance of Record Type-21 as Field 21.021: Associated context number (CAN). The value of the CAN shall be a sequentially assigned a positive integer starting from one and incremented by one, not to exceed 255.				
Field Min	n/a	Occur Min	1		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	"ANSI/NIST ITL 1-2013"				
XML Level 1	biom_2:AssociatedContext			Cardinality	0..255
XML Level 2	biom_2:ContextIdentification/nc:IdentificationID			Cardinality	1..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

99.995_2

Associated Segment Position

Mnemonic	ASP			Conditionality	M↑
				Status	Active
Description	The first information item is the associated segment position (ASP). This provides a unique index to a segmentation.				
Field Min	1	Occur Min	0		
Field Max	3	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	1 <= ACN <= 255; positive integer		
Code List					
Source	"ANSI/NIST ITL 1-2013"				
XML Level 1	biom_2:AssociatedContext	Cardinality	0..255		
XML Level 2	biom_2:ImageSegmentIdentification/nc:IdentificationID	Cardinality	0..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

99.996

Hash

Mnemonic	HAS			Conditionality	O↑
				Status	Active
Description	Optional field xx.996, is designed for use in Record types 10 and above with a Field xx.999 storing the biometric data. It is comprised of 64 characters representing hexadecimal values. Thus, each character may be a digit from "0" to "9" or a letter "A" through "F". See the latest version of the Federal Information Processing Standard 180, Secure Hash Standard for information on computing SHA-256 hashes. At the time of this standard's publication, FIPS 180-37 had been published. It is also possible to use Field xx.996 to contain the hash for data stored externally, which is referenced in Field 20.994: External file reference (EFR) and/or Field 21.994: External file reference (EFR). The ability to store files externally is new to this version of the standard, and is only implemented for the two new record types referred to here. Use of the hash enables the receiver of the data to perform quick searches of large databases to determine if the data already exist in the database. It is not intended as an information assurance check. That is handled by Record Type-98: Information assurance record.				
Field Min	1	Occur Min	0		
Field Max	2	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	1 <= ASP <= 99; positive integer		
Code List					
Source	"ANSI/NIST ITL 1-2013"				
XML Level 1	biom:ImageHashValue	Cardinality	0..1		
XML Level 2		Cardinality			
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

99.997

Source Representation

Mnemonic	SOR			Conditionality	0
				Status	Active
Description	This optional field refers to a representation in Record Type-20 with the same SRN from which the data in Field 13.999: Latent friction ridge image (DATA) was derived.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	1		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	"ANSI/NIST ITL 1-2013"				
XML Level 1	biom_2:SourceRepresentation			Cardinality	0..1
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

99.997_0

Source Representation

Repeating subsets

Mnemonic	SOR_0			Conditionality	M↑
				Status	Active
Description	This optional field refers to a representation in Record Type-20 with the same SRN from which the data in Field 13.999: Latent friction ridge image (DATA) was derived.				
Field Min	n/a	Occur Min	0		
Field Max	n/a	Occur Max	255		
Char Types	n/a	Special Chars	n/a		
Format	n/a	Constraints	n/a		
Code List					
Source	"ANSI/NIST ITL 1-2013"				
XML Level 1	biom_2:SourceRepresentation			Cardinality	0..255
XML Level 2				Cardinality	
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	No
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

99.997_1

Source Representation

Source Representation Number

Mnemonic	SRN	Conditionality	M↑
		Status	Active
Description	This is the first information item and is mandatory for each Field xx.997. It contains an index to a particular instance of a Type-20 record in the transaction. This same index value appears in the appropriate instance of Record Type-20 as Field 20.021: Source representation number (SRN). The value of the SRN shall be a sequentially assigned a positive integer starting from one and incremented by one, not to exceed 255.		
Field Min	1	Occur Min	1
Field Max	3	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	1 <= SRN <= 255; positive integer
Code List			
Source	"ANSI/NIST ITL 1-2013"		
XML Level 1	biom_2:SourceRepresentation	Cardinality	0..255
XML Level 2	biom_2:SourceIdentification/nc:identificationID	Cardinality	1..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

99.997_2

Source Representation

Reference Segment Position

Mnemonic	RSP	Conditionality	O↑
		Status	Active
Description	The first information item is the reference segment position (RSP). This provides a unique index to a segmentation.		
Field Min	1	Occur Min	0
Field Max	2	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	1 <= RSP <= 99; positive integer
Code List			
Source	"ANSI/NIST ITL 1-2013"		
XML Level 1	biom_2:SourceRepresentation	Cardinality	0..255
XML Level 2	biom_2:ImageSegmentIdentification/nc:IdentificationID	Cardinality	0..1
XML Level 3		Cardinality	
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

99.998

Geographic Sample Acquisition Location

Mnemonic	GEO			Conditionality	O
				Status	Active
Description	This optional field contains the location where the iris sample/original source/context information was acquired – not where it is stored.				
Field Min	n/a		Occur Min	0	
Field Max	n/a		Occur Max	1	
Char Types	n/a		Special Chars	n/a	
Format	n/a		Constraints	n/a	
Code List					
Source	"ANSI/NIST ITL 1-2013"				
XML Level 1	biom_1:CBEFFImage(1...1)/biom_2:ImageCaptureDetail(1...1)			Cardinality	1...1
XML Level 2	biom_2:CaptureLocation			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

99.998_01

Geographic Sample Acquisition Location

Universal Time Entry

Mnemonic	UTE			Conditionality	O↑
				Status	Active
Description	The coordinated universal time (UTC) where the biometric sample was collected. This time is independent of the actual time zone where the time and date is recorded. The date is YYYYMMDDhhmmssZ, where the Z indicates the zone description of 0 hours. If sample collection time is unknown, set it to "00000000000000Z."				
Field Min	15		Occur Min	0	
Field Max	15		Occur Max	1	
Char Types	AN		Special Chars	None	
Format	YYYYMMDDHHMMSSZ - for Traditional Encoding		Constraints	Dependent upon encoding	
Code List					
Source	"ANSI/NIST ITL 1-2013"				
XML Level 1	biom_1:CBEFFImage(1...1)/biom_2:ImageCaptureDetail(1...1)			Cardinality	1...1
XML Level 2	biom_2:CaptureUTCDateTime/nc:DateTime			Cardinality	0..1
XML Level 3				Cardinality	
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

99.998_02

Geographic Sample Acquisition Location

Latitude Degree Value

Mnemonic	LTD	Conditionality	D
		Status	Active
Description	The second information item is latitude degree value (LTD). This is a value that specifies the degree of latitude. The value shall be between -90 (inclusive) and +90 (inclusive). The degrees may be expressed as an integer (without a decimal) or a real number including decimals. If decimals are present, then minutes and seconds shall be empty. Examples: Buenos Aires, Argentina: -34 (with minutes LTM = 36) NIST, Gaithersburg, Maryland: 39.137627 (no LTM or LTS)		
Field Min	1	Occur Min	1
Field Max	9	Occur Max	1
Char Types	NS	Special Chars	Decimal,Minus Sign,Plus Sign
Format	n/a	Constraints	-90 <= LTD <= 90
Code List			
Source	"ANSI/NIST ITL 1-2013"		
XML Level 1	biom_1:CBEFFImage(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1
XML Level 2	biom_1:CaptureLocation(0...1)/biom_1:LocationTwoDimensionalGeographicCoordinate(0...1)/nc:GeographicCoordinateLatitude (0...1)	Cardinality	
XML Level 3	nc:LatitudeDegreeValue	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

99.998_03

Geographic Sample Acquisition Location

Latitude Minute Value

Mnemonic	LTM	Conditionality	D
		Status	Active
Description	This information item is latitude minute value (LTM). This is a value that specifies a minute of a degree. The value shall be between 0 (inclusive) to 60 (exclusive). The minute value may be expressed as an integer (without a decimal) or as a real number including decimals. If decimals are present then seconds shall be empty. Thus, the allowed special character is a period. The minute value can be empty, even if the degree value is an integer. LTM and LGM are co-conditional, so they shall both be present if either is present.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	NS	Special Chars	Decimal
Format	n/a	Constraints	0 <= LTM < 60
Code List			
Source	"ANSI/NIST ITL 1-2013"		
XML Level 1	biom_1:CBEFFImage(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1
XML Level 2	biom_1:CaptureLocation(0...1)/biom_1:LocationTwoDimensionalGeographicCoordinate(0...1)/nc:GeographicCoordinateLatitude (0...1)	Cardinality	0..1
XML Level 3	nc:LatitudeMinuteValue	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-99: CBEFF Biometric Data

Page 1031 of 1037

99.998_04

Geographic Sample Acquisition Location

Latitude Second Value

Mnemonic	LTS	Conditionality	D
		Status	Active
Description	The fourth information item is the latitude second value (LTS). This is a value that specifies a second of a minute. The integer shall be 0 (inclusive) to 60 (exclusive). The second value is empty, even if the minute value is an integer.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	0 <= LTS < 60
Code List			
Source	"ANSI/NIST ITL 1-2013"		
XML Level 1	biom_1:CBEFFImage(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1
XML Level 2	biom_1:CaptureLocation(0...1)/biom_1:LocationTwoDimensionalGeographicCoordinate(0...1)/nc:GeographicCoordinateLatitude (0...1)	Cardinality	0..1
XML Level 3	nc:LatitudeSecondValue	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

99.998_05

Geographic Sample Acquisition Location

Longitude Degree Value

Mnemonic	LGD	Conditionality	D
		Status	Active
Description	The fifth information item is the longitude degree value (LGD). It is a value that specifies the degree of a longitude. The value shall be between -180 (inclusive) and +180 (inclusive). If LTD is present, then LGD shall be present. The degrees may be expressed as whole numbers (without a decimal) or real numbers including decimals. If decimals are present, then minutes and seconds are empty. Examples: Buenos Aires, Argentina: -58 (with minutes LGM = 22), NIST, Gaithersburg, Maryland: -77.216032 (no LGM or LGS)		
Field Min	1	Occur Min	1
Field Max	10	Occur Max	1
Char Types	NS	Special Chars	Decimal, Minus Sign, Plus Sign
Format	n/a	Constraints	-180 <= LGD <= 180
Code List			
Source	"ANSI/NIST ITL 1-2013"		
XML Level 1	biom_1:CBEFFImage(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1
XML Level 2	biom_1:CaptureLocation(0...1)/biom_1:LocationTwoDimensionalGeographicCoordinate(0...1)/nc:GeographicCoordinateLongitude (0...1)	Cardinality	0..1
XML Level 3	nc:LongitudeDegreeValue	Cardinality	1..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-99: CBEFF Biometric Data

Page 1032 of 1037

99.998_06

Geographic Sample Acquisition Location

Longitude Minute Value

Mnemonic	LGM	Conditionality	D
		Status	Active
Description	The sixth information item is the longitude minute value (LGM). It is a value that specifies a minute of a degree. The value shall be from 0 (inclusive) to 60 (exclusive). The minute value may be expressed as an integer (without a decimal) or as a real number including decimals. If decimals are present then seconds shall not appear. The minute value is empty, even if the degree value is an integer. If LTM is present, then LGM shall be present.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	NS	Special Chars	Decimal
Format	n/a	Constraints	0 <= LGM < 60
Code List			
Source	"ANSI/NIST ITL 1-2013"		
XML Level 1	biom_1:CBEFFImage(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1
XML Level 2	biom_1:CaptureLocation(0...1)/biom_1:LocationTwoDimensionalGeographicCoordinate(0...1)/nc:GeographicCoordinateLongitude (0...1)	Cardinality	0..1
XML Level 3	nc:LongitudeMinuteValue	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

99.998_07

Geographic Sample Acquisition Location

Longitude Second Value

Mnemonic	LGS	Conditionality	D
		Status	Active
Description	The seventh information item is the longitude second value (LGS). This is a value that specifies a second of a minute. The integer shall be 0 (inclusive) to 60 (exclusive). The second value is empty, even if the minute value is an integer. If LTS is present, then LGS shall be present.		
Field Min	1	Occur Min	0
Field Max	8	Occur Max	1
Char Types	N	Special Chars	None
Format	n/a	Constraints	0 <= LGS < 60
Code List			
Source	"ANSI/NIST ITL 1-2013"		
XML Level 1	biom_1:CBEFFImage(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1
XML Level 2	biom_1:CaptureLocation(0...1)/biom_1:LocationTwoDimensionalGeographicCoordinate(0...1)/nc:GeographicCoordinateLongitude (0...1)	Cardinality	0..1
XML Level 3	nc:LongitudeSecondValue	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
		DoD EBTS 3.0	Yes
		DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-99: CBEFF Biometric Data

Page 1033 of 1037

99.998_08

Geographic Sample Acquisition Location

Elevation

Mnemonic	ELE	Conditionality	O
		Status	Active
Description	The eighth information item is elevation (ELE). It is expressed in meters. It is a numeric value. It is between -422 meters (Dead Sea) and 8848 meters (Mount Everest). Allowed special characters are the negative sign and the period.		
Field Min	3	Occur Min	0
Field Max	8	Occur Max	1
Char Types	NS	Special Chars	Minus Sign,Period
Format	n/a	Constraints	-422.000 < ELE < 8848.000; real number
Code List			
Source	"ANSI/NIST ITL 1-2013"		
XML Level 1	biom_1:CBEFFImage(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1
XML Level 2	biom_1:CaptureLocation(0...1)/nc:LocationGeographicElevation (0...1)	Cardinality	0..1
XML Level 3	nc:MeasurePointValue	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

99.998_09

Geographic Sample Acquisition Location

Geodetic Datum Code

Mnemonic	GDC	Conditionality	O
		Status	Active
Description	The ninth information item is the geodetic datum code (GDC11). It is an alphanumeric value of 3 to 6 characters in length. This information item is used to indicate which coordinate system was used to represent the values in information items 2 through 7. If no entry is made in this information item, then the basis for the values entered in the first eight information items shall be WGS84, the code for the World Geodetic Survey 1984 version - WGS 84 (G873). See look up codes for values. If no entry is made in this information item, then the basis for the values entered in the first eight information items shall be WGS84, the code for the World Geodetic Survey 1984 version - WGS 84 (G873). See look up codes for values.		
Field Min	2	Occur Min	0
Field Max	6	Occur Max	1
Char Types	AN	Special Chars	None
Format	n/a	Constraints	see Look Up Codes
Code List	GEOGRAPHIC COORDINATE DATUM CODES		
Source	"ANSI/NIST ITL 1-2013"		
XML Level 1	biom_1:CBEFFImage(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1
XML Level 2	biom_1:CaptureLocation(0...1)/biom_1:LocationTwoDimensionalGeographicCoordinate(0...1)	Cardinality	0..1
XML Level 3	biom_2:GeodeticDatumCoordinateSystemCode or biom_2:GeodeticDatumCoordinateSystemName	Cardinality	0..1
XML Level 4		Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No
DoD EBTS 3.0	Yes	DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

99.998_10

Geographic Sample Acquisition Location

Geographic Coordinate Universal Transverse Mercator Zone

Mnemonic	GCM			Conditionality	D
				Status	Active
Description	It is an alphanumeric value of 2 to 3 characters. This is a one or two digit UTM zone number followed by the 8 degree latitudinal band designator (which is a single letter).				
Field Min	1	Occur Min	0		
Field Max	3	Occur Max	1		
Char Types	AN	Special Chars	None		
Format	n/a	Constraints	One or two digit UTM zone		
Code List					
Source	"ANSI/NIST ITL 1-2013"				
XML Level 1	biom_1:CBEFFImage(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1		
XML Level 2	biom_1:CaptureLocation(0...1)/nc:LocationUTMCoordinate(0...1)	Cardinality	0..1		
XML Level 3	nc:UTMGridZoneID	Cardinality	0...1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

99.998_11

Geographic Sample Acquisition Location

Geographic Coordinate Universal Transverse Mercator Easting

Mnemonic	GCE			Conditionality	D
				Status	Active
Description	The eleventh information item is the geographic coordinate universal transverse Mercator easting (GCE). It is an integer of 1 to 6 digits.				
Field Min	1	Occur Min	0		
Field Max	6	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= GCE; integer		
Code List					
Source	"ANSI/NIST ITL 1-2013"				
XML Level 1	biom_1:CBEFFImage(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1		
XML Level 2	biom_1:CaptureLocation(0...1)/nc:LocationUTMCoordinate(0...1)	Cardinality	0..1		
XML Level 3	nc:UTMEastingValue	Cardinality	0...1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-99: CBEFF Biometric Data

Page 1035 of 1037

99.998_12

Geographic Sample Acquisition Location

Geographic Coordinate Universal Transverse Mercator Northing

Mnemonic	GCN			Conditionality	D
				Status	Active
Description	The twelfth information item is the geographic coordinate universal transverse Mercator northing (GCN). It is an integer of 1 to 8 digits.				
Field Min	1	Occur Min	0		
Field Max	8	Occur Max	1		
Char Types	N	Special Chars	None		
Format	n/a	Constraints	0 <= GCN; integer		
Code List					
Source	"ANSI/NIST ITL 1-2013"				
XML Level 1	biom_1:CBEFFImage(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1		
XML Level 2	biom_1:CaptureLocation(0...1)/nc:LocationUTMCoordinate(0...1)	Cardinality	0..1		
XML Level 3	nc:UTMNorthingValue	Cardinality	0...1		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

99.998_13

Geographic Sample Acquisition Location

Geographic Reference Text

Mnemonic	GRT			Conditionality	O
				Status	Active
Description	It is a free form text describing a street address or other physical location (such as 'Corner of Washington and Madison, Geneva, NY').				
Field Min	1	Occur Min	0		
Field Max	150	Occur Max	*		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints	None		
Code List					
Source	"ANSI/NIST ITL 1-2013"				
XML Level 1	biom_1:CBEFFImage(1...1)/biom_2:ImageCaptureDetail(1...1)	Cardinality	1...1		
XML Level 2	biom_1:CaptureLocation (0...1)/biom:LocationAlternateGeographicSystemValue (1...1)	Cardinality	0..1		
XML Level 3	nc:LocationDescriptionText	Cardinality	0..*		
XML Level 4		Cardinality			
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

Type-99: CBEFF Biometric Data

Page 1036 of 1037

99.998_14

Geographic Sample Acquisition Location

Geographic Coordinate Other System Identifier

Mnemonic	OSI			Conditionality	O
				Status	Active
Description	A fourteenth optional information item geographic coordinate other system identifier (OSI) allows for other coordinate systems. This information items specifies the system identifier. It is up to 10 characters in length. Examples are: • MGRS (Military Grid Reference System), • USNG (United States National Grid), • GARS (Global Area Reference System), • GEOREF (World Geographic Reference), • LANDMARK landmark (e.g. hydant) and position relative to the landmark.				
Field Min	1	Occur Min	1		
Field Max	10	Occur Max	1		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints	None		
Code List					
Source	"ANSI/NIST ITL 1-2013"				
XML Level 1	biom_1:CBEFFImage(1...1)/biom_2:ImageCaptureDetail(1...1)			Cardinality	1...1
XML Level 2	biom_1:CaptureLocation (0...1)/biom:LocationAlternateGeographicSystemValue (1...1)			Cardinality	0..1
XML Level 3	biom_2:GeographicLocationSystemName			Cardinality	1..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

99.998_15

Geographic Sample Acquisition Location

Geographic Coordinate Other System Value

Mnemonic	OCV			Conditionality	D
				Status	Active
Description	A fifteenth optional information item, is the geographic coordinate other system value (OCV). It shall only be present if OSI is present in the record. It can be up to 126 characters in length. If OSI is LANDMARK, OCV is free text and may be up to 126 characters. For details on the formatting of OCV for the other coordinate systems shown in OSI as examples, see http://earth-info.nga.mil/GandG/coordsys/grids/referencesys.html .				
Field Min	1	Occur Min	0		
Field Max	126	Occur Max	1		
Char Types	U	Special Chars	Any		
Format	n/a	Constraints	None		
Code List					
Source	"ANSI/NIST ITL 1-2013"				
XML Level 1	biom_1:CBEFFImage(1...1)/biom_2:ImageCaptureDetail(1...1)			Cardinality	1...1
XML Level 2	biom_1:CaptureLocation (0...1)/biom:LocationAlternateGeographicSystemValue (1...1)			Cardinality	0..1
XML Level 3	biom_2:GeographicLocationText			Cardinality	0..1
XML Level 4				Cardinality	
DoD EBTS 1.2	No	DoD EBTS 2.0	No	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes

Integrated Data Dictionary (IDD) for DoD EBTS v4.0

99.999

Biometric Data Block

Mnemonic	DATA			Conditionality	D
				Status	Active
Description	This mandatory field contains the fingerprint image. See Section 7.2 of ANSI/NIST ITL 1-2011 for details.				
Field Min	1	Occur Min	1		
Field Max	Unlimited	Occur Max	1		
Char Types	B	Special Chars	None		
Format	n/a	Constraints	None		
Code List					
Source	"ANSI/NIST ITL 1-2013"				
XML Level 1	biom_1:CBEFFImage	Cardinality	1..1		
XML Level 2	nc:BinaryBase64Object	Cardinality	1..1		
XML Level 3		Cardinality			
XML Level 4		Cardinality			
DoD EBTS 1.2	Yes	DoD EBTS 2.0	Yes	DoD EBTS 3.0	Yes
				DoD EBTS 4.0	Yes