DETAILS OF RADIO FACILITIES (Continued)		
	Item	Actual Provision
6.	Ship's radar transponder:	
7.	Radiotelephone distress frequency watch receiver on 2182 kHz (until 1 Feb. 1999)	
	Device for generating the radiotelephone alarm signal on 2182 kHz (until 1 Feb. 1999)	
8.	Device for generating the radiotelephone diams signal on 2.02 km2 (diffir 1.768, 1995)	
	Methods used to insure availability of radio facilities (Reg. IV/15.6 & 15.7)	
1.	Duplication of equipment:	
2.	Shore-based maintenance:	
3.	At-sea maintenance capability:	
	Ships constructed before 1 February 1995 which do not comply with all the applicable requirements of Chapter IV of the Convention as amended in 1988 (until 1 February 1999)	
	Requirements of regulations	
1.	Hours of listening by operator:	
2.	Number of operators:	
3.	Whether auto alarm fitted:	
4.	Whether main installation fitted:	
5.	Whether reserve installation fitted:	
6.	Whether main and reserve transmitters	
0.	electrically separated or combined:	
1.	Ships constructed before 1 February 1992 which do not fully comply with the applicable requirements of Chapter III of the Convention as amended in 1988 (until 1 February 1995) Radiotelegraph installation for lifeboat:	
2.	Portable radio apparatus for survival craft:	
3.	Survival craft EPIRB (121.5 MHz and 243.0 MHz):	
4.	Two-way radiotelephone apparatus:	
•	1110 110, 100 100 100 100 100 100 100 10	
	de la companya de la	
11	nspection made by or under the direction of:	
СОМ	PANY NAME	
INSP	ECTOR SIGNATURE	
-		
190	Face 508	FCC Form 806 - Page 2